

Design for class “DeliveryInfoScreen”

Inheritance of class “CustomerScreen”

DeliveryInfoScreen
- placeOrderController : PlaceOrderController - nameInput : TextField - phoneInput : TextField - addressInput : TextField - provinceSelect : ComboBox
+ setBController(bController : BaseController) : void + navigateTo(screen : BaseScreenHandler) : void + setController(controller : PlaceOrderController) : void + handleSubmitClick() : void + getDeliveryInfo() : DeliveryInfo + showInvalidInfoError(message : String) : void

Table 1. Attribute Design

#	Name	Data type	Default value	Description
1	placeOrderController	PlaceOrderController	null	Controller that processes delivery information.
2	nameInput	TextField	""	Customer’s full name field.
3	phoneInput	TextField	""	Customer’s phone number field.
4	addressInput	TextField	""	Customer’s address field.
5	provinceSelect	ComboBox	null	Dropdown selection for province/city.

Table 2. Operation Design

#	Name	Return type	Description
1	setController(controller)	void	Assign the controller for delivery processing.
2	handleSubmitClick()	void	Triggered when the user submits delivery info.

3	getDeliveryInfo()	DeliveryInfo	Collect delivery info into an object.
4	showInvalidInfoError(message)	void	Display validation error(s) for user input.

Method Design:

1. setController

- Parameter:
 - controller: PlaceOrderController

- Exception:

- Method:
 - Assigns the controller.

2. handleSubmitClick

- Parameter:

- Exception:

- Method:
 - Read all UI fields.
 - Construct a temporary delivery info map.
 - Call placeOrderController.submitDeliveryInfo(info).
 - Redirect to InvoiceScreen if valid. Otherwise call showInvalidInfoError.

3. getDeliveryInfo

- Parameter:

- Exception:

- Method:
 - Construct and return a DeliveryInfo object based on user input.

4. showInvalidInfoError

- Parameter:
 - message: String
- Exception:
- Method:
 - Display error dialog (AlertDialog.show).