


Lecture 2

Modelling with Place/Transition Nets



Lars M. Kristensen

Department of Computing, Mathematics, and Physics

Western Norway University of Applied Sciences


Email: lmkr@hvl.no / WWW: home.hib.no/ansatte/lmkr

Overview

- **Syntactical elements – model structure**
 - Places and transitions
 - Arcs and arc weights
 - Initial marking
- **Semantical concepts - dynamics/execution**
 - Tokens and current marking
 - Transition enabling and occurrence
 - Concurrency, conflict and non-determinism

Two-phase Commit Transaction Protocol

- We will focus on modelling the first phase




Places

- Used to model the **state** of the system
- drawn as ellipses



Tokens and Markings


- A place can contain a number of **tokens**



- A **marking** is a distribution of tokens on the places - represents a system state.

Initial Marking

- The **initial marking** (token distribution) represents the initial system state.
- Specified by giving the number of tokens that are initially present on a place



Initial marking is by conventional specified above the place

Current Marking


- **Current marking is representing the state that the system is currently in**



- **Starts being equal to the initial marking
- changes when the model is executed.**


Transitions

- Used to model the **actions/events** in the system
 - drawn as rectangles




Arcs

- Connect places and transitions and determine transition **enabling** and **occurrence** (firing):




Transition Enabling

- A transition is **enabled** if there is at least one token on each of its input places



Transition Occurrence

- **An enabled transition may **occur** (fire):**
 - Removes one token from each input place
 - Adds one token to each output place




CPN Tools Demo

- **Simulation of CPN models**
- **Extensions to the Place/Transition-net model**
 - Modelling votes – conflict and non-determinism
 - Multiple workers - concurrency
 - Collecting votes - arc weights
 - Modelling the protocol as a reactive system




Modelling Votes




Conflict

- Transitions are in conflict if they compete for tokens with other enabled transitions




Multiple Workers

- Extending the model to multiple workers



Concurrency


- Transitions may be **concurrently enabled** in the same simulation step



- ReceiveCanCommit** transitions can get the tokens required without sharing.


Arc Weights

- Number of tokens required for enabling, consumed and produced (occurrence)




Both workers must have sent a reply

- **Many concurrency systems are intended to continuously operating**




Inhibitor Arc

- Can be used to test for the absence of tokens on a place




Reset Arc

- Removes all tokens that are currently present on a place



Transition Priorities

- Transitions can be given a priority level



Summary

- **Basic syntactical and semantical concepts of Place/Transition Nets introduced.**
- **Additional language constructs**
 - Inhibitor arcs and reset arcs
 - Transition priorities
- **A main limitation of Place/Transitions Nets is scalability to large (real) software systems**
 - Modelling of data is inconvenient.
 - Does not allow models to be split into modules
 - Does not support parametric systems in an elegant way