

Nova AI -- Internal API Reference

Base URL

All API endpoints are served under `/api/v1/`. Production: `https://api.nova-ai.dev/api/v1/`

Authentication

Two authentication flows are supported:

1. Organization users: JWT Bearer token obtained via POST `/auth/login` with email/password.
2. Candidates: JWT Bearer token obtained via POST `/candidates/login` with interview code.

All authenticated requests require the Authorization: Bearer header. Organization endpoints also require the X-Org-Id header.

Key Endpoints

POST `/departments`

Create a new department. Required: owner role. Body: { name, website?, description? }

GET `/departments`

List all departments for the current organization.

POST `/departments/{id}/documents`

Upload a knowledge document (PDF/DOCX/TXT/MD). Triggers RAG pipeline automatically.

GET `/departments/{id}/documents`

List uploaded documents for a department.

POST `/interviews/start`

Start an interview session. Body: { department_id, job_role, mode }

POST `/interviews/{id}/respond`

Submit a response (voice or text) during an active interview.

GET `/orgs/{id}/candidates/ranking`

Get ranked candidate list for an organization, sorted by overall score.

Webhooks

Nova AI fires webhooks for the following events: `interview.completed`, `candidate.ranked`, `scorecard.ready`. Configure webhook URLs in the Organization Settings panel. Payloads are signed with HMAC-SHA256 using your organization's webhook secret.

Rate Limits

Standard tier: 1000 requests/hour per organization. Enterprise tier: 10000 requests/hour. Rate limit headers (X-RateLimit-Remaining, X-RateLimit-Reset) are included in every response.