

# Chapter 1

## Technical Solution

1.1	File Tree Diagram . . . . .	2
1.2	Summary of Complexity . . . . .	3
1.3	Overview . . . . .	3
1.3.1	Main . . . . .	3
1.3.2	Loading Screen . . . . .	4
1.3.3	Helper functions . . . . .	6
1.3.4	Theme . . . . .	14
1.4	GUI . . . . .	15
1.4.1	Laser . . . . .	15
1.4.2	Particles . . . . .	18
1.4.3	Widget Bases . . . . .	21
1.4.4	Widgets . . . . .	30
1.5	Game . . . . .	42
1.5.1	Model . . . . .	42
1.5.2	View . . . . .	47
1.5.3	Controller . . . . .	53
1.5.4	Board . . . . .	58
1.5.5	Bitboards . . . . .	63
1.6	CPU . . . . .	69
1.6.1	Minimax . . . . .	69
1.6.2	Alpha-beta Pruning . . . . .	71
1.6.3	Transposition Table . . . . .	73
1.6.4	Iterative Deepening . . . . .	74
1.6.5	Evaluator . . . . .	75
1.6.6	Multithreading . . . . .	78
1.6.7	Zobrist Hashing . . . . .	79
1.6.8	Cache . . . . .	80
1.7	States . . . . .	82
1.7.1	Review . . . . .	82
1.8	Database . . . . .	88
1.8.1	DDL . . . . .	88
1.8.2	DML . . . . .	89
1.9	Shaders . . . . .	92
1.9.1	Shader Manager . . . . .	92

1.9.2	Bloom . . . . .	97
1.9.3	Rays . . . . .	100

## 1.1 File Tree Diagram

To help navigate through the source code, I have included the following directory tree diagram, along with comments to explain the general purpose of code contained within specific directories and Python files.




Figure 1.1: File tree diagram

## 1.2 Summary of Complexity

- Minimax improvements (1.6.2 and 1.6.3 and 1.6.4)
- Shadow mapping and coordinate transformations (1.9.3)
- Recursive Depth-First Search tree traversal (1.3.4 and 1.6.1)
- Circular doubly-linked list and stack (1.4.3 and 1.7.1)
- Multipass shaders and gaussian blur (1.9.2)
- Aggregate and Window SQL functions (1.8.2)
- OOP techniques (1.4.3 and 1.4.4)
- Multithreading (1.3.2 and 1.6.6)
- Bitboards (1.5.5)
- Zobrist hashing (1.6.7)
- (File handling and JSON parsing) (1.3.3)
- (Dictionary recursion) (1.3.4)
- (Dot product) (1.3.3 and 1.9.2)

## 1.3 Overview

### 1.3.1 Main

The file `main.py` is run by the root file `run.py`. Here resources-intensive classes such as the state and asset files are initialised, while the program displays a loading screen to hide the loading process. The main game loop is then executed.

`main.py`

```
1 from sys import platform
2 # Initialises Pygame
3 import data.setup
4
5 # Windows OS requires some configuration for Pygame to scale GUI continuously
6   while window is being resized
7 if platform == 'win32':
8     import data.windows_setup as win_setup
9 from data.loading_screen import LoadingScreen
10
11 states = [None, None]
12
13 def load_states():
14     """
15     Initialises instances of all screens, executed on another thread with results
16     being stored to the main thread by modifying a mutable such as the states list
17     """
18     from data.control import Control
19     from data.states.game.game import Game
20     from data.states.menu.menu import Menu
21     from data.states.settings.settings import Settings
```

```

20     from data.states.config.config import Config
21     from data.states.browser.browser import Browser
22     from data.states.review.review import Review
23     from data.states.editor.editor import Editor
24
25     state_dict = {
26         'menu': Menu(),
27         'game': Game(),
28         'settings': Settings(),
29         'config': Config(),
30         'browser': Browser(),
31         'review': Review(),
32         'editor': Editor()
33     }
34
35     app = Control()
36
37     states[0] = app
38     states[1] = state_dict
39
40     loading_screen = LoadingScreen(load_states)
41
42     def main():
43         """
44         Executed by run.py, starts main game loop
45         """
46         app, state_dict = states
47
48         if platform == 'win32':
49             win_setup.set_win_resize_func(app.update_window)
50
51         app.setup_states(state_dict, 'menu')
52         app.main_game_loop()

```

### 1.3.2 Loading Screen

**Multithreading** is used to separate the loading screen GUI from the resources intensive actions in `main.py`, to keep the GUI responsive. The easing function `easeOutBack` is also used to animate the logo.

`loading_screen.py`

```

1  import pygame
2  import threading
3  import sys
4  from pathlib import Path
5  from data.helpers.load_helpers import load_gfx, load_sfx
6  from data.managers.window import window
7  from data.managers.audio import audio
8
9  FPS = 30
10 start_ticks = pygame.time.get_ticks()
11 logo_gfx_path = (Path(__file__).parent / '../resources/graphics/gui/icons/logo/
    logo.png').resolve()
12 sfx_path_1 = (Path(__file__).parent / '../resources/sfx/loading_screen/
    loading_screen_1.wav').resolve()
13 sfx_path_2 = (Path(__file__).parent / '../resources/sfx/loading_screen/
    loading_screen_2.wav').resolve()
14
15 def easeOutBack(progress):
16     """

```

```

17     Represents a cubic function for easing the logo position.
18     Starts quickly and has small overshoot, then ends slowly.
19
20     Args:
21         progress (float): x-value for cubic function ranging from 0-1.
22
23     Returns:
24         float:  $2.70x^3 + 1.70x^2 + 0x + 1$ , where x is time elapsed.
25     """
26     c2 = 1.70158
27     c3 = 2.70158
28
29     return c3 * ((progress - 1) ** 3) + c2 * ((progress - 1) ** 2) + 1
30
31 class LoadingScreen:
32     def __init__(self, target_func):
33         """
34         Creates new thread, and sets the load_state() function as its target.
35         Then starts draw loop for the loading screen.
36
37         Args:
38             target_func (Callable): function to be run on thread.
39         """
40         self._clock = pygame.time.Clock()
41         self._thread = threading.Thread(target=target_func)
42         self._thread.start()
43
44         self._logo_surface = load_gfx(logo_gfx_path)
45         self._logo_surface = pygame.transform.scale(self._logo_surface, (96, 96))
46         audio.play_sfx(load_sfx(sfx_path_1))
47         audio.play_sfx(load_sfx(sfx_path_2))
48
49         self.run()
50
51     @property
52     def logo_position(self):
53         duration = 1000
54         displacement = 50
55         elapsed_ticks = pygame.time.get_ticks() - start_ticks
56         progress = min(1, elapsed_ticks / duration)
57         center_pos = ((window.screen.size[0] - self._logo_surface.size[0]) / 2, (
58             window.screen.size[1] - self._logo_surface.size[1]) / 2)
59
60         return (center_pos[0], center_pos[1] + displacement - displacement *
61             easeOutBack(progress))
62
63     @property
64     def logo_opacity(self):
65         return min(255, (pygame.time.get_ticks() - start_ticks) / 5)
66
67     @property
68     def duration_not_over(self):
69         return (pygame.time.get_ticks() - start_ticks) < 1500
70
71     def event_loop(self):
72         """
73         Handles events for the loading screen, no user input is taken except to
74         quit the game.
75         """
76         for event in pygame.event.get():
77             if event.type == pygame.QUIT:
78                 pygame.quit()

```

```

76         sys.exit()
77
78     def draw(self):
79         """
80         Draws logo to screen.
81         """
82         window.screen.fill((0, 0, 0))
83
84         self._logo_surface.set_alpha(self.logo_opacity)
85         window.screen.blit(self._logo_surface, self.logo_position)
86
87         window.update()
88
89     def run(self):
90         """
91         Runs while the thread is still setting up our screens, or the minimum
92         loading screen duration is not reached yet.
93         """
94         while self._thread.is_alive() or self.duration_not_over:
95             self.event_loop()
96             self.draw()
97             self._clock.tick(FPS)

```

### 1.3.3 Helper functions

These files provide useful functions for different classes.

asset\_helpers.py (Functions used for assets and pygame Surfaces)

```

1  import pygame
2  from PIL import Image
3  from functools import cache
4  from random import randint
5  import math
6
7  @cache
8  def scale_and_cache(image, target_size):
9      """
10     Caches image when resized repeatedly.
11
12     Args:
13         image (pygame.Surface): Image surface to be resized.
14         target_size (tuple[float, float]): New image size.
15
16     Returns:
17         pygame.Surface: Resized image surface.
18     """
19     return pygame.transform.scale(image, target_size)
20
21 @cache
22 def smoothscale_and_cache(image, target_size):
23     """
24     Same as scale_and_cache, but with the Pygame smoothscale function.
25
26     Args:
27         image (pygame.Surface): Image surface to be resized.
28         target_size (tuple[float, float]): New image size.
29
30     Returns:
31         pygame.Surface: Resized image surface.
32     """
33     return pygame.transform.smoothscale(image, target_size)

```

```

34
35 def gif_to_frames(path):
36     """
37     Uses the PIL library to break down GIFs into individual frames.
38
39     Args:
40         path (str): Directory path to GIF file.
41
42     Yields:
43         PIL.Image: Single frame.
44     """
45     try:
46         image = Image.open(path)
47
48         first_frame = image.copy().convert('RGBA')
49         yield first_frame
50         image.seek(1)
51
52         while True:
53             current_frame = image.copy()
54             yield current_frame
55             image.seek(image.tell() + 1)
56     except EOFError:
57         pass
58
59 def get_perimeter_sample(image_size, number):
60     """
61     Used for particle drawing class, generates roughly equally distributed points
62     around a rectangular image surface's perimeter.
63
64     Args:
65         image_size (tuple[float, float]): Image surface size.
66         number (int): Number of points to be generated.
67
68     Returns:
69         list[tuple[int, int], ...]: List of random points on perimeter of image
70         surface.
71     """
72     perimeter = 2 * (image_size[0] + image_size[1])
73     # Flatten perimeter to a single number representing the distance from the top-
74     # middle of the surface going clockwise, and create a list of equally spaced
75     # points
76     perimeter_offsets = [(image_size[0] / 2) + (i * perimeter / number) for i in
77                          range(0, number)]
78     pos_list = []
79
80     for perimeter_offset in perimeter_offsets:
81         # For every point, add a random offset
82         max_displacement = int(perimeter / (number * 4))
83         perimeter_offset += randint(-max_displacement, max_displacement)
84
85         if perimeter_offset > perimeter:
86             perimeter_offset -= perimeter
87
88         # Convert 1D distance back into 2D points on image surface perimeter
89         if perimeter_offset < image_size[0]:
90             pos_list.append((perimeter_offset, 0))
91         elif perimeter_offset < image_size[0] + image_size[1]:
92             pos_list.append((image_size[0], perimeter_offset - image_size[0]))
93         elif perimeter_offset < image_size[0] + image_size[1] + image_size[0]:
94             pos_list.append((perimeter_offset - image_size[0] - image_size[1],
95                             image_size[1]))

```

```

90         else:
91             pos_list.append((0, perimeter - perimeter_offset))
92     return pos_list
93
94 def get_angle_between_vectors(u, v, deg=True):
95     """
96     Uses the dot product formula to find the angle between two vectors.
97
98     Args:
99         u (list[int, int]): Vector 1.
100        v (list[int, int]): Vector 2.
101        deg (bool, optional): Return results in degrees. Defaults to True.
102
103     Returns:
104         float: Angle between vectors.
105     """
106     dot_product = sum(i * j for (i, j) in zip(u, v))
107     u_magnitude = math.sqrt(u[0] ** 2 + u[1] ** 2)
108     v_magnitude = math.sqrt(v[0] ** 2 + v[1] ** 2)
109
110     cos_angle = dot_product / (u_magnitude * v_magnitude)
111     radians = math.acos(min(max(cos_angle, -1), 1))
112
113     if deg:
114         return math.degrees(radians)
115     else:
116         return radians
117
118 def get_rotational_angle(u, v, deg=True):
119     """
120     Get bearing angle relative to positive x-axis centered on second vector.
121
122     Args:
123         u (list[int, int]): Vector 1.
124         v (list[int, int]): Vector 2, set as center of axes.
125         deg (bool, optional): Return results in degrees. Defaults to True.
126
127     Returns:
128         float: Bearing angle between vectors.
129     """
130     radians = math.atan2(u[1] - v[1], u[0] - v[0])
131
132     if deg:
133         return math.degrees(radians)
134     else:
135         return radians
136
137 def get_vector(src_vertex, dest_vertex):
138     """
139     Get vector describing translation between two points.
140
141     Args:
142         src_vertex (list[int, int]): Source vertex.
143         dest_vertex (list[int, int]): Destination vertex.
144
145     Returns:
146         tuple[int, int]: Vector between the two points.
147     """
148     return (dest_vertex[0] - src_vertex[0], dest_vertex[1] - src_vertex[1])
149
150 def get_next_corner(vertex, image_size):
151     """

```



```

152     Used in particle drawing system, finds coordinates of the next corner going
153     clockwise, given a point on the perimeter.
154
155     Args:
156         vertex (list[int, int]): Point on perimeter.
157         image_size (list[int, int]): Image size.
158
159     Returns:
160         list[int, int]: Coordinates of corner on perimeter.
161     """
162     corners = [(0, 0), (image_size[0], 0), (image_size[0], image_size[1]), (0,
163 image_size[1])]
164
165     if vertex in corners:
166         return corners[(corners.index(vertex) + 1) % len(corners)]
167
168     if vertex[1] == 0:
169         return (image_size[0], 0)
170     elif vertex[0] == image_size[0]:
171         return image_size
172     elif vertex[1] == image_size[1]:
173         return (0, image_size[1])
174     elif vertex[0] == 0:
175         return (0, 0)
176
177 def pil_image_to_surface(pil_image):
178     """
179     Args:
180         pil_image (PIL.Image): Image to be converted.
181
182     Returns:
183         pygame.Surface: Converted image surface.
184     """
185     return pygame.image.frombytes(pil_image.tobytes(), pil_image.size, pil_image.
186 mode).convert()
187
188 def calculate_frame_index(elapsed_milliseconds, start_index, end_index, fps):
189     """
190     Determine frame of animated GIF to be displayed.
191
192     Args:
193         elapsed_milliseconds (int): Milliseconds since GIF started playing.
194         start_index (int): Start frame of GIF.
195         end_index (int): End frame of GIF.
196         fps (int): Number of frames to be played per second.
197
198     Returns:
199         int: Displayed frame index of GIF.
200     """
201     ms_per_frame = int(1000 / fps)
202     return start_index + ((elapsed_milliseconds // ms_per_frame) % (end_index -
203 start_index))
204
205 def draw_background(screen, background, current_time=0):
206     """
207     Draws background to screen
208
209     Args:
210         screen (pygame.Surface): Screen to be drawn to
211         background (list[pygame.Surface, ...] | pygame.Surface): Background to be
212         drawn, if GIF, list of surfaces indexed to select frame to be drawn
213         current_time (int, optional): Used to calculate frame index for GIF.

```

```

209 Defaults to 0.
210 """
211 if isinstance(background, list):
212     # Animated background passed in as list of surfaces, calculate_frame_index
213     () used to get index of frame to be drawn
214     frame_index = calculate_frame_index(current_time, 0, len(background), fps
215     =8)
216     scaled_background = scale_and_cache(background[frame_index], screen.size)
217     screen.blit(scaled_background, (0, 0))
218 else:
219     scaled_background = scale_and_cache(background, screen.size)
220     screen.blit(scaled_background, (0, 0))
221
222 def get_highlighted_icon(icon):
223     """
224     Used for pressable icons, draws overlay on icon to show as pressed.
225
226     Args:
227         icon (pygame.Surface): Icon surface.
228
229     Returns:
230         pygame.Surface: Icon with overlay drawn on top.
231     """
232     icon_copy = icon.copy()
233     overlay = pygame.Surface((icon.get_width(), icon.get_height()), pygame.
234     SRCALPHA)
235     overlay.fill((0, 0, 0, 128))
236     icon_copy.blit(overlay, (0, 0))
237     return icon_copy

```

data\_helpers.py (Functions used for file handling and JSON parsing)

```

1 import json
2 from pathlib import Path
3
4 module_path = Path(__file__).parent
5 default_file_path = (module_path / '../app_data/default_settings.json').resolve()
6 user_file_path = (module_path / '../app_data/user_settings.json').resolve()
7 themes_file_path = (module_path / '../app_data/themes.json').resolve()
8
9 def load_json(path):
10     """
11     Args:
12         path (str): Path to JSON file.
13
14     Raises:
15         Exception: Invalid file.
16
17     Returns:
18         dict: Parsed JSON file.
19     """
20     try:
21         with open(path, 'r') as f:
22             file = json.load(f)
23
24         return file
25     except:
26         raise Exception('Invalid JSON file (data_helpers.py)')
27
28 def get_user_settings():
29     return load_json(user_file_path)

```

```

30
31 def get_default_settings():
32     return load_json(default_file_path)
33
34 def get_themes():
35     return load_json(themes_file_path)
36
37 def update_user_settings(data):
38     """
39     Rewrites JSON file for user settings with new data.
40
41     Args:
42         data (dict): Dictionary storing updated user settings.
43
44     Raises:
45         Exception: Invalid file.
46     """
47     try:
48         with open(user_file_path, 'w') as f:
49             json.dump(data, f, indent=4)
50     except:
51         raise Exception('Invalid JSON file (data_helpers.py)')

```

widget\_helpers.py (Files used for creating widgets)

```

1 import pygame
2 from math import sqrt
3
4 def create_slider(size, fill_colour, border_width, border_colour):
5     """
6     Creates surface for sliders.
7
8     Args:
9         size (list[int, int]): Image size.
10        fill_colour (pygame.Color): Fill (inner) colour.
11        border_width (float): Border width.
12        border_colour (pygame.Color): Border colour.
13
14    Returns:
15        pygame.Surface: Slider image surface.
16    """
17    gradient_surface = pygame.Surface(size, pygame.SRCALPHA)
18    border_rect = pygame.FRect((0, 0, gradient_surface.width, gradient_surface.
19    height))
20
21    # Draws rectangle with a border radius half of image height, to draw an
22    # rectangle with semicircular cap (obround)
23    pygame.draw.rect(gradient_surface, fill_colour, border_rect, border_radius=int
24    (size[1] / 2))
25    pygame.draw.rect(gradient_surface, border_colour, border_rect, width=int(
26    border_width), border_radius=int(size[1] / 2))
27
28    return gradient_surface
29
30 def create_slider_gradient(size, border_width, border_colour):
31     """
32     Draws surface for colour slider, with a full colour gradient as fill colour.
33
34     Args:
35         size (list[int, int]): Image size.
36         border_width (float): Border width.

```

```

33         border_colour (pygame.Color): Border colour.
34
35     Returns:
36         pygame.Surface: Slider image surface.
37     """
38     gradient_surface = pygame.Surface(size, pygame.SRCALPHA)
39
40     first_round_end = gradient_surface.height / 2
41     second_round_end = gradient_surface.width - first_round_end
42     gradient_y_mid = gradient_surface.height / 2
43
44     # Iterate through length of slider
45     for i in range(gradient_surface.width):
46         draw_height = gradient_surface.height
47
48         if i < first_round_end or i > second_round_end:
49             # Draw semicircular caps if x-distance less than or greater than
49             radius of cap (half of image height)
50             distance_from_cutoff = min(abs(first_round_end - i), abs(i -
50             second_round_end))
51             draw_height = calculate_gradient_slice_height(distance_from_cutoff,
51             gradient_surface.height / 2)
52
53             # Get colour from distance from left side of slider
54             color = pygame.Color(0)
55             color.hsva = (int(360 * i / gradient_surface.width), 100, 100, 100)
56
57             draw_rect = pygame.FRect((0, 0, 1, draw_height - 2 * border_width))
58             draw_rect.center = (i, gradient_y_mid)
59
60             pygame.draw.rect(gradient_surface, color, draw_rect)
61
62     border_rect = pygame.FRect((0, 0, gradient_surface.width, gradient_surface.
62     height))
63     pygame.draw.rect(gradient_surface, border_colour, border_rect, width=int(
63     border_width), border_radius=int(size[1] / 2))
64
65     return gradient_surface
66
67 def calculate_gradient_slice_height(distance, radius):
68     """
69     Calculate height of vertical slice of semicircular slider cap.
70
71     Args:
72         distance (float): x-distance from center of circle.
73         radius (float): Radius of semicircle.
74
75     Returns:
76         float: Height of vertical slice.
77     """
78     return sqrt(radius ** 2 - distance ** 2) * 2 + 2
79
80 def create_slider_thumb(radius, colour, border_colour, border_width):
81     """
82     Creates surface with bordered circle.
83
84     Args:
85         radius (float): Radius of circle.
86         colour (pygame.Color): Fill colour.
87         border_colour (pygame.Color): Border colour.
88         border_width (float): Border width.
89

```

```

90     Returns:
91         pygame.Surface: Circle surface.
92     """
93     thumb_surface = pygame.Surface((radius * 2, radius * 2), pygame.SRCALPHA)
94     pygame.draw.circle(thumb_surface, border_colour, (radius, radius), radius,
95                       width=int(border_width))
96     pygame.draw.circle(thumb_surface, colour, (radius, radius), (radius -
97                       border_width))
98
99     return thumb_surface
100
101 def create_square_gradient(side_length, colour):
102     """
103     Creates a square gradient for the colour picker widget, gradient transitioning
104     between saturation and value.
105     Uses smoothscale to blend between colour values for individual pixels.
106
107     Args:
108         side_length (float): Length of a square side.
109         colour (pygame.Color): Colour with desired hue value.
110
111     Returns:
112         pygame.Surface: Square gradient surface.
113     """
114     square_surface = pygame.Surface((side_length, side_length))
115
116     mix_1 = pygame.Surface((1, 2))
117     mix_1.fill((255, 255, 255))
118     mix_1.set_at((0, 1), (0, 0, 0))
119     mix_1 = pygame.transform.smoothscale(mix_1, (side_length, side_length))
120
121     hue = colour.hsva[0]
122     saturated_rgb = pygame.Color(0)
123     saturated_rgb.hsva = (hue, 100, 100)
124
125     mix_2 = pygame.Surface((2, 1))
126     mix_2.fill((255, 255, 255))
127     mix_2.set_at((1, 0), saturated_rgb)
128     mix_2 = pygame.transform.smoothscale(mix_2, (side_length, side_length))
129
130     mix_1.blit(mix_2, (0, 0), special_flags=pygame.BLEND_MULT)
131
132     square_surface.blit(mix_1, (0, 0))
133
134     return square_surface
135
136 def create_switch(size, colour):
137     """
138     Creates surface for switch toggle widget.
139
140     Args:
141         size (list[int, int]): Image size.
142         colour (pygame.Color): Fill colour.
143
144     Returns:
145         pygame.Surface: Switch surface.
146     """
147     switch_surface = pygame.Surface((size[0], size[1]), pygame.SRCALPHA)
148     pygame.draw.rect(switch_surface, colour, (0, 0, size[0], size[1]),
149                     border_radius=int(size[1] / 2))
150
151     return switch_surface

```

```

148
149 def create_text_box(size, border_width, colours):
150     """
151     Creates bordered textbox with shadow, flat, and highlighted vertical regions.
152
153     Args:
154         size (list[int, int]): Image size.
155         border_width (float): Border width.
156         colours (list[pygame.Color, ...]): List of 4 colours, representing border
            colour, shadow colour, flat colour and highlighted colour.
157
158     Returns:
159         pygame.Surface: Textbox surface.
160     """
161     surface = pygame.Surface(size, pygame.SRCALPHA)
162
163     pygame.draw.rect(surface, colours[0], (0, 0, *size))
164     pygame.draw.rect(surface, colours[2], (border_width, border_width, size[0] - 2
        * border_width, size[1] - 2 * border_width))
165     pygame.draw.rect(surface, colours[3], (border_width, border_width, size[0] - 2
        * border_width, border_width))
166     pygame.draw.rect(surface, colours[1], (border_width, size[1] - 2 *
        border_width, size[0] - 2 * border_width, border_width))
167
168     return surface

```

### 1.3.4 Theme

The theme manager file is responsible for providing an instance where the colour palette and dimensions for the GUI can be accessed. Values read from a JSON file are **recursively** flattened, with keys created from the dictionary hierarchy, and stored into the internal dictionary of a ThemeManager object.

theme.py

```

1 from data.helpers.data_helpers import get_themes, get_user_settings
2
3 themes = get_themes()
4 user_settings = get_user_settings()
5
6 def flatten_dictionary_generator(dictionary, parent_key=None):
7     """
8     Recursive depth-first search to yield all items in a dictionary.
9
10    Args:
11        dictionary (dict): Dictionary to be iterated through.
12        parent_key (str, optional): Prefix added to every key. Defaults to None.
13
14    Yields:
15        dict | tuple[str, str]: Another dictionary or key, value pair.
16    """
17    for key, value in dictionary.items():
18        if parent_key:
19            new_key = parent_key + key.capitalize()
20        else:
21            new_key = key
22
23        if isinstance(value, dict):
24            yield from flatten_dictionary(value, new_key).items()
25        else:
26            yield new_key, value

```

```

27
28 def flatten_dictionary(dictionary, parent_key=''):
29     return dict(flatten_dictionary_generator(dictionary, parent_key))
30
31 class ThemeManager:
32     def __init__(self):
33         self.__dict__.update(flatten_dictionary(themes['colours']))
34         self.__dict__.update(flatten_dictionary(themes['dimensions']))
35
36     def __getitem__(self, arg):
37         """
38         Override default class's __getitem__ dunder method, to make retrieving an
39         instance attribute nicer with [] notation.
40
41         Args:
42             arg (str): Attribute name.
43
44         Raises:
45             KeyError: Instance does not have requested attribute.
46
47         Returns:
48             str | int: Instance attribute.
49         """
50         item = self.__dict__.get(arg)
51
52         if item is None:
53             raise KeyError('(ThemeManager.__getitem__) Requested theme item not
54             found:', arg)
55
56         return item
57
58 theme = ThemeManager()

```

## 1.4 GUI

### 1.4.1 Laser

The LaserDraw class draws the laser in both the game and review screens.  
laser\_draw.py

```

1 import pygame
2 from data.helpers.board_helpers import coords_to_screen_pos
3 from data.utils.enums import LaserType, Colour, ShaderType
4 from data.managers.animation import animation
5 from data.utils.assets import GRAPHICS, SFX
6 from data.utils.constants import EMPTY_BB
7 from data.managers.window import window
8 from data.managers.audio import audio
9
10 type_to_image = {
11     LaserType.END: ['laser_end_1', 'laser_end_2'],
12     LaserType.STRAIGHT: ['laser_straight_1', 'laser_straight_2'],
13     LaserType.CORNER: ['laser_corner_1', 'laser_corner_2']
14 }
15
16 GLOW_SCALE_FACTOR = 1.5
17
18 class LaserDraw:
19     def __init__(self, board_position, board_size):
20         self._board_position = board_position

```

```

21         self._square_size = board_size[0] / 10
22         self._laser_lists = []
23
24     @property
25     def firing(self):
26         return len(self._laser_lists) > 0
27
28     def add_laser(self, laser_result, laser_colour):
29         """
30         Adds a laser to the board.
31
32         Args:
33             laser_result (Laser): Laser class instance containing laser trajectory
34             info.
35             laser_colour (Colour.RED | Colour.BLUE): Active colour of laser.
36         """
37         laser_path = laser_result.laser_path.copy()
38         laser_types = [LaserType.END]
39         # List of angles in degree to rotate the laser image surface when drawn
40         laser_rotation = [laser_path[0][1]]
41         laser_lights = []
42
43         # Iterates through every square laser passes through
44         for i in range(1, len(laser_path)):
45             previous_direction = laser_path[i-1][1]
46             current_coords, current_direction = laser_path[i]
47
48             if current_direction == previous_direction:
49                 laser_types.append(LaserType.STRAIGHT)
50                 laser_rotation.append(current_direction)
51             elif current_direction == previous_direction.get_clockwise():
52                 laser_types.append(LaserType.CORNER)
53                 laser_rotation.append(current_direction)
54             elif current_direction == previous_direction.get_anticlockwise():
55                 laser_types.append(LaserType.CORNER)
56                 laser_rotation.append(current_direction.get_anticlockwise())
57
58             # Adds a shader ray effect on the first and last square of the laser
59             trajectory
60             if i in [1, len(laser_path) - 1]:
61                 abs_position = coords_to_screen_pos(current_coords, self.
62                 _board_position, self._square_size)
63                 laser_lights.append([
64                     (abs_position[0] / window.size[0], abs_position[1] / window.
65                     size[1]),
66                     0.35,
67                     (0, 0, 255) if laser_colour == Colour.BLUE else (255, 0, 0),
68                     ])
69
70             # Sets end laser draw type if laser hits a piece
71             if laser_result.hit_square_bitboard != EMPTY_BB:
72                 laser_types[-1] = LaserType.END
73                 laser_path[-1] = (laser_path[-1][0], laser_path[-2][1].get_opposite())
74                 laser_rotation[-1] = laser_path[-2][1].get_opposite()
75
76             audio.play_sfx(SFX['piece_destroy'])
77
78         laser_path = [(coords, rotation, type) for (coords, dir), rotation, type
79         in zip(laser_path, laser_rotation, laser_types)]
80         self._laser_lists.append((laser_path, laser_colour))
81
82         window.clear_effect(ShaderType.RAYS)

```



```

78         window.set_effect(ShaderType.RAYS, lights=laser_lights)
79         animation.set_timer(1000, self.remove_laser)
80
81         audio.play_sfx(SFX['laser_1'])
82         audio.play_sfx(SFX['laser_2'])
83
84     def remove_laser(self):
85         """
86         Removes a laser from the board.
87         """
88         self._laser_lists.pop(0)
89
90         if len(self._laser_lists) == 0:
91             window.clear_effect(ShaderType.RAYS)
92
93     def draw_laser(self, screen, laser_list, glow=True):
94         """
95         Draws every laser on the screen.
96
97         Args:
98             screen (pygame.Surface): The screen to draw on.
99             laser_list (list): The list of laser segments to draw.
100             glow (bool, optional): Whether to draw a glow effect. Defaults to True
101
102         """
103         laser_path, laser_colour = laser_list
104         laser_list = []
105         glow_list = []
106
107         for coords, rotation, type in laser_path:
108             square_x, square_y = coords_to_screen_pos(coords, self._board_position
109 , self._square_size)
110
111             image = GRAPHICS[type_to_image[type]][laser_colour]]
112             rotated_image = pygame.transform.rotate(image, rotation.to_angle())
113             scaled_image = pygame.transform.scale(rotated_image, (self.
114 _square_size + 1, self._square_size + 1)) # +1 to prevent rounding creating
115 black lines
116             laser_list.append((scaled_image, (square_x, square_y)))
117
118             # Scales up the laser image surface as a glow surface
119             scaled_glow = pygame.transform.scale(rotated_image, (self._square_size
120 * GLOW_SCALE_FACTOR, self._square_size * GLOW_SCALE_FACTOR))
121             offset = self._square_size * ((GLOW_SCALE_FACTOR - 1) / 2)
122             glow_list.append((scaled_glow, (square_x - offset, square_y - offset))
123 )
124
125         # Scaled glow surfaces drawn on top with the RGB_ADD blend mode
126         if glow:
127             screen.fblits(glow_list, pygame.BLEND_RGB_ADD)
128
129         screen.blits(laser_list)
130
131     def draw(self, screen):
132         """
133         Draws all lasers on the screen.
134
135         Args:
136             screen (pygame.Surface): The screen to draw on.
137         """
138         for laser_list in self._laser_lists:
139             self.draw_laser(screen, laser_list)

```

```

134
135     def handle_resize(self, board_position, board_size):
136         """
137         Handles resizing of the board.
138
139         Args:
140             board_position (tuple[int, int]): The new position of the board.
141             board_size (tuple[int, int]): The new size of the board.
142         """
143         self._board_position = board_position
144         self._square_size = board_size[0] / 10

```

## 1.4.2 Particles

The `ParticlesDraw` class draws particles in both the game and review screens. The particles are either fragmented pieces when destroyed, or laser particles emitted from the Sphinx. Particles are given custom velocity, rotation, opacity and size parameters.

`particles_draw.py`

```

1  import pygame
2  from random import randint
3  from data.helpers.asset_helpers import get_perimeter_sample, get_vector,
   get_angle_between_vectors, get_next_corner
4  from data.states.game.components.piece_sprite import PieceSprite
5
6  class ParticlesDraw:
7      def __init__(self, gravity=0.2, rotation=180, shrink=0.5, opacity=150):
8          self._particles = []
9          self._glow_particles = []
10
11          self._gravity = gravity
12          self._rotation = rotation
13          self._shrink = shrink
14          self._opacity = opacity
15
16      def fragment_image(self, image, number):
17          image_size = image.get_rect().size
18          """
19          1. Takes an image surface and samples random points on the perimeter.
20          2. Iterates through points, and depending on the nature of two consecutive
           points, finds a corner between them.
21          3. Draws a polygon with the points as the vertices to mask out the area
           not in the fragment.
22
23          Args:
24              image (pygame.Surface): Image to fragment.
25              number (int): The number of fragments to create.
26
27          Returns:
28              list[pygame.Surface]: List of image surfaces with fragment of original
           surface drawn on top.
29          """
30          center = image.get_rect().center
31          points_list = get_perimeter_sample(image_size, number)
32          fragment_list = []
33
34          points_list.append(points_list[0])
35
36          # Iterate through points_list, using the current point and the next one
37          for i in range(len(points_list) - 1):

```

```

38         vertex_1 = points_list[i]
39         vertex_2 = points_list[i + 1]
40         vector_1 = get_vector(center, vertex_1)
41         vector_2 = get_vector(center, vertex_2)
42         angle = get_angle_between_vectors(vector_1, vector_2)
43
44         cropped_image = pygame.Surface(image_size, pygame.SRCALPHA)
45         cropped_image.fill((0, 0, 0, 0))
46         cropped_image.blit(image, (0, 0))
47
48         corners_to_draw = None
49
50         if vertex_1[0] == vertex_2[0] or vertex_1[1] == vertex_2[1]: # Points
on the same side
51             corners_to_draw = 4
52
53             elif abs(vertex_1[0] - vertex_2[0]) == image_size[0] or abs(vertex_1
[1] - vertex_2[1]) == image_size[1]: # Points on opposite sides
54                 corners_to_draw = 2
55
56             elif angle < 180: # Points on adjacent sides
57                 corners_to_draw = 3
58
59             else:
60                 corners_to_draw = 1
61
62             corners_list = []
63             for j in range(corners_to_draw):
64                 if len(corners_list) == 0:
65                     corners_list.append(get_next_corner(vertex_2, image_size))
66                 else:
67                     corners_list.append(get_next_corner(corners_list[-1],
image_size))
68
69             pygame.draw.polygon(cropped_image, (0, 0, 0, 0), (center, vertex_2, *
corners_list, vertex_1))
70
71             fragment_list.append(cropped_image)
72
73         return fragment_list
74
75     def add_captured_piece(self, piece, colour, rotation, position, size):
76         """
77         Adds a captured piece to fragment into particles.
78
79         Args:
80             piece (Piece): The piece type.
81             colour (Colour): The active colour of the piece.
82             rotation (int): The rotation of the piece.
83             position (tuple[int, int]): The position where particles originate
from.
84             size (tuple[int, int]): The size of the piece.
85         """
86         piece_sprite = PieceSprite(piece, colour, rotation)
87         piece_sprite.set_geometry((0, 0), size)
88         piece_sprite.set_image()
89
90         particles = self.fragment_image(piece_sprite.image, 5)
91
92         for particle in particles:
93             self.add_particle(particle, position)
94

```

```

95     def add_sparks(self, radius, colour, position):
96         """
97         Adds laser spark particles.
98
99         Args:
100             radius (int): The radius of the sparks.
101             colour (Colour): The active colour of the sparks.
102             position (tuple[int, int]): The position where particles originate
103         """
104         for i in range(randint(10, 15)):
105             velocity = [randint(-15, 15) / 10, randint(-20, 0) / 10]
106             random_colour = [min(max(val + randint(-20, 20), 0), 255) for val in
107                             colour]
108             self._particles.append([None, [radius, random_colour], [*position],
109                                   velocity, 0])
110
111     def add_particle(self, image, position):
112         """
113         Adds a particle.
114
115         Args:
116             image (pygame.Surface): The image of the particle.
117             position (tuple): The position of the particle.
118         """
119         velocity = [randint(-15, 15) / 10, randint(-20, 0) / 10]
120
121         # Each particle is stored with its attributes: [surface, copy of surface,
122         # position, velocity, lifespan]
123         self._particles.append([image, image.copy(), [*position], velocity, 0])
124
125     def update(self):
126         """
127         Updates each particle and its attributes.
128         """
129         for i in range(len(self._particles) - 1, -1, -1):
130             particle = self._particles[i]
131
132             #update position
133             particle[2][0] += particle[3][0]
134             particle[2][1] += particle[3][1]
135
136             #update lifespan
137             self._particles[i][4] += 0.01
138
139             if self._particles[i][4] >= 1:
140                 self._particles.pop(i)
141                 continue
142
143             if isinstance(particle[1], pygame.Surface): # Particle is a piece
144                 # Update velocity
145                 particle[3][1] += self._gravity
146
147                 # Update size
148                 image_size = particle[1].get_rect().size
149                 end_size = ((1 - self._shrink) * image_size[0], (1 - self._shrink)
150                             * image_size[1])
151                 target_size = (image_size[0] - particle[4] * (image_size[0] -
152                             end_size[0]), image_size[1] - particle[4] * (image_size[1] - end_size[1]))
153
154                 # Update rotation
155                 rotation = (self._rotation if particle[3][0] <= 0 else -self.

```

```

        _rotation) * particle[4]
151
152         updated_image = pygame.transform.scale(pygame.transform.rotate(
particle[1], rotation), target_size)
153
154         elif isinstance(particle[1], list): # Particle is a spark
155             # Update size
156             end_radius = (1 - self._shrink) * particle[1][0]
157             target_radius = particle[1][0] - particle[4] * (particle[1][0] -
end_radius)
158
159             updated_image = pygame.Surface((target_radius * 2, target_radius *
2), pygame.SRCALPHA)
160             pygame.draw.circle(updated_image, particle[1][1], (target_radius,
target_radius), target_radius)
161
162             # Update opacity
163             alpha = 255 - particle[4] * (255 - self._opacity)
164
165             updated_image.fill((255, 255, 255, alpha), None, pygame.
BLEND_RGBA_MULT)
166
167             particle[0] = updated_image
168
169     def draw(self, screen):
170         """
171         Draws the particles, indexing the surface and position attributes for each
particle.
172
173         Args:
174             screen (pygame.Surface): The screen to draw on.
175         """
176         screen.blit([
177             (particle[0], particle[2]) for particle in self._particles
178         ])

```

### 1.4.3 Widget Bases

Widget bases are used as the base classes for my widgets system. They contain both attributes and getter methods that provide both basic functionalities such as size and position, and abstract methods to be overridden. These bases are designed to be used with **multiple inheritance**, where multiple bases can be combined to add functionality to the final widget. **Encapsulation** also allows me to simplify interactions between widgets, as using getter methods instead of protected attributes allows me to add logic while accessing an attribute, such as in `widget.py`, where the logic to fetch the parent surface instead of the windows screen is hidden within the base class.

#### Widget

All widgets are a subclass of the `Widget` class.

`widget.py`

```

1 import pygame
2 from data.utils.constants import SCREEN_SIZE
3 from data.managers.theme import theme
4 from data.utils.assets import DEFAULT_FONT
5
6 DEFAULT_SURFACE_SIZE = SCREEN_SIZE
7 REQUIRED_KWARGS = ['relative_position', 'relative_size']

```

```

8
9 class _Widget(pygame.sprite.Sprite):
10     def __init__(self, **kwargs):
11         """
12         Every widget has the following attributes:
13
14         surface (pygame.Surface): The surface the widget is drawn on.
15         raw_surface_size (tuple[int, int]): The initial size of the window screen,
16         remains constant.
17         parent (_Widget, optional): The parent widget position and size is
18         relative to.
19
20         Relative to current surface:
21         relative_position (tuple[float, float]): The position of the widget
22         relative to its surface.
23         relative_size (tuple[float, float]): The scale of the widget relative to
24         its surface.
25
26         Remains constant, relative to initial screen size:
27         relative_font_size (float, optional): The relative font size of the widget
28         .
29         relative_margin (float): The relative margin of the widget.
30         relative_border_width (float): The relative border width of the widget.
31         relative_border_radius (float): The relative border radius of the widget.
32
33         anchor_x (str): The horizontal anchor direction ('left', 'right', 'center
34         ').
35         anchor_y (str): The vertical anchor direction ('top', 'bottom', 'center').
36         fixed_position (tuple[int, int], optional): The fixed position of the
37         widget in pixels.
38         border_colour (pygame.Color): The border color of the widget.
39         text_colour (pygame.Color): The text color of the widget.
40         fill_colour (pygame.Color): The fill color of the widget.
41         font (pygame.freetype.Font): The font used for the widget.
42         """
43         super().__init__()
44
45         for required_kwarg in REQUIRED_KWARGS:
46             if required_kwarg not in kwargs:
47                 raise KeyError(f'(_Widget.__init__) Required keyword "{
48                 required_kwarg}" not in base kwargs')
49
50         self._surface = None # Set in WidgetGroup, as needs to be reassigned every
51         frame
52         self._raw_surface_size = DEFAULT_SURFACE_SIZE
53
54         self._parent = kwargs.get('parent')
55
56         self._relative_font_size = None # Set in subclass
57
58         self._relative_position = kwargs.get('relative_position')
59         self._relative_margin = theme['margin'] / self._raw_surface_size[1]
60         self._relative_border_width = theme['borderWidth'] / self.
61         _raw_surface_size[1]
62         self._relative_border_radius = theme['borderRadius'] / self.
63         _raw_surface_size[1]
64
65         self._border_colour = pygame.Color(theme['borderPrimary'])
66         self._text_colour = pygame.Color(theme['textPrimary'])
67         self._fill_colour = pygame.Color(theme['fillPrimary'])
68         self._font = DEFAULT_FONT
69

```

```

59     self._anchor_x = kwargs.get('anchor_x') or 'left'
60     self._anchor_y = kwargs.get('anchor_y') or 'top'
61     self._fixed_position = kwargs.get('fixed_position')
62     scale_mode = kwargs.get('scale_mode') or 'both'
63
64     if kwargs.get('relative_size'):
65         match scale_mode:
66             case 'height':
67                 self._relative_size = kwargs.get('relative_size')
68             case 'width':
69                 self._relative_size = ((kwargs.get('relative_size')[0] * self.
surface_size[0]) / self.surface_size[1], (kwargs.get('relative_size')[1] *
self.surface_size[0]) / self.surface_size[1])
70             case 'both':
71                 self._relative_size = ((kwargs.get('relative_size')[0] * self.
surface_size[0]) / self.surface_size[1], kwargs.get('relative_size')[1])
72             case _:
73                 raise ValueError('(_Widget.__init__) Unknown scale mode:',
scale_mode)
74         else:
75             self._relative_size = (1, 1)
76
77         if 'margin' in kwargs:
78             self._relative_margin = kwargs.get('margin') / self._raw_surface_size
[1]
79
80             if (self._relative_margin * 2) > min(self._relative_size[0], self.
_relative_size[1]):
81                 raise ValueError('(_Widget.__init__) Margin larger than specified
size!')
82
83         if 'border_width' in kwargs:
84             self._relative_border_width = kwargs.get('border_width') / self.
_raw_surface_size[1]
85
86         if 'border_radius' in kwargs:
87             self._relative_border_radius = kwargs.get('border_radius') / self.
_raw_surface_size[1]
88
89         if 'border_colour' in kwargs:
90             self._border_colour = pygame.Color(kwargs.get('border_colour'))
91
92         if 'fill_colour' in kwargs:
93             self._fill_colour = pygame.Color(kwargs.get('fill_colour'))
94
95         if 'text_colour' in kwargs:
96             self._text_colour = pygame.Color(kwargs.get('text_colour'))
97
98         if 'font' in kwargs:
99             self._font = kwargs.get('font')
100
101     @property
102     def surface_size(self):
103         """
104         Gets the size of the surface widget is drawn on.
105         Can be either the window size, or another widget size if assigned to a
parent.
106
107         Returns:
108             tuple[int, int]: The size of the surface.
109         """
110         if self._parent:

```

```

111         return self._parent.size
112     else:
113         return self._raw_surface_size
114
115 @property
116 def position(self):
117     """
118     Gets the position of the widget.
119     Accounts for fixed position attribute, where widget is positioned in
120     pixels regardless of screen size.
121     Accounts for anchor direction, where position attribute is calculated
122     relative to one side of the screen.
123
124     Returns:
125     tuple[int, int]: The position of the widget.
126     """
127     x, y = None, None
128     if self._fixed_position:
129         x, y = self._fixed_position
130     if x is None:
131         x = self._relative_position[0] * self.surface_size[0]
132     if y is None:
133         y = self._relative_position[1] * self.surface_size[1]
134
135     if self._anchor_x == 'left':
136         x = x
137     elif self._anchor_x == 'right':
138         x = self.surface_size[0] - x - self.size[0]
139     elif self._anchor_x == 'center':
140         x = (self.surface_size[0] / 2 - self.size[0] / 2) + x
141
142     if self._anchor_y == 'top':
143         y = y
144     elif self._anchor_y == 'bottom':
145         y = self.surface_size[1] - y - self.size[1]
146     elif self._anchor_y == 'center':
147         y = (self.surface_size[1] / 2 - self.size[1] / 2) + y
148
149     # Position widget relative to parent, if exists.
150     if self._parent:
151         return (x + self._parent.position[0], y + self._parent.position[1])
152
153     return (x, y)
154
155 @property
156 def size(self):
157     return (self._relative_size[0] * self.surface_size[1], self._relative_size
158 [1] * self.surface_size[1])
159
160 @property
161 def margin(self):
162     return self._relative_margin * self._raw_surface_size[1]
163
164 @property
165 def border_width(self):
166     return self._relative_border_width * self._raw_surface_size[1]
167
168 @property
169 def border_radius(self):
170     return self._relative_border_radius * self._raw_surface_size[1]
171
172 @property

```



```

170     def font_size(self):
171         return self._relative_font_size * self.surface_size[1]
172
173     def set_image(self):
174         """
175         Abstract method to draw widget.
176         """
177         raise NotImplementedError
178
179     def set_geometry(self):
180         """
181         Sets the position and size of the widget.
182         """
183         self.rect = self.image.get_rect()
184
185         if self._anchor_x == 'left':
186             if self._anchor_y == 'top':
187                 self.rect.topleft = self.position
188             elif self._anchor_y == 'bottom':
189                 self.rect.topleft = self.position
190             elif self._anchor_y == 'center':
191                 self.rect.topleft = self.position
192         elif self._anchor_x == 'right':
193             if self._anchor_y == 'top':
194                 self.rect.topleft = self.position
195             elif self._anchor_y == 'bottom':
196                 self.rect.topleft = self.position
197             elif self._anchor_y == 'center':
198                 self.rect.topleft = self.position
199         elif self._anchor_x == 'center':
200             if self._anchor_y == 'top':
201                 self.rect.topleft = self.position
202             elif self._anchor_y == 'bottom':
203                 self.rect.topleft = self.position
204             elif self._anchor_y == 'center':
205                 self.rect.topleft = self.position
206
207     def set_surface_size(self, new_surface_size):
208         """
209         Sets the new size of the surface widget is drawn on.
210
211         Args:
212             new_surface_size (tuple[int, int]): The new size of the surface.
213         """
214         self._raw_surface_size = new_surface_size
215
216     def process_event(self, event):
217         """
218         Abstract method to handle events.
219
220         Args:
221             event (pygame.Event): The event to process.
222         """
223         raise NotImplementedError

```

## Circular

The `Circular` class provides an internal circular linked list, giving functionality to support widgets which rotate between text/icons. `circular.py`

```

1 from data.components.circular_linked_list import CircularLinkedList

```

```

2
3 class _Circular:
4     def __init__(self, items_dict, **kwargs):
5         # The key, value pairs are stored within a dictionary, while the keys to
6         # access them are stored within circular linked list.
7         self._items_dict = items_dict
8         self._keys_list = CircularLinkedList(list(items_dict.keys()))
9
10    @property
11    def current_key(self):
12        """
13        Gets the current head node of the linked list, and returns a key stored as
14        the node data.
15        Returns:
16            Data of linked list head.
17        """
18        return self._keys_list.get_head().data
19
20    @property
21    def current_item(self):
22        """
23        Gets the value in self._items_dict with the key being self.current_key.
24        Returns:
25            Value stored with key being current head of linked list.
26        """
27        return self._items_dict[self.current_key]
28
29    def set_next_item(self):
30        """
31        Sets the next item in as the current item.
32        """
33        self._keys_list.shift_head()
34
35    def set_previous_item(self):
36        """
37        Sets the previous item as the current item.
38        """
39        self._keys_list.unshift_head()
40
41    def set_to_key(self, key):
42        """
43        Sets the current item to the specified key.
44        Args:
45            key: The key to set as the current item.
46        Raises:
47            ValueError: If no nodes within the circular linked list contains the
48            key as its data.
49        """
50        if self._keys_list.data_in_list(key) is False:
51            raise ValueError('(_Circular.set_to_key) Key not found:', key)
52
53        for _ in range(len(self._items_dict)):
54            if self.current_key == key:
55                self.set_image()
56                self.set_geometry()
57                return
58
59        self.set_next_item()

```

## Circular Linked List

As described in Section ??, the `CircularLinkedList` class implements a **circular doubly-linked list**. Used for the internal logic of the `circular` class.

`circular_linked_list.py`

```
1 class Node:
2     def __init__(self, data):
3         self.data = data
4         self.next = None
5         self.previous = None
6
7 class CircularLinkedList:
8     def __init__(self, list_to_convert=None):
9         """
10            Initialises a CircularLinkedList object.
11
12            Args:
13                list_to_convert (list, optional): Creates a linked list from existing
14                items. Defaults to None.
15            """
16            self._head = None
17
18            if list_to_convert:
19                for item in list_to_convert:
20                    self.insert_at_end(item)
21
22     def __str__(self):
23         """
24            Returns a string representation of the circular linked list.
25
26            Returns:
27                str: Linked list formatted as string.
28            """
29            if self._head is None:
30                return '| empty |'
31
32            characters = '| -> '
33            current_node = self._head
34            while True:
35                characters += str(current_node.data) + ' -> '
36                current_node = current_node.next
37
38                if current_node == self._head:
39                    characters += '|'
40                    return characters
41
42     def insert_at_beginning(self, data):
43         """
44            Inserts a node at the beginning of the circular linked list.
45
46            Args:
47                data: The data to insert.
48            """
49            new_node = Node(data)
50
51            if self._head is None:
52                self._head = new_node
53                new_node.next = self._head
54                new_node.previous = self._head
55            else:
56                new_node.next = self._head
```

```

56         new_node.previous = self._head.previous
57         self._head.previous.next = new_node
58         self._head.previous = new_node
59
60         self._head = new_node
61
62     def insert_at_end(self, data):
63         """
64         Inserts a node at the end of the circular linked list.
65
66         Args:
67             data: The data to insert.
68         """
69         new_node = Node(data)
70
71         if self._head is None:
72             self._head = new_node
73             new_node.next = self._head
74             new_node.previous = self._head
75         else:
76             new_node.next = self._head
77             new_node.previous = self._head.previous
78             self._head.previous.next = new_node
79             self._head.previous = new_node
80
81     def insert_at_index(self, data, index):
82         """
83         Inserts a node at a specific index in the circular linked list.
84         The head node is taken as index 0.
85
86         Args:
87             data: The data to insert.
88             index (int): The index to insert the data at.
89
90         Raises:
91             ValueError: Index is out of range.
92         """
93         if index < 0:
94             raise ValueError('Invalid index! (CircularLinkedList.insert_at_index)'
95 )
96
97         if index == 0 or self._head is None:
98             self.insert_at_beginning(data)
99         else:
100             new_node = Node(data)
101             current_node = self._head
102             count = 0
103
104             while count < index - 1 and current_node.next != self._head:
105                 current_node = current_node.next
106                 count += 1
107
108             if count == (index - 1):
109                 new_node.next = current_node.next
110                 new_node.previous = current_node
111                 current_node.next = new_node
112             else:
113                 raise ValueError('Index out of range! (CircularLinkedList.
114 insert_at_index)')
115
116     def delete(self, data):
117         """

```

```

116         Deletes a node with the specified data from the circular linked list.
117
118     Args:
119         data: The data to delete.
120
121     Raises:
122         ValueError: No nodes in the list contain the specified data.
123     """
124     if self._head is None:
125         return
126
127     current_node = self._head
128
129     while current_node.data != data:
130         current_node = current_node.next
131
132         if current_node == self._head:
133             raise ValueError('Data not found in circular linked list! (
CircularLinkedList.delete)')
134
135     if self._head.next == self._head:
136         self._head = None
137     else:
138         current_node.previous.next = current_node.next
139         current_node.next.previous = current_node.previous
140
141     def data_in_list(self, data):
142     """
143     Checks if the specified data is in the circular linked list.
144
145     Args:
146         data: The data to check.
147
148     Returns:
149         bool: True if the data is in the list, False otherwise.
150     """
151     if self._head is None:
152         return False
153
154     current_node = self._head
155     while True:
156         if current_node.data == data:
157             return True
158
159         current_node = current_node.next
160         if current_node == self._head:
161             return False
162
163     def shift_head(self):
164     """
165     Shifts the head of the circular linked list to the next node.
166     """
167     self._head = self._head.next
168
169     def unshift_head(self):
170     """
171     Shifts the head of the circular linked list to the previous node.
172     """
173     self._head = self._head.previous
174
175     def get_head(self):
176     """

```

```

177         Gets the head node of the circular linked list.
178
179     Returns:
180         Node: The head node.
181     """
182     return self._head

```

#### 1.4.4 Widgets

As described in Section ??, each state contains a `WIDGET_DICT` map, which contains and initialises each widget with their own attributes, and provides references to run methods on them in the state code. Each `WIDGET_DICT` is passed into a `WidgetGroup` object, which is responsible for drawing, resizing and handling all widgets for the current state. Below is a list of all the widgets I have implemented (See Section ??):

- BoardThumbnailButton
- MultipleIconButton
- ReactiveIconButton
- BoardThumbnail
- ReactiveButton
- VolumeSlider
- ColourPicker
- ColourButton
- BrowserStrip
- PieceDisplay
- BrowserItem
- TextButton
- IconButton
- ScrollArea
- Chessboard
- TextInput
- Rectangle
- MoveList
- Dropdown
- Carousel
- Switch
- Timer
- Text
- Icon
- (`_ColourDisplay`)
- (`_ColourSquare`)
- (`_ColourSlider`)
- (`_SliderThumb`)
- (`_Scrollbar`)

#### CustomEvent

The `CustomEvent` class is used to pass data between states and widgets. An event argument is passed into interactive widgets; When a widget wants to pass data back to the state, it returns the event, and adds any attributes that is required. The state then receives and handles these returned events accordingly.

`custom_event.py`

```

1 from data.utils.event_types import GameEventType, SettingsEventType,
   ConfigEventType, BrowserEventType, EditorEventType
2
3 # Required keyword arguments when creating a CustomEvent object with a specific
   EventType
4 required_args = {
5     GameEventType.BOARD_CLICK: ['coords'],
6     GameEventType.ROTATE_PIECE: ['rotation_direction'],
7     GameEventType.SET_LASER: ['laser_result'],
8     GameEventType.UPDATE_PIECES: ['move_notation'],
9     GameEventType.TIMER_END: ['active_colour'],
10    GameEventType.PIECE_DROP: ['coords', 'piece', 'colour', 'rotation', '
   remove_overlay'],
11    SettingsEventType.COLOUR_SLIDER_SLIDE: ['colour'],

```

```

12 SettingsEventType.PRIMARY_COLOUR_PICKER_CLICK: ['colour'],
13 SettingsEventType.SECONDARY_COLOUR_PICKER_CLICK: ['colour'],
14 SettingsEventType.DROPDOWN_CLICK: ['selected_word'],
15 SettingsEventType.VOLUME_SLIDER_CLICK: ['volume', 'volume_type'],
16 SettingsEventType.SHADER_PICKER_CLICK: ['data'],
17 SettingsEventType.PARTICLES_CLICK: ['toggled'],
18 SettingsEventType.OPENGL_CLICK: ['toggled'],
19 ConfigEventType.TIME_TYPE: ['time'],
20 ConfigEventType.FEN_STRING_TYPE: ['time'],
21 ConfigEventType.CPU_DEPTH_CLICK: ['data'],
22 ConfigEventType.PVC_CLICK: ['data'],
23 ConfigEventType.PRESET_CLICK: ['fen_string'],
24 BrowserEventType.BROWSER_STRIP_CLICK: ['selected_index'],
25 BrowserEventType.PAGE_CLICK: ['data'],
26 EditorEventType.PICK_PIECE_CLICK: ['piece', 'active_colour'],
27 EditorEventType.ROTATE_PIECE_CLICK: ['rotation_direction'],
28 }
29
30 class CustomEvent():
31     def __init__(self, type, **kwargs):
32         self.__dict__.update(kwargs)
33         self.type = type
34
35     @classmethod
36     def create_event(event_cls, event_type, **kwargs):
37         """
38         @classmethod Factory method used to instance CustomEvent object, to check
39         for required keyword arguments
40
41         Args:
42             event_cls (CustomEvent): Reference to own class.
43             event_type: The state EventType.
44
45         Raises:
46             ValueError: If required keyword argument for passed event type not
47             present.
48             ValueError: If keyword argument passed is not required for passed
49             event type.
50
51         Returns:
52             CustomEvent: Initialised CustomEvent instance.
53         """
54         if event_type in required_args:
55             for required_arg in required_args[event_type]:
56                 if required_arg not in kwargs:
57                     raise ValueError(f"Argument '{required_arg}' required for {
58                     event_type.name} event (GameEvent.create_event)")
59
60             for kwarg in kwargs:
61                 if kwarg not in required_args[event_type]:
62                     raise ValueError(f"Argument '{kwarg}' not included in
63                     required_args dictionary for event '{event_type}'! (GameEvent.create_event)")
64
65             return event_cls(event_type, **kwargs)
66
67         else:
68             return event_cls(event_type)

```

## ReactiveIconButton

The `ReactiveIconButton` widget is a pressable button that changes the icon displayed when it is hovered or pressed.

`reactive_icon_button.py`

```
1 from data.widgets.reactive_button import ReactiveButton
2 from data.utils.constants import WidgetState
3 from data.widgets.icon import Icon
4
5 class ReactiveIconButton(ReactiveButton):
6     def __init__(self, base_icon, hover_icon, press_icon, **kwargs):
7         # Composition is used here, to initialise the Icon widgets for each widget
8         state
9         widgets_dict = {
10             WidgetState.BASE: Icon(
11                 parent=kwargs.get('parent'),
12                 relative_size=kwargs.get('relative_size'),
13                 relative_position=(0, 0),
14                 icon=base_icon,
15                 fill_colour=(0, 0, 0, 0),
16                 border_width=0,
17                 margin=0,
18                 fit_icon=True,
19             ),
20             WidgetState.HOVER: Icon(
21                 parent=kwargs.get('parent'),
22                 relative_size=kwargs.get('relative_size'),
23                 relative_position=(0, 0),
24                 icon=hover_icon,
25                 fill_colour=(0, 0, 0, 0),
26                 border_width=0,
27                 margin=0,
28                 fit_icon=True,
29             ),
30             WidgetState.PRESS: Icon(
31                 parent=kwargs.get('parent'),
32                 relative_size=kwargs.get('relative_size'),
33                 relative_position=(0, 0),
34                 icon=press_icon,
35                 fill_colour=(0, 0, 0, 0),
36                 border_width=0,
37                 margin=0,
38                 fit_icon=True,
39             )
40         }
41
42         super().__init__(
43             widgets_dict=widgets_dict,
44             **kwargs
45         )
```

## ReactiveButton

The `ReactiveButton` widget is the parent class for `ReactiveIconButton`. It provides the methods for clicking, rotating between widget states, positioning etc.

`reactive_button.py`

```
1 from data.components.custom_event import CustomEvent
2 from data.widgets.bases.pressable import _Pressable
```



```

3 from data.widgets.bases.circular import _Circular
4 from data.widgets.bases.widget import _Widget
5 from data.utils.constants import WidgetState
6
7 class ReactiveButton(_Pressable, _Circular, _Widget):
8     def __init__(self, widgets_dict, event, center=False, **kwargs):
9         # Multiple inheritance used here, to combine the functionality of multiple
10         # super classes
11         _Pressable.__init__(
12             self,
13             event=event,
14             hover_func=lambda: self.set_to_key(WidgetState.HOVER),
15             down_func=lambda: self.set_to_key(WidgetState.PRESS),
16             up_func=lambda: self.set_to_key(WidgetState.BASE),
17             **kwargs
18         )
19         # Aggregation used to cycle between external widgets
20         _Circular.__init__(self, items_dict=widgets_dict)
21         _Widget.__init__(self, **kwargs)
22
23         self._center = center
24
25         self.initialise_new_colours(self._fill_colour)
26
27 @property
28 def position(self):
29     """
30     Overrides position getter method, to always position icon in the center if
31     self._center is True.
32
33     Returns:
34         list[int, int]: Position of widget.
35     """
36     position = super().position
37
38     if self._center:
39         self._size_diff = (self.size[0] - self.rect.width, self.size[1] - self
40 .rect.height)
41         return (position[0] + self._size_diff[0] / 2, position[1] + self.
42 _size_diff[1] / 2)
43     else:
44         return position
45
46 def set_image(self):
47     """
48     Sets current icon to image.
49     """
50     self.current_item.set_image()
51     self.image = self.current_item.image
52
53 def set_geometry(self):
54     """
55     Sets size and position of widget.
56     """
57     super().set_geometry()
58     self.current_item.set_geometry()
59     self.current_item.rect.topleft = self.rect.topleft
60
61 def set_surface_size(self, new_surface_size):
62     """
63     Overrides base method to resize every widget state icon, not just the
64     current one.

```

```

60
61     Args:
62         new_surface_size (list[int, int]): New surface size.
63     """
64     super().set_surface_size(new_surface_size)
65     for item in self._items_dict.values():
66         item.set_surface_size(new_surface_size)
67
68     def process_event(self, event):
69         """
70         Processes Pygame events.
71
72         Args:
73             event (pygame.Event): Event to process.
74
75         Returns:
76             CustomEvent: CustomEvent of current item, with current key included
77         """
78         widget_event = super().process_event(event)
79         self.current_item.process_event(event)
80
81         if widget_event:
82             return CustomEvent(**vars(widget_event), data=self.current_key)

```

## ColourSlider

The ColourSlider widget is instanced in the ColourPicker class. It provides a slider for changing between hues for the colour picker, using the functionality of the SliderThumb class.

colour\_slider.py

```

1  import pygame
2  from data.helpers.widget_helpers import create_slider_gradient
3  from data.helpers.asset_helpers import smoothscale_and_cache
4  from data.widgets.slider_thumb import _SliderThumb
5  from data.widgets.bases.widget import _Widget
6  from data.utils.constants import WidgetState
7
8  class _ColourSlider(_Widget):
9      def __init__(self, relative_width, **kwargs):
10         super().__init__(relative_size=(relative_width, relative_width * 0.2), **
11             kwargs)
12
13         # Initialise slider thumb.
14         self._thumb = _SliderThumb(radius=self.size[1] / 2, border_colour=self.
15             _border_colour)
16
17         self._selected_percent = 0
18         self._last_mouse_x = None
19
20         self._gradient_surface = create_slider_gradient(self.gradient_size, self.
21             border_width, self._border_colour)
22         self._empty_surface = pygame.Surface(self.size, pygame.SRCALPHA)
23
24     @property
25     def gradient_size(self):
26         return (self.size[0] - 2 * (self.size[1] / 2), self.size[1] / 2)
27
28     @property
29     def gradient_position(self):
30         return (self.size[1] / 2, self.size[1] / 4)

```

```

29 @property
30 def thumb_position(self):
31     return (self.gradient_size[0] * self._selected_percent, 0)
32
33 @property
34 def selected_colour(self):
35     colour = pygame.Color(0)
36     colour.hsva = (int(self._selected_percent * 360), 100, 100, 100)
37     return colour
38
39 def calculate_gradient_percent(self, mouse_pos):
40     """
41     Calculate what percentage slider thumb is at based on change in mouse
42     position.
43
44     Args:
45         mouse_pos (list[int, int]): Position of mouse on window screen.
46
47     Returns:
48         float: Slider scroll percentage.
49     """
50     if self._last_mouse_x is None:
51         return
52
53     x_change = (mouse_pos[0] - self._last_mouse_x) / (self.gradient_size[0] -
54 2 * self.border_width)
55     return max(0, min(self._selected_percent + x_change, 1))
56
57 def relative_to_global_position(self, position):
58     """
59     Transforms position from being relative to widget rect, to window screen.
60
61     Args:
62         position (list[int, int]): Position relative to widget rect.
63
64     Returns:
65         list[int, int]: Position relative to window screen.
66     """
67     relative_x, relative_y = position
68     return (relative_x + self.position[0], relative_y + self.position[1])
69
70 def set_colour(self, new_colour):
71     """
72     Sets selected_percent based on the new colour's hue.
73
74     Args:
75         new_colour (pygame.Color): New slider colour.
76     """
77     colour = pygame.Color(new_colour)
78     hue = colour.hsva[0]
79     self._selected_percent = hue / 360
80     self.set_image()
81
82 def set_image(self):
83     """
84     Draws colour slider to widget image.
85     """
86     # Scales initialised gradient surface instead of redrawing it everytime
87     # set_image is called
88     gradient_scaled = smoothscale_and_cache(self._gradient_surface, self.
89 gradient_size)

```

```

87         self.image = pygame.transform.scale(self._empty_surface, (self.size))
88         self.image.blit(gradient_scaled, self.gradient_position)
89
90         # Resets thumb colour, image and position, then draws it to the widget
91         image
92         self._thumb.initialise_new_colours(self.selected_colour)
93         self._thumb.set_surface(radius=self.size[1] / 2, border_width=self.
94         border_width)
95         self._thumb.set_position(self.relative_to_global_position((self.
96         thumb_position[0], self.thumb_position[1])))
97
98         thumb_surface = self._thumb.get_surface()
99         self.image.blit(thumb_surface, self.thumb_position)
100
101     def process_event(self, event):
102         """
103         Processes Pygame events.
104
105         Args:
106             event (pygame.Event): Event to process.
107
108         Returns:
109             pygame.Color: Current colour slider is displaying.
110         """
111         if event.type not in [pygame.MOUSEMOTION, pygame.MOUSEBUTTONDOWN, pygame.
112         MOUSEBUTTONUP]:
113             return
114
115         # Gets widget state before and after event is processed by slider thumb
116         before_state = self._thumb.state
117         self._thumb.process_event(event)
118         after_state = self._thumb.state
119
120         # If widget state changes (e.g. hovered -> pressed), redraw widget
121         if before_state != after_state:
122             self.set_image()
123
124         if event.type == pygame.MOUSEMOTION:
125             if self._thumb.state == WidgetState.PRESS:
126                 # Recalculates slider colour based on mouse position change
127                 selected_percent = self.calculate_gradient_percent(event.pos)
128                 self._last_mouse_x = event.pos[0]
129
130                 if selected_percent is not None:
131                     self._selected_percent = selected_percent
132
133                 return self.selected_colour
134
135         if event.type == pygame.MOUSEBUTTONUP:
136             # When user stops scrolling, return new slider colour
137             self._last_mouse_x = None
138             return self.selected_colour
139
140         if event.type == pygame.MOUSEBUTTONDOWN or before_state != after_state:
141             # Redraws widget when slider thumb is hovered or pressed
142             return self.selected_colour

```

## TextInput

The TextInput widget is used for inputting fen strings and time controls.

## text\_input.py

```
1 import pyperclip
2 import pygame
3 from data.utils.constants import WidgetState, INPUT_COLOURS
4 from data.components.custom_event import CustomEvent
5 from data.widgets.bases.pressable import _Pressable
6 from data.managers.logs import initialise_logger
7 from data.managers.animation import animation
8 from data.widgets.bases.box import _Box
9 from data.utils.enums import CursorMode
10 from data.managers.cursor import cursor
11 from data.managers.theme import theme
12 from data.widgets.text import Text
13
14 logger = initialise_logger(__name__)
15
16 class TextInput(_Box, _Pressable, Text):
17     def __init__(self, event, blinking_interval=530, validator=(lambda x: True),
18                 default='', placeholder='PLACEHOLDER TEXT', placeholder_colour=(200, 200, 200),
19                 cursor_colour=theme['textSecondary'], **kwargs):
20         self._cursor_index = None
21         # Multiple inheritance used here, adding the functionality of pressing,
22         # and custom box colours, to the text widget
23         _Box.__init__(self, box_colours=INPUT_COLOURS)
24         _Pressable.__init__(
25             self,
26             event=None,
27             hover_func=lambda: self.set_state_colour(WidgetState.HOVER),
28             down_func=lambda: self.set_state_colour(WidgetState.PRESS),
29             up_func=lambda: self.set_state_colour(WidgetState.BASE),
30             sfx=None
31         )
32         Text.__init__(self, text="", center=False, box_colours=INPUT_COLOURS[
33             WidgetState.BASE], **kwargs)
34
35         self.initialise_new_colours(self._fill_colour)
36         self.set_state_colour(WidgetState.BASE)
37
38         pygame.key.set_repeat(500, 50)
39
40         self._blinking_fps = 1000 / blinking_interval
41         self._cursor_colour = cursor_colour
42         self._cursor_colour_copy = cursor_colour
43         self._placeholder_colour = placeholder_colour
44         self._text_colour_copy = self._text_colour
45
46         self._placeholder_text = placeholder
47         self._is_placeholder = None
48         if default:
49             self._text = default
50             self.is_placeholder = False
51         else:
52             self._text = self._placeholder_text
53             self.is_placeholder = True
54
55         self._event = event
56         self._validator = validator
57         self._blinking_cooldown = 0
58
59         self._empty_cursor = pygame.Surface((0, 0), pygame.SRCALPHA)
```

```

57         self.resize_text()
58         self.set_image()
59         self.set_geometry()
60
61     @property
62     # Encapsulated getter method
63     def is_placeholder(self):
64         return self._is_placeholder
65
66     @is_placeholder.setter
67     # Encapsulated setter method, used to replace text colour if placeholder text
68     # is shown
69     def is_placeholder(self, is_true):
70         self._is_placeholder = is_true
71
72         if is_true:
73             self._text_colour = self._placeholder_colour
74         else:
75             self._text_colour = self._text_colour_copy
76
77     @property
78     def cursor_size(self):
79         cursor_height = (self.size[1] - self.border_width * 2) * 0.75
80         return (cursor_height * 0.1, cursor_height)
81
82     @property
83     def cursor_position(self):
84         current_width = (self.margin / 2)
85         for index, metrics in enumerate(self._font.get_metrics(self._text, size=
86 self.font_size)):
87             if index == self._cursor_index:
88                 return (current_width - self.cursor_size[0], (self.size[1] - self.
89 cursor_size[1]) / 2)
90
91             glyph_width = metrics[4]
92             current_width += glyph_width
93         return (current_width - self.cursor_size[0], (self.size[1] - self.
94 cursor_size[1]) / 2)
95
96     @property
97     def text(self):
98         if self.is_placeholder:
99             return ''
100
101         return self._text
102
103     def relative_x_to_cursor_index(self, relative_x):
104         """
105         Calculates cursor index using mouse position relative to the widget
106         position.
107
108         Args:
109             relative_x (int): Horizontal distance of the mouse from the left side
110             of the widget.
111
112         Returns:
113             int: Cursor index.
114         """
115         current_width = 0
116
117         for index, metrics in enumerate(self._font.get_metrics(self._text, size=
118 self.font_size)):

```

```

112         glyph_width = metrics[4]
113
114         if current_width >= relative_x:
115             return index
116
117         current_width += glyph_width
118
119     return len(self._text)
120
121 def set_cursor_index(self, mouse_pos):
122     """
123     Sets cursor index based on mouse position.
124
125     Args:
126         mouse_pos (list[int, int]): Mouse position relative to window screen.
127     """
128     if mouse_pos is None:
129         self._cursor_index = mouse_pos
130         return
131
132     relative_x = mouse_pos[0] - (self.margin / 2) - self.rect.left
133     relative_x = max(0, relative_x)
134     self._cursor_index = self.relative_x_to_cursor_index(relative_x)
135
136 def focus_input(self, mouse_pos):
137     """
138     Draws cursor and sets cursor index when user clicks on widget.
139
140     Args:
141         mouse_pos (list[int, int]): Mouse position relative to window screen.
142     """
143     if self.is_placeholder:
144         self._text = ''
145         self.is_placeholder = False
146
147     self.set_cursor_index(mouse_pos)
148     self.set_image()
149     cursor.set_mode(CursorMode.IBEAM)
150
151 def unfocus_input(self):
152     """
153     Removes cursor when user unselects widget.
154     """
155     if self._text == '':
156         self._text = self._placeholder_text
157         self.is_placeholder = True
158         self.resize_text()
159
160     self.set_cursor_index(None)
161     self.set_image()
162     cursor.set_mode(CursorMode.ARROW)
163
164 def set_text(self, new_text):
165     """
166     Called by a state object to change the widget text externally.
167
168     Args:
169         new_text (str): New text to display.
170
171     Returns:
172         CustomEvent: Object containing the new text to alert state of a text
173         update.

```

```

173         """
174         super().set_text(new_text)
175         return CustomEvent(**vars(self._event), text=self.text)
176
177     def process_event(self, event):
178         """
179         Processes Pygame events.
180
181         Args:
182             event (pygame.Event): Event to process.
183
184         Returns:
185             CustomEvent: Object containing the new text to alert state of a text
186 update.
187         """
188         previous_state = self.get_widget_state()
189         super().process_event(event)
190         current_state = self.get_widget_state()
191
192         match event.type:
193             case pygame.MOUSEMOTION:
194                 if self._cursor_index is None:
195                     return
196
197             # If mouse is hovering over widget, turn mouse cursor into an I-
198 beam
199             if self.rect.collidepoint(event.pos):
200                 if cursor.get_mode() != CursorMode.IBEAM:
201                     cursor.set_mode(CursorMode.IBEAM)
202             else:
203                 if cursor.get_mode() == CursorMode.IBEAM:
204                     cursor.set_mode(CursorMode.ARROW)
205
206             return
207
208             case pygame.MOUSEBUTTONDOWN:
209                 # When user selects widget
210                 if previous_state == WidgetState.PRESS:
211                     self.focus_input(event.pos)
212                 # When user unselects widget
213                 if current_state == WidgetState.BASE and self._cursor_index is not
214 None:
215                     self.unfocus_input()
216                     return CustomEvent(**vars(self._event), text=self.text)
217
218             case pygame.KEYDOWN:
219                 if self._cursor_index is None:
220                     return
221
222                 # Handling Ctrl-C and Ctrl-V shortcuts
223                 if event.mod & (pygame.KMOD_CTRL):
224                     if event.key == pygame.K_c:
225                         pyperclip.copy(self.text)
226                         logger.info(f'COPIED {self.text}')
227
228                     elif event.key == pygame.K_v:
229                         pasted_text = pyperclip.paste()
230                         pasted_text = ''.join(char for char in pasted_text if 32
231 <= ord(char) <= 127)
232                         self._text = self._text[:self._cursor_index] + pasted_text
233                         + self._text[self._cursor_index:]
234                         self._cursor_index += len(pasted_text)

```



```

230
231         elif event.key == pygame.K_BACKSPACE or event.key == pygame.
K_DELETE:
232             self._text = ''
233             self._cursor_index = 0
234
235             self.resize_text()
236             self.set_image()
237             self.set_geometry()
238
239             return
240
241         match event.key:
242             case pygame.K_BACKSPACE:
243                 if self._cursor_index > 0:
244                     self._text = self._text[:self._cursor_index - 1] +
self._text[self._cursor_index:]
245                     self._cursor_index = max(0, self._cursor_index - 1)
246
247             case pygame.K_RIGHT:
248                 self._cursor_index = min(len(self._text), self.
_cursor_index + 1)
249
250             case pygame.K_LEFT:
251                 self._cursor_index = max(0, self._cursor_index - 1)
252
253             case pygame.K_ESCAPE:
254                 self.unfocus_input()
255                 return CustomEvent(**vars(self._event), text=self.text)
256
257             case pygame.K_RETURN:
258                 self.unfocus_input()
259                 return CustomEvent(**vars(self._event), text=self.text)
260
261             case _:
262                 if not event.unicode:
263                     return
264
265                 potential_text = self._text[:self._cursor_index] + event.
unicode + self._text[self._cursor_index:]
266
267                 # Validator lambda function used to check if inputted text
is valid before displaying
268                 # e.g. Time control input has a validator function
checking if text represents a float
269                 if self._validator(potential_text) is False:
270                     return
271
272                 self._text = potential_text
273                 self._cursor_index += 1
274
275                 self._blinking_cooldown += 1
276                 animation.set_timer(500, lambda: self.subtract_blinking_cooldown
(1))
277
278                 self.resize_text()
279                 self.set_image()
280                 self.set_geometry()
281
282         def subtract_blinking_cooldown(self, cooldown):
283             """
284             Subtracts blinking cooldown after certain timeframe. When

```

```

285     blinking_cooldown is 1, cursor is able to be drawn.
286     Args:
287         cooldown (float): Duration before cursor can no longer be drawn.
288     """
289     self._blinking_cooldown = self._blinking_cooldown - cooldown
290
291     def set_image(self):
292         """
293         Draws text input widget to image.
294         """
295         super().set_image()
296
297         if self._cursor_index is not None:
298             scaled_cursor = pygame.transform.scale(self._empty_cursor, self.
299 cursor_size)
300             scaled_cursor.fill(self._cursor_colour)
301             self.image.blit(scaled_cursor, self.cursor_position)
302
303     def update(self):
304         """
305         Overrides based update method, to handle cursor blinking.
306         """
307         super().update()
308         # Calculate if cursor should be shown or not
309         cursor_frame = animation.calculate_frame_index(0, 2, self._blinking_fps)
310         if cursor_frame == 1 and self._blinking_cooldown == 0:
311             self._cursor_colour = (0, 0, 0, 0)
312         else:
313             self._cursor_colour = self._cursor_colour_copy
314         self.set_image()

```

## 1.5 Game

### 1.5.1 Model

As described in Section ??, this is the model class for my implementation of a **MVC architecture** for the game screen. It is responsible for processing user inputs through the game controller, processing the board and CPU, and sending information through the view class.

game\_model.py

```

1 from random import getrandbits
2 from data.states.game.components.fen_parser import encode_fen_string
3 from data.states.game.widget_dict import GAME_WIDGETS
4 from data.states.game.cpu.cpu_thread import CPUThread
5 from data.components.custom_event import CustomEvent
6 from data.helpers.bitboard_helpers import is_occupied
7 from data.helpers import input_helpers as ip_helpers
8 from data.states.game.components.board import Board
9 from data.states.game.components.move import Move
10 from data.utils.event_types import GameEventType
11 from data.managers.logs import initialise_logger
12 from data.managers.animation import animation
13 from data.states.game.cpu.engines import *
14 from data.utils.constants import EMPTY_BB
15 from data.utils.enums import Colour
16
17 logger = initialise_logger(__name__)
18

```

```

19 CPU_LIMIT_MS = 15000
20
21 class GameModel:
22     def __init__(self, game_config):
23         self._listeners = {
24             'game': [],
25             'win': [],
26             'pause': [],
27         }
28         self.states = {
29             'CPU_ENABLED': game_config['CPU_ENABLED'],
30             'CPU_DEPTH': game_config['CPU_DEPTH'],
31             'AWAITING_CPU': False,
32             'WINNER': None,
33             'PAUSED': False,
34             'ACTIVE_COLOUR': game_config['COLOUR'],
35             'TIME_ENABLED': game_config['TIME_ENABLED'],
36             'TIME': game_config['TIME'],
37             'START_FEN_STRING': game_config['FEN_STRING'],
38             'MOVES': [],
39             'ZOBRIST_KEYS': []
40         }
41
42         self._board = Board(fen_string=game_config['FEN_STRING'])
43
44         self._cpu = IDMinimaxCPU(self.states['CPU_DEPTH'], self.cpu_callback,
45 verbose=False)
46         self._cpu_thread = CPUThread(self._cpu)
47         self._cpu_thread.start()
48         self._cpu_move = None
49
50         logger.info(f'Initialising CPU depth of {self.states['CPU_DEPTH']}')
51
52     def register_listener(self, listener, parent_class):
53         """
54         Registers listener method of another MVC class.
55
56         Args:
57             listener (callable): Listener callback function.
58             parent_class (str): Class name.
59         """
60         self._listeners[parent_class].append(listener)
61
62     def alert_listeners(self, event):
63         """
64         Alerts all registered classes of an event by calling their listener
65         function.
66
67         Args:
68             event (GameEventType): Event to pass as argument.
69
70         Raises:
71             Exception: If an unrecognised event tries to be passed onto listeners.
72         """
73         for parent_class, listeners in self._listeners.items():
74             match event.type:
75                 case GameEventType.UPDATE_PIECES:
76                     if parent_class in 'game':
77                         for listener in listeners: listener(event)
78
79                 case GameEventType.SET_LASER:
80                     if parent_class == 'game':

```

```

79         for listener in listeners: listener(event)
80
81     case GameEventType.PAUSE_CLICK:
82         if parent_class in ['pause', 'game']:
83             for listener in listeners:
84                 listener(event)
85
86     case _:
87         raise Exception('Unhandled event type (GameModel.
alert_listeners)')
88
89 def set_winner(self, colour=None):
90     """
91     Sets winner.
92
93     Args:
94         colour (Colour, optional): Describes winnner colour, or draw. Defaults
to None.
95     """
96     self.states['WINNER'] = colour
97
98 def toggle_paused(self):
99     """
100     Toggles pause screen, and alerts pause view.
101     """
102     self.states['PAUSED'] = not self.states['PAUSED']
103     game_event = CustomEvent.create_event(GameEventType.PAUSE_CLICK)
104     self.alert_listeners(game_event)
105
106 def get_terminal_move(self):
107     """
108     Debugging method for inputting a move from the terminal.
109
110     Returns:
111         Move: Parsed move.
112     """
113     while True:
114         try:
115             move_type = ip_helpers.parse_move_type(input('Input move type (m/r
): '))
116             src_square = ip_helpers.parse_notation(input("From: "))
117             dest_square = ip_helpers.parse_notation(input("To: "))
118             rotation = ip_helpers.parse_rotation(input("Enter rotation (a/b/c/
d): "))
119             return Move.instance_from_notation(move_type, src_square,
dest_square, rotation)
120         except ValueError as error:
121             logger.warning('Input error (Board.get_move): ' + str(error))
122
123 def make_move(self, move):
124     """
125     Takes a Move object and applies it to the board.
126
127     Args:
128         move (Move): Move to apply.
129     """
130     colour = self._board.bitboards.get_colour_on(move.src)
131     piece = self._board.bitboards.get_piece_on(move.src, colour)
132     # Apply move and get results of laser trajectory
133     laser_result = self._board.apply_move(move, add_hash=True)
134
135     self.alert_listeners(CustomEvent.create_event(GameEventType.SET_LASER,

```

```

136         laser_result=laser_result))
137
138     # Sets new active colour and checks for a win
139     self.states['ACTIVE_COLOUR'] = self._board.get_active_colour()
140     self.set_winner(self._board.check_win())
141
142     move_notation = move.to_notation(colour, piece, laser_result.
143 hit_square_bitboard)
144
145     self.alert_listeners(CustomEvent.create_event(GameEventType.UPDATE_PIECES,
146 move_notation=move_notation))
147
148     # Adds move to move history list for review screen
149     self.states['MOVES'].append({
150         'time': {
151             Colour.BLUE: GAME_WIDGETS['blue_timer'].get_time(),
152             Colour.RED: GAME_WIDGETS['red_timer'].get_time()
153         },
154         'move': move_notation,
155         'laserResult': laser_result
156     })
157
158 def make_cpu_move(self):
159     """
160     Starts CPU calculations on the separate thread.
161     """
162     self.states['AWAITING_CPU'] = True
163
164     # Employ time management system to kill search if using an iterative
165     # deepening CPU
166     if isinstance(self._cpu, IDMinimaxCPU):
167         move_id = getrandbits(32)
168         self._cpu_thread.start_cpu(self.get_board(), id=move_id)
169         animation.set_timer(CPU_LIMIT_MS, lambda: self._cpu_thread.stop_cpu(id
170 =move_id))
171     else:
172         self._cpu_thread.start_cpu(self.get_board())
173
174 def cpu_callback(self, move):
175     """
176     Callback function passed to CPU thread. Called when CPU stops processing.
177
178     Args:
179         move (Move): Move that CPU found.
180     """
181     if self.states['WINNER'] is None:
182         # CPU move passed back to main thread by reassigning variable
183         self._cpu_move = move
184         self.states['AWAITING_CPU'] = False
185
186 def check_cpu(self):
187     """
188     Constantly checks if CPU calculations are finished, so that make_move can
189     be run on the main thread.
190     """
191     if self._cpu_move is not None:
192         self.make_move(self._cpu_move)
193         self._cpu_move = None
194
195 def kill_thread(self):
196     """
197     Interrupt and kill CPU thread.

```

```

192         """
193         self._cpu_thread.kill_thread()
194         self.states['AWAITING_CPU'] = False
195
196     def is_selectable(self, bitboard):
197         """
198         Checks if square is occupied by a piece of the current active colour.
199
200         Args:
201             bitboard (int): Bitboard representing single square.
202
203         Returns:
204             bool: True if square is occupied by a piece of the current active
205             colour. False if not.
206         """
207         return is_occupied(self._board.bitboards.combined_colour_bitboards[self.
208             states['ACTIVE_COLOUR']], bitboard)
209
210     def get_available_moves(self, bitboard):
211         """
212         Gets all surrounding empty squares. Used for drawing overlay.
213
214         Args:
215             bitboard (int): Bitboard representing single center square.
216
217         Returns:
218             int: Bitboard representing all empty surrounding squares.
219         """
220         if (bitboard & self._board.get_all_active_pieces()) != EMPTY_BB:
221             return self._board.get_valid_squares(bitboard)
222
223         return EMPTY_BB
224
225     def get_piece_list(self):
226         """
227         Returns:
228             list[Piece, ...]: Array of all pieces on the board.
229         """
230         return self._board.get_piece_list()
231
232     def get_piece_info(self, bitboard):
233         """
234         Args:
235             bitboard (int): Square containing piece.
236
237         Returns:
238             tuple[Colour, Rotation, Piece]: Piece information.
239         """
240         colour = self._board.bitboards.get_colour_on(bitboard)
241         rotation = self._board.bitboards.get_rotation_on(bitboard)
242         piece = self._board.bitboards.get_piece_on(bitboard, colour)
243         return (piece, colour, rotation)
244
245     def get_fen_string(self):
246         return encode_fen_string(self._board.bitboards)
247
248     def get_board(self):
249         return self._board

```

## 1.5.2 View

As described in Section ??, the view class is responsible for displaying changes to information regarding the gameplay. The `process_model_event` procedure is registered with the model class, which executes it whenever the display needs to be updated (e.g. piece move), and the appropriate handling function within the view class is called by mapping the event type to the corresponding handler function.

`game_view.py`

```
1 import pygame
2 from data.utils.enums import Colour, StatusText, Miscellaneous, ShaderType
3 from data.states.game.components.overlay_draw import OverlayDraw
4 from data.states.game.components.capture_draw import CaptureDraw
5 from data.states.game.components.piece_group import PieceGroup
6 from data.states.game.components.laser_draw import LaserDraw
7 from data.states.game.components.father import DragAndDrop
8 from data.helpers.bitboard_helpers import bitboard_to_coords
9 from data.helpers.board_helpers import screen_pos_to_coords
10 from data.states.game.widget_dict import GAME_WIDGETS
11 from data.components.custom_event import CustomEvent
12 from data.components.widget_group import WidgetGroup
13 from data.utils.event_types import GameEventType
14 from data.managers.window import window
15 from data.managers.audio import audio
16 from data.utils.assets import SFX
17
18 class GameView:
19     def __init__(self, model):
20         self._model = model
21         self._hide_pieces = False
22         self._selected_coords = None
23         self._event_to_func_map = {
24             GameEventType.UPDATE_PIECES: self.handle_update_pieces,
25             GameEventType.SET_LASER: self.handle_set_laser,
26             GameEventType.PAUSE_CLICK: self.handle_pause,
27         }
28
29         # Register model event handling with process_model_event()
30         self._model.register_listener(self.process_model_event, 'game')
31
32         # Initialise WidgetGroup with map of widgets
33         self._widget_group = WidgetGroup(GAME_WIDGETS)
34         self._widget_group.handle_resize(window.size)
35         self.initialise_widgets()
36
37         self._laser_draw = LaserDraw(self.board_position, self.board_size)
38         self._overlay_draw = OverlayDraw(self.board_position, self.board_size)
39         self._drag_and_drop = DragAndDrop(self.board_position, self.board_size)
40         self._capture_draw = CaptureDraw(self.board_position, self.board_size)
41         self._piece_group = PieceGroup()
42         self.handle_update_pieces()
43
44         self.set_status_text(StatusText.PLAYER_MOVE)
45
46     @property
47     def board_position(self):
48         return GAME_WIDGETS['chessboard'].position
49
50     @property
51     def board_size(self):
52         return GAME_WIDGETS['chessboard'].size
```

```

53
54 @property
55 def square_size(self):
56     return self.board_size[0] / 10
57
58 def initialise_widgets(self):
59     """
60     Run methods on widgets stored in GAME_WIDGETS dictionary to reset them.
61     """
62     GAME_WIDGETS['move_list'].reset_move_list()
63     GAME_WIDGETS['move_list'].kill()
64     GAME_WIDGETS['help'].kill()
65     GAME_WIDGETS['tutorial'].kill()
66
67     GAME_WIDGETS['scroll_area'].set_image()
68
69     GAME_WIDGETS['chessboard'].refresh_board()
70
71     GAME_WIDGETS['blue_piece_display'].reset_piece_list()
72     GAME_WIDGETS['red_piece_display'].reset_piece_list()
73
74 def set_status_text(self, status):
75     """
76     Sets text on status text widget.
77
78     Args:
79         status (StatusText): The game stage for which text should be displayed
80     for.
81     """
82     match status:
83         case StatusText.PLAYER_MOVE:
84             GAME_WIDGETS['status_text'].set_text(f"{self._model.states['
ACTIVE_COLOUR'].name}'s turn to move")
85         case StatusText.CPU_MOVE:
86             GAME_WIDGETS['status_text'].set_text("CPU calculating a crazy move
...")
87         case StatusText.WIN:
88             if self._model.states['WINNER'] == Miscellaneous.DRAW:
89                 GAME_WIDGETS['status_text'].set_text("Game is a draw! Boring
...")
90             else:
91                 GAME_WIDGETS['status_text'].set_text(f"{self._model.states['
WINNER'].name} won!")
92         case StatusText.DRAW:
93             GAME_WIDGETS['status_text'].set_text("Game is a draw! Boring...")
94
95 def handle_resize(self):
96     """
97     Handles resizing of the window.
98     """
99     self._overlay_draw.handle_resize(self.board_position, self.board_size)
100     self._capture_draw.handle_resize(self.board_position, self.board_size)
101     self._piece_group.handle_resize(self.board_position, self.board_size)
102     self._laser_draw.handle_resize(self.board_position, self.board_size)
103     self._laser_draw.handle_resize(self.board_position, self.board_size)
104     self._widget_group.handle_resize(window.size)
105
106     if self._laser_draw.firing:
107         self.update_laser_mask()
108
109 def handle_update_pieces(self, event=None):
110     """

```



```

110         Callback function to update pieces after move.
111
112     Args:
113         event (GameEventType, optional): If updating pieces after player move,
114         event contains move information. Defaults to None.
115         toggle_timers (bool, optional): Toggle timers on and off for new
116         active colour. Defaults to True.
117     """
118     piece_list = self._model.get_piece_list()
119     self._piece_group.initialise_pieces(piece_list, self.board_position, self.
120     board_size)
121
122     if event:
123         GAME_WIDGETS['move_list'].append_to_move_list(event.move_notation)
124         GAME_WIDGETS['scroll_area'].set_image()
125         audio.play_sfx(SFX['piece_move'])
126
127     if self._model.states['ACTIVE_COLOUR'] == Colour.BLUE:
128         self.set_status_text(StatusText.PLAYER_MOVE)
129     elif self._model.states['CPU_ENABLED'] is False:
130         self.set_status_text(StatusText.PLAYER_MOVE)
131     else:
132         self.set_status_text(StatusText.CPU_MOVE)
133
134     if self._model.states['TIME_ENABLED']:
135         self.toggle_timer(self._model.states['ACTIVE_COLOUR'], True)
136         self.toggle_timer(self._model.states['ACTIVE_COLOUR'].
137         get_flipped_colour(), False)
138
139     if self._model.states['WINNER'] is not None:
140         self.handle_game_end()
141
142     def handle_game_end(self, play_sfx=True):
143         self.toggle_timer(self._model.states['ACTIVE_COLOUR'], False)
144         self.toggle_timer(self._model.states['ACTIVE_COLOUR'].get_flipped_colour()
145         , False)
146
147     if self._model.states['WINNER'] == Miscellaneous.DRAW:
148         self.set_status_text(StatusText.DRAW)
149     else:
150         self.set_status_text(StatusText.WIN)
151
152     if play_sfx:
153         audio.play_sfx(SFX['sphinx_destroy_1'])
154         audio.play_sfx(SFX['sphinx_destroy_2'])
155         audio.play_sfx(SFX['sphinx_destroy_3'])
156
157     def handle_set_laser(self, event):
158         """
159         Callback function to draw laser after move.
160
161         Args:
162             event (GameEventType): Contains laser trajectory information.
163         """
164         laser_result = event.laser_result
165
166         # If laser has hit a piece
167         if laser_result.hit_square_bitboard:
168             coords_to_remove = bitboard_to_coords(laser_result.hit_square_bitboard
169             )
170
171             self._piece_group.remove_piece(coords_to_remove)

```

```

166         if laser_result.piece_colour == Colour.BLUE:
167             GAME_WIDGETS['red_piece_display'].add_piece(laser_result.piece_hit
168     )
169         elif laser_result.piece_colour == Colour.RED:
170             GAME_WIDGETS['blue_piece_display'].add_piece(laser_result.
171     piece_hit)
172
173     # Draw piece capture GFX
174     self._capture_draw.add_capture(
175         laser_result.piece_hit,
176         laser_result.piece_colour,
177         laser_result.piece_rotation,
178         coords_to_remove,
179         laser_result.laser_path[0][0],
180         self._model.states['ACTIVE_COLOUR']
181     )
182
183     self._laser_draw.add_laser(laser_result, self._model.states['ACTIVE_COLOUR
184     '])
185     self.update_laser_mask()
186
187     def handle_pause(self, event=None):
188         """
189         Callback function for pausing timer.
190
191         Args:
192             event (None): Event argument not used.
193         """
194         is_active = not(self._model.states['PAUSED'])
195         self.toggle_timer(self._model.states['ACTIVE_COLOUR'], is_active)
196
197     def initialise_timers(self):
198         """
199         Initialises both timers with the correct amount of time and starts the
200         timer for the active colour.
201         """
202         if self._model.states['TIME_ENABLED']:
203             GAME_WIDGETS['blue_timer'].set_time(self._model.states['TIME'] * 60 *
204     1000)
205             GAME_WIDGETS['red_timer'].set_time(self._model.states['TIME'] * 60 *
206     1000)
207         else:
208             GAME_WIDGETS['blue_timer'].kill()
209             GAME_WIDGETS['red_timer'].kill()
210
211         self.toggle_timer(self._model.states['ACTIVE_COLOUR'], True)
212
213     def toggle_timer(self, colour, is_active):
214         """
215         Stops or resumes timer.
216
217         Args:
218             colour (Colour): Timer to toggle.
219             is_active (bool): Whether to pause or resume timer.
220         """
221         if colour == Colour.BLUE:
222             GAME_WIDGETS['blue_timer'].set_active(is_active)
223         elif colour == Colour.RED:
224             GAME_WIDGETS['red_timer'].set_active(is_active)
225
226     def update_laser_mask(self):
227         """

```

```

222     Uses pygame.mask to create a mask for the pieces.
223     Used for occluding the ray shader.
224     """
225     temp_surface = pygame.Surface(window.size, pygame.SRCALPHA)
226     self._piece_group.draw(temp_surface)
227     mask = pygame.mask.from_surface(temp_surface, threshold=127)
228     mask_surface = mask.to_surface(unsetcolor=(0, 0, 0, 255), setcolor=(255,
0, 0, 255))
229
230     window.set_apply_arguments(ShaderType.RAYS, occlusion=mask_surface)
231
232     def draw(self):
233         """
234         Draws GUI and pieces onto the screen.
235         """
236         self._widget_group.update()
237         self._capture_draw.update()
238
239         self._widget_group.draw()
240         self._overlay_draw.draw(window.screen)
241
242         if self._hide_pieces is False:
243             self._piece_group.draw(window.screen)
244
245         self._laser_draw.draw(window.screen)
246         self._drag_and_drop.draw(window.screen)
247         self._capture_draw.draw(window.screen)
248
249     def process_model_event(self, event):
250         """
251         Registered listener function for handling GameModel events.
252         Each event is mapped to a callback function, and the appropriate one is run
253         .
254
255         Args:
256             event (GameEventType): Game event to process.
257
258         Raises:
259             KeyError: If an unrecognised event type is passed as the argument.
260         """
261         try:
262             self._event_to_func_map.get(event.type)(event)
263         except:
264             raise KeyError('Event type not recognized in Game View (GameView.
process_model_event):', event.type)
265
266     def set_overlay_coords(self, available_coords_list, selected_coord):
267         """
268         Set board coordinates for potential moves overlay.
269
270         Args:
271             available_coords_list (list[tuple[int, int]], ...): Array of
coordinates
272             selected_coord (list[int, int]): Coordinates of selected piece.
273         """
274         self._selected_coords = selected_coord
275         self._overlay_draw.set_selected_coords(selected_coord)
276         self._overlay_draw.set_available_coords(available_coords_list)
277
278     def get_selected_coords(self):
279         return self._selected_coords

```

```

280 def set_dragged_piece(self, piece, colour, rotation):
281     """
282     Passes information of the dragged piece to the dragging drawing class.
283
284     Args:
285         piece (Piece): Piece type of dragged piece.
286         colour (Colour): Colour of dragged piece.
287         rotation (Rotation): Rotation of dragged piece.
288     """
289     self._drag_and_drop.set_dragged_piece(piece, colour, rotation)
290
291 def remove_dragged_piece(self):
292     """
293     Stops drawing dragged piece when user lets go of piece.
294     """
295     self._drag_and_drop.remove_dragged_piece()
296
297 def convert_mouse_pos(self, event):
298     """
299     Passes information of what mouse cursor is interacting with to a
    GameController object.
300
301     Args:
302         event (pygame.Event): Mouse event to process.
303
304     Returns:
305         CustomEvent | None: Contains information what mouse is doing.
306     """
307     clicked_coords = screen_pos_to_coords(event.pos, self.board_position, self
    .board_size)
308
309     if event.type == pygame.MOUSEBUTTONDOWN:
310         if clicked_coords:
311             return CustomEvent.create_event(GameEventType.BOARD_CLICK, coords=
    clicked_coords)
312
313         else:
314             return None
315
316     elif event.type == pygame.MOUSEBUTTONUP:
317         if self._drag_and_drop.dragged_sprite:
318             piece, colour, rotation = self._drag_and_drop.get_dragged_info()
319             piece_dragged = self._drag_and_drop.remove_dragged_piece()
320             return CustomEvent.create_event(GameEventType.PIECE_DROP, coords=
    clicked_coords, piece=piece, colour=colour, rotation=rotation, remove_overlay=
    piece_dragged)
321
322 def add_help_screen(self):
323     """
324     Draw help overlay when player clicks on the help button.
325     """
326     self._widget_group.add(GAME_WIDGETS['help'])
327     self._widget_group.handle_resize(window.size)
328
329 def add_tutorial_screen(self):
330     """
331     Draw tutorial overlay when player clicks on the tutorial button.
332     """
333     self._widget_group.add(GAME_WIDGETS['tutorial'])
334     self._widget_group.handle_resize(window.size)
335     self._hide_pieces = True
336

```

```

337     def remove_help_screen(self):
338         GAME_WIDGETS['help'].kill()
339
340     def remove_tutorial_screen(self):
341         GAME_WIDGETS['tutorial'].kill()
342         self._hide_pieces = False
343
344     def process_widget_event(self, event):
345         """
346         Passes Pygame event to WidgetGroup to allow individual widgets to process
347         events.
348
349         Args:
350             event (pygame.Event): Event to process.
351
352         Returns:
353             CustomEvent | None: A widget event.
354         """
355         return self._widget_group.process_event(event)

```

### 1.5.3 Controller

As described in Section ??, the controller class is responsible for receiving external input through Pygame events, and processing them via the model and view classes.

game\_controller.py

```

1  import pygame
2  from data.helpers import bitboard_helpers as bb_helpers
3  from data.utils.enums import MoveType, Miscellaneous
4  from data.states.game.components.move import Move
5  from data.utils.event_types import GameEventType
6  from data.managers.logs import initialise_logger
7
8  logger = initialise_logger(__name__)
9
10 class GameController:
11     def __init__(self, model, view, win_view, pause_view, to_menu, to_review,
12                 to_new_game):
13         self._model = model
14         self._view = view
15         self._win_view = win_view
16         self._pause_view = pause_view
17
18         self._to_menu = to_menu
19         self._to_review = to_review
20         self._to_new_game = to_new_game
21
22         self._view.initialise_timers()
23         self._win_view.set_win_type('CAPTURE')
24
25     def cleanup(self, next):
26         """
27         Handles game quit, either leaving to main menu or restarting a new game.
28
29         Args:
30             next (str): New state to switch to.
31         """
32         self._model.kill_thread()
33
34         if next == 'menu':

```

```

34         self._to_menu()
35     elif next == 'game':
36         self._to_new_game()
37     elif next == 'review':
38         self._to_review()
39
40     def make_move(self, move):
41         """
42         Handles player move.
43
44         Args:
45             move (Move): Move to make.
46         """
47         self._model.make_move(move)
48         self._view.set_overlay_coords([], None)
49
50         if self._model.states['CPU_ENABLED']:
51             self._model.make_cpu_move()
52
53     def handle_pause_event(self, event):
54         """
55         Processes events when game is paused.
56
57         Args:
58             event (GameEventType): Event to process.
59
60         Raises:
61             Exception: If event type is unrecognised.
62         """
63         game_event = self._pause_view.convert_mouse_pos(event)
64
65         if game_event is None:
66             return
67
68         match game_event.type:
69             case GameEventType.PAUSE_CLICK:
70                 self._model.toggle_paused()
71
72             case GameEventType.MENU_CLICK:
73                 self.cleanup('menu')
74
75             case _:
76                 raise Exception('Unhandled event type (GameController.handle_event
77 )')
78
79     def handle_winner_event(self, event):
80         """
81         Processes events when game is over.
82
83         Args:
84             event (GameEventType): Event to process.
85
86         Raises:
87             Exception: If event type is unrecognised.
88         """
89         game_event = self._win_view.convert_mouse_pos(event)
90
91         if game_event is None:
92             return
93
94         match game_event.type:
95             case GameEventType.MENU_CLICK:

```

```

95         self.cleanup('menu')
96         return
97
98     case GameEventType.GAME_CLICK:
99         self.cleanup('game')
100        return
101
102     case GameEventType.REVIEW_CLICK:
103         self.cleanup('review')
104
105     case _:
106         raise Exception('Unhandled event type (GameController.handle_event
)')
107
108 def handle_game_widget_event(self, event):
109     """
110     Processes events for game GUI widgets.
111
112     Args:
113         event (GameEventType): Event to process.
114
115     Raises:
116         Exception: If event type is unrecognised.
117
118     Returns:
119         CustomEvent | None: A widget event.
120     """
121     widget_event = self._view.process_widget_event(event)
122
123     if widget_event is None:
124         return None
125
126     match widget_event.type:
127         case GameEventType.ROTATE_PIECE:
128             src_coords = self._view.get_selected_coords()
129
130             if src_coords is None:
131                 logger.info('None square selected')
132                 return
133
134             move = Move.instance_from_coords(MoveType.ROTATE, src_coords,
src_coords, rotation_direction=widget_event.rotation_direction)
135             self.make_move(move)
136
137         case GameEventType.RESIGN_CLICK:
138             self._model.set_winner(self._model.states['ACTIVE_COLOUR'].
get_flipped_colour())
139             self._view.handle_game_end(play_sfx=False)
140             self._win_view.set_win_type('RESIGN')
141
142         case GameEventType.DRAW_CLICK:
143             self._model.set_winner(Miscellaneous.DRAW)
144             self._view.handle_game_end(play_sfx=False)
145             self._win_view.set_win_type('DRAW')
146
147         case GameEventType.TIMER_END:
148             if self._model.states['TIME_ENABLED']:
149                 self._model.set_winner(widget_event.active_colour.
get_flipped_colour())
150                 self._win_view.set_win_type('TIME')
151                 self._view.handle_game_end(play_sfx=False)
152

```

```

153         case GameEventType.MENU_CLICK:
154             self.cleanup('menu')
155
156         case GameEventType.HELP_CLICK:
157             self._view.add_help_screen()
158
159         case GameEventType.TUTORIAL_CLICK:
160             self._view.add_tutorial_screen()
161
162         case _:
163             raise Exception('Unhandled event type (GameController.handle_event
164 )')
165
166         return widget_event.type
167
168     def check_cpu(self):
169         """
170         Checks if CPU calculations are finished every frame.
171         """
172         if self._model.states['CPU_ENABLED'] and self._model.states['AWAITING_CPU']
173         ] is False:
174             self._model.check_cpu()
175
176     def handle_game_event(self, event):
177         """
178         Processes Pygame events for main game.
179
180         Args:
181             event (pygame.Event): If event type is unrecognised.
182
183         Raises:
184             Exception: If event type is unrecognised.
185         """
186         # Pass event for widgets to process
187         widget_event = self.handle_game_widget_event(event)
188
189         if event.type in [pygame.MOUSEBUTTONDOWN, pygame.MOUSEBUTTONUP, pygame.
190 KEYDOWN]:
191             if event.type != pygame.KEYDOWN:
192                 game_event = self._view.convert_mouse_pos(event)
193             else:
194                 game_event = None
195
196             if game_event is None:
197                 if widget_event is None:
198                     if event.type in [pygame.MOUSEBUTTONUP, pygame.KEYDOWN]:
199                         # If user releases mouse click not on a widget
200                         self._view.remove_help_screen()
201                         self._view.remove_tutorial_screen()
202                     if event.type == pygame.MOUSEBUTTONUP:
203                         # If user releases mouse click on neither a widget or
204 board
205                         self._view.set_overlay_coords(None, None)
206
207                 return
208
209             match game_event.type:
210                 case GameEventType.BOARD_CLICK:
211                     if self._model.states['AWAITING_CPU']:
212                         return
213
214                     clicked_coords = game_event.coords

```



```

211         clicked_bitboard = bb_helpers.coords_to_bitboard(
clicked_coords)
212         selected_coords = self._view.get_selected_coords()
213
214         if selected_coords:
215             if clicked_coords == selected_coords:
216                 # If clicking on an already selected square, start
dragging piece on that square
217                 self._view.set_dragged_piece(*self._model.
get_piece_info(clicked_bitboard))
218                 return
219
220         selected_bitboard = bb_helpers.coords_to_bitboard(
selected_coords)
221         available_bitboard = self._model.get_available_moves(
selected_bitboard)
222
223         if bb_helpers.is_occupied(clicked_bitboard,
available_bitboard):
224             # If the newly clicked square is not the same as the
old one, and is an empty surrounding square, make a move
225             move = Move.instance_from_coords(MoveType.MOVE,
selected_coords, clicked_coords)
226             self.make_move(move)
227         else:
228             # If the newly clicked square is not the same as the
old one, but is an invalid square, unselect the currently selected square
229             self._view.set_overlay_coords(None, None)
230
231             # Select hovered square if it is same as active colour
232             elif self._model.is_selectable(clicked_bitboard):
233                 available_bitboard = self._model.get_available_moves(
clicked_bitboard)
234                 self._view.set_overlay_coords(bb_helpers.
bitboard_to_coords_list(available_bitboard), clicked_coords)
235                 self._view.set_dragged_piece(*self._model.get_piece_info(
clicked_bitboard))
236
237         case GameEventType.PIECE_DROP:
238             hovered_coords = game_event.coords
239
240             # if piece is dropped onto the board
241             if hovered_coords:
242                 hovered_bitboard = bb_helpers.coords_to_bitboard(
hovered_coords)
243                 selected_coords = self._view.get_selected_coords()
244                 selected_bitboard = bb_helpers.coords_to_bitboard(
selected_coords)
245                 available_bitboard = self._model.get_available_moves(
selected_bitboard)
246
247                 if bb_helpers.is_occupied(hovered_bitboard,
available_bitboard):
248                     # Make a move if mouse is hovered over an empty
surrounding square
249                     move = Move.instance_from_coords(MoveType.MOVE,
selected_coords, hovered_coords)
250                     self.make_move(move)
251
252                 if game_event.remove_overlay:
253                     self._view.set_overlay_coords(None, None)
254

```

```

255         self._view.remove_dragged_piece()
256
257         case _:
258             raise Exception('Unhandled event type (GameController.
handle_event)', game_event.type)
259
260     def handle_event(self, event):
261         """
262         Passe a Pygame event to the correct handling function according to the
game state.
263
264         Args:
265             event (pygame.Event): Event to process.
266         """
267         if event.type in [pygame.MOUSEBUTTONDOWN, pygame.MOUSEBUTTONUP, pygame.
MOUSEMOTION, pygame.KEYDOWN]:
268             if self._model.states['PAUSED']:
269                 self.handle_pause_event(event)
270             elif self._model.states['WINNER'] is not None:
271                 self.handle_winner_event(event)
272             else:
273                 self.handle_game_event(event)
274
275         if event.type == pygame.KEYDOWN:
276             if event.key == pygame.K_ESCAPE:
277                 self._model.toggle_paused()
278             elif event.key == pygame.K_l:
279                 logger.info('\nSTOPPING CPU')
280                 self._model._cpu_thread.stop_cpu() #temp

```

## 1.5.4 Board

The `Board` class implements the Laser Chess board, and is responsible for handling moves, captures, and win conditions.

`board.py`

```

1 from collections import defaultdict
2 from data.utils.constants import A_FILE_MASK, J_FILE_MASK, ONE_RANK_MASK,
EIGHT_RANK_MASK, EMPTY_BB
3 from data.utils.enums import Colour, Piece, Rank, File, MoveType,
RotationDirection, Miscellaneous
4 from data.states.game.components.bitboard_collection import BitboardCollection
5 from data.helpers import bitboard_helpers as bb_helpers
6 from data.states.game.components.laser import Laser
7 from data.states.game.components.move import Move
8
9
10 class Board:
11     def __init__(self, fen_string="sc3ncfcncpb2/2pc7/3Pd6/pa1Pc1rbra1pb1Pd/
pb1Pd1RaRb1pa1Pc/6pb3/7Pa2/2PdNaFaNa3Sa b"):
12         self.bitboards = BitboardCollection(fen_string)
13         self.hash_list = [self.bitboards.get_hash()]
14
15     def __str__(self):
16         """
17         Returns a string representation of the board.
18
19         Returns:
20             str: Board formatted as string.
21         """

```

```

22     characters = '8 '
23     pieces = defaultdict(int)
24
25     for rank_idx, rank in enumerate(reversed(Rank)):
26         for file_idx, file in enumerate(File):
27             mask = 1 << (rank * 10 + file)
28             blue_piece = self.bitboards.get_piece_on(mask, Colour.BLUE)
29             red_piece = self.bitboards.get_piece_on(mask, Colour.RED)
30
31             if blue_piece:
32                 pieces[blue_piece.value.upper()] += 1
33                 characters += f'{blue_piece.upper()} '
34             elif red_piece:
35                 pieces[red_piece.value] += 1
36                 characters += f'{red_piece} '
37             else:
38                 characters += '. '
39
40         characters += f'\n\n{7 - rank_idx} '
41     characters += 'A B C D E F G H I J\n\n'
42     characters += str(dict(pieces))
43     characters += f'\nCURRENT PLAYER TO MOVE: {self.bitboards.active_colour.name}\n'
44     return characters
45
46 def get_piece_list(self):
47     """
48     Converts the board bitboards to a list of pieces.
49
50     Returns:
51         list: List of Pieces.
52     """
53     return self.bitboards.convert_to_piece_list()
54
55 def get_active_colour(self):
56     """
57     Gets the active colour.
58
59     Returns:
60         Colour: The active colour.
61     """
62     return self.bitboards.active_colour
63
64 def to_hash(self):
65     """
66     Gets the hash of the current board state.
67
68     Returns:
69         int: A Zobrist hash.
70     """
71     return self.bitboards.get_hash()
72
73 def check_win(self):
74     """
75     Checks for a Pharoah capture or threefold-repetition.
76
77     Returns:
78         Colour | Miscellaneous: The winning colour, or Miscellaneous.DRAW.
79     """
80     for colour in Colour:
81         if self.bitboards.get_piece_bitboard(Piece.PHAROAH, colour) ==
EMPTY_BB:

```

```

82         return colour.get_flipped_colour()
83
84     if self.hash_list.count(self.hash_list[-1]) >= 3:
85         return Miscellaneous.DRAW
86
87     return None
88
89     def apply_move(self, move, fire_laser=True, add_hash=False):
90         """
91         Applies a move to the board.
92
93         Args:
94             move (Move): The move to apply.
95             fire_laser (bool): Whether to fire the laser after the move.
96             add_hash (bool): Whether to add the board state hash to the hash list.
97
98         Returns:
99             Laser: The laser trajectory result.
100         """
101         piece_symbol = self.bitboards.get_piece_on(move.src, self.bitboards.
102             active_colour)
103
104         if piece_symbol is None:
105             raise ValueError(f'Invalid move - no piece found on source square. {
106                 move}')
107         elif piece_symbol == Piece.SPHINX:
108             raise ValueError(f'Invalid move - sphinx piece is immovable. {move}')
109
110         if move.move_type == MoveType.MOVE:
111             possible_moves = self.get_valid_squares(move.src)
112             if bb_helpers.is_occupied(move.dest, possible_moves) is False:
113                 raise ValueError('Invalid move - destination square is occupied')
114
115             piece_rotation = self.bitboards.get_rotation_on(move.src)
116
117             self.bitboards.update_move(move.src, move.dest)
118             self.bitboards.update_rotation(move.src, move.dest, piece_rotation)
119
120         elif move.move_type == MoveType.ROTATE:
121             piece_symbol = self.bitboards.get_piece_on(move.src, self.bitboards.
122                 active_colour)
123             piece_rotation = self.bitboards.get_rotation_on(move.src)
124
125             if move.rotation_direction == RotationDirection.CLOCKWISE:
126                 new_rotation = piece_rotation.get_clockwise()
127             elif move.rotation_direction == RotationDirection.ANTICLOCKWISE:
128                 new_rotation = piece_rotation.get_anticlockwise()
129
130             self.bitboards.update_rotation(move.src, move.src, new_rotation)
131
132         laser = None
133         if fire_laser:
134             laser = self.fire_laser(add_hash)
135
136         if add_hash:
137             self.hash_list.append(self.bitboards.get_hash())
138
139         self.bitboards.flip_colour()
140
141         return laser
142
143     def undo_move(self, move, laser_result):

```

```

141     """
142     Undoes a move on the board.
143
144     Args:
145         move (Move): The move to undo.
146         laser_result (Laser): The laser trajectory result.
147     """
148     self.bitboards.flip_colour()
149
150     if laser_result.hit_square_bitboard:
151         # Get info of destroyed piece, and add it to the board again
152         src = laser_result.hit_square_bitboard
153         piece = laser_result.piece_hit
154         colour = laser_result.piece_colour
155         rotation = laser_result.piece_rotation
156
157         self.bitboards.set_square(src, piece, colour)
158         self.bitboards.clear_rotation(src)
159         self.bitboards.set_rotation(src, rotation)
160
161         # Create new Move object that is the inverse of the passed move
162         if move.move_type == MoveType.MOVE:
163             reversed_move = Move.instance_from_bitboards(MoveType.MOVE, move.dest,
164 move.src)
165         elif move.move_type == MoveType.ROTATE:
166             reversed_move = Move.instance_from_bitboards(MoveType.ROTATE, move.src
167 , move.src, move.rotation_direction.get_opposite())
168
169         self.apply_move(reversed_move, fire_laser=False)
170         self.bitboards.flip_colour()
171
172     def remove_piece(self, square_bitboard):
173         """
174         Removes a piece from a given square.
175
176         Args:
177             square_bitboard (int): The bitboard representation of the square.
178         """
179         self.bitboards.clear_square(square_bitboard, Colour.BLUE)
180         self.bitboards.clear_square(square_bitboard, Colour.RED)
181         self.bitboards.clear_rotation(square_bitboard)
182
183     def get_valid_squares(self, src_bitboard, colour=None):
184         """
185         Gets valid squares for a piece to move to.
186
187         Args:
188             src_bitboard (int): The bitboard representation of the source square.
189             colour (Colour, optional): The active colour of the piece.
190
191         Returns:
192             int: The bitboard representation of valid squares.
193         """
194         target_top_left = (src_bitboard & A_FILE_MASK & EIGHT_RANK_MASK) << 9
195         target_top_middle = (src_bitboard & EIGHT_RANK_MASK) << 10
196         target_top_right = (src_bitboard & J_FILE_MASK & EIGHT_RANK_MASK) << 11
197         target_middle_right = (src_bitboard & J_FILE_MASK) << 1
198
199         target_bottom_right = (src_bitboard & J_FILE_MASK & ONE_RANK_MASK) >> 9
200         target_bottom_middle = (src_bitboard & ONE_RANK_MASK) >> 10
201         target_bottom_left = (src_bitboard & A_FILE_MASK & ONE_RANK_MASK) >> 11
202         target_middle_left = (src_bitboard & A_FILE_MASK) >> 1

```

```

201
202     possible_moves = target_top_left | target_top_middle | target_top_right |
target_middle_right | target_bottom_right | target_bottom_middle |
target_bottom_left | target_middle_left
203
204     if colour is not None:
205         valid_possible_moves = possible_moves & ~self.bitboards.
combined_colour_bitboards[colour]
206     else:
207         valid_possible_moves = possible_moves & ~self.bitboards.
combined_all_bitboard
208
209     return valid_possible_moves
210
211 def get_mobility(self, colour):
212     """
213     Gets all valid squares for a given colour.
214
215     Args:
216         colour (Colour): The colour of the pieces.
217
218     Returns:
219         int: The bitboard representation of all valid squares.
220     """
221     active_pieces = self.get_all_active_pieces(colour)
222     possible_moves = 0
223
224     for square in bb_helpers.occupied_squares(active_pieces):
225         possible_moves += bb_helpers.pop_count(self.get_valid_squares(square))
226
227     return possible_moves
228
229 def get_all_active_pieces(self, colour=None):
230     """
231     Gets all active pieces for the current player.
232
233     Args:
234         colour (Colour): Active colour of pieces to retrieve. Defaults to None
235
236     Returns:
237         int: The bitboard representation of all active pieces.
238     """
239     if colour is None:
240         colour = self.bitboards.active_colour
241
242     active_pieces = self.bitboards.combined_colour_bitboards[colour]
243     sphinx_bitboard = self.bitboards.get_piece_bitboard(Piece.SPHINX, colour)
244     return active_pieces ^ sphinx_bitboard
245
246 def fire_laser(self, remove_hash):
247     """
248     Fires the laser and removes hit pieces.
249
250     Args:
251         remove_hash (bool): Whether to clear the hash list if a piece is hit.
252
253     Returns:
254         Laser: The result of firing the laser.
255     """
256     laser = Laser(self.bitboards)
257

```

```

258         if laser.hit_square_bitboard:
259             self.remove_piece(laser.hit_square_bitboard)
260
261         if remove_hash:
262             self.hash_list = [] # Remove all hashes for threefold repetition,
as the position is impossible to be repeated after a piece is removed
263         return laser
264
265     def generate_square_moves(self, src):
266         """
267         Generates all valid moves for a piece on a given square.
268
269         Args:
270             src (int): The bitboard representation of the source square.
271
272         Yields:
273             Move: A valid move for the piece.
274         """
275         for dest in bb_helpers.occupied_squares(self.get_valid_squares(src)):
276             yield Move(MoveType.MOVE, src, dest)
277
278     def generate_all_moves(self, colour):
279         """
280         Generates all valid moves for a given colour.
281
282         Args:
283             colour (Colour): The colour of the pieces.
284
285         Yields:
286             Move: A valid move for the active colour.
287         """
288         sphinx_bitboard = self.bitboards.get_piece_bitboard(Piece.SPHINX, colour)
289         # Remove source squares for Sphinx pieces, as they cannot be moved
290         sphinx_masked_bitboard = self.bitboards.combined_colour_bitboards[colour]
~ sphinx_bitboard
291
292         for square in bb_helpers.occupied_squares(sphinx_masked_bitboard):
293             # Generate movement moves
294             yield from self.generate_square_moves(square)
295
296             # Generate rotational moves
297             for rotation_direction in RotationDirection:
298                 yield Move(MoveType.ROTATE, square, rotation_direction=
rotation_direction)

```

### 1.5.5 Bitboards

As described in Section ??, the BitboardCollection class uses helper functions found in bitboard\_helpers.py such as pop\_count, to initialise and manage bitboard transformations.

bitboard\_collection.py

```

1 from data.utils.enums import Rank, File, Piece, Colour, Rotation, RotationIndex
2 from data.states.game.components.fen_parser import parse_fen_string
3 from data.states.game.cpu.zobrist_hasher import ZobristHasher
4 from data.helpers import bitboard_helpers as bb_helpers
5 from data.managers.logs import initialise_logger
6 from data.utils.constants import EMPTY_BB
7
8 logger = initialise_logger(__name__)
9

```

```

10 class BitboardCollection:
11     def __init__(self, fen_string):
12         self.piece_bitboards = [{char: EMPTY_BB for char in Piece}, {char:
EMPTY_BB for char in Piece}]
13         self.combined_colour_bitboards = [EMPTY_BB, EMPTY_BB]
14         self.combined_all_bitboard = EMPTY_BB
15         self.rotation_bitboards = [EMPTY_BB, EMPTY_BB]
16         self.active_colour = Colour.BLUE
17         self._hasher = ZobristHasher()
18
19         try:
20             if fen_string:
21                 self.piece_bitboards, self.combined_colour_bitboards, self.
combined_all_bitboard, self.rotation_bitboards, self.active_colour =
parse_fen_string(fen_string)
22                 self.initialise_hash()
23             except ValueError as error:
24                 logger.error('Please input a valid FEN string:', error)
25                 raise error
26
27     def __str__(self):
28         """
29         Returns a string representation of the bitboards.
30
31         Returns:
32             str: Bitboards formatted with piece type and colour shown.
33         """
34         characters = ''
35         for rank in reversed(Rank):
36             for file in File:
37                 bitboard = 1 << (rank * 10 + file)
38
39                 colour = self.get_colour_on(bitboard)
40                 piece = self.get_piece_on(bitboard, Colour.BLUE) or self.
get_piece_on(bitboard, Colour.RED)
41
42                 if piece is not None:
43                     characters += f'{piece.upper() if colour == Colour.BLUE
else piece} '
44                 else:
45                     characters += '. '
46
47             characters += '\n\n'
48
49         return characters
50
51     def get_rotation_string(self):
52         """
53         Returns a string representation of the board rotations.
54
55         Returns:
56             str: Board formatted with only rotations shown.
57         """
58         characters = ''
59         for rank in reversed(Rank):
60
61             for file in File:
62                 mask = 1 << (rank * 10 + file)
63                 rotation = self.get_rotation_on(mask)
64                 has_piece = bb_helpers.is_occupied(self.combined_all_bitboard,
mask)
65

```



```

66         if has_piece:
67             characters += f'{rotation.upper()} '
68         else:
69             characters += '. '
70
71         characters += '\n\n'
72
73     return characters
74
75 def initialise_hash(self):
76     """
77     Initialises the Zobrist hash for the current board state.
78     """
79     for piece in Piece:
80         for colour in Colour:
81             piece_bitboard = self.get_piece_bitboard(piece, colour)
82
83             for occupied_bitboard in bb_helpers.occupied_squares(
84 piece_bitboard):
85                 self._hasher.apply_piece_hash(occupied_bitboard, piece, colour
86 )
87
88         for bitboard in bb_helpers.loop_all_squares():
89             rotation = self.get_rotation_on(bitboard)
90             self._hasher.apply_rotation_hash(bitboard, rotation)
91
92     if self.active_colour == Colour.RED:
93         self._hasher.apply_red_move_hash()
94
95 def flip_colour(self):
96     """
97     Flips the active colour and updates the Zobrist hash.
98     """
99     self.active_colour = self.active_colour.get_flipped_colour()
100
101     if self.active_colour == Colour.RED:
102         self._hasher.apply_red_move_hash()
103
104 def update_move(self, src, dest):
105     """
106     Updates the bitboards for a move.
107
108     Args:
109         src (int): The bitboard representation of the source square.
110         dest (int): The bitboard representation of the destination square.
111     """
112     piece = self.get_piece_on(src, self.active_colour)
113
114     self.clear_square(src, Colour.BLUE)
115     self.clear_square(dest, Colour.BLUE)
116     self.clear_square(src, Colour.RED)
117     self.clear_square(dest, Colour.RED)
118
119     self.set_square(dest, piece, self.active_colour)
120
121 def update_rotation(self, src, dest, new_rotation):
122     """
123     Updates the rotation bitboards for a move.
124
125     Args:
126         src (int): The bitboard representation of the source square.
127         dest (int): The bitboard representation of the destination square.

```

```

126         new_rotation (Rotation): The new rotation.
127     """
128     self.clear_rotation(src)
129     self.set_rotation(dest, new_rotation)
130
131 def clear_rotation(self, bitboard):
132     """
133     Clears the rotation for a given square.
134
135     Args:
136         bitboard (int): The bitboard representation of the square.
137     """
138     old_rotation = self.get_rotation_on(bitboard)
139     rotation_1, rotation_2 = self.rotation_bitboards
140     self.rotation_bitboards[RotationIndex.FIRSTBIT] = bb_helpers.clear_square(
rotation_1, bitboard)
141     self.rotation_bitboards[RotationIndex.SECONDBIT] = bb_helpers.clear_square
(rotation_2, bitboard)
142
143     self._hasher.apply_rotation_hash(bitboard, old_rotation)
144
145 def clear_square(self, bitboard, colour):
146     """
147     Clears a square piece and rotation for a given colour.
148
149     Args:
150         bitboard (int): The bitboard representation of the square.
151         colour (Colour): The colour to clear.
152     """
153     piece = self.get_piece_on(bitboard, colour)
154
155     if piece is None:
156         return
157
158     piece_bitboard = self.get_piece_bitboard(piece, colour)
159     colour_bitboard = self.combined_colour_bitboards[colour]
160     all_bitboard = self.combined_all_bitboard
161
162     self.piece_bitboards[colour][piece] = bb_helpers.clear_square(
piece_bitboard, bitboard)
163     self.combined_colour_bitboards[colour] = bb_helpers.clear_square(
colour_bitboard, bitboard)
164     self.combined_all_bitboard = bb_helpers.clear_square(all_bitboard,
bitboard)
165
166     self._hasher.apply_piece_hash(bitboard, piece, colour)
167
168 def set_rotation(self, bitboard, rotation):
169     """
170     Sets the rotation for a given square.
171
172     Args:
173         bitboard (int): The bitboard representation of the square.
174         rotation (Rotation): The rotation to set.
175     """
176     rotation_1, rotation_2 = self.rotation_bitboards
177     self._hasher.apply_rotation_hash(bitboard, rotation)
178
179     match rotation:
180         case Rotation.UP:
181             return
182         case Rotation.RIGHT:

```

```

183         self.rotation_bitboards[RotationIndex.FIRSTBIT] = bb_helpers.
set_square(rotation_1, bitboard)
184         return
185     case Rotation.DOWN:
186         self.rotation_bitboards[RotationIndex.SECONDBIT] = bb_helpers.
set_square(rotation_2, bitboard)
187         return
188     case Rotation.LEFT:
189         self.rotation_bitboards[RotationIndex.FIRSTBIT] = bb_helpers.
set_square(rotation_1, bitboard)
190         self.rotation_bitboards[RotationIndex.SECONDBIT] = bb_helpers.
set_square(rotation_2, bitboard)
191         return
192     case _:
193         raise ValueError('Invalid rotation input (bitboard.py):', rotation
)
194
195 def set_square(self, bitboard, piece, colour):
196     """
197     Sets a piece on a given square.
198
199     Args:
200         bitboard (int): The bitboard representation of the square.
201         piece (Piece): The piece to set.
202         colour (Colour): The colour of the piece.
203     """
204     piece_bitboard = self.get_piece_bitboard(piece, colour)
205     colour_bitboard = self.combined_colour_bitboards[colour]
206     all_bitboard = self.combined_all_bitboard
207
208     self.piece_bitboards[colour][piece] = bb_helpers.set_square(piece_bitboard
, bitboard)
209     self.combined_colour_bitboards[colour] = bb_helpers.set_square(
colour_bitboard, bitboard)
210     self.combined_all_bitboard = bb_helpers.set_square(all_bitboard, bitboard)
211
212     self._hasher.apply_piece_hash(bitboard, piece, colour)
213
214 def get_piece_bitboard(self, piece, colour):
215     """
216     Gets the bitboard for a piece type for a given colour.
217
218     Args:
219         piece (Piece): The piece bitboard to get.
220         colour (Colour): The colour of the piece.
221
222     Returns:
223         int: The bitboard representation for all squares occupied by that
piece type.
224     """
225     return self.piece_bitboards[colour][piece]
226
227 def get_piece_on(self, target_bitboard, colour):
228     """
229     Gets the piece on a given square for a given colour.
230
231     Args:
232         target_bitboard (int): The bitboard representation of the square.
233         colour (Colour): The colour of the piece.
234
235     Returns:
236         Piece: The piece on the square, or None if square is empty.

```

```

237         """
238         if not (bb_helpers.is_occupied(self.combined_colour_bitboards[colour],
239 target_bitboard)):
240             return None
241
242         return next(
243             (piece for piece in Piece if
244              bb_helpers.is_occupied(self.get_piece_bitboard(piece, colour),
245 target_bitboard)),
246             None)
247
248 def get_rotation_on(self, target_bitboard):
249     """
250     Gets the rotation on a given square.
251
252     Args:
253         target_bitboard (int): The bitboard representation of the square.
254
255     Returns:
256         Rotation: The rotation on the square.
257     """
258     rotationBits = [bb_helpers.is_occupied(self.rotation_bitboards[
259 RotationIndex.SECONDBIT], target_bitboard), bb_helpers.is_occupied(self.
260 rotation_bitboards[RotationIndex.FIRSTBIT], target_bitboard)]
261
262     match rotationBits:
263         case [False, False]:
264             return Rotation.UP
265         case [False, True]:
266             return Rotation.RIGHT
267         case [True, False]:
268             return Rotation.DOWN
269         case [True, True]:
270             return Rotation.LEFT
271
272 def get_colour_on(self, target_bitboard):
273     """
274     Gets the colour of the piece on a given square.
275
276     Args:
277         target_bitboard (int): The bitboard representation of the square.
278
279     Returns:
280         Colour: The colour of the piece on the square.
281     """
282     for piece in Piece:
283         if self.get_piece_bitboard(piece, Colour.BLUE) & target_bitboard !=
284 EMPTY_BB:
285             return Colour.BLUE
286         elif self.get_piece_bitboard(piece, Colour.RED) & target_bitboard !=
287 EMPTY_BB:
288             return Colour.RED
289
290 def get_piece_count(self, piece, colour):
291     """
292     Gets the count of a given piece type and colour.
293
294     Args:
295         piece (Piece): The piece to count.
296         colour (Colour): The colour of the piece.
297
298     Returns:

```

```

293         int: The number of that piece of that colour on the board.
294     """
295     return bb_helpers.pop_count(self.get_piece_bitboard(piece, colour))
296
297 def get_hash(self):
298     """
299     Gets the Zobrist hash of the current board state.
300
301     Returns:
302         int: The Zobrist hash.
303     """
304     return self._hasher.hash
305
306 def convert_to_piece_list(self):
307     """
308     Converts all bitboards to a list of pieces.
309
310     Returns:
311         list: Board represented as a 2D list of Piece and Rotation objects.
312     """
313     piece_list = []
314
315     for i in range(80):
316         if x := self.get_piece_on(1 << i, Colour.BLUE):
317             rotation = self.get_rotation_on(1 << i)
318             piece_list.append((x.upper(), rotation))
319         elif y := self.get_piece_on(1 << i, Colour.RED):
320             rotation = self.get_rotation_on(1 << i)
321             piece_list.append((y, rotation))
322         else:
323             piece_list.append(None)
324
325     return piece_list

```

## 1.6 CPU

This section includes my implementation for the CPU engine run on minimax, including its various improvements and accessory classes.

Every CPU engine class is a subclass of a `BaseCPU` abstract class, and therefore contains the same attribute and method names. This means **polymorphism** can be used again to easily to test and vary the difficulty by switching out which CPU engine is used.

The method `find_move` is called by the CPU thread. `search` is then called recursively to traverse the minimax tree, and find an optimal move. The move is then return to `find_move` and passed and run with the callback function. A `stats` dictionary is also created in the base class, used to collect information for each search.

### 1.6.1 Minimax

As described in Section ??, the minimax engine uses **DFS** to traverse the game tree and evaluate node accordingly, by **recursively** calling the `search` function.

`minimax.py`

```

1 from random import choice
2 from data.states.game.cpu.base import BaseCPU
3 from data.utils.enums import Score, Colour
4

```

```

5 class MinimaxCPU(BaseCPU):
6     def __init__(self, max_depth, callback, verbose=False):
7         super().__init__(callback, verbose)
8         self._max_depth = max_depth
9
10    def find_move(self, board, stop_event):
11        """
12        Finds the best move for the current board state.
13
14        Args:
15            board (Board): The current board state.
16            stop_event (threading.Event): Event used to kill search from an
17            external class.
18        """
19        self.initialise_stats()
20        best_score, best_move = self.search(board, self._max_depth, stop_event)
21
22        if self._verbose:
23            self.print_stats(best_score, best_move)
24
25        self._callback(best_move)
26
27    def search(self, board, depth, stop_event):
28        """
29        Recursively DFS through minimax tree with evaluation score.
30
31        Args:
32            board (Board): The current board state.
33            depth (int): The current search depth.
34            stop_event (threading.Event): Event used to kill search from an
35            external class.
36        Returns:
37            tuple[int, Move]: The best score and the best move found.
38        """
39        if (base_case := super().search(board, depth, stop_event)):
40            return base_case
41
42        best_move = None
43
44        # Blue is the maximising player
45        if board.get_active_colour() == Colour.BLUE:
46            max_score = -Score.INFINITE
47
48            for move in board.generate_all_moves(Colour.BLUE):
49                laser_result = board.apply_move(move)
50
51                new_score = self.search(board, depth - 1, stop_event)[0]
52
53                # if depth < self._max_depth:
54                #     print('DEPTH', depth, new_score, move)
55
56                if new_score > max_score:
57                    max_score = new_score
58                    best_move = move
59
60                if new_score == (Score.CHECKMATE + self._max_depth):
61                    board.undo_move(move, laser_result)
62                    return max_score, best_move
63
64            elif new_score == max_score:
65                # If evaluated scores are equal, pick a random move

```

```

65         best_move = choice([best_move, move])
66
67         board.undo_move(move, laser_result)
68
69         return max_score, best_move
70
71     else:
72         min_score = Score.INFINITE
73
74         for move in board.generate_all_moves(Colour.RED):
75             laser_result = board.apply_move(move)
76             # print('DEPTH', depth, move)
77             new_score = self.search(board, depth - 1, stop_event)[0]
78
79             if new_score < min_score:
80                 # print('setting new', new_score, move)
81                 min_score = new_score
82                 best_move = move
83
84                 if new_score == (-Score.CHECKMATE - self._max_depth):
85                     board.undo_move(move, laser_result)
86                     return min_score, best_move
87
88             elif new_score == min_score:
89                 best_move = choice([best_move, move])
90
91         board.undo_move(move, laser_result)
92
93     return min_score, best_move

```

## 1.6.2 Alpha-beta Pruning

As described in Section ??, the `ABMinimaxCPU` class introduces pruning to reduce the number of nodes evaluated during a minimax search.

`alpha_beta.py`

```

1  from data.states.game.cpu.move_orderer import MoveOrderer
2  from data.states.game.cpu.base import BaseCPU
3  from data.utils.enums import Score, Colour
4
5  class ABMinimaxCPU(BaseCPU):
6      def __init__(self, max_depth, callback, verbose=True):
7          super().__init__(callback, verbose)
8          self._max_depth = max_depth
9          self._orderer = MoveOrderer()
10
11      def initialise_stats(self):
12          """
13          Initialises the number of prunes to the statistics dictionary to be logged
14          """
15          super().initialise_stats()
16          self._stats['beta_prunes'] = 0
17          self._stats['alpha_prunes'] = 0
18
19      def find_move(self, board, stop_event):
20          """
21          Finds the best move for the current board state.
22
23          Args:

```

```

24         board (Board): The current board state.
25         stop_event (threading.Event): Event used to kill search from an
external class.
26     """
27     self.initialise_stats()
28     best_score, best_move = self.search(board, self._max_depth, -Score.
INFINITE, Score.INFINITE, stop_event)
29
30     if self._verbose:
31         self.print_stats(best_score, best_move)
32
33     self._callback(best_move)
34
35 def search(self, board, depth, alpha, beta, stop_event, hint=None,
laser_coords=None):
36     """
37     Recursively DFS through minimax tree while pruning branches using the
alpha and beta bounds.
38
39     Args:
40         board (Board): The current board state.
41         depth (int): The current search depth.
42         alpha (int): The upper bound value.
43         beta (int): The lower bound value.
44         stop_event (threading.Event): Event used to kill search from an
external class.
45
46     Returns:
47         tuple[int, Move]: The best score and the best move found.
48     """
49     if (base_case := super().search(board, depth, stop_event)):
50         return base_case
51
52     best_move = None
53
54     # Blue is the maximising player
55     if board.get_active_colour() == Colour.BLUE:
56         max_score = -Score.INFINITE
57
58         for move in self._orderer.get_moves(board, hint=hint, laser_coords=
laser_coords):
59             laser_result = board.apply_move(move)
60             new_score = self.search(board, depth - 1, alpha, beta, stop_event,
laser_coords=laser_result.pieces_on_trajectory)[0]
61
62             if new_score > max_score:
63                 max_score = new_score
64                 best_move = move
65
66             board.undo_move(move, laser_result)
67
68             alpha = max(alpha, max_score)
69
70             if beta <= alpha:
71                 self._stats['alpha_prunes'] += 1
72                 break
73
74         return max_score, best_move
75
76     else:
77         min_score = Score.INFINITE
78

```



```

79         for move in self._orderer.get_moves(board, hint=hint, laser_coords=
laser_coords):
80             laser_result = board.apply_move(move)
81             new_score = self.search(board, depth - 1, alpha, beta, stop_event,
laser_coords=laser_result.pieces_on_trajectory)[0]
82
83             if new_score < min_score:
84                 min_score = new_score
85                 best_move = move
86
87             board.undo_move(move, laser_result)
88
89             beta = min(beta, min_score)
90             if beta <= alpha:
91                 self._stats['beta_prunes'] += 1
92                 break
93
94         return min_score, best_move

```

### 1.6.3 Transposition Table

For adding transposition table functionality to my other engine classes, as described in Section ??, I have decided to use a mixin design architecture. This allows me to **reuse code** by adding mixins to many different classes, and inject additional transposition table methods and functionality into other engines.

transposition\_table.py

```

1 from data.states.game.cpu.transposition_table import TranspositionTable
2 from data.states.game.cpu.engines.alpha_beta import ABMinimaxCPU
3
4 class TranspositionTableMixin:
5     def __init__(self, *args, **kwargs):
6         super().__init__(*args, **kwargs)
7         self._table = TranspositionTable()
8
9     def find_move(self, *args, **kwargs):
10        self._table = TranspositionTable()
11        super().find_move(*args, **kwargs)
12
13    def search(self, board, depth, alpha, beta, stop_event, hint=None,
laser_coords=None):
14        """
15        Searches transposition table for a cached move before running a full
search if necessary.
16        Caches the searched result.
17
18        Args:
19            board (Board): The current board state.
20            depth (int): The current search depth.
21            alpha (int): The upper bound value.
22            beta (int): The lower bound value.
23            stop_event (threading.Event): Event used to kill search from an
external class.
24
25        Returns:
26            tuple[int, Move]: The best score and the best move found.
27        """
28        hash = board.to_hash()
29        score, move = self._table.get_entry(hash, depth, alpha, beta)
30

```

```

31         if score is not None:
32             self._stats['cache_hits'] += 1
33             self._stats['nodes'] += 1
34
35         return score, move
36     else:
37         # If board hash entry not found in cache, run a full search
38         score, move = super().search(board, depth, alpha, beta, stop_event,
hint)
39         self._table.insert_entry(score, move, hash, depth, alpha, beta)
40
41         return score, move
42
43 class TTMinimaxCPU(TranspositionTableMixin, ABMinimaxCPU):
44     def initialise_stats(self):
45         """
46         Initialises cache statistics to be logged.
47         """
48         super().initialise_stats()
49         self._stats['cache_hits'] = 0
50
51     def print_stats(self, score, move):
52         """
53         Logs the statistics for the search.
54
55         Args:
56             score (int): The best score found.
57             move (Move): The best move found.
58         """
59         # Calculate number of cached entries retrieved as a percentage of all
nodes
60         self._stats['cache_hits_percentage'] = round(self._stats['cache_hits'] /
self._stats['nodes'], 3)
61         self._stats['cache_entries'] = len(self._table._table)
62         super().print_stats(score, move)

```

### 1.6.4 Iterative Deepening

As described in ??, the depth for each search is increased for each iteration through the for loop, with the best move found on one depth being used as the starting move for the following depth.

iterative\_deepening.py

```

1 from copy import deepcopy
2 from random import choice
3 from data.states.game.cpu.engines.transposition_table import
TranspositionTableMixin
4 from data.states.game.cpu.transposition_table import TranspositionTable
5 from data.states.game.cpu.engines.alpha_beta import ABMinimaxCPU
6 from data.managers.logs import initialise_logger
7 from data.utils.enums import Score
8
9 logger = initialise_logger(__name__)
10
11 class IterativeDeepeningMixin:
12     def find_move(self, board, stop_event):
13         """
14         Iterates through increasing depths to find the best move.
15
16         Args:
17             board (Board): The current board state.

```

```

18         stop_event (threading.Event): Event used to kill search from an
external class.
19         """
20         self._table = TranspositionTable()
21
22         best_move = None
23
24         for depth in range(1, self._max_depth + 1):
25             self.initialise_stats()
26
27             # Use copy of board as search can be terminated before all tested
moves are undone
28             board_copy = deepcopy(board)
29
30             try:
31                 best_score, best_move = self.search(board_copy, depth, -Score.
INFINITE, Score.INFINITE, stop_event, hint=best_move)
32             except TimeoutError:
33                 # If allocated time is up, use previous depth's best move
34                 logger.info(f'Terminated CPU search early at depth {depth}. Using
existing best move: {best_move}')
35
36                 if best_move is None:
37                     # If search is terminated at depth 0, use random move
38                     best_move = choice(board_copy.generate_all_moves())
39                     logger.warning('CPU terminated before any best move found!
Using random move.')
40
41                 break
42
43             self._stats['ID_depth'] = depth
44
45             if self._verbose:
46                 self.print_stats(best_score, best_move)
47
48             self._callback(best_move)
49
50 class IDMinimaxCPU(TranspositionTableMixin, IterativeDeepeningMixin, ABMinimaxCPU)
:
51     def initialise_stats(self):
52         super().initialise_stats()
53         self._stats['cache_hits'] = 0
54
55     def print_stats(self, score, move):
56         self._stats['cache_hits_percentage'] = round(self._stats['cache_hits'] /
self._stats['nodes'], 3)
57         self._stats['cache_entries'] = len(self._table._table)
58         super().print_stats(score, move)

```

### 1.6.5 Evaluator

As described in Section ??, I have opted to separate the evaluation class into separate methods for each aspect of the evaluation, and amalgamating all of them to form one unified `evaluate` function, as this allows me to debug each function easily.

`evaluator.py`

```

1 from data.helpers.bitboard_helpers import pop_count, occupied_squares,
bitboard_to_index
2 from data.states.game.components.psqt import PSQT, FLIP
3 from data.utils.enums import Colour, Piece, Score

```

```

4 from data.managers.logs import initialise_logger
5
6 logger = initialise_logger(__name__)
7
8 class Evaluator:
9     def __init__(self, verbose=True):
10         self._verbose = verbose
11
12     def evaluate(self, board, absolute=False):
13         """
14         Evaluates and returns a numerical score for the board state.
15
16         Args:
17             board (Board): The current board state.
18             absolute (bool): Whether to always return the absolute score from the
19                             active colour's perspective (for NegaMax).
20
21         Returns:
22             int: Score representing advantage/disadvantage for the player.
23         """
24         blue_score = (
25             self.evaluate_material(board, Colour.BLUE),
26             self.evaluate_position(board, Colour.BLUE),
27             self.evaluate_mobility(board, Colour.BLUE),
28             self.evaluate_pharoah_safety(board, Colour.BLUE)
29         )
30
31         red_score = (
32             self.evaluate_material(board, Colour.RED),
33             self.evaluate_position(board, Colour.RED),
34             self.evaluate_mobility(board, Colour.RED),
35             self.evaluate_pharoah_safety(board, Colour.RED)
36         )
37
38         if self._verbose:
39             logger.info(f'Material: {blue_score[0]} | {red_score[0]}')
40             logger.info(f'Position: {blue_score[1]} | {red_score[1]}')
41             logger.info(f'Mobility: {blue_score[2]} | {red_score[2]}')
42             logger.info(f'Safety: {blue_score[3]} | {red_score[3]}')
43             logger.info(f'Overall score: {sum(blue_score) - sum(red_score)}')
44
45         if absolute and board.get_active_colour() == Colour.RED:
46             return sum(red_score) - sum(blue_score)
47         else:
48             return sum(blue_score) - sum(red_score)
49
50     def evaluate_material(self, board, colour):
51         """
52         Evaluates the material score for a given colour.
53
54         Args:
55             board (Board): The current board state.
56             colour (Colour): The colour to evaluate.
57
58         Returns:
59             int: Sum of all piece scores.
60         """
61         return (
62             Score.SPHINX * board.bitboards.get_piece_count(Piece.SPHINX, colour) +
63             Score.PYRAMID * board.bitboards.get_piece_count(Piece.PYRAMID, colour)
64         +
65             Score.ANUBIS * board.bitboards.get_piece_count(Piece.ANUBIS, colour) +

```

```

64         Score.SCARAB * board.bitboards.get_piece_count(Piece.SCARAB, colour)
65     )
66
67     def evaluate_position(self, board, colour):
68         """
69         Evaluates the positional score for a given colour.
70
71         Args:
72             board (Board): The current board state.
73             colour (Colour): The colour to evaluate.
74
75         Returns:
76             int: Score representing positional advantage/disadvantage.
77         """
78         score = 0
79
80         for piece in Piece:
81             if piece == Piece.SPHINX:
82                 continue
83
84             piece_bitboard = board.bitboards.get_piece_bitboard(piece, colour)
85
86             for bitboard in occupied_squares(piece_bitboard):
87                 index = bitboard_to_index(bitboard)
88                 # Flip PSQT if using from blue player's perspective
89                 index = FLIP[index] if colour == Colour.BLUE else index
90
91                 score += PSQT[piece][index] * Score.POSITION
92
93         return score
94
95     def evaluate_mobility(self, board, colour):
96         """
97         Evaluates the mobility score for a given colour.
98
99         Args:
100             board (Board): The current board state.
101             colour (Colour): The colour to evaluate.
102
103         Returns:
104             int: Score on numerical representation of mobility.
105         """
106         number_of_moves = board.get_mobility(colour)
107         return number_of_moves * Score.MOVE
108
109     def evaluate_pharoah_safety(self, board, colour):
110         """
111         Evaluates the safety of the Pharoah for a given colour.
112
113         Args:
114             board (Board): The current board state.
115             colour (Colour): The colour to evaluate.
116
117         Returns:
118             int: Score representing mobility of the Pharoah.
119         """
120         pharoah_bitboard = board.bitboards.get_piece_bitboard(Piece.PHAROAH,
121             colour)
122
123         if pharoah_bitboard:
124             pharoah_available_moves = pop_count(board.get_valid_squares(
125                 pharoah_bitboard, colour))

```

```

124         return (8 - pharoah_available_moves) * Score.PHAROAH_SAFETY
125     else:
126         return 0

```

### 1.6.6 Multithreading

As described in Section ??, when the game starts, a `CPUThread` object is created with the selected CPU. The `start` method is called whenever it is the CPU's turn, passing the board as an argument to work on. Each run is also given a random ID, to ensure that only the right search is able to be forcibly terminated early. Using **multithreading** allows the game MVC to continue running smoothly while the CPU calculates its moves on a separate thread.

`cpu_thread.py`

```

1  import threading
2  import time
3  from data.managers.logs import initialise_logger
4
5  logger = initialise_logger(__name__)
6
7  class CPUThread(threading.Thread):
8      def __init__(self, cpu, verbose=False):
9          super().__init__()
10         self._stop_event = threading.Event()
11         self._running = True
12         self._verbose = verbose
13         self.daemon = True
14
15         self._board = None
16         self._cpu = cpu
17         self._id = None
18
19     def kill_thread(self):
20         """
21         Kills the CPU and terminates the thread by stopping the run loop.
22         """
23         self.stop_cpu(force=True)
24         self._running = False
25
26     def stop_cpu(self, id=None, force=False):
27         """
28         Kills the CPU's move search.
29
30         Args:
31             id (int, optional): Id of search to kill, only kills if matching.
32             force (bool, optional): Forcibly kill search regardless of id.
33         """
34         if self._id == id or force:
35             self._stop_event.set()
36             self._board = None
37
38     def start_cpu(self, board, id=None):
39         """
40         Starts the CPU's move search.
41
42         Args:
43             board (Board): The current board state.
44             id (int, optional): Id of current search.
45         """
46         self._stop_event.clear()
47         self._board = board

```

```

48         self._id = id
49
50     def run(self):
51         """
52         Periodically checks if the board variable is set.
53         If it is, then starts CPU search.
54         """
55         while self._running:
56             if self._board and self._cpu:
57                 self._cpu.find_move(self._board, self._stop_event)
58                 self.stop_cpu()
59             else:
60                 time.sleep(1)
61                 if self._verbose:
62                     logger.debug(f'(CPUThread.run) Thread {threading.get_native_id
        (()) idling...')

```

### 1.6.7 Zobrist Hashing

As described in Section ??, the `ZobristHasher` class provides methods to successively **hash** a given board for every move played, with the initial hash being generated in the `Board` class.

`zobrist_hasher.py`

```

1  from random import randint
2  from data.helpers.bitboard_helpers import bitboard_to_index
3  from data.utils.enums import Piece, Colour, Rotation
4
5  # Initialise random values for each piece type on every square
6  # (5 x 2 colours) pieces + 4 rotations, for 80 squares
7  zobrist_table = [[randint(0, 2 ** 64) for i in range(14)] for j in range(80)]
8  # Hash for when the red player's move
9  red_move_hash = randint(0, 2 ** 64)
10
11 # Maps piece to the correct random value
12 piece_lookup = {
13     Colour.BLUE: {
14         piece: i for i, piece in enumerate(Piece)
15     },
16     Colour.RED: {
17         piece: i + 5 for i, piece in enumerate(Piece)
18     },
19 }
20
21 # Maps rotation to the correct random value
22 rotation_lookup = {
23     rotation: i + 10 for i, rotation in enumerate(Rotation)
24 }
25
26 class ZobristHasher:
27     def __init__(self):
28         self.hash = 0
29
30     def get_piece_hash(self, index, piece, colour):
31         """
32         Gets the random value for the piece type on the given square.
33
34         Args:
35             index (int): The index of the square.
36             piece (Piece): The piece on the square.
37             colour (Colour): The colour of the piece.

```

```

38
39         Returns:
40             int: A 64-bit value.
41         """
42         piece_index = piece_lookup[colour][piece]
43         return zobrist_table[index][piece_index]
44
45     def get_rotation_hash(self, index, rotation):
46         """
47         Gets the random value for the rotation on the given square.
48
49         Args:
50             index (int): The index of the square.
51             rotation (Rotation): The rotation on the square.
52             colour (Colour): The colour of the piece.
53
54         Returns:
55             int: A 64-bit value.
56         """
57         rotation_index = rotation_lookup[rotation]
58         return zobrist_table[index][rotation_index]
59
60     def apply_piece_hash(self, bitboard, piece, colour):
61         """
62         Updates the Zobrist hash with a new piece.
63
64         Args:
65             bitboard (int): The bitboard representation of the square.
66             piece (Piece): The piece on the square.
67             colour (Colour): The colour of the piece.
68         """
69         index = bitboard_to_index(bitboard)
70         piece_hash = self.get_piece_hash(index, piece, colour)
71         self.hash ^= piece_hash
72
73     def apply_rotation_hash(self, bitboard, rotation):
74         """Updates the Zobrist hash with a new rotation.
75
76         Args:
77             bitboard (int): The bitboard representation of the square.
78             rotation (Rotation): The rotation on the square.
79         """
80         index = bitboard_to_index(bitboard)
81         rotation_hash = self.get_rotation_hash(index, rotation)
82         self.hash ^= rotation_hash
83
84     def apply_red_move_hash(self):
85         """
86         Applies the Zobrist hash for the red player's move.
87         """
88         self.hash ^= red_move_hash

```

### 1.6.8 Cache

As described in Section ??, the `TranspositionTable` class maintains an internal hash map to store already evaluated board positions. Since I have chosen to use a dictionary instead of an array, the Zobrist hash for the board can be used as the keys for the dictionary as is, as it doesn't correspond to the index position as will be the case if I use an array.

`transposition_table.py`



```

1  from data.utils.enums import TranspositionFlag
2
3  class TranspositionEntry:
4      def __init__(self, score, move, flag, hash_key, depth):
5          self.score = score
6          self.move = move
7          self.flag = flag
8          self.hash_key = hash_key
9          self.depth = depth
10
11 class TranspositionTable:
12     def __init__(self, max_entries=100000):
13         self._max_entries = max_entries
14         self._table = dict()
15
16     def calculate_entry_index(self, hash_key):
17         """
18         Gets the dictionary key for a given Zobrist hash.
19
20         Args:
21             hash_key (int): A Zobrist hash.
22
23         Returns:
24             int: Key for the given hash.
25         """
26         return hash_key
27
28     def insert_entry(self, score, move, hash_key, depth, alpha, beta):
29         """
30         Inserts an entry into the transposition table.
31
32         Args:
33             score (int): The evaluation score.
34             move (Move): The best move found.
35             hash_key (int): The Zobrist hash key.
36             depth (int): The depth of the search.
37             alpha (int): The upper bound value.
38             beta (int): The lower bound value.
39
40         Raises:
41             Exception: Invalid depth or score.
42         """
43         if depth == 0 or alpha < score < beta:
44             flag = TranspositionFlag.EXACT
45             score = score
46         elif score <= alpha:
47             flag = TranspositionFlag.UPPER
48             score = alpha
49         elif score >= beta:
50             flag = TranspositionFlag.LOWER
51             score = beta
52         else:
53             raise Exception('(TranspositionTable.insert_entry)')
54
55         self._table[self.calculate_entry_index(hash_key)] = TranspositionEntry(
56             score, move, flag, hash_key, depth)
57
58         if len(self._table) > self._max_entries:
59             # Removes the longest-existing entry to free up space for more up-to-
60             # date entries
61             # Expression to remove leftmost item taken from https://docs.python.org/3/library/collections.html#ordereddict-objects

```

```

60         (k := next(iter(self._table)), self._table.pop(k))
61
62     def get_entry(self, hash_key, depth, alpha, beta):
63         """
64         Gets an entry from the transposition table.
65
66         Args:
67             hash_key (int): The Zobrist hash key.
68             depth (int): The depth of the search.
69             alpha (int): The alpha value for pruning.
70             beta (int): The beta value for pruning.
71
72         Returns:
73             tuple[int, Move] | tuple[None, None]: The evaluation score and the
74             best move found, if entry exists.
75         """
76         index = self.calculate_entry_index(hash_key)
77
78         if index not in self._table:
79             return None, None
80
81         entry = self._table[index]
82
83         if entry.hash_key == hash_key and entry.depth >= depth:
84             if entry.flag == TranspositionFlag.EXACT:
85                 return entry.score, entry.move
86
87             if entry.flag == TranspositionFlag.LOWER and entry.score >= beta:
88                 return entry.score, entry.move
89
90             if entry.flag == TranspositionFlag.UPPER and entry.score <= alpha:
91                 return entry.score, entry.move
92
93         return None, None

```

## 1.7 States

To switch between different screens, I have decided to use a state machine design pattern. This ensures that there is only one main game loop controlling movement between states, handled with the `Control` object. All `State` object contain a `next` and `previous` attribute to tell the `Control` class which screen to switch to, which also calls all `State` methods accordingly.

The `startup` method is called when switched to a new state, and `cleanup` when exiting. Within the `startup` function, the state widgets dictionary is passed into a `WidgetGroup` object. The `process_event` method is called on the `WidgetGroup` every frame to process user input, and handle the returned events accordingly. The `WidgetGroup` object can therefore be thought of as a controller, and the state as the model, and the widgets as the view.

### 1.7.1 Review

The `Review` state uses this logic to allow users to scroll through moves in their past games. All moves are stored in two stacks, as described in Section ??, and exchanged using `pop` and `append` (push) methods.

`review.py`

```

1 import pygame
2 from collections import deque

```

```

3 from data.states.game.components.capture_draw import CaptureDraw
4 from data.states.game.components.piece_group import PieceGroup
5 from data.states.game.components.laser_draw import LaserDraw
6 from data.helpers.bitboard_helpers import bitboard_to_coords
7 from data.helpers.browser_helpers import get_winner_string
8 from data.states.review.widget_dict import REVIEW_WIDGETS
9 from data.states.game.components.board import Board
10 from data.utils.event_types import ReviewEventType
11 from data.components.game_entry import GameEntry
12 from data.managers.logs import initialise_logger
13 from data.utils.constants import ShaderType
14 from data.managers.window import window
15 from data.utils.assets import MUSIC
16 from data.utils.enums import Colour
17 from data.control import _State
18
19 logger = initialise_logger(__name__)
20
21 class Review(_State):
22     def __init__(self):
23         super().__init__()
24
25         self._moves = deque()
26         self._popped_moves = deque()
27         self._game_info = {}
28
29         self._board = None
30         self._piece_group = None
31         self._laser_draw = None
32         self._capture_draw = None
33
34     def cleanup(self):
35         """
36         Cleanup function. Clears shader effects.
37         """
38         super().cleanup()
39
40         window.clear_apply_arguments(ShaderType.BLOOM)
41         window.clear_effect(ShaderType.RAYS)
42
43         return None
44
45     def startup(self, persist):
46         """
47         Startup function. Initialises all objects, widgets and game data.
48
49         Args:
50             persist (dict): Dict containing game entry data.
51         """
52         super().startup(REVIEW_WIDGETS, MUSIC['review'])
53
54         window.set_apply_arguments(ShaderType.BASE, background_type=ShaderType.
BACKGROUND_WAVES)
55         window.set_apply_arguments(ShaderType.BLOOM, highlight_colours=[(pygame.
Color('0x95e0cc')).rgb, pygame.Color('0xf14e52').rgb], colour_intensity=0.8)
56         REVIEW_WIDGETS['help'].kill()
57
58         self._moves = deque(GameEntry.parse_moves(persist.pop('moves', '')))
59         self._popped_moves = deque()
60         self._game_info = persist
61
62         self._board = Board(self._game_info['start_fen_string'])

```

```

63         self._piece_group = PieceGroup()
64         self._laser_draw = LaserDraw(self.board_position, self.board_size)
65         self._capture_draw = CaptureDraw(self.board_position, self.board_size)
66
67         self.initialise_widgets()
68         self.simulate_all_moves()
69         self.refresh_pieces()
70         self.refresh_widgets()
71
72         self.draw()
73
74     @property
75     def board_position(self):
76         return REVIEW_WIDGETS['chessboard'].position
77
78     @property
79     def board_size(self):
80         return REVIEW_WIDGETS['chessboard'].size
81
82     @property
83     def square_size(self):
84         return self.board_size[0] / 10
85
86     def initialise_widgets(self):
87         """
88         Initializes the widgets for a new game.
89         """
90         REVIEW_WIDGETS['move_list'].reset_move_list()
91         REVIEW_WIDGETS['move_list'].kill()
92         REVIEW_WIDGETS['scroll_area'].set_image()
93
94         REVIEW_WIDGETS['winner_text'].set_text(f'WINNER: {get_winner_string(self._game_info["winner"])}')
95         REVIEW_WIDGETS['blue_piece_display'].reset_piece_list()
96         REVIEW_WIDGETS['red_piece_display'].reset_piece_list()
97
98         if self._game_info['time_enabled']:
99             REVIEW_WIDGETS['timer_disabled_text'].kill()
100         else:
101             REVIEW_WIDGETS['blue_timer'].kill()
102             REVIEW_WIDGETS['red_timer'].kill()
103
104     def refresh_widgets(self):
105         """
106         Refreshes the widgets after every move.
107         """
108         REVIEW_WIDGETS['move_number_text'].set_text(f'MOVE NO: {(len(self._moves)) / 2:.1f} / {(len(self._moves) + len(self._popped_moves)) / 2:.1f}')
109         REVIEW_WIDGETS['move_colour_text'].set_text(f'{self.calculate_colour().name} TO MOVE')
110
111         if self._game_info['time_enabled']:
112             if len(self._moves) == 0:
113                 REVIEW_WIDGETS['blue_timer'].set_time(float(self._game_info['time']
114 ] * 60 * 1000)
115                 REVIEW_WIDGETS['red_timer'].set_time(float(self._game_info['time']
116 ] * 60 * 1000)
117             else:
118                 REVIEW_WIDGETS['blue_timer'].set_time(float(self._moves[-1]['blue_time']
119 ] * 60 * 1000)
120                 REVIEW_WIDGETS['red_timer'].set_time(float(self._moves[-1]['red_time']
121 ] * 60 * 1000)

```

```

118
119         REVIEW_WIDGETS['scroll_area'].set_image()
120
121     def refresh_pieces(self):
122         """
123         Refreshes the pieces on the board.
124         """
125         self._piece_group.initialise_pieces(self._board.get_piece_list(), self.
board_position, self.board_size)
126
127     def simulate_all_moves(self):
128         """
129         Simulates all moves at the start of every game to obtain laser results and
fill up piece display and move list widgets.
130         """
131         for index, move_dict in enumerate(self._moves):
132             laser_result = self._board.apply_move(move_dict['move'], fire_laser=
True)
133             self._moves[index]['laser_result'] = laser_result
134
135             if laser_result.hit_square_bitboard:
136                 if laser_result.piece_colour == Colour.BLUE:
137                     REVIEW_WIDGETS['red_piece_display'].add_piece(laser_result.
piece_hit)
138                 elif laser_result.piece_colour == Colour.RED:
139                     REVIEW_WIDGETS['blue_piece_display'].add_piece(laser_result.
piece_hit)
140
141             REVIEW_WIDGETS['move_list'].append_to_move_list(move_dict['
unparsed_move'])
142
143     def calculate_colour(self):
144         """
145         Calculates the current active colour to move.
146
147         Returns:
148             Colour: The current colour to move.
149         """
150         if self._game_info['start_fen_string'][-1].lower() == 'b':
151             initial_colour = Colour.BLUE
152         elif self._game_info['start_fen_string'][-1].lower() == 'r':
153             initial_colour = Colour.RED
154
155         if len(self._moves) % 2 == 0:
156             return initial_colour
157         else:
158             return initial_colour.get_flipped_colour()
159
160     def handle_move(self, move, add_piece=True):
161         """
162         Handles applying or undoing a move.
163
164         Args:
165             move (dict): The move to handle.
166             add_piece (bool): Whether to add the captured piece to the display.
Defaults to True.
167         """
168         laser_result = move['laser_result']
169         active_colour = self.calculate_colour()
170         self._laser_draw.add_laser(laser_result, laser_colour=active_colour)
171
172         if laser_result.hit_square_bitboard:

```

```

173         if laser_result.piece_colour == Colour.BLUE:
174             if add_piece:
175                 REVIEW_WIDGETS['red_piece_display'].add_piece(laser_result.
piece_hit)
176             else:
177                 REVIEW_WIDGETS['red_piece_display'].remove_piece(laser_result.
piece_hit)
178         elif laser_result.piece_colour == Colour.RED:
179             if add_piece:
180                 REVIEW_WIDGETS['blue_piece_display'].add_piece(laser_result.
piece_hit)
181             else:
182                 REVIEW_WIDGETS['blue_piece_display'].remove_piece(laser_result
.piece_hit)
183
184         self._capture_draw.add_capture(
185             laser_result.piece_hit,
186             laser_result.piece_colour,
187             laser_result.piece_rotation,
188             bitboard_to_coords(laser_result.hit_square_bitboard),
189             laser_result.laser_path[0][0],
190             active_colour,
191             shake=False
192         )
193
194     def update_laser_mask(self):
195         """
196         Updates the laser mask for the light rays effect.
197         """
198         temp_surface = pygame.Surface(window.size, pygame.SRCALPHA)
199         self._piece_group.draw(temp_surface)
200         mask = pygame.mask.from_surface(temp_surface, threshold=127)
201         mask_surface = mask.to_surface(unsetcolor=(0, 0, 0, 255), setcolor=(255,
0, 0, 255))
202
203         window.set_apply_arguments(ShaderType.RAYS, occlusion=mask_surface)
204
205     def get_event(self, event):
206         """
207         Processes Pygame events.
208
209         Args:
210             event (pygame.event.Event): The event to handle.
211         """
212         if event.type in [pygame.MOUSEBUTTONDOWN, pygame.KEYDOWN]:
213             REVIEW_WIDGETS['help'].kill()
214
215         widget_event = self._widget_group.process_event(event)
216
217         if widget_event is None:
218             return
219
220         match widget_event.type:
221             case None:
222                 return
223
224             case ReviewEventType.MENU_CLICK:
225                 self.next = 'menu'
226                 self.done = True
227
228             case ReviewEventType.PREVIOUS_CLICK:
229                 if len(self._moves) == 0:

```

```

230         return
231
232         # Pop last applied move off first stack
233         move = self._moves.pop()
234         # Pushed onto second stack
235         self._popped_moves.append(move)
236
237         # Undo last applied move
238         self._board.undo_move(move['move'], laser_result=move['
laser_result'])
239         self.handle_move(move, add_piece=False)
240         REVIEW_WIDGETS['move_list'].pop_from_move_list()
241
242         self.refresh_pieces()
243         self.refresh_widgets()
244         self.update_laser_mask()
245
246         case ReviewEventType.NEXT_CLICK:
247             if len(self._popped_moves) == 0:
248                 return
249
250             # Peek at second stack to get last undone move
251             move = self._popped_moves[-1]
252
253             # Reapply last undone move
254             self._board.apply_move(move['move'])
255             self.handle_move(move, add_piece=True)
256             REVIEW_WIDGETS['move_list'].append_to_move_list(move['
unparsed_move'])
257
258             # Pop last undone move from second stack
259             self._popped_moves.pop()
260             # Push onto first stack
261             self._moves.append(move)
262
263             self.refresh_pieces()
264             self.refresh_widgets()
265             self.update_laser_mask()
266
267         case ReviewEventType.HELP_CLICK:
268             self._widget_group.add(REVIEW_WIDGETS['help'])
269             self._widget_group.handle_resize(window.size)
270
271     def handle_resize(self):
272         """
273         Handles resizing of the window.
274         """
275         super().handle_resize()
276         self._piece_group.handle_resize(self.board_position, self.board_size)
277         self._laser_draw.handle_resize(self.board_position, self.board_size)
278         self._capture_draw.handle_resize(self.board_position, self.board_size)
279
280         if self._laser_draw.firing:
281             self.update_laser_mask()
282
283     def draw(self):
284         """
285         Draws all components onto the window screen.
286         """
287         self._capture_draw.update()
288         self._widget_group.draw()
289         self._piece_group.draw(window.screen)

```

```

290         self._laser_draw.draw(window.screen)
291         self._capture_draw.draw(window.screen)

```

## 1.8 Database

This section outlines my database implementation using the Python module `sqlite3`.

### 1.8.1 DDL

As mentioned in Section ??, the `migrations` directory contains a collection of Python scripts that edit the game table schema. The files are named with a description of their changes and datetime for organisational purposes.

`create_games_table_19112024.py`

```

1  import sqlite3
2  from pathlib import Path
3
4  database_path = (Path(__file__).parent / '../database.db').resolve()
5
6  def upgrade():
7      """
8      Upgrade function to create games table.
9      """
10     connection = sqlite3.connect(database_path)
11     cursor = connection.cursor()
12
13     cursor.execute('''
14         CREATE TABLE games(
15             id INTEGER PRIMARY KEY,
16             cpu_enabled INTEGER NOT NULL,
17             cpu_depth INTEGER,
18             winner INTEGER,
19             time_enabled INTEGER NOT NULL,
20             time REAL,
21             number_of_ply INTEGER NOT NULL,
22             moves TEXT NOT NULL
23         )
24     ''')
25
26     connection.commit()
27     connection.close()
28
29  def downgrade():
30      """
31      Downgrade function to revert table creation.
32      """
33     connection = sqlite3.connect(database_path)
34     cursor = connection.cursor()
35
36     cursor.execute('''
37         DROP TABLE games
38     ''')
39
40     connection.commit()
41     connection.close()
42
43  upgrade()
44  # downgrade()

```



Using the ALTER command allows me to rename table columns.

change\_fen\_string\_column\_name\_23122024.py

```
1 import sqlite3
2 from pathlib import Path
3
4 database_path = (Path(__file__).parent / '../database.db').resolve()
5
6 def upgrade():
7     """
8     Upgrade function to rename fen_string column.
9     """
10    connection = sqlite3.connect(database_path)
11    cursor = connection.cursor()
12
13    cursor.execute('''
14        ALTER TABLE games RENAME COLUMN fen_string TO final_fen_string
15    ''')
16
17    connection.commit()
18    connection.close()
19
20 def downgrade():
21     """
22     Downgrade function to revert fen_string column renaming.
23     """
24    connection = sqlite3.connect(database_path)
25    cursor = connection.cursor()
26
27    cursor.execute('''
28        ALTER TABLE games RENAME COLUMN final_fen_string TO fen_string
29    ''')
30
31    connection.commit()
32    connection.close()
33
34 upgrade()
35 # downgrade()
```

## 1.8.2 DML

As described in Section ??, this file provides functions to help modify the database, with **Aggregate** and **Window** commands used to retrieve the number of rows and sort them to be returned. database\_helpers.py

```
1 import sqlite3
2 from pathlib import Path
3 from datetime import datetime
4
5 database_path = (Path(__file__).parent / '../database/database.db').resolve()
6
7 def insert_into_games(game_entry):
8     """
9     Inserts a new row into games table.
10
11    Args:
12        game_entry (GameEntry): GameEntry object containing game information.
13    """
14    connection = sqlite3.connect(database_path, detect_types=sqlite3.PARSE_DECLTYPES)
```

```

15     connection.row_factory = sqlite3.Row
16     cursor = connection.cursor()
17
18     # Datetime added for created_dt column
19     game_entry = (*game_entry, datetime.now())
20
21     cursor.execute('''
22         INSERT INTO games (cpu_enabled, cpu_depth, winner, time_enabled, time,
23         number_of_ply, moves, start_fen_string, final_fen_string, created_dt)
24         VALUES (?, ?, ?, ?, ?, ?, ?, ?, ?, ?)
25     ''', game_entry)
26
27     connection.commit()
28
29     # Return inserted row
30     cursor.execute('''
31         SELECT * FROM games WHERE id = LAST_INSERT_ROWID()
32     ''')
33     inserted_row = cursor.fetchone()
34
35     connection.close()
36
37     return dict(inserted_row)
38
39 def get_all_games():
40     """
41     Get all rows in games table.
42
43     Returns:
44         list[dict]: List of game entries represented as dictionaries.
45     """
46     connection = sqlite3.connect(database_path, detect_types=sqlite3.
47     PARSE_DECLTYPES)
48     connection.row_factory = sqlite3.Row
49     cursor = connection.cursor()
50
51     cursor.execute('''
52         SELECT * FROM games
53     ''')
54     games = cursor.fetchall()
55
56     connection.close()
57
58     return [dict(game) for game in games]
59
60 def delete_all_games():
61     """
62     Delete all rows in games table.
63     """
64     connection = sqlite3.connect(database_path)
65     cursor = connection.cursor()
66
67     cursor.execute('''
68         DELETE FROM games
69     ''')
70
71     connection.commit()
72     connection.close()
73
74 def delete_game(id):
75     """
76     Deletes specific row in games table using id attribute.

```

```

75
76     Args:
77         id (int): Primary key for row.
78     """
79     connection = sqlite3.connect(database_path)
80     cursor = connection.cursor()
81
82     cursor.execute('''
83         DELETE FROM games WHERE id = ?
84     ''', (id,))
85
86     connection.commit()
87     connection.close()
88
89 def get_ordered_games(column, ascend=True, start_row=1, end_row=10):
90     """
91     Get specific number of rows from games table ordered by a specific column(s).
92
93     Args:
94         column (_type_): Column to sort by.
95         ascend (bool, optional): Sort ascending or descending. Defaults to True.
96         start_row (int, optional): First row returned. Defaults to 1.
97         end_row (int, optional): Last row returned. Defaults to 10.
98
99     Raises:
100         ValueError: If ascend argument or column argument are invalid types.
101
102     Returns:
103         list[dict]: List of ordered game entries represented as dictionaries.
104     """
105     if not isinstance(ascend, bool) or not isinstance(column, str):
106         raise ValueError('(database_helpers.get_ordered_games) Invalid input arguments!')
107
108     connection = sqlite3.connect(database_path, detect_types=sqlite3.PARSE_DECLTYPES)
109     connection.row_factory = sqlite3.Row
110     cursor = connection.cursor()
111
112     # Match ascend bool to correct SQL keyword
113     if ascend:
114         ascend_arg = 'ASC'
115     else:
116         ascend_arg = 'DESC'
117
118     # Partition by winner, then order by time and number_of_ply
119     if column == 'winner':
120         cursor.execute(f'''
121             SELECT * FROM
122                 (SELECT ROW_NUMBER() OVER (
123                     PARTITION BY winner
124                     ORDER BY time {ascend_arg}, number_of_ply {ascend_arg}
125                 ) AS row_num, * FROM games)
126             WHERE row_num >= ? AND row_num <= ?
127         ''', (start_row, end_row))
128     else:
129         # Order by time or number_of_ply only
130         cursor.execute(f'''
131             SELECT * FROM
132                 (SELECT ROW_NUMBER() OVER (
133                     ORDER BY {column} {ascend_arg}
134                 ) AS row_num, * FROM games)

```

```

135         WHERE row_num >= ? AND row_num <= ?
136         ''', (start_row, end_row))
137
138     games = cursor.fetchall()
139
140     connection.close()
141
142     return [dict(game) for game in games]
143
144 def get_number_of_games():
145     """
146     Returns:
147         int: Number of rows in the games.
148     """
149     connection = sqlite3.connect(database_path)
150     cursor = connection.cursor()
151
152     cursor.execute("""
153         SELECT COUNT(ROWID) FROM games
154     """)
155
156     result = cursor.fetchall()[0][0]
157
158     connection.close()
159
160     return result
161
162 # delete_all_games()

```

## 1.9 Shaders

### 1.9.1 Shader Manager

The `ShaderManager` class is responsible for handling all shader passes, handling the Pygame display, and combining both and drawing the result to the window screen. The class also **inherits** from the `SMProtocol` class, an **interface** class containing all required `ShaderManager` methods and attributes to aid with syntax highlighting in the fragment shader classes.

Fragment shaders such as `Bloom` are applied by default, and others such as `Ray` are applied during runtime through calling methods on `ShaderManager`, and adding the appropriate fragment shader class to the internal shader pass list.

`shader.py`

```

1 from pathlib import Path
2 from array import array
3 import moderngl
4 from data.shaders.classes import shader_pass_lookup
5 from data.shaders.protocol import SMProtocol
6 from data.utils.constants import ShaderType
7
8 shader_path = (Path(__file__).parent / '../shaders/').resolve()
9
10 SHADER_PRIORITY = [
11     ShaderType.CRT,
12     ShaderType.SHAKE,
13     ShaderType.BLOOM,
14     ShaderType.CHROMATIC_ABBREVIATION,
15     ShaderType.RAYS,
16     ShaderType.GRAYSCALE,

```

```

17     ShaderType.BASE,
18 ]
19
20 pygame_quad_array = array('f', [
21     -1.0, 1.0, 0.0, 0.0,
22     1.0, 1.0, 1.0, 0.0,
23     -1.0, -1.0, 0.0, 1.0,
24     1.0, -1.0, 1.0, 1.0,
25 ])
26
27 opengl_quad_array = array('f', [
28     -1.0, -1.0, 0.0, 0.0,
29     1.0, -1.0, 1.0, 0.0,
30     -1.0, 1.0, 0.0, 1.0,
31     1.0, 1.0, 1.0, 1.0,
32 ])
33
34 class ShaderManager(SMProtocol):
35     def __init__(self, ctx: moderngl.Context, screen_size):
36         self._ctx = ctx
37         self._ctx.gc_mode = 'auto'
38
39         self._screen_size = screen_size
40         self._opengl_buffer = self._ctx.buffer(data=opengl_quad_array)
41         self._pygame_buffer = self._ctx.buffer(data=pygame_quad_array)
42         self._shader_list = [ShaderType.BASE]
43
44         self._vert_shaders = {}
45         self._frag_shaders = {}
46         self._programs = {}
47         self._vao = {}
48         self._textures = {}
49         self._shader_passes = {}
50         self.framebuffers = {}
51
52         self.load_shader(ShaderType.BASE)
53         self.load_shader(ShaderType._CALIBRATE)
54         self.create_framebuffer(ShaderType._CALIBRATE)
55
56     def load_shader(self, shader_type, **kwargs):
57         """
58         Loads a given shader by creating a VAO reading the corresponding .frag
59         file.
60
61         Args:
62             shader_type (ShaderType): The type of shader to load.
63             **kwargs: Additional arguments passed when initialising the fragment
64             shader class.
65         """
66         self._shader_passes[shader_type] = shader_pass_lookup[shader_type](self,
67 **kwargs)
68         self.create_vao(shader_type)
69
70     def clear_shaders(self):
71         """
72         Clears the shader list, leaving only the base shader.
73         """
74         self._shader_list = [ShaderType.BASE]
75
76     def create_vao(self, shader_type):
77         """
78         Creates a vertex array object (VAO) for the given shader type.

```

```

76
77
78     shader_type (ShaderType): The type of shader.
79     """
80     frag_name = shader_type[1:] if shader_type[0] == '_' else shader_type
81     vert_path = Path(shader_path / 'vertex/base.vert').resolve()
82     frag_path = Path(shader_path / f'fragments/{frag_name}.frag').resolve()
83
84     self._vert_shaders[shader_type] = vert_path.read_text()
85     self._frag_shaders[shader_type] = frag_path.read_text()
86
87     program = self._ctx.program(vertex_shader=self._vert_shaders[shader_type],
88 fragment_shader=self._frag_shaders[shader_type])
89     self._programs[shader_type] = program
90
91     if shader_type == ShaderType._CALIBRATE:
92         self._vaos[shader_type] = self._ctx.vertex_array(self._programs[
93 shader_type], [(self._pygame_buffer, '2f 2f', 'vert', 'texCoords')])
94     else:
95         self._vaos[shader_type] = self._ctx.vertex_array(self._programs[
96 shader_type], [(self._opengl_buffer, '2f 2f', 'vert', 'texCoords')])
97
98
99 def create_framebuffer(self, shader_type, size=None, filter=moderngl.NEAREST):
100     """
101     Creates a framebuffer for the given shader type.
102
103     Args:
104         shader_type (ShaderType): The type of shader.
105         size (tuple[int, int], optional): The size of the framebuffer.
106         Defaults to screen size.
107         filter (moderngl.Filter, optional): The texture filter. Defaults to
108         NEAREST.
109     """
110     texture_size = size or self._screen_size
111     texture = self._ctx.texture(size=texture_size, components=4)
112     texture.filter = (filter, filter)
113
114     self._textures[shader_type] = texture
115     self.framebuffers[shader_type] = self._ctx.framebuffer(color_attachments=[
116 self._textures[shader_type]])
117
118
119 def render_to_fbo(self, shader_type, texture, output_fbo=None, program_type=
120 None, use_image=True, **kwargs):
121     """
122     Applies the shaders and renders the resultant texture to a framebuffer
123     object (FBO).
124
125     Args:
126         shader_type (ShaderType): The type of shader.
127         texture (moderngl.Texture): The texture to render.
128         output_fbo (moderngl.Framebuffer, optional): The output framebuffer.
129         Defaults to None.
130         program_type (ShaderType, optional): The program type. Defaults to
131         None.
132         use_image (bool, optional): Whether to use the image uniform. Defaults
133         to True.
134         **kwargs: Additional uniforms for the fragment shader.
135     """
136     fbo = output_fbo or self.framebuffers[shader_type]
137     program = self._programs[program_type] if program_type else self._programs
138 [shader_type]
139     vao = self._vaos[program_type] if program_type else self._vaos[shader_type]

```

```

126
127     fbo.use()
128     texture.use(0)
129
130     if use_image:
131         program['image'] = 0
132     for uniform, value in kwargs.items():
133         program[uniform] = value
134
135     vao.render(mode=moderngl.TRIANGLE_STRIP)
136
137 def apply_shader(self, shader_type, **kwargs):
138     """
139     Applies a shader of the given type and adds it to the list.
140
141     Args:
142         shader_type (ShaderType): The type of shader to apply.
143
144     Raises:
145         ValueError: If the shader is already being applied.
146     """
147     if shader_type in self._shader_list:
148         return
149
150     self.load_shader(shader_type, **kwargs)
151     self._shader_list.append(shader_type)
152
153     # Sort shader list based on the order in SHADER_PRIORITY, so that more
154     # important shaders are applied first
155     self._shader_list.sort(key=lambda shader: -SHADER_PRIORITY.index(shader))
156
157 def remove_shader(self, shader_type):
158     """
159     Removes a shader of the given type from the list.
160
161     Args:
162         shader_type (ShaderType): The type of shader to remove.
163     """
164     if shader_type in self._shader_list:
165         self._shader_list.remove(shader_type)
166
167 def render_output(self):
168     """
169     Renders the final output to the screen.
170
171     # Render to the screen framebuffer
172     self._ctx.screen.use()
173
174     # Take the texture of the last framebuffer to be rendered to, and render
175     # that to the screen framebuffer
176     output_shader_type = self._shader_list[-1]
177     self.get_fbo_texture(output_shader_type).use(0)
178     self._programs[output_shader_type]['image'] = 0
179
180     self._vaos[output_shader_type].render(mode=moderngl.TRIANGLE_STRIP)
181
182 def get_fbo_texture(self, shader_type):
183     """
184     Gets the texture from the specified shader type's FBO.
185
186     Args:
187         shader_type (ShaderType): The type of shader.

```

```

186
187     Returns:
188         moderngl.Texture: The texture from the FBO.
189     """
190     return self.framebuffers[shader_type].color_attachments[0]
191
192 def calibrate_pygame_surface(self, pygame_surface):
193     """
194     Converts the Pygame window surface into an OpenGL texture.
195
196     Args:
197         pygame_surface (pygame.Surface): The finished Pygame surface.
198
199     Returns:
200         moderngl.Texture: The calibrated texture.
201     """
202     texture = self._ctx.texture(pygame_surface.size, 4)
203     texture.filter = (moderngl.NEAREST, moderngl.NEAREST)
204     texture.swizzle = 'BGRA'
205     # Take the Pygame surface's pixel array and draw it to the new texture
206     texture.write(pygame_surface.get_view('1'))
207
208     # ShaderType._CALIBRATE has a VAO containing the pygame_quad_array
209     # coordinates, as Pygame uses different texture coordinates than ModernGL
210     # textures
211     self.render_to_fbo(ShaderType._CALIBRATE, texture)
212     return self.get_fbo_texture(ShaderType._CALIBRATE)
213
214 def draw(self, surface, arguments):
215     """
216     Draws the Pygame surface with shaders applied to the screen.
217
218     Args:
219         surface (pygame.Surface): The final Pygame surface.
220         arguments (dict): A dict of { ShaderType: Args } items, containing
221         keyword arguments for every fragment shader.
222     """
223     self._ctx.viewport = (0, 0, *self._screen_size)
224     texture = self.calibrate_pygame_surface(surface)
225
226     for shader_type in self._shader_list:
227         self._shader_passes[shader_type].apply(texture, **arguments.get(
228             shader_type, {}))
229         texture = self.get_fbo_texture(shader_type)
230
231     self.render_output()
232
233 def __del__(self):
234     """
235     Cleans up ModernGL resources when the ShaderManager object is deleted.
236     """
237     self.cleanup()
238
239 def cleanup(self):
240     """
241     Cleans up resources used by the ModernGL.
242     Probably unnecessary as the 'auto' garbage collection mode is used.
243     """
244     self._pygame_buffer.release()
245     self._opengl_buffer.release()
246     for program in self._programs:
247         self._programs[program].release()

```



```

244         for texture in self._textures:
245             self._textures[texture].release()
246         for vao in self._vaos:
247             self._vaos[vao].release()
248         for framebuffer in self.framebuffers:
249             self.framebuffers[framebuffer].release()
250
251     def handle_resize(self, new_screen_size):
252         """
253         Handles resizing of the screen.
254
255         Args:
256             new_screen_size (tuple[int, int]): The new screen size.
257         """
258         self._screen_size = new_screen_size
259
260         # Recreate all framebuffers to prevent scaling issues
261         for shader_type in self.framebuffers:
262             filter = self._textures[shader_type].filter[0]
263             self.create_framebuffer(shader_type, size=self._screen_size, filter=
filter)

```

## 1.9.2 Bloom

The `Bloom` shader effect is a common shader effect giving the illusion of a bright light. It consists of blurred fringes of light extending from the borders of bright areas. This effect can be achieved through obtaining all bright areas of the image, applying a Gaussian blur, and blending the blur additively onto the original image.

My `ShaderManager` class works with this multi-pass shader approach by reading the texture from the last shader's framebuffer for each pass.

### Extracting bright colours

The `highlight_brightness` fragment shader extracts all colours that are bright enough to exert the bloom effect.

`highlight_brightness.frag`

```

1  # version 330 core
2
3  in vec2 uvs;
4  out vec4 f_colour;
5
6  uniform sampler2D image;
7  uniform float threshold;
8  uniform float intensity;
9
10 void main() {
11     vec4 pixel = texture(image, uvs);
12     // Dot product used to calculate brightness of a pixel from its RGB values
13     // Values taken from https://en.wikipedia.org/wiki/Relative_luminance
14     float brightness = dot(pixel.rgb, vec3(0.2126, 0.7152, 0.0722));
15     float isBright = step(threshold, brightness);
16
17     f_colour = vec4(vec3(pixel.rgb * intensity) * isBright, 1.0);
18 }

```

## Blur

The `Blur` class implements a two-pass **Gaussian blur**. This is preferably over a one-pass blur, as the complexity is  $O(2n)$ , sampling  $n$  pixels twice, as opposed to  $O(n^2)$ . I have implemented this using the ping-pong technique, with the first pass for blurring the image horizontally, and the second pass for blurring vertically, and the resultant textures being passed repeatedly between two framebuffers.

`blur.py`

```
1 from data.shaders.protocol import SMPProtocol
2 from data.utils.constants import ShaderType
3
4 BLUR_ITERATIONS = 4
5
6 class _Blur:
7     def __init__(self, shader_manager: SMPProtocol):
8         self._shader_manager = shader_manager
9
10        shader_manager.create_framebuffer(ShaderType._BLUR)
11
12        shader_manager.create_framebuffer("blurPing")
13        shader_manager.create_framebuffer("blurPong")
14
15    def apply(self, texture):
16        """
17        Applies Gaussian blur to a given texture.
18
19        Args:
20            texture (moderngl.Texture): Texture to blur.
21        """
22        self._shader_manager.get_fbo_texture("blurPong").write(texture.read())
23
24        for _ in range(BLUR_ITERATIONS):
25            # Apply horizontal blur
26            self._shader_manager.render_to_fbo(
27                ShaderType._BLUR,
28                texture=self._shader_manager.get_fbo_texture("blurPong"),
29                output_fbo=self._shader_manager.framebuffers["blurPing"],
30                passes=5,
31                horizontal=True
32            )
33            # Apply vertical blur
34            self._shader_manager.render_to_fbo(
35                ShaderType._BLUR,
36                texture=self._shader_manager.get_fbo_texture("blurPing"), # Use
horizontal blur result as input texture
37                output_fbo=self._shader_manager.framebuffers["blurPong"],
38                passes=5,
39                horizontal=False
40            )
41
42        self._shader_manager.render_to_fbo(ShaderType._BLUR, self._shader_manager.
get_fbo_texture("blurPong"))
```

`blur.frag`

```
1 // Modified from https://learnopengl.com/Advanced-Lighting/Bloom
2 #version 330 core
3
4 in vec2 uvs;
```

```

5 out vec4 f_colour;
6
7 uniform sampler2D image;
8 uniform bool horizontal;
9 uniform int passes;
10 uniform float weight[5] = float[] (0.227027, 0.1945946, 0.1216216, 0.054054,
    0.016216);
11
12 void main() {
13     vec2 offset = 1.0 / textureSize(image, 0);
14     vec3 result = texture(image, uvs).rgb * weight[0];
15
16     if (horizontal) {
17         for (int i = 1 ; i < passes ; ++i) {
18             result += texture(image, uvs + vec2(offset.x * i, 0.0)).rgb * weight[i
19 ];
20             result += texture(image, uvs - vec2(offset.x * i, 0.0)).rgb * weight[i
21 ];
22         }
23     }
24     else {
25         for (int i = 1 ; i < passes ; ++i) {
26             result += texture(image, uvs + vec2(0.0, offset.y * i)).rgb * weight[i
27 ];
28             result += texture(image, uvs - vec2(0.0, offset.y * i)).rgb * weight[i
29 ];
30         }
31     }
32
33     f_colour = vec4(result, 1.0);
34 }

```

## Combining

The Bloom class combines the two operations, taking the highlighted areas, blurs them, and adds the RGB values for the final result onto the original texture to simulate bloom.

bloom.py

```

1 from data.shaders.classes.highlight_brightness import _HighlightBrightness
2 from data.shaders.classes.highlight_colour import _HighlightColour
3 from data.shaders.protocol import SMProtocol
4 from data.shaders.classes.blur import _Blur
5 from data.utils.constants import ShaderType
6
7 BLOOM_INTENSITY = 0.6
8
9 class Bloom:
10     def __init__(self, shader_manager: SMProtocol):
11         self._shader_manager = shader_manager
12
13         shader_manager.load_shader(ShaderType._BLUR)
14         shader_manager.load_shader(ShaderType._HIGHLIGHT_BRIGHTNESS)
15         shader_manager.load_shader(ShaderType._HIGHLIGHT_COLOUR)
16
17         shader_manager.create_framebuffer(ShaderType.BLOOM)
18         shader_manager.create_framebuffer(ShaderType._BLUR)
19         shader_manager.create_framebuffer(ShaderType._HIGHLIGHT_BRIGHTNESS)
20         shader_manager.create_framebuffer(ShaderType._HIGHLIGHT_COLOUR)
21

```

```

22     def apply(self, texture, highlight_surface=None, highlight_colours=[],
23               surface_intensity=BLOOM_INTENSITY, brightness_intensity=BLOOM_INTENSITY,
24               colour_intensity=BLOOM_INTENSITY):
25         """
26         Applies a bloom effect to a given texture.
27
28         Args:
29             texture (modernogl.Texture): Texture to apply bloom to.
30             highlight_surface (pygame.Surface, optional): Surface to use as the
31             highlights. Defaults to None.
32             highlight_colours (list[list[int, int, int], ...], optional): Colours
33             to use as the highlights. Defaults to [].
34             surface_intensity (_type_, optional): Intensity of bloom applied to
35             the highlight surface. Defaults to BLOOM_INTENSITY.
36             brightness_intensity (_type_, optional): Intensity of bloom applied to
37             the highlight brightness. Defaults to BLOOM_INTENSITY.
38             colour_intensity (_type_, optional): Intensity of bloom applied to the
39             highlight colours. Defaults to BLOOM_INTENSITY.
40         """
41         if highlight_surface:
42             # Calibrate Pygame surface and apply blur
43             glare_texture = self._shader_manager.calibrate_pygame_surface(
44             highlight_surface)
45             _Blur(self._shader_manager).apply(glare_texture)
46
47             self._shader_manager.get_fbo_texture(ShaderType._BLUR).use(1)
48             self._shader_manager.render_to_fbo(ShaderType.BLOOM, texture,
49             blurredImage=1, intensity=surface_intensity)
50
51             # Set bloom-applied texture as the base texture
52             texture = self._shader_manager.get_fbo_texture(ShaderType.BLOOM)
53
54             # Extract bright colours (highlights) from the texture
55             _HighlightBrightness(self._shader_manager).apply(texture, intensity=
56             brightness_intensity)
57             highlight_texture = self._shader_manager.get_fbo_texture(ShaderType.
58             _HIGHLIGHT_BRIGHTNESS)
59
60             # Use colour as highlights
61             for colour in highlight_colours:
62                 _HighlightColour(self._shader_manager).apply(texture, old_highlight=
63                 highlight_texture, colour=colour, intensity=colour_intensity)
64                 highlight_texture = self._shader_manager.get_fbo_texture(ShaderType.
65                 _HIGHLIGHT_COLOUR)
66
67             # Apply Gaussian blur to highlights
68             _Blur(self._shader_manager).apply(highlight_texture)
69
70             # Add the pixel values for the highlights onto the base texture
71             self._shader_manager.get_fbo_texture(ShaderType._BLUR).use(1)
72             self._shader_manager.render_to_fbo(ShaderType.BLOOM, texture, blurredImage
73             =1, intensity=BLOOM_INTENSITY)

```

### 1.9.3 Rays

As described in Section ??, the Ray shader is applied whenever the sphinx shoots a laser. It simulates a 2D light source, providing pixel perfect shadows, through the shadow mapping technique outlined in Section ?. The laser demo seen on the main menu screen is also achieved using the Ray shader, by clamping the angle at which it emits light to a narrower range.

## Occlusion

The occlusion fragment shader processes all pixels with a given colour value as being occluding.  
occlusion.frag

```
1 # version 330 core
2
3 in vec2 uvs;
4 out vec4 f_colour;
5
6 uniform sampler2D image;
7 uniform vec3 checkColour;
8
9 void main() {
10     vec4 pixel = texture(image, uvs);
11
12     // If pixel is occluding colour, set pixel to white
13     if (pixel.rgb == checkColour) {
14         f_colour = vec4(1.0, 1.0, 1.0, 1.0);
15     } else {
16         // Else, set pixel to black
17         f_colour = vec4(vec3(0.0), 1.0);
18     }
19 }
```

## Shadowmap

The shadowmap fragment shader takes the occluding texture and creates a 1D shadow map.  
shadowmap.frag

```
1 # version 330 core
2
3 #define PI 3.1415926536;
4
5 in vec2 uvs;
6 out vec4 f_colour;
7
8 uniform sampler2D image;
9 uniform float resolution;
10 uniform float THRESHOLD=0.99;
11
12 void main() {
13     float maxDistance = 1.0;
14
15     for (float y = 0.0 ; y < resolution ; y += 1.0) {
16         //rectangular to polar filter
17         float currDistance = y / resolution;
18
19         vec2 norm = vec2(uvs.x, currDistance) * 2.0 - 1.0; // Range from [0, 1] ->
20         [-1, 1]
21         float angle = (1.5 - norm.x) * PI; // Range from [-1, 1] -> [0.5PI, 2.5PI]
22         float radius = (1.0 + norm.y) * 0.5; // Range from [-1, 1] -> [0, 1]
23
24         //coord which we will sample from occlude map
25         vec2 coords = vec2(radius * -sin(angle), radius * -cos(angle)) / 2.0 +
26         0.5;
27
28         // Sample occlusion map
29         vec4 occluding = texture(image, coords);
30     }
```

```

29     // If pixel is not occluding (Red channel value below threshold), set
    maxDistance to current distance
30     // If pixel is occluding, don't change distance
31     // maxDistance therefore is the distance from the center to the nearest
    occluding pixel
32     maxDistance = max(maxDistance * step(occluding.r, THRESHOLD), min(
    maxDistance, currDistance));
33 }
34
35 f_colour = vec4(vec3(maxDistance), 1.0);
36 }

```

## Lightmap

The lightmap shader checks if a pixel is in shadow, blurs the result, and applies the radial light source.

lightmap.frag

```

1  # version 330 core
2
3  #define PI 3.14159265
4
5  in vec2 uvs;
6  out vec4 f_colour;
7
8  uniform float softShadow;
9  uniform float resolution;
10 uniform float falloff;
11 uniform vec3 lightColour;
12 uniform vec2 angleClamp;
13 uniform sampler2D occlusionMap;
14 uniform sampler2D image;
15
16 vec3 normLightColour = lightColour / 255;
17 vec2 radiansClamp = angleClamp * (PI / 180);
18
19 float sample(vec2 coord, float r) {
20     /*
21     Sample from the 1D distance map.
22
23     Returns:
24     float: 1.0 if sampled radius is greater than the passed radius, 0.0 if not.
25     */
26     return step(r, texture(image, coord).r);
27 }
28
29 void main() {
30     // Cartesian to polar transformation
31     // Range from [0, 1] -> [-1, 1]
32     vec2 norm = uvs.xy * 2.0 - 1.0;
33     float angle = atan(norm.y, norm.x);
34     float r = length(norm);
35
36     // The texture coordinates to sample our 1D lookup texture
37     // Always 0.0 on y-axis, as the texture is 1D
38     float x = (angle + PI) / (2.0 * PI); // Normalise angle to [0, 1]
39     vec2 tc = vec2(x, 0.0);
40
41     // Sample the 1D lookup texture to check if pixel is in light or in shadow
42     // Gives us hard shadows
43     // 1.0 -> in light, 0.0, -> in shadow

```

```

44 float inLight = sample(tc, r);
45 // Clamp angle so that only pixels within the range are in light
46 inLight = inLight * step(angle, radiansClamp.y) * step(radiansClamp.x, angle);
47
48 // Multiply the blur amount by the distance from the center
49 // So that the blurring increases as distance increases
50 float blur = (1.0 / resolution) * smoothstep(0.0, 0.1, r);
51
52 // Use gaussian blur to apply blur effect
53 float sum = 0.0;
54
55 sum += sample(vec2(tc.x - blur * 4.0, tc.y), r) * 0.05;
56 sum += sample(vec2(tc.x - blur * 3.0, tc.y), r) * 0.09;
57 sum += sample(vec2(tc.x - blur * 2.0, tc.y), r) * 0.12;
58 sum += sample(vec2(tc.x - blur * 1.0, tc.y), r) * 0.15;
59
60 sum += inLight * 0.16;
61
62 sum += sample(vec2(tc.x + blur * 1.0, tc.y), r) * 0.15;
63 sum += sample(vec2(tc.x + blur * 2.0, tc.y), r) * 0.12;
64 sum += sample(vec2(tc.x + blur * 3.0, tc.y), r) * 0.09;
65 sum += sample(vec2(tc.x + blur * 4.0, tc.y), r) * 0.05;
66
67 // Mix with the softShadow uniform to toggle degree of softShadows
68 float finalLight = mix(inLight, sum, softShadow);
69
70 // Multiply the final light value with the distance, to give a radial falloff
71 // Use as the alpha value, with the light colour being the RGB values
72 f_colour = vec4(normLightColour, finalLight * smoothstep(1.0, falloff, r));
73 }

```

## Class

The `Rays` class takes in a texture and array of light information, applies the aforementioned shaders, and blends the final result with the original texture.

`rays.py`

```

1 from data.shaders.classes.lightmap import _Lightmap
2 from data.shaders.classes.blend import _Blend
3 from data.shaders.protocol import SMPProtocol
4 from data.shaders.classes.crop import _Crop
5 from data.utils.constants import ShaderType
6
7 class Rays:
8     def __init__(self, shader_manager: SMPProtocol, lights):
9         self._shader_manager = shader_manager
10        self._lights = lights
11
12        # Load all necessary shaders
13        shader_manager.load_shader(ShaderType._LIGHTMAP)
14        shader_manager.load_shader(ShaderType._BLEND)
15        shader_manager.load_shader(ShaderType._CROP)
16        shader_manager.create_framebuffer(ShaderType.RAYS)
17
18    def apply(self, texture, occlusion=None, softShadow=0.3):
19        """
20        Applies the light rays effect to a given texture.
21
22        Args:
23            texture (moderngl.Texture): The texture to apply the effect to.

```

```

24         occlusion (pygame.Surface, optional): A Pygame mask surface to use as
the occlusion texture. Defaults to None.
25         """
26         final_texture = texture
27
28         # Iterate through array containing light information
29         for pos, radius, colour, *args in self._lights:
30             # Topleft of light source square
31             light_topleft = (pos[0] - (radius * texture.size[1] / texture.size[0])
, pos[1] - radius)
32             # Relative size of light compared to texture
33             relative_size = (radius * 2 * texture.size[1] / texture.size[0],
radius * 2)
34
35             # Crop texture to light source diameter, and to position light source
at the center
36             _Crop(self._shader_manager).apply(texture, relative_pos=light_topleft,
relative_size=relative_size)
37             cropped_texture = self._shader_manager.get_fbo_texture(ShaderType.
_CROP)
38
39             if occlusion:
40                 # Calibrate Pygame mask surface and crop it
41                 occlusion_texture = self._shader_manager.calibrate_pygame_surface(
occlusion)
42                 _Crop(self._shader_manager).apply(occlusion_texture, relative_pos=
light_topleft, relative_size=relative_size)
43                 occlusion_texture = self._shader_manager.get_fbo_texture(
ShaderType._CROP)
44             else:
45                 occlusion_texture = None
46
47             # Apply lightmap shader, shadowmap and occlusion are included within
the _Lightmap class
48             _Lightmap(self._shader_manager).apply(cropped_texture, colour,
softShadow, occlusion_texture, *args)
49             light_map = self._shader_manager.get_fbo_texture(ShaderType._LIGHTMAP)
50
51             # Blend the final result with the original texture
52             _Blend(self._shader_manager).apply(final_texture, light_map,
light_topleft)
53             final_texture = self._shader_manager.get_fbo_texture(ShaderType._BLEND
)
54
55             self._shader_manager.render_to_fbo(ShaderType.RAYS, final_texture)

```