

Dotpay Technical Support
Wielicka Str. 28B, 30-552 Cracow, Poland
phone. +48 12 688 26 00
e-mail: tech@dotpay.pl



Worldwide **secure** payment

SDK (Android)

Version 1.4.x



TABLE OF CONTENTS

Page | 2 / 34

| | |
|---|----|
| TABLE OF CONTENTS..... | 2 |
| INTRODUCTION | 4 |
| RELATED DOCUMENTS | 4 |
| Getting started with SDK..... | 5 |
| LANGUAGE SETTINGS | 5 |
| SYSTEM SELECTION | 6 |
| ADDITIONAL OPTIONS | 6 |
| BLOCK SCREENSHOT : | 6 |
| SDK VERSION | 6 |
| Payment process..... | 7 |
| REGISTERING RETURN CALLBACK | 7 |
| PAYMENT PROCESS INITIALIZATION | 7 |
| FINALIZING PAYMENT PROCESS..... | 10 |
| SUMMARY DETAILS | 11 |
| AVAILABLE CURRENCIES..... | 11 |
| CHANGING PRESENTATION STYLE | 12 |
| PERSONAL CHANNEL SELECTION CONTROL | 16 |
| FILTERING CHANNELS..... | 16 |
| CUSTOM ORDER SUMMARY CONTROLLER | 17 |
| Special channel support..... | 19 |
| CREDIT CARD PAYMENT - 1CLICK | 19 |
| INITIALIZING 1CLICK PAYMENT | 19 |
| USING BUILT-IN CARD MANAGEMENT CONTROLLER | 20 |
| CARD REGISTRATION REGULATIONS | 21 |
| CHANGING PRESENTATION STYLE | 22 |
| CUSTOM CARD MANAGEMENT CONTROLLER | 23 |
| 1. REGISTERED CARDS LIST | 23 |
| 2. CARD REGISTRATION | 23 |
| 3. DELETING CARD | 24 |
| 4. SETTING DEFAULT CARD | 24 |
| EXTERNAL CARDS DATA | 25 |
| 1. CARD REGISTRATION IN THE CONTEXT OF AN EXTERNAL USER | 27 |
| 2. CHANGE DEFAULT CARDS..... | 28 |
| MASKING THE CVV FILED | 28 |
| PAYMENT WITHOUT THE PAYMENT FORM. | 29 |
| MASTERPASS CHAMPION WALLET | 29 |
| ADDITIONAL PARAMETERS FOR PAYMENT INITIATION | 29 |
| PAYMENT AUTHORIZATION..... | 29 |
| GOOGLE PAY..... | 30 |
| Transaction history and status..... | 32 |
| THE USE OF BUILT-IN CONTROL..... | 32 |

| | |
|----------------------------------|----|
| CHANGING PRESENTATION STYLE..... | 32 |
| PERSONAL HISTORY CONTROL..... | 34 |

INTRODUCTION

Page | 4 / 34

This document describes a set of software development tools (SDK library) that allows integrating merchant's mobile application with Dotpay payment system.

Thanks to devolving as many steps from our web application as possible to mobile application, the payment process is more convenient for a user and a developer obtains more control over it.

There is an option to modify visualization style of SDK (colors, fonts) to have best integration possible with merchant's mobile application.

The SDK library was created in language Java. It supports Android system version 4.1 (API:16, JELLY BEAN) and higher. Due to Android system limitations related to supported versions of cryptographic algorithms (TLS 1.2), fully correct operation on the default configured device is possible from version 4.4.4 (API: 20). If you try to pay with no support for TLS 1.2, the payment will fail, the control will be returned to the application along with information about the process failure.

This document uses the following terms and symbols:

| | |
|-----------------------|--|
| Contractor / Merchant | Dotpay service user receiving the payment or owner of web shop, web page, on which payment process starts. |
| Shop | Merchant's web shop that uses mobile application. |
| Client / Buyer | The person making the payment to the merchant via the online transaction with a use of mobile application. |
| Developer | A developer, who creates mobile application for a merchant. |

Related documents

[Dotpay technical manual](#) – a document that describes a basic payment process for web shops, available for downloading in Dotpay panel.

Getting started with SDK

If you want to use the SDK you have to:

Page | 5 / 34

1. Add the appropriate sections to the gradle project in configuration file:

```
// Project build.gradle
allprojects {
    repositories {
        maven { url 'https://github.com/dotpay/Mobile-SDK-Android/raw/master/'
    }
    flatDir {
        dirs 'libs'
    }
}
// Module build.gradle
dependencies {

    // needed to compile Visa Checkout .aar, see paragraph below
    implementation fileTree(include: ['*.jar', '*.aar'], dir: 'libs')

    // Standard Dotpay SDK version
    implementation('pl.mobiltek.paymentsmobile:dotpay:1.4.18@aar') {
        transitive = true
    }
}
```

2. Add like below in AndroidManifest.xml file:

```
<application
    ...
    tools:replace="android:allowBackup"
    ...
</application>
```

3. Attach the Visa Checkout library manually, due to no distributed in the form of a gradle dependency. The correct version of the library for SDK 1.4.18 is 6.6.1, it can be downloaded from the visa_checkout_sdk subdirectory from the Dotpay SDK repository. The library should be attached to the libs directories of the project.
4. You need to initialize SDK before you can use it. Add in onCreate method in your Application class:

```
AppSDK.initialize(this);
```

Language settings

The SDK library, in a current version, supports Polish and English language. Further language extensions are planned so that dynamic configuration is recommended. In order to do this, you need to:

1. Download available languages list from PaymentManager:

```
PaymentManager.getInstance().getLanguages();
```

2. Select most appropriate language
3. Set a selected language

```
PaymentManager.getInstance().setApplicationLanguage(bestLang.getLang());
```

System selection

The SDK library may communicate both with Dotpay production and test environment. With no system selection SDK library won't work properly, therefore it is necessary to select a system.

In order to select the test system, you need to follow the instruction:

```
PaymentManager.getInstance().setApplicationVersion(Configuration.TEST_VERSION);
```

In order to select the production system, you need to follow the instruction:

```
PaymentManager.getInstance().setApplicationVersion(Configuration.RELEASE_VERSION);
```

Additional options

Switching off the last selected channel by a client:

```
Configuration.loadLastSelectedChannel(false);
```

Block screenshot :

```
PaymentManager.getInstance().enableSecureFlagOnWindows(true)
```

SDK version

We recommend to display the SDK version in the web shop which will make problems diagnostic process easier in the future. The SDK version is available using:

```
Settings.getSDKVersion();
```

Payment process

The payment process consists of handing over a control to the class `PaymentManager` and awaiting an error/success event that returns control.

Page | 7 / 34

The SDK library will guide the client through the process of selecting payment channel, passing on/verification client's data, selecting extra options, accepting proper terms of use and finalizing the payment process.

In the event of paying for real goods, payment status received from SDK is just informational, a right order status will be delivered in the backend system according to Dotpay technical manual.

In next chapters we described steps that are required to use `PaymentManager` class and extra options that enable adjusting payment process to own needs.

Registering return callback

Preparing payment process starts from creating callback functions that listen for signaled finish payment events. The `PaymentManagerCallback` interface should be implemented in a class, in which a payment will be initialized.

```
public interface PaymentManagerCallback {  
    void onPaymentSuccess(PaymentEndedEventArgs paymentEndedEventArgs);  
    void onPaymentFailure(PaymentEndedEventArgs paymentEndedEventArgs);  
}
```

And next register it in the `PaymentManager`:

```
PaymentManager.getInstance().setPaymentManagerCallback(paymentManagerCallback);
```

Payment process initialization

The payment process initialization starts from the use of `initialize` method of `PaymentManager`. This method receives arguments described in a table below. The initialization process has to take place in a current Android activity.

| PARAMETER | DESCRIPTION |
|--------------------|---|
| context | Type: Context Context, from which this method was called out |
| paymentInformation | Typ: PaymentInformation Object that contains all required parameters for payment process |

An object constructor of type `PaymentInformation` receives arguments in accordance with the following table:

| PARAMETER | DESCRIPTION |
|-------------|--|
| id | <u>Type</u> : string Merchant's ID number in Dotpay system |
| amount | <u>Type</u> : double Payment amount |
| description | <u>Type</u> : string Payment description |
| currency | <u>Type</u> : string <u>Default value</u> : "PLN" It describes currency of parameter amount. In the chapter Available currencies we described a way how to download available currency list. |

Additionally, there is possibility to set the following parameters for `PaymentInformation` object, using setters:

| PARAMETER | DESCRIPTION |
|-----------------------|---|
| senderInformation | <u>Type</u> : Map<string, string> <u>Default value</u> : null <u>Setter name</u> : <code>setSenderInformation(Map<String, String> senderInformation)</code> Additional information on client. Keys: "firstname"; "lastname"; "email"; "phone"; "phone_verified" – information about the phone number verified, "street"; "street_n1" – building number; "street_n2" – flat number; "postcode"; "city"; "country" (3 letters ISO3166). These values are not mandatory. We recommend to pass on at least firstname, lastname and email. The payment form should be filled out with that type of data. SDK will ask a client for missing data. Specific explanation of these fields is described in Dotpay technical manual . |
| additionalInformation | <u>Type</u> : Map<string, string> <u>Default value</u> : null |

| | |
|---------|--|
| | <p><u>Setter name:</u> <code>setAdditionalInformation (Map<String, String> additionalInformation)</code></p> <p>Extra parameters handed over in a payment process in accordance with additional technical manuals.</p> |
| control | <p><u>Type:</u> string</p> <p><u>Default value:</u> null</p> <p><u>Setter name:</u> <code>setControl (String)</code></p> <p>The parameter that defines a payment, handed over in payment confirmation, which is sent to a Shop. This parameter is required to match a payment status to an appropriate order in a Shop.</p> <p>More information you will find in the Dotpay technical manual.</p> <p>If not set, it is generated by SDK.</p> <p>ATTENTION</p> <p>To have properly working payment history, this parameter should be unique for every order.</p> |
| urlc | <p><u>Type:</u> string</p> <p><u>Default value:</u> null</p> <p><u>Setter name:</u> <code>setUrlc (String)</code></p> <p>URL address used for receiving payment information (order completed or rejected).</p> <p>More information you will find in the Dotpay technical manual.</p> |

Example of payment initialization:

```
String description = "order 12345";
double amount = 123.45;
PaymentInformation paymentInformation = new PaymentInformation(merchant_Id, amount,
description, selectedCurrency);

Map<String, String> sender = new Map<String, String> {"firstname", "Jan"},
{"lastname", "Kowalski"}, {"email", "jan.kowalski@test.pl"}}
Map<String, String> additional = new Map<String, String> {"id1", "12345"},
{"amount1", "100"}, {"id2", "67890"}, {"amount2", "23.45"}}

paymentInformation.setSenderInformation(sender);
paymentInformation.setAdditionalInformation(additional);
PaymentManager.getInstance().initialize(ShopActivity.this, paymentInformation);
```

Finalizing payment process

Page | 10 / 34

A correctly finalized payment process is signalized by calling out `onPaymentSuccess` method, while payment error (both in parameters initialization and in latter stage) is signalized by calling out `onPaymentFailure` method. These events have the type `PaymentEndedEventArgs` argument with the following details:

| PARAMETER | DESCRIPTION |
|-------------|--|
| Result | <p><u>Type</u>: <code>PaymentResult</code></p> <p>Information on payment (amount, currency, control, channel id).</p> <p>A payment status is located in a field <code>StateType</code>.</p> <p>This parameter has an empty value, if transaction finished with an error.</p> |
| ErrorResult | <p><u>Type</u>: <code>ProcessResult</code></p> <p>Describes the reason of finishing a payment process. A status different than "OK" means error. An announcement about payment problem should be displayed for a client.</p> |

Attention!!! A finalized payment process with a success doesn't mean the payment was processed, but it means the payment had no errors. A payment result will be returned in an appropriate event parameter.

Examples of event handlers:

```
private PaymentManagerCallback paymentManagerCallback = new PaymentManagerCallback() {  
    @Override  
    public void onPaymentSuccess(PaymentEndedEventArgs paymentEndedEventArgs) {  
        if(paymentEndedEventArgs.getPaymentResult().getStateType() == StateType.COMPLETED) {  
            // payment successful  
        } else if(paymentEndedEventArgs.getPaymentResult().getStateType() ==  
            StateType.REJECTED) {  
            // payment rejected  
        } else {  
            // payment in progress  
        }  
    }  
}  
  
@Override  
public void onPaymentFailure(PaymentEndedEventArgs paymentEndedEventArgs) {  
    // internal error during payment process,  
}  
};
```

Summary details

On summary page it is possible to enable additional details like description, status and amount. Disabled by default.

In order to enable this functionality call method:

```
Configuration.setPaymentDetailsResultEnable(true);
```

Available currencies

A list of currencies supported by Dotpay can be downloaded by the following method of PaymentManager:

```
PaymentManager.getInstance().getCurrencies()
```

Changing presentation style

Page | 12 / 34

In order to change presentation style of controls elements in a payment process, proper setters of Configuration singleton have to be set. Settings have to be executed before initializing PaymentManager parameters.

Global settings:

| PARAMETER | DESCRIPTION |
|-------------------------------|--|
| ToolBarBackgroundColor | <u>Type:</u> int Defines toolbar background color |
| ToolBarTitleTextColor | <u>Type:</u> int Defines toolbar text color |
| ButtonTitleTextColor | <u>Type:</u> int Defines button text color |
| ButtonBackgroundColorResource | <u>Type:</u> int Defines button background color |

Example:

```
Configuration.setToolBarBackgroundColor(R.color.red);  
Configuration.setToolBarTitleTextColor(R.color.white);  
Configuration.setButtonTitleTextColor(R.color.white);  
Configuration.setButtonBackgroundColorResource(R.drawable.colorfulBtn);
```

Channels selecting control:

| PARAMETER | DESCRIPTION |
|---------------------------------|--|
| ChannelBackgroundColor | <u>Type:</u> int Defines view background color |
| ChannelBackgroundItemColor | <u>Type:</u> int Defines a single tile background color |
| ChannelBackgroundPressItemColor | <u>Type:</u> int Defines tile background color when pressed |
| ChannelItemTextColor | <u>Type:</u> int Defines tile text color |
| ChannelTextGravity | <u>Type:</u> int Defines tile text placement |

Page | 13 / 34

Example:

```
Configuration.setChannelBackgroundColor(R.color.white);  
Configuration.setChannelBackgroundItemColor(R.color.gray);  
Configuration.setChannelBackgroundPressItemColor(R.color.green);  
Configuration.setChannelTextGravity(Gravity.CENTER_HORIZONTAL);  
Configuration.setChannelItemTextColor(R.color.black);
```

Favorite payment channel controller:

| PARAMETER | DESCRIPTION |
|---|--|
| FavoriteChannelBackgroundItemColor | <u>Type:</u> int Defines a single tile background color |
| FavoriteChannelBackgroundPressItemColor | <u>Type:</u> int Defines tile background color when pressed |

| | |
|------------------------------|---|
| FavoriteChannelItemTextStyle | <u>Type:</u> int Defines tile text style |
|------------------------------|---|

Example:

```
Configuration.setFavoriteChannelBackgroundItemColor(R.color.white);  
Configuration.setFavoriteChannelBackgroundPressItemColor(R.color.gray);
```

Payment method change controller:

| PARAMETER | DESCRIPTION |
|-------------------------------|---|
| PaymentFormBackgroundColor | <u>Type:</u> int Defines the background color of the view |
| PaymentFormChannelText | <u>Type:</u> int Defines text in channel change controller |
| PaymentFormChannelTextColor | <u>Type:</u> int Defines text color in controller |
| PaymentFormChannelTextSize | <u>Type:</u> int Defines text size in controller |
| PaymentFormChannelTextGravity | <u>Type:</u> int Defines text placement in controller |
| PaymentFormChannelTextAllCaps | <u>Type:</u> boolean Sets letter to capital |
| PaymentAmountTextColor | <u>Type:</u> int Defines text color for amount |
| PaymentReceiverTextColor | <u>Type:</u> int |

| | |
|-----------------------------|--|
| | Defines text color for receiver |
| PaymentDescriptionTextColor | <u>Type:</u> int Defines text color for description |
| PaymentInfoBackgroundColor | <u>Type:</u> int Defines payment information background color |

Example:

```
Configuration.setPaymentFormBackgroundColor(R.color.white);  
Configuration.setPaymentFormChannelText(R.string.change_channel);  
Configuration.setPaymentFormChannelTextColor(R.color.green);  
Configuration.setPaymentFormChannelTextGravity(Gravity.RIGHT);  
Configuration.setPaymentFormChannelTextSize(20);  
Configuration.setPaymentFormChannelTextAllCaps(true);  
Configuration.setPaymentInfoBackgroundColor(R.color.dpsdk_green);
```

It is also possible to change default status text colors. To change status color call method setStatusColor:

```
Configuration.setStatusColor(StateType.COMPLETED, R.color.green);  
Configuration.setStatusColor(StateType.NEW, R.color.gray);  
Configuration.setStatusColor(StateType.PROCESSING, R.color.gray);  
Configuration.setStatusColor(StateType.REJECTED, R.color.red);  
Configuration.setStatusColor(StateType.PROCESSING_REALISATION, R.color.gray);  
Configuration.setStatusColor(StateType.PROCESSING_REALISATION_WAITING,  
R.color.gray);
```

Change the background in the transaction summary view:

| WŁAŚCIWOŚĆ | ZNACZENIE / OPIS |
|------------------------------|--|
| PaymentResultBackgroundColor | <u>Typ:</u> int Defines the background color of the transaction summary |

Przykład:

```
Configuration.setPaymentResultBackgroundColor(R.color.white);
```

Personal channel selection control

SDK library enables replacing default channel selection control, to adjust needs of Merchant's shop. The following steps are required to use this possibility:

1. In `PaymentManager` register personal channel selection activity (in the example it is `CustomChannelList`) with current context:

```
PaymentManager.getInstance().registerCustomChannelComponent((MenuActivity.this, CustomChannelList.class);
```

2. Initialize payment in `PaymentManager` (in accordance with aforementioned chapter [Payment process initialization](#))
3. Download channel list using one of the following methods:

```
PaymentManager.getInstance().getChannels() - returns all channels
```

```
PaymentManager.getInstance().getChannels(isOnline) - returns online/offline channels
```

```
PaymentManager.getInstance().getChannels(ids) - returns channels according to ID
```

```
PaymentManager.getInstance().getChannels(paymentTypes) - returns channels according to types
```

4. Set returned channel list as a data source for personal channel selection control.
5. After selecting channel by a client an appropriate `PaymentManager` method should be set:

```
PaymentManager.getInstance().initialPaymentForm(context, selectedChannel)
```

Filtering channels

If we use our application to sell various types of products/services, where each of them expect different set of payment channels (e.g. one of them requires a quick payment finalization time), so there is no need to create a custom channel selection control yourself, you can create a simple callback, through which we filter payments in a given context.

In order to use it you must implement the `ChannelFilterCallback` interface:


```
public interface ChannelFilterCallback {  
    List<Channel> filter(List<Channel> channels);  
}
```

And register it in PaymentManager:

```
PaymentManager.getInstance().setChannelFilterCallback(channelFilterCallback);
```

Example of a callback filtering channels by groups:

```
ChannelFilterCallback channelFilterCallback = new ChannelFilterCallback() {  
    @Override  
    public List<Channel> filter(List<Channel> channels) {  
        List<Channel> filteredChannels = new LinkedList<>();  
        for (Channel channel : channels) {  
            if (channelGroups.contains(channel.group)) {  
                filteredChannels.add(channel);  
            }  
        }  
        return filteredChannels;  
    }  
};
```

Custom order summary controller

Library allows to change order summary controller with your own, better suited for shop's needs. In order to use it:

1. Call method `setPaymentResultEnabled(boolean paymentResultEnabled)` singleton `Configuration` passing `false` as a value. It will disable order summary page from SDK.
2. The end of payment process is indicated by calling method `onPaymentSuccess` from interface `PaymentManagerCallback` passing `PaymentResult` object.
3. To request status from server call method

```
getTransactionStatus(String id, String token, String number, String  
language) singleton PaymentManager, where arguments can be downloaded from object  
paymentEndedEventArgs.getResult();
```

Example:

Page | 18 / 34

```
@Override

public void onPaymentSuccess(PaymentEndedEventArgs paymentEndedEventArgs) {
    final PaymentResult paymentResult = paymentEndedEventArgs.getResult();
    new Thread(new Runnable() {
        @Override
        public void run() {
            try{

PaymentResult result=PaymentManager.getInstance().getTransactionStatus(paymentResult.getRecipientId(),paymentResult.getToken(),
paymentResult.getNumber(),paymentResult.getPaymentLanguage());

                // your code...

            }catch(OperationException e){

                // your code...

            }catch(NoConnectionException e){

                // your code...

            }
        }
    }).start();
}
```

Special channel support

In this chapter extra functions related to special payment channels are described.

Page | 19 / 34

Credit card payment - 1Click

1Click functionality enables quick payment process with a saved credit card. Basic credit card data are saved in Dotpay system.

This functionality (if available in Merchant's shop) is turned on by default in SDK. A client's consent is also required to use 1Click service (while filling out the payment form).

In order to turn off 1Click, the following command is required:

```
PaymentManager.getInstance().setOneClickEnabled(false);
```

ATTENTION

After turning off aforementioned options, formerly saved credit card data is not removed. To remove that data, the following commands are required.

Initializing 1Click payment

Payment process should be initialized with method `oneClickPayment` `PaymentManager`. Required arguments have been described in section [**Błąd! Nie można odnaleźć źródła odwołania.**](#)

For development purposes method has special exceptions, which should be handled. They are listed in table below:

| PARAMETER | DESCRIPTION |
|-------------------------------------|---|
| OneClickUnableException | Exception informs about disabled 1Click functionality |
| NotFoundPaymentCardException | Exception informs about no registered cards |
| NotFoundDefaultPaymentCardException | Exception informs about no default card Setting default card has been described in another section |

Example:

Page | 20 / 34

```
String description = "Order no. 12345";
double amount = 123.45;

PaymentInformation paymentInformation = new PaymentInformation(merchant_Id, amount,
description, selectedCurrency);

Map<String, String> sender = new Map<String, String> {"firstname", "Jan"},
{"lastname", "Kowalski"}, {"email", "jan.kowalski@test.pl"}
Map<String, String> additional = new Map<String, String> {"id1", "12345"},
{"amount1", "100"}, {"id2", "67890"}, {"amount2", "23.45"}

paymentInformation.setSenderInformation(sender);
paymentInformation.setAdditionalInformation(additional);

try {
    PaymentManager.getInstance().oneClickPayment(this, paymentInformation);
} catch (NotFoundPaymentCardException e) {

    // your code...

} catch (NotFoundDefaultPaymentCardException e) {

    // your code...

} catch (OneClickUnableException e) {

    // your code...

}
}
```

Using built-in card management controller

In manager all remembered cards are listed. Manager also allows to add new cards.

ATTENTION: if functionality is disabled button will not be displayed.

In order to use built-in controller managing cards:

1. In xml layout, prepare controller `FrameLayout`.
2. Create instance `PaymentCardManagerFragment` via static method `newInstance` which should be passed to `FragmentManager`. `newInstance` method accepts arguments from table below:

| PARAMETER | DESCRIPTION |
|-----------|-------------|
|-----------|-------------|

| | |
|-------------|---|
| merchant_id | <u>Type</u> : string Account ID for which payment is made |
| currency | <u>Type</u> : string currency of payment Downlaoding available currencies list has been described in section <i>Available curriencies</i> . |
| language | <u>Type</u> : string payment language |
| firstname | <u>Type</u> : string <u>First name of the card holder</u> |
| lastname | <u>Type</u> : string Last name of the card holder |
| email | <u>Type</u> : string Email of the card holder |

Example:

```
private void initPaymentCardManagerFragment() {  
    FragmentManager fm = getSupportFragmentManager();  
    FragmentTransaction ft = fm.beginTransaction();  
    Fragment fragment = PaymentCardManagerFragment.newInstance(merchant_id,  
currency, language);  
    ft.replace(R.id.fragment_container, fragment, null).commit();  
}
```

Card registration regulations

In order to register new card user has to accept two regulations. There are two methods which allow to change shop's name and redirect to shop's regulation available at given URL. To do this call `Configuration` singleton setters.

Available methods:

| PARAMETER | DESCRIPTION |
|-----------|-------------|
|-----------|-------------|

| | |
|-------------------|---|
| MerchantName | <u>Type:</u> String Defines shop's name |
| MerchantPolicyUrl | <u>Type:</u> String Redirects customer to shop's regulation available at given URL |

Changing presentation style

To change presentation of card management controller elements call `Configuration` singleton setters. Configuration should be done before initiating layout containing card manager controller.

Card list controller:

| PARAMETER | DESCRIPTION |
|--|---|
| PaymentCardManagerBackgroundColor | <u>Type:</u> int Defines view background color |
| PaymentCardManagerBackgroundItemColor | <u>Type:</u> int Defines a single tile background color |
| PaymentCardManagerBackgroundPressItemColor | <u>Type:</u> int Defines tile background controller when pressed |
| PaymentCardManagerTextStyle | <u>Type:</u> int Defines tile text style |
| PaymentCardManagerDefaultMarkColor | <u>Type:</u> int Defines marked icon color (available for API 17+) |

Card adding form controller:

| PARAMETER | DESCRIPTION |
|---------------------------------------|---|
| PaymentCardManagerFormBackgroundColor | <u>Type:</u> int Defines view background color |

| | |
|----------------------------------|--|
| PaymentCardManagerFormLabelStyle | <u>Type</u> : int Defines controller label text style |
|----------------------------------|--|

Example:

```
Configuration.setPaymentCardManagerBackgroundColor(R.color.gray);  
Configuration.setPaymentCardManagerTextStyle(R.style.CardManagerTextStyle);  
Configuration.setPaymentCardManagerDefaultMarkColor(R.color.red);  
Configuration.setPaymentCardManagerFormBackgroundColor(R.color.gray);  
Configuration.setPaymentCardManagerFormLabelStyle(R.style.CardManagerLabelStyle);
```

Custom card management controller

To have data presented in a way better for shop, you can create own controller for card management downloading data from library.

1. Registered cards list

To download registered cards list call method:

`PaymentManager.getInstance().getPaymentCardList()` - method returns list of objects *PaymentCardInfo*, representing credit card.

2. Card registration

To register new card call method:

`PaymentManager.getInstance().registerPaymentCard()`

which accepts arguments from table below:

| PARAMETER | DESCRIPTION |
|------------------------|--|
| context | <u>Type</u> : Context Method call Context |
| merchantId | <u>Type</u> : string Dotpay account ID |
| email | <u>Type</u> : string Customer email for registration |
| paymentCardData | <u>Type</u> : PaymentCardData Object containing card data |
| cardRegisteredCallback | <u>Type</u> : CardRegisteredCallback |

Callback awaiting the end of registration signal. Correctly registered card returns object *PaymentCardInfo*

3. Deleting card

To delete card call method:

`PaymentManager.getInstance().unregisterCardData(paymentCardId)` – which argument is available in object *PaymentCardInfo.getPaymentCardId()*. List of exceptions for this method has been described below:

| PARAMETER | DESCRIPTION |
|--|--|
| <code>PaymentOperationException</code> | Exception sent by server containing event description. |
| <code>NoConnectionException</code> | Exception indicates network problems. |

4. Setting default card

To make 1Click payment you have to set default card with method:

`PaymentManager.getInstance().setDefaultPaymentCard(paymentCardId)` – which argument is available in object *PaymentCardInfo.getPaymentCardId()*.

To check which card is currently marked as default call method:

`PaymentManager.getInstance().getDefaultPaymentCard()` – which returns object *PaymentCardInfo*.

Exceptions for this method are listed below:

| PARAMETER | DESCRIPTION |
|--|---|
| <code>NotFoundDefaultPaymentCardException</code> | Exception indicates there is no default card. |

Example:

Page | 25 / 34

```
PaymentManager.getInstance().registerPaymentCard(ShopActivity.this, merchantId, email,
paymentCardData, new CardRegisteredCallback() {
    @Override
    public void onSuccess(final PaymentCardInfo paymentCardInfo) {

PaymentManager.getInstance().setDefaultPaymentCard(paymentCardInfo.getCredit_card_id()
);
        new Thread(new Runnable() {
            @Override
            public void run() {
                try {

PaymentManager.getInstance().unregisterCardData(paymentCardInfo.getCredit_card_id());
                } catch (PaymentOperationException e) {

                    // your code ...

                } catch (NoConnectionException e) {

                    // your code ...

                }
            }
        }).start();
    }
    @Override
    public void onFailure(ErrorCode errorCode) {

        // your code ...

    }
});
```

External cards data

Cards references are remembered inside the SDK by default, so the functionality is available without any additional work necessary either on the side of the mobile application or backend with which the application can work. A side effect of this approach is the inability to transfer registered cards between devices or after reinstalling the application.

However, if the application works with its own backend, uniquely identifying the User (this is a necessary condition), card references can be stored in the backend, which will allow them to be shared (e.g. if the user account is shared between the website and the mobile application).

Detailed description about card storage mechanisms you can find at [Technical manual for payments implementation Dotpay](#).

To enable support for such remembered cards, add a list of cards with identifier `credit_card_customer_id` to the `PaymentManager` before payment initiation :

```
setExternalCreditCards(List<PaymentCardInfo> creditCards, String creditCardCustomerId)
```

where `creditCards` are list of objects `PaymentCardInfo` containing complete information about the card, and `creditCardCustomerId` is the unique user ID, in the context of which the cards were registered. In addition,

there is an overloaded method with the same name, taking an additional parameter that allows you to turn off the visibility of cards remembered inside the SDK (if the application currently uses such cards, or if it must work both in a context without a logged in user / with a logged in user).

`PaymentCardInfo` accepts arguments from the table below:

| PARAMETER | DESCRIPTION |
|--------------|---|
| maskedNumber | Type: string Masked card number |
| cardId | Type: string Card ID |
| name | Type: string Card name |
| codeName | Type: string Card type |
| logo | Type: string Link to the card's logo (according to the Dotpay basic documentation, the link is returned together with the data of registered card) |

Example:

```
PaymentCardInfo externalCard = new PaymentCardInfo(maskedNumber, cardId, name,
codeName, logo);
List<PaymentCardInfo> externalCreditCards = new ArrayList();
externalCreditCards.add(externalCard);
PaymentManager.getInstance().setExternalCreditCards(externalCreditCards,
creditCardCustomerId);
```

ATTENTION

the method of setting cards from the outside overwrites all cards added previously marked as external, this method can be called repeatedly to update the list of cards.

If we want to remove the user context, remove the added cards from the SDK memory so as to work again only in the context of the cards remembered in the SDK, call method `PaymentManager.disableExternalCards()`

```
PaymentManager.getInstance().disableExternalCards();
```

1. Card registration in the context of an external User

When initializing the SDK with external card data, note that all cards registered from the SDK level will be registered with the given `credit_card_customer_id` (both by the Card Manager and those registered during payment).

If the User has no registered card yet, but we want to register new cards in its context, the `setExternalCreditCards` method should be called with an empty list of cards.

All cards registered in this way are automatically added to the SDK, as are cards delivered from outside (in the context of the indicated `credit_card_customer_id`). Information about the registration of a new card can be obtained at the backend level. As soon as the application receives this information, you must set the current list of external cards in the `PaymentManager`.

In order to get information about registration, you need to implement the interface :

```
public interface ExternalCardRegisteredCallback {  
    void onCardRegistered(PaymentCardInfo creditCard);  
}
```

And register in `PaymentManager`:

```
PaymentManager.getInstance().setExternalCardRegisteredCallback  
(externalCardRegisteredCallback);
```

As soon as a new card is registered, the application will be notified about that , so the application can send a request to backend for refresh the list of cards.

2. Change default cards

External cards , just like the cards remembered in the SDK, can be marked as "default" for the purposes of the 1Click functionality (according to the section Default card setting). Please note that the default card is a different concept from the last one used for standard payments.

To get information if the default card has been changed to the SDK, you need to implement the interface:

```
public interface DefaultCardChangedCallback {  
    void onDefaultCardChanged(PaymentCardInfo newDefaultCard);  
}
```

And register it in `PaymentManager`:

```
PaymentManager.getInstance().setDefaultCardChangedCallback(defaultCardChangedCallback  
).
```

When the default card in the SDK will be changed, the application will be notified about that , so it will be possible to send this information to the backend.

Masking the cvv filed

If the SDK is used in an application that is often used by Users in conditions that limit the possibility of maintaining an adequate level of confidentiality of entered data (e.g. purchase of a public transport ticket after entering a crowded vehicle), you can use the field masking option on the CVV to give The user has a greater sense of security.

To do this call the method:

```
PaymentManager.getInstance().setCvvConcealed(true);
```

However, it should be noted that this value is only one of the factors ensuring the security of card payments, hence there is no recommendation that this field should be so secured in every application, remembering that incorrect entry of this field leads to unsuccessful payments, and multiple unsuccessful payments can lead to blocking the card for online payments.

Payment without the payment form.

In case you need to remove a special payment channel to the basket of the mobile application (e.g. Visa Checkout). It was created mechanism that allows calling the payment with the channel indication, without the option to choose the payment channel and payment form.

To make such a payment, use the `payment` method on `PaymentManager`, whose parameters are described in the section Payment initiation. An additional parameter is the channel identifier.

Additional, channel-specific parameters should be send as elements of the `additionalInformation` dictionary in the `PaymentInformation` class object.

Masterpass Champion Wallet

Masterpass Champion Wallet allows you to quickly and conveniently use the Masterpass payment functionality when you do not have such a wallet during payment. Registering Masterpass Champion Wallet is convenient, it can be carried out completely online and allows for "1click" payments. After registering / logging into the wallet once, subsequent payments are carried out with the minimum amount of information.

To use the functionality, after business arrangements, an appropriate configuration of the Store account is performed, which automatically gives access to this version of the wallet.

ATTENTION

to use this functionality, mobile applications using the SDK must have a dedicated dotpay Store account.

Additional parameters for payment initiation

To improve the process of using the wallet by the Payer, it is recommended to pass the `phone` parameter in the `senderInformation` property of the `PaymentInformation` object, with which the SDK instance is initiated.

In addition, if the `phone_verified` parameter with the value "true" is passed, the transfer of which the mobile application clearly confirms that the phone number transferred to the SDK is fully verified (e.g. with a single-use SMS code), the registration process will be simplified.

Payment authorization

Masterpass Champion Wallet was created to make payments as easy as possible. To reduce the risk of frauds, it is recommended to perform payment authorization on the application side. To do this, you must implement the interface:

```
public interface MasterpassPaymentCallback {  
    void onPaymentShouldCreateAuthorization (Context context);  
    void onPaymentShouldAuthorizeUser (Context context);  
}
```

and register in `PaymentManager`:

```
PaymentManager.getInstance().setMasterpassPaymentCallback(masterpassPaymentCallback);
```

The following methods are issued in the `PaymentManager` class:

```
public void authorizationCreateResult(boolean isAuthorizationCreated);
```

```
public void authorizeUserResult (boolean isUserAuthorize, Activity activity);
```

`onPaymentShouldCreateAuthorization` methods will be called when the user logs in (or registers) to the wallet, and allows to define / initiate authorization mechanisms in the mobile application (e.g. to define the application PIN). After completing this process, you should call the `authorizationCreateResult` method by passing the authorization creation status. In the event of a positive one, the SDK will continue the registration process to the wallet, in the case of a negative one it will terminate this process.

The `onPaymentShouldAuthorizeUser` method will be called whenever the logged-in Payer wants to make another payment with the associated wallet. As part of its course, we should perform authorization (e.g. PIN verification), and when finished, call the `authorizeUserResult` method of `PaymentManager`, transferring its status. Confirmation of authorization will allow you to make a payment, information about incorrect authorization will interrupt it.

The return method requires an additional parameter, -the current Activity, which will allow proper reference to the Android context.

Example:

```
private MasterpassPaymentCallback masterpassPaymentCallback = new
MasterpassPaymentCallback() {

    @Override

    public void onPaymentShouldCreateAuthorization(Context context) {

PaymentManager.getInstance().authorizationCreateResult(true);

    }

    @Override

    public void onPaymentShouldAuthorizeUser(Context context) {

        //create activity if required

        ...
PaymentManager.getInstance().authorizeUserWithResult(true, CurrentActivity.this);

    };

}
```

Google Pay

The default version of the SDK library hides Google Pay payments support, even if they are available in the store configuration and available for web payments, because without meeting additional requirements, this method is not able to function properly in the mobile application.

The alternative version of the SDK library includes native Google Pay SDK support, to use it, in the gradle file you must replace the Dotpay SDK dependency for :

```
implementation('pl.mobiltek.paymentsmobile:dotpay-googlepay:1.4.18@aar') {  
    transitive = true  
}
```

Using this library for production requires submitting application to Google.

A detailed description of all conditions can be found in the documentation available at:

<https://www.dotpay.pl/developer/doc/google-pay/en/>

In chapter 5 of the documentation there is a reference to a Google checklist that you must go through to request permission to switch to production.

Transaction history and status

Page | 32 / 34

SDK library offers saving and displaying transaction history. The transaction history also displays related operations, e.g. subsequently made refunds and other additional operations.

The use of built-in control

In order to use built-in history control the following step is required:

1. Put in history control in xml file of selected layout. This layout will be responsible for displaying history, e.g.:

```
<fragment  
  
    android:name="pl.mobiltek.paymentsmobile.dotpay.fragment.TransactionHistoryFragment"  
    android:id="@+id/transactionHistory"  
    android:layout_width="match_parent"  
    android:layout_height="match_parent" />
```

Changing presentation style

In order to change the way how control history elements are presented, proper `Configuration singleton` setters have to be set. Settings have to be executed before layout initialization that contains history control.

Channel selecting control:

| PARAMETER | DESCRIPTION |
|------------------------|---|
| HistoryTitleVisibility | <u>Type:</u> boolean Hide title |
| HistoryTitleText | <u>Type:</u> int Defines title text |
| HistoryTitleStyle | <u>Type:</u> int Defines title TextView style |
| HistoryDividerColor | <u>Type:</u> int Defines separator color under divider |

| | |
|------------------------------------|---|
| HistoryBackgroundColor | <u>Type:</u> int Defines background color |
| setHistoryDateTextStyle | <u>Type:</u> int Defines TextView style for element data |
| setHistoryAmountTextStyle | <u>Type:</u> int Defines TextView style for element amount |
| HistoryDescriptionTextStyle | <u>Type:</u> int Defines TextView style for element description |
| HistoryBackgroundItemColor | <u>Type:</u> int Defines background color for whole element |
| HistoryDetailsHeaderTitleTextStyle | <u>Type:</u> int Defines TextView style for summary window title |
| HistoryDetailDividerColor | <u>Type:</u> int Defines TextView style for summary window title divider |
| HistoryDetailsTitleTextStyle | <u>Type:</u> int Defines TextView subtitle details style |
| HistoryDetailsValueTextStyle | <u>Type:</u> int Defines TextView details value style |

Example:

```
Configuration.setHistoryTitleVisibility(true);
Configuration.setHistoryTitleText(R.string.HistoryTitle);
Configuration.setHistoryTitleStyle(R.style.HistoryTitleStyle);
Configuration.setHistoryDividerColor(R.color.black);
Configuration.setHistoryBackgroundColor(R.color.gray);
Configuration.setHistoryDateTextStyle(R.style.HistoryDateStyle);
Configuration.setHistoryAmountTextStyle(R.style.HistoryAmountStyle);
Configuration.setHistoryDescriptionTextStyle(R.style.HistoryDescriptionStyle);
Configuration.setHistoryBackgroundItemColor(R.color.white);
Configuration.setHistoryDetailsHeaderTitleTextStyle(R.style.HistoryTitleStyle);
Configuration.setHistoryDetailDividerColor(R.color.black);
Configuration.setHistoryDetailsTitleTextStyle(R.style.HistoryDetailsTitleStyle);
Configuration.setHistoryDetailsValueTextStyle(R.style.HistoryDetailsValueStyle);
```

Personal history control

SDK library offers creating personal history control to better match web shop specification.

In order to download information on transaction list, the following PaymentManager method is required:

```
PaymentManager.getInstance().loadTransactions();
```

Additionally, for transactions presented in personal history you can:

1. Remove a single record:

```
PaymentManager.getInstance().deleteTransaction(paymentResult);
```

2. Check current transaction status:

```
PaymentManager.getInstance().getTransactionStatus(paymentResult);
```

List of exceptions for this method has been described below:

| PARAMETER | DESCRIPTION |
|---------------------------|--|
| PaymentOperationException | Exception from server containing even description. |
| NoConnectionException | Exception indicates network problems. |