

Natural Language Inference for Question Answering

Gabor Angeli

Stanford University

April 14, 2015



My View on Question Answering

Two parts to question answering:

- Understanding the question
- Understanding the corpus (IE)



My View on Question Answering

Two parts to question answering:

- Understanding the question
 - Can be arbitrarily hard; I only worry about easy factoids
 - (For the rest, just use Semantic Parsing)
- Understanding the corpus (IE)



My View on Question Answering

Two parts to question answering:

- Understanding the question
 - Can be arbitrarily hard; I only worry about easy factoids
 - (For the rest, just use Semantic Parsing)
- Understanding the corpus (IE)



My View on Question Answering

Two parts to question answering:

- Understanding the question
 - Can be arbitrarily hard; I only worry about easy factoids
 - (For the rest, just use Semantic Parsing)
- Understanding the corpus (IE)
 - What facts are in the corpus?
[Angeli et al., 2014a, Angeli et al., 2014b]



My View on Question Answering

Two parts to question answering:

- Understanding the question
 - Can be arbitrarily hard; I only worry about easy factoids
 - (For the rest, just use Semantic Parsing)
- Understanding the corpus (IE)
 - What facts are in the corpus?
[Angeli et al., 2014a, Angeli et al., 2014b]
 - What facts are entailed by the corpus?
[ACL OpenIE Submission]



My View on Question Answering

Two parts to question answering:

- Understanding the question
 - Can be arbitrarily hard; I only worry about easy factoids
 - (For the rest, just use Semantic Parsing)
- Understanding the corpus (IE)
 - What facts are in the corpus?
[Angeli et al., 2014a, Angeli et al., 2014b]
 - What facts are entailed by the corpus?
[ACL OpenIE Submission]
 - How do we find if a fact is entailed by the corpus?
[Angeli and Manning, 2013, Angeli and Manning, 2014]



Challenges that Inference Will Solve

Questions don't always fit into relation schema



Challenges that Inference Will Solve

Questions don't always fit into relation schema

✓ *Where was Barack Obama born?*



Challenges that Inference Will Solve

Questions don't always fit into relation schema

- ✓ *Where was Barack Obama born?*
- ? *What city borders the largest river in California?*
- ? *Who is Chris Manning's academic advisor?*



Challenges that Inference Will Solve

Questions don't always fit into relation schema

- ✓ *Where was Barack Obama born?*
- ? *What city borders the largest river in California?*
- ? *Who is Chris Manning's academic advisor?*
- ✗ *Do cats have tails?*



Challenges that Inference Will Solve

Questions don't always fit into relation schema

- ✓ *Where was Barack Obama born?*
- ? *What city borders the largest river in California?*
- ? *Who is Chris Manning's academic advisor?*
- ✗ *Do cats have tails?*

Questions don't always talk about named entities

- ✓ *Where was Barack Obama born?*



Challenges that Inference Will Solve

Questions don't always fit into relation schema

- ✓ *Where was Barack Obama born?*
- ? *What city borders the largest river in California?*
- ? *Who is Chris Manning's academic advisor?*
- ✗ *Do cats have tails?*

Questions don't always talk about named entities

- ✓ *Where was Barack Obama born?*
- ? *What treatments are there for diabetes?*
- ✗ *Do cats have tails?*



Challenges that Inference Will Solve

Questions don't always fit into relation schema

- ✓ *Where was Barack Obama born?*
- ? *What city borders the largest river in California?*
- ? *Who is Chris Manning's academic advisor?*
- ✗ *Do cats have tails?*

Questions don't always talk about named entities

- ✓ *Where was Barack Obama born?*
- ? *What treatments are there for diabetes?*
- ✗ *Do cats have tails?*

Answers aren't always literally justified in text

- ✓ *Born in Hawaii, Barack Obama ...*
- ? *Doctors prescribe Insulin for Diabetes.*
- ✗ *All animals have tails.*



No entailment: What facts are in the corpus?

We can do QA from Freebase ... so let's make Freebase bigger

Relation Extraction + TAC-KBP



No entailment: What facts are in the corpus?

We can do QA from Freebase ... so let's make Freebase bigger

Relation Extraction + TAC-KBP

- Done: KBP 2013 – 2014
- Done: KBP + active learning
- Pending: KBP + deep learning / matrix factorization



No entailment: What facts are in the corpus?

We can do QA from Freebase ... so let's make Freebase bigger

Relation Extraction + TAC-KBP

- Done: KBP 2013 – 2014
- Done: KBP + active learning
- Pending: KBP + deep learning / matrix factorization

Does it address the challenges?

- Fixed relation schema
- Very named-entity-centric
- Zero entailments from text



Mini-Entailment: List facts entailed by corpus

Extract maximally informative, correct things

Natural Logic + OpenIE (ACL submission)



Mini-Entailment: List facts entailed by corpus

Extract maximally informative, correct things

Natural Logic + OpenIE (ACL submission)

1. Split sentence up into short, entailed clauses
2. Strip away excess information in clauses
3. Extract open IE triples



Mini-Entailment: List facts entailed by corpus

Extract maximally informative, correct things

Natural Logic + OpenIE (ACL submission)

1. Split sentence up into short, entailed clauses
2. Strip away excess information in clauses
3. Extract open IE triples

Does it address the challenges?

- Open relation schema
- Named entity agnostic
- Only limited entailment from text



Lots of Entailment: Is a fact entailed by corpus?

Given a fact, can we support it in the corpus?

NaturalLI



Lots of Entailment: Is a fact entailed by corpus?

Given a fact, can we support it in the corpus?

NaturalLI

- Done: Natural Logic for common sense facts
- Pending: Natural Logic for factoid facts (EMNLP)
- Future: ... stay tuned



Lots of Entailment: Is a fact entailed by corpus?

Given a fact, can we support it in the corpus?

NaturalLI

- Done: Natural Logic for common sense facts
- Pending: Natural Logic for factoid facts (EMNLP)
- Future: ... stay tuned

Does it address the challenges?

- Open relation schema
- Named entity agnostic
- Large class of entailments from corpus



Main Idea of Thesis

Natural language inference allows us to leverage latent information in plain text to find support for enough types of questions to be useful for open-domain QA.



KBP: Directly find facts in text

Where is Chris Manning from?



KBP: Directly find facts in text

Topic

Christopher D. Manning^{en}

People /people [Freebase Commons](#)

Person /people/person X

Date of birth /people/person/date_of_birth

9/18/1965

Place of birth /people/person/place_of_birth

-

Country of nationality /people/person/nationality

Gender /people/person/gender

Male

Profession /people/person/profession

-



KBP: Directly find facts in text

Christopher Manning

Professor of [Linguistics](#) and [Computer Science](#)

[Natural Language Processing Group](#), [Stanford University](#)



Brief Bio

- I'm Australian ("I come from a land of wide open spaces ...")
- BA (Hons) Australian National University 1989 (majors in mathematics, computer science and linguistics)
- PhD Stanford Linguistics 1995
- Asst Professor Carnegie Mellon University Computational Linguistics Program 1994-96
- Lecturer University of Sydney Dept of Linguistics 1996-99
- Asst Professor Stanford University Depts of Computer Science and Linguistics 1999-2006
- Assoc Professor Stanford University Depts of Linguistics and Computer Science 2006-2012
- Professor Stanford University Depts of Linguistics and Computer Science 2012-



KBP: Directly find facts in text

Australia

Christopher D. Manning, origin

Feedback



Active Learning for Relation Extraction

Input: Sentences containing (entity, slot value).

Output: Relation between entity and slot value.



Active Learning for Relation Extraction

Input: Sentences containing (entity, slot value).

Output: Relation between entity and slot value.

Consider two approaches:

- **Supervised:** Trivial as a supervised classifier.

Training data: {(sentence, relation)}.

But...



Active Learning for Relation Extraction

Input: Sentences containing (entity, slot value).

Output: Relation between entity and slot value.

Consider two approaches:

- **Supervised:** Trivial as a supervised classifier.
Training data: {(sentence, relation)}.
But... this training data is expensive to produce.



Active Learning for Relation Extraction

Input: Sentences containing (entity, slot value).

Output: Relation between entity and slot value.

Consider two approaches:

- **Supervised:** Trivial as a supervised classifier.
Training data: {(sentence, relation)}.
But... this training data is expensive to produce.
- **Distantly Supervised:** Artificially produce “supervised” data.
Training data: {(entity, relation, slot value)}.
But...



Active Learning for Relation Extraction

Input: Sentences containing (entity, slot value).

Output: Relation between entity and slot value.

Consider two approaches:

- **Supervised:** Trivial as a supervised classifier.
Training data: {(sentence, relation)}.
But... this training data is expensive to produce.
- **Distantly Supervised:** Artificially produce “supervised” data.
Training data: {(entity, relation, slot value)}.
But... this training data is much more noisy.



Active Learning: Combine Benefits of Both

Adding carefully selected supervision improves distantly supervised relation extraction.



Active Learning: Combine Benefits of Both

Adding carefully selected supervision improves distantly supervised relation extraction.

Old problem: Supervision is expensive, but very useful.

Old solution: Active learning!



Active Learning: Combine Benefits of Both

Adding carefully selected supervision improves distantly supervised relation extraction.

Old problem: Supervision is expensive, but very useful.


Old solution: Active learning!

- Select a subset of sentences to annotate.
- Fix these labels during training.




State-of-the-art results

Slot filling evaluation of Surdeanu et al. (2012).




State-of-the-art results

Slot filling evaluation of Surdeanu et al. (2012).




State-of-the-art results

Slot filling evaluation of Surdeanu et al. (2012).




State-of-the-art results

Slot filling evaluation of Surdeanu et al. (2012).



State-of-the-art results

Slot filling evaluation of Surdeanu et al. (2012).



KBP is already “entailment”

Chris, a tenured professor at Stanford, is friends with Fei-Fei

⇒ *Chris is a tenured professor at Stanford*

⇒ *Chris is a professor at Stanford*

⇒ *Chris is employed by Stanford*

⇒ *(Chris; employee_of; Stanford)*



KBP is already “entailment”

Chris, a tenured professor at Stanford, is friends with Fei-Fei


- ⇒ *Chris is a tenured professor at Stanford*
- ⇒ *Chris is a professor at Stanford*
- ⇒ *Chris is employed by Stanford*
- ⇒ *(Chris; employee_of; Stanford)*

Born in a small town, she took the midnight train going anywhere


- ⇒ *She took the midnight train going anywhere*
- ⇒ *She took the midnight train*
- ⇒ *She took midnight train*
- ⇒ *(She; took; midnight train)*



Treat As Entailment



Treat As Entailment



(input)



she took the midnight train going anywhere

Born in a small town, she took the midnight train

Born in a town, she took the midnight train


she took the midnight train

she took midnight train

...



Treat As Entailment



(input)

she took the midnight train going anywhere

Born in a small town, she took the midnight train

Born in a town, she took the midnight train

she took the midnight train


she took midnight train

...

(she; took; midnight train)



Treat As Entailment



(input)

she took the midnight train going anywhere

Born in a small town, she took the midnight train

Born in a town, she took the midnight train

she took the midnight train


she took midnight train

...

(she; took; midnight train)



Treat As Entailment



(extracted clause)



she Born in small town

she Born in a town

she Born in town



(she; born in; small town)

(she; born in; town)



OpenIE Summary

Chris, a tenured professor at Stanford, is friends with Fei-Fei
⇒ (Chris; is friends with; Fei-Fei)

1. Split a long sentence into short entailed sentences.
(e.g., *Chris is a tenured professor at Stanford*)



OpenIE Summary

Chris, a tenured professor at Stanford, is friends with Fei-Fei
 \Rightarrow (Chris; is friends with; Fei-Fei)

1. Split a long sentence into short entailed sentences.
(e.g., *Chris is a tenured professor at Stanford*)
2. Shorten each clause maximally
 - ✓ *Chris is friends with Fei-Fei*
 - ✓ *Chris is professor*
 - ✗ *Chris is friends*



OpenIE Summary

Chris, a tenured professor at Stanford, is friends with Fei-Fei
 \Rightarrow (Chris; is friends with; Fei-Fei)

1. Split a long sentence into short entailed sentences.
(e.g., *Chris is a tenured professor at Stanford*)
2. Shorten each clause maximally
 - ✓ *Chris is friends with Fei-Fei*
 - ✓ *Chris is professor*
 - ✗ *Chris is friends*
3. Optionally segment into triples



State-of-the-art OpenIE

KBP 2013 end-to-end evaluation:

System	P	R	F ₁
UW Official	69.8	11.4	19.6
Ollie	57.4	4.8	8.9
NaturalLI – Nominals	66.7	7.7	13.8
Ollie + Nominal Rels	56.8	12.1	19.9
NaturalLI	60.3	14.3	23.1



State-of-the-art OpenIE

KBP 2013 end-to-end evaluation:

System	P	R	F ₁
UW Official	69.8	11.4	19.6
Ollie	57.4	4.8	8.9
NaturalLI – Nominals	66.7	7.7	13.8
Ollie + Nominal Rels	56.8	12.1	19.9
NaturalLI	60.3	14.3	23.1

- If we add alternate names and websites: 28.6 F₁
- Context: NYU *trained on KBP*: 27.7 F₁



State-of-the-art OpenIE

KBP 2013 end-to-end evaluation:

System	P	R	F ₁
UW Official	69.8	11.4	19.6
Ollie	57.4	4.8	8.9
NaturalLI – Nominals	66.7	7.7	13.8
Ollie + Nominal Rels	56.8	12.1	19.9
NaturalLI	60.3	14.3	23.1

- If we add alternate names and websites: 28.6 F₁
- Context: NYU *trained on KBP*: 27.7 F₁
- MIML-RE: 36.2 F₁; Top system: 40.2 F₁



Natural Logic subsumes Syllogisms

Some cat ate a mouse
(*all mice are rodents*)

∴ *Some cat ate a **rodent***



Natural Logic subsumes Syllogisms

Some cat ate a mouse
(*all mice are rodents*)

∴ *Some cat ate a **rodent***

Cognitively easy inferences are easy:

- Most cats eat mice
∴ *Most cats eat **rodents***



Natural Logic subsumes Syllogisms

Some cat ate a mouse
(*all mice are rodents*)

∴ *Some cat ate a **rodent***

Cognitively easy inferences are easy:

- Most cats eat mice
∴ *Most cats eat **rodents***
- “*All students who know a foreign language learned it at university.*”



Natural Logic subsumes Syllogisms

Some cat ate a mouse
(*all mice are rodents*)

∴ *Some cat ate a **rodent***

Cognitively easy inferences are easy:

- Most cats eat mice
∴ *Most cats eat **rodents***
- “All students who know a foreign language learned it at university.”
∴ “*They learned it at school.*”



Natural Logic subsumes Syllogisms

Some cat ate a mouse
(*all mice are rodents*)

∴ *Some cat ate a **rodent***

Cognitively easy inferences are easy:


- Most cats eat mice
∴ *Most cats eat **rodents***
- “All students who know a foreign language learned it at university.”
∴ *“They learned it at school.”*

Facts are text; inference is lexical mutation




Natural Logic and Polarity

Treat hypernymy as a *partial order*.




Natural Logic and Polarity

Treat hypernymy as a *partial order*.




Polarity is the direction a lexical item can move in the ordering.



Natural Logic and Polarity

Treat hypernymy as a *partial order*.




Polarity is the direction a lexical item can move in the ordering.



Natural Logic and Polarity

Treat hypernymy as a *partial order*.




Polarity is the direction a lexical item can move in the ordering.



Natural Logic and Polarity

Treat hypernymy as a *partial order*.




Polarity is the direction a lexical item can move in the ordering.



Natural Logic and Polarity

Treat hypernymy as a *partial order*.




Polarity is the direction a lexical item can move in the ordering.



Natural Logic and Polarity

Treat hypernymy as a *partial order*.




Polarity is the direction a lexical item can move in the ordering.



Natural Logic and Polarity

Treat hypernymy as a *partial order*.




Polarity is the direction a lexical item can move in the ordering.



An Example Inference

Quantifiers determines the *polarity* (\uparrow or \downarrow) of words.



An Example Inference

Quantifiers determines the *polarity* (\uparrow or \downarrow) of words.

Mutations must respect *polarity*.



An Example Inference

Quantifiers determines the *polarity* (\uparrow or \downarrow) of words.


Mutations must respect *polarity*.



An Example Inference

Quantifiers determines the *polarity* (\uparrow or \downarrow) of words.


Mutations must respect *polarity*.



An Example Inference

Quantifiers determines the *polarity* (\uparrow or \downarrow) of words.


Mutations must respect *polarity*.



An Example Inference

Quantifiers determines the *polarity* (\uparrow or \downarrow) of words.

Mutations must respect *polarity*.




An Example Inference


Quantifiers determines the *polarity* (\uparrow or \downarrow) of words.

Mutations must respect *polarity*.

Inference is reversible.



Natural Logic Inference is Search



Natural Logic Inference is Search

No carnivores
eat animals? 🔍

The carnivores
eat animals

The **cat**
eats animals

The cat
ate **an** animal


The cat
ate a **mouse**

All cats
have tails


All kittens
are cute



Natural Logic Inference is Search




Natural Logic Inference is Search



Nodes (*fact*, truth maintained $\in \{\text{true}, \text{false}\}$)



Natural Logic Inference is Search




Nodes (*fact*, truth maintained $\in \{\text{true}, \text{false}\}$)

Start Node (*query fact*, *true*)

End Nodes *any known fact*



Natural Logic Inference is Search



Nodes (*fact*, truth maintained $\in \{\text{true}, \text{false}\}$)


Start Node (*query fact*, *true*)

End Nodes *any known fact*

Edges Mutations of the current fact



Natural Logic Inference is Search



Nodes (*fact*, truth maintained $\in \{\text{true}, \text{false}\}$)

Start Node (*query fact*, *true*)

End Nodes *any known fact*


Edges Mutations of the current fact

Edge Costs How “wrong” an inference step is (learned)



An Example Search (as reverse inference)

Search mutates *opposite* to polarity



An Example Search (as reverse inference)

**Truth
maintained:**

true

**Current
Node:**



An Example Search (as reverse inference)

**Truth
maintained:**

false

**Current
Node:**




An Example Search (as reverse inference)

Truth
maintained:

false

Current
Node:



An Example Search (as reverse inference)

**Truth
maintained:**

false

**Current
Node:**



An Example Search (as reverse inference)

Truth
maintained:

false

Current
Node:



An Example Search (as reverse inference)

Truth
maintained:

false

Current
Node:




An Example Search (as reverse inference)

Truth
maintained:

false

Current
Node:



An Example Search (as graph search)


Shorthand for a node:




*No carnivores
eat animals?*




An Example Search (as graph search)




An Example Search (as graph search)




An Example Search (as graph search)




An Example Search (as graph search)



An Example Search (as graph search)



An Example Search (as graph search)



“Soft” Natural Logic

Want to make likely (but not certain) inferences.

- Same motivation as Markov Logic, Probabilistic Soft Logic, etc.



“Soft” Natural Logic

Want to make likely (but not certain) inferences.

- Same motivation as Markov Logic, Probabilistic Soft Logic, etc.
- Each *edge template* has a cost $\theta \geq 0$.



“Soft” Natural Logic

Want to make likely (but not certain) inferences.

- Same motivation as Markov Logic, Probabilistic Soft Logic, etc.
- Each *edge template* has a cost $\theta \geq 0$.

Detail: Variation among *edge instances* of a template.

- WordNet: *cat* \rightarrow *feline* **vs.** *cup* \rightarrow *container*.
- Nearest neighbors distance.
- Each *edge instance* has a distance f .



“Soft” Natural Logic

Want to make likely (but not certain) inferences.

- Same motivation as Markov Logic, Probabilistic Soft Logic, etc.
- Each *edge template* has a cost $\theta \geq 0$.

Detail: Variation among *edge instances* of a template.

- WordNet: *cat* \rightarrow *feline* **vs.** *cup* \rightarrow *container*.
- Nearest neighbors distance.
- Each *edge instance* has a distance f .

Cost of an edge is $\theta_i \cdot f_i$.



“Soft” Natural Logic

Want to make likely (but not certain) inferences.

- Same motivation as Markov Logic, Probabilistic Soft Logic, etc.
- Each *edge template* has a cost $\theta \geq 0$.

Detail: Variation among *edge instances* of a template.

- WordNet: *cat* \rightarrow *feline* **vs.** *cup* \rightarrow *container*.
- Nearest neighbors distance.
- Each *edge instance* has a distance f .

Cost of an edge is $\theta_i \cdot f_i$.

Cost of a path is $\theta \cdot f$.



“Soft” Natural Logic

Want to make likely (but not certain) inferences.

- Same motivation as Markov Logic, Probabilistic Soft Logic, etc.
- Each *edge template* has a cost $\theta \geq 0$.

Detail: Variation among *edge instances* of a template.

- WordNet: *cat* \rightarrow *feline* **vs.** *cup* \rightarrow *container*.
- Nearest neighbors distance.
- Each *edge instance* has a distance f .

Cost of an edge is $\theta_i \cdot f_i$.

Cost of a path is $\theta \cdot \mathbf{f}$.

Can learn parameters θ .



Summary: NaturalLI

High-Level Takeaways

- *Deep* inferences from a *large* knowledge base.
- Leverage arbitrarily large plain-text knowledge bases.
- “Soft” logic with probability of truth.



Summary: NaturalLI

High-Level Takeaways

- *Deep* inferences from a *large* knowledge base.
- Leverage arbitrarily large plain-text knowledge bases.
- “Soft” logic with probability of truth.

Results

- ConceptNet facts: 12% recall → 49% recall @ 91% precision.
- Checks logical entailment (not just fuzzy query).



Summary: NaturalLI

High-Level Takeaways

- *Deep* inferences from a *large* knowledge base.
- Leverage arbitrarily large plain-text knowledge bases.
- “Soft” logic with probability of truth.

Results

- ConceptNet facts: 12% recall → 49% recall @ 91% precision.
- Checks logical entailment (not just fuzzy query).

Complexity doesn't grow with knowledge base size.



The “Proposal” Part



Possible Projects

What is NaturalLI bad at?



Possible Projects

What is NaturalLI bad at?

- **Real world Q/A (WebQuestions, TREC, AI2 Biology).**
Most people don't really care about common-sense.



Possible Projects

What is NaturalLI bad at?

- **Real world Q/A (WebQuestions, TREC, AI2 Biology).**
Most people don't really care about common-sense.
- **Reasoning with multiple premises.**
E.g., DeMorgan's laws.



Possible Projects

What is NaturalLI bad at?

- **Real world Q/A (WebQuestions, TREC, AI2 Biology).**
Most people don't really care about common-sense.
- **Reasoning with multiple premises.**
E.g., DeMorgan's laws.
- **Fully leveraging training data.**
What if the entailment rules aren't in WordNet?



Real World Q/A (EMNLP 2015)

Goal: Make NaturalLI useful, not just cute.



Real World Q/A (EMNLP 2015)

Goal: Make NaturalLI useful, not just cute.

Start with NaturalLI...

- + Dependency trees (for passivization, etc.)
- + Meronymy (Hawaii is in USA)
- + Relational entailment (*works* \rightarrow *employed*)
- + Paraphrases



Real World Q/A (EMNLP 2015)

Goal: Make NaturalLI useful, not just cute.

Start with NaturalLI...

- + Dependency trees (for passivization, etc.)
- + Meronymy (Hawaii is in USA)
- + Relational entailment (*works* \rightarrow *employed*)
- + Paraphrases

Evaluate on:

- AI2 Biology tests
- WebQuestions
- TREC QA



Multiple Premises (logic paper?)

Goal: Make Natural Logic look more appealing.



Multiple Premises (logic paper?)

Goal: Make Natural Logic look more appealing.

The Trivial Case: Parse premises that define edges in a partial order (e.g., *cats are animals*, *Hawaii is in the USA*).



Multiple Premises (logic paper?)

Goal: Make Natural Logic look more appealing.

The Trivial Case: Parse premises that define edges in a partial order (e.g., *cats are animals*, *Hawaii is in the USA*).

Propositional + Natural Logic

- E.g., $a \vee b; \neg a \Rightarrow b$



Multiple Premises (logic paper?)

Goal: Make Natural Logic look more appealing.

The Trivial Case: Parse premises that define edges in a partial order (e.g., *cats are animals*, *Hawaii is in the USA*).

Propositional + Natural Logic

- E.g., $a \vee b; \neg a \Rightarrow b$
- Shallow semantic parse of sentence for conjunction / disjunction



Multiple Premises (logic paper?)

Goal: Make Natural Logic look more appealing.

The Trivial Case: Parse premises that define edges in a partial order (e.g., *cats are animals*, *Hawaii is in the USA*).

Propositional + Natural Logic

- E.g., $a \vee b; \neg a \Rightarrow b$
- Shallow semantic parse of sentence for conjunction / disjunction
- Operators in hypothesis are trivial (run all atoms and combine)
- Conjunction in premise is trivial (NaturalLI OpenIE can do this)
- Disjunction and material implication in premise is a bit tricky



Multiple Premises (logic paper?)

Goal: Make Natural Logic look more appealing.

The Trivial Case: Parse premises that define edges in a partial order (e.g., *cats are animals*, *Hawaii is in the USA*).

Propositional + Natural Logic

- E.g., $a \vee b; \neg a \Rightarrow b$
- Shallow semantic parse of sentence for conjunction / disjunction
- Operators in hypothesis are trivial (run all atoms and combine)
- Conjunction in premise is trivial (NaturalLI OpenIE can do this)
- Disjunction and material implication in premise is a bit tricky

Probabilistic logic of “some:” *some cats have tails; some cats are male* \Rightarrow *some males have tails* (with some probability)



Fully Leveraging Training Data (??? paper)

Goal: Make NaturalLI less hand-coded.



Fully Leveraging Training Data (??? paper)

Goal: Make NaturalLI less hand-coded.

Research by Analogy:

- MIML-RE is to NaturalLI as Neural QA is to X .
- High level idea: Natural Logic mutations are transforms in vector space.



Fully Leveraging Training Data (??? paper)

Goal: Make NaturalLI less hand-coded.

Research by Analogy:

- MIML-RE is to NaturalLI as Neural QA is to X .
- High level idea: Natural Logic mutations are transforms in vector space.

Implementation 1: NaturalLI in vector space

- Same search, but each rule (e.g., go up WordNet) is a matrix operation. “Hit” a premise if we get close enough.
- Can train from SNLI corpus + MT alignments.



Fully Leveraging Training Data (??? paper)

Goal: Make NaturalLI less hand-coded.

Research by Analogy:

- MIML-RE is to NaturalLI as Neural QA is to X .
- High level idea: Natural Logic mutations are transforms in vector space.

Implementation 1: NaturalLI in vector space

- Same search, but each rule (e.g., go up WordNet) is a matrix operation. “Hit” a premise if we get close enough.
- Can train from SNLI corpus + MT alignments.

Implementation 2: Learn hyperplane between true and false facts.





- Positives from the internet.
- Negatives from mutating *each* positive, + unrelated facts.



Thanks!



References I

-  Angeli, G., Chaganty, A., Chang, A., Reschke, K., Tibshirani, J., Wu, J. Y., Bastani, O., Siilats, K., and Manning, C. D. (2014a). Stanford's 2013 KBP system.
In *TAC-KBP*.
-  Angeli, G. and Manning, C. D. (2013). Philosophers are mortal: Inferring the truth of unseen facts.
In *CoNLL*.
-  Angeli, G. and Manning, C. D. (2014). Naturalli: Natural logic inference for common sense reasoning.
In *EMNLP*.
-  Angeli, G., Tibshirani, J., Wu, J. Y., and Manning, C. D. (2014b). Combining distant and partial supervision for relation extraction.
In *EMNLP*.

