

API Documentation

Market

Get market info

Retrieve general market information

Method: GET

Endpoint: /v1/market/get-market-info

[Try it]

Request Example

```
curl --request GET \  
  --url  
[https://api.modo.link/canton-mainnet/v1/market/get-market-info](https://api.modo.link/canton-mainnet/v1/market/get-market-info) \  
  --header 'x-api-key: <api-key>'
```

Response Example (200 OK)

```
{  
  "circulatingSupply": {  
    "valueCoin": 123  
  },  
  "dominanceDto": {  
    "valuePercent": 123  
  },  
  "marketCapDto": {  
    "changePercent": 123,  
    "valueUsd": 123,  
    "period": "<string>"  
  },  
  "totalSupplyDto": {  
    "valueCoin": 123,  
    "valueUsd": 123  
  },  
  "totalStakeDto": {  
    "valueCoin": 123,  
    "valueUsd": 123  
  }  
}
```

```
},  
"tokenPriceDto": {  
  "price": 123,  
  "change24h": 123,  
  "updateTimestamp": 123  
},  
"updateTimestamp": 123  
}
```

Documentation Index > Fetch the complete documentation index at:
<https://docs.modo.link/lms.txt>

Use this file to discover all available pages before exploring further.

Authorizations

- **x-api-key**: string [header] **required**

Response Structure (200 - / OK)

- **circulatingSupply**: object (*Show child attributes*)
- **dominanceDto**: object (*Show child attributes*)
- **marketCapDto**: object (*Show child attributes*)
- **totalSupplyDto**: object (*Show child attributes*)
- **totalStakeDto**: object (*Show child attributes*)
- **tokenPriceDto**: object (*Show child attributes*)
- **updateTimestamp**: integer<int64>

Get token rate

Retrieve the current token price

Method: GET

Endpoint: /v1/market/get-price

[Try it]

Request Example

```
curl --request GET \  
  --url  
[https://api.modo.link/canton-mainnet/v1/market/get-price](https://api.modo.link/canton-mainnet/  
v1/market/get-price) \  
  --header 'x-api-key: <api-key>'
```

Response Example (200 OK)

```
{  
  "price": 123,  
  "change24h": 123,  
  "updateTimestamp": 123  
}
```

Documentation Index > Fetch the complete documentation index at:
<https://docs.modo.link/lms.txt>

Use this file to discover all available pages before exploring further.

Authorizations

- **x-api-key**: string [header] **required**

Response Structure (200 - / OK)

- **price**: number<double>
- **change24h**: number<double>
- **updateTimestamp**: integer<int64>

Parties

Get parties list

Retrieve paginated list of parties

Method: GET

Endpoint: /v1/parties

[Try it]

Request Example

```
curl --request GET \  
  --url  
  '[https://api.modo.link/canton-mainnet/v1/parties?sortBy=LAST_ACTIVITY_AT&size=20&orderB  
y=DESC](https://api.modo.link/canton-mainnet/v1/parties?sortBy=LAST_ACTIVITY_AT&size=2  
0&orderBy=DESC)' \  
  --header 'x-api-key: <api-key>'
```

Response Example (200 OK)

```
{
  "content": [
    {
      "partyAddress": "<string>",
      "partyName": "<string>",
      "partyImg": "<string>",
      "balance": 123,
      "firstSeen": 123,
      "lastSeen": 123,
      "totalRewards": 123
    }
  ],
  "pageable": {
    "sort": {
      "sorted": true,
      "empty": true,
      "unsorted": true
    },
    "pageSize": 123, "pageNumber": 123, "offset": 123, "paged": true, "unpaged": true },
  "last": true, "totalPages": 123, "totalElements": 123, "totalCount": 123, "size": 123, "number":
  123, "sort": { "sorted": true, "empty": true, "unsorted": true }, "first": true,
  "numberOfElements": 123, "empty": true}
```

Documentation Index > Fetch the complete documentation index at:
<https://docs.modo.link/lms.txt>

Use this file to discover all available pages before exploring further.

Authorizations

- **x-api-key**: string [header] **required**

Query Parameters

- **sortBy**: enum<string> [default: LAST_ACTIVITY_AT] **required**
 - Sorting parameter. Available options: LAST_ACTIVITY_AT, FIRST_SEEN_AT
- **page**: integer<int32> [default: 0] **required**
 - Queried API page. Required range: 0 <= x <= 50
- **size**: integer<int32> [default: 20] **required**
 - Number of queried entries. Required range: 1 <= x <= 100
- **orderBy**: enum<string> [default: DESC] **required**
 - Sorting method: from the lowest element to the highest (ASC) or from the highest

element to the lowest (DESC). Available options: ASC, DESC

Response Structure (200 - / OK)

- **content:** object[] (*Show child attributes*)
- **pageable:** object (*Show child attributes*)
- **last:** boolean
- **totalPages:** integer<int64>
- **totalElements:** integer<int64>
- **totalCount:** integer<int64>
- **size:** integer<int32>
- **number:** integer<int32>
- **sort:** object (*Show child attributes*)
- **first:** boolean
- **numberOfElements:** integer<int32>
- **empty:** boolean

Get top parties

Retrieve paginated list of top parties

Method: GET

Endpoint: /v1/parties/top

[Try it]

Request Example

```
curl --request GET \
  --url
'https://api.mod0.link/canton-mainnet/v1/parties/top?sortBy=BALANCE&size=20&orderBy=DESC'
'https://api.mod0.link/canton-mainnet/v1/parties/top?sortBy=BALANCE&size=20&orderBy=DESC' \
  --header 'x-api-key: <api-key>'
```

Response Example (200 OK)

```
{
  "content": [
    {
      "partyAddress": "<string>",
      "partyName": "<string>",
      "partyImg": "<string>",
      "balance": 123,
      "firstSeen": 123,
```

```

    "lastSeen": 123,
    "totalRewards": 123
  }
],
"pageable": {
  "sort": {
    "sorted": true,
    "empty": true,
    "unsorted": true
  },
  "pageSize": 123,
  "pageNumber": 123,
  "offset": 123,
  "paged": true,
  "unpaged": true
},
"last": true,
"totalPages": 123,
"totalElements": 123,
"totalCount": 123,
"size": 123,
"number": 123,
"sort": {
  "sorted": true,
  "empty": true,
  "unsorted": true
},
"first": true,
"numberOfElements": 123,
"empty": true
}

```

Documentation Index > Fetch the complete documentation index at:
<https://docs.modo.link/lms.txt>

Use this file to discover all available pages before exploring further.

Authorizations

- **x-api-key**: string [header] **required**

Query Parameters

- **sortBy**: enum<string> [default: BALANCE] **required**

- Sorting parameter. Available options: BALANCE
- **page:** integer<int32> [default: 0] **required**
 - Queried API page. Required range: $0 \leq x \leq 50$
- **size:** integer<int32> [default: 20] **required**
 - Number of queried entries. Required range: $1 \leq x \leq 100$
- **orderBy:** enum<string> [default: DESC] **required**
 - Sorting method: from the lowest element to the highest (ASC) or from the highest element to the lowest (DESC). Available options: ASC, DESC

Response Structure (200 - / OK)

- **content:** object[] (*Show child attributes*)
- **pageable:** object (*Show child attributes*)
- **last:** boolean
- **totalPages:** integer<int64>
- **totalElements:** integer<int64>
- **totalCount:** integer<int64>
- **size:** integer<int32>
- **number:** integer<int32>
- **sort:** object (*Show child attributes*)
- **first:** boolean
- **numberOfElements:** integer<int32>
- **empty:** boolean

Get party details

Retrieve detailed information about a specific party

Method: GET

Endpoint: /v1/parties/{partyId}

[Try it]

Request Example

```
curl --request GET \
  --url
[https://api.modo.link/canton-mainnet/v1/parties/](https://api.modo.link/canton-mainnet/v1/parties
/){partyId} \
  --header 'x-api-key: <api-key>'
```

Response Example (200 OK)

```
{
  "partyId": "<string>",
```

```

"createdAt": 123,
"holdingsSummaryResponse": {
  "record_time": "2023-11-07T05:31:56Z",
  "migration_id": 123,
  "computed_as_of_round": 123,
  "summaries": [
    {
      "party_id": "<string>",
      "total_unlocked_coin": "<string>",
      "total_locked_coin": "<string>",
      "total_coin_holdings": "<string>",
      "accumulated_holding_fees_unlocked": "<string>",
      "accumulated_holding_fees_locked": "<string>",
      "accumulated_holding_fees_total": "<string>",
      "total_available_coin": "<string>",
      "record_time": "2023-11-07T05:31:56Z",
      "migration_id": 123,
      "computed_as_of_round": 123
    }
  ]
}
}

```

Documentation Index > Fetch the complete documentation index at:
<https://docs.modo.link/llms.txt>

Use this file to discover all available pages before exploring further.

Authorizations

- **x-api-key**: string [header] **required**

Path Parameters

- **partyId**: string **required**
 - Party ID

Response Structure (200 - / OK)

- **partyId**: string
- **createdAt**: integer<int64>
- **holdingsSummaryResponse**: object

Get party types

Retrieve party types for a specific party

Method: GET

Endpoint: /v1/parties/{partyId}/types

[Try it]

Request Example

```
curl --request GET \  
  --url \  
[https://api.modolink/canton-mainnet/v1/parties/](https://api.modolink/canton-mainnet/v1/parties/  
{partyId}/types \  
  --header 'x-api-key: <api-key>'
```

Response Example (200 OK)

```
{  
  "isAccount": true,  
  "isValidator": true,  
  "isSv": true  
}
```

Documentation Index > Fetch the complete documentation index at:
<https://docs.modolink.com/docs.txt>

Use this file to discover all available pages before exploring further.

Authorizations

- **x-api-key:** string [header] **required**

Path Parameters

- **partyId:** string **required**
 - Party ID

Response Structure (200 - / OK)

- **isAccount:** boolean
- **isValidator:** boolean
- **isSv:** boolean