

API Documentation

Tokens

Get tokens list

Get a list of all token denominations

Method: GET

Endpoint: /v1/tokens

[Try it]

Request Example

```
curl --request GET \
  --url
'https://api.mod0.link/canton-mainnet/v1/tokens?sortBy=CREATED_AT&size=20&orderBy=DESC'
  --header 'x-api-key: <api-key>'
```

Response Example (200 OK)

```
{
  "content": [
    {
      "symbol": "<string>",
      "contractId": "<string>",
      "templateId": "<string>",
      "registrar": "<string>",
      "createdAt": 123
    }
  ],
  "pageable": {
    "sort": {
      "sorted": true,
      "empty": true,
      "unsorted": true
    },
    "pageSize": 123,
    "pageNumber": 123,
```

```

    "offset": 123,
    "paged": true,
    "unpaged": true
  },
  "last": true,
  "totalPages": 123,
  "totalElements": 123,
  "totalCount": 123,
  "size": 123,
  "number": 123,
  "sort": {
    "sorted": true,
    "empty": true,
    "unsorted": true
  },
  "first": true,
  "numberOfElements": 123,
  "empty": true
}

```

Documentation Index > Fetch the complete documentation index at:
<https://docs.modolink.com/lms.txt>

Use this file to discover all available pages before exploring further.

Authorizations

- **x-api-key**: string [header] **required**

Query Parameters

- **search**: string
 - Search tokens by symbol, name, or contract ID.
- **sortBy**: enum<string> [default: CREATED_AT] **required**
 - Sorting parameter. Available options: CREATED_AT
- **page**: integer<int32> [default: 0] **required**
 - Queried API page. Required range: 0 <= x <= 50
- **size**: integer<int32> [default: 20] **required**
 - Number of queried entries. Required range: 1 <= x <= 100
- **orderBy**: enum<string> [default: DESC] **required**
 - Sorting method: from the lowest element to the highest (ASC) or from the highest element to the lowest (DESC). Available options: ASC, DESC

Response Structure (200 - / OK)

- **content:** object[] (*Show child attributes*)
- **pageable:** object (*Show child attributes*)
- **last:** boolean
- **totalPages:** integer<int64>
- **totalElements:** integer<int64>
- **totalCount:** integer<int64>
- **size:** integer<int32>
- **number:** integer<int32>
- **sort:** object (*Show child attributes*)
- **first:** boolean
- **numberOfElements:** integer<int32>
- **empty:** boolean

Get token details

Get token details by contract id

Method: GET

Endpoint: /v1/tokens/{contractId}

[Try it]

Request Example

```
curl --request GET \
  --url
[https://api.mod0.link/canton-mainnet/v1/tokens/](https://api.mod0.link/canton-mainnet/v1/tokens
/){contractId} \
  --header 'x-api-key: <api-key>'
```

Response Example (200 OK)

```
{
  "id": "<string>",
  "name": "<string>",
  "symbol": "<string>",
  "operator": "<string>",
  "provider": "<string>",
  "registrar": "<string>",
  "contractId": "<string>",
  "templateId": "<string>",
  "domainId": "<string>",
  "createdEventBlob": "<string>",
  "createdAt": 123,
```

```
"additionalIdentifiersJson": {},  
"issuerRequirementsJson": {},  
"holderRequirementsJson": {}  
}
```

Documentation Index > Fetch the complete documentation index at:
<https://docs.mod0.link/lms.txt>

Use this file to discover all available pages before exploring further.

Authorizations

- **x-api-key**: string [header] **required**

Path Parameters

- **contractId**: string **required**
 - Contract id

Response Structure (200 - / OK)

- **id**: string
- **name**: string
- **symbol**: string
- **operator**: string
- **provider**: string
- **registrar**: string
- **contractId**: string
- **templateId**: string
- **domainId**: string
- **createdEventBlob**: string
- **createdAt**: integer<int64>
- **additionalIdentifiersJson**: object
- **issuerRequirementsJson**: object
- **holderRequirementsJson**: object

Transfers

Get transfers list

Retrieve paginated list of transfers

Method: GET

Endpoint: /v1/transfers

[Try it]

Request Example

```
curl --request GET \
  --url
'https://api.mod0.link/canton-mainnet/v1/transfers?sortBy=CREATED_AT&size=20&orderBy=D
ESC'(https://api.mod0.link/canton-mainnet/v1/transfers?sortBy=CREATED_AT&size=20&orderB
y=DESC)' \
  --header 'x-api-key: <api-key>'
```

Response Example (200 OK)

```
{
  "content": [
    {
      "eventId": "<string>",
      "transferType": "<string>",
      "senders": [
        {
          "partyId": "<string>",
          "accountName": "<string>",
          "imageUrl": "<string>"
        }
      ],
      "receivers": [
        {
          "partyId": "<string>",
          "accountName": "<string>",
          "imageUrl": "<string>"
        }
      ],
      "amount": 123,
      "fee": 123,
      "amuletPrice": 123,
      "createdAt": 123
    }
  ],
  "pageable": {
    "sort": {
      "sorted": true,
      "empty": true,
      "unsorted": true
    }
  }
}
```

```

    },
    "pageSize": 123,
    "pageNumber": 123,
    "offset": 123,
    "paged": true,
    "unpaged": true
  },
  "last": true,
  "totalPages": 123,
  "totalElements": 123,
  "totalCount": 123,
  "size": 123,
  "number": 123,
  "sort": {
    "sorted": true,
    "empty": true,
    "unsorted": true
  },
  "first": true,
  "numberOfElements": 123,
  "empty": true
}

```

Documentation Index > Fetch the complete documentation index at:
<https://docs.modolink.com/lms.txt>

Use this file to discover all available pages before exploring further.

Authorizations

- **x-api-key**: string [header] **required**

Query Parameters

- **sortBy**: enum<string> [default: CREATED_AT] **required**
 - Sorting parameter. Available options: CREATED_AT
- **page**: integer<int32> [default: 0] **required**
 - Queried API page. Required range: 0 <= x <= 50
- **size**: integer<int32> [default: 20] **required**
 - Number of queried entries. Required range: 1 <= x <= 100
- **orderBy**: enum<string> [default: DESC] **required**
 - Sorting method: from the lowest element to the highest (ASC) or from the highest element to the lowest (DESC). Available options: ASC, DESC

Response Structure (200 - / OK)

- **content:** object[] (*Show child attributes*)
- **pageable:** object (*Show child attributes*)
- **last:** boolean
- **totalPages:** integer<int64>
- **totalElements:** integer<int64>
- **totalCount:** integer<int64>
- **size:** integer<int32>
- **number:** integer<int32>
- **sort:** object (*Show child attributes*)
- **first:** boolean
- **numberOfElements:** integer<int32>
- **empty:** boolean

Get transfers by party

Retrieve paginated list of transfers for a specific party

Method: GET

Endpoint: /v1/transfers/{partyId}

[Try it]

Request Example

```
curl --request GET \
  --url
'https://api.modo.link/canton-mainnet/v1/transfers/](https://api.modo.link/canton-mainnet/v1/transfers/){partyId}?role=ANY&sortBy=AGE&size=20&orderBy=DESC' \
  --header 'x-api-key: <api-key>'
```

Response Example (200 OK)

```
{
  "content": [
    {
      "eventId": "<string>",
      "transferType": "<string>",
      "senders": [
        {
          "partyId": "<string>",
          "accountName": "<string>",
          "imageUrl": "<string>"
        }
      ]
    }
  ]
}
```

```

    }
  ],
  "receivers": [
    {
      "partyId": "<string>",
      "accountName": "<string>",
      "imageUrl": "<string>"
    }
  ],
  "amount": 123,
  "fee": 123,
  "createdAt": 123
}
],
"hasNextPage": true,
"nextCursor": "<string>"
}

```

Documentation Index > Fetch the complete documentation index at:
<https://docs.modo.link/lms.txt>

Use this file to discover all available pages before exploring further.

Authorizations

- **x-api-key**: string [header] **required**

Path Parameters

- **partyId**: string **required**
 - Party ID

Query Parameters

- **role**: enum<string> [default: ANY]
 - Filter transfers by role: ANY, SENDER, RECEIVER, or PROVIDER. Available options: ANY, SENDER, RECEIVER, PROVIDER
- **sortBy**: enum<string> [default: AGE] **required**
 - Sorting parameter. Available options: AGE
- **size**: integer<int32> [default: 20] **required**
 - Number of queried entries. Required range: 1 <= x <= 100
- **orderBy**: enum<string> [default: DESC] **required**
 - Sorting method: from the lowest element to the highest (ASC) or from the highest element to the lowest (DESC). Available options: ASC, DESC
- **nextCursor**: string

- Cursor for pagination to retrieve the next page of results. Leave empty for the first page.

Response Structure (200 - / OK)

- **content:** object[] (*Show child attributes*)
- **hasNextPage:** boolean
- **nextCursor:** string