



Week 4 : MACHINE LEARNING OPERATIONS

# **Week 4**

## **Undoing Changes**

## Week 4 Undoing Changes

- We've explored how to create repositories, how to push and pull code from GitHub, how to use commits with Git, and how to work with branches.
- But what happens when we make a mistake or wish to undo an action?
- Or what if we wish to explore some historical commits?

## Week 4 Undoing Changes

- Today we're focused on how to undo actions related to git commands and explore historical commits.
- We'll discuss:
  - **git checkout** and **Detached HEAD**
  - **git restore**
  - **git reset**
  - **git revert**

## Week 4 Undoing Changes

- Keep in mind that you don't use these commands as often as the other commands we've learned so far, but they are still important actions to know!

**Let's get started!**

# **Week 4**

## **Git Checkout**

## Week 4 Undoing Changes

- **git checkout**

- This is actually a very versatile command, so versatile in fact, that developers complained it was used for too many different actions, thus new git commands were created, such as **git switch**.



## Week 4 Undoing Changes

- **git checkout**

- A "checkout" is the act of switching between different versions of a target entity.
- The **git checkout** command can operate on three distinct entities: files, commits, and branches.

## Week 4 Undoing Changes

- **git checkout**

- For example, you could use **git checkout branch\_name** instead of **git switch branch\_name** to checkout a new branch.
- Unlike **git switch** however, recall checkout can operate on commits, meaning we can “checkout” historical commits.


## Week 4 Undoing Changes

- **git checkout**

- We can check out a particular commit by specifying its hash, we can get hashes from the **git log** command and we can also see the abbreviated hash using:
  - **git log --oneline**
- Then we can provide the hash as:
  - **git checkout #####**


## Week 4 Undoing Changes

- Typically our HEAD points to the branch which points to the latest commit.




## Week 4 Undoing Changes

- Upon calling **git checkout a9jd3h7** we detach the HEAD to a previous commit




## Week 4 Undoing Changes

- You can think of this as traveling back in history to what your code looked like when you ran this commit.




## Week 4 Undoing Changes

- This command does **not** undo previous work, you are simply exploring the historical commit.



## Week 4 Undoing Changes


- If you started making changes here, they won't be preserved since HEAD is not pointing at a branch reference.






## Week 4 Undoing Changes

- However you could create a new branch at this point in time, reattaching HEAD to a branch again.




## Week 4 Undoing Changes

- However you could create a new branch at this point in time, reattaching HEAD to a branch again.



## Week 4 Undoing Changes

- However you could create a new branch at this point in time, reattaching HEAD to a branch again.



## Week 4 Undoing Changes

- Let's explore these commands in practice!

# **Week 4**

## **Git Restore**

## Week 4 Undoing Changes

- Imagine you've been working on a file that is already part of a commit.
- You know the code was working at the point of the last commit, however now the code is totally broken, and you just can't seem to fix it.
- You've written too much code to just run Ctrl+Z! How to fix this?

## Week 4 Undoing Changes

- **Git restore**

- We can restore a file to its state at the previous most recent commit using the

**git restore command:**

- **git restore file\_name**

## Week 4 Undoing Changes

- **Git restore**

- We can restore a file to its state at the previous most recent commit using the

**git restore command:**

- **git restore file\_name**

- ***Warning:***

- You can not undo a git restore command, since your changes were not committed!



## Week 4 Undoing Changes

- **Git restore**

- We can restore a file to its state at the previous most recent commit using the **git restore command**:
  - **git restore file\_name**
- **Warning:**
  - Think of this command as an ultimate “Ctrl+Z” restoring files to their previous commit.

## Week 4 Undoing Changes

- **Git restore**

- Technically speaking **git restore** will restore the file back to the HEAD, which typically we have pointing to the most recent commit in the branch.

## Week 4 Undoing Changes

- **Git restore**

- This actually gives us even more flexibility in our restore procedure, we can restore a file to any commit in the log.
- We state the number of commits from the HEAD to go back to:
  - **git restore --source HEAD~N file.txt**

## Week 4 Undoing Changes

- **Git restore**

- This actually gives us even more flexibility in our restore procedure, we can restore a file to any commit in the log.
- We state the number of commits prior from the HEAD to go back to:
  - **git restore --source HEAD~N file.txt**

## Week 4 Undoing Changes

- **Git restore**

- This actually gives us even more flexibility in our restore procedure, we can restore a file to any commit in the log.
- We state the number of commits prior from the HEAD to go back to:
  - **git restore --source HEAD~N file.txt**

## Week 4 Undoing Changes

- **Git restore**

- Finally, git restore also allows us to unstage files that we had already added to the staging area using **git add**.
- We can do this with:
  - **git restore --staged filename**

## Week 4 Undoing Changes

- Let's explore this command in practice:
  - **git restore filename**
  - **git restore --source HEAD~N filename**
  - **git restore --staged filename**

# **Week 4**

## **Git Reset**



## Week 4 Undoing Changes

- Git reset allows us to remove commits and “reset” the branch.
- There are two main types of **git reset** calls:
  - **git reset #####**
    - Removes commits in front of the specific hash called, files unchanged.
  - **git reset ##### --hard**
    - Removes commits *and* the changes in the files.

## Week 4 Undoing Changes

- To fully understand this, let's recall our discussions about working directory, staging area, and repository.

# Week 4 Undoing Changes

Working Directory



program.py

Staging Area

Repository

# Week 4 Undoing Changes

Working Directory



Staging Area

`program.py`

Repository

# Week 4 Undoing Changes

Working Directory



Staging Area



Repository

`program.py`

“python code”  
f3h4782

# Week 4 Undoing Changes

Working Directory



index.html

style.css

Staging Area

Repository

program.py

“python code”  
f3h4782

# Week 4 Undoing Changes

Working Directory



Staging Area

index.html

style.css

Repository

program.py

“python code”  
f3h4782

# Week 4 Undoing Changes

Working Directory



Staging Area



Repository

program.py

“python code”  
f3h4782

index.html

style.css

“style code”  
g82j37l



# Week 4 Undoing Changes

Working Directory



Staging Area



Repository

program.py

“python code”  
f3h4782

index.html

style.css

“style code”  
g82j37l

# Week 4 Undoing Changes

Working Directory



Staging Area

Repository

```
>>git reset f3h4782
```

program.py

“python code”  
f3h4782

index.html

style.css

“style code”  
g82j37l

# Week 4 Undoing Changes

Working Directory



index.html

style.css

Staging Area

Repository

program.py

“python code”  
f3h4782

# Week 4 Undoing Changes

Working Directory



index.html

style.css

Staging Area

Files are unchanged!  
You just reset the  
commits only.

Repository

program.py

“python code”  
f3h4782

## Week 4 Undoing Changes

- This means when you do **git reset** you won't notice a change in the files themselves, you just reset the commits.
- This is useful if you accidentally committed to the wrong branch (for example, maybe you forgot to run **git switch** right after creating a new branch, accidentally committing to the original branch).

## Week 4 Undoing Changes

- What if you do want the files to change?
- In the case where you just want to undo everything, including changes and have the branch files look like they did at a previous commit, you add the flag **--hard**.
- For example:
  - **git reset f3h4782 --hard**

# Week 4 Undoing Changes

Working Directory



Staging Area



Repository

program.py

“python code”  
f3h4782

index.html

style.css

“style code”  
g82j37l

# Week 4 Undoing Changes

Working Directory



Staging Area

Repository

program.py

“python code”  
f3h4782

index.html

style.css

“style code”  
g82j37l

```
>>git reset f3h4782 --hard
```



# Week 4 Undoing Changes

Working Directory



Staging Area

Repository


program.py

“python code”  
f3h4782

```
>>git reset f3h4782 --hard
```


## Week 4 Undoing Changes

- We can visualize a **git reset** moving back to a previous commit, but not undoing file changes (unless it is --hard)




## Week 4 Undoing Changes

- We can visualize a **git reset** moving back to a previous commit, but not undoing file changes (unless it is --hard)



## Week 4 Undoing Changes

- We can visualize a **git reset** moving back to a previous commit, but not undoing file changes (unless it is --hard)



## Week 4 Undoing Changes

- *Can you undo a git reset --hard?*
  - Technically you can try to recover a commit before Git does its garbage collection, however you should operate under the assumption that a --hard reset is not recoverable.

## Week 4 Undoing Changes

- Let's explore examples of **git reset**!

# **Week 4**

## **Git Revert**


## Week 4 Undoing Changes

- Let's explore the last command for undoing changes, **git revert**.
- The **git revert** command will create a new commit that undoes work from previous commits, but keeps those commits in the branch.




## Week 4 Undoing Changes

- Let's review a **git reset** first.
- A **git reset** goes back and removes the commits (and changes if its **--hard**)




## Week 4 Undoing Changes

- Let's review a **git reset** first.
- A **git reset** goes back and removes the commits (and changes if its **--hard**)




## Week 4 Undoing Changes

- Let's review a **git reset** first.
- A **git reset** goes back and removes the commits (and changes if its **--hard**)




## Week 4 Undoing Changes

- Why could this be an issue?
- You can lose **shared history**!




## Week 4 Undoing Changes

- Why could this be an issue?
- You can lose **shared history**!




## Week 4 Undoing Changes

- Why could this be an issue?
- You can lose **shared history**!




## Week 4 Undoing Changes

- This makes a merge of the branches harder!



## Week 4 Undoing Changes

- A **git revert** creates a new commit that matches the historical state of a previous commit.






## Week 4 Undoing Changes

- **Git revert** doesn't change the project history, which makes it a “safe” operation for commits that have already been published to a shared repository.


## Week 4 Undoing Changes

- A **git revert** creates a new commit that matches the historical state of a previous commit.




## Week 4 Undoing Changes

- A **git revert** creates a new commit that matches the historical state of a previous commit.




## Week 4 Undoing Changes

- A **git revert** creates a new commit that matches the historical state of a previous commit.



## Week 4 Undoing Changes

- The **git revert** command is a forward-moving undo operation that offers a safe method of undoing changes. Instead of deleting or orphaning commits in the commit history, a revert will create a new commit that inverses the changes specified.



## Week 4 Undoing Changes

- **Git revert** is a safer alternative to git reset in regards to losing work.

