

# Rajalakshmi Engineering College

Name: TUFAIL AHMED B  
Email: 241901119@rajalakshmi.edu.in  
Roll no: 241901119  
Phone: 9566336640  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 3\_COD\_Question 1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

In a coding competition, you are assigned a task to create a program that simulates a stack using a linked list.

The program should feature a menu-driven interface for pushing an integer to stack, popping, and displaying stack elements, with robust error handling for stack underflow situations. This challenge tests your data structure skills.

##### ***Input Format***

The input consists of integers corresponding to the operation that needs to be performed:

Choice 1: Push the integer value onto the stack. If the choice is 1, the following input is a space-separated integer, representing the element to be pushed onto

the stack.

Choice 2: Pop the integer from the stack.

Choice 3: Display the elements in the stack.

Choice 4: Exit the program.

### ***Output Format***

The output displays messages according to the choice and the status of the stack:

If the choice is 1, push the given integer to the stack and display the following:  
"Pushed element: " followed by the value pushed.

If the choice is 2, pop the integer from the stack and display the following:  
"Popped element: " followed by the value popped.

If the choice is 2, and if the stack is empty without any elements, print "Stack is empty. Cannot pop."

If the choice is 3, print the elements in the stack: "Stack elements (top to bottom): " followed by the space-separated values.

If the choice is 3, and there are no elements in the stack, print "Stack is empty".

If the choice is 4, exit the program and display the following: "Exiting program".

If any other choice is entered, print "Invalid choice".

Refer to the sample input and output for the exact format.

### **Sample Test Case**

Input: 1 3

1 4

3

2

3

4

Output: Pushed element: 3

Pushed element: 4

Stack elements (top to bottom): 4 3

Popped element: 4

Stack elements (top to bottom): 3

Exiting program

### **Answer**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int data;  
    struct Node* next;  
};
```

```
struct Node* top = NULL;
```

```
// You are using GCC
```

```
void push(int value) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    newNode->data = value;  
    newNode->next = top;  
    printf("Pushed element: %d\n", newNode->data);  
    top = newNode;  
}
```

```

void pop() {
    if (top == NULL) {
        printf("Stack is empty. Cannot pop.\n");
        return;
    }
    struct Node* temp = top;
    printf("Popped element: %d\n", top->data);
    top = top->next;
    free(temp);
}

```

```

void displayStack() {
    if (top == NULL) {
        printf("Stack is empty\n");
        return;
    }
    struct Node* temp = top;
    printf("Stack elements (top to bottom): ");
    while (temp != NULL) {
        printf("%d ", temp->data);
        temp = temp->next;
    }
    printf("\n");
}

```

```

int main() {
    int choice, value;
    do {
        scanf("%d", &choice);
        switch (choice) {
            case 1:
                scanf("%d", &value);
                push(value);
                break;
            case 2:
                pop();
                break;
            case 3:
                displayStack();
                break;
            case 4:
                printf("Exiting program\n");
                return 0;
        }
    } while (choice != 4);
}

```

```
        default:
            printf("Invalid choice\n");
        }
    } while (choice != 4);

    return 0;
}
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: TUFAIL AHMED B  
Email: 241901119@rajalakshmi.edu.in  
Roll no: 241901119  
Phone: 9566336640  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 3\_COD\_Question 2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 2.5

#### Section 1 : Coding

##### 1. Problem Statement

Sanjeev is in charge of managing a library's book storage, and he wants to create a program that simplifies this task. His goal is to implement a program that simulates a stack using an array.

Help him in writing a program that provides the following functionality:

Add Book ID to the Stack (Push): You can add a book ID to the top of the book stack. Remove Book ID from the Stack (Pop): You can remove the top book ID from the stack and display its details. If the stack is empty, you cannot remove any more book IDs. Display Books ID in the Stack (Display): You can view the books ID currently on the stack. Exit the Library: You can choose to exit the program.

##### **Input Format**

The input consists of integers corresponding to the operation that needs to be performed:

Choice 1: Push the book onto the stack. If the choice is 1, the following input is a space-separated integer, representing the ID of the book to be pushed onto the stack.

Choice 2: Pop the book ID from the stack.

Choice 3: Display the book ID in the stack.

Choice 4: Exit the program.

### **Output Format**

The output displays messages according to the choice and the status of the stack:

1. If the choice is 1, push the given book ID to the stack and display the corresponding message.
2. If the choice is 2, pop the book ID from the stack and display the corresponding message.
3. If the choice is 2, and if the stack is empty without any book ID, print "Stack Underflow"
4. If the choice is 3, print the book IDs in the stack.
5. If the choice is 3, and there are book IDs in the stack, print "Stack is empty"
6. If the choice is 4, exit the program and display the corresponding message.
7. If any other choice is entered, print "Invalid choice"

Refer to the sample output for the exact text and format.

### **Sample Test Case**

Input: 1 19

1 28

2

3

2

4

Output: Book ID 19 is pushed onto the stack

Book ID 28 is pushed onto the stack

Book ID 28 is popped from the stack  
Book ID in the stack: 19  
Book ID 19 is popped from the stack  
Exiting the program

**Answer**

```
// You are using GCC
#include <stdio.h>
#include <stdlib.h>
```

```
#define MAX_SIZE 100
```

```
struct Stack {
    int arr[MAX_SIZE];
    int top;
};
```

```
void initStack(struct Stack* stack) {
    stack->top = -1;
}
```

```
void push(struct Stack* stack, int book_id) {
    if (stack->top >= MAX_SIZE - 1) {
        printf("Stack Overflow\n");
    } else {
        stack->arr[++(stack->top)] = book_id;
        printf("Book ID %d is pushed onto the stack\n", book_id);
    }
}
```

```
void pop(struct Stack* stack) {
    if (stack->top == -1) {
        printf("Stack Underflow\n");
    } else {
        int book_id = stack->arr[(stack->top)--];
        printf("Book ID %d is popped from the stack\n", book_id);
    }
}
```

```
void display(struct Stack* stack) {
    if (stack->top == -1) {
        printf("Stack is empty\n");
    }
}
```



```
    } else {  
        printf("Book ID in the stack: ");  
        for (int i = 0; i <= stack->top; i++) {  
            printf("%d ", stack->arr[i]);  
        }  
        printf("\n");  
    }  
}
```

```
int main() {  
    struct Stack stack;  
    int choice, book_id;  
  
    initStack(&stack);  
  
    while (1) {  
        scanf("%d", &choice);  
  
        switch (choice) {  
            case 1:  
                scanf("%d", &book_id);  
                push(&stack, book_id);  
                break;  
  
            case 2:  
                pop(&stack);  
                break;  
  
            case 3:  
                display(&stack);  
                break;  
  
            case 4:  
                printf("Exiting the program\n");  
                return 0;  
  
            default:  
                printf("Invalid choice\n");  
                break;  
        }  
    }  
}
```

```
} return 0;
```

**Status :** Partially correct

**Marks :** 2.5/10

# Rajalakshmi Engineering College

Name: TUFAIL AHMED B  
Email: 241901119@rajalakshmi.edu.in  
Roll no: 241901119  
Phone: 9566336640  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 3\_COD\_Question 3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Sharon is developing a programming challenge for a coding competition. The challenge revolves around implementing a character-based stack data structure using an array.

Sharon's project involves a stack that can perform the following operations:

Push a Character: Users can push a character onto the stack. Pop a Character: Users can pop a character from the stack, removing and displaying the top character. Display Stack: Users can view the current elements in the stack. Exit: Users can exit the stack operations application.

Write a program to help Sharon to implement a program that performs the given operations.

***Input Format***

The input consists of integers corresponding to the operation that needs to be performed:

Choice 1: Push the character onto the stack. If the choice is 1, the following input is a space-separated character, representing the character to be pushed onto the stack.

Choice 2: Pop the character from the stack.

Choice 3: Display the characters in the stack.

Choice 4: Exit the program.

### ***Output Format***

The output displays messages according to the choice and the status of the stack:

1. If the choice is 1, push the given character to the stack and display the pushed character having the prefix "Pushed: ".
2. If the choice is 2, undo the character from the stack and display the character that is popped having the prefix "Popped: ".
3. If the choice is 2, and if the stack is empty without any characters, print "Stack is empty. Nothing to pop."
4. If the choice is 3, print the elements in the stack having the prefix "Stack elements: ".
5. If the choice is 3, and there are no characters in the stack, print "Stack is empty."
6. If the choice is 4, exit the program.
7. If any other choice is entered, print "Invalid choice"

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 2

4

Output: Stack is empty. Nothing to pop.

### ***Answer***

```
#include <stdio.h>
```

```
#include <stdbool.h>
```

```
#define MAX_SIZE 100
```

```
char items[MAX_SIZE];
```

```
int top = -1;
```

```
void initialize() {
```

```
    top = -1;
```

```
}
```

```
bool isFull() {
```

```
    return top == MAX_SIZE - 1;
```

```
}
```

```
bool isEmpty() {
```

```
    return top == -1;
```

```
}
```

```
// You are using GCC
```

```
void push(char value) {
```

```
    if (isFull()) {
```

```
        printf("Stack is empty.\n");
```

```
        return;
```

```
    }
```

```
    items[++top] = value;
```

```
    printf("Pushed: %c\n", value);
```

```
}
```

```
char pop() {
```

```
    if (isEmpty()) {
```

```
        printf("Stack is empty. Nothing to pop.\n");
```

```
        return '\0';
```

```
    }
```

```
    char poppedValue = items[top--];
```

```
    printf("Popped: %c\n", poppedValue);
```

```
    return poppedValue;
```

```
}
```

```
void display() {
```

```
    if (isEmpty()) {
```

```
        printf("Stack is empty.\n");
```

```
        return;
```

```
    }
```

```
    printf("Stack elements: ");
    for (int i = top; i >= 0; i--) {
        printf("%c ", items[i]);
    }
    printf("\n");
}

int main() {
    initialize();
    int choice;
    char value;

    while (true) {
        scanf("%d", &choice);
        switch (choice) {
            case 1:
                scanf(" %c", &value);
                push(value);
                break;
            case 2:
                pop();
                break;
            case 3:
                display();
                break;
            case 4:
                return 0;
            default:
                printf("Invalid choice\n");
        }
    }
    return 0;
}
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: TUFAIL AHMED B  
Email: 241901119@rajalakshmi.edu.in  
Roll no: 241901119  
Phone: 9566336640  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 3\_COD\_Question 4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

You are a software developer tasked with building a module for a scientific calculator application. The primary function of this module is to convert infix mathematical expressions, which are easier for users to read and write, into postfix notation (also known as Reverse Polish Notation). Postfix notation is more straightforward for the application to evaluate because it removes the need for parentheses and operator precedence rules.

The scientific calculator needs to handle various mathematical expressions with different operators and ensure the conversion is correct. Your task is to implement this infix-to-postfix conversion algorithm using a stack-based approach.

Example

Input:

a+b

Output:

ab+

Explanation:

The postfix representation of (a+b) is ab+.

### ***Input Format***

The input is a string, representing the infix expression.

### ***Output Format***

The output displays the postfix representation of the given infix expression.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: a+(b\*e)

Output: abe\*+

### ***Answer***

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
```

```
struct Stack {
    int top;
    unsigned capacity;
    char* array;
};
```

```
struct Stack* createStack(unsigned capacity) {
    struct Stack* stack = (struct Stack*)malloc(sizeof(struct Stack));
    if (!stack)
```



```

        return NULL;

    stack->top = -1;
    stack->capacity = capacity;
    stack->array = (char*)malloc(stack->capacity * sizeof(char));

    return stack;
}

```

```

int isEmpty(struct Stack* stack) {
    return stack->top == -1;
}

```

```

char peek(struct Stack* stack) {
    return stack->array[stack->top];
}

```

```

char pop(struct Stack* stack) {
    if (!isEmpty(stack))
        return stack->array[stack->top--];
    return '$';
}

```

```

void push(struct Stack* stack, char op) {
    stack->array[++stack->top] = op;
}

```

```

int isOperand(char ch) {
    return (ch >= 'a' && ch <= 'z') || (ch >= 'A' && ch <= 'Z') || (ch >= '0' && ch <= '9');
}

```

```

int Prec(char ch) {
    switch (ch) {
        case '+':
        case '-':
            return 1;
        case '*':
        case '/':
            return 2;
        case '^':
            return 3;
        default:
            return -1;
    }
}

```

```

    }
}

void infixToPostfix(char* exp) {
    int i, k;
    struct Stack* stack = createStack(strlen(exp));
    if (!stack)
        return;

    for (i = 0, k = -1; exp[i]; i++) {
        if (isOperand(exp[i]))
            exp[++k] = exp[i];
        else if (exp[i] == '(')
            push(stack, exp[i]);
        else if (exp[i] == ')') {
            while (!isEmpty(stack) && peek(stack) != '(')
                exp[++k] = pop(stack);
            if (!isEmpty(stack) && peek(stack) == '(')
                pop(stack);
        } else {
            while (!isEmpty(stack) && Prec(peek(stack)) >= Prec(exp[i]))
                exp[++k] = pop(stack);
            push(stack, exp[i]);
        }
    }

    while (!isEmpty(stack))
        exp[++k] = pop(stack);

    exp[++k] = '\0';
    printf("%s\n", exp);
}

```

```

int main() {
    char exp[100];
    scanf("%s", exp);

    infixToPostfix(exp);
    return 0;
}

```

}

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: TUFAIL AHMED B  
Email: 241901119@rajalakshmi.edu.in  
Roll no: 241901119  
Phone: 9566336640  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 3\_COD\_Question 5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Milton is a diligent clerk at a school who has been assigned the task of managing class schedules. The school has various sections, and Milton needs to keep track of the class schedules for each section using a stack-based system.

He uses a program that allows him to push, pop, and display class schedules for each section. Milton's program uses a stack data structure, and each class schedule is represented as a character. Help him write a program using a linked list.

##### ***Input Format***

The input consists of integers corresponding to the operation that needs to be performed:

Choice 1: Push the character onto the stack. If the choice is 1, the following input is a space-separated character, representing the class schedule to be pushed onto the stack.

Choice 2: Pop class schedule from the stack

Choice 3: Display the class schedules in the stack.

Choice 4: Exit the program.

### ***Output Format***

The output displays messages according to the choice and the status of the stack:

- If the choice is 1, push the given class schedule to the stack and display the following: "Adding Section: [class schedule]"
- If the choice is 2, pop the class schedule from the stack and display the following: "Removing Section: [class schedule]"
- If the choice is 2, and if the stack is empty without any class schedules, print "Stack is empty. Cannot pop."
- If the choice is 3, print the class schedules in the stack in the following: "Enrolled Sections: " followed by the class schedules separated by space.
- If the choice is 3, and there are no class schedules in the stack, print "Stack is empty"
- If the choice is 4, exit the program and display the following: "Exiting the program"
- If any other choice is entered, print "Invalid choice"

Refer to the sample output for the exact format.

### ***Sample Test Case***

Input: 1 d

1 h

3

2

3

4

Output: Adding Section: d  
Adding Section: h  
Enrolled Sections: h d  
Removing Section: h  
Enrolled Sections: d  
Exiting program

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    char data;
    struct Node* next;
};
```

```
struct Node* top = NULL;
```

```
// You are using GCC
```

```
void push(char value) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    if (!newNode) {
        printf("Stack Overflow\n");
        return;
    }
    newNode->data = value;
    newNode->next = top;
    top = newNode;
    printf("Adding Section: %c\n", value);
}
```

```
void pop() {
    if (top == NULL) {
        printf("Stack is empty. Cannot pop.\n");
        return;
    }
    struct Node* temp = top;
    printf("Removing Section: %c\n", top->data);
    top = top->next;
    free(temp);
}
```

```
}
```

```
void displayStack() {  
    if (top == NULL) {  
        printf("Stack is empty\n");  
        return;  
    }  
    struct Node* temp = top;  
    printf("Enrolled Sections: ");  
    while (temp) {  
        printf("%c ", temp->data);  
        temp = temp->next;  
    }  
    printf("\n");  
}
```

```
int main() {  
    int choice;  
    char value;  
    do {  
        scanf("%d", &choice);  
        switch (choice) {  
            case 1:  
                scanf(" %c", &value);  
                push(value);  
                break;  
            case 2:  
                pop();  
                break;  
            case 3:  
                displayStack();  
                break;  
            case 4:  
                printf("Exiting program\n");  
                break;  
            default:  
                printf("Invalid choice\n");  
        }  
    } while (choice != 4);  
    return 0;  
}
```

Status : Correct

Marks : 10/10



# Rajalakshmi Engineering College

Name: TUFAIL AHMED B  
Email: 241901119@rajalakshmi.edu.in  
Roll no: 241901119  
Phone: 9566336640  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 3\_CY

Attempt : 2  
Total Mark : 30  
Marks Obtained : 30

### Section 1 : Coding

#### 1. Problem Statement

Rithi is building a simple text editor that allows users to type characters, undo their typing, and view the current text. She has implemented this text editor using an array-based stack data structure.

She has to develop a basic text editor with the following features:

Type a Character (Push): Users can type a character and add it to the text editor. Undo Typing (Pop): Users can undo their typing by removing the last character they entered from the editor. View Current Text (Display): Users can view the current text in the editor, which is the sequence of characters in the buffer. Exit: Users can exit the text editor application.

Write a program that simulates this text editor's undo feature using a character stack and implements the push, pop and display operations accordingly.

### ***Input Format***

The input consists of integers corresponding to the operation that needs to be performed:

Choice 1: Push the character onto the stack. If the choice is 1, the following input is a space-separated character, representing the character to be pushed onto the stack.

Choice 2: Pop the character from the stack.

Choice 3: Display the characters in the stack.

Choice 4: Exit the program.

### ***Output Format***

The output displays messages according to the choice and the status of the stack:

1. If the choice is 1, print: "Typed character: <character>" where <character> is the character that was pushed to the stack.
2. If the choice is 2, print: "Undo: Removed character <character>" where <character> is the character that was removed from the stack.
3. If the choice is 2, and if the stack is empty without any characters, print "Text editor buffer is empty. Nothing to undo."
4. If the choice is 3, print: "Current text: <character1> <character2> ... <characterN>" where <character1>, <character2>, ... are the characters in the stack, starting from the last pushed character.
5. If the choice is 3, and there are no characters in the stack, print "Text editor buffer is empty."
6. If the choice is 4, exit the program.
7. If any other choice is entered, print "Invalid choice"

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1 H

1 A

3

4

Output: Typed character: H

Typed character: A

Current text: A H

### **Answer**

// You are using GCC

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#define MAX_SIZE 100
```

```
char stack[MAX_SIZE];
```

```
int top = -1;
```

```
void push(char ch) {  
    if (top < MAX_SIZE - 1) {  
        stack[++top] = ch;  
        printf("Typed character: %c\n", ch);  
    } else {  
        printf("Stack Overflow\n");  
    }  
}
```

```
void pop() {  
    if (top >= 0) {  
        printf("Undo: Removed character %c\n", stack[top--]);  
    } else {  
        printf("Text editor buffer is empty. Nothing to undo.\n");  
    }  
}
```

```
void display() {  
    if (top >= 0) {  
        printf("Current text:");  
        for (int i = top; i >= 0; i--) {  
            printf(" %c", stack[i]);  
        }  
        printf("\n");  
    } else {  
        printf("Text editor buffer is empty.\n");  
    }  
}
```

```

}

int main() {
    int choice;
    char ch;

    while (1) {
        scanf("%d", &choice);
        switch (choice) {
            case 1:
                scanf(" %c", &ch);
                push(ch);
                break;
            case 2:
                pop();
                break;
            case 3:
                display();
                break;
            case 4:
                exit(0);
            default:
                printf("Invalid choice\n");
        }
    }

    return 0;
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Siri is a computer science student who loves solving mathematical problems. She recently learned about infix and postfix expressions and was fascinated by how they can be used to evaluate mathematical expressions.

She decided to write a program to convert an infix expression with operators to its postfix form. Help Siri in writing the program.

### ***Input Format***

The input consists of a single line containing an infix expression.

### ***Output Format***

The output prints a single line containing the postfix expression equivalent to the given infix expression.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: (2 + 3) \* 4

Output: 23+4\*

### ***Answer***

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#include <ctype.h>
```

```
#include <string.h>
```

```
#define MAX_SIZE 50
```

```
char stack[MAX_SIZE];
```

```
int top = -1;
```

```
void push(char c) {
```

```
    stack[++top] = c;
```

```
}
```

```
char pop() {
```

```
    return stack[top--];
```

```
}
```

```
int precedence(char c) {
```

```
    if (c == '+' || c == '-') return 1;
```

```
    if (c == '*' || c == '/') return 2;
```

```
    return 0;
```

```
}
```

```

int is_operator(char c) {
    return c == '+' || c == '-' || c == '*' || c == '/';
}

```

```

void infix_to_postfix(char* infix, char* postfix) {
    int i = 0, j = 0;
    char c;
    while (infix[i] != '\0') {
        if (isdigit(infix[i])) {
            postfix[j++] = infix[i];
        } else if (infix[i] == '(') {
            push(infix[i]);
        } else if (infix[i] == ')') {
            while (top != -1 && stack[top] != '(') {
                postfix[j++] = pop();
            }
            pop();
        } else if (is_operator(infix[i])) {
            while (top != -1 && precedence(stack[top]) >= precedence(infix[i])) {
                postfix[j++] = pop();
            }
            push(infix[i]);
        }
        i++;
    }
    while (top != -1) {
        postfix[j++] = pop();
    }
    postfix[j] = '\0';
}

```

```

int main() {
    char infix[MAX_SIZE], postfix[MAX_SIZE];
    fgets(infix, MAX_SIZE, stdin);
    infix[strcspn(infix, "\n")] = '\0';
    infix_to_postfix(infix, postfix);
    printf("%s\n", postfix);
    return 0;
}

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

In an educational setting, Professor Smith tasks Computer Science students with designing an algorithm to evaluate postfix expressions efficiently, fostering problem-solving skills and understanding of stack-based computations.

The program prompts users to input a postfix expression, evaluates it, and displays the result, aiding students in honing their coding abilities.

#### ***Input Format***

The input consists of the postfix mathematical expression.

The expression will contain real numbers and mathematical operators ( +, -, \*, / ), without any space.

#### ***Output Format***

The output prints the result of evaluating the given postfix expression.

Refer to the sample output for formatting specifications.

#### ***Sample Test Case***

Input: 82/

Output: 4

#### ***Answer***

```
// You are using GCC
#include <stdio.h>
#include <ctype.h>

#define MAX_SIZE 100

float stack[MAX_SIZE];
int top = -1;

void push(float value) {
    stack[++top] = value;
```

```

    }

float pop() {
    return stack[top--];
}

float evaluate_postfix(const char* expression) {
    for (int i = 0; expression[i] != '\0'; i++) {
        if (isdigit(expression[i])) {
            push(expression[i] - '0');
        } else {
            float b = pop();
            float a = pop();
            switch (expression[i]) {
                case '+': push(a + b); break;
                case '-': push(a - b); break;
                case '*': push(a * b); break;
                case '/': push(a / b); break;
            }
        }
    }
    return pop();
}

int main() {
    char expression[MAX_SIZE];
    scanf("%s", expression);
    int a=evaluate_postfix(expression);
    printf("%d\n",a);
    return 0;
}

```

**Status :** Correct

**Marks :** 10/10