MEDFORD Grammar

```
::= from # to end-of-line
\langle comment \rangle
\langle macro \rangle
                           \langle \cancel{L} T_{\cancel{E}} X-literal\rangle
                           ::= \$\$ \langle \cancel{L} T_F X \rangle \$\$
\langle text \rangle
                           ::= *(\langle string\text{-}literal \rangle \mid \langle PTEX\text{-}literal \rangle \mid \langle macro \rangle \mid \langle whitespace \rangle)
                                  terminated by (# | @ | `@)
                           ::= \langle macro \rangle \langle whitespace \rangle \langle text \rangle
\langle macro-def \rangle
\langle minor-token \rangle
                           ::= \langle string-literal \rangle (expected tokens defined in the spec)
\langle data	ext{-}prov	ext{-}token 
angle ::= Data\_Primary | Data\_Copy | Data\_Ref
                                 Code_Primary | Code_Copy | Code_Ref
                             | Paper_Primary | Paper_Copy | Paper_Ref
\langle major-token \rangle
                           ::= Comment | Contributor | Data | Date | Expedetion
                                  File | Funding | Keyword | Method | Paper | Software |
                                  Species | Version
                                 \langle data-prov-token \rangle
                                 \langle string\text{-}literal \rangle
\langle metadata \rangle
                           ::= @ \langle major-token \rangle - \langle minor-token \rangle \langle whitespace \rangle \langle text \rangle
\langle statement \rangle
                           ::= \langle metadata \rangle
                                  \langle comment \rangle
                                  \langle macro-def \rangle
                                  \langle empty \rangle
\langle MEDFORD \rangle
                           ::= *\langle statement \rangle
```

Notes:

• *<string-literal>* excludes whitespace