

# CSCI 5254 Homework 5\*

Tuguluke Abulitibu

November 12, 2020<sup>†</sup>

## Chapter 6, Function fitting and interpolation

### 6.9

Using the definition of quasiconvex, all we need to show is the level set

$$\{t_i \mid \max_{i=1, \dots, k} \left| \frac{p(t_i)}{q(t_i)} - y_i \right| \leq \alpha\}$$

to be convex. Since

$$-\alpha q(t_i) \leq p(t_i) - y_i q(t_i) \leq \alpha q(t_i), \quad i = 1, \dots, k$$

linear inequality (polyhedron), hence convex. therefore the original minimization problem is quasiconvex.

## Additional

### 3.9

$$\|x\|_\infty = \max\{|x_1|, \dots, |x_n|\}.$$

$$\|x\|_2 := \sqrt{x_1^2 + \dots + x_n^2}.$$

(a)

With the given hint:  $z = (\Re x, \Im x)$ , by the definition of Modulus of a complex number

$$\|x_j\| = \frac{\sqrt{z_j^2 + z_j^2}}{\sqrt{(\Re x_j)^2 + (\Im x_j)^2}}$$

Setup a system of equations using the vector breakdown of  $x$  for its  $\Re$  and  $\Im$  components:

minimize	$\ z\ _2$
subject to	$\begin{bmatrix} \Re A & -\Im A \\ \Im A & \Re A \end{bmatrix} z = \begin{bmatrix} \Re b \\ \Im b \end{bmatrix}$
	$z = (\Re x, \Im x)$

---

\*The codes of this HW are between python and matlab, I used matlab whenever I can not debug the py file, it would be great if we have some hints for cvxpy, since there are so many online materials for mat


<sup>†</sup>Late submission due to family matters.

(b)

Introducing another auxiliary variable  $t$ , SOCP:

$$\begin{array}{ll}
 \text{minimize} & t \\
 \text{subject to} & \left\| \begin{bmatrix} z_i \\ z_{i+n} \end{bmatrix} \right\| \leq t, \forall i \\
 & \begin{bmatrix} \Re A & -\Im A \\ \Im A & \Re A \end{bmatrix} z = \begin{bmatrix} \Re b \\ \Im b \end{bmatrix}
 \end{array}$$

(c)

As seen in figure, infinity norm is the circle one, same as the definition: minimizing the maximum of  $x$ .Figure 1:  $L$ 

```

import numpy as np
import cvxpy as cp
import matplotlib.pyplot as plt
import math

m = 30
n = 100
A = np.random.rand(m,n) + np.random.rand(m,n) * 1j
b = np.random.rand(m,1) + np.random.rand(m,1) * 1j

x = cp.Variable((n,1), complex=True)
constraints = [A@x - b == 0]
# objective = cp.Minimize(cp.norm(x_inf, p = "inf"))
objective = cp.Minimize(cp.norm(x, p = 2))

prob = cp.Problem(objective, constraints)
prob.solve()
print(x.value[:10])

x_inf = cp.Variable((n,1), complex=True)
constraints = [A@x_inf - b == 0]
objective = cp.Minimize(cp.norm(x_inf, p = "inf"))
# objective = cp.Minimize(cp.norm(x, p = 2))

prob = cp.Problem(objective, constraints)

```

```

prob.solve()
print(x_inf.value[:10])

X = [x.real for x in x.value]
Y = [x.imag for x in x.value]
X_inf = [x.real for x in x_inf.value]
Y_inf = [x.imag for x in x_inf.value]
plt.scatter(X,Y, color='red',label='L2')
plt.scatter(X_inf,Y_inf, color='blue',label='L-inf')
plt.legend(loc="upper left")
plt.savefig('prob_39.png')
plt.show()

```

#### 4.1

(a)

$$x = \begin{cases} -2.3333 \\ 0.1667 \end{cases} \quad \lambda = \begin{cases} 1.8994 \\ 3.4684 \\ 0.0931 \end{cases}$$

hence, KKT holds.

- primal feasibility  $\begin{cases} x_1^* + 2x_2^* \leq u_1 \\ x_1^* + 4x_2^* \leq u_2 \\ 5x_1^* + 76x_2^* \leq 1 \end{cases}$
- dual feasibility  $\lambda_i \geq 0, \forall i$
- complimentary slackness  $\begin{cases} \lambda_1^*(x_1^* + 2x_2^* - u_1) = 0 \\ \lambda_2^*(x_1^* + 4x_2^* - u_2) = 0 \\ \lambda_3^*(5x_1^* + 76x_2^* - 1) = 0 \end{cases}$
- first order condition:  $\begin{cases} 4x_2^* - x_1^* + 2\lambda_1^* - 4\lambda_2^* + 76\lambda_3^* = 0 \\ 2x_1^* - x_2^* - 1 + \lambda_1^* + \lambda_2^* + 5\lambda_3^* = 0 \end{cases}$

hold for the optimal primal and dual variables

```

import cvxpy as cp
import numpy as np
q1 = np.array([[1,-1/2],[-1/2,2]])
q2 = np.array([-1,0])
x = cp.Variable((2,1))
u1 = cp.Constant(-2)
u2 = cp.Constant(-3)

constraints = [x[0] + 2*x[1] <=u1,
               x[0] -4 *x[1] <=u2,
               5*x[0] + 76*x[1] <= 1]

objectives = cp.Minimize(cp.quad_form(x,q1)+q2@x)
prob = cp.Problem(objectives, constraints)
prob.solve()
x.value

```

(b)<sup>1</sup>

$$p_{pred}^* = p^* - \lambda_1^* \delta_1 - \lambda_2^* \delta_2$$

$\delta_1$	$\delta_2$	$p_{pred}^*$	$\leq$	$p_{exact}^*$
0	0	8.2222	$\leq$	8.2222
0	-0.1000	8.5691	$\leq$	8.7064
0	0.1000	7.8754	$\leq$	7.9800
-0.1000	0	8.4122	$\leq$	8.5650
-0.1000	-0.1000	8.7590	$\leq$	8.8156
-0.1000	0.1000	8.0653	$\leq$	8.3189
0.1000	0	8.0323	$\leq$	8.2222
0.1000	-0.1000	8.3791	$\leq$	8.7064
0.1000	0.1000	7.6854	$\leq$	7.7515

```

q1 = [1 -1/2; -1/2 2];
q2 = [-1 0];
A = [1 2; 1 -4; 5 76];
b = [-2 -3 1]';

cvx_begin
    variable x(2)
    dual variable lambda %TODO
    minimize(quad_form(x, q1)+q2*x)
    subject to
        lambda: A*x <= b; %TODO
cvx_end

% cvx_optval
% lambda
% x

% n = size(A,2);
% cvx_begin
%     variable x(n);
%     dual variable y;
%     minimize( c' * x );
%     subject to
%         y : A * x <= b;
% cvx_end

p_star = cvx_optval
array = [0 -1 1];
delta = 0.1;
pa_table = [];
for i = array
    for j = array
        p_pred = p_star - [lambda(1) lambda(2)]*[i; j]*delta;
        cvx_begin
            variable x(2)
            dual variable lambda
            minimize(quad_form(x,q1)+q2*x)
            subject to

```

---

<sup>1</sup>I consulted the online solution on this one

```

        A*x <= b+[i;j;0]*delta
    cvx_end
    p_exact = cvx_optval;
    pa_table = [pa_table; i*delta j*delta p_pred p_exact]
end
end

```

## 5.2

$$\min \max \left\| \frac{p(t_i)}{q(t_i)} - y_i \right\| \leq s \Rightarrow -sq(t_i) \leq p(t_i) - y_i q(t_i) \leq sq(t_i)$$

is quasiconvex. Hence with bisection method

$\begin{array}{ll} \text{find} & a, b \\ \text{subject to} & \ a_0 + a_1 t_i + a_2 t_i^2 - y_i(1 + b_1 t_i + b_2 t_i^2)\  \leq s(1 + b_1 t_i + b_2 t_i^2) \end{array}$
--




Figure 2: Problem 5.2 Data and the optimal rational function fit




Figure 3: Problem 5.2 The fitting error, i.e.  $f(t_i) - y_i$

```

top = 1000;
bottom = 0;
TOL = .001
k = 201
t=(-3:6/(k-1):3)'; % linspace(-3,3,k)
y=exp(t);
VDM=[ones(k,1) t t.^2];
% bisection method
% https://github.com/cvxr/CVX/blob/master/examples/filter_design/fir_lin_phase_lowpass_min_trans.m

while (top - bottom > TOL)
    cur = (top + bottom)/2
    cvx_begin quiet
        variable a(3)
        variable b(2)

        subject to
            abs(VDM*a-y.*(VDM*[1;b])) <= cur*VDM*[1;b]
    cvx_end
    if strcmp(cvx_status,'Solved')
        fprintf(1,'Problem is feasible for %3.4f',cur);
    end
end

```

```

        a_star = a;
        b_star = b;
        top = cur;
    else
        fprintf(1,'Problem is not feasible for %3.4f',cur);
        bottom = cur
    end
end

y_star = VDM*a_star./(VDM*[1;b_star]);
% y_star
% a_star
% b_star

figure(1);
plot(t,y, t,y_star,'r');
xlabel('t');
ylabel('y_i');

figure(2);
plot(t, y_star-y);
xlabel('t');
ylabel('fitting err f(t_i) - y_i');

```

5.6<sup>2</sup>




Figure 4: Total variation image interpolation

```

% tv_img_interp.m
% Total variation image interpolation.
% Defines m, n, Uorig, Known.

% Load original image.
Uorig = double(imread('tv_img_interp.png'));

```

<sup>2</sup>I consulted the online solution on this one

```

[m, n] = size(Uorig);
% Create 50% mask of known pixels.
rand('state', 1029);
Known = rand(m,n) > 0.5;
%%%%% Put your solution code here

% Calculate and define U12 and Utv.
% Placeholder:
cvx_begin
variable U12(m, n);
U12(Known) == Uorig(Known);
Ux = U12(2:end,2:end) - U12(2:end,1:end-1);
Uy = U12(2:end,2:end) - U12(1:end-1,2:end);
% L2 norm
minimize(norm([Ux(:); Uy(:)], 2));
cvx_end
cvx_begin
variable Utv(m, n);
Utv(Known) == Uorig(Known);
Ux = Utv(2:end,2:end) - Utv(2:end,1:end-1);
Uy = Utv(2:end,2:end) - Utv(1:end-1,2:end);
% L1 norm
minimize(norm([Ux(:); Uy(:)], 1)); %TODO
cvx_end
%%%%%

% Graph everything.
figure(1); cla;
colormap gray;
subplot(221);
imagesc(Uorig)
title('Original image');
axis image;
subplot(222);
imagesc(Known.*Uorig + 256-150*Known);
title('Obscured image');
axis image;
subplot(223);
imagesc(U12);
title('l_2 reconstructed image');
axis image;
subplot(224);
imagesc(Utv);
title('Total variation reconstructed image');
axis image;

```

## 5.13

(a)

Since convex, by adding more info, say  $y$  is bounded from below (additional constraints):

$$\begin{array}{ll} \text{minimize} & \sum_{i=1}^M (y_i - c^T x_i)^2 \\ \text{subject to} & c^T x_i \geq D, \\ & \text{for } i = M+1, \dots, K \end{array}$$

(b)

$$\frac{\|c_{true} - \hat{c}\|_2}{\|c_{true}\|_2} = 0.50, \quad \frac{\|c_{true} - \hat{c}_{ls}\|_2}{\|c_{true}\|_2} = 1.33$$

```
## Data gen
n = 20 # number of variables
M = 25 # number of censored observations
K = 100 # total number of observations

np.random.seed(n*M*K)
X = np.random.randn(K*n).reshape(K, n)
c_true = np.random.rand(n)

# generating the y variable
y = X.dot(c_true) + .3*np.sqrt(n)*np.random.randn(K)

# ordering them based on y
order = np.argsort(y)
y_ordered = y[order]
X_ordered = X[order,:]

#finding boundary
D = (y_ordered[M-1] + y_ordered[M])/2.

# applying censoring
y_censored = np.concatenate((y_ordered[:M], np.ones(K-M)*D))

X_uncensored = X_ordered[:M, :]

## cvxpy
# with constraints
c = cp.Variable(shape=n)
objective = cp.Minimize(cp.sum_squares(X_uncensored*c - y_ordered[:M]))
constraints = [ X_ordered[M:,:]*c >= D]
prob = cp.Problem(objective, constraints)
result = prob.solve()
c_cvx = np.array(c.value).flatten()

# without constraints
c = cp.Variable(shape=n)
objective = cp.Minimize(cp.sum_squares(X_uncensored*c - y_ordered[:M]))
# constraints = [ X_ordered[M:,:]*c >= D]
prob = cp.Problem(objective)
result = prob.solve()
```



```

c_ols_uncensored = np.array(c.value).flatten()

print("norm(c_true - c_cvx)/norm(c_true):\n
{:.2f}".format(np.linalg.norm((c_true - c_cvx))/np.linalg.norm((c_true))))
print("norm(c_true - c_ols_uncensored)/norm(c_true): \n
{:.2f}".format(np.linalg.norm((c_true - c_ols_uncensored))/np.linalg.norm((c_true)) ))

```

## 5.15

(a)

From HW matlab hint, we optimize the following convex problem

$$\begin{array}{ll} \text{minimize} & \frac{1}{N} \sum_{i=1}^N (d_i - (x_i - y_i)^T P (x_i - y_i))^2 \\ \text{subject to} & P \succeq 0 \end{array}$$

(b)

The optimal mean squared distance error:  $+1.24901e - 10$

```

%% data for learning a quadratic metric
% provides X, Y, d, X_test, Y_test, d_test
rand('seed',0);
randn('seed',0); %TODO
n = 5; % dimension
N = 100; % number of distance samples
N_test = 10;
X = randn(n,N);
Y = randn(n,N);
X_test = randn(n,N_test);
Y_test = randn(n,N_test);

P =randn(n,n);
P = P*P'+eye(n);
sqrtP = sqrtm(P);

d = norms(sqrtP*(X-Y)); % exact distances
d = pos(d+randn(1,N)); % add noise and make nonnegative
d_test = norms(sqrtP*(X_test-Y_test));
d_test = pos(d_test+randn(1,N_test));

[d_test, sort_ind] = sort(d_test);
X_test = X_test(:,sort_ind);
Y_test = Y_test(:,sort_ind);
diff = X_test-Y_test

clear P sqrtP;
% solution
cvx_begin
    variable P(n,n)
    minimize((1/N_test)*pow_pos(sum(d_test' - sqrt(diag(diff'*P*diff))),2)),
    subject to
        P>0
cvx_end

```