

GMRS15 Rear Helper Spring Kit Installation Manual

Model: GMRS15 (Rear Suspension Package)

Please read these instructions carefully before commencing installation. Ensure all standard safety protocols are observed when working beneath the vehicle.

1. Parts List

Before beginning, verify that all components listed in the table below are present in your kit.

Ref #	Description / Specifications	Qty
1	Steel Mounting Disc	2
2	Hollow Rubber Spring	2
3	Rubber Spacer	2
4	Hex Head Fastener (Standard Length)	2
5	Hex Head Fastener (Extended Length)	2

2. Installation Instructions

- 1. Remove OEM Bump Stop:** Locate and remove the original equipment manufacturer (OEM) bump stop. If access is restricted, partially raise the vehicle to create sufficient working clearance.
- 2. Assemble Components:** Stack the steel mounting disc, rubber spacer, and hollow rubber spring in the specified order.
- 3. Mount Assembly:** Secure the assembled components to the vehicle frame using the provided fasteners.
- 4. Torque Fasteners:** Tighten the mounting bolt to a torque specification of 30-35 ft-lbs (41-47 Nm).
- 5. Lower Vehicle:** Carefully lower the vehicle to the ground.

3. Clearance Instructions & Fitting Guidance

- Inspect for potential interference between the helper spring and other vehicle components. Note that under load, the rubber spring's diameter will increase.

Important Safety Warnings:

- Do not exceed the vehicle manufacturer's specified axle weight rating.

Note: Illustrations are for reference only. If no specific reference image is provided, please install according to the standard mechanical guidelines.