

Containers

what, how, which and when

10/02/2022

Guilhem Saurel

Available at

[https://homepages.laas.fr/gsaurel/talks/
containers.pdf](https://homepages.laas.fr/gsaurel/talks/containers.pdf)

Under License



<https://creativecommons.org/licenses/by-sa/4.0/>

Source

`https://gitlab.laas.fr/gsaurel/talks :
containers.md`

Discussions

`https://im.laas.fr/#/room/#containers:laas.fr`


- 1 Concepts
- 2 Usage
- 3 Container platforms
- 4 Use cases

Concepts

Filesystem

- A read-only tar of the filesystem

- A read-only tar of the filesystem
- Metadata
 - ID, Checksum, Size
 - Author, creation date
 - Environment variables
 - Working directory, User
 - Architecture, OS
 - Entrypoint and/or default command
 - History



```
$ docker pull ubuntu:20.04
$ docker save ubuntu:20.04 | tar x
$ cat 54c9d8*.json | jq .history
```

```
[
  {
    "created": "2022-02-02T02:14:45.667699167Z",
    "created_by": "ADD file:3ccf74... in / "
  },
  {
    "created": "2022-02-02T02:14:46.177066251Z",
    "created_by": "CMD [\"bash\"]",
    "empty_layer": true
  }
]
```

```
$ docker history ubuntu:20.04
```

IMAGE	CREATED	CREATED BY	SIZE
54c9d81cbb44	6 days ago	CMD ["bash"]	0B
<missing>	6 days ago	ADD file:3ccf74...	72.8MB

```
$ docker inspect ubuntu:20.04 | jq .[0].Size  
$ docker run --rm -it ubuntu:20.04 du -sxB1 /
```

```
$ docker inspect ubuntu:20.04 | jq .[0].Size
$ docker run --rm -it ubuntu:20.04 du -sxB1 /
```

Image	docker inspect	docker run
ubuntu:20.04	72775208	81620992

FROM ubuntu:20.04

RUN `rm -rf /usr/share/doc`

FROM ubuntu:20.04

RUN `rm -rf /usr/share/doc`

Image	docker inspect	docker run
ubuntu:20.04	72775208	81620992
custom	72775208	80019456

```
$ mount  
[...]  
overlay on /var/lib/docker/overlay2/eeaff.../merged ...
```



```
$ mount
```

```
[...]
```

```
overlay on /var/lib/docker/overlay2/eeaff.../merged ...
```

```
$ sudo ls /var/lib/docker/overlay2/eeaff*/merged
```

```
bin    etc    lib32    media    proc    sbin    tmp
```

```
boot  home  lib64    mnt      root    srv     usr
```

```
dev   lib    libx32   opt      run     sys     var
```

Network

```
$ docker run --rm -it ubuntu:20.04
root@a4c1089933e0:/# apt update && apt install iproute2
[...]
root@a4c1089933e0:/# ip address
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
359: eth0@if360: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu
    link/ether 02:42:ac:11:00:02 brd ff:ff:ff:ff:ff:ff
    inet 172.17.0.2/16 brd 172.17.255.255 scope global
```

```
359: eth0@if360: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu  
link/ether 02:42:ac:11:00:02 brd ff:ff:ff:ff:ff:ff  
inet 172.17.0.2/16 brd 172.17.255.255 scope global
```

```
359: eth0@if360: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu
link/ether 02:42:ac:11:00:02 brd ff:ff:ff:ff:ff:ff
inet 172.17.0.2/16 brd 172.17.255.255 scope global
```

```
$ ip address show docker0
```

```
[...]
```

```
4: docker0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500
link/ether 02:42:19:c7:ea:42 brd ff:ff:ff:ff:ff:ff
inet 172.17.0.1/16 brd 172.17.255.255 scope global
inet6 fe80::42:19ff:fec7:ea42/64 scope link
360: veth80c16b5@if359: <BROADCAST,MULTICAST,UP,LOWER_UP>
link/ether de:9b:10:58:45:70 brd ff:ff:ff:ff:ff:ff
inet6 fe80::dc9b:10ff:fe58:4570/64 scope link
```

```
$ pid=$(docker inspect -f '{{.State.Pid}}' $cont)
$ sudo mkdir -p /var/run/netns/
$ sudo ln -sT /proc/$pid/ns/net /var/run/netns/$cont
$ sudo ip netns exec "$cont" ip address
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
359: eth0@if360: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu
    link/ether 02:42:ac:11:00:02 brd ff:ff:ff:ff:ff:ff
    inet 172.17.0.2/16 brd 172.17.255.255 scope global
```

- bridge: default, with NAT
- host: remove isolation
- none: remove network
- ipvlan, macvlan: advanced use cases

Other isolations


```
$ docker run --rm -it ubuntu:20.04 env  
PATH=/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/  
HOSTNAME=14e30a0c1bc7  
TERM=xterm  
HOME=/root
```

```
$ docker run --rm -it ubuntu:20.04  
root@a4c1089933e0:/# apt update && apt install stress  
[...]  
root@a4c1089933e0:/# stress --cpu 3
```

```
$ docker run --rm -it ubuntu:20.04
root@a4c1089933e0:/# apt update && apt install stress
[...]
root@a4c1089933e0:/# stress --cpu 3

$ top
  PID  UTIL  PR  NI  VIRT  RES  SHR  S   %CPU  %MEM  TEMPS+  COM.
3694  root  20   0  3856  100   0  R  100,0  0,0  1:52.95  stress
3692  root  20   0  3856  100   0  R   99,7  0,0  1:52.94  stress
3693  root  20   0  3856  100   0  R   99,7  0,0  1:52.94  stress
[...]
```

Performances

- processes, CPU, RAM: native

- processes, CPU, RAM: native
- network: NAT by default / native with host

- processes, CPU, RAM: native
- network: NAT by default / native with host
- filesystem: CoW, bind mounts

- processes, CPU, RAM: native
- network: NAT by default / native with host
- filesystem: CoW, bind mounts
- size: ubuntu: 72M, debian: 12M, alpine: 5M

- processes, CPU, RAM: native
- network: NAT by default / native with host
- filesystem: CoW, bind mounts
- size: ubuntu: 72M, debian: 12M, alpine: 5M
- isolation: namespaces

Usage

Run a container

```
$ docker run --rm -it hello-world
Unable to find image 'hello-world:latest' locally
latest: Pulling from library/hello-world
2db29710123e: Pull complete
Digest: sha256:97a379f4f88575512824f3b352bc03cd75e23917...
Status: Downloaded newer image for hello-world:latest

Hello from Docker!
[...]
```

```
$ docker run -it my-project
root@ad2955960ee7:/# vim my-script.sh
root@ad2955960ee7:/# exit
$ docker run -it my-project bash ./my-script.sh
```

```
$ docker run -it my-project  
root@ad2955960ee7:/# vim my-script.sh  
root@ad2955960ee7:/# exit  
$ docker run -it my-project bash ./my-script.sh  
  
bash: ./my-script.sh: No such file or directory
```

How you could find your work back...

```
$ docker ps
```

CONTAINER	ID	IMAGE	COMMAND	CREATED	STATUS
-----------	----	-------	---------	---------	--------

```
$ docker ps -a
```

CONTAINER	ID	IMAGE	COMMAND	CREATED	STATUS
-----------	----	-------	---------	---------	--------

ad2955960ee7	my-project	"bash"	15 seconds ago	Exited
--------------	------------	--------	----------------	--------

```
$ docker start ad2955960ee7
```

```
ad2955960ee7
```

```
$ docker ps
```

CONTAINER	ID	IMAGE	COMMAND	CREATED	STATUS
-----------	----	-------	---------	---------	--------

ad2955960ee7	my-project	"bash"	42 seconds ago	Up 4 sec...
--------------	------------	--------	----------------	-------------

```
$ docker attach ad2955960ee7
```

```
root@ad2955960ee7:/# bash ./my-script.sh
```

```
Hi ! ./my-script.sh is starting...
```

```
$ docker volume create my-workspace
my-workspace
$ docker run --rm -it -v my-workspace:/ws ubuntu:20.04
root@1ab7b3188c76:/# ls /ws
root@1ab7b3188c76:/# touch /ws/hello
root@1ab7b3188c76:/# exit
$ docker run --rm -it -v my-workspace:/ws ubuntu:20.04
root@0994f95db805:/# ls /ws
hello
```



```
$ docker run --rm -it -v ~/my-ws:/ws ubuntu:20.04
root@1ab7b3188c76:/# ls /ws
Dockerfile  README.md  requirements.txt  script.py
root@1ab7b3188c76:/# touch /ws/hi
root@1ab7b3188c76:/# exit
$ ls ~/my-ws
Dockerfile  hi  README.md  requirements.txt  script.py
```

Name

```
$ docker run --rm -it --name my-container ubuntu:20.04
```

Name

```
$ docker run --rm -it --name my-container ubuntu:20.04
```

Network

```
$ docker run --rm -it -p 8000:8000 ubuntu:20.04
```

```
$ docker run --rm -it --net host ubuntu:20.04
```

Name

```
$ docker run --rm -it --name my-container ubuntu:20.04
```

Network

```
$ docker run --rm -it -p 8000:8000 ubuntu:20.04
```

```
$ docker run --rm -it --net host ubuntu:20.04
```

Detach

```
$ docker run --rm -it -d ubuntu:20.04
```

Name

```
$ docker run --rm -it --name my-container ubuntu:20.04
```

Network

```
$ docker run --rm -it -p 8000:8000 ubuntu:20.04
```

```
$ docker run --rm -it --net host ubuntu:20.04
```

Detach

```
$ docker run --rm -it -d ubuntu:20.04
```

Ressources

```
$ docker run --rm -it --cpus 2 ubuntu:20.04
```

```
$ docker run --rm -it --gpus all ubuntu:20.04
```

Tag

```
docker tag my-project \
gitlab.laas.fr:4567/my-name/my-project
```

Tag

```
docker tag my-project \  
gitlab.laas.fr:4567/my-name/my-project
```

Push

```
docker push gitlab.laas.fr:4567/my-name/my-project
```

Tag

```
docker tag my-project \  
gitlab.laas.fr:4567/my-name/my-project
```

Push

```
docker push gitlab.laas.fr:4567/my-name/my-project
```

Pull

```
docker pull gitlab.laas.fr:4567/my-name/my-project
```


Tag

```
docker tag my-project \  
gitlab.laas.fr:4567/my-name/my-project
```

Push

```
docker push gitlab.laas.fr:4567/my-name/my-project
```

Pull

```
docker pull gitlab.laas.fr:4567/my-name/my-project
```

NB: <https://hub.docker.com> by default

Build an image

```
$ cat Dockerfile
```

```
FROM python:3.10
```

```
WORKDIR /app
```

```
ADD requirements.txt .
```

```
RUN python -m pip install -r requirements.txt
```

```
ADD . .
```

```
CMD ./manage.py test
```

```
ENV PYTHONUNBUFFERED=1
```

```
$ cat Dockerfile
```

```
FROM python:3.10
```

```
WORKDIR /app
```

```
ADD requirements.txt .
```

```
RUN python -m pip install -r requirements.txt
```

```
ADD . .
```

```
CMD ./manage.py test
```

```
ENV PYTHONUNBUFFERED=1
```

```
$ docker build -t my-app .
```

```
$ cat Dockerfile
```

```
FROM python:3.10
```

```
WORKDIR /app
```

```
ADD requirements.txt .
```

```
RUN python -m pip install -r requirements.txt
```

```
ADD . .
```

```
CMD ./manage.py test
```

```
ENV PYTHONUNBUFFERED=1
```

```
$ docker build -t my-app .
```

NB: Build context

```
$ docker run --rm -it ubuntu:20.04
root@40e14372a5b9:/# apt update
root@40e14372a5b9:/# apt install python3-pip
root@40e14372a5b9:/# pip install django numpy
root@40e14372a5b9:/# vim script.py

$ docker commit 42491f28c1f6 my-app
```

Tips

```
$ export DOCKER_BUILDKIT=1
```



```
$ export DOCKER_BUILDKIT=1
```

```
FROM python:3.10
```

```
RUN --mount=type=cache,target=/var/cache/apt \  
    --mount=type=cache,target=/var/lib/apt \  
    --mount=type=cache,target=/root/.cache \  
    apt-get update -y && apt-get install -qqy \  
    gcc \  
    libpq-dev \  
    && python -m pip install -U pip \  
    && python -m pip install \  
    psycpg2 \  
    && apt-get autoremove -qqy gcc
```

```
$ echo 'build' >> .dockerignore  
$ echo '*.tar.gz' >> .dockerignore
```

```
$ docker system prune
```

```
$ docker system prune
```

```
$ docker system prune -a --volumes
```

```
$ cat docker-compose.yml
```

```
version: "3"
```

```
services:
```

```
  worker:
```

```
    build: .
```

```
    volumes:
```

```
      - ./code
```

```
      - worker-vol:/data
```

```
  cache:
```

```
    image: redis
```


```
volumes:
```

```
  worker-vol: {}
```

```
$ docker compose up -d  
$ docker compose logs  
$ docker compose down
```

Container platforms

<https://cncf.io>



- Daemonless container engine
- Root is not required

- Daemonless container engine
- Root is not required

```
$ alias docker=podman
```

- Secure container platform
- Made for use on HPC / large clusters
- Use Singularity files (.sif)

- Secure container platform
- Made for use on HPC / large clusters
- Use Singularity files (.sif)

```
$ singularity pull docker://ubuntu:20.04
```

```
$ singularity shell ubuntu_20.04.sif
```

```
Singularity> whoami
```

```
gsaurel
```

```
Singularity> pwd
```

```
/home/gsaurel/talks
```

```
Singularity> ls
```

```
Dockerfile  Makefile  README.md  containers.md  containe
```

```
Bootstrap: docker
```

```
From: python:3.10
```

```
%post
```

```
    apt-get update
```

```
    apt-get -qy install gcc libpq-dev
```

```
    python -m pip install psycpg2
```

```
%environment
```

```
    export PYTHONUNBUFFERED=1
```

```
%runscript
```

```
    ./manage.py test
```

```
$ singularity build my-container.sif my-container.def
```

Use cases

- continuous integration
- complex dependency setup
- software debugging

- continuous integration
- complex dependency setup
- software debugging
- reproducible science

- HPC
- host web services
- run single statically linked binary with metadata

Thanks for your time :)