

# Introduction to Modern CMake

C++ dependency tutorial

Guilhem Saurel







#### This presentation

#### Available at

#### **Under License**



https://creativecommons.org/licenses/by-sa/4.0/



#### This presentation (continued)

#### Source

#### **Discussions**

https://im.laas.fr/#/room/#modern-cmake:laas.fr





# Configure

- Find the dependencies you need
- Declare the options you want



# Configure

- Find the dependencies you need
- Declare the options you want

### Compile

- Generate the right arguments for your compiler
- Run it



# Configure

- Find the dependencies you need
- Declare the options you want

### Compile

- Generate the right arguments for your compiler
- Run it

#### Run

■ Start your executable with its associated \*.so



### Example

- You develop a library called "my-lib"
- It needs a dependency from someone else called "a-dep"



### Example

- You develop a library called "my-lib"
- It needs a dependency from someone else called "a-dep"



### Legacy CMake

#### FindA-dep.cmake

```
find_path(a_dep_INCLUDE_DIRS NAMES a-dep/fwd.hpp)
find_library(a_dep_LIBRARIES NAMES liba-dep.so)
```

### Legacy CMake

```
FindA-dep.cmake
find_path(a_dep_INCLUDE_DIRS NAMES a-dep/fwd.hpp)
find_library(a_dep_LIBRARIES NAMES liba-dep.so)

CMakeLists.txt
find_package(a-dep REQUIRED)
include_directories(${a_dep_INCLUDE_DIRS})
link_libraries(${a_dep_LIBRARIES})
add_library(my-prog main.cpp include/my-proj/fwd.hpp)
```

#### Modern CMake

# CMakeLists.txt find\_package(a-dep REQUIRED) add\_library(my-lib main.cpp include/my-prog/fwd.hpp) target\_link\_libraries(my-prog PUBLIC a-dep::a-dep) a-dep-config.cmake add\_library(a-dep::a-dep SHARED IMPORTED) set\_target\_properties(a-dep::a-dep PROPERTIES LINK LIBRARIES "liba-dep.so" INCLUDE DIRECTORIES "\${ IMPORTED PREFIX}/include")



### Advantages

a-dep can change whatever it needs



#### Advantages

- a-dep can change whatever it needs
- No more naming issues like

```
set(A_DEP_INCLUDE_DIRS ${a_dep_INCLUDE_DIRS})
set(A_DEP_INCLUDE_DIR ${a_dep_INCLUDE_DIRS})
set(a_dep_INCLUDE_DIR ${a_dep_INCLUDE_DIRS})
```



- a-dep can change whatever it needs
- No more naming issues like

```
set(A_DEP_INCLUDE_DIRS ${a_dep_INCLUDE_DIRS})
set(A_DEP_INCLUDE_DIR ${a_dep_INCLUDE_DIRS})
set(a_dep_INCLUDE_DIR ${a_dep_INCLUDE_DIRS})
```

Relocatable packages



#### Relocation

my-lib-config.cmake from legacy a-dep
add\_library(my-lib::my-lib SHARED IMPORTED)
set\_target\_properties(my-lib::my-lib PROPERTIES
 LINK\_LIBRARIES "libmy-lib.so;/usr/lib/liba-dep.so"



#### Relocation

```
my-lib-config.cmake from legacy a-dep
add_library(my-lib::my-lib SHARED IMPORTED)
set_target_properties(my-lib::my-lib PROPERTIES
  LINK_LIBRARIES "libmy-lib.so;/usr/lib/liba-dep.so"
  INCLUDE DIRECTORIES
  "${_IMPORTED_PREFIX}/include;/usr/include")
my-lib-config.cmake from modern a-dep
find_dependency(a-dep REQUIRED)
add_library(my-lib::my-lib SHARED IMPORTED)
set_target_properties(my-lib::my-lib PROPERTIES
  LINK_DEPENDENT_LIBRARIES "a-dep::a-dep"
  LINK_LIBRARIES "libmy-lib.so"
  INCLUDE_DIRECTORIES "${_IMPORTED_PREFIX}/include")
```



### That's all folks!

Thanks for your time:)