



NOTES:

MATERIAL :

- 1.HOUSING MATERIAL :GLASS FILLED POLYESTER UL94V-0.
- 2.CONTACT MATERIAL :PHOSPHOR BRONZE φ0.46mm.
- 3.PLATING :GOLD PLATING OVER NICKEL.

ELECTRICAL:

- 1.VOLTAGE RATING :125 VAC RMS.
- 2.CURRENT RATING :15 AMP.
- 3.CONTACT RESISTANCE :30 MILLIOHMS MAX.
- 4.INSULATION RESISTANCE :500 MEGOHMS MIN @ 500V DC .
- 5.DIELECTRIC WITHSTANDING RESISTANCE :1000V AC RMS 50Hz 1MIN.

MECHANICAL:

- 1.DURABILITY :750 CYCLES MIN.
- 2.PCB RETENTION PRE-SOLDER :1LB MIN.

ENVIRONMENTAL:

- 1.STORAGE : -40℃~+85℃
2. OPERATION : -40℃ TO 70℃.

PC Board Layout Component Side Shown

Units		mm	Scale	2:1	Drawing By		Date	Title		Drawing No.		REV
Tolerance Unless Otherwise Specified		Check By		Date	Date		Date	Thirt Angle Projection		File Path		A
.X ~ ±0.30		Approval By		Date	Sheet		2008/03/01	1 of 1		RJ45 JACK 90 °屏蔽带灯带弹片		
.XX ~ ±0.25		Date			Date							
.XXX ~ ±0.20												
Angle ~ ± 3°												
ECN.NO.		Date										
01/03-08												
RELEASED												
LTR												
DESCRIPTION.												
1		2		3	4		5	6		7		8