

C++

PENG

October 7, 2026

Contents

1	Introduction	1
1.1	IO	1
1.2	Comments	2
1.3	Flow of Control	2
1.4	Class	2
2	Types	3
2.1	Compound Types	4
2.2	Qualifier	4
2.3	Data structure	5
3	Vectors	5
3.1	String	5

1 Introduction

C++ is a high-level, statically typed programming language [1].

1.1 IO

Definition 1.1 (IO objects).

- `iostream` : *std lib*
- `std::cin` : *istream type*
- `std::cout` : *ostream type*

```
std::cout << "str";           // return object: std::cout
std::cout << "str" << "\n"; // (std::cout << "str") << "\n";
```

```
int v1 = 0, v2 = 0;
std::cin >> v1;           // return object: std::cin
std::cin >> v1 >> v2;     // (std::cin >> v1) >> v2;
```

Definition 1.2 (namespace).

`namespace::name` // :: scope operator

```
// headers file should not include using declarations
using namespace::name;
```

1.2 Comments

Definition 1.3 (comment).

```
// single line, best way
/* paired, can not nest */

std::cout << /* */ /* */ /* */;
// remove everything between */ and closest /* before
// std::cout << " /* ";
```

1.3 Flow of Control

Definition 1.4 (while).

```
while(cond)
{
    statements;
}

while(std::cin >> val)
// std::cin >> val return left operand: std::cin
// istream become invalid:
// 1. reading a non-integer val: 1 2 3.1
// 2. end-of-file: Ctrl-c
```

Definition 1.5 (for).

```
for (init-statement; cond; expr)
{
    statements;
}

// init-statement:
// local var used only inside for, executed only once
// expr: executed after for body
```

Definition 1.6 (if).

```
if (cond)
{
    statements;
}
else if (cond)
{
    statements;
}
else
{
    statements;
}

if (std::cin >> val)
    std::cout << val << "\n";
// 1 2 3 RET => 1
```

1.4 Class

Definition 1.7 (class). *Define data structures:*

- *name*

- *defined*
- *operation*

```
// #include <std lib>
// #include "header.h"
```

Definition 1.8 (member function).

```
data.func()
```

2 Types

Definition 2.1 (arithmetic types).

```
char          // '\0': null, '\t': horizontal tab, '\n': newline
#include <string>
std::string
int           // unsigned: >= 0
bool          // true for 1 and false for 0
double
```

Definition 2.2 (object). *An object is a region of memory that contain data and has a type.*

Definition 2.3 (declaration and definition).

```
// define: allocate storage and defined only once
// source.cpp
int i = 10;

// declare: specify type and var names
// headers should have guards to be safe to be included multiple times
// header.h
#ifndef HEADER // true if CLASSNAME not defined
#define HEADER // preprocessor vars are all uppercase
extern int i;
#endif

// main.cpp
#include "header.h"
i ...
```

Definition 2.4 (scope). *Delimited by {}.*

```
// vars defined outside any function body are initialized to 0
int val; // 0
int main ()
{
    int val = 1; // block scope
    // ::val == 0 global scope
    ...
}

// var: lowercase
// class: first letter uppercase
```

Definition 2.5 (bit).

bit	combination	total	number
1 bit:	0, 1;	2	= 2^1 ; 0, 1
2 bits:	00, 01, 10, 11;	$2*2$	= 2^2 ; 0, 1, 2, 3
3 bits:	000, 001, ..., 111;	$2*2*2$	= 2^3 ; 0, 1, 2, 3, ..., 7
32 bits:			= 2^{32} ; 0, 1, 2, ..., $2^{32} - 1$

Definition 2.6 (type conversion).

```
unsigned i = -1; // 2^32 - 1 for 32-bit int

// when mix int and unsigned, int is automatically converted to unsigned
unsigned a = 1;
int b = -1;
a + b // 1 + (2^32 - 1) = 2^32 = 0
a * b // 1 * (2^32 - 1)
a < b // 1 < (2^32 - 1), always true
```

2.1 Compound Types

Definition 2.7 (reference). *A reference defines an alias for an object.*

```
int i = 0;
int &ref = i;
// ref must be bound only to an int object, not a literal
// error: int &ref = 1;
```

Definition 2.8 (pointer). *A pointer is an object that holds the address of another object.*

```
int i = 0;
int *p;
p = &i; // p holds the address of i
*p = 0; // return the object i to which p points
p = nullptr; // or p = 0, null pointer, not bound to any object

// pointer to pointer to ...
int **pp; // * indicate pointer level
pp = &p;

// ref to pointer
int *&ref = p; // & => ref is reference, * => ref refers to pointer type
```

2.2 Qualifier

Definition 2.9 (const). *The compiler will replace the const var with its value.*

```
const int i = 1; // must be initialized, local to a file by default

// must specify extern to be used in other files
// source.cpp
extern const i = 10;
// header.h
extern const i;
// main.cpp
#include "header.h"
i ...

// ref to const
// cannot change the object to which it bounds
const int i = 1;
const int &r = i;
const int &r2 = 2; // compiler: const int temp = 2; const int &r2 = temp;

// pointer to const
// cannot change the object to which it points
const int i = 1;
const int *p = &i;
```

```
// const pointer
// the address it holds cannot be changed
int i = 1;
int *const p = &i; // p always points to i
```

Definition 2.10 (constant expr). *A constant expression is an expr whose value cannot change at compile time.*

```
constexpr int i = size(); // ok only if size is a constexpr function
constexpr int *p = nullptr; // const pointer, constexpr applies to p
```

Definition 2.11 (type alias). *A synonym for a type.*

```
typedef int base; // or: using base = int;
typedef base *p; // type: int*, pointer to int
p p1 = &i;
```

```
// const p: const modify the given type,
// constant pointer to int: int *const
const p p2 = 0; // int *const p2 = 0
const p *p3; // int *const *p3
```

Definition 2.12 (const level).

```
// top-level const
// low-level const
```

Definition 2.13 (auto). *Deduce the type from the initializer at compile time.*

```
auto i = 1, *p = &i; // must have initializer
auto i = 0, pi = 3.14; // error, types must be consistent
```

```
// auto may differ from initializer's type
// auto ignores top-level const
```

Definition 2.14 (decltype).

2.3 Data structure

Definition 2.15 (structure). *A data structure is a way to group together related data elements and for using those data.*

```
// class is ordinarily defined outside functions, usually in className.h
struct className
{
    statements;
}; // must end with ;

className x, *y;
```

3 Vectors

3.1 String

Definition 3.1 (string). *A string is a variable-length sequence of characters.*

```
#include <string>
using std::string;

string str = "A";
// copy of the string literal "A": ['A', '\0'],
// not include null char '\0' at the end

str.size(); // unsigned string::size_type
```

References

- [1] S.B. Lippman, J. Lajoie, and B.E. Moo. *C++ Primer*. Pearson Education, 2012. ISBN: 9780133053036.