C++

PENG

October 14, 2026

Contents

1 Introduction **1**
1.1 Flow of Control . . . 2
1.2 Class . . . 2

2 Types **2**
2.1 Compound Types . . . 3
2.2 Qualifier . . . 3
2.3 Data Structure . . . 5

3 string **5**

4 vector **6**
4.1 Iterators . . . 6

5 Array **6**
5.1 Pointers and Arrays . . . 7
5.2 Arrays of Arrays . . . 7

6 Exprs **8**
6.1 Type conversion . . . 10

7 Statement **10**

8 Function **10**

1 Introduction

C++ is a statically typed programming language [1].

Definition 1.1 (IO objects)**.**

```
#include <iostream>
// using std::cout, std::cin;
std::cout << "str"; // return left operand: std::cout
std::cin  >> v1;    // return left operand: std::cin
// IO operators: left associative
std::cout << "str" << "\n"; // (std::cout << "str") << "\n";
std::cin  >> v1 >> v2;      // (std::cin >> v1) >> v2;
```

Definition 1.2 (comment)**.**

```
// single line
/* paired can not nest */

std::cout << /* "*/" /* "/*" */;
// std::cout << " /* ";
// remove everything between */ and /*
```

1.1 Flow of Control

Definition 1.3 (while)**.**

```
while(cond)
{
    statements;
}

while(std::cin >> v)
    ...
// istream become invalid:
// reading a non-integer val: 1 2 3.1
// end-of-file: Ctrl-Z then RET (windows), or Ctrl-D then RET (linux)
```

Definition 1.4 (for)**.**

```
for (init-statement; cond; expr) // loop var used locally inside for body
{
    statements;
}
```

Definition 1.5 (if)**.**

```
if (cond)
{
    statements;
}
else if (cond)
{
    statements;
}
else
{
    statements;
}
```

1.2 Class

Definition 1.6 (class)**.** *Define data structures.*

2 Types

Definition 2.1 (arithmetic types)**.**

```
char // '\0': null, '\t': horizontal tab, '\n': newline
#include <string>
std::string
int  // unsigned int >= 0
bool // true 1 and false 0
double
```

Definition 2.2 (object)**.** *Memory region that contains data with type.*

Definition 2.3 (decl and def)**.**

```
// def: allocate storage and define only once
// decl: specify type and var names
// headers should have guards to be safe to be included multiple times
// source.cpp
int i = 10;
// source.h
```

```
#ifndef SOURCE_H
#define SOURCE_H
extern int i;
#endif
// main.cpp
#include "header.h"
i ...
```

Definition 2.4 (bit)**.**

bit	*combination*	*total*	`unsigned`	`int`
1	$0, 1$	2^1	$0, 1$	$0, 1$
2	$00, 01, 10, 11$	2^2	$0, 1, 2, 3$	$0, 1, -2, -1$
...				
32		2^{32}	$0, 1, ..., 2^{32} - 1$	$0, ..., 2^{16} - 1, -2^{16}, ..., -1$

1 byte = 8 bits

Definition 2.5 (type conversion)**.**

```
// int => unsigned
unsigned i = -1;              // -1 = 2^32 - 1 for 32-bit unsigned int
#include <cmath>
unsigned i = std::pow(2, 32); // 2^32 = 0 for 32-bit unsigned int
unsigned a = 1; int b = -1;
a + b // 1 + (2^32 - 1) = 2^32 = 0
a < b // 1 < (2^32 - 1) true
```

2.1 Compound Types

Definition 2.6 (reference)**.** *A ref defines an alias for an object.*

```
int i = 0;
int &ref = i;
```

Definition 2.7 (pointer)**.** *A pointer is an object that holds the address of another object.*

```
int i = 0;
int *p = &i; // p holds the address of i
*p           // return object i lvalue
p = nullptr; // null pointer: not bound to any object
p = 0;

// pointer to pointer
int **pp = &p; // * indicate pointer level

// ref to pointer
int *&ref = p; // refer to int*
```

2.2 Qualifier

Definition 2.8 (const)**.** *The compiler will replace the const var with its value.*

```
// const must be initialized
const int i = 1;

// const var is local to file by default
// must specify extern to be used in other files
// source.cpp
extern const i = 10;
// header.h
extern const i;
```

```
// main.cpp
#include "header.h"
i ...

// ref to const
// cannot change the object to which it bounds
const int i = 1;
const int &r = i;
const int &r2 = 2; // compiler: const int temp = 2; const int &r2 = temp;

// pointer to const
// cannot change the object to which it points
const int i = 1;
const int *p = &i;

// const pointer
// the address it holds cannot be changed
int i = 1;
int *const p = &i; // p always points to i
```

Definition 2.9 (constant expr)**.** *A constant expression is an expr whose value cannot change at compile time.*

```
constexpr int i = size();   // ok only if size is a constexpr function
constexpr int *p = nullptr; // const pointer, constexpr applies to p
```

Definition 2.10 (type alias)**.** *A synonym for a type.*

```
typedef int base;
using base = int;
typedef base *p;  // int*: pointer to int
p p1 = &i;

// const p: const modify the given type: int *const: constant pointer to int
const p p2 = 0; // int *const p2 = 0
const p *p3;    // int *const *p3
```

Definition 2.11 (const level)**.**

```
// top-level const: an object itself is const, i.e. const pointer
const int i = 1;
int *const p1 = &i;

// low-level const: point or refer to const object
const int *p2 = &i;
const int &r = i;

// when copying, top-level const is ignored,
// low-level const is never ignored
const int *const p3 = &i;
p2 = p3;
```

Definition 2.12 (auto)**.** *Deduce the type from the initializer at compile time.*

```
auto i = 1, *p = &i;   // must have initializer
auto i = 0, pi = 3.14; // error, types must be consistent

// auto may different from initializer's type
// auto ignores top-level const
```

Definition 2.13 (decltype)**.** *Return the operand type without evaluating the expr.*

```
decltype(expr) var
```

2.3 Data Structure

Definition 2.14 (structure)**.** *A data structure is a way to group data elements.*

```
// Ordinarily defined outside functions in ClassName.h
struct ClassName
{
    statements;
}; // must end with ;
```

3 string

Definition 3.1 (string)**.** *Variable-length sequence of characters.*

```
#include <string>
// using std::string;

// class defines how objects can be initialized
std::string s = "A";   // copy ['A', '\0'], drop null char
std::string s(n, 'c'); // "c...c"

// read string
std::cin >> s1 >> s2;

// read line
std::getline(std::cin, s)

// compare
// at least one should be std::string
std::string s = "Hello";
s < "Hiya" // compare first diff char ASCII: i > e
s < "Hello World"

// concat
// cant add two string literals, i.e. "A" + "B"
s + " World\n" // "Hello World\n"

// for range statement: iterate through elems in a given sequence
for (char c : s)
    ...
for (char &r : s) // change char in string
    r = toupper(r); // uppercase

// ispunct(c): check if char is punctuation, i.e. ',', '!', ...
// isspace(c): check if char is space

// subscript operator: s[n]
// !s.empty()
// s.size(): unsigned std::string::size_type
// s.size() < -1 => 2^32 - 1 for 32-bit int
// n: unsigned std::string::size_type
// 0 <= n < s.size()
for(decltype(s.size()) i = 0; i != s.size(); i = i + 1)
    ...

// iterator
```

4 vector

Definition 4.1 (vector)**.** *Variable-length sequence of objects of a given type.*

```
#include <vector> // class template
// using std::vector;

std::vector<int> v; // empty vector
std::vector<int> v = {val_1, ..., val_n};
std::vector<int> v(size, val); // {val, ..., val}
v.push_back(elem) // append elem

// for range statement
for(auto &r : v)
    ...

// compare

// subscript operator
// !v.empty()
// v.size(): unsigned std::vector<int>::size_type
// 0, ..., v.size() - 1
```

4.1 Iterators

Definition 4.2 (iterator)**.** *Access the elem in container. General mechanism, all lib containers have iterator.*

```
auto b = v.begin(); // return iterator: denotes first elem
auto e = v.end();   // return iterator: denotes one after the last elem

// deref
*b // return ref to elem obj
b->mem // arrow operator: (*b).mem, i.e. b->empty()

// operation
++b // next elem
--e // previous elem
b != e

// for vector and string iterators
auto mid = b + (e - b) / 2;
b <= e
```

5 Array

Definition 5.1 (array)**.**

```
constexpr size_t size = ...;
int a[size] = {};
// array type cannot be: auto
// any object size type: unsigned size_t
// dimension must be known at compile time: constexpr

// cannot copy
// error: a2 = a1;

// pointers and ref
int *p[size]; // array of n pointers to int
```

```
int (*p)[size] = &a; // pointer to array of n int
int (&r)[size] = a;  // refer to array of n int
int *(&r)[size] = p; // refer to array of n pointers to int
// () for def -> right for array size -> left for elem type

// for range statement
for (auto &r : a)
    ...

// subscript operator
```

5.1 Pointers and Arrays

```
int *p = a;  // a automatically convert to &a[0]
auto p = a;  // p = &a[0]
decltype(a) a2 = {0, 1, 2};

// iterator
int *b = std::begin(a); // pointer to first elem
int *e = std::end(a);   // pointer to one after last elem

// subscript
int *p = &a[m]; // p = a + m
p[n] // *(p + n) => a[m + n]

// C-style char string
char c[] = "str"; // c[] = {'s', 't', 'r', '\0'}
strcmp(c1, c2)    // 0 for c1 == c2; 1 for c1 > c2; -1 for c1 < c2

// initialize vector with array {a[i], ..., a[j]}
std::vector<int> v(a + i, a + j);
```

5.2 Arrays of Arrays

Definition 5.2 (multidimensional array)**.**

```
constexpr size_t rows=..., cols=...;
int a[rows][cols] = {0};

// subscript operator
a[n] // nth inner-array elem

// for range statement
// control vars except innermost array must be ref
for (auto &row : a)     // for every elem in outer array
    for(auto col : row) // for every elem in inner array
        ...

// pointers
int (*p)[cols] = a; // p = &a[0]

for (auto p = a; p != a + rows; ++p)       // int (*p)[cols] = &a[0]
    for (auto q = *p; q != *p + cols; ++q) // int *q = &a[0][0]
        ...

// type alias
using int_array = int[rows];
// typedef int int_array[rows];
for (int_array *p = a; p != a + rows; ++p)
```

...

6 Exprs

Definition 6.1 (expression)**.** *Composed of operators and operands.*

```
// unary operator: act one one operand
// & address-of
// * dereference

// binary operator: act on two operands1
// == equality
// * multiplication

// overloaded operator
// define operator in class

// lvalue and rvalue
// lvalue: can be assignment
// rvalue: cannot be assignment
// lvalue = ...                    return left-hand operand as lvalue
// address-of &lvalue              return a pointer to lvalue as rvalue
// deref * and subscript operator return lvalue
// ++iterator or --iterator        return lvalue
// decltype(lvalue)                return ref
// decltype(rvalue)                return the exact type of rvalue
decltype(*p) // int&
decltype(&i) // int*
decltype(&p) // int**

// compound expr with two or more operators
// precedence:
// operands of operators with higher precedence group tightly than
// operands of operators at lower precedence
// associativity: group operands with same precedence
// left associative: operators with same precedence group from left-most to right
// right associative: operators with same precedence group from right-most to left
// () force grouping

// arithmetic operator
// left associative
// return rvalue
// reminder: int % int
// return same sign as m
(-m) % n // -(m % n)
m % (-n) // -(m % n)

// logical and relational operator
// return bool val
// 0 return false
// non-zero return true
// guarantee eval order
expr1 && expr2 // eval expr2 if and only if expr1 is true
expr1 || expr2 // eval expr2 if and only if expr1 is false
// precedence:
// right associative
// 1. !
// left associative
```

```
// 2. <=, >=
// 3. ==, !=
// 4. &&
// 5. ||
i != j < k // i != (j < k)

// assignment operator
// low precedence
// right associative
// left-hand operand: a modifiable lvalue
// return left-hand operand lvalue
// compound assignment operator
// *=, /=, %=
a *= b;    // compound assignment: a eval only once
a = a * b; // ordinary assignment: a eval twice

// increment and decrement operator
// require lvalue operand
// prefix:  increment operand and return the changed object as lvalue
// postfix: increment operand and return object's original value as rvalue
// use postfix only when necessary
// precedence: ++-- > dereference
*b++ // *(b++)

// evaluation order

// member access operator
p->mem => (*p).mem
// precedence: . > dereference
pointer-> return lvalue
.mem return lvalue or rvalue same as mem

// conditional operator
cond ? expr1 : expr2;
// return lvalue if both expr1 and expr2 are lvalue
// otherwise return rvalue
cond ? expr1 : cond ? expr2 : expr3
// right associative
// low precedence, need ()

// bitwise operator
// hardware

// shift operator (IO operator)
// left associative
// precedence:
1. arithmetic operator
2. IO operator
3. relational, assignment, conditional operator

// sizeof operator
// right associative
// return constexpr size_t in byte
// 1 byte = 8 bits
sizeof(type)
sizeof(expr)
// array
sizeof(a) // sizeof(*a) * size
```

```
// comma operator
// guarantee eval order from left to right
// lowest precedence
// expr1, expr2
// return expr2 lvalue or rvalue
for (int v1=..., v2=...; cond; expr1, expr2)
    ...
```

6.1 Type conversion

Definition 6.2 (type conversion)**.**

```
// implicit conversion
// arithmetic conversion
// integer promotion
// unsigned type
// array to pointer conversion
// conversion to bool
// conversion to const

// explicit conversion
// static_cast<type>(expr)
int i = 1, j = 2;
// double k = i / j; // 0
double k = static_cast<double>(i) / j; // 0.5
// const_cast: remove low-level const
// reinterpret_cast: bit-pattern of operands
// old-style cast
// type (expr);
// (type) expr;
```

7 Statement

Definition 7.1 (statement)**.**

```
// simple statement
// expr statement
; // null statement
// compound statement (block, scope)

// flow-of-control statement
```

8 Function

Definition 8.1 (func)**.** *Block of code with name.*

References

[1] S.B. Lippman, J. Lajoie, and B.E. Moo. *C++ Primer*. Addison-Wesley Professional, 2012. ISBN: 978-0-321-71411-4.