

1. **Why version control:** What version control is, and why · Git vs GitHub · Repository
2. **How Git thinks:** The three areas (and the remote) · The staging area (index) · Commits: snapshot, hash, message
3. **Setup:** Install and configure Git · git init vs git clone
4. **Everyday commands:** The daily loop: status, add, commit · Inspecting: git log and git diff · .gitignore: what never goes into Git
5. **Branches and merging:** Branches and HEAD · Merging: fast-forward vs merge commit · Merge conflicts
6. **Remotes:** Signing in to GitHub from Git · Remotes, origin and git push · git fetch vs git pull
7. **Working in a team:** Tags and stash: marking versions, setting work aside · GitHub flow and pull requests
8. **Undoing safely:** Undo before committing: git restore · Undo after committing: revert, amend, reset

Why version control

What version control is, and why

Version control records chosen, labelled states of a whole project over time, so you can see what changed, when and by whom, go back to any earlier state, and work in parallel with other people.

- Tracking** Every change is recorded with who, when and why.
- Collaboration** Several people change the same project without overwriting each other.
- Rollback** Go back to, or cancel, any earlier change.
- Branching** Try an idea on a separate line of work, then combine it or throw it away.

Example. On Monday you save a checkpoint called "Add contact form". On Wednesday the layout is broken. The history shows three checkpoints since Monday, and comparing Monday with today shows the single line in `styles.css` that changed `display: grid` to `display: flex`. You fix that line instead of guessing.

Common mistake. Treating version control as cloud sync (OneDrive, Dropbox, Google Drive). Sync silently keeps the **latest** version of each file; version control keeps **chosen, described, whole-project** checkpoints, and records nothing until you ask. Do not keep a Git project inside a synced folder either: sync and Git writing the same hidden files at once causes lock errors and damaged repositories.

Git vs GitHub

Git is the version-control program that runs on your computer; GitHub is a website that stores copies of Git repositories online and adds team features such as pull requests, reviews and issues.

Who does what

	Git	GitHub
What it is	A command-line program you install	A website (a hosting service) run by a company
Where it runs	Your laptop, offline	GitHub servers, through the browser or the network
Main jobs	Stage, commit, branch, merge, read history	Store a shared copy, pull requests, code review, access control
Account needed?	No: only a name and email in its settings	Yes, a free github.com account

Example. On a train without Wi-Fi you create a repository, make 12 commits and browse the history: that is all Git. At home, `git push` uploads those 12 commits to GitHub, where your teammate sees them and can review them.

Common mistake. "I committed, so my teammates can see it." A commit exists only in your **local** repository until you run `git push`. The mirror mistake: editing a file on github.com and expecting your laptop to know about it; your local copy changes only after `git pull`.

Repository

A repository (repo) is a project folder whose complete history Git tracks; the history and Git's settings live in a

hidden .git folder at the root of that folder.

- **Two repositories, one project:** your laptop copy and the GitHub copy are separate repositories. They are not linked live; they exchange commits only when you push or pull.
- `README.md` at the root is the project's front page: GitHub shows it under the file list, so it says what the project is and how to run it.

shell

```
$ cd my-first-repo
$ ls -a
.  .. .git README.md index.html
$ git status
On branch main
nothing to commit, working tree clean
```


Example. A two-person project lives in one repository on GitHub. Each partner has a local repository created by cloning it. Both local repositories hold the full history, so if one laptop dies, nothing committed and pushed is lost.

Common mistake. Running `git init` in your home folder or on the Desktop, which turns every file below it into one giant repository, or inside a folder that is already a repository (one repository nested in another). Check where you are with `pwd` and `git status` first: if `git status` already answers "On branch ...", you are inside a repository.

How Git thinks

The three areas (and the remote)

Git keeps your work in three local areas: the **working directory** (the files you edit), the **staging area** or **index** (the next commit being prepared) and the **repository** (the commits already saved); a remote such as GitHub is a fourth, separate copy.



Work reaches GitHub only by passing through every area, one command at a time.

The four places your work can be

Area	What it holds	Where it lives
Working directory	The files as you see them in the editor	The project folder
Staging area (index)	The exact content of the next commit	A file inside <code>.git</code>
Repository	Every commit, every branch	The <code>.git</code> folder
Remote (GitHub)	The shared copy of the commits	A server

Each file has a status, shown by `git status`

Untracked Git has never stored it: a brand-new file.

- Unmodified** The same as in the last commit.
- Modified** Changed since the last commit; the change is not staged yet.
- Staged** Its current content will go into the next commit.

Example. You create `about.html` (untracked) and edit `index.html` (modified). `git add about.html` stages only the new page. `git commit -m "Add about page"` saves it in the repository, while `index.html` is still modified in the working directory and in no commit. GitHub has none of this until `git push`.

Common mistake. Believing that pressing Ctrl+S in VS Code "saves into Git". Saving writes only to the **working directory**. Until you `git add` and `git commit`, Git has no copy of that change, and until you `git push`, nobody else has one either.

The staging area (index)

The staging area, also called the **index**, is a draft of your next commit: it holds the exact version of each file that `git commit` will record.

- **Right after a commit** the draft equals that commit, so `git status` says "nothing to commit".
- **Never sent to GitHub:** only commits travel.

shell

```
$ git add styles.css      # snapshot of styles.css goes into the draft
$ # ...you edit styles.css again and save...
$ git status
On branch main
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
    modified:   styles.css

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
    modified:   styles.css
```

Example. You fix a typo in the heading of `index.html` and, in the same session, start an experimental animation in `styles.css`. `git add index.html` then `git commit -m "Fix typo in main heading"` records only the fix. The animation stays modified in the working directory, out of the history, until it works.

Common mistake. Thinking that once a file has been added, the commit takes whatever content it has later. Edits after `git add` need another `git add`, or the commit silently contains the older version. Also, `git add` does not move the file anywhere: it copies its content, and the file stays on your disk.

Commits: snapshot, hash, message

A commit is a saved snapshot of the whole project at one moment, identified by a unique **hash** and stored with an author, a date, a message and a link to its parent commit(s).



Each commit points to its parent; the chain is the history.

Hash

A 40-character hexadecimal identifier computed from the commit's content, metadata and parent. Change anything, even one letter of the message, and the hash changes, so history cannot be altered silently. The first 7 characters (`3f9c2a1`) are enough within a project, and each commit has its own page on GitHub, <https://github.com/<user>/<repo>/commit/<hash>>: the link to paste when someone asks you to "link the fix commit".

Message

A short summary line (about 50 characters) in the imperative, completing "If applied, this commit will...": "Add search filter to /books". If the reason is not obvious, add a blank line and explain **why**.

Author and date

From your Git settings (see [Install and configure Git](#)).

Commit messages: [one logical change per commit](#)

Weak	Better	Why
update	Add footer with contact links	Says what the commit does
fix	Fix 400 response when title is empty	Says which bug, so it can be found later
final version!!	Validate year as an integer in PATCH	Nothing is ever final; describe the change
stuff from today	Two commits: Add /stats route, Style the book list	One logical change per commit

shell

```
$ git log
commit 3f9c2a1e8b7d4c6a5f0e1d2c3b4a59687f1e2d3c
Author: Ana Ruiz <ana.ruiz@example.com>
Date: Mon Oct 5 10:12:44 2026 +0200

    Add contact form to index.html
```

Example. A teammate, or you three months later, asks: "which commit fixed the bug where PATCH wiped other fields?" A history like a1b2c3d Add Book store module, e4f5a6b Validate title and year, c7d8e9f Fix PATCH overwriting untouched fields gives the answer in seconds; 40 commits called "changes" do not.

Common mistake. Saving all work in one huge commit at the end ("final"). You lose the ability to undo one change without the others, your partner cannot review it, and the history no longer shows who did what or why. Commit small and often: each time one thing works.

Setup

Install and configure Git

Install Git once per computer, then tell it who you are (the name and email stamped on every commit), to call the first branch `main`, and which editor to open when it needs a message.

Installing Git

System	How
Windows	winget install Git.Git, or the installer from git-scm.com. It also brings Git Bash (a Unix-style terminal) and Git Credential Manager (the GitHub sign-in)
macOS	xcode-select --install (Apple's command-line tools), or brew install git with Homebrew
Linux	sudo apt install git (Debian, Ubuntu) or sudo dnf install git (Fedora)

user.name, user.email

Stamped on every commit. Use the email of your GitHub account, so your commits link to your profile.

init.defaultBranch main

Names the first branch `main`, as GitHub does since 2020. Git used to call it `master`: read `master` in older tutorials as `main`.

core.editor

The editor Git opens when it needs a message, for example VS Code with `"code --wait"`.

shell

```
# identity: use the same email as your GitHub account
git config --global user.name "Ana Ruiz"
git config --global user.email "ana.ruiz@example.com"

# name the first branch main, like GitHub
git config --global init.defaultBranch main
```

```
# open VS Code (not Vim) when Git needs a message, e.g. for a merge commit
git config --global core.editor "code --wait"

# check everything
git config --list
```

Example. Ana sets her name and the email of her GitHub account on her laptop. Every commit she makes in the team project shows "Ana Ruiz" with her avatar on GitHub. Her partner skipped the email step on a shared computer: his commits appear on GitHub as an unlinked author, with no profile picture.

Common mistake. Skipping the configuration. Git then refuses to commit with "Please tell me who you are", or guesses an identity like `ana@LAPTOP-7Q2.local` that GitHub cannot link to your account. Another classic: without `core.editor`, a merge opens **Vim** and you cannot get out. In Vim, type `:wq` and press Enter to save and quit.

git init vs git clone

`git init` **turns a local folder into a new, empty repository**; `git clone <url>` **downloads an existing repository, with all its files and history, and remembers where it came from.**

Which one?

	git init	git clone <url>
Starts from	A local folder	A repository that already exists, usually on GitHub
History	Empty	A complete copy
Link to GitHub	None yet: you add it later	Remembered under the name <code>origin</code>
Run it	Inside the project folder	In the parent folder: it creates the project folder

shell

```
# Path A (recommended): repository created on GitHub first
git clone https://github.com/ana-ruiz/books-api.git
cd books-api

# Path B: a local folder that already has work
cd my-project
git init
git add .
git commit -m "Initial commit"
```


Example. For a team project, one partner creates `books-api` on GitHub with a README and adds the other as a collaborator; then **both** run `git clone` on their own laptops. Both local repositories share the same first commit, so their work can later be pushed, pulled and merged.

Common mistake. Doing both: creating the GitHub repository **with** a README and also running `git init` and committing locally. The two repositories now have unrelated first commits, `git push` is rejected and `git pull` stops with "refusing to merge unrelated histories". Start again by cloning, and copy your files into the clone.

Everyday commands

The daily loop: status, add, commit

The everyday loop is: edit files, `git status`, `git add` **the changes that belong together**, `git commit -m "message"`, and repeat.



Every change goes round the same loop once.

- git add <file>** Stages one file; list several to stage them together: `git add index.html about.html`.
- git add .** Stages **every** change in this folder and below: modified files, new files and deletions.
- git commit -m "message"** Records the staged changes as a new commit. Without `-m`, Git opens your editor for the message. With nothing staged it answers "nothing added to commit" and creates nothing.

shell

```
$ git status
On branch main
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
    modified:   index.html

Untracked files:
  (use "git add <file>..." to include in what will be committed)
    about.html

no changes added to commit (use "git add" and/or "git commit -a")

$ git add index.html about.html
$ git commit -m "Add about page and link it from the home page"
[main 4b1e9d2] Add about page and link it from the home page
 2 files changed, 31 insertions(+), 1 deletion(-)
 create mode 100644 about.html

$ git status
On branch main
nothing to commit, working tree clean
```

Example. In the first `git status` output, `index.html` is modified and `about.html` is untracked. They belong together (the new page and the link to it), so one `git add` with both names and one commit record them. The commit exists only on your laptop until you push it (see [Remotes, origin and git push](#)).

Common mistake. Running `git add .` without looking. It happily stages `node_modules/` (thousands of files) and `.env` (your secrets) if no `.gitignore` excludes them. Run `git status` after `git add .` and before `git commit`, and read the list.

Inspecting: git log and git diff

`git log` **lists the commits of the current branch, newest first**; `git diff` **shows line by line what you changed but have not staged**, and `git diff --staged` **shows what the next commit will contain**.

What each command shows

Command	Shows
<code>git diff</code>	Working directory vs staging area: the edits not added yet
<code>git diff --staged</code>	Staging area vs last commit: what <code>git commit</code> would record now
<code>git log</code>	The commits of the current branch, newest first
<code>git log --oneline</code>	One line per commit: short hash and message
<code>git log --oneline --graph --all</code>	Every branch, drawn as a graph

Reading a diff

- **lines** were removed, + **lines** were added, lines starting with a space are unchanged context.
- @@ -6,7 +6,7 @@ means "7 lines starting at line 6, before and after".
- Long output** opens in a pager: the arrow keys scroll and `q` quits.

shell

```
$ git diff
diff --git a/index.html b/index.html
index 8a1f2c3..5d7e9b0 100644
--- a/index.html
+++ b/index.html
@@ -6,7 +6,7 @@
<body>
  <header>
    <a href="index.html">Home</a>
-   <h1>My Portfolio</h1>
+   <h1>Ana Ruiz - Portfolio</h1>
    <p>Web developer</p>
  </header>
  <main>

$ git log --oneline
4b1e9d2 Add about page and link it from the home page
3f9c2a1 Add contact form to index.html
a07e5c8 Initial commit
```

Example. Before committing, run `git diff --staged` and read it as your partner would: a forgotten `console.log("here")` comes out now, not in the history. In your own log you will also see labels such as (HEAD -> main) next to some hashes: they are branch names (see [Branches and HEAD](#)).

Common mistake. Running `git diff` right after `git add`, seeing nothing, and concluding the changes are lost. They are safe in the staging area; plain `git diff` shows only **unstaged** edits. Use `git diff --staged` to see them.

.gitignore: what never goes into Git

A **.gitignore file in the repository root lists file patterns Git must not track, such as** `node_modules/` **(re-created by** `npm install`**) and** `.env` **(secrets).**

What to ignore

Kind of file	Ignore it?	Examples
Generated or re-installable	Yes	<code>node_modules/</code> , <code>dist/</code> , <code>coverage/</code>
Secret	Yes	<code>.env</code>
Personal clutter	Yes	<code>.DS_Store</code> , <code>Thumbs.db</code>
What rebuilds the project	No: commit it	<code>package.json</code> , <code>package-lock.json</code> , <code>.env.example</code> with fake values

gitignore

```
# dependencies: re-created by npm install
node_modules/

# secrets: never commit; ship .env.example with fake values instead
.env
.env.*
!.env.example

# build output and test reports
dist/
coverage/

# operating-system clutter
.DS_Store
Thumbs.db
```

Example. An API reads `DATABASE_URL` and `JWT_SECRET` from `.env`, ships a `.env.example`, and must work from a fresh clone: a new teammate clones it, runs `npm install` (which rebuilds `node_modules/`) and copies `.env.example` to `.env`. The `.gitignore` in this card covers all of that.

Common mistake. Adding `.env` to `.gitignore` **after** it was committed and pushed. Git keeps tracking it, and the secret stays readable in the history on GitHub. Fix: `git rm --cached .env`, commit, push, and **change the secret** (a new password or key), because the old value stays public in the history.

Branches and merging

Branches and HEAD

A branch is a **movable label that points to one commit**; when you commit on a branch, its label moves forward to the new commit. HEAD marks the branch you are currently on.

Branch commands

Command	What it does
<code>git branch</code>	Lists local branches; * marks the current one
<code>git branch add-footer</code>	Creates the label at the current commit; you stay on your branch
<code>git switch add-footer</code>	Moves HEAD to that branch and updates your files to its latest commit
<code>git switch -c add-footer</code>	Creates and switches in one step
<code>git branch -d add-footer</code>	Deletes a branch that is already merged; its commits remain

- **In a log**, (HEAD -> add-footer) next to a hash shows where HEAD and each branch label point.
- **Older commands:** `git switch` and `git restore` (Git 2.23, 2019) split the old `git checkout`. Tutorials that use `git checkout add-footer` and `git checkout -b add-footer` mean the same.

shell


```
$ git switch -c add-footer
Switched to a new branch 'add-footer'
$ git branch
* add-footer
  main
$ # ...edit index.html and save...
$ git commit -am "Add footer"      # -a stages already-tracked modified files
$ git log --oneline --graph --all
* 8e4d7b2 (HEAD -> add-footer) Add footer
* 3f9c2a1 (main) Add contact form to index.html
```

Example. Before `git commit -am "Add footer"`, `main` and `add-footer` both pointed at `3f9c2a1`. After it, only `add-footer` moved to `8e4d7b2`; `main` still points at `3f9c2a1`, so switching back to `main` shows the page without the footer.

Common mistake. Creating a branch with `git branch add-footer` and then committing without switching: the commits land on `main`, because HEAD never moved. Check the * in `git branch` (or "On branch ..." in `git status`) before you commit. Also commit before switching: uncommitted edits travel with you to the other branch, or Git refuses to switch if they would be overwritten.

Merging: fast-forward vs merge commit

`git merge <branch>` **brings the commits of <branch> into the branch you are on**; if your branch has not moved since the other one started, Git just slides your label forward (**fast-forward**), otherwise it creates a **merge**

commit with two parents.

A merge commit has two parents, and both lines meet again at the common ancestor.

Fast-forward main has no commits that add-footer lacks, so the history is a straight line: Git moves the main label up to the tip of add-footer. No new commit.

Merge commit Both branches gained commits since they split. Git compares both tips with their **common ancestor** (the last commit they share), combines the changes and records a commit with **two parents**. It opens your editor for the message; the default "Merge branch 'add-footer'" is fine.

shell

```

$ git switch main
$ git merge add-footer          # main had not moved: fast-forward
Updating 3f9c2a1..8e4d7b2
Fast-forward
 index.html | 6 +++++
 1 file changed, 6 insertions(+)

$ git merge add-search          # main had moved too: merge commit
Merge made by the 'ort' strategy.
 app.js | 14 ++++++
 1 file changed, 14 insertions(+)

$ git log --oneline --graph
* d41c9a7 (HEAD -> main) Merge branch 'add-search'
| \
| * 5b2e1f0 (add-search) Add search box
* | 8e4d7b2 (add-footer) Add footer
| /
* 3f9c2a1 Add contact form to index.html
  
```

Example. Ana branches add-search from 3f9c2a1. Meanwhile her footer branch is fast-forwarded into main, so main moves to 8e4d7b2. When she merges add-search, both sides have new commits, so Git creates the merge commit d41c9a7, whose parents are 8e4d7b2 and 5b2e1f0.

Common mistake. Merging in the wrong direction: running `git merge main` while on add-footer when you meant to bring the footer into main. That updates the feature branch instead. Read "On branch ..." in `git status` first: you must be **on the receiving branch**.

Merge conflicts

A merge conflict happens when both sides changed the **same lines** of a file (or one side deleted a file the other edited); Git stops, writes both versions into the file between markers, and waits for you to choose the final content and commit.

```

<<<<<< HEAD           Starts your version, from the branch you are on ("Current" in VS Code).
=====               Separates the two versions.
>>>>>> add-title       Ends their version, from the branch being merged ("Incoming" in VS
                        Code). During a git pull, "theirs" is the commits that arrived from GitHub.
  
```

Resolving it

1. `git status` lists the files under "Unmerged paths" as "both modified".

2. Edit each file to its final content (yours, theirs, both or something new) and delete all three marker lines.
3. `git add <file>` marks it resolved.
4. `git commit` completes the merge; the message is pre-filled.

shell

```
$ git merge add-title
Auto-merging index.html
CONFLICT (content): Merge conflict in index.html
Automatic merge failed; fix conflicts and then commit the result.

# index.html now contains:
<<<<<< HEAD
    <h1>Ana Ruiz - Portfolio</h1>
=====
    <h1>Ana Ruiz - Web Developer</h1>
>>>>>> add-title

# edit it to the final line, e.g. <h1>Ana Ruiz - Web Developer Portfolio</h1>
$ git add index.html
$ git commit                                # accept the pre-filled "Merge branch 'add-title'"
```

Example. Both partners add a row to the endpoint table in `README.md`, each on their own branch. Luis's branch is merged first; merging Ana's then stops with a conflict in `README.md`. She keeps both new rows, deletes the markers, runs `git add README.md` and `git commit`. Total: two minutes.

Common mistake. Committing with the markers still in the file: the page then shows <<<<<< HEAD, or JavaScript fails with a syntax error. Before `git add`, search the file for <<<<<<. The other panic reaction, deleting the folder and cloning again, throws away your un-pushed commits.

Remotes

Signing in to GitHub from Git

GitHub does not accept your account password for Git commands; you prove who you are with a browser sign-in through a credential helper, a personal access token, the GitHub CLI or an SSH key.

Ways to sign in; the first two are the easiest

Option	How	Notes
Git Credential Manager (HTTPS)	Included with Git for Windows. On the first push a browser window opens; sign in to GitHub and approve	Nothing to configure on Windows
GitHub CLI (HTTPS)	Install <code>gh</code> , run <code>gh auth login</code> , choose HTTPS and "Login with a web browser"	Works on Windows, macOS and Linux; also configures Git
Personal access token (HTTPS)	github.com → Settings → Developer settings → Personal access tokens; paste the token when Git asks for a password	Treat it like a password; it expires; never commit it
SSH key	<code>ssh-keygen -t ed25519 -C "you@example.com"</code> ; add the public key (~/.ssh/id_ed25519.pub) in Settings → SSH and GPG keys; use the SSH URL <code>git@github.com:user/repo.git</code>	No prompts afterwards; the private key never leaves your computer

shell

```
$ git push
Username for 'https://github.com': ana-ruiz
Password for 'https://ana-ruiz@github.com':          # account password typed here
remote: Support for password authentication was removed on August 13, 2021.
fatal: Authentication failed for 'https://github.com/ana-ruiz/portfolio.git/'

$ gh auth login      # fix: sign in once through the browser, then push again
$ git push
```

Example. On a Windows laptop with Git for Windows, Ana's first `git push` opens the browser, she clicks "Authorize", and the push completes. On a shared Linux machine the same push asks for a username and password, so she runs `gh auth login` once instead.

Common mistake. Pasting a token into a script, a README or a `.env` that gets committed. A token in a public repository is a leaked key: anyone can push to your repositories with it. If it happens, delete the token on GitHub at once and generate a new one.

Remotes, origin and git push

A remote is a named link to another copy of the repository, usually on GitHub (origin is the name `git clone` gives it); `git push` uploads the commits of your current branch that the remote does not have yet.

`git push`

Uploads the commits of your branch that the remote does not have: commits only, not files, edits or the staging area.

`git push -u origin <branch>`

The first push of a branch: creates it on GitHub and, with `-u` (upstream), remembers the link, so later `git push` and `git pull` need no arguments.

`git remote add origin <url>`

Links a repository made with `git init` to an **empty** GitHub repository (no README, no licence). Then push with `git push -u origin main`.

"ahead of 'origin/main' by 1 commit"

What `git status` says when you have commits the remote lacks: push them.

shell

```
$ git remote -v
origin https://github.com/ana-ruiz/books-api.git (fetch)
origin https://github.com/ana-ruiz/books-api.git (push)

$ git push -u origin main      # first push of main
$ git push                    # later pushes


# when your partner pushed first:
$ git push
To https://github.com/ana-ruiz/books-api.git
 ! [rejected]        main -> main (fetch first)
error: failed to push some refs to 'https://github.com/ana-ruiz/books-api.git'
$ git pull                    # integrate their commits, then
$ git push
```

Example. Reviewers, teammates and deployment tools read the default branch **on GitHub**, not your laptop. After the final `git push`, open the repository page on `github.com` and check that the latest commit message and time are yours.

Common mistake. Trusting "Your branch is up to date with 'origin/main'" as live news. It compares with `origin/main` **as of your last fetch or pull**; your partner may have pushed five minutes ago. Run `git fetch` (or `git pull`) first when you need the current state.

git fetch vs git pull

`git fetch` **downloads new commits from the remote into `origin/<branch>` without touching your files or your branch**; `git pull` is `git fetch` **followed by integrating those commits into your current branch (by default with a merge)**.



`git pull` takes both steps; `git fetch` stops halfway, so you can look first.

fetch vs pull

	git fetch	git pull
Downloads new commits	Yes	Yes
Updates origin/main	Yes	Yes
Changes your branch and files	No	Yes: a merge, or a fast-forward
Can cause a conflict	Never	Yes, if both sides changed the same lines

shell

```
# once per computer: make pull merge when histories diverge
git config --global pull.rebase false

git fetch                # see what arrived without changing anything
git log --oneline main..origin/main # commits on GitHub you do not have yet
git pull                 # bring them into your branch
```

Example. Monday morning: your partner pushed the validation module during the weekend. `git pull` brings their three commits into your `main` (a fast-forward, because you had not committed anything since). Only then do you start your own work.

Common mistake. Pulling with uncommitted edits to files the incoming commits change. Git refuses with "Your local changes to the following files would be overwritten by merge". Commit your work, set it aside with `git stash` (see [Tags and stash](#)), or discard it, then pull again.

Working in a team

Tags and stash: marking versions, setting work aside

A **tag** is a permanent name for one commit, such as `v1.0`; `git stash` sets uncommitted changes aside so the working directory is clean, and `git stash pop` brings them back.

Tags

`git tag -a v1.0 -m "First release"` Creates an annotated tag, with author, date and message, on the current commit.

`git tag` Lists the tags.

`git push origin v1.0` Tags are not pushed with your commits: push each one, or all of them with `git push --tags`. GitHub lists them under Tags and Releases.

`git switch --detach v1.0` Shows that version. You are on no branch ("detached HEAD"), so create a branch before committing there.

Stash

`git stash` Saves your uncommitted changes to tracked files, staged or not, and cleans the working directory.

`git stash -u` Includes untracked files too.

`git stash list` The saved stashes, newest first.

`git stash pop` Re-applies the newest stash and removes it from the list.

shell

```
# mark the version you deliver
git tag -a v1.0 -m "First finished version"
git push origin v1.0


# a pull refused because of local edits
git stash          # edits set aside, working directory clean
git pull
git stash pop      # edits back, on top of the new commits
```

Example. `git pull` refuses: "Your local changes to the following files would be overwritten by merge", and your edits are not ready to commit. `git stash`, `git pull`, `git stash pop`: your partner's commits arrive and your edits land back on top. If both touched the same lines, `pop` stops with a conflict, which you resolve like a [merge conflict](#).

Common mistake. Forgetting a stash. Stashed work is in no commit and on no branch, so weeks later it is easy to lose: check `git stash list` before you delete a clone, and keep anything you need for longer than a few minutes as a commit on a branch. Also, a plain `git stash` leaves new files behind; add `-u` to include them.

GitHub flow and pull requests

GitHub flow is a team workflow: create a branch for each change, push it, open a **pull request (PR)** on GitHub, get it reviewed, merge it into `main`, and everyone pulls the updated `main`.



Every change reaches `main` the same way: through a reviewed pull request.

On GitHub

- **Open the PR:** Compare & pull request; describe what and why; request your partner as reviewer.
- **Review:** the reviewer reads the diff and comments or approves; fixes you push to the same branch update the PR.
- **Merge:** Merge pull request. Then everyone runs `git switch main` and `git pull`, and deletes the branch with `git branch -d`.

shell

```

git switch main
git pull
git switch -c validate-form
# ...edit, git add, git commit (several small commits)...
git push -u origin validate-form
# on github.com: Compare & pull request -> request review -> Merge pull request
git switch main
git pull
git branch -d validate-form
  
```

Example. A first version is finished and you want to start the next phase while keeping that version easy to find: `git tag -a v1.0 -m "First finished version"`, `git push origin v1.0`, and keep working on `main` through pull requests. The README says: "The first version is the tag `v1.0`" (see [Tags and stash](#)).

Common mistake. Long-lived branches: two weeks of work on one branch without pulling `main` produces one enormous PR with dozens of conflicts. Keep each PR to one change and merge it within a day or two. And never keep committing on a branch whose PR was already merged; start a new branch from the updated `main`.

Undoing safely

Undo before committing: `git restore`

`git restore --staged <file>` **takes a file out of the staging area but keeps your edits**; `git restore <file>` **throws away uncommitted edits in the working directory, returning the file to its staged (or last committed) version.**

Pick the right undo

Situation	Command	Safe?
Staged a file by mistake (e.g. <code>.env</code>)	<code>git restore --staged .env</code>	Yes: the file and its content stay
Throw away an unstaged experiment	<code>git restore styles.css</code>	No: the edits are lost for good
Staged and want to discard	<code>git restore --staged styles.css</code> , then <code>git restore styles.css</code>	No: the edits are lost
Deleted a tracked file by accident	<code>git restore index.html</code>	Yes: it comes back from Git

- **Unstaging is always safe.**
- **Discarding is permanent:** those edits were never committed, so Git has no copy of them.
- **Older tutorials** use `git reset HEAD <file>` to unstage and `git checkout -- <file>` to discard.

shell

```
$ git add .
$ git status
On branch main
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
    new file:   .env
    modified:   index.html

$ git restore --staged .env      # .env back to untracked; the file is untouched
$ git commit -m "Show book count in header"

$ git restore styles.css        # DISCARD the unstaged edits to styles.css
```


Example. You ran `git add .` and `git status` shows `new file: .env`. Before committing, `git restore --staged .env` takes it out; then add `.env` to `.gitignore` so it never happens again. Nothing has left your laptop, so nothing leaked.

Common mistake. Typing `git restore styles.css` when you meant `git restore --staged styles.css`. The first one erases a morning of uncommitted work with no way back. When unsure, commit first (on a branch if it is experimental): committed work can always be recovered.

Undo after committing: `revert`, `amend`, `reset`

To undo a commit that is already pushed, use `git revert <hash>`, which adds a new commit that cancels it; `git`

`commit --amend` and `git reset` **rewrite history**, so use them only on commits that exist only on your laptop.



Pushed: revert. Not pushed yet: amend or reset are fine.

Undoing commits

Command	What it does	Rewrites history?	OK after push?
<code>git revert <hash></code>	New commit with the opposite changes	No	Yes
<code>git commit --amend</code>	Replaces the last commit: fix the message, add a forgotten file	Yes	No
<code>git reset --soft HEAD~1</code>	Removes the last commit; its changes stay staged	Yes	No
<code>git reset --hard <hash></code>	Moves the branch back and discards all uncommitted work	Yes	No; avoid it unless you are sure

shell

```

# a pushed commit broke the page: cancel it with a new commit
$ git log --oneline
8e4d7b2 (HEAD -> main, origin/main) Remove contact form
3f9c2a1 Add contact form to index.html
$ git revert --no-edit 8e4d7b2
[main c71a0f4] Revert "Remove contact form"
1 file changed, 12 insertions(+)
$ git push
  
```

```

# forgot a file in the last commit, NOT pushed yet:
$ git add about.html
$ git commit --amend --no-edit
  
```

Example. Luis pushed a commit that deleted the contact form. Ana, who already pulled it, sees `git revert` arrive as an ordinary new commit "Revert ..." on her next pull. Had Luis used `git reset` and `git push --force`, Ana's next push would bring the bad commit back or fail, and work could be lost.

Common mistake. Amending or resetting a commit that was already pushed, then "fixing" the rejected push with `git push --force`. That replaces the shared history and can delete your partner's commits. On a shared branch, use `git revert`.