

On the Complexity of Finding Approximate LCS of Multiple Strings

Hamed Hasibi, Neerja Mhaskar, and W. F. Smyth

Department of Computing & Software, McMaster University, Canada
hasibih, pophlin, smyth@mcmaster.ca

Abstract. Finding an Approximate Longest Common Substring (ALCS) within a given set $\mathcal{S} = \{s_1, s_2, \dots, s_m\}$ of $m \geq 2$ strings is a problem of particular importance in computational biology (e.g., identifying related mutations across multiple genetic sequences). In this paper, we study several ALCS problems that, for given integers k and $t \leq m$, require finding a longest string u — or a longest substring u of any string in \mathcal{S} — that lies within distance k of at least one substring in t distinct strings of \mathcal{S} . Although two of these problems, denoted k -LCS and k - t LCS, are NP-hard, nevertheless restricted variations of them under Hamming and edit distance can be solved in $\mathcal{O}(N^2)$ and $\mathcal{O}(k\ell N^2)$ time, respectively, where ℓ is the length of each string and $N = m\ell$. Further, we show that using the k -errata tree data structure, a restricted variation of the ALCS problem under both Hamming and edit distance can be computed in $\mathcal{O}(mN \log^k \ell)$ time.

Keywords: Approximate Longest Common Substring · LCS of multiple strings · Hamming distance · Edit distance · k -errata trie

1 Introduction

Finding similar strings occurring within a specified distance from a given string set is a challenging problem in many application areas, notably in the analysis of genomic sequences in computational biology. The Longest Common Substring (LCS) is widely used to quantify similarity among DNA sequences. However, due to the evolutionary processes affecting biological sequences, instead of finding exact common substrings, “approximate” occurrences — such as the Approximate Longest Common Substring (ALCS) — are of great interest.

Exact applications of the LCS problem are not always useful for measuring the similarity between two or more sequences. For example, let $ELCS(s_1, s_2)$ denote the Exact LCS between strings s_1 and s_2 . For given strings $s_1 = a^m b a^m$, $s_2 = a^{2m} b$, and $s_3 = b a^{2m}$, we find $ELCS(s_1, s_2) = ELCS(s_1, s_3) = a^m b$, while $ELCS(s_2, s_3) = a^{2m}$. But the similarity of s_1 with s_2 also relates to a^{2m} . To more accurately address these similarities, several problems related to the ALCS of two strings have been defined [1, 3, 9, 11, 21]. In this paper, we study ALCS problems for more than two strings.

In Section 2, we introduce terminology. Then, in Section 3 we define new problems related to the ALCS of multiple strings. In Section 4 we review existing literature on ELCS and ALCS problems, in addition to NP-hardness of some of ALCS problems. In Sections 5 and 6, we introduce polynomial and polylog time solutions to problems defined in Section 3, respectively.

2 Preliminaries

A **string** s is a sequence of $n \geq 0$ **letters** drawn from a finite ordered set Σ called an **alphabet**. Alphabet **size** is $\sigma = |\Sigma|$. Thus, we treat a string s as an array $s[1..n]$ of elements drawn from Σ . We say that s has **length** $n = |s|$ and **positions** $1, 2, 3, \dots, n$. An **empty** string ($n = 0$) is denoted by ε . For any pair of integers i and j satisfying $1 \leq i \leq j \leq n$, we define a **substring** $s[i..j]$ (sometimes called **factor**) of s as follows: $s[i..j] = s[i]s[i+1]..s[j]$. We say that substring $s_1[i..j]$ of s_1 **occurs** in string s_2 if a substring $s_2[i'..j'] = s_1[i..j]$. A **prefix** (**suffix**) of nonempty s is a substring $s[i..j]$, where $i = 1$ ($j = n$).

An **edit operation** on a string is the insertion, deletion or substitution of a single letter. The **cost** of an edit operation is an integer function of the operation type and the letters involved. Given two strings s_1 and s_2 , both of length n , the **Hamming distance** $d_H(s_1, s_2)$, is defined to be the minimum cost of substitutions that transform s_1 to s_2 . More generally, for $n_1 = |s_1|$ and $n_2 = |s_2|$, $n_1 < n_2$, the **edit distance** $d_E(s_1, s_2)$ is the minimum cost over all sequences of edit operations that transform s_1 to s_2 . In the case that each edit operation has unit cost, the edit distance is called **Levenshtein distance** and denoted $d_L(s_1, s_2)$. A **k -approximate occurrence** of any string u under distance $\delta \in \{H, L, E\}$ is a string u' such that $d_\delta(u, u') \leq k$.

3 Definitions of ALCS Problems on Multiple Strings

In this section, we define the following problems on a given alphabet Σ related to the ALCS of multiple strings under distance metric δ , where $\delta \in \{H, L, E\}$ represents Hamming, Levenshtein, and edit distances, respectively, and a maximum distance $k > 0$ is specified. For given finite $k, t, m \in \mathbb{N}$, $t \leq m$, a set $\mathcal{S} = \{s_1, s_2, \dots, s_m\}$ of strings, where $|s_1| = |s_2| = \dots = |s_m| = \ell$, we define the following problems:

1. **k Longest Common Substring (k -LCS)**: find a longest string u such that there exist substrings u_i of s_i , $1 \leq i \leq m$, for which $d_\delta(u, u_i) \leq k$.
2. **k - t Longest Common Substring (k - t LCS)**: find a longest string u such that there exists a subset $\mathcal{S}' = \{s'_1, s'_2, \dots, s'_t\} \subseteq \mathcal{S}$, for which substrings u'_i of s'_i , $1 \leq i \leq t$, satisfy $d_\delta(u, u'_i) \leq k$.
3. **Restricted k Longest Common Substring (Rk -LCS)**: find a longest substring u of any string in \mathcal{S} , such that there exist substrings u_i of s_i , $1 \leq i \leq m$, for which $d_\delta(u, u_i) \leq k$.

4. **Restricted k - t Longest Common Substring (Rkt -LCS)**: find a longest substring u of any string in S such that a subset $S' = \{s'_1, s'_2, \dots, s'_t\} \subseteq S$ exists for which substrings u'_i of s'_i , $1 \leq i \leq t$, satisfy $d_\delta(u, u'_i) \leq k$.
5. **Max Coverage Rkt -LCS**: find the maximum size set $U = \{u_1, u_2, \dots, u_q\}$, where each u_i , $1 \leq i \leq q$, is a Rkt -LCS of S under metric δ .
6. **Max Set Rkt -LCS**: given a string u , which is an Rkt -LCS of S under distance metric δ , find the maximum size set $S' = \{s'_1, s'_2, \dots, s'_p\} \subseteq S$, $p \geq t$, such that there exist substrings u'_i of s'_i , $1 \leq i \leq p$, satisfying $d_\delta(u, u'_i) \leq k$.
7. **Restricted k -LCS Set (Rk -LCSS)**: Given finite $k, m \in \mathbb{N}$ and a set $S = \{s_1, s_2, \dots, s_m\}$ of strings, find a set of longest substrings $\{u_1, \dots, u_m\}$ of $\{s_1, \dots, s_m\}$, respectively, such that $d_\delta(u_i, u_j) \leq k$ for every $1 \leq i, j \leq m$.

In the first two problems (k -LCS and k - t LCS), the output is a longest string drawn from S , while, in the *restricted* variations of these problems (Rk -LCS and Rkt -LCS), we require the solution to be a longest substring of one of the strings in S .

4 Literature Review

In this section, we review the three following categories of LCS problems. These problems can be regarded as variations of the problems defined in Section 3:

- ELCS of two strings (Rk -LCS, where $k=0$ and $m=2$)
- ELCS of more than two strings (Rkt -LCS, where $k=0$ and $t > 2$)
- ALCS of two strings (Rk -LCS, where $k > 0$ and $m=2$)

ELCS of two strings. Given two strings s_1 and s_2 , each of length n , find a longest substring occurring in both s_1 and s_2 .

Weiner showed that this problem can be solved in $\mathcal{O}(n)$ -time for a constant-size alphabet [22]. Later, Farach showed that if the alphabet is not constant, a suffix tree can be constructed in linear time in addition to the time required for sorting its letters [8]. This yielded an $\mathcal{O}(n)$ -time algorithm for the ELCS problem in the word RAM model for polynomially-bounded integer alphabets. Then, using Farach's results, Charalampopoulos *et al.* showed that the ELCS problem over an alphabet $[0, \sigma)$ can be solved in $\mathcal{O}(n \log \sigma / \sqrt{\log n})$ -time and $\mathcal{O}(n / \log_\sigma n)$ -space complexity, where $\log \sigma = o(\sqrt{\log n})$ [6].

ELCS of more than two strings. Given a string set $S = \{s_1, s_2, \dots, s_m\}$, m positive integers x_1, x_2, \dots, x_m , and t where $1 \leq t \leq m$, find a longest substring u of any string in S for which there are at least t strings $s_{i_1}, s_{i_2}, \dots, s_{i_t}$ ($1 \leq i_1 < i_2 < \dots < i_t \leq m$) such that u occurs at least x_{i_j} times in s_{i_j} for each j with $1 \leq j \leq t$ [2].

Lee and Pinzon show that this problem can be solved in $\mathcal{O}(N)$ time [17], where $N = \sum_{i=1}^m |s_i|$. A simple solution for all $1 \leq t \leq m$, requires $\mathcal{O}(mN)$ time using Lee and Pinzon results. However, a much simpler and more efficient solution was proposed by Arnold and Ohlebusch that requires $\mathcal{O}(N)$ time for all $1 \leq t \leq m$ [2].

ALCS of two strings ($\delta = H$). Given two strings s_1 and s_2 , each of length n , find a longest substring (of either s_1 or s_2) that occurs in both s_1 and s_2 with at most k mismatches.

In 2011, Babenko and Starikovskaya [3] solve this problem for $k = 1$ in $\mathcal{O}(n^2)$ -time and $\mathcal{O}(n)$ -space complexity. This result for $k = 1$ was later improved by Flouri *et al.* in [9], where they propose an $\mathcal{O}(n \log n)$ -time and $\mathcal{O}(n)$ -space approach.

Leimeister and Morgenstern, in 2014, introduced this problem for $k > 1$ and proposed a greedy heuristic algorithm to solve it [18]. Since then, several researchers have worked on this problem and presented improved solutions. In particular, Flouri *et al.* in 2015 [9] presented a simple and elegant $\mathcal{O}(n^2)$ -time algorithm that uses constant additional space. Grabowski [11] presented two output-dependent algorithms, with $\mathcal{O}(n((k+1)(l_o+1))^k)$ and $\mathcal{O}(n^2 k/l_k)$ time complexities, where l_o is the length of the ELCS of s_1 and s_2 and l_k is the length of the ALCS of s_1 and s_2 . Abboud *et al.* in [1] described a $k^{1.5} n^2 / 2^{\Omega(\sqrt{(\log n)/k})}$ -time randomized solution to this problem. In 2016, Thankachan *et al.* [21] presented an $\mathcal{O}(n \log^k n)$ -time and $\mathcal{O}(n)$ -space solution. Then in 2018, Charalampopoulos *et al.* proved an $\mathcal{O}(n)$ -time and space solution where the length of ALCS is $\Omega(\log^{2k+2} n)$ [5]. In 2019, Kociumaka *et al.* showed that assuming the Strong Exponential Time Hypothesis (SETH) [13][14], no strongly subquadratic-time solution for this problem exists for $k \in \Omega(\log n)$ [16]. Finally in 2021, Charalampopoulos *et al.* [6] showed that this problem can be solved in $\mathcal{O}(n \log^{k-1/2} n)$ -time and $\mathcal{O}(n)$ -space complexity.

ALCS of two strings ($\delta = \{L, E\}$). Given two strings s_1 and s_2 , each of length n , find a longest substring (of either s_1 or s_2) that occurs in both s_1 and s_2 with at most k edit operations.

In 2015 Abboud *et al.* described a $k^{1.5} n^2 / 2^{\Omega(\sqrt{(\log n)/k})}$ -time randomized solution [1] for ALCS of two strings for $\delta = \{L, E\}$. In 2018, Thankachan *et al.* proposed an $\mathcal{O}(n \log^k n)$ -time and $\mathcal{O}(n)$ -space solution to this problem [20].

4.1 NP-Hardness of k -LCS and $k - t$ LCS

The k -LCS problem under Hamming distance (defined in Section 3) is called the *Longest Common Approximate Substring* problem in [19], and has been proved to be NP-hard by reducing the *Vertex Cover* problem to it. It has also been shown that this problem cannot be approximated in polynomial time with a performance ratio better than $2 - \varepsilon$, for any $\varepsilon > 0$, unless $P = NP$ [19, Theorems 4.12 & 4.13]. Hence, we have the following:

Theorem 1. *The k -LCS problem is NP-hard under Hamming distance.*

(Partial Vertex Cover) Given a graph $G = (V, E)$, positive integers k, t , is there a vertex subset $C \subseteq V$, $|C| \leq k$, such that C covers at least t edges?

It is shown that *Partial Vertex Cover* is NP-hard [4, 10, 12]. We can make a reduction from *Partial Vertex Cover* to k - t LCS. We construct an instance of k - t LCS with $|E|$ strings corresponding to edges in G . k -approximate occurrence

of a k - t LCS in at least t strings of set S corresponds to a *Partial Vertex Cover*, covering at least t edges. String gadget construction for this reduction remains similar to [19].

Theorem 2. *The k - t LCS problem is NP-hard under Hamming distance.*

5 Polynomial Time Solution for Restricted ALCS

In this section, we solve the four restricted variations of the ALCS problem identified by prefix Rk in Section 3. For this, we use an auxiliary table called *lengthStat* (Definition 1).

For strings s_1 and s_2 , and $k \in \mathbb{N}$, $LCP_{(s_1, s_2)}^{H, k}[i', j']$ for $1 \leq i' \leq |s_1|$ and $1 \leq j' \leq |s_2|$, is the length of the longest common prefix with at most k mismatches, of suffixes $s_1[i'..|s_1|]$ and $s_2[j'..|s_2|]$. An example of $LCP_{(s_1, s_2)}^{H, k}$ is shown in Table 1 (See appendix). In addition to ALCS of two strings under the Hamming distance, Flouri et al. [9] compute $LCP_{(s_1, s_2)}^{H, k}$ in $\mathcal{O}(|s_1||s_2|)$ time. Hence, for two strings of equal length, we establish the following lemma.

Lemma 1. ([9]) *For strings s_1 and s_2 , each of length ℓ , and $k \in \mathbb{N}$, the $LCP_{(s_1, s_2)}^{H, k}$ table can be computed in $\mathcal{O}(\ell^2)$ time.*

Definition 1 (LengthStat Data Structure). *For $S = \{s_1, s_2, \dots, s_m\}$, $1 \leq i, j \leq m$, $1 \leq p \leq |s_i|$, and $1 \leq l \leq |s_i| - p + 1$, $lengthStat_{(p, i)}^k[l, j] = 1$ iff there exists a position $1 \leq q \leq |s_j|$ such that $LCP_{(s_i, s_j)}^{H, k}[p, q] \geq l$; otherwise, $lengthStat_{(p, i)}^k[l, j] = 0$. The last $(m + 1)$ -th column contains the sum of the values in each row.*

Algorithm 1 Computes *lengthStat* table for suffix p of s_i

```

1: procedure LENGTHSTAT( $LCP_{(s_i, s_j)}^{H, k}, p, i$ )
2:    $lengthStat_{(p, i)}^k[1..|s_i| - p + 1, 1..m + 1] \leftarrow 0$        $\triangleright$  Initial table with all zeros
3:   for all  $j, q$  values do
4:      $l \leftarrow LCP_{(s_i, s_j)}^{H, k}[p, q]$ 
5:      $lengthStat_{(p, i)}^k[l, j] \leftarrow 1$ 
6:   for  $r$  from  $|s_i| - p + 1$  to  $k + 2$  do
7:      $lengthStat_{(p, i)}^k[r - 1, 1..m] \leftarrow lengthStat_{(p, i)}^k[r, 1..m] \vee lengthStat_{(p, i)}^k[r -$ 
8:        $1, 1..m]$ 
9:      $lengthStat_{(p, i)}[r, m + 1] = \sum_{j=1}^m lengthStat_{(p, i)}[r, j]$ 
10:     $lengthStat_{(p, i)}[k + 1, m + 1] = \sum_{j=1}^m lengthStat_{(p, i)}[k + 1, j]$ 
11:   return  $lengthStat_{(p, i)}^k$ 

```

Thus, $lengthStat_{(p, i)}^k[l, j] = 1$ indicates the existence of a k -approximate occurrence of $s_i[p, p + l - 1]$ (the l -length prefix of the suffix of s_i starting at

position p) in \mathbf{s}_j . Under the Hamming distance metric, it checks whether there exists at least one q such that $d_H(\mathbf{s}_i[p, p+l-1], \mathbf{s}_j[q, q+l-1]) \leq k$. We present Algorithm 1 to compute the *lengthStat* table for a suffix starting at position p of \mathbf{s}_i .

Lemma 2. *For a given set \mathbf{S} of m strings, $LCP_{(s_i, s_j)}^{H,k}$ for all i and j values, $1 \leq i, j \leq m$, can be computed in $\mathcal{O}(N^2)$ time, where $N = m\ell$.*

Proof. By Lemma 1, computing $LCP^{H,k}$ between any two strings in \mathbf{S} requires $\mathcal{O}(\ell^2)$ time. Therefore, computing $LCP_{(s_i, s_j)}^{H,k}$ $1 \leq i, j \leq m$, for all pairs of strings in \mathbf{S} ; that is, $\binom{m}{2} = \mathcal{O}(m^2)$ pairs, requires $\mathcal{O}(m^2\ell^2) = \mathcal{O}(N^2)$ time. \square

Lemma 3. *After computing $LCP_{(s_i, s_j)}^{H,k}$ for all (s_i, s_j) pairs, $1 \leq i, j \leq m$, $lengthStat_{(p,i)}^k$ for any suffix of any string $\mathbf{s}_i \in \mathbf{S}$ can be computed in $\mathcal{O}(N)$ time.*

Proof. The **for** loop in line 3 of Algorithm 1 takes $\mathcal{O}(m\ell) = \mathcal{O}(N)$ time to iterate through all the $LCP_{(s_i, s_j)}^{H,k}[p, q]$ values, where $1 \leq j \leq m$ and $1 \leq q \leq \ell$. The **for** loop in line 6 takes $\mathcal{O}(\ell)$ time. Hence, the total time complexity is $\mathcal{O}(N)$. \square

In a greedy approach, since each substring can be a solution to *Rk*-LCS or *Rkt*-LCS, we compute the *lengthStat* table for all N suffixes in \mathbf{S} . Using the last column of $lengthStat_{(p,i)}$ table, we pick the substring $\mathbf{s}_i[p..p+l'-1]$ with maximum l' , that has k -approximate occurrences in m (t) distinct strings for *Rk*-LCS (*Rkt*-LCS) problems. Our approach greedily computes the set of the longest prefix of every suffix in set \mathbf{S} , which has k -approximate occurrences in up to t (or m) distinct strings and finally selects the longest one.

Theorem 3. *The restricted ALCS problems for $\mathbf{S} = \{\mathbf{s}_1, \mathbf{s}_2, \dots, \mathbf{s}_m\}$ under Hamming distance can be computed in $\mathcal{O}(N^2)$ time and $\mathcal{O}(N)$ additional space.*

Proof. Algorithm 2 is a solution to restricted ALCS problems. The **for** loop in line 3 takes $\mathcal{O}(N)$ time. Line 4 computes *lengthStat* table for each suffix in $\mathcal{O}(N)$ time using Lemma 3. The **for** loop in line 5 takes at most $\mathcal{O}(\ell)$ time, where ℓ is the length of each string in \mathbf{S} . Therefore, the total time complexity is $\mathcal{O}(N(N + \ell)) = \mathcal{O}(N^2)$. Line 20 releases the space used by *lengthStat* of a particular suffix, which will be used by the next suffix. Hence, the total space required is $\mathcal{O}(m\ell) = \mathcal{O}(N)$. \square

For $\mathbf{S} = \{\mathbf{s}_1, \mathbf{s}_2, \mathbf{s}_3, \mathbf{s}_4\} = \{aabc f, fabcd, dgiabc, ahabch\}$, $k = 2$, and $t = 3$, substring *iabc* of \mathbf{s}_3 is a *Rk*-LCS of \mathbf{S} , substring *aabc f* of \mathbf{s}_1 is a *Rkt*-LCS of \mathbf{S} , substring set $U = \{aabc f, habch, fabcd\}$ is the Max Coverage *Rkt*-LCS of \mathbf{S} , and the Max Set *Rkt*-LCS of \mathbf{S} for the *Rkt*-LCS *habch* is $\mathbf{S}' = \{\mathbf{s}_1, \mathbf{s}_2, \mathbf{s}_4\}$.

For finding the solutions to restricted ALCS problems under Levenshtein and edit distances, we use the *Longest Approximate Prefix* data structure introduced by Kędzierski and Radoszewski in [15].

Algorithm 2 Computes solution to restricted ALCS problems

```

1: procedure ALCS( $k, t$ )
2:    $kLCS, ktLCS, msktLCS, mcktLCS \leftarrow \emptyset$ 
3:   for each suffix  $p$  of every  $s_i$  in  $\mathbf{S}$  do  $\triangleright \mathcal{O}(N)$  time
4:     Compute  $lengthStat_{(p,i)}^k[1..|s_i| - p + 1, 1..m + 1]$   $\triangleright \mathcal{O}(N)$  time
5:     for  $l = |s_i| - p + 1$  to 1 do
6:       if  $lengthStat_{(p,i)}^k[l, m + 1] = m$  &&  $|kLCS| < l$  then
7:          $kLCS \leftarrow s_i[p..p + l - 1]$ 
8:       if  $lengthStat_{(p,i)}^k[l, m + 1] \geq t$  &&  $|ktLCS| < l$  then
9:          $ktLCS \leftarrow s_i[p..p + l - 1]$ 
10:       $msktLCS, mcktLCS \leftarrow \emptyset$ 
11:       $mcktLCS.append(s_i[p..p + l - 1])$ 
12:      for  $str = 1$  to  $m$  do
13:        if  $lengthStat_{(p,i)}^k[l, str] = 1$  then
14:           $msktLCS.append(s_i[p..p + l - 1], str)$ 
15:      if  $lengthStat_{(p,i)}^k[l, m + 1] \geq t$  &&  $|ktLCS| = l$  then
16:         $mcktLCS.append(s_i[p..p + l - 1])$ 
17:      for  $str = 1$  to  $m$  do
18:        if  $lengthStat_{(p,i)}^k[l, str] = 1$  then
19:           $msktLCS.append(s_i[p..p + l - 1], str)$ 
20:       $lengthStat_{(p,i)}^k \leftarrow 0$ 
21:   return  $kLCS, ktLCS, msktLCS, mcktLCS$ 

```

Longest Approximate Prefix. For given strings s_1 and s_2 , a distance metric $\delta = \{L, E\}$, and an integer k , compute table $P_{(s_1, s_2)}^{\delta, k}$ such that $P_{(s_1, s_2)}^{\delta, k}[a, b, a']$ is the maximum $b' \geq a' - 1$, where $d_\delta(s_1[a, b], s_2[a', b']) \leq k$, or -1 if no such b' exists.

Lemma 4. ([15]) For two strings s_1 and s_2 , each of length ℓ , $P_{(s_1, s_2)}^{\{L, E\}, k}$ (for Levenshtein and edit distances) can be computed in $\mathcal{O}(k\ell^3)$ time.

Lemma 5. Computing the $P_{(s_i, s_j)}^{\{L, E\}, k}$ table for all i and j values, $1 \leq i, j \leq m$, takes $\mathcal{O}(k\ell N^2)$ time.

Proof. There are $\mathcal{O}(m^2)$ string pairs and by Lemma 4, $P_{(s_i, s_j)}^{\{L, E\}, k}$ can be computed in $\mathcal{O}(k\ell^3)$ for each string pair (i, j) . The time complexity of $P_{(s_i, s_j)}^{\{L, E\}, k}$ for all i and j values is $\mathcal{O}(m^2 \cdot k\ell^3) = \mathcal{O}(k\ell N^2)$. \square

For Levenshtein and edit distances, we fill $lengthStat_{(p,i)}^k$ auxiliary tables using $P_{(s_i, s_j)}^{\delta, k}$ tables for each suffix of any string in set \mathbf{S} , similar to Hamming distance.

$$lengthStat_{(p,i)}^k[l, j] = \begin{cases} 1, & \text{if } \exists q : P_{(s_i, s_j)}^{\{L, E\}, k}[p, p + l - 1, q] \neq -1 \\ 0, & \text{otherwise} \end{cases}$$

where $1 \leq p \leq |s_i|, 1 \leq l \leq |s_i| - p + 1$ and $1 \leq i, j \leq m$ (1)

Analogous to Lemma 3, Theorem 3, and Algorithms 1 and 2, we have the following results.

Lemma 6. *Given $P_{(s_i, s_j)}^{\delta, k}$, $\delta = \{L, E\}$ for all (s_i, s_j) pairs, $1 \leq i, j \leq m$, the `lengthStat` table can be computed in $\mathcal{O}(N)$ -time for each suffix of a string in \mathbf{S} .*

Theorem 4. *The restricted ALCS problems under Levenshtein and edit distances for $\mathbf{S} = \{s_1, s_2, \dots, s_m\}$ can be computed in $\mathcal{O}(k\ell N^2)$ time.*

6 Polylog Time Solution for Restricted ALCS

Thankachan *et al.* describe a $\mathcal{O}(\ell \log^k \ell)$ -time and $\mathcal{O}(\ell)$ -space solution for ALCS of two strings, each of length ℓ , under Hamming [21] and edit distance [20]. Their method uses k -errata trie data structure proposed by Cole *et al.* in [7]. Let $LCP_{(s_i, s_j)}^{E, k}[i', j']$ be the length of the longest common prefix between the suffixes $s_i[i'..|s_i|]$ and $s_j[j'..|s_j|]$, with at most k edit operations. $MaxLCP_{(s_i, s_j)}^{H, k}[i']$ ($MaxLCP_{(s_i, s_j)}^{E, k}[i']$) is an array of size $|s_i|$, where each element i' contains the maximum value of $LCP_{(s_i, s_j)}^{H, k}[i', j']$ ($LCP_{(s_i, s_j)}^{E, k}[i', j']$) for all $1 \leq j' \leq |s_j|$.

Theorem 5. ([21], [20]) *Let s_i and s_j be strings of length ℓ . $MaxLCP_{(s_i, s_j)}^{H, k}[i']$ and $MaxLCP_{(s_i, s_j)}^{E, k}[i']$ arrays can be computed in $\mathcal{O}(\ell \log^k \ell)$ overall time using $\mathcal{O}(\ell)$ space for **all** values of i' .*

Theorem 6. *For any $\delta = \{H, L, E\}$, Rk -LCS problem can be computed by solving $T = \max_{1 \leq i \leq m} \max_{1 \leq i' \leq |s_i|} \min_{1 \leq j \leq m} MaxLCP_{(s_i, s_j)}^{\delta, k}[i']$.*

Proof. For a string s_i and its suffix $s_i[i'..|s_i|]$, $\min_{1 \leq j \leq m} MaxLCP_{(s_i, s_j)}^{\delta, k}[i']$ is the length of the longest prefix of $s_i[i'..|s_i|]$ that occurs in all $\mathbf{S} - \{s_i\}$ strings with at most k errors. $T = \max_{1 \leq i \leq m} \max_{1 \leq i' \leq |s_i|} \min_{1 \leq j \leq m} MaxLCP_{(s_i, s_j)}^{\delta, k}[i']$ is the length of a Rk -LCS of set \mathbf{S} . To compute an answer to this problem, we need to find a (i, i') pair that maximizes T . Argument pair (i, i') maximizing T corresponds to i' -th suffix of the string s_i , which constitutes an answer to the Rk -LCS of \mathbf{S} ; such that substring $s_i[i'..T - i' + 1]$ is a Rk -LCS. We prove the correctness of this solution by contradiction. Assume that pair (i, i') is not a Rk -LCS and there exists a pair (v, v') which is an answer to this problem. Therefore, T value for (v, v') is larger than its value for (i, i') ; however, pair (v, v') has not been captured by T . This is in contradiction with maximizing T . \square

Theorem 7. *The Rk -LCS problem for $\mathbf{S} = \{s_1, s_2, \dots, s_m\}$ can be computed in $\mathcal{O}(mN \log^k \ell)$ time with $\mathcal{O}(N)$ additional space, for any $\delta = \{H, L, E\}$.*

Proof. The time complexity for computing $MaxLCP_{(s_i, s_j)}^{\delta, k}[i']$ for all i', i , and j values (string pairs) is $\mathcal{O}(m^2 \ell \log^k \ell) = \mathcal{O}(mN \log^k \ell)$. This is achieved by calculating $MaxLCP_{(s_i, s_j)}^{\delta, k}[i']$ for $\mathcal{O}(m^2)$ string pairs. Finding argument pair (i, i') of

T takes $\mathcal{O}(m^2\ell) = \mathcal{O}(mN)$ time, which is less than the time complexity of computing $MaxLCP_{(s_i, s_j)}^{\delta, k}[i']$ for all i', i , and j values. Thus, the overall time complexity of the Rk -LCS problem under any distance metric in δ is $\mathcal{O}(mN \log^k \ell)$. For a given string s_i , $MaxLCP_{(s_i, s_j)}^{\delta, k}[i']$ must be computed for all $1 \leq j \leq m$, $j \neq i$. This requires $\mathcal{O}(m\ell) = \mathcal{O}(N)$ space. Since this space can be reused for other values of i , the overall space complexity remains $\mathcal{O}(N)$. \square

Corollary 1. *The $\mathcal{O}(mN \log^k \ell)$ -time solution of the Rk -LCS problem outperforms*

1. *The $\mathcal{O}(N^2)$ -time solution for Hamming distance when $k < \frac{\log \ell}{\log \log \ell}$.*
2. *The $\mathcal{O}(k\ell N^2)$ -time solution for Levenshtein and edit distance when $k < \frac{\log k + 2 \log \ell}{\log \log \ell}$.*

Acknowledgments. The authors wish to thank Dr. Brian Golding for suggesting this research topic and guiding us during the problem formulation. The second and third authors were funded by the Natural Sciences & Engineering Research Council of Canada [Grant Numbers RGPIN-2024-06915 and RGPIN-2024-05921, respectively].

References

1. Abboud, A., Williams, R., Yu, H.: More applications of the polynomial method to algorithm design. In: Proceedings of the Annual ACM-SIAM Symposium on Discrete Algorithms. vol. 2015-January (2015). <https://doi.org/10.1137/1.9781611973730.17>
2. Arnold, M., Ohlebusch, E.: Linear time algorithms for generalizations of the longest common substring problem. *Algorithmica* (New York) **60**(4) (2011). <https://doi.org/10.1007/s00453-009-9369-1>
3. Babenko, M.A., Starikovskaya, T.A.: Computing the longest common substring with one mismatch. *Problems of Information Transmission* **47**(1) (2011). <https://doi.org/10.1134/S0032946011010030>
4. Caskurlu, B., Mkrtchyan, V., Parekh, O., Subramani, K.: On partial vertex cover and budgeted maximum coverage problems in bipartite graphs. In: IFIP International Conference on Theoretical Computer Science. pp. 13–26. Springer (2014)
5. Charalampopoulos, P., Crochemore, M., Iliopoulos, C.S., Kociumaka, T., Pissis, S.P., Radoszewski, J., Rytter, W., Waleń, T.: Linear-time algorithm for long LCF with κ mismatches. In: Leibniz International Proceedings in Informatics, LIPIcs. vol. 105 (2018). <https://doi.org/10.4230/LIPIcs.CPM.2018.23>
6. Charalampopoulos, P., Kociumaka, T., Pissis, S.P., Radoszewski, J.: Faster algorithms for longest common substring. In: Leibniz International Proceedings in Informatics, LIPIcs. vol. 204 (2021). <https://doi.org/10.4230/LIPIcs.ESA.2021.30>
7. Cole, R., Gottlieb, L.A., Lewenstein, M.: Dictionary matching and indexing with errors and don't cares. In: Conference Proceedings of the Annual ACM Symposium on Theory of Computing (2004). <https://doi.org/10.1145/1007352.1007374>
8. Farach, M.: Optimal suffix tree construction with large alphabets. In: Annual Symposium on Foundations of Computer Science - Proceedings (1997). <https://doi.org/10.1109/sfcs.1997.646102>

9. Flouri, T., Giaquinta, E., Kobert, K., Ukkonen, E.: Longest common substrings with k mismatches. *Information Processing Letters* **115**(6-8) (2015). <https://doi.org/10.1016/j.ipl.2015.03.006>
10. Gandhi, R., Khuller, S., Srinivasan, A.: Approximation algorithms for partial covering problems. *Journal of Algorithms* **53**(1), 55–84 (2004)
11. Grabowski, S.: A note on the longest common substring with k -mismatches problem. *Information Processing Letters* **115**(6-8) (2015). <https://doi.org/10.1016/j.ipl.2015.03.003>
12. Halperin, E., Srinivasan, A.: Improved approximation algorithms for the partial vertex cover problem. In: *International Workshop on Approximation Algorithms for Combinatorial Optimization*. pp. 161–174. Springer (2002)
13. Impagliazzo, R., Paturi, R.: On the complexity of k -SAT. In: *Journal of Computer and System Sciences*. vol. 62 (2001). <https://doi.org/10.1006/jcss.2000.1727>
14. Impagliazzo, R., Paturi, R., Zane, F.: Which problems have strongly exponential complexity? *Journal of Computer and System Sciences* **63**(4) (2001). <https://doi.org/10.1006/jcss.2001.1774>
15. Kędzierski, A., Radoszewski, J.: k -Approximate Quasiperiodicity Under Hamming and Edit Distance. *Algorithmica* **84**(3) (2022). <https://doi.org/10.1007/s00453-021-00842-7>
16. Kociumaka, T., Radoszewski, J., Starikovskaya, T.: Longest Common Substring with Approximately k Mismatches. *Algorithmica* **81**(6) (2019). <https://doi.org/10.1007/s00453-019-00548-x>
17. Lee, I., Pinzon, Y.: A simple algorithm for finding exact common repeats. *IEICE Transactions on Information and Systems* **E90-D**(12) (2007). <https://doi.org/10.1093/ietisy/e90-d.12.2096>
18. Leimeister, C.A., Morgenstern, B.: Kmacs: The k -mismatch average common substring approach to alignment-free sequence comparison. *Bioinformatics* **30**(14) (2014). <https://doi.org/10.1093/bioinformatics/btu331>
19. Smith, A.D.: Common approximate substrings. Ph.D. thesis, University of New Brunswick, Faculty of Computer Science (2004)
20. Thankachan, S.V., Aluru, C., Chockalingam, S.P., Aluru, S.: Algorithmic framework for approximate matching under bounded edits with applications to sequence analysis. In: *Research in Computational Molecular Biology: 22nd Annual International Conference, RECOMB 2018, Paris, France, April 21-24, 2018, Proceedings* 22. pp. 211–224. Springer (2018)
21. Thankachan, S.V., Apostolico, A., Aluru, S.: A provably efficient algorithm for the k -mismatch average common substring problem. *Journal of Computational Biology* **23**(6) (2016). <https://doi.org/10.1089/cmb.2015.0235>
22. Weiner, P.: Linear pattern matching algorithms. In: *14th Annual Symposium on Switching and Automata Theory* (1973). <https://doi.org/10.1109/SWAT.1973.4569722>

Appendix

Table 1. $LCP_{(s_1, s_2)}^{H,2}$ table for $s_1 = GTACAAT$ and $s_2 = CTTGTA$. For example, $LCP_{(s_1, s_2)}^{H,2}[2, 3] = 4$ is the length of the longest common prefix of suffixes $s_1[2..|s_1|] = TACAAT$ and $s_2[3..|s_2|] = TGT A$ up to 2 mismatches.

	C	T	T	G	T	A
G	3	3	2	3	2	1
T	2	3	4	2	2	1
A	2	2	2	3	2	1
C	3	2	2	3	2	1
A	3	2	3	2	2	1
A	2	2	2	2	2	1
T	1	1	1	1	1	1

Table 2. The $lengthStat_{(3,1)}^1$ table for $S = \{TTGAC, CGAAAT, TGGTA\}$, where $k = 1$. The $lengthStat_{(3,1)}^1[3, 2] = 1$ indicates the 1-approximate occurrence of the length-3 prefix of $s_1[3..5]$ (GAC), somewhere in s_2 ($s_2[2..4] = GAA$).

	1 (s_1)	2 (s_2)	3 (s_3)	4 (Frequency)
1	1	1	1	3
2	1	1	1	3
3	1	1	0	2