Are the Hidden States Hiding Something? Testing the Limits of Factuality-Encoding Capabilities in LLMs *

Giovanni Servedio^{1,2} Alessandro De Bellis¹ Dario Di Palma¹ Vito Walter Anelli¹ Tommaso Di Noia¹

¹Politecnico di Bari, Italy ²Sapienza University of Rome, Italy name.surname@poliba.it

Abstract

Factual hallucinations are a major challenge for Large Language Models (LLMs). They undermine reliability and user trust by generating inaccurate or fabricated content. Recent studies suggest that when generating false statements, the internal states of LLMs encode information about truthfulness. However, these studies often rely on synthetic datasets that lack realism, which limits generalization when evaluating the factual accuracy of text generated by the model itself. In this paper, we challenge the findings of previous work by investigating truthfulness encoding capabilities, leading to the generation of a more realistic and challenging dataset. Specifically, we extend previous work by introducing: (1) a strategy for sampling plausible true-false factoid sentences from tabular data and (2) a procedure for generating realistic, LLM-dependent truefalse datasets from Question Answering collections. Our analysis of two open-source LLMs reveals that while the findings from previous studies are partially validated, generalization to LLM-generated datasets remains challenging. This study lays the groundwork for future research on factuality in LLMs and offers practical guidelines for more effective evaluation. Code is provided at our Github Repo.

1 Introduction

In the last few years, Large Language Models (LLMs) have shown outstanding abilities in natural language processing tasks and beyond (Biancofiore et al., 2025; Di Palma, 2023). Nevertheless,

This work is licensed under a Creative Commons Attribution 4.0 International License (CC BY 4.0).

Please cite the official published version when available.

factual hallucinations (Zhang et al., 2023) represent a significant obstacle, limiting their reliability and hindering their safe deployment in real-world applications (Di Palma et al., 2025) such as healthcare (Pham and Vo, 2024), education (Upadhyay et al., 2023), legal advice (Dahl et al., 2024), and language understanding (De Bellis et al., 2024; Anelli et al., 2022). Hallucinations occur when an LLM generates content that is syntactically coherent but factually inaccurate, decreasing trust in AI systems (Huang et al., 2024). Recent research suggests that LLMs may encode internal representations of factuality in their hidden states, indicating an awareness of whether a generated statement is true or false (Chen et al., 2024). These efforts led to the development of approaches to evaluate the factual accuracy of the LLM outputs given their internal representations (factuality "self-evaluation"). Self-evaluation can be used to identify gaps in the knowledge of an LLM, improving truthfulness and transparency through abstention mechanisms (Feng et al., 2024), fact verification (Wadden et al., 2020), and self-correction (Ji et al., 2023). Azaria and Mitchell (2023) suggest that LLMs have "some internal notion as to whether a sentence is true or false, as this information is required for generating (or predicting) following tokens." Based on this assumption, they propose a neural classifier to discern factual from non-factual statements based on hidden layer activations. However, the datasets used to evaluate the probe present limitations since they contain trivially incorrect statements (e.g., "The zebra uses flying for locomotion") that easily fail to align with the generative patterns of LLMs. Additionally, the false statements are generated using random substitutions of the true terms with little regard for the plausibility of negative samples. This misalignment not only weakens the generalizability of results but also raises concerns about the applicability of these models to real-world scenarios where false statements may be subtle or nuanced.

^{*}This is the authors' version of the work. The final, published version will appear in the *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (ACL '25)*.

This study addresses these gaps by generating more plausible datasets (see Figure 1) to explore LLM factuality encoding and evaluating refined models. The primary contributions are:

- 1. We **reproduce** the methodology of Azaria and Mitchell (2023) to ensure transparency.
- 2. We propose two strategies to generate realistic datasets and discuss how well the original and newly developed models generalize.

Specifically, we extend their work with two novel dataset creation strategies and design a strategy that better fits the factuality self-evaluation task, introducing:

- A perplexity-based negative sampling strategy that enhances the original generation mechanism and leverages the LLM token distribution.
- A novel strategy to sample realistic LLMgenerated facts, leveraging Question Answering datasets to elicit responses from the LLM.

Through this analysis, we lay the groundwork for more robust factuality assessments and offer practical guidelines for enhancing the reliability of LLMs in diverse applications.

2 Reproduction of Prior Work: Settings

In their study, Azaria and Mitchell (2023) investigate whether LLMs internally represent the factuality of sentences. This section summarizes the dataset generation approach they employed and the specific probing architecture used in their study.

2.1 Dataset Generation Strategy

To explore whether LLMs internally represent the factuality of statements, the authors constructed a 'True-False' dataset of facts labeled as either True or False, covering six disjoint topics: Cities, Inventions, Chemical Elements, Animals, Companies, and Scientific Facts. To generate the dataset, for the first five topics, i.e. with the exception of Scientific Facts, the authors selected true statements from reliable sources (see Table 7 in the appendix) and produced false statements, replacing part of a true statement (e.g. "Hydrogen has an atomic number of 1") with randomly sampled incorrect information ("Hydrogen has an atomic number of 34"). Meanwhile, for Scientific Facts, they employed ChatGPT (13 Feb 2023) as a generator of true and false sentences, and two human annotators manually verified their correctness. The authors publicly release the dataset, which we refer to as the "True-False dataset". Furthermore, the authors

constructed a second dataset using the OPT-6.7b model, which we refer to as the 'OPT-Generated Dataset'. To create this dataset, the model was prompted with a true statement absent from the True-False dataset and then used to generate a subsequent sentence. The responses were manually fact-checked and annotated by three independent human judges. Non-factual responses were filtered out, resulting in a final set of 245 statements.

2.2 Internal States Analysis via SAPLMA

To investigate whether LLMs internally represent the factuality of statements, Azaria and Mitchell (2023) developed a probe (Statement Accuracy Prediction based on Language Model Activations) that predicts the factual accuracy of a statement by analyzing the hidden layer activations of an LLM. SAPLMA is a feedforward neural network designed to classify statements as true or false. It consists of three hidden layers (256, 128, 64) and a sigmoid output activation. The model is trained using the Adam optimizer for five epochs without hyperparameter tuning. The authors studied two LLMs, namely OPT-6.7b (Zhang et al., 2022) and Llama 2-7b (Touvron et al., 2023), both consisting of 32 layers. To identify which layers best capture factuality, they trained five SAPLMA models, forwarding each statement in the True-False Dataset as input to the LLMs and extracting the corresponding activation values from the 32nd (last layer), 28th, 24th, 20th, and 16th layers. These activations serve as input for training the classifiers. To ensure generalizability, i.e., making SAPLMA independent of specific topics, the authors adopted a cross-validation strategy using a leave-one-topicout approach to train the classifier on five topics and test the probe on the held-out topic.

2.3 Reproducibility Settings

In this section, we provide details on the datasets and experimental settings for reproducing the work of Azaria and Mitchell (2023). Our goal is to answer the Research Question (**RQ0**): Can we reproduce the results reported by Azaria and Mitchell (2023)?" Although the code is not publicly accessible, the authors made it available upon request.

Dataset generation. The code provided by Azaria and Mitchell (2023) contains all the necessary material to recreate the entire dataset generation process. However, their template-matching code is influenced by randomness in the generation of false statements, and a random seed is not set.

Due to this non-deterministic behavior, recreating their dataset using the original code was unfeasible. However, the authors released their dataset, allowing us to reproduce their exact dataset settings.

SAPLMA reproducibility. To reproduce the results of the original study, we trained 20 SAPLMA probes for each of the following layers: the 32nd, 28th, 24th, 20th, and 16th, over 5 epochs, resulting in a total of 100 probes. We employed Llama 2-7b and OPT-6.7b, both using half-precision (16-bit float) parameters, with a default temperature of 0.8 for Llama 2-7b and 1.0 for OPT-6.7b. The hardware used for the experiments was an Intel(R) Core(TM) i7-5820K paired with an NVIDIA RTX 3090 graphics card. The authors do not specify from which token they extract the associated hidden state. However, code inspection led to the identification of the last token as the target state.

3 Experimental Reproducibility Results

To answer **RQ0**, we report the results for the reproduction of the experiments in Tables 1, 2 and 3. The results labeled with 'Orig.' are retrieved from the original work, while the ones achieved in the reproducibility study are labeled with 'Repr.'.

3.1 Reproduction of SAPLMA Results on the True-False Dataset

Table 1 reports SAPLMA's performance on the True-False dataset across different layers of Llama 2-7b and OPT-6.7b for six categories: Cities, Inventions, Elements, Animals, Companies, and Facts. Results indicate that Llama 2-7b consistently outperforms OPT-6.7b across all layers and categories. Middle layers (16, 20, 24) achieve the highest performance, while accuracy declines toward the final layer. The reproduced results closely align with the original findings, with minor deviations observed across specific categories and layers. Moreover, although OPT-6.7b shows greater variability, the ranking of layers remains consistent with the original work. Both experiments confirm that factuality information is more effectively encoded in the middle layers (16-24) than in the final layer. Additionally, we reproduce the baseline used by the authors to compare SAPLMA. Specifically, their baseline includes a trained SAPLMA on BERT activations, a few-shot approach where the LLM is prompted with a sentence and asked to label it as 'True' or 'False,' and an 'It-is-true' test. In this test, the LLMs were asked: Is it true that X? and

Is it false that X?, where X is a dataset sample. A response was considered correct if the model assigned a higher probability to the 'True' token. Table 2 summarizes the baseline performance. BERT achieves the highest average performance among non-prompted methods, demonstrating its effectiveness in factual classification, and the results indicate high reproducibility. The It-is-true baseline yields the highest average performance, particularly in the 'Companies' topic. The results demonstrate consistent reproducibility.

In general, the reproduction on the True-False Dataset is considered successful based on the following observations: (i) the overall performance trends remain consistent, with Llama 2-7b outperforming OPT-6.7b; (ii) observed deviations are minor and do not indicate fundamental inconsistencies; (iii) the relative ranking of layers remains unchanged, reinforcing previous findings; and (iv) baseline methods retain their rankings, confirming the validity of the original results.

3.2 Reproduction of the Results on the OPT-Generated Dataset

Table 3 presents the results of the reproduced experiments on the OPT-Generated Dataset. Performance is evaluated using Accuracy, AUC, Accuracy with an Optimal Threshold (selected by estimating it from a held-out validation set), and the Average Optimal Threshold. The final layers, specifically the 28th and final layers, outperform the middle and lower layers in terms of Accuracy and AUC. The reproduced results closely align with the original findings, exhibiting only minor variations. Accuracy with anoptimal threshold consistently exceeds raw accuracy, suggesting that tuning the decision boundary improves performance.

Regarding baselines, BERT exhibits lower accuracy compared to the LLMs' last layers, with slight improvements over the original results. Notably, the 3- and 5-shot prompting results were identical between the original and reproduced experiments.

RQ0: Can we reproduce the results reported by Azaria and Mitchell (2023)?

This reproducibility study demonstrates a high degree of alignment with the original results, confirming the validity of previous findings. It shows that the ranking and trends remain unchanged, reinforcing the robustness of the results.

Ls	iver	Cities		Inventions		Elements		Animals		Companies		Facts		Average	
,		Llama2	OPT-6.7b	Llama2	OPT-6.7b	Llama2	OPT-6.7b	Llama2	OPT-6.7b	Llama2	OPT-6.7b	Llama2	OPT-6.7b	Llama2	OPT-6.7b
Last	Orig. Repr.	0.7574 0.7939	0.7796 0.7836	0.6735 0.7470	0.5696 0.5603	0.6814 0.7057	0.5760 0.5656	0.7338 0.7133	0.6022 0.5984	0.6736 0.6463	0.6925 0.6900	0.7444 0.7894	0.6498 0.6640	0.7107 0.7326	0.6449 0.6437
28	Orig. Repr.	0.8146 0.8261	0.7732 0.8014	0.7207 0.7221	0.5761 0.5938	0.6767 0.6746	0.5907 0.5931	0.7249 0.7046	0.5777 0.5945	0.6894 0.6860	0.7247 0.7252	0.7662 0.7976	0.6618 0.6639	0.7321 0.7351	0.6507 0.6620
24	Orig. Repr.	0.8722 0.8619	0.7963 0.8043	0.7816 0.7737	0.6712 0.6604	0.6849 0.6789	0.6211 0.6172	0.7394 0.7415	0.5800 0.6095	0.7094 0.7049	0.7758 0.7844	0.7858 0.7910	0.6868 0.6804	0.7622 0.7586	0.6886 0.6927
20	Orig. Repr.	0.8820 0.8672	0.8125 0.8118	0.8459 0.8584	0.7268 0.7222	0.6950 0.6761	0.6197 0.6218	0.7758 0.7736	0.6058 0.6208	0.8319 0.8254	0.8122 0.8160	0.8053 0.8065	0.6819 0.6734	0.8060 0.8012	0.7098 0.7110
16	Orig. Repr.	0.9223 0.9174	0.7435 0.7554	0.8938 0.8847	0.6400 0.6403	0.6939 0.7005	0.5645 0.5732	0.7774 0.7883	0.5800 0.5693	0.8658 0.8672	0.7570 0.7760	0.8254 0.8104	0.6237 0.6340	0.8298 0.8281	0.6515 0.6580

Table 1: Replicated SAPLMA performance on the True-False dataset across the selected layers. The results labeled as 'Orig.' are taken from the original work, while those labeled as 'Repr.' are the replicated results from this study.

Mod	el	Cities	Inventions	Elements	Animals	Companies	Facts	Average	
BERT	Orig.	0.5357	0.5537	0.5645	0.5228	0.5533	0.5302	0.5434	
	Repr.	0.5257	0.5611	0.5435	0.5603	0.5302	0.5361	0.5428	
3-shot	Orig.	0.5410	0.4799	0.5685	0.5650	0.5538	0.5164	0.5374	
	Repr.	0.5416	0.4800	0.5685	0.5652	0.5539	0.5115	0.5368	
5-shot	Orig.	0.5416	0.4799	0.5676	0.5643	0.5540	0.5148	0.5370	
	Repr.	0.5416	0.4800	0.5676	0.5643	0.5540	0.5082	0.5359	
It-is-true	Orig.	0.5230	0.5068	0.5688	0.4851	0.6883	0.5840	0.5593	
	Repr.	0.5233	0.5046	0.5688	0.4831	0.6875	0.5856	0.5588	

Table 2: Replicated baselines performance on the True-False dataset. The results labeled as 'Orig.' are taken from the original work, while those labeled as 'Repr.' are the replicated results from this study.

Layer		Accuracy	AUC	Accuracy with Optimal Threshold	Average Threshold
Last-layer	Orig.	0.6187	0.7587	0.7052	0.8687
Lust-myer	Repr.	0.6406	0.7720	0.7264	0.8910
28th-layer	Orig.	0.6362	0.7614	0.7134	0.8838
20tii-iayei	Repr.	0.6410	0.7686	0.7203	0.8276
24th-layer	Orig.	0.6134	0.7435	0.6988	0.8801
24tii-iayer	Repr.	0.6206	0.7496	0.6973	0.8500
20th Janean	Orig.	0.6029	0.7182	0.6587	0.9063
20th-layer	Repr.	0.5965	0.7183	0.6669	0.8868
Middle-laver	Orig.	0.5566	0.6610	0.6500	0.8123
Middle-layer	Repr.	0.5579	0.6760	0.6468	0.7948
BERT	Orig.	0.5115	0.5989	0.5705	0.9403
DEKI	Repr.	0.5522	0.6092	0.5689	0.7939
2 -1 -4	Orig.	0.5041	0.4845	=	-
3-shot	Repr.	0.5041	0.4845	=	=
5 ab 4	Orig.	0.5125	0.4822	=	-
5-shot	Repr.	0.5125	0.4822	=	=

Table 3: Reproduced SAPLMA performance on the **OPT-Generated Dataset** (Section 2.1). The results labeled as 'Orig.' are taken from the original work, while those labeled as 'Repr.' are the reproduced results.

4 Novel Dataset Generation Strategies for Factuality Self-Evaluation

This section introduces two novel dataset generation strategies to investigate LLM factuality self-evaluation. To contextualize our approach, we first examine the limitations of the True-False dataset by Azaria and Mitchell (2023). While it provides a structured framework for evaluating LLMs, its construction imposes constraints that may limit generalizability of the findings. Specifically, true and false statements are derived from tabular data using

predefined templates. We argue that this approch suffers from several limitations:

- Adherence to predefined templates: The use of fixed templates limits the linguistic expressiveness of the dataset, potentially constraining the probe classifier's ability to generalize beyond rigidly structured statements (e.g., <company> operates in the industry of <industry>).
- Distribution misalignment: The statements are constructed from tabular data rather than generated by the LLM itself. As a result, the dataset may not align with the LLM's generative distribution. For instance, a niche true fact in the dataset –but unknown by the model– could have high perplexity for the LLM, undermining the study's core premise: evaluating an LLM's intrinsic ability to "judge" its false claims.
- Lack of consideration for the LLM's knowledge state: LLMs exhibit uneven factual knowledge based on their pretraining data, with strengths in some domains and gaps in others. A model can assess a statement factuality only if it has prior exposure to it. The dataset does not account for these inconsistencies: it evaluates whether an LLM can detect factual errors without considering whether the model actually possesses knowledge of the fact.
- Differences in cardinality: Some properties in the dataset have fewer admissible values, making certain facts easier to evaluate. For example, a statement like "<element> appears in its standard state as _" has fewer possible values (i.e.,{Solid, Liquid, Gas}) compared to statements like "<city> is a city in _" that involve a broader set. This imbalance in complexity may bias the evaluation process.

These limitations impact the interpretability of results when evaluating an LLM's internal representations of factuality. To ensure a more realistic as-

sessment of an LLM's self-evaluation of factuality, we propose two strategies to address these issues. The first strategy samples statements from tabular data to better align with the LLM's generative predictions. The second strategy involves sampling LLM-generated facts as answers to questions from a well-known Question Answering dataset.

4.1 Perplexity-based Dataset Construction

This section presents a novel dataset generation strategy to address limitations in the Azaria and Mitchell (2023) True-False dataset, particularly distribution misalignment and implausible negative samples. To improve negative sampling based on random property-object substitutions, we introduce a **perplexity-guided probabilistic sampling** method, which re-weights false statements based on perplexity for better alignment with LLM output distributions. Since perplexity depends on the model, the same LLM under evaluation must generate false statements to ensure consistency, resulting in a model-dependent dataset tailored to the characteristics and biases of the LLM being studied.

True statements are initially constructed, as in Azaria and Mitchell (2023), by directly inserting correct entity-property pairs into pre-defined sentence templates. Regarding the false statements generation, we proceed as follows: (i) for each true statement, all unique alternative property values are gathered from the entire dataset; (ii) a candidate sentence is created for each alternative property by inserting it into the corresponding template; (iii) the target LLM (i.e., OPT-6.7b or Llama 2-7b) computes the perplexity of each candidate sentence. This perplexity score serves as a plausibility metric, with lower perplexity indicating a more plausible (yet incorrect) statement.

Given a true statement, we define C as the set of potential candidate sentences, which includes the true statement. Furthermore, $C' \subset C$ is defined as the subset of candidate false sentences (i.e. excluding the true statement). Candidates $c \in C$ are ranked based on their perplexity scores, with lower scores indicating higher plausibility.

Since perplexity can be interpreted as a measure of plausibility, we operate under the assumption that an LLM possesses factual knowledge about a fact if the fact is assigned a "sufficiently low perplexity". Conversely, a high perplexity score for the true statement suggests that the LLM lacks knowledge of the fact. Given the limitations discussed earlier, we aim to evaluate the LLM ability

to discern between true and false statements when it possesses the relevant knowledge. Therefore, we exclude instances where the LLM exhibits limited knowledge about the true statement: if the true statement does not rank among the lowest k perplexity candidates, the generation process for that instance is aborted, and the next true fact is considered. In practice, we define k as $k=\alpha|C|$, where α is a hyperparameter ($0<\alpha<1$). This accounts for the varying cardinality of the property ranges in the dataset, ensuring that the threshold for "sufficiently low perplexity" is adjusted based on the number of possible values for a given property.

In addition, we want to simulate a real hallucination scenario where the LLM is uncertain between the true fact and plausible alternatives: given the perplexity score function $PP(\cdot)$, all false candidates c with a perplexity score $PP(c) < (1+\beta)PP(true)$, where $0 < \beta < 1$ is a hyperparameter, are considered, resulting in a reduced set of candidates C^{\star} . A min-max normalization is applied to their perplexity,

$$NormPP(c) = \frac{PP(c) - \min_{c \in C} PP(c)}{\max_{c \in C} PP(c) - \min_{c \in C} PP(c)},$$
(1)

The normalized perplexities are transformed using a plausibility score function $s(\cdot)$, i.e., lower perplexity scores result in higher plausibility scores. The scores are then normalized to ensure that they sum to 1 and are treated as a probability distribution over the candidates:

$$s(c) = e^{-\text{NormPP}(c)}, \quad P(c_i) = \frac{s(c_i)}{\sum_{c_j \in C^*} s(c_j)}.$$
(2)

The normalization guarantees that $P(c_i)$ values are suitable for sampling. Finally, a mixture of top-k and nucleus sampling (Holtzman et al., 2020) is employed to sample the candidate for insertion into the template. This process generates a coherent yet factually incorrect statement that is more realistic and closely aligned with the LLM internal token prediction patterns.

4.2 LLM-Generated Dataset Construction

The strategy in Section 4.1 constructs a balanced true-false dataset from tabular data but has inherent limitations. While enabling direct comparison with Azaria and Mitchell (2023), it restricts generative models to rigid templates, limiting expressiveness. Additionally, its reliance on fixed candidate sets can lead to easily classifiable false

statements when the set is small. Finally, templatebased sampling reduces diversity, likely due to token bias: we found LMs consistently assigning lower perplexity to certain property-object pairs, regardless of the subject. To more realistically assess an LLM factuality self-evaluation, we propose generating both true and false statements directly from the model, overcoming the limitations of template-based approaches. This involves (a) a method to elicit diverse factoid statements from the LLM, and (b) a strategy to annotate statement veracity, addressing biases and inconsistencies in the process. Consider a Question Answering dataset composed of N questions, $D_{QA} = \{(q_i, a_i)\}_{i=1}^N$, where each question q_i has a corresponding groundtruth answer a_i . Given a LLM \mathcal{M} , we prompt it with each question K times, yielding a set of generated answers. This results in an extended dataset $D_{QA}^{\mathcal{M}} = \{(q_i, a_i, \{a_{i,k}^{\mathcal{M}}\}_{k=1}^K)\}_{i=1}^N$. LLM-generated answers in $D_{QA}^{\mathcal{M}}$ can be annotated using an oracle LLM, which we assume is able to evaluate the veracity of each answer $a_{i,k}^{\mathcal{M}}$ given the ground-truth answer a_i and the question q_i . This operation results in an annotated dataset

$$\hat{D}_{QA}^{\mathcal{M}} = \{ (q_i, a_i, \{a_{i,k}^{\mathcal{M}}, v_{i,k}^{\mathcal{M}}\}_{k=1}^K) \}_{i=1}^N, \quad (3)$$

where $v_{i,k}$ is a veracity label assigned by the oracle, indicating whether the generated answer $\hat{a}_{i,k}$ is correct $(v_{i,k}=1)$ or incorrect $(v_{i,k}=0)$.

Increasing K enhances the reliability of responses by offering a more accurate evaluation of the LLM knowledge state regarding a question. This evaluation can lead to three possible outcomes: (i) a high proportion of correct answers suggests the LLM fully understands the facts; (ii) an high proportion of incorrect answers indicates the LLM lacks or has partial knowledge, preventing correct responses; (iii) a mix of correct and incorrect answers implies knowledge with a tendency toward hallucination. This study assumes that an LLM can only encode factuality regarding a generated fact if it has some knowledge about it. Therefore, we focus exclusively on the third scenario. This scenario also naturally provides balance, including true and false variations of the same fact. We define the correct answer ratio $p_i^{\mathcal{M}} = \frac{1}{K} \sum_{k=1}^K v_{i,k}^{\mathcal{M}}.$ We consider questions whose p_i is around 0.5 with a tolerance hyperparameter τ , that is $|p_i^{\mathcal{M}} - 0.5| < \tau$. The dataset is obtained by selecting the answers and their veracity labels satisfying the condition:

$$D_{Facts}^{\mathcal{M}} = \{ (a_{i,k}^{\mathcal{M}}, v_{i,k}^{\mathcal{M}}) : |p_i^{\mathcal{M}} - 0.5| < \tau \}_{i=1}^{N}.$$
 (4)

5 Experiments and Discussion

This section describes the experimental setup used to extend the prior investigation, presents the results, and discusses their implications. We address the following Research Questions:

RQ1 Are probing classifiers trained as in Azaria and Mitchell (2023) capable of generalizing to True-False sentences with similar perplexity?

RQ2 Can the same probes generalize to facts generated by LLMs?

5.1 Dataset Generation Setup

To generate the datasets for training the probe and alleviate the limitations of Azaria and Mitchell (2023), we employ the perplexity-based sampling procedure described in Section 4.1. Specifically, we set the needed hyperparameters as follows: $\alpha=0.1,\,\beta=0.1,\,k=10$ and p=0.9 We do not sample a dataset for the *Scientific Facts* topic, as the original version was generated by ChatGPT and not from tabular data (additional details in Appendix B). Table 4 summarizes the statistics for the two refined True-False datasets, while Figure 1 shows the differences in average perplexity between the original and the proposed datasets.

Dataset	Llama	a 2-7b	OPT-6.7b			
Dutuset	Sentences	(%) True	Sentences	(%) True		
Cities	674	50	756	50		
Inventions	336	50	202	50		
Elements	118	50	220	50		
Animals	116	50	114	50		
Companies	326	50	310	50		

Table 4: Novel generation of our True-False dataset, following the approach described in Section 4.1, including number of sentences and percentage of true samples.




Figure 1: Comparison of average perplexity scores for Llama 2-7b and OPT-6.7b for the Original dataset by Azaria and Mitchell (2023) and our refined version. Lower perplexity indicates that the sentences are more likely to have been generated by the model. PP(T/F) denotes average perplexity of true/false sentences.

We construct an LLM-generated dataset following the procedure described in Section 4.2. Our experiments use TriviaQA (Joshi et al., 2017), a dataset of question-answer pairs collected from 14 trivia and quiz-league websites. Given the limited computational resources, we limit our focus to the validation split of TriviaQA Wikipedia questions. For each LLM in our analysis, we set K=10 and $\tau=0.1$, and we refuse the answers composed of less than 5 tokens to improve self-consistency. For annotation, we use **GPT-40 mini** with a 3-shot learning strategy, where three examples are provided. More details are included in Appendix C.1, and Table 8 reports the dataset statistics.

5.2 Impact of Perplexity-Based Sampling on SAPLMA Accuracy

We assess the impact of our perplexity-based sampling strategy by training the SAPLMA probe classifier separately on the original True-False dataset from Azaria and Mitchell (2023) and our refined version. As shown in Table 5, classifiers tested on our refined dataset achieve the highest accuracy in deeper layers. For Llama 2-7b, Layer 16 shows the most consistent results, achieving the highest average accuracy across all tested configurations when trained on our dataset. Although accuracy fluctuates across different topics, overall performance remains largely consistent between the training configurations. Comparing the results with the original results in Table 1, it emerges that classifiers trained on the original dataset achieve higher accuracy when tested on the same dataset. This is particularly evident in the 'Animals' topic. However, it is important to consider that the perplexity values in our refined dataset are significantly lower than those in the original dataset for both true and false statements (see 1). Additionally, our refined dataset features lower and more closely aligned perplexity scores between true and false statements, with false statements often yielding even lower perplexity values than true ones. This finding implies the validity of Azaria and Mitchell hypothesis, which states that factuality information is encoded in LLM hidden states, although it might not be immediately evident from the model predicted probabilities.

RQ1: Are probing classifiers trained as in Azaria and Mitchell (2023) capable of generalizing to True-False sentences with similar perplexity?

Surprisingly, the results between the probes trained on our refined dataset and the probes trained

on the original dataset are mostly comparable. This proves that the probes can generalize even when the train-test datasets have different perplexity.

5.3 Generalization of SAPLMA on LLM-generated Sentences

We extend our experiments with the SAPLMA classifier to a new setting, where both training and evaluation are conducted on sentences generated by an LLM and sourced from TriviaQA, leveraging the procedure described in Section 4.2. Table 6 reports the performance of SAPLMA on a set of factual statements extracted from TriviaQA. The results indicate that the currently used probes are inadequate for factuality self-assessment in real-world scenarios, as the observed accuracy does not reach a noteworthy threshold. Furthermore, following the suggestion of Azaria and Mitchell, we optimize the classification threshold; however, this adjustment yields no significant improvement in performance. For completeness, the interested reader may find the result obtained on the same dataset when training on the original True-False dataset of Azaria and Mitchell in Appendix D.

RQ2: Can the same probes generalize to facts generated by LLMs?

In summary, this experiment partially contradicts the findings of Azaria and Mitchell (2023): the trained probes are not capable of providing good generalization to an LLM-generated dataset, even when the accuracy threshold is tuned. The motivation could stem from the nature of the dataset, as TriviaQA contains open-domain questions that result in more nuanced facts than the ones in the original True-False dataset (Section 2) or the OPT-generated dataset (Section 3.2).

We believe that further research is needed to enhance the effectiveness of factuality self-assessment techniques, particularly in settings involving LLM-generated content. Promising research directions may be leveraging datasets that are closely aligned with the distribution of LLM-generated text and exploring alternative techniques such as uncertainty-aware classification.

6 Related Work

Probing techniques have become central for the layer-wise interpretation of deep learning models (Alain, 2016). This approach was then extended to Large Language Models (LLMs) to assess LLMs ability to encode syntax and seman-

Layer	Training	Cities		Inventions		Elem	ents	Anin	nals	Comp	anies	Average	
Lujer	Data	Llama 2-7b	OPT-6.7b	Llama 2-7b	OPT-6.7b	Llama 2-7b	OPT-6.7b	Llama 2-7b	OPT-6.7b	Llama 2-7b	OPT-6.7b	Llama 2-7b	OPT-6.7b
last	Orig. Novel	0.6882 0.6365	0.5724 0.6143	0.6409 0.6101	0.5094 0.5144	0.6314 0.5623	0.5482 0.5293	0.5685 0.5461	0.5259 0.4846	0.6290 0.7414	0.6984 0.7211	0.6316 0.6311	0.5709 0.5720
28	Orig. Novel	0.7056 0.5091	0.5870 0.6057	0.7001 0.6591	0.5178 0.5473	0.6161 0.5665	0.5832 0.5655	0.6013 0.6052	0.5566 0.4662	0.7079 0.7061	0.7234 0.7065	0.6662 0.6092	0.5936 0.5811
24	Orig. Novel	0.8286 0.6025	0.7026 0.6710	0.7250 0.6609	0.6022 0.6248	0.6432 0.5763	0.5918 0.5993	0.6310 0.5836	0.5439 0.4868	0.7121 0.7868	0.7366 0.7366	0.7080 0.6420	0.6354 0.6225
20	Orig. Novel	0.8272 0.7382	0.7313 0.7528	0.7741 0.6973	0.6230 0.6131	0.6492 0.6051	0.6255 0.5986	0.5832 0.6190	0.5075 0.4807	0.7583 0.8270	0.7502 0.7566	0.7184 0.6973	0.6475 0.6404
16	Orig. Novel	0.8941 0.9301	0.6433 0.7505	0.7888 0.7961	0.5698 0.5644	0.6801 0.6623	0.5930 0.5568	0.5836 0.6319	0.3816 0.5307	0.7768 0.8265	0.7426 0.7231	0.7447 0.7694	0.5860 0.6151

Table 5: Accuracy values obtained training SAPLMA on the original True-False dataset and on our refined version, then **tested on our refined version**. Results are shown for the Llama 2-7b and OPT-6.7b models. 'Orig.' denotes the 'original True-False dataset as training data, while 'Novel' denotes our version of the True-False dataset as training data. In **bold** we denote the best combination of layer/training dataset for each combination of model/topic.

Dataset	Dataset		,	Thre	shold	= 0.5	5	O	ptima	al Th	resho	ld
Def	Dataset		last	28	24	20	16	last	28	24	20	16
CPT .544 .558 .591 .551 .537 .530 .558 .547 .530 .499	hilltuenhull	Llama	.561	.576	.618	.621	.628	.547	.581	.618	.634	.639
derby* OPT .553 .564 .584 .587 .572 .562 .566 .583 .586 .580 quiz4free Llama .564 .547 .523 .561 .589 .548 .523 .521 .547 .573 quizguy Llama .578 .585 .588 .607 .635 .576 .587 .601 .595 .637 triviabug Llama .494 .518 .521 .525 .538 .508 .500 .530 .532 .559 .558 .558 .588 .507 .533 .560 .559 .555 .564 .543 .544 .530 .533 .546 .541 triviabug Llama .494 .518 .521 .525 .538 .508 .500 .530 .542 .543 businessball Llama .566 .528 .555 .574 .582 .585 .574 .582 .558 .55	DIIITUTIDUII	OPT	.547	.558	.591	.551	.537	.530	.558	.547	.530	.499
quiz4free Llama .564 .547 .523 .561 .589 .548 .523 .521 .577 quizguy Llama .564 .547 .523 .561 .589 .548 .523 .521 .5773 OPT .559 .559 .575 .581 .600 .544 .530 .533 .546 .541 triviabug Llama .579 .583 .589 .590 .584 .559 .555 .565 .559 .548 businessballs Llama .696 .558 .565 .574 .582 .583 .560 .559 .555 .565 .559 .558 .559 .553 .560 .522 .553 .555 .560 .573 .553 .545 .547 .573 .562 .551 .566 .573 .583 .580 .543 .580 .550 .554 .601 .602 .613 .544 .541 .541 .541 <td>dorby*</td> <td>Llama</td> <td>.568</td> <td>.581</td> <td>.575</td> <td>.596</td> <td>.617</td> <td>.560</td> <td>.565</td> <td>.559</td> <td>.571</td> <td>.597</td>	dorby*	Llama	.568	.581	.575	.596	.617	.560	.565	.559	.571	.597
quiz/free OPT .559 .559 .575 .581 .560 .544 .530 .533 .546 .541 quizguy Llama .578 .585 .588 .607 .635 .576 .587 .601 .595 .637 triviabug Llama .494 .518 .521 .525 .538 .508 .500 .530 .542 .545 businessballs Llama .566 .558 .565 .574 .582 .558 .551 .555 .554 .575 jetpunk Llama .566 .558 .565 .574 .582 .551 .555 .554 .575 jetpunk Llama .587 .578 .578 .570 .553 .545 .577 .556 .573 .550 .554 .601 quiz Llama .551 .536 .546 .562 .573 .530 .550 .551 .566 .571 .569<	derby	OPT	.553	.564	.584	.587	.572	.562	.566	.583	.586	.580
Quizguy Llama 578 585 588 607 635 576 587 601 595 637 triviabug Llama 494 518 521 525 538 589 590 584 559 555 565 559 548 triviabug Llama 494 518 521 525 538 508 500 530 542 545 businessballs Llama 566 558 565 574 582 558 551 555 564 575 jetpunk Llama 566 558 567 570 582 553 545 547 573 560 551 jetpunk Llama 587 627 620 643 654 543 580 550 554 651 560 551 560 551 560 551 560 551 560 561 601 602 561 560	aniz/fron	Llama	.564	.547	.523	.561	.589	.548	.523	.521	.547	.573
quizguy OPT .579 .583 .589 .590 .584 .559 .555 .565 .559 .548 triviabug Llama .494 .518 .521 .525 .538 .508 .500 .530 .542 .545 businessballs Llama .566 .588 .565 .574 .582 .585 .551 .555 .564 .575 jetpunk Llama .587 .627 .620 .643 .654 .543 .580 .550 .554 .601 odquiz Llama .557 .627 .620 .643 .654 .543 .580 .550 .554 .601 oppt .606 .612 .614 .596 .621 .618 .618 .621 .605 .519 .560 .501 .601 .601 .601 .601 .601 .601 .601 .601 .601 .601 .601 .601 .601 .601	quiz-ii ee	OPT	.559	.559	.575	.581	.560	.544	.530	.533	.546	.541
triviabug Llama .494 .518 .521 .525 .538 .508 .500 .530 .542 .545 OPT .620 .624 .607 .596 .528 .632 .635 .605 .598 .553 businessballs Llama .566 .558 .565 .574 .582 .558 .51 .555 .564 .575 OPT .559 .558 .578 .570 .553 .545 .547 .573 .562 .551 jetpunk OPT .606 .612 .614 .596 .621 .618 .618 .621 .605 .619 OPT .560 .573 .583 .583 .583 .542 .551 .555 .564 .575 OPT .560 .573 .583 .583 .542 .551 .566 .571 .569 .521 Llama .556 .557 .558 .565 .61 .541 .541 .549 .555 .569 .615 OPT .560 .573 .582 .592 .552 .537 .550 .535 .580 .588 Quiz-zone Quiz-zone Quiz-zone Quiz-zone Quiz-sone Quiz-sone Llama .603 .575 .572 .578 .571 .602 .561 .570 .559 .615 OPT .558 .565 .574 .571 .540 .550 .549 .564 .564 .539 Quiz-wise Llama .560 .565 .579 .609 .618 .563 .551 .574 .605 .619 OPT .586 .563 .565 .577 .540 .555 .556 .552 .575 .537 sfquiz CPT .586 .563 .565 .577 .540 .555 .556 .552 .575 .537 sfquiz Llama .560 .563 .565 .577 .540 .555 .556 .552 .575 .537 sfquiz Llama .560 .563 .565 .577 .540 .555 .556 .552 .575 .537 sfquiz Ulama .560 .563 .565 .579 .609 .618 .563 .551 .574 .605 .619 OPT .584 .591 .589 .590 .547 .570 .582 .577 .573 .536 triviacountry OPT .584 .591 .589 .590 .547 .570 .582 .577 .573 .536 triviacountry OPT .536 .551 .550 .587 .584 .554 .559 .556 .566 .566 .564 .549 OPT .584 .591 .589 .590 .547 .570 .582 .577 .573 .536 OPT .584 .591 .589 .590 .547 .570 .582 .577 .573 .536 OPT .584 .591 .589 .590 .547 .570 .582 .577 .573 .536 OPT .584 .591 .589 .590 .547 .570 .582 .577 .573 .536 OPT .584 .591 .589 .590 .547 .570 .582 .577 .573 .536	anizany	Llama	.578	.585	.588	.607	.635	.576	.587	.601	.595	.637
triviabug OPT .620 .624 .607 .596 .528 .632 .635 .605 .598 .553 businessballs COPT .559 .558 .565 .574 .582 .558 .551 .555 .564 .575 jetpunk Llama .587 .627 .620 .643 .654 .543 .580 .550 .554 .601 OPT .606 .612 .614 .596 .621 .618 .618 .621 .605 .619 OPT .560 .573 .583 .583 .542 .551 .555 .569 .615 OPT .560 .573 .582 .592 .552 .551 .555 .569 .615 OPT .559 .570 .582 .592 .552 .531 .555 .569 .615 OPT .550 .570 .582 .592 .552 .537 .550 .535 .580 .598 quizballs OPT .550 .576 .587 .578 .571 .602 .561 .561 .570 .553 OPT .558 .565 .574 .571 .540 .550 .549 .564 .564 .539 quizwise Llama .560 .565 .579 .609 .618 .563 .551 .574 .605 .619 OPT .584 .591 .589 .590 .547 .570 .582 .592 .552 .537 .550 .535 .580 squizwise Llama .560 .565 .579 .609 .618 .563 .551 .574 .605 .619 OPT .584 .591 .589 .590 .547 .570 .582 .572 .573 .536 triviacountry CLama .536 .554 .559 .559 .575 .564 .554 .559 .566 .583 OPT .584 .591 .589 .590 .547 .570 .582 .577 .573 .536 triviacountry COPT .584 .591 .589 .590 .547 .570 .582 .577 .573 .536 Mrexham** Llama .570 .563 .569 .558 .554 .554 .555 .555 .556 .552 .574 .579 .571 Average Llama .562 .564 .568 .579 .594 .555 .550 .558 .567 .587	quizguy	OPT	.579	.583	.589	.590	.584	.559	.555	.565	.559	.548
businessballs Llama .566 .558 .565 .574 .582 .558 .551 .555 .564 .575	triviahua	Llama										
Description Description Description	uiviabug	OPT	.620	.624	.607	.596	.528	.632	.635	.605	.598	.553
OPT .559 .558 .570 .553 .545 .547 .573 .562 .551 Jetpunk	husinoscholls	Llama	.566	.558	.565	.574	.582	.558	.551	.555	.564	.575
odquiz OPT .606 .612 .614 .596 .621 .618 .621 .605 .619 odquiz Llama .551 .536 .546 .562 .573 .537 .525 .532 .550 .550 .560 quiz-zone Llama .556 .573 .583 .583 .542 .551 .566 .571 .569 .521 quiz-zone Llama .569 .570 .582 .592 .552 .537 .550 .530 .580 .508 quizballs Llama .603 .575 .572 .578 .571 .602 .561 .561 .570 .553 oPT .558 .565 .574 .571 .502 .561 .561 .570 .553 oPT .560 .563 .565 .577 .571 .502 .551 .556 .551 .574 .605 .619 .564 .564 .544 <	businessbans	OPT	.559	.558	.578	.570	.553	.545	.547	.573	.562	.551
odquiz Llama .551 .566 .573 .583 .542 .551 .566 .571 .569 .521 quiz-zone Llama .556 .573 .583 .542 .551 .566 .571 .569 .512 quiz-zone Llama .556 .577 .582 .592 .552 .553 .555 .569 .618 quizballs Llama .603 .575 .572 .578 .571 .602 .561 .570 .553 OPT .558 .565 .574 .571 .540 .550 .561 .561 .570 .583 quizwise Llama .603 .575 .572 .571 .540 .550 .549 .564 .539 sfquiz DPT .560 .565 .579 .609 .618 .563 .551 .574 .605 .619 priviacountry Llama .568 .554 .559 .575 </td <td>iotnunk</td> <td>Llama</td> <td>.587</td> <td>.627</td> <td>.620</td> <td>.643</td> <td>.654</td> <td>.543</td> <td>.580</td> <td>.550</td> <td>.554</td> <td>.601</td>	iotnunk	Llama	.587	.627	.620	.643	.654	.543	.580	.550	.554	.601
odquiz OPT .560 .573 .583 .583 .582 .551 .566 .571 .569 .521 quiz-zone Llama .556 .557 .558 .565 .611 .541 .549 .555 .569 .615 quizballs Llama .603 .575 .572 .578 .571 .602 .561 .561 .570 .553 quizwise Llama .560 .565 .574 .571 .540 .550 .549 .564 .564 .539 squizwise Llama .560 .565 .577 .509 .618 .563 .551 .574 .605 .619 OPT .560 .563 .565 .577 .540 .555 .552 .551 .574 .605 .619 opn .560 .563 .565 .577 .540 .555 .555 .556 .552 .577 .537 squizwise	jetpunk	OPT	.606	.612	.614	.596	.621	.618	.618	.621	.605	.619
quiz-zone Llama .556 .57 .58 .658 .611 .541 .549 .555 .569 .615 quizballs Llama .603 .575 .572 .578 .571 .602 .561 .570 .558 quizballs Llama .603 .575 .572 .578 .571 .602 .561 .570 .558 QPT .558 .565 .574 .571 .540 .550 .549 .564 .539 stquiz Llama .560 .565 .579 .609 .618 .563 .551 .574 .605 .619 oPT .560 .563 .565 .577 .540 .555 .556 .552 .575 .537 stquiz Llama .568 .554 .559 .575 .564 .554 .559 .575 .564 .559 .566 .583 triviacountry OPT .536 .551	odaniz	Llama	.551	.536	.546	.562	.573	.537	.525	.532	.550	.560
quiz-zone OPT .569 .570 .582 .592 .552 .537 .550 .535 .580 .508 quizballs Llama .603 .575 .572 .578 .571 .602 .561 .561 .570 .553 oPT .558 .565 .574 .571 .540 .550 .564 .569 .519 oPT .560 .563 .565 .577 .540 .555 .556 .552 .575 .537 sfquiz Llama .568 .554 .559 .575 .564 .554 .559 .575 .564 .559 .566 .583 triviacountry Llama .536 .551 .559 .556 .566 .506 .530 .536 .524 .549 oPT .536 .551 .559 .587 .534 .449 .476 .472 .511 .472 wrexham** Llama .570	ouquiz											
quizballs Llama 603 570 582 592 552 537 550 535 580 508 quizwise Llama 560 565 577 571 540 550 564 564 539 sfquiz Llama 560 565 579 609 618 563 551 574 605 619 sfquiz Llama 560 563 555 577 540 555 556 552 575 537 triviacountry Llama 536 554 559 556 566 563 577 573 536 weexham** Llama 536 551 559 556 566 506 530 531 570 581 549 570 574 573 573 536 triviacountry Llama 570 561 551 550 587 534 449 476 472 511 472<	aniz-zone	Llama	.556	.557	.558	.565	.611	.541	.549	.555	.569	.615
quizballs OPT .558 .565 .574 .571 .540 .550 .564 .564 .563 .59 quizwise Llama .560 .565 .579 .609 .618 .563 .551 .574 .605 .619 sfquiz Llama .560 .563 .565 .577 .540 .555 .556 .552 .575 .537 triviacountry .584 .591 .589 .590 .547 .570 .582 .577 .573 .536 triviacountry OPT .536 .551 .550 .587 .534 .449 .476 .472 .511 .472 wrexham** Llama .570 .563 .569 .553 .565 .567 .48 .561 .545 .579 Average Llama .562 .568 .579 .584 .554 .559 .550 .554 .552 .550 .555 .556 .5	quiz-zone	OPT	.569	.570	.582	.592	.552	.537	.550	.535	.580	.508
Quizwise OPT .588 .565 .574 .571 .540 .550 .564 .565 .576 .560 .661 .560 .618 .63 .551 .574 .605 .619 OPT .560 .563 .565 .577 .540 .555 .556 .552 .575 .537 sfquiz Llama .568 .554 .559 .575 .564 .554 .559 .566 .560 .550 .577 .573 .366 Lima .536 .554 .559 .556 .566 .506 .530 .536 .524 .536 OPT .536 .551 .559 .556 .566 .506 .530 .536 .524 .549 OPT .536 .551 .559 .556 .566 .506 .503 .536 .524 .549 Wrexham** Llama .570 .569 .553 .565<	anizhalle	Llama	.603	.575	.572	.578	.571	.602	.561	.561	.570	.553
quizwise OPT .560 .563 .565 .577 .540 .555 .556 .552 .575 .537 sfquiz Llama .568 .554 .554 .559 .575 .564 .554 .559 .566 .583 triviacountry Llama .536 .554 .559 .556 .566 .506 .530 .534 .549 wrexham** Llama .570 .563 .569 .553 .565 .567 .548 .561 .556 Average Llama .562 .564 .568 .579 .594 .552 .550 .557 .587	quizbans	OPT	.558	.565	.574	.571	.540	.550	.549	.564	.564	.539
GPT	anizwica	Llama	.560	.565	.579	.609	.618	.563	.551	.574	.605	.619
sfquiz OPT .584 .591 .589 .590 .547 .570 .582 .577 .573 .536 triviacountry Llama .536 .554 .559 .556 .566 .506 .530 .530 .542 .549 wrexham** Llama .570 .563 .569 .553 .565 .566 .506 .503 .530 .531 .449 OPT .548 .570 .569 .553 .565 .567 .548 .561 .545 .566 Average Llama .570 .563 .569 .553 .565 .567 .548 .571 .575 .584 .554 .535 .552 .574 .579 .571 Average Llama .562 .564 .568 .579 .594 .552 .550 .558 .567 .587	quizwise	OPT	.560	.563	.565	.577	.540	.555	.556	.552	.575	.537
triviacountry Lama 536 554 559 590 547 570 536 524 549 wrexham** Llama 570 563 569 553 565 567 548 561 551 571 wrexham** Llama 570 563 569 553 565 567 548 561 545 566 578 552 574 579 571 Average Llama 562 564 568 579 594 552 550 558 567 587	efaniz	Llama	.568	.554	.554	.559	.575	.564	.554	.559	.566	.583
triviacountry OPT .536 .551 .550 .587 .534 .449 .476 .472 .511 .472 wrexham** Llama .570 .563 .569 .553 .565 .567 .548 .561 .545 .566 OPT .548 .573 .578 .584 .554 .552 .574 .579 .571 Average Llama .562 .564 .568 .579 .594 .552 .550 .558 .567 .587 OPT .567 .575 .583 .583 .555 .553 .560 .562 .567 .587	siquiz	OPT	.584	.591	.589	.590	.547	.570	.582	.577	.573	.536
OPT .536 .551 .550 .587 .534 .449 .476 .472 .511 .472 wrexham** Llama .570 .563 .569 .553 .565 .567 .548 .561 .545 .566 OPT .548 .573 .578 .584 .554 .535 .552 .574 .579 .571 Average Llama .562 .564 .568 .579 .594 .552 .550 .558 .567 .587 OPT .567 .575 .583 .583 .555 .553 .560 .562 .567 .587	triviacountry	Llama	.536	.554	.559	.556	.566	.506	.530	.536	.524	.549
wrexham*** OPT .548 .573 .578 .584 .554 .535 .552 .574 .579 .571 Average Llama .562 .564 .568 .579 .594 .552 .550 .558 .567 .587 OPT .567 .575 .583 .583 .555 .553 .560 .562 .567 .587	ti iviacounti y											
Average CPT .548 .5/3 .5/8 .584 .554 .535 .552 .5/4 .5/9 .5/1 Llama .562 .564 .568 .579 .594 .552 .550 .558 .567 .587 OPT .567 .575 .583 .583 .555 .553 .560 .562 .567 .587	wrovhom**							l				
Average OPT .567 .575 .583 .583 .555 .553 .560 .562 .567 .587	witchiam											
OP1 .567 .575 .583 .585 .555 .560 .562 .567 .587	Average											
	Average	OPT	.567	.575	.583	.583	.555	.553	.560	.562	.567	.587

^{*:} derby is adopted as abbreviation of derbyshirepubquizleague **: wrexham is adopted as abbreviation of wrexhamquizleague

Table 6: Performance of SAPLMA on a fact dataset generated from TriviaQA. The original topic-wise leave-one-out strategy is adopted. Results are shown for the Llama 2-7b and OPT-6.7b models.

tics (Conneau et al., 2018; Tenney et al., 2019). Specifically, among the different applications, a technique that emerges is **self-evaluation**, defined as *a model's ability to assess the accuracy of its own outputs* (Kadavath et al., 2022). Among the various works, notable research by Kadavath et al. (2022) explored estimating a well-calibrated P(True) directly from output probabilities to reflect answer accuracy. Orgad et al. (2024) explore error detection and hallucination mitigation in Ques-

tion Answering by probing the internal representations of question-answer pairs. Their study shows that while LLMs encode factuality signals, these signals do not generalize well across task-specific datasets, suggesting that factuality encoding is taskdependent rather than universal. While, Chen et al. (2024) introduce the INSIDE framework, which detects hallucinations using the EigenScore metric to measure self-consistency across multiple LLM outputs for a single input. Similarly, Zhang et al. (2024) leverage a probe model, PINOSE, trained via offline consistency-checking, to perform online hallucination detection. Although INSIDE and PINOSE primarily focus on self-consistency in internal representations across multiple generated responses, they do not interpret hidden states or look for a veracity encoding.

7 Conclusion and Future Work

In this paper, we investigate the factuality-encoding capabilities of LLMs. Our work replicates the methodology of Azaria and Mitchell (2023) to ensure reproducibility and extend their approach with two novel dataset construction strategies: perplexity-based negative sampling and fact generation based on QA datasets. We applied these strategies to analyze two open-source LLMs, and found that although the findings from previous studies are partially validated even on more challenging synthetic datasets, transferring these findings to LLM-generated datasets proves difficult. This study paves the way for more reliable LLM evaluations and offers practical guidelines for improving model transparency and trustworthiness in realworld applications.

Limitations

There are a few aspects of our study that could be explored further. We made every effort to check the datasets for inconsistencies, but a more thorough manual verification by human annotators would be beneficial for ensuring their robustness and minimizing potential biases. Additionally, our analysis is based on a limited set of models. While these models provide valuable insights, it is possible that larger or more complex models could demonstrate enhanced performance, particularly in the context of self-evaluation. Future work could expand on this by incorporating a wider range of models to investigate whether scalability can lead to improved results.

Ethical Statement

A major concern when working with LLMs is their tendency to generate factually inaccurate information. When training probe classifiers to assess factual accuracy, biases and beliefs from the LLM may transfer to the probe, potentially reinforcing cultural, demographic, or ideological biases in factuality self-evaluation. However, with careful design, probing techniques can be adapted not only to minimize bias but also to actively mitigate its consequences.

References

- Guillaume Alain. 2016. Understanding intermediate layers using linear classifier probes. *arXiv preprint arXiv:1610.01644*.
- Vito Walter Anelli, Giovanni Maria Biancofiore, Alessandro De Bellis, Tommaso Di Noia, and Eugenio Di Sciascio. 2022. Interpretability of BERT latent space through knowledge graphs. In *Proceedings of the 31st ACM International Conference on Information & Knowledge Management, Atlanta, GA, USA, October 17-21, 2022*, pages 3806–3810. ACM.
- Amos Azaria and Tom M. Mitchell. 2023. The internal state of an LLM knows when it's lying. In *EMNLP* (*Findings*), pages 967–976. Association for Computational Linguistics.
- Giovanni Maria Biancofiore, Dario Di Palma, Claudio Pomo, Fedelucio Narducci, and Tommaso Di Noia. 2025. Conversational user interfaces and agents. In *Human-Centered AI: An Illustrated Scientific Quest*, pages 399–438. Springer.
- Chao Chen, Kai Liu, Ze Chen, Yi Gu, Yue Wu, Mingyuan Tao, Zhihang Fu, and Jieping Ye. 2024. Inside: Llms' internal states retain the power of hallucination detection. *arXiv preprint arXiv:2402.03744*.

- Alexis Conneau, German Kruszewski, Guillaume Lample, Loïc Barrault, and Marco Baroni. 2018. What you can cram into a single vector: Probing sentence embeddings for linguistic properties. *arXiv preprint arXiv:1805.01070*.
- Matthew Dahl, Varun Magesh, Mirac Suzgun, and Daniel E. Ho. 2024. Large legal fictions: Profiling legal hallucinations in large language models. *CoRR*, abs/2401.01301.
- Alessandro De Bellis, Vito Walter Anelli, Tommaso Di Noia, and Eugenio Di Sciascio. 2024. PRONTO: prompt-based detection of semantic containment patterns in mlms. In *ISWC* (2), volume 15232 of *Lecture Notes in Computer Science*, pages 227–246. Springer.
- Dario Di Palma. 2023. Retrieval-augmented recommender system: Enhancing recommender systems with large language models. In *RecSys*, pages 1369–1373. ACM.
- Dario Di Palma, Felice Antonio Merra, Maurizio Sfilio, Vito Walter Anelli, Fedelucio Narducci, and Tommaso Di Noia. 2025. Do llms memorize recommendation datasets? a preliminary study on movielens-1m. In *Proceedings of the 48th International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR 2025, Padua, Italy July 13-18, 2025.* ACM.
- Shangbin Feng, Weijia Shi, Yike Wang, Wenxuan Ding, Vidhisha Balachandran, and Yulia Tsvetkov. 2024. Don't hallucinate, abstain: Identifying LLM knowledge gaps via multi-LLM collaboration. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 14664–14690, Bangkok, Thailand. Association for Computational Linguistics.
- Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. 2020. The curious case of neural text degeneration. In 8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020. OpenReview.net.
- Lei Huang, Weijiang Yu, Weitao Ma, Weihong Zhong, Zhangyin Feng, Haotian Wang, Qianglong Chen, Weihua Peng, Xiaocheng Feng, Bing Qin, and Ting Liu. 2024. A survey on hallucination in large language models: Principles, taxonomy, challenges, and open questions. *ACM Trans. Inf. Syst.*
- Ziwei Ji, Tiezheng Yu, Yan Xu, Nayeon Lee, Etsuko Ishii, and Pascale Fung. 2023. Towards mitigating LLM hallucination via self reflection. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 1827–1843, Singapore. Association for Computational Linguistics.
- Mandar Joshi, Eunsol Choi, Daniel S. Weld, and Luke Zettlemoyer. 2017. Triviaqa: A large scale distantly supervised challenge dataset for reading comprehension. In *ACL* (1), pages 1601–1611. Association for Computational Linguistics.

Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, Scott Johnston, Sheer El Showk, Andy Jones, Nelson Elhage, Tristan Hume, Anna Chen, Yuntao Bai, Sam Bowman, Stanislav Fort, Deep Ganguli, Danny Hernandez, Josh Jacobson, Jackson Kernion, Shauna Kravec, Liane Lovitt, Kamal Ndousse, Catherine Olsson, Sam Ringer, Dario Amodei, Tom Brown, Jack Clark, Nicholas Joseph, Ben Mann, Sam McCandlish, Chris Olah, and Jared Kaplan. 2022. Language models (mostly) know what they know. *CoRR*, abs/2207.05221.

Hadas Orgad, Michael Toker, Zorik Gekhman, Roi Reichart, Idan Szpektor, Hadas Kotek, and Yonatan Belinkov. 2024. Llms know more than they show: On the intrinsic representation of LLM hallucinations. *CoRR*, abs/2410.02707.

Duy Khoa Pham and Bao Quoc Vo. 2024. Towards reliable medical question answering: Techniques and challenges in mitigating hallucinations in language models. *CoRR*, abs/2408.13808.

Ian Tenney, Patrick Xia, Berlin Chen, Alex Wang, Adam Poliak, R Thomas McCoy, Najoung Kim, Benjamin Van Durme, Samuel R Bowman, Dipanjan Das, et al. 2019. What do you learn from context? probing for sentence structure in contextualized word representations. arXiv preprint arXiv:1905.06316.

Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, and Yasmine Babaei et al. 2023. Llama 2: Open foundation and fine-tuned chat models. *CoRR*, abs/2307.09288.

Shriyash Upadhyay, Etan Ginsberg, and Chris Callison-Burch. 2023. Improving mathematics tutoring with A code scratchpad. In *BEA@ACL*, pages 20–28. Association for Computational Linguistics.

David Wadden, Shanchuan Lin, Kyle Lo, Lucy Lu Wang, Madeleine van Zuylen, Arman Cohan, and Hannaneh Hajishirzi. 2020. Fact or fiction: Verifying scientific claims. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7534–7550, Online. Association for Computational Linguistics.

Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, et al. 2022. Opt: Open pre-trained transformer language models. *arXiv preprint arXiv:2205.01068*.

Xiaokang Zhang, Zijun Yao, Jing Zhang, Kaifeng Yun, Jifan Yu, Juanzi Li, and Jie Tang. 2024. Transferable and efficient non-factual content detection via probe training with offline consistency checking. *arXiv* preprint arXiv:2404.06742.

Yue Zhang, Yafu Li, Leyang Cui, Deng Cai, Lemao Liu, Tingchen Fu, Xinting Huang, Enbo Zhao, Yu Zhang, Yulong Chen, et al. 2023. Siren's song in the ai ocean: a survey on hallucination in large language models. arXiv preprint arXiv:2309.01219.

A Dataset Statistics

A.1 True-False Dataset (Azaria and Mitchell, 2023) Statistics

Table 7 provides a summary of the number of sentences and the distribution of true and false statements across each topic in the original True-False dataset (Azaria and Mitchell, 2023) on which we base our replication experiments.

Dataset	Sentences	Source	(%) True
Cities	1458	SimpleMaps dataset	50
Inventions	876	Wikipedia's list of inventors	53
Chemical Elements	930	PubChem's periodic table	50
Animals	1008	National Geographic Kids	50
Companies	1200	Forbes Global 2000 List 2022: The Top 200	50
Scientific Facts	612	ChatGPT and human annotators	50

Table 7: True-False dataset categories, original sources, and label splits from (Azaria and Mitchell, 2023).

A.2 LLM-Generated Trivia Facts Dataset

Table 8 illustrates the number of annotates facts extracted from TriviaQA (Joshi et al., 2017) employing the procedure described in section 4.2. Statistics are presented for each of the 14 question sources.

Dataset	Llama	a 2-7b	OPT-6.7b				
	Sentences	(%) True	Sentences	(%) True			
triviacountry	118	49.15%	118	49.15%			
wwwodquiz	700	49.71%	525	49.71%			
triviabug	97	50.52%	88	51.14%			
derby*	342	50.00%	325	50.00%			
quiz-zone	187	48.13%	239	50.63%			
businessballs	433	50.84%	443	49.43%			
wrexham**	216	50.00%	276	50.72%			
sfquiz	1054	49.80%	1085	50.39%			
quizwise	565	49.91%	704	50.42%			
billturnbull	216	49.54%	105	50.48%			
jetpunk	139	51.80%	364	50.27%			
quizballs	500	49.60%	488	50.82%			
quizguy	240	51.67%	341	50.74%			
quiz4free	171	49.12%	141	48.94%			

Table 8: Summary of the dataset obtained by extracting factoid sentences from TriviaQA (Joshi et al., 2017) Wikipedia validation split, following the procedure described in Section 4.2.

B Perplexity-Based Refinement of the True-False Dataset (Azaria and Mitchell, 2023)

We base our dataset generation strategy described in Section 4 on the same tabular data employed by Azaria and Mitchell, which was made available upon request. The properties used for sampling are analogous to the ones employed by the original authors in their dataset generation. However, for the *Cities* topic, we restrict the analysis to facts like "*<city>* is city in *<country>*." Differently from the original authors, we avoid generating facts such as "*<city>* is the name of a city/country" having only two possible values, potentially resulting in too many easy-to-classify samples.

C LLM-Generated Dataset Extraction Details

C.1 Factoid Answer Generation

Below is an example prompt used in the text generation pipeline for TriviaQA (Joshi et al., 2017). The 10 examples are sampled from the train Wikipedia split. The answers for the examples are manually crafted by looking at the available ground truth.

Question: Where in England was Dame Judi Dench born?

Answer: The English actress Dame Judi Dench was born in York, England.

Question: From which country did Angola achieve independence in 1975?

Answer: Angola achieved independence

Answer: Angola achieved independence from Portugal in 1975.

Question: Which city does David Soul come from?

Answer: David Soul hails from Chicago, Illinois.

Question: Who won Super Bowl XX?

Answer: The Chicago Bears won Super Bowl

XX.

Question: Which was the first European country to abolish capital punishment?

Answer: Norway was the first European country to abolish capital punishment.

Question: In which country did the widespread use of ISDN begin in 1988?

Answer: The widespread use of ISDN began in Japan in 1988.

Question: What is Bruce Willis' real
 first name?

Answer: Bruce Willis' real first name is Walter.

Question: Which William wrote the novel Lord of the Flies?

Answer: The William who wrote Lord of the Flies was William Golding.

Question: How is Joan Molinsky better known?

Answer: Joan Molinsky is better known as Joan Rivers.

Question: In which branch of the arts is Patricia Neary famous? Answer: Patricia Neary is famous in the field of ballet.

To generate responses, the model is provided with a continuation prompt such as:

Question: Ford Prefect came from a star in which constellation? Answer:

The model then generates a response, adhering to the pattern set by the previous examples. Responses are filtered based on length and uniqueness to ensure meaningful and high-quality outputs.

The generation process uses the following hyperparameters for all the employed models (i.e. Llama 2-7b and OPT-6.7b):

• max_new_tokens: 128

• top_k: 50

• top_p: 0.95

• temperature: 1.0

• num_return_sequences: 10

C.2 Factoid Answer Annotation

Below is an example prompt to **GPT-40 mini** (2024-08-01), the LLM that we use as the oracle for the procedure described in Section 4.2. In this setup, we employ a 3-shot learning strategy, where the model is provided with three examples to establish a clear pattern of judgment. These examples demonstrate the task of evaluating answers against a given ground truth. The model is then tasked with using this context to evaluate a new answer to a question, based on the same criteria. In our experiments, we employ a temperature setting of 1.

SYSTEM:

You are a judge and your role is to judge whether the provided answer is correct for the given question, based on the provided ground truth. Answer with a 1 if the answer is correct and 0 if the answer is incorrect.

Here are a few examples:

USER:

Question: Who was the next British Prime Minister after Arthur Balfour? Answer: Arthur Balfour was followed by David Lloyd George.

```
Bannerman', 'Campbell Bannerman'
     Sir Henry Campbell Bannerman', '
    Henry Campbell Bannerman', 'Henry
     Campbell-Bannerman'],
    normalized_aliases': ['henry
    campbell bannerman', 'sir henry campbell bannerman', 'campbell
     bannerman'],
    matched_wiki_entity_name': '', '
    normalized_matched_wiki_entity_name
     ': '', 'normalized_value': 'campbell
     bannerman', 'type': '
    WikipediaEntity', 'value': 'Campbell
     -Bannerman'}"
Evaluation:
ASSISTANT:
USER:
Question: Who had a 70s No 1 hit with
    Kiss You All Over?
Answer: The band Exile had a 70s No 1
    hit with Kiss You All Over.
Ground truth: "{'aliases': ['Internal
    exile', 'Exiles', 'Transported for life', 'Exile (politics and government)', 'Voluntary exile', '
    Sent into exile', 'Exile and Banishment', 'Self-exile', 'Forced
    exile', 'Exile', 'Exile in Greek tragedy', 'Banish', 'Banishment'], normalized_aliases': ['exiles', 'voluntary exile', 'forced exile', banish', 'self exile', 'exile
    politics and government', 'exile in
    greek tragedy', 'sent into exile', banishment', 'transported for life' 'exile', 'internal exile', 'exile
     and banishment'],
    matched_wiki_entity_name': '',
     normalized_matched_wiki_entity_name
    ': '', 'normalized_value': 'exile',
'type': 'WikipediaEntity', 'value':
     'Exile'}"
Evaluation:
ASSISTANT:
1
USFR:
Question: Which common mineral is used
    to make casts, moulds, blackboard
    chalk and plaster of Paris?
Answer: The common mineral used to make
    casts, moulds, blackboard chalk and
    plaster of Paris is calcium
    carbonate.
Ground truth: "{'aliases': ['CaSO4.2H20
    ', 'Gypsum', 'Calcium sulfate
dihydrate', 'CaSO4*2H2O', 'Gipsum'],
      'normalized_aliases': ['calcium
     sulfate dihydrate', 'caso4 2h2o',
    gipsum', 'caso4.2h2o', 'gypsum'], '
```

```
matched_wiki_entity_name': '', '
normalized_matched_wiki_entity_name
': '', 'normalized_value': 'gypsum',
   'type': 'WikipediaEntity', 'value':
   'Gypsum'}"
Evaluation:
ASSISTANT:
```

D Additional Experiments on the LLM-Generated dataset

Dataset			Thre						al Th		
Dutuset		last	28	24	20	16	last	-	24	20	16
billturnbull	Llama	.579	.560	.560	.593	.648	.605	.553	.632	.632	.691
Dilitui libuli	OPT	.543	.533	.533	.486	.476	.527	.500	.486	.500	.500
J b #	Llama	.556	.576	.550	.544	.602	.542	.529	.529	.554	.575
derby*	OPT	.526	.548	.554	.563	.535	.535	.583	.570	.579	.561
:16	Llama	.602	.573	.544	.538	.608	.575	.600	.525	.550	.642
quiz4free	OPT	.525	.489	.511	.525	.504	.545	.535	.556	.576	.495
quizguy	Llama	.608	.571	.546	.567	.571	.601	.595	.583	.577	.565
quizguy	OPT	.557	.557	.587	.569	.557	.586	.594	.552	.548	.552
4-4-4-1-1	Llama	.412	.619	.526	.598	.577	.485	.471	.471	.544	.544
triviabug	OPT	.557	.602	.671	.614	.500	.629	.597	.629	.597	.532
businessballs	Llama	.580	.577	.559	.575	.589	.586	.605	.546	.563	.592
	OPT	.564	.578	.555	.587	.521	.585	.579	.585	.547	.537
iotnunk	Llama	.612	.590	.583	.619	.640	.582	.561	.520	.592	.673
jetpunk	OPT	.569	.571	.593	.604	.566	.620	.631	.631	.631	.635
adania	Llama	.546	.536	.537	.559	.564	.527	.522	.547	.563	.571
odquiz	OPT	.511	.543	.591	.579	.552	.565	.535	.592	.571	.565
	Llama	.578	.519	.588	.562	.578	.611	.534	.534	.534	.557
quiz-zone	OPT	.544	.577	.603	.611	.586	.542	.518	.554	.601	.613
!	Llama	.610	.568	.592	.582	.582	.617	.563	.583	.557	.586
quizballs	OPT	.535	.578	.559	.594	.549	.532	.564	.512	.599	.576
	Llama	.572	.588	.570	.572	.586	.581	.598	.611	.616	.616
quizwise	OPT	.540	.550	.574	.568	.551	.580	.550	.554	.582	.576
	Llama	.530	.533	.528	.538	.560	.545	.581	.584	.570	.575
sfquiz	OPT	.531	.546	.568	.590	.545	.595	.597	.599	.611	.553
4-4-4	Llama	.602	.636	.602	.602	.619	.639	.602	.639	.590	.578
triviacountry	OPT	.525	.542	.585	.551	.525	.494	.602	.506	.578	.446
wrexham**	Llama	.532	.519	.528	.574	.583	.474	.526	.533	.566	.579
wrexnam**	OPT	.500	.533	.594	.583	.525	.572	.552	.562	.608	.567
Avonogo	Llama	.566	.569	.558	.573	.593	.569	.560	.560	.572	.596
Average	OPT	.538	.553	.577	.573	.535	.565	.567	.563	.581	.551

^{*:} derby is adopted as abbreviation of derbyshirepubquizleague **: wrexham is adopted as abbreviation of wrexhamquizleague

Table 9: Accuracy values obtained training SAPLMA on the original True-False dataset and testing on our facts dataset generated from TriviaQA. The original topic-wise leave-one-out strategy is adopted. Results are shown for the Llama 2-7b and OPT-6.7b models.

Table 9 reports the performances of the SAPLMA classifier trained on the original True-False dataset by Azaria and Mitchell (2023) and tested on the dataset generated from TriviaQA. Similarly to Table 6, SAPLMA does not generalize well over LLM-generated facts. Moreover, tuning an optimal threshold did not provide solid enhancements.