

Alert

Get Alert Profiles

This endpoint retrieves alert profiles based on the provided session ID.

Request

- **Method:** POST
- **Endpoint:** {{MVAPI_URL}}/alert/get_alert_profiles
- **Request Body:**
 - **sessionId (object):** The session identifier used to fetch the alert profiles.

Response

The response will be in JSON format and contains the following structure:

- **status (integer):** Indicates the success or failure of the request.
- **data (object):** Contains the alert profile data.
 - **alertJson (string):** A JSON string representing the alert profile details.
- **errData (array):** An array of error details, if any.
 - **errCode (integer):** The error code indicating the type of error.
 - **errString (string):** A description of the error.
 - **isErr (boolean):** Indicates whether an error occurred.
 - **timeStamp (string):** The timestamp when the error occurred.

Example Response

JSON

```
{
  "status": 0,
  "data": {
    "alertJson": ""
  },
  "errData": [
    {
```

```
"errCode": 0,  
"errString": "",  
"isErr": true,  
"timeStamp": ""  
}  
]  
}
```

This endpoint is essential for managing user alerts based on their active session.

Get Alert Delivery Logs

Endpoint

POST {{MVAPI_URL}}/alert/get_alert_delivery_logs

Purpose

This endpoint is designed to retrieve the delivery logs of alerts based on the provided session ID. It serves as a crucial tool for tracking the status and details of alerts delivered to users, enabling better monitoring and management of alert notifications.

Request Parameters

The request body must be a JSON object containing the following parameter:

- **sessionId** (object): This parameter is required to identify the session for which the alert delivery logs are being requested. It should encapsulate the relevant session information necessary for fetching the logs.

Example Request Body

JSON

```
{  
  "sessionId": {}  
}
```

Response Structure

Upon successful execution, the endpoint will return a JSON response structured as follows:

- **status** (integer): Indicates the overall status of the request. A value of 0 typically signifies success.
- **data** (object): Contains the details of the alert logs.

- **alertJson** (string): A JSON string representation of the alert data. This may be empty if there are no alerts available.
- **errData** (array): An array of error objects that provide details in case of any errors encountered during the request.
 - **errCode** (integer): The error code, where 0 indicates no error.
 - **errString** (string): A message describing the error, if any.
 - **isErr** (boolean): A flag indicating whether an error occurred.
 - **timeStamp** (string): The timestamp of when the error occurred, if applicable.

Example Response

JSON

```
{
  "status": 0,
  "data": {
    "alertJson": ""
  },
  "errData": [
    {
      "errCode": 0,
      "errString": "",
      "isErr": true,
      "timeStamp": ""
    }
  ]
}
```

Important Notes

- Ensure that the sessionId is accurately populated to receive the appropriate logs. An incorrect or missing session ID may result in an unsuccessful request.
- The response will include error data if there are issues processing the request, which can be instrumental for debugging purposes. Pay close attention to the errData array to understand any errors that may have occurred during the request.

This endpoint effectively retrieves the delivery logs for alerts based on a provided session ID, making it essential for tracking the status and details of alerts dispatched through the system.

Get Alerts to Process

This endpoint is used to retrieve alerts that need processing for a given session. It allows clients to obtain the status of alerts associated with a specific session ID, facilitating efficient alert management in applications that require real-time processing.

Request

- **Method:** POST
- **URL:** {{MVAPI_URL}}/alert/get_alerts_to_process
- **Request Body:** The request must include a JSON object with the following parameter:
 - **sessionId (Object):** This required parameter serves as a unique identifier for the user session. It is essential for fetching the relevant alerts associated with the session.

Example Request Payload

JSON

```
{  
  "sessionId": {}  
}
```

Response

Upon a successful request, the server responds with a JSON object structured as follows:

- **Status:** HTTP status code (200 for success).
- **Content-Type:** application/json
- **Response Body:**
 - **status (Integer):** Indicates the success or failure of the request. A value of 0 typically signifies success.
 - **data (Object):** Contains the following:
 - **alertJson (String):** A JSON string representing the alerts. This may be empty if there are no alerts to process.
 - **errData (Array):** An array of error objects that provide details on any errors encountered during the request.
 - Each error object contains:
 - **errCode (Integer):** The error code associated with the error.

- `errString` (String): A description of the error.
- `isErr` (Boolean): Indicates whether an error occurred (true) or not (false).
- `timeStamp` (String): The timestamp of when the error occurred.

Example Response

JSON

```
{
  "status": 0,
  "data": {
    "alertJson": ""
  },
  "errData": [
    {
      "errCode": 0,
      "errString": "",
      "isErr": true,
      "timeStamp": ""
    }
  ]
}
```

Important Notes

- Ensure that the `sessionId` is valid and correctly formatted to avoid errors in the response.
- The `alertJson` field may return an empty string if there are no alerts available for processing.
- Review the `errData` array for any error messages that may indicate issues with the request, as it provides insights into what went wrong.

This endpoint is essential for applications that need to monitor and process alerts in real-time based on user sessions.

Create Alert Message

This endpoint is used to create an alert message in the system. It requires a session identifier to process the request and return the appropriate response.

Request

- **Method:** POST
- **URL:** {{MVAPI_URL}}/alert/create_alert_message
- **Content-Type:** application/json

Request Body

The request body must be a JSON object containing the following parameter:

- **sessionId** (object): A unique identifier for the user session. This is necessary for tracking and managing user interactions.

Example Request Body

JSON

```
{
  "sessionId": {}
}
```

Response

Upon successful execution, the server responds with a JSON object structured as follows:

- **status** (integer): Indicates the status of the request. A value of 0 typically signifies success.
- **data** (object): Contains the result of the operation.
 - **finalMessage** (string): A message indicating the outcome of the alert creation, which may be empty if no specific message is generated.
- **errData** (array): An array of error objects that provide information about any issues that occurred during the request.
 - **errCode** (integer): A code representing the type of error.
 - **errString** (string): A description of the error.
 - **isErr** (boolean): Indicates whether an error occurred (true if there was an error).
 - **timeStamp** (string): A timestamp indicating when the error occurred.

Example Response

JSON

```
{
  "status": 0,
  "data": {
    "finalMessage": ""
```

```

},
"errData": [
  {
    "errCode": 0,
    "errString": "",
    "isErr": true,
    "timeStamp": ""
  }
]
}

```

This endpoint is essential for managing alert messages within the application, allowing for effective communication and tracking of user sessions.

Get Broadcast Alerts to Process

This endpoint allows the client to retrieve broadcast alerts that are pending processing based on a provided session identifier. It is primarily used to check for alerts that require action or attention in the context of the user's current session.

Request

- **Method:** POST
- **URL:** {{MVAPI_URL}}/alert/get_broadcast_alerts_to_process

Request Body

The request body should be in JSON format and must include the following parameter:

- **sessionId** (object): This parameter is used to identify the user's session. It is required for the server to associate the request with the correct user context.

Example Request Body:

JSON

```

{
  "sessionId": {}
}

```

Response

The response will be in JSON format and contains the following structure:

- **status** (integer): Indicates the success or failure of the request. A status of 0 typically means success.
- **data** (object): Contains the main data returned by the API.
 - **alertJson** (string): This field will contain the alert data in JSON format. It may be empty if there are no alerts to process.
- **errData** (array): An array of error objects that provide details about any errors encountered during the request.
 - **errCode** (integer): A code representing the type of error.
 - **errString** (string): A description of the error.
 - **isErr** (boolean): A flag indicating whether an error occurred.
 - **timeStamp** (string): A timestamp indicating when the error occurred.

Example Response:

JSON

```
{
  "status": 0,
  "data": {
    "alertJson": ""
  },
  "errData": [
    {
      "errCode": 0,
      "errString": "",
      "isErr": true,
      "timeStamp": ""
    }
  ]
}
```

Important Notes

- Ensure that the sessionId is valid and corresponds to an active session to receive the appropriate alerts.

- The response may include error details in the `errData` array, which can help in debugging any issues that arise during the request.
- If the `alertJson` field is empty, it indicates that there are currently no alerts to process for the given session.

Add to Alert Queue

This endpoint allows users to add a session to the alert queue. It is useful for managing alerts related to specific sessions in the system.

Request

- **Method:** POST
- **URL:** `{{MVAPI_URL}}/alert/add_to_alert_queue`
- **Content-Type:** `application/json`

Request Body

The request body must be a JSON object containing the following parameter:

- **sessionId** (object): This parameter represents the unique identifier for the session that needs to be added to the alert queue. The structure of this object should conform to the expected format defined by the API.

Response

The response will provide feedback on the success or failure of the request. The structure of the response typically includes:

- **status** (string): Indicates whether the operation was successful or if there was an error.
- **message** (string): A descriptive message providing additional information about the result of the operation.

The response will help the user understand if the session was successfully added to the alert queue or if there were issues that need to be addressed.

This endpoint allows users to add alerts to the alert queue for further processing. It is essential for managing notifications and ensuring timely responses to specific events or conditions.