

Queries:

```
CREATE DATABASE
student_faculty;

USE student_faculty;

CREATE TABLE student(
    snum INT,
    sname VARCHAR(10),
    major VARCHAR(2),
    lvl VARCHAR(2),
    age INT, primary key(snum));

CREATE TABLE faculty(
    fid INT,fname VARCHAR(20),
    deptid INT,
    PRIMARY KEY(fid));

CREATE TABLE class(
    cname VARCHAR(20),
    metts_at TIMESTAMP,
    room VARCHAR(10),
    fid INT,
    PRIMARY KEY(cname),
    FOREIGN KEY(fid) REFERENCES faculty(fid));

CREATE TABLE enrolled(
    snum INT,
    cname VARCHAR(20),
    PRIMARY KEY(snum,cname),
    FOREIGN KEY(snum) REFERENCES student(snum),
    FOREIGN KEY(cname) REFERENCES class(cname));

INSERT INTO STUDENT VALUES(1, 'jhon', 'CS', 'Sr', 19);
INSERT INTO STUDENT VALUES(2, 'Smith', 'CS', 'Jr', 20);
INSERT INTO STUDENT VALUES(3 , 'Jacob', 'CV', 'Sr', 20);
INSERT INTO STUDENT VALUES(4, 'Tom ', 'CS', 'Jr', 20);
INSERT INTO STUDENT VALUES(5, 'Rahul', 'CS', 'Jr', 20);
INSERT INTO STUDENT VALUES(6, 'Rita', 'CS', 'Sr', 21);

INSERT INTO FACULTY VALUES(11, 'Harish', 1000);
INSERT INTO FACULTY VALUES(12, 'MV', 1000);
INSERT INTO FACULTY VALUES(13 , 'Mira', 1001);
```

```

INSERT INTO FACULTY VALUES(14, 'Shiva', 1002);
INSERT INTO FACULTY VALUES(15, 'Nupur', 1000);

insert into class values('class1', '12/11/15 10:15:16', 'R1', 14);
insert into class values('class10', '12/11/15 10:15:16', 'R128', 14);
insert into class values('class2', '12/11/15 10:15:20', 'R2', 12);
insert into class values('class3', '12/11/15 10:15:25', 'R3', 11);
insert into class values('class4', '12/11/15 20:15:20', 'R4', 14);
insert into class values('class5', '12/11/15 20:15:20', 'R3', 15);
insert into class values('class6', '12/11/15 13:20:20', 'R2', 14);
insert into class values('class7', '12/11/15 10:10:10', 'R3', 14);

insert into enrolled values(1, 'class1');
insert into enrolled values(2, 'class1');
insert into enrolled values(3, 'class3');
insert into enrolled values(4, 'class3');
insert into enrolled values(5, 'class4');
insert into enrolled values(1, 'class5');
insert into enrolled values(2, 'class5');
insert into enrolled values(3, 'class5');
insert into enrolled values(4, 'class5');
insert into enrolled values(5, 'class5');

```

**Class Table:**

	cname	metts_at	room	fid
	class4	2012-11-15 20:15:20	R4	14
	class5	2012-11-15 20:15:20	R3	15
	class6	2012-11-15 13:20:20	R2	14
	class3	2012-11-15 10:15:25	R3	11
	class2	2012-11-15 10:15:20	R2	12
	class1	2012-11-15 10:15:16	R1	14
	class10	2012-11-15 10:15:16	R128	14
▶	class7	2012-11-15 10:10:10	R3	14
•	NULL	NULL	NULL	NULL

**Enrolled Table:**

	snum	cname
▶	1	class1
	2	class1
	3	class3
	4	class3
	5	class4
	1	class5
	2	class5
	3	class5
	4	class5
	5	class5
★	NULL	NULL

**Faculty Table:**

	fid	fname	deptid
▶	11	Harish	1000
	12	MV	1000
	13	Mira	1001
	14	Shiva	1002
	15	Nupur	1000
★	NULL	NULL	NULL

**Student Table:**


	snum	sname	major	lvl	age
▶	1	jhon	CS	Sr	19
	2	Smith	CS	Jr	20
	3	Jacob	CV	Sr	20
	4	Tom	CS	Jr	20
	5	Rahul	CS	Jr	20
	6	Rita	CS	Sr	21
★	NULL	NULL	NULL	NULL	NULL

## ADDITIONAL QUERIES

### Query 1:

```
SELECT DISTINCT S.Sname
FROM Student S, Class C, Enrolled E, Faculty F
WHERE S.snum = E.snum AND E.cname = C.cname AND C.fid = F.fid AND
F.fname = 'Harish' AND S.lvl = 'Jr';
```

### Output:




Sname
Tom

### Query 2:

```
SELECT DISTINCT cname
FROM class
WHERE room='R128'
OR
cname IN (SELECT e.cname FROM enrolled e GROUP BY e.cname HAVING COUNT(*)>=5);
```

### Output:



cname
class10
class5
NULL

### Query 3:

```
SELECT DISTINCT S.sname
FROM Student S
WHERE S.snum IN (SELECT E1.snum
                  FROM Enrolled E1, Enrolled E2, Class C1, Class C2
```

```

WHERE E1.snum = E2.snum AND E1.cname <> E2.cname

AND E1.cname = C1.cname

AND E2.cname = C2.cname AND C1.metts_at = C2.metts_at);

```

**Output:**

	sname
▶	Rahul

**Query 4:**

```

SELECT f.fname,f.fid
FROM faculty f
WHERE f.fid in ( SELECT fid FROM class
GROUP BY fid HAVING COUNT(*)=(SELECT COUNT(DISTINCT room) FROM class) );

```

**Output:**

	fname	fid
▶	Shiva	14
●	NULL	NULL

**Query 5:**

```

SELECT DISTINCT F.fname
FROM Faculty F
WHERE 5 > (SELECT COUNT(E.snum)
FROM Class C, Enrolled E
WHERE C.cname = E.cname
AND C.fid = F.fid);


```

**Output:**

	fname
▶	Harish
	MV
	Mira
	Shiva

**Query 6:**


```
SELECT DISTINCT S.sname
FROM Student S
WHERE S.snum NOT IN (SELECT E.snum
FROM Enrolled E );
```

**Output:**

	sname
▶	Rita

**Query 7:**

```
SELECT S.age, S.lvl
FROM STUDENT S
GROUP BY S.age, S.lvl
HAVING S.lvl IN(SELECT S1.lvl
FROM STUDENT S1
WHERE S1.age=S.age
GROUP BY S1.age, S1.lvl
HAVING COUNT(*) >= ALL (SELECT COUNT(*)
FROM STUDENT S2
WHERE S1.age=S2.age
GROUP BY S2.lvl, S2.age))
ORDER BY S.age;
```

**Output:**

	age	lvl
▶	19	Sr
	20	Jr
	21	Sr