

Queries:

```
create
database
flightdb;

use flightdb;

create table flights(
    flno int,
    fromplace varchar(15),
    toplace varchar(15),
    distance int,
    departs datetime,
    arrives datetime,
    price int,
    primary key (flno)
);
desc flights;
create table aircraft(
    aid int,
    aname varchar(15),
    cruisingrange int,
    primary key (aid)
);
desc aircraft;
create table employees (
    eid int,
    ename varchar(15),
    salary int,
    primary key (eid)
);
desc employees;
create table certified (
    eid int,
    aid int,
    foreign key (eid) references employees(eid),
    foreign key (aid) references aircraft(aid)
);
desc certified;
insert into flights values(101, 'Bangalore', 'Delhi', 2500, '2005-05-13
07:15:31', '2005-05-13 18:15:31', 5000);
```

```
insert into flights values(102, 'Bangalore', 'Lucknow', 3000, '2013-05-05
07:15:31', '2013-05-05 11:15:31', 6000);
insert into flights values(103, 'Lucknow', 'Delhi', 500, '2013-05-05
12:15:31', '2013-05-05 17:15:31', 3000);
insert into flights values(107, 'Bangalore', 'Frankfurt', 8000, '2013-05-05
07:15:31', '2013-05-05 22:15:31', 60000);
insert into flights values(104, 'Bangalore', 'Frankfurt', 8500, '2013-05-05
07:15:31', '2013-05-05 23:15:31', 75000);
insert into flights values(105, 'Kolkata', 'Delhi', 3400, '2013-05-05
07:15:31', '2013-05-05 09:15:31', 7000);
insert into flights values(106, 'Bangalore', 'Kolkata', 1000, '2013-05-05
01:15:30', '2013-05-05 09:20:30', 10000);
insert into flights values(108, 'Lucknow', 'Kolkata', 1000, '2013-05-05
11:30:30', '2013-05-05 15:20:30', 10000);
```

```
commit;
```

```
select * from flights;
```

```
insert into aircraft values(101, '747', 3000);
insert into aircraft values(102, 'Boeing', 900);
insert into aircraft values(103, '647', 800);
insert into aircraft values(104, 'Dreamliner', 10000);
insert into aircraft values(105, 'Boeing', 3500);
insert into aircraft values(106, '707', 1500);
insert into aircraft values(107, 'Dream', 120000);
insert into aircraft values(108, '707', 760);
insert into aircraft values(109, '747', 1000);
commit;
```

```
select * from aircraft;
```

```
insert into employees values(701, 'A', 50000);
insert into employees values(702, 'B', 100000);
insert into employees values(703, 'C', 150000);
insert into employees values(704, 'D', 90000);
insert into employees values(705, 'E', 40000);
insert into employees values(706, 'F', 60000);
insert into employees values(707, 'G', 90000);
commit;
```

```
select * from employees;
```

```
insert into certified values(701, 101);
insert into certified values(701, 102);
insert into certified values(701, 106);
```

```

insert into certified values(701, 105);

insert into certified values(702, 104);
insert into certified values(703, 104);
insert into certified values(704, 104);

insert into certified values(702, 107);
insert into certified values(703, 107);
insert into certified values(704, 107);

insert into certified values(702, 101);
insert into certified values(702, 108);
insert into certified values(701, 109);
commit;
select * from certified;

```

Aircraft Table :

	aid	aname	cruisingrange
▶	101	747	3000
	102	Boeing	900
	103	647	800
	104	Dreamliner	10000
	105	Boeing	3500
	106	707	1500
	107	Dream	120000
	108	707	760
	109	747	1000
•	NULL	NULL	NULL

Employees Table:

	eid	ename	salary
▶	701	A	50000
	702	B	100000
	703	C	150000
	704	D	90000
	705	E	40000
	706	F	60000
	707	G	90000
•	NULL	NULL	NULL

Certified Table :

	eid	aid
▶	701	101
	701	102
	701	106
	701	105
	702	104
	703	104
	704	104
	702	107
	703	107
	704	107
	702	101
	702	108
	701	109

Flights Table:

	fno	fromplace	toplace	distance	departs	arrives	price
▶	101	Bangalore	Delhi	2500	2005-05-13 07:15:31	2005-05-13 18:15:31	5000
	102	Bangalore	Lucknow	3000	2013-05-05 07:15:31	2013-05-05 11:15:31	6000
	103	Lucknow	Delhi	500	2013-05-05 12:15:31	2013-05-05 17:15:31	3000
	104	Bangalore	Frankfurt	8500	2013-05-05 07:15:31	2013-05-05 23:15:31	75000
	105	Kolkata	Delhi	3400	2013-05-05 07:15:31	2013-05-05 09:15:31	7000
	106	Bangalore	Kolkata	1000	2013-05-05 01:15:30	2013-05-05 09:20:30	10000
	107	Bangalore	Frankfurt	8000	2013-05-05 07:15:31	2013-05-05 22:15:31	60000
	108	Lucknow	Kolkata	1000	2013-05-05 11:30:30	2013-05-05 15:20:30	10000
*	NULL	NULL	NULL	NULL	NULL	NULL	NULL

ADDITIONAL QUERIES

Query 1:

```
select distinct a.aname from aircraft a where a.aid in (
    select c.aid from certified c, employees e where
    c.eid = e.eid and not exists(
        select * from employees e1 where e1.eid=e.eid and e1.salary<80000
    )
);
```

Result:

	aname
▶	747
	Dreamliner
	Dream
	707

Query 2:

select max(a.cruisingrange), c.eid from certified c, aircraft a where c.aid = a.aid group by c.eid having count(c.eid)>3;

Result:

	max(a.cruisingrange)	eid
▶	3500	701
	120000	702

Query 3:

select ename from employees where salary <(
select min(price) from flights where fromplace='Bangalore' and toplace='Frankfurt');

Result:

Result Grid	
	ename
▶	A
	E

Query 4:

select avg(e.salary), c.aid from certified c, employees e where c.aid in(
select aid from aircraft where cruisingrange>1000) and e.eid = c.eid group by c.aid;

Result:

	avg(e.salary)	aid
▶	75000.0000	101
	113333.3333	104
	50000.0000	105
	50000.0000	106
	113333.3333	107

Query 5:

```
select ename from employees where eid in(  
select eid from certified where aid in(  
select aid from aircraft where aname = 'Boeing'));
```

Result:

	ename
▶	A

Query 6:

```
select aname from aircraft where cruisingrange > any (select distance from flights where  
fromplace='Bangalore' and toplace='Delhi');
```

Result:

	aname
▶	747
	Dreamliner
	Boeing
	Dream

Query 7:

```
SELECT F.flno, F.departs  
FROM flights F  
WHERE F.flno IN ( ( SELECT F0.flno  
FROM flights F0
```

```

WHERE F0.fromplace = 'Bangalore' AND F0.toplace = 'Kolkata'
AND extract(hour from F0.arrives) < 18 )
UNION
( SELECT F0.flno
FROM flights F0, flights F1
WHERE F0.fromplace = 'Bangalore' AND F0.toplace <> 'Kolkata'
AND F0.toplace = F1.fromplace AND F1.toplace = 'Kolkata'
AND F1.departs > F0.arrives
AND extract(hour from F1.arrives) < 18)
UNION
( SELECT F0.flno
FROM flights F0, flights F1, flights F2
WHERE F0.fromplace = 'Bangalore'
AND F0.toplace = F1.fromplace
AND F1.toplace = F2.fromplace
AND F2.toplace = 'Kolkata'
AND F0.toplace <> 'Kolkata'
AND F1.toplace <> 'Kolkata'
AND F1.departs > F0.arrives
AND F2.departs > F1.arrives
AND extract(hour from F2.arrives) < 18));

```

Result:

Result Grid			Filter Rows:
	flno	departs	
▶	102	2013-05-05 07:15:31	
	106	2013-05-05 01:15:30	