

ASTITTVA

Project file & folder analysis

Detailed responsibility directory and feature brief | 11 September 2026

Workspace: E:\Astittva Emergent version 4

Purpose: explain the task performed by each project file and folder, with its name alongside the explanation, and connect the code to the website features.

Inventory: 266 project/support files and 34 traversed folders. Third-party dependencies, Git internals, generated builds/caches and this report output are excluded from individual enumeration.

Evidence level: static source inspection, route/configuration tracing and saved test-artifact review. No application tests, database connections, CRM calls, image generators or deployment actions were run. Implemented in source does not mean verified live.

Reading guide

1. Feature brief and user journeys. 2. Architecture and backend differences. 3. Folder responsibility map. 4. File-by-file directory. 5. API inventory. 6. Test evidence and maintenance priorities.

1. Feature brief

Feature	What it does
Property discovery	Visitors browse published real estate listings with location, property type, budget, builder, availability and category filters. Filter values are stored in the URL for shareable catalogue views. Sources: PropertiesPage.jsx; property APIs.
Property details and enquiries	A detail page presents images, price, location, amenities and property information, then captures a property-specific enquiry. This is a lead-generation flow, not a purchase/checkout flow. Source: PropertyDetailPage.jsx.
Consultation and contact	Homepage, contact page and reusable forms submit enquiries to /api/leads. The Python implementation stores the lead first and performs CRM forwarding separately. Sources: HomePage.jsx, ContactPage.jsx, LeadForm.jsx, crm_service.py.
Editorial publishing	Public blog list/detail pages are paired with admin editing, image upload, slug and SEO fields, draft/published controls and sanitized HTML rendering. Sources: blog pages; sanitize.js; blog APIs.
Market intelligence	Newsroom offers trending content and location/category filters. Python fetches and classifies RSS topics with cached fallback; the UI also includes evergreen content. Node only reads stored news cache.
Staff operations	Protected dashboard, property management, blog management, lead status updates and admin-only staff account management. Roles in code: admin, sales, marketing. Sources: App.js, admin pages and API authorization.
Brand and navigation	Cinematic homepage imagery, responsive header/footer, WhatsApp shortcuts, about content and expansion narrative support the advisory business presentation.
SEO and loading support	Per-page metadata, a Python dynamic sitemap, route-level lazy loading, responsive WebP images and backend compression/index setup are present. These are implementation mechanisms, not measured SEO or performance results.

Typical workflows

Visitor: home or catalogue -> choose filters -> open a property -> submit an enquiry -> database lead -> Python CRM delivery when configured -> staff follow-up.

Staff: log in -> create/edit property or blog -> upload imagery where supported -> publish -> public API exposes published content. Administrators additionally manage accounts and destructive operations.

2. Architecture and implementation status

The React frontend calls an Axios client configured with `REACT_APP_BACKEND_URL` plus `/api`, or same-origin `/api` when no URL is supplied. Node starts from `root/package.json`; Render selects `backend/server.py`. Both backends use MongoDB, but they are alternative runtimes with different behavior.

Name / source	Task performed / feature brief
React frontend	Browser routes and presentation in <code>frontend/src</code> ; public and protected admin experiences share API and authentication helpers.
Node execution path	<code>npm start -> server.js -> db.js -> MongoDB</code> . Can also serve <code>frontend/build</code> if the compiled index exists.
Python execution path	Render/Gunicorn or Procfile <code>-> backend/server.py -> MongoDB</code> , <code>news_service.py</code> and <code>crm_service.py</code> . <code>server.py</code> owns its route definitions.
Modular Python code	<code>backend/routers</code> , <code>config.py</code> , <code>auth.py</code> , <code>models.py</code> and <code>storage.py</code> form a separate modular implementation. The configured <code>server.py</code> does not import the router package. Editing those routers alone will not change its registered endpoints.
External dependencies	MongoDB is needed for persistent records. Python storage requires its integration key; CRM requires its environment configuration; live RSS requires external network availability.
Historical backups	<code>backups/local_20260612_074339</code> contains an <code>astitva_realestate</code> database dump. The snapshot directory name does not prove backup completeness or restorability.

Backend differences that affect the interface

Name / source	Task performed / feature brief
Core catalogue, blog and admin APIs	Both backends define these API families. Equivalent route names do not establish identical validation, fields or behavior.
File uploads / file delivery	Python defines <code>/api/admin/upload</code> and <code>/api/files/{path:path}</code> . No matching routes are defined in <code>server.js</code> . Admin forms call upload endpoints, so Node-only deployment needs additional support for this flow.
CRM lead forwarding	Python calls <code>crm_service.py</code> and defines a staff CRM retry endpoint. Node lead handling stores records but does not implement this forwarding/retry integration.
Live news refresh	Python has RSS fetch/classification, grouped feeds, topics, diagnostics and refresh routes. Node offers trending/all reads from MongoDB cache.
Sitemap	Python defines <code>/api/sitemap.xml</code> . No matching Node sitemap route is defined.
Authentication implementation	Both use JWT and bcrypt with role checks. Cookie behavior and login protections must be assessed separately for each runtime; this report does not assert full parity.

Documentation drift: `docs/ARCHITECTURE.md` describes an older state. For example, the current Axios timeout is 30 seconds, Python startup creates indexes, blog routes exist, and storage is integrated with an object service. Source/configuration takes precedence over historical prose.

3. Folder responsibility map

Name / source	Task performed / feature brief
.emergent/	Managed development-platform configuration and cron support.
.emergent/cron/	Webhook scheduling scripts and persisted cron state.
.emergent/markers/	Platform lifecycle markers.
backend/	Python API, integrations, image utilities and backend tests.
backend/routers/	Modular API route implementations; not wired into the configured monolithic entry point.
backend/tests/	Python API regression test source.
backups/	Historical database dumps; not the live database.
backups/local_20260612_074339/	Historical MongoDB snapshot directory.
backups/local_20260612_074339/astitva_reale state/	Historical MongoDB snapshot directory.
docs/	Architecture and deployment documentation.
frontend/	React browser application and frontend build configuration.
frontend/plugins/	Frontend build/development extensions.
frontend/plugins/health-check/	Webpack development health checks.
frontend/public/	Static HTML shell, icons and public media.
frontend/public/images/	Location/brand images with optimized variants.
frontend/public/images/luxe/	Luxury property and landmark visual assets.
frontend/src/	Application source code.
frontend/src/components/	Shared website components.
frontend/src/components/admin/	Reusable admin presentation components.
frontend/src/components/ui/	Reusable UI primitive library.
frontend/src/constants/	Shared values and test selectors.
frontend/src/constants/testIds/	Grouped test identifiers.
frontend/src/context/	Shared authentication state.
frontend/src/data/	Bundled fallback editorial data.
frontend/src/hooks/	Reusable React state hooks.
frontend/src/layouts/	Public and admin page shells.

Name / source	Task performed / feature brief
frontend/src/lib/	API, formatting, HTML sanitization and other utilities.
frontend/src/pages/	Public visitor page implementations.
frontend/src/pages/admin/	Internal management page implementations.
memory/	Product requirements and project history.
scripts/	Maintenance and Node verification utilities.
test_reports/	Historical QA reports.
test_reports/pytest/	Saved machine-readable test results.
tests/	Root Python test package placeholder.

Name / source	Task performed / feature brief
node_modules/	Installed third-party Node packages. Excluded from per-file analysis because they are dependency internals, not project-owned feature code.
.git/	Version history, refs, index and local repository metadata. Excluded from per-file analysis.
Generated build/cache directories	build/, dist/, virtual environments and Python caches, where present, are excluded. Their source/configuration is documented instead.

4. File-by-file responsibility directory

Paths are relative to the workspace root. Every inventoried file appears once below. Descriptions identify intended source responsibilities; assets and historical records are not treated as independently working product features.

Workspace root

Name / source	Task performed / feature brief
<code>.gitconfig</code>	Repository-provided Git configuration file; presence alone does not establish that Git loads it.
<code>.gitignore</code>	Ignore patterns controlling which generated/local files Git normally excludes.
<code>README.md</code>	Root documentation placeholder; currently contains only an instruction heading.
<code>db.js</code>	Reusable MongoDB connection pool, environment loading, database-name selection and retry cooldown for the Node server.
<code>design_guidelines.json</code>	Brand and UI design guidance for typography, colors, layout and visual presentation.
<code>package-lock.json</code>	Records the resolved npm dependency tree and integrity data for reproducible installations.
<code>package.json</code>	Root Node dependencies and commands: start Express, build the frontend, and run the database connection test.
<code>render.yaml</code>	Render deployment blueprint selecting backend/server.py through Gunicorn/Uvicorn, with environment variables and health probe.
<code>server.js</code>	Node/Express API entry point. Handles authentication, property and blog CRUD, lead storage, user management, statistics, cached news and serving a compiled React site.
<code>test_result.md</code>	Development/testing handoff notes and historical verification context; not a current test run.

.emergent/

Name / source	Task performed / feature brief
<code>emergent.yml</code>	Emergent platform project configuration.
<code>system_deps.txt</code>	Platform-level system dependency declarations.

.emergent/cron/

Name / source	Task performed / feature brief
applied.hash	Tracks the last applied cron configuration hash.
dispatch_webhook.sh	Dispatches configured scheduled webhook requests using environment-provided settings.
watch_crons.sh	Checks cron configuration changes and asks the preview service to reconcile schedules.
webhook-crons	Persisted platform-generated crontab entries.
webhook_crond.sh	Starts and restores the platform webhook cron daemon under process supervision.

.emergent/markers/

Name / source	Task performed / feature brief
.restore-complete	Platform marker indicating a restoration step completed.

backend/

Name / source	Task performed / feature brief
<code>.dockerignore</code>	Excludes unnecessary/local files from the backend Docker build context.
<code>.env</code>	Environment configuration. Values intentionally omitted from this report.
<code>.env.example</code>	Environment configuration. Values intentionally omitted from this report.
<code>Dockerfile</code>	Builds a container image for the Python backend and declares its execution environment.
<code>Procfile</code>	Process command for hosting the Python API.
<code>auth.py</code>	Modular password hashing, JWT/cookie authentication and staff/admin role checks.
<code>config.py</code>	Separate configuration/database module used by modular backend helpers; duplicates configuration also defined by <code>server.py</code> .
<code>crm_service.py</code>	Maps saved website enquiries to CRM webhook payloads, forwards with timeout/retry handling, and reports delivery results. Requires CRM configuration.
<code>gen_hero_images.py</code>	One-off image generation utility for hero images. Produces visual assets; not a visitor-facing AI feature.
<code>gen_images.py</code>	One-off image generation utility for images. Produces visual assets; not a visitor-facing AI feature.
<code>gen_kolkata.py</code>	One-off image generation utility for kolkata. Produces visual assets; not a visitor-facing AI feature.
<code>gen_location_images.py</code>	One-off image generation utility for location images. Produces visual assets; not a visitor-facing AI feature.
<code>gen_property_images.py</code>	One-off image generation utility for property images. Produces visual assets; not a visitor-facing AI feature.
<code>models.py</code>	Modular Pydantic request/response schemas for users, properties, leads and blogs; includes serialization helpers.
<code>news_service.py</code>	Fetches Google News RSS topics, classifies articles, merges/deduplicates cached items and retains last-known-good results. Cache TTL is 3 hours.
<code>requirements-dev.txt</code>	Additional Python development/test dependencies.
<code>requirements.txt</code>	Python runtime dependency list for API, database, authentication and integrations.
<code>seed_properties.py</code>	Utility to insert sample property records into MongoDB; changes data when executed.
<code>server.py</code>	Configured FastAPI entry point. Defines its own models, helpers and routes, including uploads, sitemap, CRM forwarding, RSS news and database index startup work.
<code>storage.py</code>	Modular object-storage initialization, upload and download helpers using the Emergent storage service.

backend/routers/

Name / source	Task performed / feature brief
<code>__init__.py</code>	Python package marker; enables package/module organization.
<code>auth.py</code>	Modular routes for login/logout/session refresh and user management. Present in source, but not imported/mounted by the configured <code>server.py</code> entry point.
<code>blogs.py</code>	Modular routes for public blog summaries/detail and staff editorial CRUD. Present in source, but not imported/mounted by the configured <code>server.py</code> entry point.
<code>files.py</code>	Modular routes for staff file uploads and public stored-file access. Present in source, but not imported/mounted by the configured <code>server.py</code> entry point.
<code>leads.py</code>	Modular routes for lead capture, status management and CRM delivery retry. Present in source, but not imported/mounted by the configured <code>server.py</code> entry point.
<code>news.py</code>	Modular routes for news feeds, grouping, diagnostics and staff refresh. Present in source, but not imported/mounted by the configured <code>server.py</code> entry point.
<code>properties.py</code>	Modular routes for public property search/detail and staff listing CRUD. Present in source, but not imported/mounted by the configured <code>server.py</code> entry point.
<code>seo.py</code>	Modular routes for dynamic sitemap generation. Present in source, but not imported/mounted by the configured <code>server.py</code> entry point.
<code>stats.py</code>	Modular routes for admin dashboard counts. Present in source, but not imported/mounted by the configured <code>server.py</code> entry point.

backend/tests/

Name / source	Task performed / feature brief
<code>backend_test.py</code>	General API/authentication/property/lead regression suite. Test code exists; not executed for this report.
<code>test_aramya_leads.py</code>	Aramya campaign lead submission and CRM-related regression checks. Test code exists; not executed for this report.
<code>test_blogs.py</code>	Public/admin blog lifecycle tests. Test code exists; not executed for this report.
<code>test_market_intelligence.py</code>	Market news feeds and classification checks. Test code exists; not executed for this report.
<code>test_performance.py</code>	Backend performance-related regression checks. Test code exists; not executed for this report.

backups/local_20260612_074339/astitva_realestate/

Name / source	Task performed / feature brief
files.bson	MongoDB binary backup of the files collection. Historical snapshot; contents were not decoded or exposed.
files.metadata.json	Backup metadata/index definitions for the files collection; not application execution code.
leads.bson	MongoDB binary backup of the leads collection. Historical snapshot; contents were not decoded or exposed.
leads.metadata.json	Backup metadata/index definitions for the leads collection; not application execution code.
login_attempts.bson	MongoDB binary backup of the login_attempts collection. Historical snapshot; contents were not decoded or exposed.
login_attempts.metadata.json	Backup metadata/index definitions for the login_attempts collection; not application execution code.
news_cache.bson	MongoDB binary backup of the news_cache collection. Historical snapshot; contents were not decoded or exposed.
news_cache.metadata.json	Backup metadata/index definitions for the news_cache collection; not application execution code.
prelude.json	MongoDB backup snapshot metadata; retained for restore context.
properties.bson	MongoDB binary backup of the properties collection. Historical snapshot; contents were not decoded or exposed.
properties.metadata.json	Backup metadata/index definitions for the properties collection; not application execution code.
users.bson	MongoDB binary backup of the users collection. Historical snapshot; contents were not decoded or exposed.
users.metadata.json	Backup metadata/index definitions for the users collection; not application execution code.

docs/

Name / source	Task performed / feature brief
ARCHITECTURE.md	Historical architecture/business report. Useful context, but several details differ from this checkout.
RENDER_DEPLOYMENT.md	Instructions for configuring and deploying the Python backend on Render.

frontend/

Name / source	Task performed / feature brief
<code>.env</code>	Environment configuration. Values intentionally omitted from this report.
<code>.env.example</code>	Environment configuration. Values intentionally omitted from this report.
<code>.gitignore</code>	Local Git ignore rules for generated/developer files.
<code>README.md</code>	Frontend setup/scaffold documentation.
<code>components.json</code>	UI component generator configuration.
<code>craco.config.js</code>	Customizes Create React App build tooling and aliases/plugins.
<code>jsconfig.json</code>	JavaScript editor/compiler path configuration.
<code>package-lock.json</code>	Records the resolved npm dependency tree and integrity data for reproducible installations.
<code>package.json</code>	React UI dependencies, frontend scripts and local API proxy configuration.
<code>postcss.config.js</code>	CSS transformation plugin configuration.
<code>tailwind.config.js</code>	Tailwind theme tokens and stylesheet source scanning.

frontend/plugins/health-check/

Name / source	Task performed / feature brief
<code>health-endpoints.js</code>	HTTP health endpoint helpers for frontend development tooling.
<code>webpack-health-plugin.js</code>	Build/development health-check plugin integrated with webpack.

frontend/public/

Name / source	Task performed / feature brief
apple-touch-icon.png	Brand icon for browser tabs, shortcuts or home-screen use at the indicated size.
favicon-16x16.png	Brand icon for browser tabs, shortcuts or home-screen use at the indicated size.
favicon-192x192.png	Brand icon for browser tabs, shortcuts or home-screen use at the indicated size.
favicon-32x32.png	Brand icon for browser tabs, shortcuts or home-screen use at the indicated size.
favicon-48x48.png	Brand icon for browser tabs, shortcuts or home-screen use at the indicated size.
favicon-512x512.png	Brand icon for browser tabs, shortcuts or home-screen use at the indicated size.
favicon.ico	Brand icon for browser tabs, shortcuts or home-screen use at the indicated size.
index.html	HTML shell into which the React application is mounted.
robots.txt	Instructions for search-engine crawlers.
site.webmanifest	Browser application metadata and icon references; does not establish offline support.

frontend/public/images/

Name / source	Task performed / feature brief
biswa-bangla-hero-mobile.webp	Biswa bangla hero: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
biswa-bangla-hero.png	Biswa bangla hero: original image asset for property/brand/location visuals. Usage depends on component references.
biswa-bangla-hero.webp	Biswa bangla hero: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
biswa-bangla-newtown-mobile.webp	Biswa bangla newtown: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
biswa-bangla-newtown.png	Biswa bangla newtown: original image asset for property/brand/location visuals. Usage depends on component references.
biswa-bangla-newtown.webp	Biswa bangla newtown: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
city-centre-2-rajarhat-mobile.webp	City centre 2 rajarhat: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
city-centre-2-rajarhat.png	City centre 2 rajarhat: original image asset for property/brand/location visuals. Usage depends on component references.
city-centre-2-rajarhat.webp	City centre 2 rajarhat: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
eco-park-kolkata-mobile.webp	Eco park kolkata: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
eco-park-kolkata.png	Eco park kolkata: original image asset for property/brand/location visuals. Usage depends on component references.
eco-park-kolkata.webp	Eco park kolkata: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
howrah-bridge-mobile.webp	Howrah bridge: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
howrah-bridge.png	Howrah bridge: original image asset for property/brand/location visuals. Usage depends on component references.
howrah-bridge.webp	Howrah bridge: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
new-town-skyline-mobile.webp	New town skyline: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
new-town-skyline.png	New town skyline: original image asset for property/brand/location visuals. Usage depends on component references.
new-town-skyline.webp	New town skyline: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
victoria-memorial-mobile.webp	Victoria memorial: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.

Name / source	Task performed / feature brief
victoria-memorial.png	Victoria memorial: original image asset for property/brand/location visuals. Usage depends on component references.
victoria-memorial.webp	Victoria memorial: desktop WebP asset for property/brand/location visuals. Usage depends on component references.

frontend/public/images/luxe/

Name / source	Task performed / feature brief
biswa_bangla_gate-mobile.webp	Biswa bangla gate: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
biswa_bangla_gate.jpg	Biswa bangla gate: original image asset for property/brand/location visuals. Usage depends on component references.
biswa_bangla_gate.webp	Biswa bangla gate: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
howrah_bridge-mobile.webp	Howrah bridge: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
howrah_bridge.jpg	Howrah bridge: original image asset for property/brand/location visuals. Usage depends on component references.
howrah_bridge.webp	Howrah bridge: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
locations_kolkata-mobile.webp	Locations kolkata: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
locations_kolkata.jpg	Locations kolkata: original image asset for property/brand/location visuals. Usage depends on component references.
locations_kolkata.webp	Locations kolkata: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
locations_newtown-mobile.webp	Locations newtown: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
locations_newtown.jpg	Locations newtown: original image asset for property/brand/location visuals. Usage depends on component references.
locations_newtown.webp	Locations newtown: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
locations_rajarhat-mobile.webp	Locations rajarhat: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
locations_rajarhat.jpg	Locations rajarhat: original image asset for property/brand/location visuals. Usage depends on component references.
locations_rajarhat.webp	Locations rajarhat: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
luxury_villa-mobile.webp	Luxury villa: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
luxury_villa.jpg	Luxury villa: original image asset for property/brand/location visuals. Usage depends on component references.
luxury_villa.webp	Luxury villa: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
new_town_skyline-mobile.webp	New town skyline: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.

Name / source	Task performed / feature brief
<code>new_town_skyline.jpg</code>	New town skyline: original image asset for property/brand/location visuals. Usage depends on component references.
<code>new_town_skyline.webp</code>	New town skyline: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
<code>property_heritage_estate-mobile.webp</code>	Property heritage estate: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
<code>property_heritage_estate.jpg</code>	Property heritage estate: original image asset for property/brand/location visuals. Usage depends on component references.
<code>property_heritage_estate.webp</code>	Property heritage estate: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
<code>property_tower-mobile.webp</code>	Property tower: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
<code>property_tower.jpg</code>	Property tower: original image asset for property/brand/location visuals. Usage depends on component references.
<code>property_tower.webp</code>	Property tower: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
<code>property_villa_garden-mobile.webp</code>	Property villa garden: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
<code>property_villa_garden.jpg</code>	Property villa garden: original image asset for property/brand/location visuals. Usage depends on component references.
<code>property_villa_garden.webp</code>	Property villa garden: desktop WebP asset for property/brand/location visuals. Usage depends on component references.
<code>victoria_memorial-mobile.webp</code>	Victoria memorial: mobile-optimized WebP asset for property/brand/location visuals. Usage depends on component references.
<code>victoria_memorial.jpg</code>	Victoria memorial: original image asset for property/brand/location visuals. Usage depends on component references.
<code>victoria_memorial.webp</code>	Victoria memorial: desktop WebP asset for property/brand/location visuals. Usage depends on component references.

frontend/src/

Name / source	Task performed / feature brief
<code>App.css</code>	Application-level CSS rules layered over the global styles.
<code>App.js</code>	Root route map, lazy page loading, public/admin layouts, protected routes, authentication provider and toast/SEO providers.
<code>index.css</code>	Global styling, brand typography, utility rules and visual design foundation.
<code>index.js</code>	Browser entry point that mounts the React application.

frontend/src/components/

Name / source	Task performed / feature brief
AmbientGlow.jsx	Reusable decorative ambient background treatment.
CinematicHero.jsx	Homepage cinematic image slideshow and hero presentation.
ExpansionRoadmap.jsx	Presents geographic expansion/brand roadmap content; not an operational expansion tracking system.
FloatingWhatsApp.jsx	Persistent WhatsApp contact shortcut.
Footer.jsx	Shared footer with brand, navigation and contact information.
Header.jsx	Public navigation and responsive header.
LeadForm.jsx	Reusable consultation/contact/property enquiry forms, submission state, validation feedback and POST /api/leads calls.
LuxImage.jsx	Responsive picture wrapper selecting desktop/mobile WebP siblings with original-image fallback and lazy/eager loading.
PropertyCard.jsx	Reusable property summary card linking into listing details.
ProtectedRoute.jsx	Restricts frontend navigation to authenticated users and optional allowed roles; backend authorization remains necessary.
ScrollToTop.jsx	Resets scroll position on client-side route navigation.
Seo.jsx	Per-page metadata and search/social presentation support.

frontend/src/components/admin/

Name / source	Task performed / feature brief
AdminPageHeader.jsx	Reusable title/action header for admin pages.
StatusBadge.jsx	Consistent visual labels for administrative record statuses.

frontend/src/components/ui/

Name / source	Task performed / feature brief
accordion.jsx	Reusable accordion UI primitive/wrapper. Library availability does not mean it is used on every page.
alert-dialog.jsx	Reusable alert dialog UI primitive/wrapper. Library availability does not mean it is used on every page.
alert.jsx	Reusable alert UI primitive/wrapper. Library availability does not mean it is used on every page.
aspect-ratio.jsx	Reusable aspect ratio UI primitive/wrapper. Library availability does not mean it is used on every page.
avatar.jsx	Reusable avatar UI primitive/wrapper. Library availability does not mean it is used on every page.
badge.jsx	Reusable badge UI primitive/wrapper. Library availability does not mean it is used on every page.
breadcrumb.jsx	Reusable breadcrumb UI primitive/wrapper. Library availability does not mean it is used on every page.
button.jsx	Reusable button UI primitive/wrapper. Library availability does not mean it is used on every page.
calendar.jsx	Reusable calendar UI primitive/wrapper. Library availability does not mean it is used on every page.
card.jsx	Reusable card UI primitive/wrapper. Library availability does not mean it is used on every page.
carousel.jsx	Reusable carousel UI primitive/wrapper. Library availability does not mean it is used on every page.
checkbox.jsx	Reusable checkbox UI primitive/wrapper. Library availability does not mean it is used on every page.
collapsible.jsx	Reusable collapsible UI primitive/wrapper. Library availability does not mean it is used on every page.
command.jsx	Reusable command UI primitive/wrapper. Library availability does not mean it is used on every page.
context-menu.jsx	Reusable context menu UI primitive/wrapper. Library availability does not mean it is used on every page.
dialog.jsx	Reusable dialog UI primitive/wrapper. Library availability does not mean it is used on every page.
drawer.jsx	Reusable drawer UI primitive/wrapper. Library availability does not mean it is used on every page.
dropdown-menu.jsx	Reusable dropdown menu UI primitive/wrapper. Library availability does not mean it is used on every page.
form.jsx	Reusable form UI primitive/wrapper. Library availability does not mean it is used on every page.

Name / source	Task performed / feature brief
hover-card.jsx	Reusable hover card UI primitive/wrapper. Library availability does not mean it is used on every page.
input-otp.jsx	Reusable input otp UI primitive/wrapper. Library availability does not mean it is used on every page.
input.jsx	Reusable input UI primitive/wrapper. Library availability does not mean it is used on every page.
label.jsx	Reusable label UI primitive/wrapper. Library availability does not mean it is used on every page.
menubar.jsx	Reusable menubar UI primitive/wrapper. Library availability does not mean it is used on every page.
navigation-menu.jsx	Reusable navigation menu UI primitive/wrapper. Library availability does not mean it is used on every page.
pagination.jsx	Reusable pagination UI primitive/wrapper. Library availability does not mean it is used on every page.
popover.jsx	Reusable popover UI primitive/wrapper. Library availability does not mean it is used on every page.
progress.jsx	Reusable progress UI primitive/wrapper. Library availability does not mean it is used on every page.
radio-group.jsx	Reusable radio group UI primitive/wrapper. Library availability does not mean it is used on every page.
resizable.jsx	Reusable resizable UI primitive/wrapper. Library availability does not mean it is used on every page.
scroll-area.jsx	Reusable scroll area UI primitive/wrapper. Library availability does not mean it is used on every page.
select.jsx	Reusable select UI primitive/wrapper. Library availability does not mean it is used on every page.
separator.jsx	Reusable separator UI primitive/wrapper. Library availability does not mean it is used on every page.
sheet.jsx	Reusable sheet UI primitive/wrapper. Library availability does not mean it is used on every page.
skeleton.jsx	Reusable skeleton UI primitive/wrapper. Library availability does not mean it is used on every page.
slider.jsx	Reusable slider UI primitive/wrapper. Library availability does not mean it is used on every page.
sonner.jsx	Reusable sonner UI primitive/wrapper. Library availability does not mean it is used on every page.
switch.jsx	Reusable switch UI primitive/wrapper. Library availability does not mean it is used on every page.

Name / source	Task performed / feature brief
<code>table.jsx</code>	Reusable table UI primitive/wrapper. Library availability does not mean it is used on every page.
<code>tabs.jsx</code>	Reusable tabs UI primitive/wrapper. Library availability does not mean it is used on every page.
<code>textarea.jsx</code>	Reusable textarea UI primitive/wrapper. Library availability does not mean it is used on every page.
<code>toast.jsx</code>	Reusable toast UI primitive/wrapper. Library availability does not mean it is used on every page.
<code>toaster.jsx</code>	Reusable toaster UI primitive/wrapper. Library availability does not mean it is used on every page.
<code>toggle-group.jsx</code>	Reusable toggle group UI primitive/wrapper. Library availability does not mean it is used on every page.
<code>toggle.jsx</code>	Reusable toggle UI primitive/wrapper. Library availability does not mean it is used on every page.
<code>tooltip.jsx</code>	Reusable tooltip UI primitive/wrapper. Library availability does not mean it is used on every page.

frontend/src/constants/

Name / source	Task performed / feature brief
<code>siteData.js</code>	Reusable site data and option lists for website content.
<code>testIds.js</code>	Shared test-selector constants or compatibility exports for UI automation.

frontend/src/constants/testIds/

Name / source	Task performed / feature brief
<code>auth.js</code>	Stable test identifiers for authentication elements.
<code>home.js</code>	Stable test identifiers for homepage elements.
<code>index.js</code>	Exports grouped test-selector constants.

frontend/src/context/

Name / source	Task performed / feature brief
<code>AuthContext.jsx</code>	Shares logged-in user state and login/logout/session lifecycle with React components.

frontend/src/data/

Name / source	Task performed / feature brief
evergreenNews.js	Bundled editorial fallback articles shown when live/cached market news is unavailable or has no matching results.

frontend/src/hooks/

Name / source	Task performed / feature brief
use-toast.js	Reusable toast notification state and actions for the component system.

frontend/src/layouts/

Name / source	Task performed / feature brief
AdminLayout.jsx	Shared admin navigation and content outlet for staff workflows.
PublicLayout.jsx	Shared public-page shell with navigation, footer and site-wide presentation components.

frontend/src/lib/

Name / source	Task performed / feature brief
api.js	Axios client: /api URL selection, cookies, local-storage Bearer fallback, 30-second timeout, readable errors and file URL generation.
formatters.js	Formats Indian-locale dates and relative time, strips HTML text, and generates URL slugs.
sanitize.js	DOMPurify allowlist for blog HTML; hardens links opening new browser tabs.
site.js	Shared brand/contact/site constants consumed by the interface.
utils.js	Shared utility for composing and merging UI class names.

frontend/src/pages/

Name / source	Task performed / feature brief
AboutPage.jsx	Brand story and real estate advisory positioning.
BlogDetailPage.jsx	Loads an article by slug and displays sanitized HTML plus article metadata.
BlogsListPage.jsx	Published editorial/blog listing with links to articles.
ContactPage.jsx	Office/contact information and enquiry form.
HomePage.jsx	Brand landing page, featured properties, location/brand sections and consultation lead capture.
MarketIntelligencePage.jsx	Trending news and geographic/category filtering with live API requests and bundled fallback content.
PropertiesPage.jsx	Property catalogue with URL-based filters for location, type, budget, builder, availability and category; responsive filter controls.
PropertyDetailPage.jsx	Property gallery, pricing, location, specifications, amenities and property-specific enquiry submission.

frontend/src/pages/admin/

Name / source	Task performed / feature brief
AdminBlogFormPage.jsx	Creates/edits blog HTML, slug, image and SEO fields with preview and upload support.
AdminBlogsPage.jsx	Lists editorial content, changes publication status and deletes permitted records.
AdminDashboardPage.jsx	Loads API statistics for properties, leads and users.
AdminLeadsPage.jsx	Lead inbox, enquiry details, status changes and permitted deletion.
AdminLoginPage.jsx	Staff email/password login and validation feedback.
AdminPropertiesPage.jsx	Staff property listing with publication-state changes and permitted deletion.
AdminPropertyFormPage.jsx	Creates/edits property content, image uploads, amenities and publication details.
AdminUsersPage.jsx	Admin-only staff account creation, role selection and account deletion.

memory/

Name / source	Task performed / feature brief
.gitkeep	Empty placeholder preserving this directory in version control.
PRD.md	Product requirements and accumulated project decisions; intent/history rather than proof of deployed behavior.

scripts/

Name / source	Task performed / feature brief
<code>optimize_images.py</code>	Generates desktop and mobile WebP assets from original website images.
<code>test_db_connection.js</code>	Node database connectivity diagnostic invoked by the root npm test command.
<code>test_server_api.js</code>	Express integration checks for health, API root, authentication/404 behavior and SPA fallback.

test_reports/

Name / source	Task performed / feature brief
<code>.gitkeep</code>	Empty placeholder preserving this directory in version control.
<code>iteration_1.json</code>	Historical iteration 1 QA report: findings and handoff notes; not fresh verification.
<code>iteration_10.json</code>	Historical iteration 10 QA report: findings and handoff notes; not fresh verification.
<code>iteration_11.json</code>	Historical iteration 11 QA report: findings and handoff notes; not fresh verification.
<code>iteration_12.json</code>	Historical iteration 12 QA report: findings and handoff notes; not fresh verification.
<code>iteration_13.json</code>	Historical iteration 13 QA report: findings and handoff notes; not fresh verification.
<code>iteration_14.json</code>	Historical iteration 14 QA report: findings and handoff notes; not fresh verification.
<code>iteration_2.json</code>	Historical iteration 2 QA report: findings and handoff notes; not fresh verification.
<code>iteration_3.json</code>	Historical iteration 3 QA report: findings and handoff notes; not fresh verification.
<code>iteration_4.json</code>	Historical iteration 4 QA report: findings and handoff notes; not fresh verification.
<code>iteration_5.json</code>	Historical iteration 5 QA report: findings and handoff notes; not fresh verification.
<code>iteration_6.json</code>	Historical iteration 6 QA report: findings and handoff notes; not fresh verification.
<code>iteration_7.json</code>	Historical iteration 7 QA report: findings and handoff notes; not fresh verification.
<code>iteration_8.json</code>	Historical iteration 8 QA report: findings and handoff notes; not fresh verification.
<code>iteration_9.json</code>	Historical iteration 9 QA report: findings and handoff notes; not fresh verification.

test_reports/pytest/

Name / source	Task performed / feature brief
.gitkeep	Empty placeholder preserving this directory in version control.
aramya_results.xml	Saved pytest/JUnit results for aramya results. Historical evidence only.
blogs_iter13.xml	Saved pytest/JUnit results for blogs iter13. Historical evidence only.
blogs_results.xml	Saved pytest/JUnit results for blogs results. Historical evidence only.
performance_results.xml	Saved pytest/JUnit results for performance results. Historical evidence only.
pytest_results.xml	Saved pytest/JUnit results for pytest results. Historical evidence only.

tests/

Name / source	Task performed / feature brief
__init__.py	Python package marker; enables package/module organization.

5. Registered route inventory

Routes below are extracted from configured entry-point source. Python `api_router` routes receive the `/api` prefix; decorators attached directly to app retain their literal path. This lists declarations, not successful endpoint tests.

Node / Express

Method and path	Source reference
GET <code>"/healthz"</code>	server.js:271
GET <code>"/api", "/api/"</code>	server.js:280
POST <code>"/api/auth/login"</code>	server.js:287
POST <code>"/api/auth/logout"</code>	server.js:326
GET <code>"/api/auth/me"</code>	server.js:331
POST <code>"/api/auth/refresh"</code>	server.js:340
GET <code>"/api/properties"</code>	server.js:372
GET <code>"/api/properties/:id"</code>	server.js:466
GET <code>"/api/blogs"</code>	server.js:488
GET <code>"/api/blogs/:slug"</code>	server.js:505
POST <code>"/api/leads"</code>	server.js:530
GET <code>"/api/admin/properties"</code>	server.js:571
GET <code>"/api/admin/properties/:id"</code>	server.js:581
POST <code>"/api/admin/properties"</code>	server.js:592
PUT <code>"/api/admin/properties/:id"</code>	server.js:604
PATCH <code>"/api/admin/properties/:id/status"</code>	server.js:620
DELETE <code>"/api/admin/properties/:id"</code>	server.js:637
GET <code>"/api/admin/blogs"</code>	server.js:651
GET <code>"/api/admin/blogs/:id"</code>	server.js:661
POST <code>"/api/admin/blogs"</code>	server.js:672
PUT <code>"/api/admin/blogs/:id"</code>	server.js:697
PATCH <code>"/api/admin/blogs/:id/status"</code>	server.js:713
DELETE <code>"/api/admin/blogs/:id"</code>	server.js:737
GET <code>"/api/admin/leads"</code>	server.js:751
PATCH <code>"/api/admin/leads/:id"</code>	server.js:778
DELETE <code>"/api/admin/leads/:id"</code>	server.js:792
GET <code>"/api/admin/stats"</code>	server.js:803

Method and path	Source reference
GET <code>"/api/users"</code>	server.js:828
POST <code>"/api/users"</code>	server.js:846
DELETE <code>"/api/users/:id"</code>	server.js:875
GET <code>"/api/news/trending"</code>	server.js:890
GET <code>"/api/news/all"</code>	server.js:900
ALL <code>"/api/*", "/healthz/*"</code>	server.js:932
GET <code>"*"</code>	server.js:941

Python / FastAPI

Method and path	Source reference
GET /	backend/server.py:316
GET /healthz	backend/server.py:317
GET /api/sitemap.xml	backend/server.py:334
POST /api/auth/login	backend/server.py:390
POST /api/auth/logout	backend/server.py:427
GET /api/auth/me	backend/server.py:434
POST /api/auth/refresh	backend/server.py:444
GET /api/users	backend/server.py:465
POST /api/users	backend/server.py:476
DELETE /api/users/{user_id}	backend/server.py:495
GET /api/properties	backend/server.py:578
GET /api/properties/{prop_id}	backend/server.py:668
GET /api/admin/properties	backend/server.py:679
GET /api/admin/properties/{prop_id}	backend/server.py:685
POST /api/admin/properties	backend/server.py:696
PUT /api/admin/properties/{prop_id}	backend/server.py:706
PATCH /api/admin/properties/{prop_id}/status	backend/server.py:717
DELETE /api/admin/properties/{prop_id}	backend/server.py:731
POST /api/leads	backend/server.py:770
GET /api/admin/leads	backend/server.py:790
PATCH /api/admin/leads/{lead_id}	backend/server.py:826
POST /api/admin/leads/{lead_id}/crm-retry	backend/server.py:837
DELETE /api/admin/leads/{lead_id}	backend/server.py:857
GET /api/blogs	backend/server.py:927
GET /api/blogs/{slug}	backend/server.py:936
GET /api/admin/blogs	backend/server.py:944
GET /api/admin/blogs/{blog_id}	backend/server.py:950

Method and path	Source reference
POST /api/admin/blogs	backend/server.py:961
PUT /api/admin/blogs/{blog_id}	backend/server.py:975
PATCH /api/admin/blogs/{blog_id}/status	backend/server.py:990
DELETE /api/admin/blogs/{blog_id}	backend/server.py:1007
POST /api/admin/upload	backend/server.py:1022
GET /api/files/{path:path}	backend/server.py:1046
GET /api/admin/stats	backend/server.py:1068
GET /api/	backend/server.py:1080
GET /api/news/trending	backend/server.py:1086
GET /api/news/all	backend/server.py:1092
GET /api/news/group/{group}	backend/server.py:1100
GET /api/news/topics	backend/server.py:1108
GET /api/news/debug	backend/server.py:1113
POST /api/admin/news/refresh	backend/server.py:1149

6. Verification evidence and follow-up work

The tests below already existed in the workspace. They were read, not run. Some suites submit records or rely on a configured remote backend; running them was outside this documentation task.

Name / source	Task performed / feature brief
backend/tests/backend_test.py	General API/authentication/property/lead regression suite. Test code exists; not executed for this report.
backend/tests/test_aramya_leads.py	Aramya campaign lead submission and CRM-related regression checks. Test code exists; not executed for this report.
backend/tests/test_blogs.py	Public/admin blog lifecycle tests. Test code exists; not executed for this report.
backend/tests/test_market_intelligence.py	Market news feeds and classification checks. Test code exists; not executed for this report.
backend/tests/test_performance.py	Backend performance-related regression checks. Test code exists; not executed for this report.
scripts/test_db_connection.js	Node database connectivity diagnostic invoked by the root npm test command.
scripts/test_server_api.js	Express integration checks for health, API root, authentication/404 behavior and SPA fallback.

Saved pytest result summaries

Name / source	Task performed / feature brief
aramya_results.xml	tests: 5, failures: 0, errors: 0, skipped: 0. Saved report only.
blogs_iter13.xml	tests: 12, failures: 2, errors: 0, skipped: 0. Saved report only.
blogs_results.xml	tests: 12, failures: 0, errors: 0, skipped: 0. Saved report only.
performance_results.xml	tests: 8, failures: 0, errors: 0, skipped: 1. Saved report only.
pytest_results.xml	tests: 5, failures: 0, errors: 0, skipped: 0. Saved report only.

Specific gaps and maintenance priorities

Name / source	Task performed / feature brief
Choose and document the active backend	Resolve whether production should use Node or Python, then verify every frontend API dependency against that implementation. This directly affects uploads, CRM, sitemap and news.
Resolve duplicate Python implementations	Either wire the modular routers into an entry point with regression validation or clearly mark their status. Maintaining two copies of route logic invites inconsistent fixes.
Confirm campaign page availability	Saved reports and test_aramya_leads.py reference /aramya/index.html, but no such page is present in this inventoried checkout. Do not describe it as a current delivered page without locating its source/deployment.
Update project documentation	Replace the root README placeholder with setup/runtime guidance and bring ARCHITECTURE.md into line with the current code and environment variables.
Validate operational configuration	Before claiming readiness, confirm database, JWT/admin settings, allowed origins, storage and CRM configuration for the selected runtime. Default credential/secret fallbacks are visible in source; their actual deployment values were not inspected.
Perform fresh verification	Run relevant API/UI checks against a designated test environment, including uploads, login, publication, lead persistence, CRM outcomes and news fallback. Saved success percentages are not current evidence.
Confirm backup coverage	The supplied dump lists users, properties, leads, files, login_attempts and news_cache artifacts; no blog collection dump is present. Review required backup coverage and perform a controlled restore test.

Scope and interpretation

This report describes responsibilities, not the identity of whoever wrote each file, time spent, or task completion history. Those require version history and project-management evidence. Image subjects are inferred from asset names; binary image content and BSON records were not individually audited. UI primitives are listed as available components without claiming each is currently imported.

Source basis: this local checkout on 11 September 2026; source paths and API declaration line references are provided for traceability. No external deployment or website was inspected.