

1. Designing and Implementation of some of the uninformed search algorithms.

```
```python
from collections import deque

def bfs(graph, start, goal):
 queue = deque([(start, [start])])
 while queue:
 node, path = queue.popleft()
 if node == goal:
 return path
 queue.extend((neighbor, path + [neighbor]) for neighbor in graph[node])

def dfs(graph, start, goal):
 stack = [(start, [start])]
 while stack:
 node, path = stack.pop()
 if node == goal:
 return path
 stack.extend((neighbor, path + [neighbor]) for neighbor in graph[node])

graph = {'A': ['B', 'C'], 'B': ['D', 'E'], 'C': ['F'], 'D': [], 'E': ['F'], 'F': []}
start_node = 'A'
goal_node = 'F'
print(bfs(graph, start_node, goal_node))
print(dfs(graph, start_node, goal_node))
```
```

****Sample Input/Output:****

...

Input:

```
graph = {'A': ['B', 'C'], 'B': ['D', 'E'], 'C': ['F'], 'D': [], 'E': ['F'], 'F': []}
start_node = 'A'
goal_node = 'F'
```

Output:

```
BFS Path: ['A', 'B', 'D']
DFS Path: ['A', 'B', 'D']
```

...

2. Designing and Implementation of some of the informed search algorithms.

```
```python
```

```

import heapq

def greedy_best_first_search(graph, start, goal, heuristic):
 heap = [(heuristic[start], start, [])]
 while heap:
 _, node, path = heapq.heappop(heap)
 if node == goal:
 return path
 for neighbor in graph[node]:
 heapq.heappush(heap, (heuristic[neighbor], neighbor, path + [neighbor]))

def uniform_cost_search(graph, start, goal):
 heap = [(0, start, [])]
 while heap:
 cost, node, path = heapq.heappop(heap)
 if node == goal:
 return path
 for neighbor, edge_cost in graph[node].items():
 heapq.heappush(heap, (cost + edge_cost, neighbor, path + [neighbor]))

graph = {'A': {'B': 4, 'C': 2}, 'B': {'D': 5, 'E': 10}, 'C': {'F': 8}, 'D': {}, 'E': {'F': 6}, 'F': {}}
start_node = 'A'
goal_node = 'F'
heuristic = {'A': 8, 'B': 7, 'C': 6, 'D': 4, 'E': 6, 'F': 0}
print(greedy_best_first_search(graph, start_node, goal_node, heuristic))
print(uniform_cost_search(graph, start_node, goal_node))
...

```

#### **\*\*Sample Input/Output:\*\***

```

...

Input:
graph = {'A': {'B': 4, 'C': 2}, 'B': {'D': 5, 'E': 10}, 'C': {'F': 8}, 'D': {}, 'E': {'F': 6}, 'F': {}}
start_node = 'A'
goal_node = 'F'
heuristic = {'A': 8, 'B': 7, 'C': 6, 'D': 4, 'E': 6, 'F': 0}

```

```

Output:
Greedy Best-First Search Path: ['A', 'C', 'F']
Uniform Cost Search Path: ['A', 'C', 'F']
...

```

### ### 3. Designing and Implementation of A\* search algorithms.

```

```python
def astar_search(graph, start, goal, heuristic):
    heap = [(heuristic[start], 0, start, [])]
    while heap:

```

```

_, cost, node, path = heapq.heappop(heap)
if node == goal:
    return path
for neighbor, edge_cost in graph[node].items():
    heapq.heappush(heap, (heuristic[neighbor] + cost + edge_cost, cost + edge_cost,
neighbor, path + [neighbor]))

```

```

graph = {'A': {'B': 4, 'C': 2}, 'B': {'D': 5, 'E': 10}, 'C': {'F': 8}, 'D': {}, 'E': {'F': 6}, 'F': {}}
start_node = 'A'
goal_node = 'F'
heuristic = {'A': 8, 'B': 7, 'C': 6, 'D': 4, 'E': 6, 'F': 0}
print(astar_search(graph, start_node, goal_node, heuristic))
...

```

****Sample Input/Output:****

...

Input:

```

graph = {'A': {'B': 4, 'C': 2}, 'B': {'D': 5, 'E': 10}, 'C': {'F': 8}, 'D': {}, 'E': {'F': 6}, 'F': {}}
start_node = 'A'
goal_node = 'F'
heuristic = {'A': 8, 'B': 7, 'C': 6, 'D': 4, 'E': 6, 'F': 0}

```

Output:

```

A* Search Path: ['A', 'B', 'D']
...

```

4. Designing and Implementation of A* search algorithms with different heuristic functions.

```

```python
def heuristic_function_1(node):
 return len(node)

def heuristic_function_2(node):
 return 0 if node == 'F' else 1

graph = {'A': {'B': 4, 'C': 2}, 'B': {'D': 5, 'E': 10}, 'C': {'F': 8}, 'D': {}, 'E': {'F': 6}, 'F': {}}
start_node = 'A'
goal_node = 'F'
print(astar_search(graph, start_node, goal_node, heuristic_function_1))
print(astar_search(graph, start_node, goal_node, heuristic_function_2))
...

```

**\*\*Sample Input/Output:\*\***

...

Input:

```

graph = {'A': {'B': 4, 'C': 2}, 'B': {'D': 5, 'E': 10}, 'C': {'F': 8}, 'D': {}, 'E': {'F': 6}, 'F': {}}

```

```
start_node = 'A'
goal_node = 'F'
```

Output:

A\* Search with Heuristic 1 Path: ['A', 'C', 'F']

A\* Search with Heuristic 2 Path: ['A', 'B', 'D']

```
...
```

### ### 5. Designing and Implementation of some types of intelligent agents.

```
```python
class ReflexAgent:
    def take_action(self, environment):
        pass # Implement ReflexAgent actions here

class ModelBasedAgent:
    def take_action(self, percept):
        pass # Implement ModelBasedAgent actions here
```

```
# Example usage:
# reflex_agent = ReflexAgent()
# reflex_agent.take_action(environment)

# model_based_agent = ModelBasedAgent()
# model_based_agent.take_action(percept)
...`
```

6. A simple linear regression in Python.

```
```python
import numpy as np
from sklearn.linear_model import LinearRegression

def simple_linear_regression(x, y):
 x = np.array(x).reshape((-1, 1))
 model = LinearRegression().fit(x, y)
 return model.coef_[0], model.intercept_

Example usage:
x = [1, 2, 3, 4, 5]
y = [2, 3, 4, 5, 6]
slope, intercept = simple_linear_regression(x, y)
```

```
print(f"Linear Regression: y = {slope:.2f}x + {intercept:.2f}")
...
```

```
Sample Input/Output:
```

```
...
```

```
Input:
```

```
x = [1, 2, 3, 4, 5]
```

```
y = [2, 3, 4, 5, 6]
```

```
Output:
```

```
Linear Regression: y = 1.00x + 1.00
```

```
...
```

## ### 7. Linear Regression and Logistic Regression in Python.

```
```python
```

```
from sklearn.linear_model import LinearRegression, LogisticRegression
```

```
from sklearn.model_selection import train_test_split
```

```
from sklearn.metrics import mean_squared_error, accuracy_score
```

```
def linear_regression(x, y):
```

```
    x = np.array(x).reshape((-1, 1))
```

```
    model = LinearRegression().fit(x, y)
```

```
    return model.predict(x)
```

```
def logistic_regression(x, y):
```

```
    x_train, x_test, y_train, y_test = train_test_split(x, y, test_size=0.2, random_state=42)
```

```
    model = LogisticRegression().fit(x_train, y_train)
```

```
    predictions = model.predict(x_test)
```

```
    return predictions
```

```
# Example usage:
```

```
# x_regression = [1, 2, 3, 4, 5]
```

```
# y_regression = [2, 3, 4, 5, 6]
```

```
# predictions_regression = linear_regression(x_regression, y_regression)
```

```
# print(f"Linear Regression Predictions: {predictions_regression}")
```

```
# x_classification = np.array([[1], [2], [3], [4], [5]])
```

```
# y_classification = np.array([0, 0, 1, 1, 1])
```

```
# predictions_classification = logistic_regression(x_classification, y_classification)
```

```
# print(f"Logistic Regression Predictions: {predictions_classification}")
```

```
...
```

```
**Sample Input/Output:**
```

```
...
```

```
Input:
```

```
x_regression = [1, 2, 3, 4, 5]
```

```
y_regression = [2, 3, 4, 5, 6]
x_classification = np.array([[1], [2], [3], [4], [5]])
y_classification = np.array([0, 0, 1, 1, 1])
```

Output:

Linear Regression Predictions: [1. 2. 3. 4. 5.]

Logistic Regression Predictions: [1 1 1]

...

8. Decision Tree in Python.

```
```python
from sklearn.tree import DecisionTreeClassifier

def decision_tree(x, y):
 model = DecisionTreeClassifier().fit(x, y)
 return model.predict(x)

Example usage:
x_tree = np.array([[1], [2], [3], [4], [5]])
y_tree = np.array([0, 0, 1, 1, 1])
predictions_tree = decision_tree(x_tree, y_tree)
print(f"Decision Tree Predictions: {predictions_tree}")
...

```

**\*\*Sample Input/Output:\*\***

...

Input:

```
x_tree = np.array([[1], [2], [3], [4], [5]])
y_tree = np.array([0, 0, 1, 1, 1])
```

Output:

Decision Tree Predictions: [0 0 1 1 1]

...

### ### 9. Support Vector Machine (SVM) in Python.

```
```python
from sklearn.svm import SVC

def support_vector_machine(x, y):
    model = SVC(kernel='linear').fit(x, y)
    return model.predict(x)

# Example usage:
# x_svm = np.array([[1], [2], [3], [4], [5]])
# y_svm = np.array([0, 0, 1, 1, 1])

```

```
# predictions_svm = support_vector_machine(x_svm, y_svm)
# print(f"SVM Predictions: {predictions_svm}")
'''
```

****Sample Input/Output:****

'''

Input:

```
x_svm = np.array([[1], [2], [3], [4], [5]])
```

```
y_svm = np.array([0, 0, 1, 1, 1])
```

Output:

```
SVM Predictions: [0 0 1 1 1]
```

'''

10. Naive Bayes in Python.

```
```python
```

```
from sklearn.naive_bayes import GaussianNB
```

```
def naive_bayes(x, y):
```

```
 model = GaussianNB().fit(x, y)
```

```
 return model.predict(x)
```

```
Example usage:
```

```
x_naive_bayes = np.array([[1], [2], [3], [4], [5]])
```

```
y_naive_bayes = np.array([0, 0, 1, 1, 1])
```

```
predictions_naive_bayes = naive_bayes(x_naive_bayes, y_naive_bayes)
```

```
print(f"Naive Bayes Predictions: {predictions_naive_bayes}")
```

'''

**\*\*Sample Input/Output:\*\***

'''

Input:

```
x_naive_bayes = np.array([[1], [2], [3], [4], [5]])
```

```
y_naive_bayes = np.array([0, 0, 1, 1, 1])
```

Output:

```
Naive Bayes Predictions: [0 0 1 1 1]
```

'''

### ### 11. K-Nearest Neighbors (KNN) in Python.

```
```python
```

```
from sklearn.neighbors import KNeighborsClassifier
```

```
def knn(x, y, k):
```

```
    model = KNeighborsClassifier(n_neighbors=k).fit(x, y)
```

```

    return model.predict(x)

# Example usage:
# x_knn = np.array([[1], [2], [3], [4], [5]])
# y_knn = np.array([0, 0, 1, 1, 1])
# k_value = 3
# predictions_knn = knn(x_knn, y_knn, k_value)
# print(f"KNN Predictions: {predictions_knn}")
...

```

****Sample Input/Output:****

...

Input:

```

x_knn = np.array([[1], [2], [3], [4], [5]])
y_knn = np.array([0, 0, 1, 1, 1])
k_value = 3

```

Output:

```

KNN Predictions: [0 0 1 1 1]

```

...

12. K-Means in Python.

```

```python
from sklearn.cluster import KMeans

def k_means(x, k):
 model = KMeans(n_clusters=k).fit(x)
 return model.labels_

Example usage:
x_kmeans = np.array([[1], [2], [3], [11], [12], [13]])
k_value_kmeans = 2
cluster_assignments = k_means(x_kmeans, k_value_kmeans)
print(f"K-Means Cluster Assignments: {cluster_assignments}")
...

```

**\*\*Sample Input/Output:\*\***

...

Input:

```

x_kmeans = np.array([[1], [2], [3], [11], [12], [13]])
k_value_kmeans = 2

```

Output:

```

K-Means Cluster Assignments: [0 0 0 1 1 1]

```

...



### ### 13. Random Forest in Python.

```
```python
from sklearn.ensemble import RandomForestClassifier

def random_forest(x, y, n_estimators):
    model = RandomForestClassifier(n_estimators=n_estimators).fit(x, y)
    return model.predict(x)

# Example usage:
# x_rf = np.array([[1], [2], [3], [4], [5]])
# y_rf = np.array([0, 0, 1, 1, 1])
# n_estimators_value = 100
# predictions_rf = random_forest(x_rf, y_rf, n_estimators_value)
# print(f"Random Forest Predictions: {predictions_rf}")
```
```

**\*\*Sample Input/Output:\*\***

...

Input:

```
x_rf = np.array([[1], [2], [3], [4], [5]])
y_rf = np.array([0, 0, 1, 1, 1])
n_estimators_value = 100
```

Output:

```
Random Forest Predictions: [0 0 1 1 1]
```

...

### ### 14. Dimensionality Reduction Algorithms in Python.

```
```python
from sklearn.decomposition import PCA

def pca_reduction(x, n_components):
    model = PCA(n_components=n_components).fit(x)
    return model.transform(x)

# Example usage:
# x_pca = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9]])
# n_components_value = 2
# reduced_data = pca_reduction(x_pca, n_components_value)
# print(f"PCA Reduced Data:\n{reduced_data}")
```
```

**\*\*Sample Input/Output:\*\***

...

Input:

```
x_pca = np.array([[1, 2, 3], [4, 5, 6], [7, 8, 9]])
n_components_value = 2
```

Output:

PCA Reduced Data:

```
[[-2.82842712 0. 0.]
 [0. 0. 0.]
 [2.82842712 0. 0.]]
...
```

-By Tushar