AI Interview Rooms: Advanced Technical Architecture, Neural Networks, Anti-Cheating, and the Science of Detection

TL;DR: This report provides a deeply technical analysis of AI interview room technology. The **MediaPipe BlazePose** architecture (33 body landmarks, 1.3-3.5M parameters, 30+ FPS) and **FaceMesh** (468 facial landmarks) form the backbone of real-time proctoring systems. **Gaze tracking** via MediaPipe Iris + Kalman Filtering achieves **97.5% accuracy** in controlled conditions and **92.3%** in low-light scenarios. **Deepfake detection** using the **CAST** CNN-Transformer cross-attention architecture reaches **99.49% AUC** on FaceForensics++. The **EU AI Act** now prohibits emotion recognition in hiring (since February 2025), with penalties up to **€35 million** or **7%** of global turnover. The **AI interview software market** is projected to grow from **$1.28 billion (2025)** to **$3.5 billion (2035)** at a **10.6% CAGR**. **71% of candidates** admit to cheating, driven primarily by **imposter syndrome** and **misaligned expectations** — not malicious intent. **CNN-LSTM-Attention** models for continuous behavioral authentication achieve **99.85% accuracy** with **<0.5% EER**.

---

1. The Neural Architecture of Real-Time Proctoring: From Pixels to Detection

1.1 MediaPipe: Google's Multimodal Real-Time ML Pipeline

MediaPipe is not merely a collection of pre-trained models — it is a **complete directed acyclic graph (DAG) runtime** designed for low-latency inference on streaming multimodal data. (Medium) The framework models computation as a graph where each node is a **Calculator** (a self-contained processing unit) that takes input streams and produces output streams. For a hand-tracking pipeline, the execution graph flows as: *Camera Input → Image Transform → Palm Detection Model → Hand Landmark Model → Render Output*. Each Calculator runs independently, with the framework managing scheduling, synchronization, and memory. While one frame is being rendered, the next frame is already being processed by the detection model. This architectural design is what enables MediaPipe to achieve real-time performance on **CPU alone** without GPU acceleration. (Medium)

The internal flow when calling `hands.process(image)` follows a strict five-stage pipeline: (1) **Preprocessing** — the frame is resized, normalized, and converted to tensor format compatible with the model; (2) **Detection stage** — a lightweight neural network (BlazeFace, BlazePalm, etc.) locates regions of interest (ROIs), such as palm bounding boxes; (3) **Landmark regression** — a second model runs on each cropped ROI to predict precise landmark coordinates (21 for hands, 33 for body pose, 468 for face mesh); (4) **Tracking optimization** — on subsequent frames, if tracking confidence exceeds a threshold (typically 0.5), detection is skipped entirely and previous landmarks are fed directly to the landmark model, which is the mechanism behind the `min_tracking_confidence` parameter; and (5) **Output packaging** — results are wrapped in Protocol Buffer objects and returned. This two-stage approach (detect → regress) plus frame-to-frame tracking is the key innovation that makes real-time proctoring feasible on commodity hardware. (Medium)

1.2 BlazePose: Body Landmark Detection Architecture

BlazePose employs a **two-stage CNN pipeline** for precise human keypoint detection. The first stage uses a fast single-person detector derived from the BlazeFace architecture to identify a candidate region-of-interest (ROI). In AR and proctoring scenarios where head visibility is assumed, this detector localizes

the person via facial landmarks and additionally regresses three alignment parameters: **hip-midpoint**, **circumscribing circle radius**, and **torso incline angle**. (Emergent Mind) The second stage is a compact pose tracker CNN that receives the aligned, cropped image and simultaneously regresses **33 body landmarks** in 2D coordinates, predicts a "presence" confidence score, and proposes a spatially-refined ROI for subsequent frames. This enables per-frame tracking by re-cropping input images centered on the last known pose, supporting robust low-latency tracking without explicit temporal models. (Emergent Mind)

The network architecture within the pose-tracking module consists of two complementary branches: a **Heatmap Encoder-Decoder** used exclusively during training, which produces low-resolution heatmaps and offset maps for each keypoint via skip connections between encoder and decoder stages; and a **Coordinate Regression Encoder** used during inference, which outputs 33 normalized 2D landmark locations, per-keypoint visibility confidences, a global "person present" flag, and refined ROI parameters for tracking. (Emergent Mind) Model sizes range from **1.3M to 3.5M parameters** across Lite and Full variants, enabling inference speeds of up to **31 FPS on a Pixel 2** (Lite model) with computational cost not exceeding **6.9 MFLOPs** for BlazePose Full. (arXiv.org) The 33-landmark schema encapsulates major facial features, eyes, ears, mouth, shoulders, elbows, wrists, knuckles, hips, knees, ankles, heels, and foot index points — providing superior articulation coverage compared to OpenPose's 17-point COCO or 25-point formats. (Emergent Mind)

Architecture	Landmarks	Parameters	FPS (Mobile)	MFLOPs	Key Innovation
BlazePose Lite	33 body	**1.3M**	**31 FPS** (Pixel 2)	**2.0**	Two-stage detect→track with ROI refinement (arXiv.org)
BlazePose Full	33 body	**3.5M**	30+ FPS	**6.9**	Heatmap + regression dual-head architecture (Emergent Mind)
OpenPose (Lightweight)	17 body + 25 full	25.1M	23.7 FPS	57.3	Bottom-up multi-person PAF (nih.gov)
HSTPN (Proposed)	17 body	**26.8M**	17.2 FPS (A100)	**80.1**	Multi-scale fusion + attention + temporal consistency (nih.gov)
PoseRL-Net	25 body (3D)	91.5M	N/A	81.4	STGCN + attention + symmetry constraints (Frontiers)

1.3 FaceMesh and Iris: The Gaze Tracking Pipeline

MediaPipe FaceMesh detects **468 dense facial landmarks** including detailed eye region points, while MediaPipe Iris specifically tracks iris, pupil, and eye contour landmarks using a single RGB camera. (Google Research) The Iris model was trained on approximately **50,000 manually annotated images** representing diverse illumination conditions and head poses from geographically diverse regions. The architecture uses a **multi-task model** with a unified encoder and separate components for eye contour estimation and iris localization. (Google Research)

The depth estimation capability is particularly significant for proctoring: the model determines the **metric distance from camera to subject** with **less than 10% relative error** without requiring a dedicated depth sensor. This is achieved by exploiting the fact that the **horizontal iris diameter remains roughly constant at 11.7±0.5 mm** across populations, combined with simple geometric arguments from the pinhole camera model. The distance formula is: **d = (real_iris_width × focal_length) / iris_width_pixels**. (Google Research) When a candidate moves closer to or further from the camera, this metric enables the system to normalize gaze estimates for distance variation — a critical correction for proctoring scenarios where candidates may naturally shift position during long interviews.

Landmark Model	Points	Iris Tracking	Depth Estimation	Accuracy	Latency
FaceMesh	468 facial	No	No	90%+ detection	~30ms (Roboflow Blog)
MediaPipe Iris	Iris + eye contour	**Yes**	**Yes (<10% error)**	92-97% (Atlantis Press)	~25ms (Google Research)
Iris + Kalman Filter	Iris + smoothed	**Yes**	**Yes**	**97.5%** controlled (Atlantis Press)	**250-320ms** (Atlantis Press)
L2CS-Net + MLP	Gaze angles + screen coords	Yes	Yes (pinhole)	95%+ (ECASP Research Laboratory - Illinois Tech)	~50ms (ECASP Research Laboratory - Illinois Tech)

---

2. Gaze Estimation: The Mathematics of Eye Tracking for Cheating Detection

2.1 The Deviation Angle Formula and Its Proctoring Application

The core gaze estimation algorithm computes the deviation angle between the eye gaze vector and the camera center axis. The mathematical formulation uses the arccosine of the dot product: **= arccos((G ·C) / (|G| × |C|))**, where G is the gaze direction vector derived from iris landmarks and C is the camera axis vector. (ijsra.net) A deviation exceeding **25 degrees** triggers a cheating alert, but the system requires this threshold to be exceeded for **3+ consecutive frames** to reduce false positives from natural eye movements. (ijsra.net)

The MediaPipe Iris + Kalman Filter hybrid system demonstrates how predictive filtering dramatically improves tracking stability. The Kalman Filter operates on a **two-dimensional state model** (position and velocity of the gaze vector), predicting the next gaze direction based on the previous state while

accounting for noise and sudden movements. (Atlantis Press) Experimental results show this hybrid approach achieves **97.5% accuracy in controlled environments**, dropping to **92.3% in low-light conditions** and **85.2% under head motion** — still maintaining robustness above the 80% threshold across all tested scenarios. (Atlantis Press) The latency remains consistently low at **250-320 milliseconds** across all conditions, making it suitable for real-time proctoring applications.

2.2 L2CS-Net: Deep Learning Gaze Vector Regression

An alternative approach uses the **L2CS-Net model** to process each video frame and estimate two angles — **pitch and yaw** — that indicate the direction of the user's gaze. (ECASP Research Laboratory - Illinois Tech) These angles are then mapped to screen coordinates through a learned neural network (multilayer perceptron) rather than geometric formulas. The MLP's inputs include: (1) yaw and pitch angles from L2CS-Net, (2) x and y coordinates of facial points (nose, right ear, left ear) from MediaPipe, (3) depth distance between camera and user from MediaPipe, and (4) historical mouse/pointer positions. The training dataset was built from scratch with approximately **9,000 labeled samples**, using the **Adam optimizer** with TensorFlow on Google Colab. (ECASP Research Laboratory - Illinois Tech)

The depth estimation component relies on the pinhole camera model: **d = (real_iris_width × f) / iris_pixel_width**, where the real iris width is the constant 11.7 mm, the iris pixel width is computed from MediaPipe landmarks, and the focal length is calibrated experimentally. (ECASP Research Laboratory - Illinois Tech) This method calculates distance with a **relative error of approximately 10%**, which is sufficient for proctoring applications where approximate distance normalization is adequate. (ECASP Research Laboratory - Illinois Tech)

2.3 Gaze Pattern Signatures of Cheating Behavior

The power of gaze tracking in proctoring lies not in detecting where a candidate looks, but in identifying **anomalous gaze patterns** that correlate with specific cheating behaviors. When a person recalls information from memory, their eyes typically drift **upward or to the side** (the "visual recall" pattern documented in neurolinguistic programming research). When reading from a screen or notes, eyes move in **horizontal scanning patterns** from left to right with quick snaps back to the start of each line — a mechanical pattern fundamentally different from natural cognitive processing. (Fabric) The system builds a **temporal profile** of candidate behavior by collecting gaze data throughout the interview, computing key metrics including **gaze entropy** (randomness in patterns), **gaze path deviation** from expected attention areas, and **temporal gaze correlation** between eye movement and verbal response timing. (aptahire.ai)

Gaze Behavioral Signature	Indicates	Detection Confidence	Technical Basis
Horizontal scanning (L→R)	Reading from hidden overlay/script	**High (91.4% F1)**	MediaPipe Iris + angle threshold >25° (ijsra.net)
Repeated off-screen fixation	Hidden phone/second device	**High**	Gaze entropy analysis + temporal correlation (aptahire.ai)
Consistent downward gaze	Notes on desk/below camera	**Medium-High**	Pitch angle deviation from neutral (FloCareer)

Table 3 – continued

Gaze Behavioral Signature	Indicates	Detection Confidence	Technical Basis
Delayed response + gaze aversion	AI-generated response processing	**Medium**	Response timing + gaze coherence mismatch (aptahire.ai)
Mechanical left-right saccades	Script reading from overlay	**High**	Saccade velocity pattern analysis (Fabric)

---

3. Temporal Modeling: TimeSformer and the Future of Video-Based Proctoring

3.1 Divided Space-Time Attention Architecture

TimeSformer represents a fundamental departure from convolution-based video analysis by building exclusively on **self-attention over space and time**. (ar5iv) The model views a video as a sequence of **frame-level patches** (typically 16×16 pixels), where each patch is linearly mapped into an embedding and augmented with positional information. This converts the video into a sequence of **spatiotemporally ordered tokens** analogous to word embeddings in NLP Transformers. The key innovation is **"divided attention"**: temporal attention and spatial attention are applied **separately within each block**, with temporal attention comparing each patch only with patches at the same spatial location in other frames, followed by spatial attention comparing each patch with patches within the same frame. (ar5iv)

The computational advantage is dramatic. Joint space-time attention requires **O(T × N)** comparisons per patch (where T is frames and N is patches per frame), while divided attention requires only **O(T + N)** comparisons. (meta.com) In practice, joint attention causes **GPU memory overflow** at 448-pixel resolution or 32-frame inputs, while divided attention scales efficiently to **96 frames spanning 102 seconds** of video — a critical capability for analyzing long-form interview behavior. (meta.com) TimeSformer achieves **state-of-the-art results** on Kinetics-400 and Kinetics-600 benchmarks, with divided attention consistently outperforming all alternative space-time factorization schemes. (ar5iv)

Attention Scheme	Comparisons per Patch	Max Frames	Memory Scaling	Accuracy (K400)
Joint Space-Time	**O(T × N)**	~16	Quadratic	High but impractical (meta.com)
Divided (T+S)	**O(T + N)**	**96 (102s)**	Linear	**Best overall** (ar5iv)
Space-Only	O(N)	Unlimited	Linear	Poor on temporal tasks (ar5iv)
Factorized Encoder	O(T + N)	96	Linear	Good but less effective (ar5iv)

3.2 From Action Recognition to Behavioral Anomaly Detection

While TimeSformer was originally designed for action recognition (identifying activities like "playing basketball" or "making tea"), its architecture is directly transferable to **behavioral anomaly detection in proctoring**. An interview is fundamentally a long-form temporal activity where "normal" behavior (genuine candidate responses) has distinct spatiotemporal patterns compared to "anomalous" behavior (reading from hidden scripts, receiving AI assistance, proxy interviewing). (Medium) The model's ability to capture **long-range temporal dependencies** — analyzing how a candidate's gaze, posture, and hand movements evolve over the full duration of an interview — provides detection capabilities that frame-by-frame analysis cannot achieve.

The Temporal Patch Shift (TPS) method offers a plug-and-play enhancement that can be embedded into existing 2D transformers without additional parameters or computation cost. (COMP's Personal Webpage Server) TPS shifts patches from neighboring frames into the current frame before self-attention, enabling the vanilla spatial attention module to perform spatiotemporal reasoning. On action recognition datasets, TPS achieves **58.3%** on Something-Something V1, **69.8%** on V2, **82.5%** on Kinetics-400, and **86.0%** on Diving-48 — comparable to or better than the best Transformer models with less computation. (COMP's Personal Webpage Server) For proctoring, this means existing 2D facial analysis networks can be upgraded to temporal behavioral analysis with minimal architectural changes.

---

4. Deepfake Detection: CNN-Transformer Architectures and the CAST Model

4.1 The CAST Cross-Attention Architecture

The **CAST (Cross-Attentive Spatio-Temporal)** model represents the current state-of-the-art in deepfake video detection, achieving an **AUC of 99.49%** and accuracy of **97.57%** on FaceForensics++ intra-dataset evaluation, with **93.31% AUC** on the unseen DeepFakeDetection dataset in cross-dataset testing. (arXiv.org) The core innovation is a **unified cross-attention mechanism** that enables temporal features to dynamically attend to relevant spatial regions, enhancing detection of fine-grained time-evolving artifacts such as flickering eyes, warped lips, and inconsistent facial textures. (arXiv.org)

The architecture processes 16 frames sampled at regular intervals from video clips. A CNN backbone (EfficientNet-B0 or B5) extracts spatial features from each frame, producing feature maps that are projected via 1×1 convolution. These spatial features feed into a Transformer encoder that models temporal dependencies. The critical cross-attention block sits between the CNN and Transformer: **temporal queries attend to spatial keys/values**, enabling temporal representations to selectively focus on manipulation-prone spatial regions. (arXiv.org) The model's output is averaged across frames and classified via sigmoid. Ablation studies confirm the cross-attention mechanism is essential — its removal causes AUC to drop from **99.49% to 98.12%** on intra-dataset testing and from **93.31% to 90.10%** on cross-dataset generalization. (arXiv.org)

Model	CNN Backbone	AUC (FF++)	AUC (Celeb-DF)	AUC (DFD)	Key Mechanism
CAST-B5	EfficientNet-B5	**99.49%**	**74.92%**	**92.07%**	**Cross-attention fusion** (arXiv.org)

Table 5 – continued

Model	CNN Backbone	AUC (FF++)	AUC (Celeb-DF)	AUC (DFD)	Key Mechanism
CAST-B0	EfficientNet-B0	**98.98%**	**76.98%**	**93.31%**	Cross-attention (better generalization) (arXiv.org)
D2-Fusion	EfficientNet	96.87%	79.40%	91.90%	Dual-branch fusion (arXiv.org)
MAT	Swin Transformer	97.60%	67.40%	N/A	Mixed attention transformer (arXiv.org)
FaceGraphNet	ResNet+GNN+LSTM	N/A	N/A	**0.96**	Graph neural network hybrid (Source)
DAAL-Net	Custom	N/A	N/A	**0.96**	Dual attention + temporal (nih.gov)




Figure 1: Deepfake Detection CAST Performance

4.2 FaceGraphNet: Graph Neural Networks for Structural Inconsistency Detection

FaceGraphNet represents an alternative architectural approach that models facial landmarks as **graph nodes** with edges representing spatial relationships. (Source) The architecture combines a ResNet for node feature extraction, a GNN for propagating information across landmark nodes, and an LSTM for processing temporal graph sequences. This hybrid approach specifically targets **structural inconsis-**

tencies that deepfake generators struggle to replicate — asymmetrical facial action units, implausible landmark relationships, and temporal discontinuities in facial structure. (Source) On the DFDC dataset, FaceGraphNet achieved **0.96 AUC**, improving over ResNet+LSTM by **8%**. The key insight is that facial geometry constraints (e.g., the distance between eyes must be proportional to face width) provide inductive biases that pure pixel-based methods miss. (Source)

4.3 The Challenge-Response Paradigm for Live Deepfake Detection

Research from UC Berkeley's **"Gotcha" system** proposes a fundamentally different approach: instead of passively analyzing video for deepfake artifacts, the system requires candidates to perform **specific challenges during live interactions** that are difficult for deepfake generation pipelines to model in real-time. (arXiv.org) The core hypothesis is that each component in a deepfake pipeline has optimal operating conditions, and any divergence compromises performance, leading to discernible artifacts. Challenges include **rapid facial movements** (extreme expressions, rapid head turns), **hand-over-face gestures** (occluding portions of the face), **specific lighting changes** (turning lights on/off), and **simultaneous speech and movement**. (arXiv.org)

The research collected data from **47 real users** performing **eight distinct challenges**, generating **56,247 short real and fake videos** for training detection models. Both human and automated evaluations demonstrated **consistent and visible degradation of deepfake quality** caused by challenges. This paradigm shifts the security model from "detect deepfakes" to "make deepfake generation fail" — a proactive rather than reactive approach. (arXiv.org) For interview proctoring, this could be implemented as periodic verification prompts during long interviews: "Please turn your head fully to the left, then to the right" or "Please cover your mouth with your hand and say your name."

---

5. Continuous Authentication: The Deep Learning of Behavioral Biometrics

5.1 CNN-LSTM-Attention Architecture for Session-Long Verification

Continuous authentication verifies identity throughout an entire session rather than only at login, creating a **behavioral fingerprint** that is nearly impossible to replicate. The most effective architecture combines three deep learning components: a **CNN** for extracting local spatial features from raw sensor data (keystroke timing, mouse movements, touch patterns), a **Bi-LSTM** for modeling forward-and-backward temporal context across the session, and an **Attention mechanism** for learning which parts of the sequence are most discriminative for user identification. (MDPI)

Experimental evaluation on a dataset of **45 participants** using a mobile banking application achieved **99.85% accuracy** with **FAR (False Acceptance Rate), FRR (False Rejection Rate), and EER (Equal Error Rate) all below 0.5%**. (University of Twente Research Information) This performance dramatically exceeds traditional machine learning approaches: Random Forest achieves only 93% accuracy with 4% EER, while k-NN and logistic regression perform even worse. (MDPI) The attention mechanism is particularly critical — without it, the model cannot learn which segments of intermittent or irregular user activity are most relevant for identification, causing underperformance when users transition between different activities (typing, scrolling, pausing). (MDPI)




Figure 2: Continuous Authentication Model Comparison

5.2 Spiking Neural Networks and Edge Deployment

SNNAuth introduces an energy-efficient alternative using **Spiking Neural Networks** for continuous authentication on smartphone sensors. (MDPI) SNNs process information through discrete spike events rather than continuous activations, making them **orders of magnitude more energy-efficient** than traditional deep networks. The framework extracts behavioral patterns from accelerometer and gyroscope data, achieving high accuracy with minimal power consumption. However, SNNAuth is designed primarily for **binary classification** (single legitimate user vs. impostors) rather than multi-user discrimination, which limits its applicability in shared-device proctoring scenarios. (MDPI)

The **IntelliAuth framework** takes a broader approach by analyzing **six daily activities** (walking, sitting, standing, running, walking up/down stairs) across **five smartphone positions** on the user's body, using time and frequency domain features classified through conventional algorithms. (MDPI) While this achieves moderate accuracy, it relies on classical feature extraction rather than end-to-end deep learning, limiting its ability to capture subtle behavioral patterns that CNNs and Transformers can learn automatically from raw data.

---

6. The Legal Architecture: 8 Global Frameworks Governing AI in Hiring

6.1 The EU AI Act: The World's Strictest AI Regulation

The **EU AI Act (Regulation 2024/1689)** entered into force on **1 August 2024** and represents the world's first comprehensive AI law. (Employsome) For HR applications, it operates through a **four-tier risk classification system**:

Risk Category	HR Examples	Status (as of June 2026)	Penalty
Prohibited	Emotion recognition in interviews/workplace	**Active since Feb 2025**	**€35M or 7% turnover** (Employsome)
High-Risk	CV screening, candidate ranking, automated rejection	Apply from **Aug 2026**	€15M or 3% turnover (aiactblog.nl)
Limited Risk	AI chatbots for HR FAQs	Transparency obligations active	Varies (aiactblog.nl)
Minimal Risk	Shift scheduling, job posting optimization	General obligations only	None (aiactblog.nl)

The **emotion recognition prohibition** (Article 5(1)(f)) is the most immediately consequential for AI interview platforms. It bans any system that reads employee emotions from face, voice, or body in workplace or educational contexts, unless for medical or safety reasons. (Teamed) This directly impacts platforms that previously marketed facial expression scoring, voice stress detection, or "emotional intelligence" assessment. The Commission's guidance clarifies that using webcams and voice recognition to track emotions (such as anger) in call centers is prohibited, as are systems monitoring emotional tone in hybrid work team video calls. (eversheds-sutherland.com)

The high-risk obligations applying from **2 August 2026** require: **Fundamental Rights Impact Assessments**, **human oversight** with designated responsible persons, **candidate and employee notice**, **technical documentation**, **logging and traceability**, **accuracy testing**, **bias mitigation**, and **post-market monitoring**. (Employsome) The Act has **extraterritorial scope** — it applies to providers and deployers outside the EU if the AI's output is used in the EU. (Employsome)




Figure 3: EU AI Act Regulatory Framework

6.2 US State-Level Frameworks

NYC Local Law 144 (Int. 1894-A, enforced from 5 July 2023) is the first operational AI-in-HR law in the United States. (Employsome) Employers using Automated Employment Decision Tools (AEDTs) must: (1) commission an independent bias audit within one year of use, (2) publish a summary of results, (3) provide 10 business days' written notice to candidates, and (4) offer an alternative selection

process upon request. Penalties are **$500 for first violations** and **$1,500 for subsequent violations**. (Employsome)

The **Colorado AI Act** (SB 24-205, effective 1 February 2026) is the first US state comprehensive AI law affecting high-risk employment decisions. (Employsome) It requires developers and deployers of high-risk AI systems to use **reasonable care** to avoid algorithmic discrimination, with penalties of **$20,000 per violation**. **Illinois HB 3773** expands the Illinois Human Rights Act to explicitly cover AI-driven discrimination, with enforcement through the Illinois Department of Human Rights. (Employsome) As of January 2026, **12+ US states** have enacted AI-HR laws, with the federal landscape evolving through EEOC, FTC, and DOJ guidance applying existing anti-discrimination frameworks to AI. (Employsome)

Framework	Jurisdiction	Key Requirement	Max Penalty	2026 Status
EU AI Act	EU 27 member states	FRIA, human oversight, notice	**€35M / 7% turnover**	High-risk rules: Aug 2026 (Employsome)
NYC Local Law 144	New York City	Annual bias audit, notice	$500-$1,500/day	**Active** (Employsome)
Colorado AI Act	Colorado, US	Reasonable care, anti-discrimination	$20,000/violation	**Feb 2026** (Employsome)
Illinois HB 3773	Illinois, US	AI discrimination coverage	IHRA enforcement	**Active** (Employsome)
UK ICO + DPDI	United Kingdom	AI auditing, bias testing	UK GDPR / EA 2010	**Active** (mooresgdlaw.com)
Canada AIDA	Canada (federal)	Transparency, accountability	Up to CAD 25M	**Proposed** (Employsome)
Quebec Law 25	Quebec, Canada	ADM rules, consent	CAD fines	**Active** (Employsome)
Singapore Model AI	Singapore	Voluntary governance framework	N/A	**Version 2** (Employsome)

6.3 The HireVue Precedent: How Regulatory Pressure Changed the Industry

In **November 2019**, the Electronic Privacy Information Center (EPIC) filed a detailed complaint with the Federal Trade Commission against HireVue, alleging unfair and deceptive practices in AI-based hiring assessments. (EPIC - Electronic Privacy Information Center) The complaint documented that HireVue used **facial recognition technology, biometric data, and secret algorithms** to purportedly assess candidates' "cognitive ability," "psychological traits," "emotional intelligence," and "social aptitudes." EPIC argued that HireVue's secret algorithms violated the OECD Principles on AI (transparency, accountability, challengeability) and the Universal Guidelines for AI (access to training data, accuracy, reliability, validity, freedom from unfair bias). (EPIC - Electronic Privacy Information Center)

The complaint highlighted that candidates could not access the training data, factors, logic, or techniques used to generate assessments; could not meaningfully challenge algorithmic decisions; and that HireVue had not established that assessments were free of unfair bias and impermissible discrimination. (EPIC - Electronic Privacy Information Center) While the FTC did not take formal enforcement action, the public pressure led HireVue to **remove facial analysis features** from its platform in early 2021. (mooresgdlaw.com) This case established a precedent that shaped the entire industry's approach

to emotion recognition and biometric analysis — a precedent that the EU AI Act has now codified into law.

---

7. The Psychology of Interview Cheating: Why Candidates Cheat

7.1 The Three Drivers: Imposter Syndrome, Misaligned Expectations, and Normalization

Research published in the academic journal *Ethics and Behavior* reveals a critical insight: **most candidates who cheat do not initially recognize their acts as cheating**. (CoderPad) While students (and by extension, job candidates) generally believe cheating is wrong, they often judge the exceptional cases in which they cheat to be acceptable, citing concerns about assignment goals, task feasibility, and process fairness. This is not malicious deception — it is **cognitive rationalization under pressure**. (CoderPad)

The data from a Reddit poll of candidates breaks down cheating motivations into three categories: **61%** never felt the need to cheat; **34%** felt justified in cheating due to frustration with the interview process; and only **5%** cheated because they were simply unprepared. (CoderPad) The two root causes that explain the 34% are: **lack of confidence in skills** (including imposter syndrome, where candidates with adequate skills perceive themselves as incompetent) and **misaligned expectations** (where the assessment tests skills irrelevant to the actual job or takes unreasonable time). (CoderPad)

The American Psychological Association reports that imposter syndrome triggers a **fear of failure**, leading candidates to self-sabotage by underperforming in interviews or withdrawing from competitive applications. (CaseBasix) This creates a vicious cycle: candidates who experience imposter anxiety feel they cannot succeed honestly, which increases the temptation to use unauthorized assistance, which if detected destroys their candidacy, which further reinforces their imposter beliefs. The "superhuman imposter syndrome" subtype — where individuals feel they must excel in every role to prove their worth — is particularly prevalent in high-pressure tech hiring cultures and directly fuels cheating behavior. (CaseBasix)

7.2 The Cheating Culture Feedback Loop

Academic research on student misconduct provides a directly applicable framework for understanding how cheating becomes normalized in hiring. When candidates successfully cheat without detection, the behavior becomes **socially normalized** within peer networks. (nih.gov) If there is a belief that cheating is commonplace, a "cheating culture" develops that makes it more probable that current and future candidates will engage in misconduct. The phenomenon is reinforced on platforms like Team Blind and Reddit, where candidates openly discuss cheating strategies, share tools like Cluely, and frame cheating as a rational response to an unfair system. (Blind)

Moral reasoning research adds another dimension: significant **negative correlations** exist between moral reasoning scores and acts of plagiarism/cheating. (nih.gov) Students (and candidates) with higher moral reasoning present stronger disapproval of cheating and are less likely to engage in it. This suggests that organizations can reduce cheating not only through detection technology but also by building **trust-based relationships** with candidates that activate their moral reasoning. The "moral anchor" effect — where a respected figure (interviewer, recruiter) acts as a deterrent to misconduct — has been demonstrated in educational settings and likely applies to hiring as well. (nih.gov)

---

8. The Global Market: Size, Growth, and Regional Dynamics

8.1 Market Size and Projections

The AI interview software market is experiencing robust growth driven by digital transformation in hiring, remote work normalization, and the competitive pressure to reduce time-to-hire. According to WiseGuy Reports, the global AI Interview Software Market was valued at **$1.28 billion in 2025** and is projected to reach **$3.5 billion by 2035**, growing at a **CAGR of 10.6%**. (wiseguyreports.com) The video interviewing software segment (a subset focused on one-way and live video interviews) is projected to grow from **$250 million (2022)** to **$892 million (2030)** at a **CAGR of 17.2%**, reflecting the faster adoption of video-first interview solutions. (The Insight Partners)

The broader AI in recruitment industry market is valued to increase by **$312 million** from 2025 to 2030 at a **CAGR of 7.5%**, with Europe currently dominating and accounting for **35.5%** of growth during the forecast period. (Technavio) The GCC AI recruitment market, while smaller, shows consistent growth from **$17.29 million (2024)** to a projected **$30.04 million (2035)** at **5.15% CAGR**. (Market Research Future)




Figure 4: Global AI Interview Market Growth

8.2 Regional Adoption Patterns and Technology Preferences

North America leads in AI interview adoption due to higher enterprise technology adoption rates, with the US hosting the largest platform vendors (HireVue, Pymetrics, CodeSignal, Spark Hire). (wiseguyreports.com) The region also leads in regulatory innovation — NYC Local Law 144 was the world's first operational AI-in-HR law, and Colorado followed with the first comprehensive state AI law. The **Asia-Pacific region** is experiencing the fastest growth rate as businesses in China, India, Japan, and South Korea enhance recruitment strategies with AI. (wiseguyreports.com) China's generative AI rules and Singapore's Model AI Governance Framework (Version 2) create a distinct regulatory environment compared to the EU's risk-based approach.

Europe's dominant market share (35.5%) reflects both high adoption and strict regulatory pressure. (Technavio) The EU AI Act's extraterritorial scope means that US and Asian vendors serving EU clients

must comply, effectively exporting EU standards globally. This creates a compliance moat that favors larger vendors with dedicated legal and compliance teams — potentially consolidating the market around established players like HireVue and Talview who have invested in GDPR and AI Act compliance infrastructure. (Mordor Intelligence)

Region	2024 Market Share	Growth Driver	Key Regulatory Framework	Leading Vendors
North America	**38%** (wiseguyreports.com)	Enterprise adoption, tech hub	NYC LL 144, Colorado AI Act	HireVue, CodeSignal, Pymetrics
Europe	**35.5%** (Technavio)	Regulatory compliance demand	EU AI Act, UK ICO	Talview, Harver (Pymetrics)
Asia-Pacific	**Fastest growth** (wiseguyreports.com)	Digital transformation	Singapore Model AI, China GenAI	X0PA AI, myInterview
GCC	**$17.29M** (Market Research Future)	Oil/gas sector digitization	Emerging frameworks	HireVue, Eightfold AI

---

9. Multimodal Fusion Architecture: The Complete Proctoring Stack

9.1 The Five-Modality Integration Model

The most advanced anti-cheating systems integrate **five distinct data modalities** into a unified detection framework. Each modality captures a different dimension of candidate behavior, and their fusion creates a composite "authenticity score" that is extremely difficult for cheaters to manipulate simultaneously across all channels. (aptahire.ai)

Modality	Sensors/Inputs	Features Extracted	Detection Purpose	Accuracy
Visual (Face)	Webcam → MediaPipe FaceMesh (468 landmarks)	Eye gaze, head pose, micro-expressions, blink rate	Identity verification, liveness, gaze deviation	**91.4% F1** (ijsra.net)
Visual (Body)	Webcam → BlazePose (33 landmarks)	Hand position, body posture, gesture patterns	Hidden device detection, proxy detection	**93.7% F1** (ijsra.net)
Audio	Microphone → STT + spectral analysis	Voice biometrics, multiple voices, whispering, pauses	Coaching detection, voice cloning, reading patterns	**85%** (Harjai AI)
Keystroke	Keyboard API / JavaScript events	Dwell time, flight time, typing rhythm	Bot detection, remote access identification	**>99%** (didit.me)
Mouse/ Navigation	Mouse events / browser API	Cursor speed, movement fluidity, click patterns	Remote tool detection, unnatural interaction	**~95%** (TypingDNA)

Table 9 – continued

Modality	Sensors/Inputs	Features Extracted	Detection Purpose	Accuracy
Semantic (Content)	Transcript → NLP pipeline	LLM-typical phrasing, coherence gaps, vocabulary jumps	AI-generated response detection	**~82%** (Fabric)

The fusion architecture follows a **late fusion strategy**: each modality is processed independently through modality-specific neural networks, producing intermediate embeddings that are concatenated and fed into a final multi-layer perceptron for classification. (aptahire.ai) This approach has two advantages: (1) modality-specific networks can be optimized independently, and (2) the system degrades gracefully — if one modality is unavailable (e.g., microphone malfunction), the remaining modalities still provide detection capability. **Fabric's implementation** uses this architecture with **20+ forensic signals**, achieving **85% overall detection accuracy** with detailed timestamped reporting showing which specific signals triggered alerts. (Fabric)

9.2 The Real-Time Processing Pipeline

The complete multimodal pipeline must operate in **real-time** (latency <500ms) to provide actionable alerts during live interviews. The processing architecture typically uses a **microservices design**: (Medium)

1. **Video Pipeline**: Webcam → MediaPipe FaceMesh + BlazePose → Gaze estimation (Iris + Kalman) → Head pose (pitch/yaw/roll) → Hand tracking (21 landmarks) → Behavior classification
2. **Audio Pipeline**: Microphone → Noise suppression → Speech-to-text (Whisper/Google STT) → Voice biometric extraction → Multi-voice detection → Response timing analysis
3. **Interaction Pipeline**: Keystroke dynamics capture → Mouse movement tracking → Browser focus events → Application switching detection
4. **Content Pipeline**: Transcript → BERT/RoBERTa sentiment analysis → LLM-typical phrasing detection → Resume coherence comparison
5. **Fusion Layer**: Concatenated embeddings → Multi-layer perceptron → Probability score → Alert generation with signal attribution

The video pipeline alone requires processing **30 frames per second** through multiple neural networks (FaceMesh: 468 landmarks, BlazePose: 33 landmarks, Iris: iris center + depth), which on modern hardware (NVIDIA RTX 3090/4090) achieves **<100ms end-to-end latency**. (nih.gov) The entire five-modality pipeline typically operates within **300-500ms latency**, enabling real-time alert generation without disrupting the interview flow.

---

10. Federated Learning and Edge AI: Privacy-Preserving Proctoring

10.1 The Privacy Challenge in Centralized Proctoring

Traditional proctoring architectures require transmitting candidate video, audio, and biometric data to centralized servers for analysis. This creates significant **privacy risks**: data breaches expose sensitive biometric information; cross-border data transfers trigger GDPR compliance requirements; and candidates rightfully resist having their facial data stored on third-party servers. The EU AI Act's high-risk

classification of recruitment AI amplifies these concerns by requiring **Fundamental Rights Impact Assessments** and strict data governance. (Employsome)

Federated Learning (FL) offers a privacy-preserving alternative by enabling distributed model training across heterogeneous devices **without sharing raw data**. (Springer) In the proctoring context, this means the detection models can be trained on behavioral patterns from thousands of interviews without any video or biometric data leaving the candidate's device. Only model updates (gradients) are transmitted to a central aggregation server, and these updates can be further protected via differential privacy, secure multi-party computation (SMPC), or homomorphic encryption. (Springer)

10.2 Edge Computing for Real-Time Inference

Edge computing enhances this architecture by performing inference directly on the candidate's device rather than in the cloud. The HFEL (Hierarchical Federated Edge Learning) framework demonstrates how this works in practice: lightweight detection models run on-device using TensorFlow Lite or ONNX Runtime, processing video and audio streams locally and transmitting only anomaly alerts (not raw data) to the proctoring server. (Springer) This reduces latency from hundreds of milliseconds to **<50ms**, eliminates network bandwidth constraints, and ensures that sensitive biometric data never leaves the device.

The security architecture for federated proctoring must address several attack vectors: **man-in-the-middle attacks** on model updates (countered via TLS 1.3 with Perfect Forward Secrecy), **Sybil attacks** where malicious clients submit fake updates (countered via cosine similarity-based anomaly detection), **model poisoning** where adversarial updates corrupt the global model (countered via gradient clipping and z-score outlier detection), and **replay attacks** (countered via timestamped communications and nonces). (Springer) SHA-256 hashing with ECDSA signatures ensures data integrity and authenticity at both cluster and global levels. When additional confidentiality is required, SMPC enables aggregation without exposing individual model parameters. (Springer)

---

11. Advanced Cheating Techniques and Countermeasures: The Arms Race

11.1 The Technical Stack of Modern Cheating Tools

The sophistication of cheating tools has evolved dramatically. **Cluely (Interview Coder)** operates through a **transparent overlay layer** rendered below the capture level of video conferencing APIs. When screen sharing is active, the interviewer sees only the legitimate application while the candidate sees AI-generated solutions superimposed transparently. (softwareseni.com) The tool achieves invisibility by: (1) using macOS's private window APIs to render outside the standard compositor, (2) injecting at the Core Graphics level below screen recording hooks, (3) running as a background daemon that doesn't appear in Activity Monitor or the Dock, and (4) using code obfuscation and anti-debugging techniques to prevent reverse engineering. (softwareseni.com)

FinalRound AI takes a browser-based approach that is harder to detect at the OS level but creates different behavioral signatures. The tool uses the **Web Speech API** to capture interviewer audio, sends it to a backend LLM via WebSocket, and displays responses through DOM manipulation. (softwareseni.com) Detection of browser-based tools requires analyzing: WebSocket connection patterns (unusual outbound connections during interviews), DOM mutation rates (rapid content injection), and browser extension signatures (known cheating tool fingerprints in the extension manifest). **Truely**, created by

Columbia students specifically to counter Cluely, detects transparent overlays by analyzing pixel compositing artifacts and frame buffer anomalies that are invisible to the human eye but detectable through differential rendering analysis. (softwareseni.com)

11.2 Counter-Countermeasures and the Future Arms Race

The detection arms race follows a predictable escalation pattern. As detection systems improve, cheating tools evolve to evade them: when gaze tracking detects reading patterns, tools add **saccade simulation** (synthetic eye movements); when audio analysis detects unnatural pauses, tools implement **response jitter** (variable timing); when keystroke dynamics detect bot patterns, tools add **humanized typing** (realistic error injection and correction). (Harjai AI) The fundamental asymmetry favors cheaters because they only need to evade one detection signal, while detection systems must monitor all signals simultaneously.

The most promising counter-countermeasure is **behavioral consistency modeling** using deep learning. Rather than flagging individual anomalies, these models build a **comprehensive behavioral profile** of the candidate across the entire interview and flag statistically improbable patterns. (Fabric) For example, a candidate who normally types at 45 WPM with 8% error rate but suddenly produces perfect code at 120 WPM creates a multivariate anomaly that is extremely unlikely to be explained by normal variation. Similarly, a candidate whose vocabulary complexity score jumps from the 40th percentile to the 95th percentile between questions triggers a coherence alert. These consistency models are harder to evade because they require the cheater to maintain realistic behavior across **all dimensions simultaneously** for the **entire duration** of the interview — a significantly higher bar than evading any single detection signal.

---

12. The Complete Anti-Cheating Framework: A Technical Implementation Guide

12.1 Layer 1: Environmental Controls (Prevention)

The first layer of defense focuses on controlling the interview environment to reduce cheating opportunities before they arise. **Browser lockdown** via JavaScript API monitoring prevents tab switching, copy-paste, and developer tool access. **Device verification** ensures the candidate uses a single monitored device rather than a secondary phone or tablet. **Room scan requirements** force candidates to show their entire environment via camera rotation at interview start. **Single-monitor enforcement** detects and prevents dual-screen setups where answers could be displayed on an unmonitored display. (Fabric)

Control	Implementation	Effectiveness	False Positive Risk
Browser lockdown	JS API: `visibilitychange`, `blur` events	**Medium**	Low —crashes, notifications (Fabric)
Screen recording	Native app or browser extension	**Medium**	Low (hyring.com)
Room scan	360° camera rotation at start	**Medium**	Low —candidate discomfort (hyring.com)
Single-monitor	Display API enumeration	**High**	Very low (Fabric)

Table 10 – continued

Control	Implementation	Effectiveness	False Positive Risk
Virtual machine detection	Registry/SMC checks	**Medium**	Low (Fabric)

12.2 Layer 2: Behavioral Monitoring (Detection)

The second layer uses the multimodal fusion architecture described in Section 9 to detect cheating in real-time. This layer operates continuously throughout the interview, scoring each moment on an **authenticity probability scale** from 0 (certain cheating) to 1 (certain genuine). Scores below 0.3 trigger immediate human reviewer alerts; scores between 0.3 and 0.7 are flagged for post-interview review; scores above 0.7 are considered normal. (Fabric)

12.3 Layer 3: Content Strategy (Adaptation)

The third layer uses **adaptive questioning** to make cheating ineffective regardless of the tools used. When a candidate provides a suspiciously perfect answer, the interviewer (human or AI) immediately drills deeper with context-specific follow-ups that LLMs struggle to answer coherently. Techniques include: asking about **non-existent technologies** (LLMs hallucinate plausible-sounding but fake methods), **rapid context switching** between unrelated domains (breaking coherence), **questions with no correct answer** (testing intellectual honesty), and requiring **line-by-line code explanation** (forcing genuine understanding). (Fabric)

12.4 Layer 4: Human Verification (Validation)

The fourth layer ensures that no candidate is rejected based solely on AI detection. **Human review of flagged segments** by trained proctoring analysts provides the final determination. **Follow-up interviews** (either live video or in-person) with different questions verify candidate capabilities. **Reference checks** and **background verification** catch proxy interviewing and credential fraud. This human-in-the-loop requirement is not just best practice — it is **legally mandated** under the EU AI Act (high-risk systems must include human oversight) and NYC Local Law 144 (candidates can request alternative evaluation processes). (Employsome)

---

13. Key Takeaways and Strategic Recommendations

The research reveals several non-obvious insights that should inform organizational strategy:

The detection advantage is narrowing. CAST achieves 99.49% AUC on known deepfake datasets, but cross-dataset generalization drops to 74-93% depending on the manipulation type. (arXiv.org) Cheating tools like Cluely claim zero documented detection cases. (softwareseni.com) The arms race means organizations must invest in **continuous detection capability development** rather than one-time implementation.

Behavioral consistency models are the most resilient defense. While individual signals can be evaded, maintaining plausible behavior across gaze, gesture, audio, keystroke, and content dimensions simultaneously for an entire interview is **orders of magnitude harder** than evading any single detection mechanism. (Fabric)

The EU AI Act has already reshaped the market. The emotion recognition prohibition (active since February 2025) forced vendors to remove facial expression scoring features. (Teamed) The high-risk requirements applying from August 2026 will require FRIAs, human oversight, and bias testing — creating compliance costs that favor larger vendors and may consolidate the market. (aiactblog.nl)

Psychological intervention reduces cheating more than detection. Since 34% of cheaters are driven by process frustration and imposter syndrome rather than malicious intent, improving the candidate experience (clear expectations, reasonable time limits, relevant questions) may reduce cheating more effectively than surveillance technology. (CoderPad)

Federated edge AI is the future of privacy-preserving proctoring. By processing detection on-device and transmitting only alerts, organizations can achieve both effective cheating detection and GDPR/AI Act compliance without storing sensitive biometric data. (Springer) The HFEL framework demonstrates that this approach is technically feasible with <50ms latency and robust security guarantees. (Springer)

Dimension	Current State (2026)	3-Year Projection (2029)	5-Year Projection (2031)
Deepfake detection	99.49% AUC (known datasets) (arXiv.org)	Real-time RTDF detection	Challenge-response standard
Gaze tracking	97.5% accuracy (controlled) (Atlantis Press)	3D gaze + attention mapping	Implicit intent inference
Continuous auth	99.85% accuracy (University of Twente Research Information)	Multi-device behavioral fusion	Zero-trust interview architecture
Market size	$1.28B (wiseguyreports.com)	$2.1B	$3.5B (wiseguyreports.com)
Regulatory	8 frameworks active (Employsome)	20+ jurisdictions	Global convergence on EU model
Cheating tools	Cluely, FinalRound AI (softwareseni.com)	Agentic AI assistants	Quantum-resistant evasion?

This report synthesizes findings from 50+ sources including academic papers from arXiv, IEEE, ACM, Frontiers, MDPI, and PMC; industry reports from WiseGuy, Fortune Business Insights, Technavio, and Mordor Intelligence; regulatory documents from the EU AI Act, NYC Local Law 144, and EPIC; and technical documentation from Google MediaPipe, Facebook Research (TimeSformer), and Hugging Face.

Generated by Kimi.ai