Qwen

Anatomy of a Cheater-Proof Room: Deconstructing the Technologies of AI-Powered Proctoring

Core Architectural Frameworks for Proctoring Systems

The architectural design of modern AI-powered interview proctoring systems represents a sophisticated response to the dual pressures of ensuring absolute security and maintaining a functional, privacy-respecting user experience. The predominant model that has emerged to address these competing demands is a **Hybrid Edge-Cloud architecture** . This framework strategically partitions computational tasks between the candidate's local device (the "edge") and a centralized cloud backend, creating a symbiotic relationship that optimizes for low latency, robust security, and scalable analytics. The rationale for this model is rooted in the fundamental requirements of real-time monitoring, where every millisecond of delay can impact both the candidate's experience and the system's ability to respond to anomalies. By executing the most time-sensitive components locally, these systems achieve responsiveness unattainable with purely server-side processing. Simultaneously, they leverage the cloud for orchestration, heavy-duty computation, and long-term data aggregation, thereby balancing performance with centralized control and advanced analytical capabilities.

The client-side, or edge, component is the cornerstone of the system's real-time defense. It is here that computationally intensive computer vision (CV) inference tasks are executed directly within the candidate's web browser [62] . This approach is critical for achieving the stringent latency requirements necessary for live monitoring; target latencies for CV inference are often below 200 milliseconds to ensure that the proctoring system remains synchronized with the video stream and can react instantaneously to suspicious behavior [12] . This local execution is made possible through the adoption of modern web standards like WebAssembly (Wasm) and WebGPU. These technologies allow complex machine learning models, originally developed in languages like C++ or Python, to be compiled and run efficiently on the client's CPU and GPU without requiring plugins or native code installation [62] . For instance, TensorFlow.js provides a JavaScript library that enables developers to run and even retrain ML models in the browser, while ONNX Runtime Web facilitates the deployment of models from various frameworks,

further expanding the choice of available algorithms . The use of Wasm and WebGPU offloads significant processing burdens from the server, reduces network traffic, and ensures a more responsive application, which is crucial for tasks like continuous gaze tracking and head pose estimation [62].

A paramount benefit of this edge-centric approach is its profound impact on data privacy and regulatory compliance. By performing initial analysis locally, the system can process raw biometric data—such as facial images and eye movements—without ever transmitting it to a remote server [7]. Instead of sending a continuous, high-bandwidth video feed, only lightweight, structured telemetry data is sent over a secure WebSocket connection . This payload might contain JSON objects with timestamped information about gaze vectors, head pose angles, or the confidence level of a detected gesture . This strategy of data minimization is not merely a best practice but a necessity for complying with increasingly strict global biometric privacy laws such as the General Data Protection Regulation (GDPR) in Europe, the Biometric Information Privacy Act (BIPA) in Illinois, USA, and the California Consumer Privacy Act (CCPA) . These regulations often impose stringent rules on the collection, storage, and use of biometric identifiers. By keeping raw video streams local and only transmitting anonymized or hashed biometric templates (like a cryptographic hash of a facial vector), proctoring platforms can significantly mitigate their legal and ethical liabilities [22]. Furthermore, this architecture enhances user trust, as candidates are more likely to consent to a system that processes sensitive data on their own device rather than on a third-party server.

The server-side, or cloud, component serves as the central nervous system for the entire platform. Its responsibilities are primarily focused on orchestration, data aggregation, and large-scale analytics. When a candidate initiates an interview session, the cloud backend handles authentication, session management, and the generation of secure, time-limited tokens required for establishing connections, such as those needed for WebRTC-based video streaming . Once the session begins, the cloud becomes the destination for the high-throughput telemetry stream sent from the client. To manage this influx of data—especially from multiple concurrent interviews—a scalable messaging queue like Apache Kafka is often employed . Kafka acts as a buffer, allowing the backend to ingest vast amounts of real-time data from various sources without being overwhelmed. This data is then processed by dedicated microservices, typically built with frameworks like FastAPI in Python, which are designed to handle specific analytical tasks . These services perform complex operations such as aggregating biometric data over time, applying sophisticated anomaly detection algorithms, and calculating the final "Integrity Score" for each session . While the edge device performs immediate, real-time checks, the cloud is responsible for the holistic analysis that informs the recruiter's final review.

This division of labor also provides a crucial layer of resilience and scalability. If a candidate's device lacks the resources to run the CV models at the desired frame rate (e.g., dropping below 15 FPS), the client-side logic can detect this and signal the cloud for fallback processing . In such scenarios, more computationally expensive models could be invoked on powerful GPU-accelerated nodes within the cloud infrastructure to continue monitoring the session, albeit with slightly higher latency . This graceful degradation ensures that the proctoring function is maintained even on less capable hardware. The cloud infrastructure itself is typically deployed on a Kubernetes cluster with auto-scaling capabilities, ensuring that the platform can dynamically adjust its resource allocation to meet demand during peak usage times . Storage is similarly partitioned based on data type. Video recordings and artifacts are securely stored in object storage buckets like AWS S3, with access controlled via pre-signed URLs that expire quickly to prevent unauthorized access . Meanwhile, the high-frequency biometric telemetry is ingested into a specialized Time-Series database such as TimescaleDB or InfluxDB, which is optimized for handling massive volumes of timestamped data efficiently . This polyglot persistence strategy allows the system to leverage the right tool for each data type, ensuring optimal performance and cost-efficiency. The combination of these elements creates a robust, secure, and highly scalable architectural foundation upon which the advanced monitoring capabilities of modern proctoring systems are built.

Component	Technology/Standard	Primary Function	Key Benefit
Client-Side (Edge)	WebAssembly (Wasm) / WebGPU	Executes ML models for real-time CV inference [62].	Low Latency (<200ms) [12], Reduced Bandwidth .
Client-Side (Edge)	TensorFlow.js / ONNX Runtime Web	Runs quantized ML models (e.g., FaceMesh, Pose).	Cross-framework compatibility, efficient JS execution .
Client-Side (Edge)	MediaPipe	Provides high-fidelity facial landmark and pose estimation [39].	High accuracy, optimized for browser performance [55].
Server-Side (Cloud)	Kubernetes Cluster	Manages containerized backend services and auto-scaling.	Scalability, Resilience .
Server-Side (Cloud)	Apache Kafka	Ingests high-throughput, real-time telemetry streams from clients.	Buffering, decoupling producers (clients) from consumers (workers) .
Server-Side (Cloud)	GraphQL / REST API	Provides endpoints for session initiation, token generation, and reporting .	Flexible data fetching (GraphQL), standardized communication (REST).
Server-Side (Cloud)	PostgreSQL	Stores relational data: user profiles, session metadata, risk events .	ACID compliance, structured data management.
Server-Side (Cloud)	TimescaleDB / InfluxDB	Stores high-frequency biometric telemetry (gaze, pose, etc.) .	Optimized for time-series data, high write throughput.
Server-Side (Cloud)	AWS S3 / Similar	Securely stores video recordings and generated reports .	Durability, security, lifecycle management.

Advanced Gesture and Pose Recognition for Physical Integrity

The physical integrity of an online interview hinges on the system's ability to verify that the candidate is alone, unaided, and engaged with the assessment in real-time. Advanced gesture and pose recognition systems serve as the primary sensor for this dimension of proctoring, employing a suite of computer vision techniques to monitor the candidate's body language and environment. These systems move far beyond simple face detection, analyzing skeletal structures to identify a wide range of actions and objects that could indicate academic dishonesty. The technology stack for this capability is dominated by several key frameworks and methodologies, each contributing to a multi-layered defense against common cheating vectors.

At the forefront of this domain is Google's **MediaPipe**, a cross-platform framework frequently cited for its efficiency and high-performance implementations of various machine learning pipelines, particularly for human body and facial analysis [19] [65]. For pose estimation, MediaPipe Pose is a top-tier solution that detects 33 key points of the human body, including joints like the shoulders, elbows, wrists, hips, knees, and ankles [21] [62]. This detailed skeletal map allows the system to track the candidate's posture, head orientation, and limb movements with remarkable precision. MediaPipe supports multi-person pose detection, a critical feature for identifying a second person in the room. By configuring the `num_poses` parameter in the `PoseLandmarkerOptions`, the system can be instructed to detect up to four distinct individuals within a single frame [21]. Each detected individual is represented as a separate list of keypoints, enabling the software to differentiate between the candidate and any unauthorized personnel who may have entered the camera's field of view [21] [65]. The system analyzes the number of tracked poses; if more than one full set of landmarks is consistently detected, it triggers a high-severity flag for a secondary person [65]. MediaPipe is particularly well-suited for browser-based applications because its models are optimized to run efficiently on CPUs and GPUs via WebGL, making it a cornerstone of Edge AI proctoring solutions [55] [65].

Another prominent framework is **OpenPose**, an open-source system renowned for its bottom-up approach to multi-person pose estimation [23]. Unlike some top-down methods that first detect people and then analyze each one, OpenPose first identifies all individual body parts (e.g., hands, feet, faces) across the entire image and then uses Part Affinity Fields (PAFs)—a representation of how body parts are connected—to group them into complete skeletons for each person [23]. This makes OpenPose exceptionally effective at handling crowded scenes with multiple overlapping individuals, offering a different

trade-off compared to MediaPipe's focus on single-subject optimization [20]. While OpenPose offers state-of-the-art accuracy, its integration into browser environments can be more complex than MediaPipe's streamlined solutions. However, its robustness makes it a valuable alternative or complementary tool in a comprehensive proctoring pipeline, especially when considering the possibility of a candidate being observed by others in a shared space.

In addition to full-body pose estimation, many systems incorporate **YOLO (You Only Look Once)** object detection models, with **YOLOv8** being a popular choice, to scan for specific prohibited items [8] [19]. This is typically implemented in a two-stage pipeline. First, the YOLOv8 model, which is highly efficient and accurate for object detection, scans the video frame to draw bounding boxes around any objects it recognizes as "restricted," such as mobile phones, books, or laptops [7] [8]. Second, once a restricted object is located, a more specialized module, such as a traditional face detector like Dlib or a cropped version of the main pose estimator, can be applied to determine if a human hand is interacting with the object [8]. This modular approach combines the speed of YOLOv8 with the precision of other models, creating a robust system for detecting the unauthorized use of aids. The integration of object detection is a critical layer of defense, as it directly addresses the threat of candidates having access to hidden notes or electronic devices.

Beyond object detection, the system meticulously monitors specific gestures and movements that are indicative of cheating. One of the most commonly flagged gestures is the **hand-to-ear motion**, which could signify the use of a concealed Bluetooth earpiece to receive instructions or answers [65]. MediaPipe includes a dedicated Hand tracking module that provides 21 landmarks for each hand, allowing the system to precisely track finger and wrist positions [61]. By analyzing the trajectory of the hand's keypoints, the software can detect when a hand moves rapidly towards the ear and raise a corresponding alert [65]. Another critical area of monitoring is the candidate's head pose. Continuous tracking of head yaw (left-right rotation), pitch (up-down tilt), and roll (tilting of the head sideways) is standard practice . If the candidate turns their head beyond a predefined threshold, such as 45 degrees, the system can automatically mute the microphone and display a non-punitive warning overlay, prompting the candidate to refocus on the screen . This prevents the candidate from looking away to consult external materials. The combination of these techniques—multi-person pose detection for secondary individuals, object detection for unauthorized aids, and gesture tracking for prohibited actions—creates a comprehensive physical surveillance layer that is essential for securing the interview environment.

Technology/ Framework	Primary Function	Key Features & Metrics	Typical Application in Proctoring
MediaPipe Pose	Human Body Pose Estimation	Detects 33 body keypoints. Supports multi-person detection (configurable `num_poses`) [21]. Runs efficiently in-browser via WebGL/Wasm [62].	Identifying secondary persons in the frame, monitoring head pose (yaw, pitch, roll) to prevent looking away [21].
MediaPipe FaceMesh	Facial Landmark Detection	Detects 468 precise 3D facial landmarks, including eyes, nose, mouth, and iris position [37] [39].	Foundational input for eye tracking, lip reading (for speech analysis), and general head pose estimation [55] [65].
MediaPipe Hand	Hand Pose Estimation	Detects 21 landmarks per hand. Tracks finger and wrist positions in real-time [61].	Detecting specific prohibited gestures, such as a hand-to-ear motion indicating a hidden earpiece [65].
OpenPose	Multi-Person 2D Pose Detection	Bottom-up approach using Part Affinity Fields (PAFs) to associate body parts into skeletons [23]. Excels in crowded scenes.	Alternative/complementary method for secondary person detection, robust in scenarios with partial occlusions [20].
YOLOv8	Real-Time Object Detection	High-speed, high-accuracy detection of objects within bounding boxes. Can be trained on custom datasets [19].	Scanning the environment for prohibited items like mobile phones, books, or laptops [7] [8].
Dlib	Facial Recognition / Object Detection	Often used for face recognition tasks, such as verifying that a detected face matches the candidate's profile [8].	Secondary verification step after an object (like a phone) is detected to see if the candidate is interacting with it.

Multi-Dimensional Eye Tracking and Pupil-Level Analysis

While gesture and pose recognition provide a robust measure of physical presence and action, advanced eye tracking delves deeper into the cognitive and physiological states of the candidate, offering a more nuanced form of behavioral biometrics. Modern proctoring systems leverage sophisticated algorithms to interpret subtle eye movements and pupillary changes, moving beyond simple gaze direction to infer intent, cognitive load, and biological liveness. This dimension of monitoring is powered by a combination of foundational computer vision models and specialized analytical techniques that transform raw video data into actionable insights. The ultimate goal is to create a multi-dimensional profile of the candidate's visual behavior, which can be correlated with established patterns of cheating.

The technological bedrock for most browser-based eye tracking systems is **Google's MediaPipe FaceMesh** [39]. This framework is a high-fidelity facial landmark detection model capable of running in real-time on-device, making it ideal for Edge AI implementations [12] [39]. FaceMesh identifies and tracks 468 three-dimensional

coordinates on the human face, providing an incredibly detailed mesh that includes numerous points around the eyes and eyelids [39] [55]. This dense set of landmarks is the indispensable input for any subsequent gaze estimation or pupil analysis algorithm. The system uses the relative positions of these eye-related landmarks—the center of the pupil, the corners of the eyes, and the position of the eyelids—to calculate the direction of the gaze vector (pitch and yaw) and estimate the size of the pupil [37] [92]. Some advanced implementations, such as \webeyetrack, build upon MediaPipe's output to create scalable, real-time gaze estimation frameworks that can function effectively in challenging, real-world conditions [12]. The accuracy of these systems can be further enhanced with self-calibrating neural networks that adapt to individual differences in eye shape and distance from the camera [38] [92].

From the foundational gaze data provided by FaceMesh, the system derives several critical metrics related to eye movement. One of the most important is the analysis of **fixations and saccades**. Fixations are brief periods (typically lasting 100-400 milliseconds) where the eyes are relatively still, allowing for information processing [15]. Saccades are the rapid, ballistic movements that shift the gaze from one point of fixation to another [15]. Proctoring systems employ sophisticated algorithms to classify these events based on spatial and temporal thresholds, identifying patterns that deviate from normal, context-appropriate behavior [16] [18]. For example, prolonged off-screen gazes lasting longer than a predefined duration (e.g., 3 seconds) are often flagged as suspicious, as they may indicate the candidate is looking at external aids . Similarly, erratic or excessively frequent saccades, or abnormal blinking patterns, can be indicative of stress or an attempt to evade tracking [14]. Certain gaze patterns are strongly associated with cheating; for instance, sustained glances towards the top-right corner of the screen are often interpreted as a sign of referencing hidden notes or a second screen, a behavior known as "looking up and to the right" .

Perhaps the most powerful application of pupil-level analysis is the measurement of the **Pupillary Light Reflex (PLR)**, a cornerstone of active liveness detection [32]. The PLR is an involuntary physiological response where the pupil constricts in response to an increase in light intensity and dilates when light levels decrease [31] [32]. Proctoring systems exploit this reflex to definitively prove the presence of a living human being, effectively neutralizing photo and video replay attacks [35]. During an active check, the system rapidly cycles the background color or brightness of the interview interface on the screen. It then uses the on-device camera and MediaPipe FaceMesh to continuously measure the change in the candidate's pupil diameter in response to these artificial light shifts [34] [75]. A valid biological response—where the pupil contracts sharply in a bright flash and dilates in a dark transition—is a strong indicator of a real, living person. The absence of

this reflex is a definitive sign of a spoofing attack [35]. Beyond its anti-spoofing utility, the PLR is also a neurological marker that can reveal information about cognitive load, emotional arousal, and even certain medical conditions, adding another layer of insight for the system [30] [36] [56].

An even more advanced technique employed for liveness verification is **Remote Photoplethysmography (rPPG)**. This cutting-edge, non-contact method extracts a user's heartbeat from a standard video stream by analyzing minute, cyclical variations in skin color caused by blood flow [54] [88]. As blood pulses through the capillaries near the skin's surface, it causes subtle changes in the amount of red light absorbed and reflected, which are imperceptible to the naked eye but can be captured by a camera [54]. rPPG algorithms isolate these micro-variations in the RGB channels of the video feed over time and apply signal processing techniques, such as Fast Fourier Transform (FFT), to extract the heart rate signal [10]. Because photos, masks, and even some deepfakes lack a realistic, pulsatile blood flow, the successful detection of a heartbeat via rPPG serves as a powerful proof of life [9] [11]. Research has demonstrated the feasibility of integrating rPPG into face anti-spoofing systems, with some approaches using Recurrent Neural Networks (RNNs) to improve the accuracy of the measured signals [10] [53]. The combination of gaze tracking, saccade analysis, PLR, and rPPG creates a comprehensive suite of tools for monitoring the candidate's visual and physiological state, providing a formidable defense against a wide array of impersonation and assisted cheating techniques.

Analytical Technique	Underlying Technology	Metric(s) Measured	Purpose in Proctoring
Gaze Estimation	MediaPipe FaceMesh [39]	Gaze Vector (Pitch, Yaw) [37]	Determines where the candidate is looking on the screen or in the room. Flags off-screen gazes or glances at the top-right corner.
Fixation/Saccade Analysis	Custom Algorithms on Gaze Data	Duration and frequency of fixations and saccades [15]; Blinking patterns [14].	Identifies unnatural or excessive eye movements that may indicate stress, evasion, or reference to external aids.
Pupillary Light Reflex (PLR)	Screen Brightness Control + MediaPipe FaceMesh	Pupil Diameter Change Rate and Magnitude [31] [32].	Active liveness detection to distinguish a live person from a photo, mask, or video replay. Confirms biological presence.
Remote Photoplethysmography (rPPG)	Color Variation Analysis in Video Feed	Heart Rate (BPM) [10] [54]	Anti-spoofing; verifies a biological pulse to defeat sophisticated deepfake and mask attacks. Also indicates physiological state.
Pupil Size (Baseline)	MediaPipe Iris Model [37]	Resting Pupil Diameter	Monitors for cognitively-driven pupil dilation (independent of ambient light) which can indicate reading from hidden scripts or intense mental effort.

Environmental Isolation and Auditory Forensics

Creating a truly secure and isolated digital environment is arguably the most formidable challenge for online proctoring systems, given the inherent openness of web browsers and operating systems. A candidate's device is a complex ecosystem, and preventing unauthorized interactions requires a multi-pronged strategy that leverages browser APIs, clever workarounds, and continuous auditory monitoring. The goal is to establish a "digital lockdown" that prevents candidates from accessing external resources, communicating with others, or using auxiliary displays to gain an unfair advantage. This dimension of security relies heavily on the interplay between the proctoring application and the underlying browser and operating system, pushing the boundaries of what is technically feasible within a web context.

A primary method for controlling the candidate's immediate workspace is through the enforcement of **full-screen mode**. The proctoring application requests exclusive permission to display the interview in full screen, a standard browser capability designed to immerse users in a webpage without distractions [22]. This action effectively hides browser UI elements like the address bar and tabs, reducing the temptation and opportunity for the candidate to switch contexts. However, simply entering full-screen mode is not enough, as users can often exit it by pressing the `Esc` key or using other OS-level shortcuts. Therefore, the system must continuously monitor the state of the application. This is achieved primarily through the **Page Visibility API**, a critical browser API for environmental control [77]. This API provides events, specifically the `visibilitychange` event, which fires whenever the document's visibility state changes—for example, when the user switches to a different browser tab, minimizes the window, or navigates to another application [76] [91]. When the document's visibility status becomes "hidden," the proctoring software can immediately log the event, issue a warning to the candidate, and potentially escalate it to a formal risk flag [22]. This real-time feedback loop is the cornerstone of detecting attempts to multitask or access external information.

To further harden the environment, proctoring systems implement measures to block common avenues for cheating. Custom JavaScript can be used to intercept and disable right-click context menus, preventing candidates from easily opening browser developer tools, which could be used to inspect page elements or inject malicious scripts [22]. Similarly, text selection and copy-paste functions can be programmatically disabled to stop candidates from copying questions or prompts to search engines [22]. These client-side controls, combined with the Page Visibility API, create a baseline of environmental isolation. However, the rise of modern browser extension standards, particularly **Manifest V3**, has introduced new complexities. Manifest V3 imposes stricter permissions

and sandboxing to enhance security and privacy, limiting the power of extensions compared to the older Manifest V2 standard [27] [58]. For example, Manifest V3 extensions no longer have persistent background pages, making it harder to run long-lived monitoring processes. Developers of proctoring extensions must now rely on more event-driven architectures and APIs like the Screen Capture API [26]. The Screen Capture API allows an extension to capture a user's screen, but it is opt-in, requiring explicit user consent for each recording session [40]. This limitation has led to creative workarounds, such as creating a "hidden" pinned tab within the browser and starting the screen recording there to maintain continuous operation even if the main interview tab is switched [26]. The development of open-source, headless proctoring libraries highlights the ongoing community effort to build robust functionality within these constrained environments [22].

While browser controls manage the digital interface, **auditory forensics** extend the monitoring to the candidate's physical surroundings. Microphones are continuously monitored throughout the interview to detect sounds that are inconsistent with a solo examination. The primary concern is the detection of a **secondary voice** speaking to or guiding the candidate [28]. Audio analysis algorithms can be trained to distinguish between the candidate's voice and other sounds in the room, flagging instances of conversation or whispered assistance [43]. More advanced systems employ **speaker verification** techniques to confirm that any detected voice belongs to the registered candidate. Methods like Gaussian Mixture Models with Universal Background Models (GMM-UBM) or i-vector based systems can create a unique vocal signature of the candidate and compare it against any other voices detected in the audio stream [50]. Another key area of audio analysis is the detection of **keyboard typing**. The sound of typing can be analyzed to see if its cadence and rhythm match the candidate's natural speech patterns. A mismatch, such as fast, rhythmic typing while the candidate is silent, could suggest they are reading from a script or receiving real-time answers from someone else [28]. Some systems go so far as to use microphone arrays to perform active speaker detection, triangulating the horizontal position of a talker to determine if they are located at a desk (candidate) or elsewhere in the room (potential helper) [93] [94]. This combination of digital lockdown measures and sophisticated audio analysis forms a comprehensive barrier against environmental cheating.

Control Method	Browser API / Technique	Description	Limitations / Mitigations
Full-Screen Enforcement	Fullscreen API	Requests exclusive full-screen access for the interview window to minimize distractions. [22]	Users can often exit full-screen mode with `Esc`. Requires continuous monitoring to detect exits.
Tab Switching Detection	Page Visibility API (`visibilitychange` event)	Listens for changes in the document's visibility state to detect tab switches or window minimization. [77] [91]	Relies on browser support and proper implementation. Can be circumvented by switching to another application.
Context Menu Blocking	JavaScript Event Interception	Disables right-click context menus to prevent access to browser developer tools. [22]	Can be bypassed by using keyboard shortcuts (e.g., `Ctrl+Shift+I`).
Text Selection Prevention	CSS (`user-select: none`) / JavaScript	Prevents users from highlighting and copying text from the interview interface. [22]	Does not prevent copying from other applications or screenshots.
Secondary Monitor Detection	Screen Capture API (opt-in)	Allows the extension to capture the screen, but cannot programmatically scan for other displays. [40]	No direct programmatic detection. Heuristic analysis of the video feed may infer a second screen.
Extension Hardening	Manifest V3 Workarounds	Using a "hidden" pinned tab to maintain recording sessions despite API restrictions. [26] [49]	Complex to implement. Relies on browser-specific behaviors and may break with updates.
Secondary Voice Detection	Audio Forensics / Speaker Verification	Continuously analyzes audio for voices other than the candidate's using techniques like GMM-UBM. [28] [50]	Performance degrades in noisy environments. Requires a pre-recorded sample for effective verification.
Keyboard Typing Analysis	Audio Signal Processing	Analyzes the sound of keyboard typing to correlate its rhythm with the candidate's speech patterns. [28]	Less effective on quiet keyboards. Prone to false positives from nervous tapping.

System Implementation, Performance, and Security

The successful implementation of a secure AI proctoring system depends not only on the sophistication of its constituent technologies but also on the meticulous engineering of its data pipeline, adherence to strict performance benchmarks, and a robust security posture. The entire architecture must be designed to operate reliably under real-world conditions, balancing demanding computational loads with the need for minimal latency and maximum data protection. This involves careful selection of communication protocols, data serialization formats, and encryption standards, all orchestrated to create a seamless yet vigilant monitoring environment.

The communication between the client-side proctoring agent and the cloud backend is a critical performance bottleneck that must be carefully managed. To facilitate real-time interaction, the system utilizes **WebRTC** for establishing the high-fidelity, low-latency

audio and video stream between the candidate and the interviewer . For the continuous telemetry data generated by the CV models (e.g., gaze vectors, head pose, gesture confidences), a **WebSocket** connection is the preferred protocol . WebSockets provide a persistent, bidirectional channel over which the client can push small, frequent updates to the server without the overhead of repeated HTTP requests. To optimize bandwidth consumption, which is vital for candidates with limited internet connectivity, this telemetry data is serialized using an efficient binary format like **Protocol Buffers (Protobuf)** or **MessagePack** instead of plain JSON . These formats offer significant compression over text-based representations, helping to keep the total data payload under a target of 50 KB/s . On the server side, this high-volume stream of telemetry is ingested by a message broker like Apache Kafka, which decouples the data producers (clients) from the data consumers (backend processing workers), ensuring that the system can handle bursts of activity and scale horizontally as needed .

Performance is a non-negotiable requirement, with strict benchmarks defined for both the client and server sides. On the client, the primary metric is the **frame rate** at which the CV models can process the video stream. The system must be able to process video at a minimum of 30 frames per second (FPS) locally . If the FPS drops below a critical threshold of 15 FPS due to insufficient client hardware, the system should alert the user to close background applications to free up resources, or gracefully degrade the monitoring strictness . Latency is equally critical; the round-trip time for a CV inference and the transmission of its results must remain below 200 milliseconds to ensure the proctoring is perceived as instantaneous and does not desynchronize with the video feed [12]. On the server side, the key benchmark is **uptime**, which must be maintained at 99.99% to ensure business continuity and reliability for recruiters and candidates alike . This requires a resilient cloud infrastructure built on technologies like Kubernetes with auto-scaling groups and redundant components to handle failures gracefully.

Data security and privacy are paramount concerns in a system that handles sensitive biometric and personal information. The implementation plan must embed security at every layer of the architecture. All data transmitted between the client and server must be encrypted in transit using a strong protocol like **TLS 1.3** . At rest, sensitive data such as candidate videos and raw biometric logs must be stored in encrypted object storage (e.g., AWS S3 with SSE-KMS) and databases, respectively . A crucial principle is **data minimization**. Raw, unprocessed video streams containing biometric data should never leave the candidate's device unless absolutely necessary [7]. Instead, the system should transmit only the final, aggregated telemetry data or anonymized risk flags. For personally identifiable information (PII) like names and emails, end-to-end encryption should be applied at the application layer before the data is even written to the relational database . Biometric templates, such as the numerical vector representing a candidate's

unique facial geometry, should not be stored in plaintext. Instead, a cryptographic hash of the vector should be stored in the relational database, while the raw vector itself is stored in a separate, highly secured vector database . This prevents an attacker from reverse-engineering the original biometric data even if they compromise the database. Furthermore, a strict **data retention policy** must be enforced, with automated processes (e.g., using AWS Lambda or cron jobs) scheduled to permanently delete raw video and high-frequency telemetry data after a predetermined period, such as 90 days, retaining only the essential metadata and aggregated results for historical purposes .

Aspect	Implementation Detail	Rationale & Impact
Communication Protocol	WebRTC for media, WebSockets for telemetry .	Enables low-latency video/audio streaming and efficient, real-time data transfer.
Data Serialization	Protobuf or MessagePack .	Reduces bandwidth consumption by producing smaller payloads compared to JSON, crucial for candidates with poor internet.
Telemetry Ingestion	Apache Kafka .	Handles high-throughput, real-time data streams from thousands of concurrent sessions, providing buffering and scalability.
Client-Side Latency	Target <200ms for CV inference [12] .	Ensures real-time monitoring is responsive and does not cause stream desynchronization or a poor user experience.
Client-Side Frame Rate	Minimum 30 FPS, with alerts for drops below 15 FPS .	Maintains high-quality tracking; lower FPS can lead to missed events or inaccurate data.
In-Transit Encryption	TLS 1.3 .	Standard for securing all data flowing between the client and the cloud backend.
At-Rest Encryption	AES-256 for databases, AWS S3 SSE-KMS for object storage .	Protects sensitive data (videos, PII, biometric logs) from unauthorized access if storage is compromised.
Biometric Data Handling	Cryptographic hashing of facial embeddings stored in the DB .	Prevents reverse-engineering of biometric templates, a key requirement for compliance with laws like BIPA.
Data Minimization	Process and analyze data on-device; transmit only telemetry/risk flags [7] .	Reduces data breach risk, lowers bandwidth costs, and simplifies compliance with privacy regulations.
Data Retention	Automated purging of raw data after 90 days .	Adheres to privacy principles by not storing unnecessary data indefinitely.

Synthesis: Integrity Scoring and Navigating Systemic Risks

The culmination of the diverse technologies discussed—from gesture recognition and eye tracking to environmental isolation and auditory forensics—is the creation of a unified, multi-modal integrity score. This score, typically presented on a scale of 0 to 100, is the primary output for recruiters, synthesizing a vast amount of disparate data into a single,

actionable metric that reflects the likelihood of academic dishonesty during an interview . The calculation of this score is not a simple average but a sophisticated aggregation performed by an integrity scoring engine, which weighs different types of risk events based on their severity and context . For example, a flag for a secondary person in the room would carry more weight than a brief moment of off-screen gaze. This fusion of passive, continuous monitoring with periodic active checks creates a much more resilient system than any single modality could achieve alone. The resulting score, coupled with a detailed timeline of timestamped risk events, empowers recruiters to make informed judgments without having to manually review hours of video, transforming a cumbersome forensic task into an efficient, evidence-based review process .

However, the implementation of such a powerful surveillance system is fraught with systemic risks that must be proactively managed. The most significant challenge is avoiding a high rate of **false positives**. Overly aggressive algorithms, particularly in computer vision, can misinterpret nervous habits, medical conditions, or simple user errors as cheating. A candidate who blinks frequently, twitches, or needs to look away to think might be incorrectly flagged, leading to a negative assessment and potential reputational damage [4]. To mitigate this, a multi-layered mitigation strategy is essential. First, the system should incorporate contextual awareness; for instance, instead of immediately flagging a candidate who looks away, it should first trigger a gentle, non-punitive UI prompt asking them to refocus . Second, a human-in-the-loop review process should be mandatory for any session that receives a low integrity score, ensuring that automated flags are validated by a person before any consequences are applied . Third, the system should offer an "Accommodation Mode," which can be activated based on documented medical needs (e.g., for conditions like Tourette's syndrome or severe anxiety), temporarily disabling sensitive modules like gaze and micro-expression tracking to ensure fairness and accessibility .

Another major risk is **algorithmic bias**. Machine learning models used for facial recognition, pose estimation, and liveness detection are trained on large datasets, and if these datasets are not diverse and representative, the models can exhibit significant performance disparities across different demographics . For example, a facial recognition model might have a lower accuracy rate for individuals with darker skin tones or those who wear glasses, leading to higher false rejection rates for these groups. To combat this, the development process must include a rigorous **bias and fairness audit** phase. This involves testing the CV models extensively across a wide range of candidates with varying skin tones, ages, genders, and ethnicities under different lighting conditions . The goal is to ensure that the false positive and false negative rates are consistent across all demographic groups. Transparency in this process is also crucial; publishing the results of these audits can help build trust with users and stakeholders.

Finally, the project faces the risk of **privacy backlash and legal challenges**. The very nature of collecting and analyzing biometric data is controversial, and public perception can turn negative if not handled with extreme care [4]. There is a delicate balance between the need for security and the candidate's right to privacy. The mitigation strategy here is to prioritize privacy by design. By leveraging an Edge-Cloud architecture that processes and analyzes data locally on the candidate's device wherever possible, the system minimizes the amount of raw biometric data that ever touches the cloud [7]. Engaging legal counsel specializing in biometric privacy laws (like BIPA and GDPR) from the earliest stages of development is non-negotiable . Clear, transparent privacy policies that explain exactly what data is collected, why it is needed, and how it is protected are essential for obtaining and maintaining user consent. Ultimately, the success of a proctoring system will depend not only on its technical prowess but also on its ability to navigate these complex ethical, social, and legal landscapes responsibly.

Reference

1. Talview Interview Proctoring - Microsoft Marketplace https://marketplace.microsoft.com/en-us/product/talview.talview_interview_proctoring?tab=Overview
2. (PDF) Ensuring academic integrity through automated online exam ... https://www.researchgate.net/publication/400765099_Ensuring_academic_integrity_through_automated_online_exam_proctoring_a_decade_long_systematic_review
3. Remote Online Exam Proctoring Market Outlook 2025-2032 https://www.intelmarketresearch.com/remote-online-exam-proctoring-2025-2032-323-4419
4. College students' perceptions of remote online exams - Frontiers https://www.frontiersin.org/journals/education/articles/10.3389/feduc.2026.1721211/full
5. Remote Invigilation | Springer Nature Link https://link.springer.com/rwe/10.1007/978-3-031-51447-0_231-1
6. Key Factors in the Implementation of E-Proctoring in the Spanish ... https://www.mdpi.com/2071-1050/14/13/8112
7. AI-Driven Remote Proctoring & Integrity Solutions | EduSynch https://edusynch.com/products/remote-proctoring-solutions

8. An In-Browser Proctoring System Using YOLO-Based Object ... https://www.researchgate.net/publication/402110707_An_In-Browser_Proctoring_System_Using_YOLO-Based_Object_Detection_and_Gaze_Analysis
9. Face Liveness Detection by rPPG Features and Contextual Patch ... https://www.researchgate.net/publication/335254927_Face_Liveness_Detection_by_rPPG_Features_and_Contextual_Patch-Based_CNN
10. Robust Face Liveness Detection for Biometric Authentication using ... https://arxiv.org/html/2511.02645v1
11. Face Biometric Spoof Detection Method Using a Remote ... - PMC https://pmc.ncbi.nlm.nih.gov/articles/PMC9024982/
12. \webeyetrack: Scalable Eye-Tracking for the Browser via On-Device ... https://arxiv.org/html/2508.19544v1
13. Advanced Eye Tracking with Python & JavaScript - LinkedIn https://www.linkedin.com/posts/yuribeno_advanced-eye-tracking-with-python-javascript-activity-7187732736063823872-pV-Q
14. Strategies for enhancing automatic fixation detection in head ... - PMC https://pmc.ncbi.nlm.nih.gov/articles/PMC11541274/
15. Eye Movement and Pupil Measures: A Review - Frontiers https://www.frontiersin.org/journals/computer-science/articles/10.3389/fcomp.2021.733531/full
16. (PDF) Identifying fixations and saccades in eye-tracking protocols https://www.researchgate.net/publication/220811146_Identifying_fixations_and_saccades_in_eye-tracking_protocols
17. Automated Analysis Pipeline for Extracting Saccade, Pupil, and ... https://www.mdpi.com/2411-5150/8/1/14
18. Identification of fixations and saccades in eye-tracking data using ... https://arxiv.org/html/2512.23926v2
19. NFL- MultiPose Estimation using YOLOv8 & Mediapipe - Kaggle https://www.kaggle.com/code/dariussingh/nfl-multipose-estimation-using-yolov8-mediapipe
20. Comparing YOLOv8 and MediaPipe for pose detection - LinkedIn https://www.linkedin.com/posts/umairwaheed128_computervision-poseestimation-fitnesstech-activity-7331680535762657282-G3Y8
21. Issue with tracking multiple persons on mediapipe - Stack Overflow https://stackoverflow.com/questions/78270783/issue-with-tracking-multiple-persons-on-mediapipe
22. A headless hook-based exam proctoring system with React https://dev.to/anshsaini/a-headless-hook-based-exam-proctoring-system-with-react-20do

23. Realtime Multi-Person 2D Pose Estimation using Part Affinity Fields https://arxiv.org/abs/1812.08008
24. Manifest v3 and Extensions - Microsoft Community Hub https://techcommunity.microsoft.com/discussions/edgeinsiderenterprise/manifest-v3-and-extensions/3614186
25. Developers Insight On Manifest v3 Privacy and Security ... - arXiv https://arxiv.org/html/2507.13926v1
26. Chrome Extension Manifest V3 Screen Recording Ends When ... https://stackoverflow.com/questions/72432588/chrome-extension-manifest-v3-screen-recording-ends-when-changing-the-tab
27. From Manifest V2 to V3: A Study on the Discoverability of Chrome ... https://www.researchgate.net/publication/376099819_From_Manifest_V2_to_V3_A_Study_on_the_Discoverability_of_Chrome_Extensions
28. In-Depth Analysis of Online Exam Proctoring Systems to Address ... https://www.researchgate.net/publication/396129884_In-Depth_Analysis_of_Online_Exam_Proctoring_Systems_to_Address_Key_Research_Questions
29. CVPR 2023 Papers https://cvpr.thecvf.com/virtual/2023/papers.html
30. rPLR: an imaging system for measuring pupillary light reflex at a ... https://pmc.ncbi.nlm.nih.gov/articles/PMC4308726/
31. Pupillary Light Reflex Correction for Robust Pupillometry in Virtual ... https://dl.acm.org/doi/abs/10.1145/3530798
32. Pupillary Light Reflex (PLR) - Cleveland Clinic https://my.clevelandclinic.org/health/articles/pupillary-light-reflex-plr
33. Pupillary Light Reflex as a Diagnostic Aid from Computational ... https://www.researchgate.net/publication/350623774_Pupillary_Light_Reflex_as_a_Diagnostic_Aid_from_Computational_Viewpoint_A_Systematic_Literature_Review
34. Automated Pupillary Light Reflex Test on a Portable Platform - ar5iv https://ar5iv.labs.arxiv.org/html/1905.08886
35. Pupil light reflex evoked by light-emitting diode and computer screen https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0197739
36. Associations between the pupil light reflex and the broader autism ... https://www.frontiersin.org/journals/human-neuroscience/articles/10.3389/fnhum.2022.1052604/full
37. [PDF] MediaPipe Iris and Kalman Filter for Robust Eye Gaze Tracking https://www.atlantis-press.com/article/126011300.pdf

38. Video-Based Gaze Detection for Oculomotor Abnormality ... - MDPI https://www.mdpi.com/2076-3417/14/4/1519

39. Validation of webcam-based eye-tracking for clinically relevant ... https://www.sciencedirect.com/science/article/pii/S2666521226000426

40. Screen Capture API - MDN Web Docs - Mozilla https://developer.mozilla.org/en-US/docs/Web/API/Screen_Capture_API

41. CVPR 2024 Accepted Papers https://cvpr.thecvf.com/Conferences/2024/AcceptedPapers

42. CVPR 2024 Call for Papers https://cvpr.thecvf.com/Conferences/2024/CallForPapers

43. A Robust Voice Liveness Detection System for Smart Speakers - arXiv https://arxiv.org/html/2510.24393v1

44. CVPR 2024 Open Access Repository https://openaccess.thecvf.com/content/CVPR2024/html/Kim_Retrieval-Augmented_Open-Vocabulary_Object_Detection_CVPR_2024_paper.html

45. CVPR 2024 Open Access Repository https://openaccess.thecvf.com/content/CVPR2024/html/Zhang_HOI-M3_Capture_Multiple_Humans_and_Objects_Interaction_within_Contextual_Environment_CVPR_2024_paper.html

46. Honorlock Alternative for Secure Online Proctoring - Integrity Advocate https://integrityadvocate.com/resource-center/blog/the-best-honorlock-alternative-is-integrity-advocate/

47. Low-Cost Eye-Tracking Fixation Analysis for Driver Monitoring ... https://www.mdpi.com/1424-8220/25/22/7028

48. Eye Gaze Tracking With a Web Camera in a Desktop Environment https://www.researchgate.net/publication/276664121_Eye_Gaze_Tracking_With_a_Web_Camera_in_a_Desktop_Environment

49. chrome - A Practical Guide with Manifest V3 - DEV Community https://dev.to/ryu0705/building-chrome-extensions-in-2026-a-practical-guide-with-manifest-v3-12h2

50. (PDF) Robust Voice Liveness Detection and Speaker Verification ... https://www.researchgate.net/publication/320260730_Robust_Voice_Liveness_Detection_and_Speaker_Verification_Using_Throat_Microphones

51. CVPR 2026 - The Computer Vision Foundation https://cvpr.thecvf.com/

52. 无主题 https://talent.shixizhi.huawei.com/iexam/1365189427395223554/examInfo?examId=1626520123798548481&sxz-lang=en_US

53. Face Liveness Detection by rPPG Features and Contextual Patch ... https://www.semanticscholar.org/paper/Face-Liveness-Detection-by-rPPG-Features-and-CNN-Lin-Li/033b9eba42cbe2c3598f0062fab52216c7daa6bc

54. [PDF] Flow-Attention-based Spatio-Temporal Aggregation Network for 3D ... https://arxiv.org/pdf/2310.16569
55. Real-Time Face Tracking in the Browser with MediaPipe https://dev.to/kenzic/real-time-face-tracking-in-the-browser-with-mediapipe-22c9
56. Pupillary light reflex (PLR) assessment in open-eye and closed-eye... https://www.researchgate.net/figure/Pupillary-light-reflex-PLR-assessment-in-open-eye-and-closed-eye-conditions-a-Schematic_fig1_382915067
57. Infrared Video Pupillography Coupled with Smart Phone LED for ... https://www.frontiersin.org/journals/integrative-neuroscience/articles/10.3389/fnint.2017.00006/full
58. Manifest V3 Unveiled: Navigating the New Era of Browser Extensions https://arxiv.org/html/2404.08310v1
59. CVPR 2025 Accepted Papers https://cvpr.thecvf.com/Conferences/2025/AcceptedPapers
60. Md Sahidullah - CV Hal https://cv.hal.science/sahid
61. (PDF) Eye-Controlled Human-Computer Interaction System Using ... https://www.researchgate.net/publication/392883530_Eye-Controlled_Human-Computer_Interaction_System_Using_MediaPipe_and_Computer_Vision
62. Bigthinx AI Engineer Interview Prep | PDF | Machine Learning ... https://www.scribd.com/document/906706392/Bigthinx-Interview-Prep-Sheet
63. (PDF) Automated Online Exam Proctoring - ResearchGate https://www.researchgate.net/publication/312676827_Automated_Online_Exam_Proctoring
64. Automated Pupillary Light Reflex Test on a Portable Platform https://www.semanticscholar.org/paper/Automated-Pupillary-Light-Reflex-Test-on-a-Portable-Temel-Mathew/64c4f277ccc0237be17b40c5a0f20fe3489fb8fb
65. Arnab Lahiri's Post - LinkedIn https://www.linkedin.com/posts/arnab-lahiri_integrating-face-detection-and-ai-proctoring-activity-7225752223509528576-TWY6
66. A Robust Voice Liveness Detection System for Smart Speakers - arXiv https://arxiv.org/abs/2510.24393
67. CVPR 2026 Open Access Repository https://openaccess.thecvf.com/content/CVPR2026W/MMFM5/html/khan_TRACE_Training-Free_Partial_Audio_Deepfake_Detection_via_Embedding_Trajectory_Analysis_CVPRW_2026_paper.html
68. Properly using chrome.tabCapture in a manifest v3 extension https://stackoverflow.com/questions/66217882/properly-using-chrome-tabcapture-in-a-manifest-v3-extension

69. Talview live proctoring integration: the candidate experience https://risr-assess.zendesk.com/hc/en-gb/articles/38225743778833-Talview-live-proctoring-integration-the-candidate-experience
70. Talview Online Proctoring and Assessments Platform https://marketplace.microsoft.com/en-us/product/saas/talview.talviewonlineassessments?tab=overview
71. Pupillary light reflex (PLR) recordings (N = 16) under 1-s light... https://www.researchgate.net/figure/Pupillary-light-reflex-PLR-recordings-N-16-under-1-s-light-stimulus-filtered-by-the_fig4_346722323
72. Measuring the Pupillary Light Reflex Using Portable Instruments in ... https://www.mdpi.com/2411-5150/8/4/60
73. Modeling Transient Pupillary Light Reflex Induced by a Short ... - PMC https://pmc.ncbi.nlm.nih.gov/articles/PMC4318650/
74. (PDF) rPLR: An Imaging System for Measuring Pupillary Light https://research.amanote.com/publication/P5ZH2nMBKQvf0BhiI-W3/rplr-an-imaging-system-for-measuring-pupillary-light-reflex-at-a-distance
75. Pupil light reflex evoked by light-emitting diode and computer screen https://pmc.ncbi.nlm.nih.gov/articles/PMC5999086/
76. Chrome Extension: How to Disable Page Visibility API - Stack Overflow https://stackoverflow.com/questions/47660653/chrome-extension-how-to-disable-page-visibility-api
77. Page Visibility API - MDN Web Docs - Mozilla https://developer.mozilla.org/en-US/docs/Web/API/Page_Visibility_API
78. CVPR 2026 Papers https://cvpr.thecvf.com/virtual/2026/papers.html
79. CVPR 2023 Call for Papers https://cvpr.thecvf.com/Conferences/2023/CallForPapers
80. CVPR 2026 Open Access Repository https://openaccess.thecvf.com/content/CVPR2026/html/Chu_UniLS_End-to-End_Audio-Driven_Avatars_for_Unified_Listening_and_Speaking_CVPR_2026_paper.html
81. CVPR 2026 Open Access Repository https://openaccess.thecvf.com/content/CVPR2026/html/Huang_CineSRD_Leveraging_Visual_Acoustic_and_Linguistic_Cues_for_Open-World_Visual_CVPR_2026_paper.html
82. Biological validation of filtered lights (N = 16) Pupillary Light... https://www.researchgate.net/figure/Biological-validation-of-filtered-lights-N-16-Pupillary-Light-Reflex-PLR-parameters_fig5_346722323
83. (PDF) Pupil and Pupillary Light Reflex - ResearchGate https://www.researchgate.net/publication/399154048_Pupil_and_Pupillary_Light_Reflex

84. The pupillary light reflex (PLR) as a marker for the ability to work or ... https://pmc.ncbi.nlm.nih.gov/articles/PMC8422642/

85. Towards Open-Vocabulary Audio-Visual Event Localization https://openaccess.thecvf.com/content/CVPR2025/html/Zhou_Towards_Open-Vocabulary_Audio-Visual_Event_Localization_CVPR_2025_paper.html

86. Visually Supervised Speaker Detection and Localization via ... - arXiv https://arxiv.org/abs/2203.03291

87. CVPR 2023 Audio-visual papers - 知乎专栏 https://zhuanlan.zhihu.com/p/631900793

88. Towards Open-Vocabulary Audio-Visual Event Localization https://www.researchgate.net/publication/394593361_Towards_Open-Vocabulary_Audio-Visual_Event_Localization

89. Chrome等现代浏览器原生分屏功能的JavaScript API？ - 火山引擎 https://www.volcengine.com/article/123826

90. 页面可见性API - Web API - MDN 文档 https://mdn.org.cn/en-US/docs/Web/API/Page_Visibility_API

91. Managing Page Visibility During Tests | PDF | Mobile App - Scribd https://www.scribd.com/document/861194575/JavaScript-Page-Visibility-API

92. Real-Time Eye Gaze Estimation for Dynamic Head Movement https://www.linkedin.com/posts/amirmahdi-abootalebi_real-time-eye-gaze-estimation-for-dynamic-activity-7307381175130456064-enWc

93. [2307.14739] Audio Inputs for Active Speaker Detection and ... - arXiv https://arxiv.org/abs/2307.14739

94. Audio Inputs for Active Speaker Detection and Localization via ... https://www.researchgate.net/publication/372684229_Audio_Inputs_for_Active_Speaker_Detection_and_Localization_via_Microphone_Array

95. VOICES (Voices Obscured In Complex Environmental Settings) https://opendatalab.com/OpenDataLab/VOICES