Qwen

Beyond the Screen: An Anatomy of AI Interview Proctoring, Spoofing Evasion, and Advanced Biometric Defenses

Core Technical Arsenal for Proctoring Automated Interviews

The landscape of AI-powered interviewing, utilized by various technology and hiring companies, is built upon a sophisticated suite of computer vision and machine learning technologies designed to ensure assessment integrity [3]. These systems move far beyond simple transcription of answers, employing a multi-layered technical arsenal to monitor candidate behavior in real-time. The primary objective is to detect any deviation from authentic, solo participation, which could indicate cheating. This involves a continuous stream of analysis focused on three key domains: eye gaze, head pose, and physical gestures. While specific commercial platforms like HireVue, Pymetrics, and MyInterview remain largely opaque about their proprietary scoring algorithms, public research and system descriptions reveal a common technological foundation for proctoring [1] [3]. The most prevalent method for direct monitoring is eye gaze tracking, which analyzes where a candidate is looking to infer attention and potential off-screen assistance [3]. Systems generate heatmaps and track fixation sequences to visualize and quantify the distribution of a candidate's gaze across the screen [3]. Research indicates that students may look away from their screen during exams, and this behavior can be detected and flagged by the system [3]. However, the understanding of how major platforms score interviews has evolved; for instance, it is noted that many people incorrectly assume HireVue judges them based on eye contact or facial expressions, when its current methodology is more nuanced [1].

A systematic literature review covering studies from 2016 to 2022 identified eight major features extracted from eye-tracking data for classification tasks, highlighting the depth of this analysis [2]. These features include pupil size, saccade (rapid eye movements), fixation, velocity of eye rotation, blink characteristics, pupil position, electrooculography (EOG) signals, and overall gaze point [2]. Among these, "fixation"—the periods when the eyes are relatively still and focused—was the most commonly used feature for

classification, appearing in 19 out of 37 reviewed studies [2]. This suggests that the duration and location of a candidate's focus points are considered highly indicative of cognitive processing and engagement. Pupil diameter was the second most common feature, used in 10 studies, likely because pupil dilation is an involuntary physiological response linked to cognitive load and emotional arousal [2]. Other less frequently used but potentially valuable features include saccades, blink rate, and pupil position [2]. The integration of these eye-tracking features with other data modalities, such as Electroencephalogram (EEG) signals, has been shown to improve the performance of classification models, underscoring the trend toward multi-modal analysis [2]. The most common machine learning classifier employed in these studies is the Support Vector Machine (SVM), used in 20 of the 37 articles reviewed, indicating its established utility in pattern recognition tasks within this domain [2].

Beyond eye gaze, head pose estimation is another critical component of the technical arsenal. This technology monitors the yaw (side-to-side), pitch (up-and-down), and roll (tilting the ear towards the shoulder) angles of a candidate's head [3] [7]. Its primary function is to identify if a candidate is looking off-screen, which could imply they are consulting unauthorized materials or receiving assistance from someone else in the room [3]. One study reported achieving 87% accuracy in pose estimation using a deep learning model called Attentive Net to solve the Perspective-n-Point (PNP) equation, demonstrating the feasibility of precise head movement tracking [3]. The ability to analyze head movements provides crucial context; for example, one framework demonstrated a positive correlation between head movements and extraversion, while finding a negative correlation with neuroticism [7]. Confident and relaxed individuals were observed to exhibit more head movements, which was also linked to higher sales abilities [7]. By using significant changes in head movement angles as predictive features, a model achieved approximately 80% accuracy in classifying these personality traits, showcasing the richness of data available from head pose analysis [7]. For extraction, systems utilize libraries like OpenCV, 3DDFA, and mediapipe to detect facial landmarks and calculate these three-dimensional rotation angles throughout the interview [7].

Hand and body gesture recognition complements gaze and head pose analysis by providing a broader view of the candidate's physical environment and actions. This is primarily accomplished using pose estimation models such as OpenPose and MediaPipe [3]. These models create a skeletal representation of the person in the video feed, identifying key body joints and tracking their movement over time. This allows the system to monitor for a range of suspicious activities, including leaving the seat, handling objects, or making hand gestures that might signal communication with an outside party

[3]. The system can be trained to recognize specific patterns associated with malpractice. For instance, activity recognition systems often combine pose estimation models with deep learning classifiers, such as Convolutional Neural Networks (CNNs), to identify prohibited actions [3]. One proposed system utilizing a 63-layer DeepCNN model for activity recognition achieved a high accuracy of 92.99%, indicating the effectiveness of this approach in flagging suspicious physical behaviors [3]. Furthermore, facial recognition itself serves a dual purpose. It is used not only for identity verification at the start of the interview to prevent impersonation but also for emotion detection to identify suspicious behaviors [3]. Common face detection models include Haar cascades, dlib, and the Multi-task Cascaded Convolutional Neural Network (MTCNN) [3]. One proposed system combining MTCNN for face detection with FaceNet for verification achieved an impressive accuracy of 99.21%, reinforcing the reliability of modern facial recognition for authentication purposes [3]. Together, these core technologies form a comprehensive surveillance layer, analyzing a candidate's visual focus, posture, and physical actions to build a behavioral profile intended to flag any anomalies indicative of cheating.

Technology	Primary Function	Key Metrics/Features Analyzed	Example Models/Methods
Eye Gaze Tracking	Monitor attention, detect off-screen glances, infer cognitive load	Gaze Point, Fixation, Pupil Size, Saccade, Blink Rate, Velocity [2] [3]	Sensors and algorithms to determine gaze points and fixations [3]
Head Pose Estimation	Detect looking off-screen, abnormal posture, potential assistance	Yaw, Pitch, Roll Angles [3] [7]	Attentive Net for solving Perspective-n-Point (PNP) equation [3]
Hand & Body Gesture Recognition	Identify suspicious physical actions, object handling, seat departure	Hand/object proximity, full-body pose keypoints, movement patterns [3]	OpenPose, MediaPipe, DeepCNN classifiers [3]
Facial Recognition	Identity verification, emotion detection, nonverbal cue analysis	Facial landmarks, identity match, expression classification (smiling, nodding) [3] [7]	MTCNN, FaceNet, Haar cascades, dlib [3]

Liveness Detection and Spoofing Countermeasures

Before any meaningful behavioral analysis can occur, AI proctoring systems must first establish a foundational layer of security: verifying that the entity being interviewed is a genuine, live human. This is the purpose of liveness detection, a critical set of anti-spoofing techniques designed to thwart attempts to impersonate a candidate using static images (photo attacks), dynamic media like videos or screen recordings (video replay attacks), or constructed masks (mask attacks) [4] [5]. Relying solely on passive facial

recognition is insufficient, as sophisticated attackers can exploit these vulnerabilities. Therefore, modern systems incorporate active and passive checks to confirm biological liveliness. Passive methods analyze inherent properties of a live face, such as the subtle micro-movements and natural texture variations that are absent in fakes. Active methods require the candidate to perform specific actions, like following a moving object on the screen with their eyes, to prove they are a live person responding in real-time [5].

One of the most promising and technically robust approaches to liveness detection involves analyzing pupillary response. The human pupil exhibits complex, involuntary reactions to both light and cognitive tasks, which are difficult for artificial stimuli to replicate. A proposed Presentation Attack Detection (PAD) system leverages this by presenting the user with visual stimuli that move along randomized trajectories [5]. The user is prompted to follow this moving stimulus with their gaze. The system then captures and analyzes the user's pupillary motion in response to these controlled visual cues [5]. Impostors attempting to use a photograph or a static mask cannot produce the correct physiological response, as their eyes lack the necessary neural pathways. This method effectively distinguishes genuine users from impostors. In experiments evaluating this technique, the system demonstrated exceptionally high detection rates. For 2D mask attacks (e.g., a printed photo with holes), the system achieved a True Positive Rate (TPR) of 99.0% at a 10% False Positive Rate (FPR). For more sophisticated 3D mask attacks (constructed from the victim's own data), the TPR reached 99.4% under the same conditions [5]. This highlights the power of using pupillary dynamics as a liveness indicator. However, the research explicitly notes a significant limitation: this particular gaze-based approach does not protect against video replay attacks, where an attacker plays a pre-recorded video of the legitimate user. This underscores the necessity of a multi-modal defense strategy, as no single technique can address all potential spoofing vectors [5].

Other research into liveness detection explores alternative methods based on facial landmark analysis. One comparative study evaluated five different approaches, including the analysis of facial landmarks projection ratio [6]. Another project focused on liveness detection through the analysis of fake face movement and the examination of the pupil [4]. These methods aim to detect the unnatural rigidity or inconsistencies in a fake face's structure or movement compared to a live one. Continuous user verification represents a more advanced application of liveness principles. Instead of a one-time check at the beginning of the session, this approach iteratively confirms the candidate's identity throughout the entire interview [3]. This is often achieved through multi-modal biometric fusion, combining signals from different sources like face recognition, keystroke dynamics, and touch-screen interactions. Such a fused approach was reported to achieve

a high accuracy of 99.12% in continuously verifying a user's identity, making it extremely difficult for an attacker to substitute themselves mid-interview [3]. Some systems even integrate Aadhar biometric data for this purpose [3]. The goal of these continuous verification methods is to maintain a high level of confidence that the person interacting with the system remains the authenticated candidate from start to finish.

In addition to biometric verification, AI proctoring systems employ several other technical measures to create a secure environment and prevent cheating. Browser lockdown is a common feature that prevents candidates from switching tabs or accessing other applications on their computer, thereby restricting their ability to search for answers online or consult external documents [3]. Port blocking is another measure that restricts network access to certain ports, limiting the candidate's ability to connect to unauthorized devices or networks [3]. Mobile device detection is also a critical safeguard. Using object detection models like Yolov3, which can be trained on datasets like COCO, the system can scan the candidate's environment for the presence of phones or other mobile devices [3]. The detection process can involve identifying phones based on facial key points and object distance, ensuring that candidates are not using secondary devices to receive answers or cheat in some other way [3]. These technical controls work in concert with the biometric monitoring layers. While eye tracking and gesture analysis observe the candidate's behavior, browser lockdown and port blocking enforce the rules of the testing environment. This combination of observation and enforcement creates a formidable barrier against many common forms of cheating. The table below summarizes key anti-spoofing and security measures.

Security Measure	Description	Purpose	Example Technologies/Methods
Liveness Detection (Active)	Requires the user to perform actions to prove they are a live human.	Prevent impersonation via photos, masks, or videos.	Randomized visual stimuli to capture pupillary response [5].
Liveness Detection (Passive)	Analyzes inherent properties of a live face without requiring user action.	Differentiate live tissue from fake materials (paper, silicone).	Analysis of facial landmark projection ratios, skin texture [4] [6].
Continuous User Verification	Iteratively confirms the user's identity throughout the session.	Ensure the same person remains in front of the camera.	Multi-modal biometric fusion (face, keystroke, touch) [3].
Browser Lockdown	Restricts the candidate's ability to switch tabs or open new applications.	Prevent online searches and access to unauthorized resources.	Software-level restrictions on browser functionality.
Port Blocking	Limits network access to certain ports on the candidate's computer.	Prevent connection to unauthorized external devices or networks.	Network traffic filtering.
Mobile Device Detection	Scans the candidate's environment for the presence of phones or tablets.	Prevent the use of secondary devices for cheating.	Object detection models like Yolov3 [3].

Candidate Evasion Techniques and System Vulnerabilities

As AI proctoring systems have become more sophisticated, so too have the methods employed by candidates to circumvent their technical defenses. This dynamic creates a persistent arms race where developers must constantly innovate to close newly discovered vulnerabilities. The evasion tactics can be broadly categorized into spoofing attacks, behavioral manipulation, and the use of external aids. Understanding these counter-strategies is crucial for developing more resilient systems and for setting realistic expectations about the capabilities of current technology. One of the most fundamental evasion techniques is spoofing, where an individual attempts to impersonate the registered candidate. This includes "photo attacks," where a high-resolution image of the candidate is displayed to fool the facial recognition system [5]. More advanced are "2D mask attacks," which involve a printed photograph of the candidate, sometimes with holes cut out for the eyes and mouth, and "3D mask attacks," which are constructed from the candidate's own data to create a more realistic replica [5]. While some liveness detection systems are highly effective against these, particularly 3D masks, the challenge varies significantly depending on the context. For instance, the gaze-based liveness detection system described in one study struggled with photo attack detection, especially on smaller mobile phone screens [5]. At a stringent 1% False Positive Rate setting, the True Positive Rate for detecting photo attacks on a phone format dropped to as low as 16.1%, although performance improved with longer challenge durations [5]. This highlights a key vulnerability: the effectiveness of anti-spoofing measures can degrade in less controlled environments or on lower-quality hardware.

Another category of evasion involves behavioral manipulation. A candidate might attempt to pre-record their answers and then read from a script or notes, thus avoiding the spontaneous interaction that AI systems are designed to assess [5]. This tactic directly undermines the platform's goal of evaluating real-time communication skills. To appear more natural, a candidate might also engage in behavioral mimicry, consciously trying to replicate the nonverbal cues that are believed to be positively correlated with desirable traits, such as nodding, smiling, or maintaining steady eye contact [5] [7]. If the system's algorithm is simplistic, it could be fooled into interpreting this mimicry as genuine confidence or engagement. A more advanced form of this is hiring a "ghost writer" who provides answers to the candidate in real-time through a hidden earpiece or other covert means [5]. This type of collusion is particularly difficult for purely visual systems to detect, as the candidate's on-camera behavior might appear perfectly authentic while they are receiving external assistance. This is why a multi-faceted approach that combines

visual analysis with other technical controls, such as audio monitoring and browser lockdowns, is essential for mitigating such risks [3].

The use of unauthorized digital and physical aids represents a third major avenue for evasion. Candidates may attempt to have unauthorized documents, notes, or textbooks visible within the camera's field of view, either on their desk or perhaps even taped to the wall behind them [5]. While a well-calibrated system with good resolution might detect these objects, their concealment or placement can make detection challenging. The primary weakness in the face of these tactics lies in the limitations of individual technologies. As previously noted, a gaze-based liveness detection system is ineffective against video replay attacks [5]. Similarly, while head pose analysis can detect if a candidate is looking down, it cannot definitively know if they are looking at a hidden piece of paper or simply taking a moment to think. This gap in knowledge necessitates a layered security architecture. The table below outlines common evasion techniques and the corresponding system vulnerabilities they exploit.

Evasion Technique	Description	System Vulnerability Exploited
Photo Attacks	Using a high-resolution photograph of the candidate to impersonate them.	Inadequate liveness detection, inability to distinguish static images from live faces. [5]
Mask Attacks (2D/3D)	Using a printed photo or a constructed 3D mask made from the candidate's data.	Static nature of fake materials, inability to replicate micro-movements or physiological responses. [5]
Video Replay Attacks	Playing a pre-recorded video of the legitimate candidate to the system.	Reliance on passive facial recognition without active liveness challenges (e.g., gaze-following). [5]
Pre-recording Answers	Recording answers in advance to read from a script or notes during the interview. [5]	Difficulty in distinguishing spontaneous speech from rehearsed delivery.
Ghost Writer Assistance	Receiving answers in real-time from an accomplice via hidden earpieces or other means. [5]	Visual-only analysis cannot detect external audio input or illicit communication.
Unauthorized Resource Use	Having notes, textbooks, or other documents visible in the camera's field of view. [5]	Field of view limitations or object recognition inaccuracies may fail to detect concealed materials.

These vulnerabilities demonstrate that no single technological solution is a silver bullet. The effectiveness of an AI proctoring system depends on the synergy of its components. For example, a system that combines robust liveness detection (like the gaze-following challenge) with browser lockdown and audio monitoring would be significantly more resistant to a wide range of these evasion tactics. However, the ongoing development of new evasion techniques ensures that the challenge for system designers is perpetual. They must not only react to existing threats but also anticipate future ones, making the domain a constant exercise in applied adversarial machine learning.

Advanced Behavioral Biometrics and Multi-Modal Data Fusion

To build truly resilient AI interview systems, developers are increasingly turning to advanced behavioral biometrics and the principle of multi-modal data fusion. This approach moves beyond analyzing isolated behaviors like eye gaze or head nods and instead seeks to construct a holistic, dynamic profile of the candidate by integrating data from multiple sensors and channels. The underlying premise is that a single biometric signal can be noisy, ambiguous, or vulnerable to spoofing. However, when combined with other signals, the resulting composite profile becomes far more reliable and difficult to manipulate. This integrated analysis allows the system to differentiate between authentic, complex human behavior and the simpler, often more rigid patterns of cheating or deception. The most sophisticated systems fuse data streams from various sources, including but not limited to eye-tracking, head pose, facial expressions, hand gestures, and even audio prosody [2] [3] [7].

Research in related fields provides strong evidence for the efficacy of this multi-modal approach. A systematic literature review of 37 relevant articles found that the majority of studies aiming for high performance combined eye-tracking data with other physiological or behavioral signals [2]. Electroencephalogram (EEG) was the most common complementary signal, used in nine of the fourteen studies that integrated multiple modalities [2]. Other combinations included Galvanic Skin Response (GSR) for measuring stress, functional MRI (fMRI) for brain activity mapping, and thermal imaging [2]. While fMRI is impractical for a standard interview setting, the principle holds: combining different types of data provides a richer context for interpretation. In the context of practical proctoring systems, this translates to fusing face recognition with other continuous authentication methods like keystroke dynamics or mouse movements [3]. A system that verifies identity through a live human's face, then continues to monitor their unique typing rhythm and mouse cursor patterns throughout the session, creates a much stronger security posture than one relying on face recognition alone [3]. This multi-modal fusion was reported to achieve a high accuracy of 99.12% in continuous user verification, demonstrating its power in maintaining session integrity [3].

Machine learning acts as the central engine that makes sense of this complex, multi-channel data. Classifiers, particularly Support Vector Machines (SVM), are trained on large datasets containing examples of both authentic candidate behavior and various forms of cheating [2]. The SVM learns to identify the subtle, complex patterns that distinguish a nervous but honest candidate from a confident cheater. For instance, a

predictive model that classified personality traits from head movements did so by analyzing significant changes in the yaw, pitch, and roll angles [7]. By training on thousands of hours of recorded interviews, these models can learn to associate specific combinations of behaviors—such as frequent glances away from the camera accompanied by irregular pupil dilation and tense jaw movements—with a high probability of malfeasance. This data-driven approach allows the system to adapt and improve over time as it is exposed to more data. The framework for assessing personality traits and nonverbal cues explicitly uses a combination of computer vision libraries (OpenCV, 3DDFA, mediapipe) to extract geometric facial features, smile detection, and eye gaze, alongside audio feature extraction (Librosa library) to analyze speech patterns [7]. This demonstrates a practical implementation of multi-modal analysis, where visual and auditory signals are processed together to build a more complete picture of the candidate's state and intentions [7].

The application of advanced biometrics extends the scope of analysis beyond simple observation. By treating the candidate's behavior as a rich stream of data, the system can infer deeper states like cognitive load, stress, and engagement. Features extracted from eye-tracking, such as pupil size and blink rate, are known to correlate with mental effort and fatigue [2]. When combined with head pose data showing signs of restlessness and audio data revealing a faster speech rate, the system can generate a more accurate assessment of the candidate's state. This is not just about detecting cheating but also about improving the quality of the assessment itself. For example, a candidate who appears stressed might give suboptimal answers regardless of their qualifications. Flagging this stress state could allow human reviewers to interpret the candidate's performance in a more nuanced context. However, this advanced analysis also introduces significant complexity and potential for error. The literature review on eye tracking highlighted major inconsistencies in how researchers handle data gaps caused by blinks, noting that poor data handling practices can lead to the loss of over 50% of usable data [8]. This underscores a critical engineering challenge: ensuring the integrity of the raw data streams before they are fed into the machine learning models. Without a robust pre-processing pipeline that correctly handles artifacts and fills gaps using appropriate methods like linear or cubic spline interpolation, the sophisticated analyses performed by the ML classifiers will be based on flawed inputs, leading to unreliable and potentially biased outcomes [8]. Thus, the strength of any advanced behavioral biometric system rests on two pillars: the quality and diversity of the fused data streams, and the rigor of the data preprocessing and validation pipelines that support them.

Systemic Challenges, Limitations, and Future Trajectories

Despite the impressive sophistication of modern AI proctoring systems, they are not without significant systemic challenges, limitations, and ethical considerations. A thorough evaluation requires acknowledging the boundaries of current technology and the potential consequences of its deployment. The most prominent gap in the public domain is the lack of transparency from commercial vendors. Companies like HireVue, Pymetrics, and others treat their specific algorithms, decision thresholds, and weighting schemes for scoring interviews as proprietary trade secrets [1]. While we can infer the general types of technologies used based on academic research and system descriptions, the exact mechanics of how a candidate receives a final score remain unknown [1]. This opacity makes it impossible for independent researchers, auditors, or even the candidates themselves to fully understand or challenge the basis of an assessment. This black-box nature of the algorithms raises profound questions about fairness, accountability, and the potential for embedded biases.

Furthermore, there is a notable disconnect between the performance of these systems in controlled laboratory settings versus their real-world efficacy. Many of the cited studies report exceptionally high accuracy rates, such as 99% or more for liveness detection or activity recognition [3] [5]. These figures are typically achieved under ideal conditions with standardized equipment and carefully selected test subjects. The performance of these systems in the wild, amidst diverse candidate demographics, varied home office environments, different lighting conditions, and a wide array of potential evasion techniques, is far less documented and likely to be lower. The risk of false positives is a critical concern that is not adequately addressed in the provided sources. An algorithm trained to detect stress or nervousness might unfairly penalize candidates from cultures where direct eye contact is considered disrespectful, or those with medical conditions that cause frequent blinking or tremors [8]. Similarly, a model trained predominantly on data from one demographic group may perform poorly or exhibit bias when applied to another. The literature review on eye tracking, for instance, pointed out significant shortcomings in how studies report their data handling procedures, which can introduce bias and reduce reproducibility [8]. Without rigorous, independent auditing for fairness and bias, these systems risk automating and amplifying existing societal inequalities.

Looking forward, the trajectory of AI proctoring technology points toward greater integration of physiological signals and the adoption of immersive environments. One emerging frontier mentioned in the research is the integration of Extended Reality (XR)

technologies, including Virtual Reality (VR) and Augmented Reality (AR) [3]. Conducting interviews within a VR or AR space could provide novel ways to measure concentration, awareness, and emotional responses in a controlled yet interactive setting [3]. Such environments could offer richer data streams than a flat webcam feed, but they currently face substantial hurdles related to hardware accessibility, user comfort, and significant privacy concerns [3]. Another potential direction is the deeper integration of physiological data from wearable devices. As smartwatches and other wearables become more common, future systems might incorporate data on heart rate variability, skin temperature, or galvanic skin response to add another layer of physiological state analysis [2]. This could enhance the ability to assess authenticity and cognitive load, but it also dramatically increases the volume and sensitivity of personal data being collected, raising serious ethical and regulatory questions.

In synthesis, the technological battle over integrity in AI-powered interviews is a dynamic arms race characterized by a cycle of innovation and evasion. The current state-of-the-art relies on a multi-modal approach, fusing data from eye trackers, cameras, and other sensors to build a comprehensive behavioral profile of the candidate. Foundational security is provided by liveness detection mechanisms, such as pupillary response analysis, designed to prevent impersonation. However, no single technology is infallible; each comes with its own set of vulnerabilities, from the difficulty of detecting photo attacks on small screens to the inability of gaze tracking to prevent video replay [5]. The true strength of modern systems lies in their resilience, achieved through the synergistic combination of multiple, overlapping layers of security. The path forward will undoubtedly involve continued advancements in machine learning, the exploration of new data modalities like physiological signals and XR, and an increasing focus on addressing the critical issues of bias, fairness, and transparency. For stakeholders—from system developers and hiring managers to the candidates themselves—the central takeaway is that while deliberate cheating is becoming increasingly difficult, the systems are not perfect. Their ultimate value will depend not only on their technical prowess but also on the responsible frameworks of oversight and accountability that govern their use.

Reference

1. How HireVue scores video interviews: transcript matters more than ... https://www.linkedin.com/videos/wfhmuva_most-people-think-hirevue-is-judging-their-activity-7372065607636238336-3Cjg
2. Eye-Tracking Feature Extraction for Biometric Machine Learning https://www.frontiersin.org/journals/neurorobotics/articles/10.3389/fnbot.2021.796895/full
3. A comprehensive review of the changing landscape of academic ... https://link.springer.com/article/10.1007/s44217-026-01275-6
4. Anti-spoofing in face recognition with liveness detection using pupil ... https://www.researchgate.net/publication/313441872_Anti-spoofing_in_face_recognition_with_liveness_detection_using_pupil_tracking
5. Directed Gaze Trajectories for Biometric Presentation Attack Detection https://pmc.ncbi.nlm.nih.gov/articles/PMC7922021/
6. biometric liveness detection: a comparative study of five approaches https://www.researchgate.net/publication/390494758_BIOMETRIC_LIVENESS_DETECTION_A_COMPARATIVE_STUDY_OF_FIVE_APPROACHES
7. Personality Traits Estimation Based on Job Interview Video Analysis https://www.mdpi.com/2504-2289/8/12/173
8. Uncovering and Addressing Blink-Related Challenges in Using Eye ... https://dl.acm.org/doi/fullHtml/10.1145/3613904.3642086