

This repository was archived by the owner on May 28, 2026. It is now read-only.

Files

dp-int-service-fundamental / mule-rtf / src / exchange-rate-otc-api / src / main / mule / config.xml

ACNRSR_capgroup updated backend URL and added okta authentication method ✓

ed2a450 · 3 months ago  History

Q Go to file **T**

Code	Blame
57	Lines (53 loc) - 4.94 KB

```

1 <?xml version="1.0" encoding="UTF-8"?>
2
3 <male xmlns:os="http://www.mulesoft.org/schema/mule/os"
4   xmlns:oauth="http://www.mulesoft.org/schema/mule/oauth"
5   xmlns:tls="http://www.mulesoft.org/schema/mule/tls"
6   xmlns:apikit="http://www.mulesoft.org/schema/mule/apikit"
7   xmlns:file="http://www.mulesoft.org/schema/mule/file"
8   xmlns:cyberark="http://www.mulesoft.org/schema/mule/cyberark"
9   xmlns:secure-properties="http://www.mulesoft.org/schema/mule/secure-properties"
10  xmlns:http="http://www.mulesoft.org/schema/mule/http"
11  http://www.mulesoft.org/schema/mule/tls http://www.mulesoft.org/schema/mule/core"
12  http://www.mulesoft.org/schema/mule/apikit http://www.mulesoft.org/schema/mule/apikit/current/mule-apikit.xsd
13  http://www.mulesoft.org/schema/mule/file http://www.mulesoft.org/schema/mule/file/current/mule-file.xsd
14  http://www.mulesoft.org/schema/mule/db http://www.mulesoft.org/schema/mule/db/current/mule-db.xsd
15  http://www.mulesoft.org/schema/mule/http http://www.mulesoft.org/schema/mule/http/current/mule-http.xsd
16  http://www.mulesoft.org/schema/mule/secure-properties http://www.mulesoft.org/schema/mule/secure-properties/current/mule-secure-properties.xsd
17  http://www.mulesoft.org/schema/mule/cyberark http://www.mulesoft.org/schema/mule/cyberark/current/mule-cyberark.xsd
18  http://www.mulesoft.org/schema/mule/apikit http://www.mulesoft.org/schema/mule/apikit/current/mule-apikit.xsd
19  http://www.mulesoft.org/schema/mule/oauth http://www.mulesoft.org/schema/mule/oauth/current/mule-oauth.xsd
20  http://www.mulesoft.org/schema/mule/os http://www.mulesoft.org/schema/mule/os/current/mule-os.xsd"
21
22 <apikit:config xmlns:apikit="http://www.mulesoft.org/schema/mule/apikit" name="Is-exchange-rate-otc-sys-api-config" outboundHeaders="outboundheaders"
23 <import doc:name="Import" file="Is-api-uttl.xml" doc:description="Is-api-uttl.xml"/>
24 <import doc:name="Import" file="Is-errors-sys.xml" doc:description="Is-errors-sys.xml"/>

```

Files

- develop
- Go to file
- exchange-rate-...
- log4j2.xml
- test/resources
- githubignore
- mule-artifactson
- pom.xml
- exchange-rate-otc-api
- src
- main
- mule
- config.xml
- is-exchange-rat...
- resources
- test/resources
- githubignore
- mule-artifactson
- pom.xml
- financial-market-api
- geography-api
- industry-classificatio...
- inflation-index-rate-...
- test

dpe-int-service-fundamental / mule-rtf / src / exchange-rate-otc-api / src / main / mule / config.xml

Code Blame 57 lines (53 loc) · 4.94 KB

```
23 <!import doc:name="Import" file="Is-api-util.xml" doc:description="Is-api-util.xml"/>
24 <!import doc:name="Import" file="Is-error-sys.xml" doc:description="Is-error-sys.xml"/>
25
26 <secure-properties:config name="Secure Properties Config" doc:id="7d6558d1-25b5-4120-8137-5c7615b0774e" file="exchange-rate-otc-api-${mule.env}.properties" key="${(
27 <secure-properties:config name="Secure Properties App" doc:name="Secure Properties Config" doc:id="0e2a4b42-e252-45eb-9907-902a5b83706e" file="stacking/app${app.env}.properties" key="${mule.aas.key}"
28 <api-gateway:autoDiscovery apiId="${secure::api.id}" doc:name="API AutoDiscovery" doc:id="39161b80-b392-44b3-8766-02cebe7b79ae" fileName="Is-exchange-rate-otc-sys-api-main" />
29 <http:request-config name="HTTP Request Configuration"
30 doc:name="HTTP Request Configuration" doc:id="a589836b-5096-4b27-89d3-6facb2d55356" responseTimeout="120000">
31 <http:request-connection protocol="HTTPS"
32 host="${secure::http.request.host}" connectionTimeout="120000" port="${secure::http.request.port}">
33 <tls:context >
34 <tls:trust-store path="certs/client-truststore.jks" type="jks"/>
35 <tls:context >
36 <http:authentication >
37 <oauth:client-credentials grant-type="client_credentials" clientId="${secure::okta.client.id}" clientSecret="${secure::okta.client.secret}" scopes="${secure::okta.scopes}" tokenUrl="${secure::okta.token.url}">
38 <oauth:token-manager objectStore="Object_store" />
39 </oauth:client-credentials-grant-type>
40 </http:authentication>
41 </http:request-connection>
42 </http:request-config>
43 <http:request-config name="HTTP Request Configuration OTC" doc:name="HTTP Request Configuration" doc:id="12031651-b54a-4694-bc03-968242c820c1">
44 <http:request-connection host="${secure::http.request.otc.host}" port="${secure::http.request.otc.port}">
45 <reconnection />
46 </http:request-connection>
47 </http:request-config>
48
49 <http:listener-config name="HTTP Listener Config"
50 doc:name="HTTP Listener Config" doc:id="694c9291-56b1-49b4-b7fd-9751897306ff">
51 <http:listener-connection host="${secure::http.listener.host}"
52 port="${secure::http.listener.port}">
53 </http:listener-connection>
54 </http:listener-config>
55 <os:object-store name="Object_store" doc:id="2531f674-3b02-4f76-ac86-5ac4bb86979e" entryTtl="${secure::okta.ttl}" expirationInterval="${secure::okta.ttl}" expirationIntervalUn
56 <os:config name="ObjectStore Config" doc:name="ObjectStore Config" doc:id="1507ba32-3955-49ac-b136-e0c6cfbb42d7" />
57 </mule>
```

Files

develop

Go to file

log4j2.xml

test/resources

.gitignore

mule-artifact.json

pom.xml

exchange-rate-otc-api

src

main

mule

config.xml

ls-exchange-rat...

resources

test/resources

.gitignore

mule-artifact.json

pom.xml

financial-market-api

geography-api

industry-classificatio...

inflation-index-rate...

test

crsccrison

dpe-int-service-fundamental / mule-rtf / src / exchange-rate-otc-api / src / main / mule / ls-exchange-rate-otc-sys-api.xml

Nitin Gupta and Nitin Gupta Updated client_id and client_secret mapping to point to property vari...

Code Blame 484 Lines (477 loc) · 27.9 KB

```
1 <?xml version="1.0" encoding="UTF-8"?>
2 <mule xmlns:file="http://www.mulesoft.org/schema/mule/file" xmlns:http="http://www.mulesoft.org/schema/mule/http" xmlns:impl:otc="http://www.mulesoft.org/schema/mule-otc-impl" xmlns:cyberark="http://www.mule
3 http://www.mulesoft.org/schema/mule/file http://www.mulesoft.org/schema/mule/file/current/mule-file.xsd">
4
5   <flow name="ls-exchange-rate-otc-sys-api-main">
6     <http:listener xmlns:http="http://www.mulesoft.org/schema/mule/http" config-ref="HTTP_Listener_config" path="/${secure:https_path}/">
7       <http:response statusCode="200" httpStatus="default 200"/>
8       <http:response statusCode="200" httpStatus="default 200"/>
9       <http:response statusCode="200" httpStatus="default 200">
10        <http:body><![CDATA[{{payload}}]]></http:body>
11      </http:response>
12    </http:listener>
13    <flow-ref doc:name="create-variables-subflow" doc:id="ea0251b-f7ab-47c3-b760-2a8a9208eb0" name="create-variables-subflow"/>
14    <transform doc:name="requestParam" doc:id="33a1725d-3e9b-46c2-a01f-430b519f96ad">
15      <ee:message>
16        </ee:message>
17      </ee:transform>
18      <ee:set-variable variableName="requestParam" value="[[{{payload}}]]"/>
19    </flow>
20  </flow>
21
22  <fromCurrencyIdentifier>
23    <if attributes.queryParams.fromCurrencyIdentifier != null>
24      <attributes.queryParams.fromCurrencyIdentifier as Number else null,
25      toCurrencyIdentifier>
26      <if (attributes.queryParams.toCurrencyIdentifier != null)>
27        <attributes.queryParams.toCurrencyIdentifier as Number else null,
28        fromIsoAlphaThreeCurrencyCode>
29        <if (attributes.queryParams.fromIsoAlphaThreeCurrencyCode != null
30        and attributes.queryParams.fromIsoAlphaThreeCurrencyCode != ""
31        )attributes.queryParams.fromIsoAlphaThreeCurrencyCode else null,
32        toIsoAlphaThreeCurrencyCode>
33        <if (attributes.queryParams.toIsoAlphaThreeCurrencyCode != null
34        and attributes.queryParams.toIsoAlphaThreeCurrencyCode != ""
```


Files

develop

Go to file

- log4j2.xml
- test/resources
- gitignore
- mule-artifactson
- pom.xml
- exchange-rate-otc-api
- src
- main
- mule
- config.xml
- is-exchange-rt...
- resources
- test/resources
- gitignore
- mule-artifactson
- pom.xml
- financial-market-api
- geography-api
- industry-classificatio...
- inflation-index-rate...
- test
- cssec.json

dpe-int-service-fundamental / mule-rt / src / exchange-rate-otc-api / src / main / mule / rt-exchange-rate-otc-sys-api.xml

Code Blame 494 Lines (477 loc) · 27.9 KB

```
70 code: 400,  
71 message: "Invalid Request: Missing a 'to/from' currency or requested with invalid currency input",  
72 createdAt: now()  
73 }  
74 }  
75 }  
76 }></set:payload>  
77  
78 </set:message>  
79 </set:variable>  
80 </set:variable>  
81 </set:transform>  
82  
83 </when>  
84 <otherwise>  
85 <logger level="INFO" doc:name="Logger" doc:id="7d8c08e-9314-4463-98a2-786735b717c" message="&{#0000}" ++ vars.<correlation_id> ++ " : " ++ "Get:\exchangeRates:is-exchange-rate-otc-sys-api" </logger>  
86 <http:router xmlns:apikit="http://www.mulesoft.org/schema/mule/apikit" config-ref="is-exchange-rate-otc-sys-api-config" />  
87  
88 </otherwise>  
89 </choice>  
90  
91 </flow>  
92 <flow name="get:\exchangeRates:is-exchange-rate-otc-sys-api-config">  
93 <choice doc:name="Choice" doc:id="3bf64349-ba55-46f1-869d-717fcdb70d5">  
94 <when expression="&{sizeOf(attributes.queryParams)} == 0 or (sizeOf(attributes.queryParams)==1 and attributes.queryParams.referenceDataProviderCode == 'OT')">  
95 <flow-ref doc:name="get-full-exchange-response-from-oneTick" doc:id="0b75b08c-4b38-43f3-a345-90db64d0c10b" name="get-full-exchange-response-from-oneTick"/>  
96 </when>  
97 <otherwise>  
98 <flow-ref doc:name="is-exchange-rate-otc-single-currency-subflow" doc:id="1bce6eb2-f590-4c21-8b43-d34fb21f014" name="is-exchange-rate-otc-single-currency-subflow"/>  
99 </otherwise>  
100 </choice>  
101  
102 </sub-flow>  
103 <sub-flow name="is-exchange-rate-otc-single-currency-subflow" doc:id="531b946d-3cde-48d7-87b4-e2de6c54826d">  
104 <flow-ref doc:name="get-to-and-from-Currency-Set" doc:id="105824ac-9d0b-44d6-9ed6-8c1971a8934" name="get-to-and-from-Currency-Set">  
105 <choice doc:name="Check for Empty Currency Response" doc:id="1d14940f-0596-4b00-94cf-02119e970594">  
106 <when expression="&{vars.fromCurrencyResponse == null or vars.toCurrencyResponse == null}">  
107 <logger level="INFO" doc:name="Info Log - Currency Response" doc:id="c06f1da8-0b5b-497b-bc94-e9ab3476d443" message="&{#0000}" ++ vars.<correlation_id> ++ " : SINGLE:" ++ "Received Empty Res"
```

Files

develop

Go to file

- log4j2.xml
- test/resources
- gitignore
- mule-artifact.json
- pom.xml
- exchange-rate-otc-api
 - src
 - main
 - mule
 - config.xml
 - is-exchange-rat...
 - resources
 - test/resources
 - gitignore
 - mule-artifact.json
 - pom.xml
 - financial-market-api
 - geography-api
 - industry-classificatio...
 - inflation-index-rate...
 - test
 - cgsec.json

dpe-int-service-fundamental / mule-rt / src / exchange-rate-otc-api / src / main / mule / le-exchange-rate-otc-gyr-api.xml

Code Blame 484 lines (477 loc) · 27.9 KB

```
106 </when>
107 </otherwise>
108 <<:transform doc:name="Create RTU_CURRENCY Var" doc:id="e3b03566-4f9f-489e-93c0-92a6da5f2060">
109 <<:message>
110 </<:message>
111 <<:variables>
112 <<:set-variable variableName="RTU_CURRENCY">{DATA[2]}</<:set-variable>
113 output application/java
114 ...
115 (vars.fromCurrencyResponse.response.currentcies.currency[0].isoAlphaThreeCurrencyCode as String ++
116 vars.toCurrencyResponse.response.currentcies.currency[0].isoAlphaThreeCurrencyCode as String
117 ))><<:set-variable>
118 </<:set-variable>
119 </<:transform>
120 <<:logger level="TRACE" doc:name="Info Log - Status Message" doc:id="789e1e3c-e05e-470b-a234-0c402ab20d4e" message="<<:message> ++ vars.<<:correlation_id ++ "SINGLE:" ++ vars.RTU_CURRENCY ++
121 <<:flow-ref doc:name="get-single-response-from-oneTick-subFlow" doc:id="f3f08055-52af-4b06-ab2a-0c4b6fcc41d7" name="get-single-response-from-oneTick" />
122 <<choice doc:name="Check for empty" doc:id="a7d97c36-123c-4a81-9e4f9-a71a08579119">
123 <<when expression="<<vars.<<singleResponse == null or isEmpty(vars.<<singleResponse.<<OTExchange))">
124 <<logger level="INFO" doc:name="Info Log - Empty OneTick Response" doc:id="4f4072ae-6f7c-41d7-b01b-7092f7a5601d" message="<<message> ++ vars.<<correlation_id ++ "SINGLE:" ++ "Received Empty
125 <<flow-ref doc:name="empty-response-subFlow" doc:id="2374c302-32e8-4da5-97d1-e407d6076cc4" name="empty-response-subFlow" />
126 </<when>
127 <<otherwise>
128 <<:transform doc:name="Map Response" doc:id="971d76e0-d97d-497a-a4fb-00906eae80972">
129 <<:message>
130 <<:set-payLoad>{DATA[2]}</<:set-payLoad>
131 output application/json
132 fun scaleExchange(rate, scalingFactor) = if (isEmpty(scalingFactor)==false and isEmpty(rate)==false and scalingFactor > 1) (rate / scalingFactor) else rate
133 ...
134 {
135 "response": {
136 responseSetDetails: {
137 timeTaken: ((now() as Number (unit: "milliseconds")) - vars.startTime) as String ++ " ms",
138 apiVersion: p("secure::api.version.number"),
139 serviceId: p("secure::api.name"),
140 "CG-CorrelationId": vars.<<correlation_id,
141 responseTime: now()
142 },
143 "exchangeRates": {
```

Files

develop

Go to file

- log4j2.xml
- test/resources
- .gitignore
- mule-artifact.json
- pom.xml
- exchange-rate-otc-api
 - src
 - main
 - mule
 - config.xml
- lb-exchange-rat...
- resources
- test/resources
- .gitignore
- mule-artifact.json
- pom.xml
- financial-market-api
- geography-api
- industry-classificatio...
- inflation-index-rate...
- test
- conscription

dpe-int-service-fundamental / mule-rt / src / exchange-rate-otc-api / src / main / mule / lb-exchange-rate-otc-sys-api.xml

Code Blame 484 Lines (477 loc) · 27.9 KB

```
143         "exchangeRates": {
144             "exchangeRate": [
145
146                 {
147                     "fromCurrencyIdentifier": vars.fromCurrencyResponse.response.currencies.currency[0].currencyUniquIdentifier,
148                     "toCurrencyIdentifier": vars.toCurrencyResponse.response.currencies.currency[0].currencyUniquIdentifier,
149                     "rateSourceCode": "OT",
150                     "priceTypeCode": "FIX",
151                     "daysForwardCount": 0,
152                     "exchangeRateOfRate": vars.otcSingleResponse.OTExchanges[0].EXCH_TIME,
153                     "rate": scaleExchange(vars.otcSingleResponse.OTExchanges[0].RID_PRICE, trim(vars.otcSingleResponse.OTExchanges[0].SCALING)),
154                     "fromAlphaThreeCurrencyCode": vars.otcSingleResponse.OTExchanges[0].FROM_CURRENCY as String,
155                     "toAlphaThreeCurrencyCode": vars.otcSingleResponse.OTExchanges[0].TO_CURRENCY as String,
156                     "fromCurrencyName": vars.fromCurrencyResponse.response.currencies.currency[0].currencyName as String,
157                     "toCurrencyName": vars.toCurrencyResponse.response.currencies.currency[0].currencyName as String,
158                     "multiplyingDivideCode": "N",
159                     "referenceDateProviderCode": "OT",
160                     "auditStatusCode": "U",
161                     "updateByTime": "HSF",
162                     "updateTimestamp": vars.otcSingleResponse.OTExchanges[0].TIMESTAMP
163                 }
164             ]
165         }
166     }
167 }
168
169 </ee:set-payload>
170 </ee:message>
171 </ee:transform>
172
173 <logger level="INFO" doc:name="Info Log - Final Response" doc:id="0e42d4f2-f4e-46d6-9476-2475f30333b5" message="if [00000] ++ vars.correlation_id ++ "SINGLE:" ++ "One Tick Final Respon"
174 </logger>
175
176 </sub-flow>
177 <sub-flow name="get-to-and-from-Currency-Set" doc:id="c0e24e2d-463d-4a66-ab32-44f09b2e9bc8">
178     <ee:transform doc:name="Build to/from Currency" doc:id="6ee7ede-f727-4d08-b65b-2a92f99f689">
179         <ee:message>
180             </ee:message>
181         </ee:message>
182     </ee:transform>
183 </sub-flow>
```

Files

develop

Go to file

- log4j2.xml
- test/resources
 - gltignore
 - mule-artifactson
 - pom.xml
- exchange-rate-otc-api
 - src
 - main
 - mule
 - config.xml
 - lw-exchange-rat...
 - resources
 - test/resources
 - gltignore
 - mule-artifactson
 - pom.xml
 - financial-market-api
 - geography-api
 - industry-classificatio...
 - inflation-index-rate-...
 - test
 - cqsc.json

dpe-int-service-fundamental / mule-rt / src / exchange-rate-otc-api / src / main / mule / lw-exchange-rate-otc-gys-api.xml

Code Blame 484 lines (477 loc) · 27.9 KB

```
179 </ee:message>
180 <ee:variables>
181   <ee:set-variable variableName="currency"><![CDATA[<kw 2.0
182   output application/json
183   fun checked() = if (vars.requestParams.fromCurrencyIdentifier == null
184   and vars.requestParams.toIsoAlphaThreeCurrencyCode != null) 'IsoAlphaThreeCurrencyCode' else
185   if (vars.requestParams.fromCurrencyIdentifier != null
186   and vars.requestParams.toIsoAlphaThreeCurrencyCode == null) 'currencyInquiryIdentifier' else false
187   ---
188   {
189     key: checked() as String,
190     value: if (isEmpty(checked())) null
191     else if (checked() == 'IsoAlphaThreeCurrencyCode') vars.requestParams.toIsoAlphaThreeCurrencyCode as String
192     else vars.requestParams.fromCurrencyIdentifier as Number
193   }
194   </ee:set-variable>
195   <ee:set-variable variableName="fromCurrency"><![CDATA[<kw 2.0
196   output application/json
197   fun checked() = if (vars.requestParams.fromCurrencyIdentifier == null
198   and vars.requestParams.fromIsoAlphaThreeCurrencyCode != null) 'IsoAlphaThreeCurrencyCode' else
199   if (vars.requestParams.fromCurrencyIdentifier != null
200   and vars.requestParams.fromIsoAlphaThreeCurrencyCode == null) 'currencyInquiryIdentifier' else false
201   ---
202   {
203     key: checked() as String,
204     value: if (checked() == 'IsoAlphaThreeCurrencyCode') vars.requestParams.fromIsoAlphaThreeCurrencyCode as String
205     else vars.requestParams.fromCurrencyIdentifier as Number
206   }></ee:set-variable>
207   </ee:variables>
208   </ee:transform>
209   <ee:transform docName="Create Currency Requests" docId="26f12a66-fdc6-4faa-beaf-54c41699360">
210     <ee:message>
211       <ee:messages>
212         <ee:variables>
213           <ee:set-variable variableName="currencyFromRequest"><![CDATA[<kw 2.0
214           output application/json
215           --
216           --"/>>P("secure:http:request:currency:path") ++ "/"currentIdas" ++ vars.fromCurrency.key ++ "-" ++ vars.fromCurrency.value}></ee:set-variable>
```

Files

develop

Go to file

- log4j2.xml
- test/resources
 - githubignore
 - mule-artifact.json
 - pom.xml
- exchange-rate-otc-api
 - src
 - main
 - mule
 - config.xml
 - lb-exchange-rat...
 - resources
 - test/resources
 - githubignore
 - mule-artifact.json
 - pom.xml
 - financial-market-api
 - geography-api
 - industry-classificatio...
 - inflation-index-rate-...
 - test

dpe-int-service-fundamental / mule-rt / src / exchange-rate-otc-api / src / main / mule / lb-exchange-rate-otc-sys-api.xml

Code Blame 484 Lines (477 Loc) · 27.9 KB

```
215 ---
216 "/*" ++ p("secure::http.request.currency.path") ++ "/currency?" ++ vars.fromCurrency.key ++ "-" ++ vars.fromCurrency.value}></set-variable>
217 <ee:set-variable variableName="currencyToRequest">{[DATA]${kw 2.0
218 output application/java
219 ---
220 "/*" ++ p("secure::http.request.currency.path") ++ "/currency?" ++ vars.toCurrency.key ++ "-" ++ vars.toCurrency.value}></set-variable>
221 </ee:variables>
222 </ee:transform>
223 <scatter-gather doc:name="Scatter-gather" doc:id="44143c12-8caa-4061-9d9c-ae5708807c59">
224 <route>
225 <http:request method="GET" doc:name="Request - To Currency" doc:id="186a40ad-228a-4c28-bd78-42a50bed5d37" config-ref="HTTP_Request_configuration" path="{vars.currencyToRequest}">
226 <http:headers><![CDATA[{"output application/java
227 ---
228 {
229 "Cc-CorrelationId" : vars.cccorrelation_id ++ "one",
230 client_id : p("secure::api.clientId"),
231 client_secret : p("secure::api.clientSecret")
232 }}]></http:headers>
233 <http:response-validator>
234 <http:failure-status-code-validator values="300" />
235 </http:response-validator>
236 </http:request>
237 <ee:transform doc:name="To Currency Response" doc:id="a322143f-04c5-4079-8c7b-0ed6eed37a3">
238 <ee:message>
239 </ee:message>
240 <ee:variables>
241 <ee:set-variable variableName="toCurrencyResponse">{[DATA]${kw 2.0
242 output application/java
243 ---
244 if(attributes.statusCode == 200) payload else null}></ee:set-variable>
245 </ee:variables>
246 </ee:transform>
247 </route>
248 </scatter-gather>
249 <http:request method="GET" doc:name="Request - From Currency" doc:id="beaf1d8e-6509-42f9-8e33-3b355d707d0d" config-ref="HTTP_Request_configuration" path="{vars.currencyFromRequest}">
250 <http:headers><![CDATA[{"output application/java
251 ---
252 {
```



```

...
{
  otcParam: encodeURIComponent('{ "query_type": "otq", "otq": "" ++ p("secure::otqfile") ++ "", "username": "" ++ p("secure::idh.account") ++ "", "context": "VFLX", "symbols": ["GDCV:RTR_CURRENCY:"
  ]}) > /ee:set-payload >
  </ee:message>
  <ee:variables> >
  </ee:variables>
  </ee:transform>
  <logger level="INFO" doc:name="Info Log - OneTick Request URI" doc:id="7c781959-61d9-4820-80c7-0a8da7db807b" message="#["@00000" ++ vars.cqcorrelation_id ++ ":SINGLE:" ++ payload.otcParam
  <http:request method="GET" doc:name="Request ExchangeSOTC" doc:id="df7d1e0e-d3a5-42fd-86ae-f1fda9c8b385" config-ref="HTTP_Request_Configuration_OTC" path="#["@00000;secure::http.request
  </http:request>
  <logger level="DEBUG" doc:name="Debug Log - OneTick Single Response" doc:id="42006841-6730-489b-ad80-b1ba5c701b58" message="#["@00000" ++ vars.cqcorrelation_id ++ vars.otcResponse.MESSAGE
  <logger level="INFO" doc:name="Inf Log - Final Single Response" doc:id="84b059ee-df20-47e2-a23a-75a50ff4ab95" message="#["@00000" ++ vars.cqcorrelation_id ++ ":SINGLE:" ++ "One Tick Resp
  <ee:transform doc:name="filter OT Response" doc:id="c2d4fbc9-435d-4802-ba6d-7b27db5f0003" >
  <ee:message> >
  </ee:message>
  <ee:variables> >
  <ee:set-variable variableName="otcSingleResponse" >{["DATA"]<xml 2.0
output application/json

```

```
++idh.account") ++ "","context":"VFLX","symbols":["GOCY::RTR_CURRENCY::" ++ vars.RTR_CURRENCY ++ ""],"readable_time":"true","response":"json","result_as_a_single_json":"true")

message="#["00000" ++ vars.cgc_correlation_id ++ ":",SINGLE:" ++ payload.otcParam ++ " @" ++ now() as Number {unit: "milliseconds"} ++ "\n"]>
g-ref="HTTP_Request_configuration_OTC" path="#["&quot;secure::http.request.otc.path&quot;]] ++ "params-" ++ payload.otcParam]" target="otc_response">
b58" message="#["00000" ++ vars.cgc_correlation_id ++ vars.otc_response.MESSAGES[0]]" />
message="#["00000" ++ vars.cgc_correlation_id ++ ":",SINGLE:" ++ "One Tick Response before filter @" ++ now() as Number {unit: "milliseconds"} ++ "\n"]>
```

dpes-int-service-fundamental/mule

https://github.com/cq-edo/dpes-int-service-fundamental/blob/develop/mule-rt/src/exchange-rate-otc-api/src/main/mule/le-exchange-rate-otc-api.xml

Files

develop

Go to file

log4j2.xml

test/resources

.gitignore

mule-artifact.json

pom.xml

exchange-rate-otc-api

src

main

mule

config.xml

le-exchange-rat...

resources

test/resources

.gitignore

mule-artifact.json

pom.xml

financial-market-api

geography-api

industry-classificatio...

inflation-index-rate...

test

config.json

dpes-int-service-fundamental / mule-rt / src / exchange-rate-otc-api / src / main / mule / le-exchange-rate-otc-api.xml

Code Blame 484 lines (477 loc) · 27.9 KB

```
293 <<:variables>
294 <<:set-variable variableName="otcSingleResponse"><![CDATA[<div>2.0
295 output application/json
296 ---
297 {
298   "OTCchanges" : vars.otcResponse.MESSAGES.filter {$,msg_type matches "PROCESS_EVENT"} map {item, index} ->
299   ((item) mapObject {value, key} ->
300     {
301       ("FROM_CURRENCY" : (value[0][0 to 2])) if ((key) matches "DIRECTION"),
302       ("TO_CURRENCY" : (value[0][3 to 5])) if ((key) matches "DIRECTION"),
303       ("TIMESTAMP" : value[0] as Number as DateTime {unit: "milliseconds"} as String {format: "yyyy-MM-dd HH:mm:ss.SSS"})
304       if (((key) matches "TS_RUN") and (value != null)),
305       ("BID_PRICE" : (try(value[0]) as Number)) if (((key) matches "BID_PRICE") and (value != null) and ((value[0]) != "nan")),
306       ("SCALING" : (try(value[0]) as Number)) if (((key) matches "SCALING") and (value != null) and ((value[0]) != "nan")),
307       ("EXPIRE_TIME" : value[0] as Number as DateTime {unit: "milliseconds"} as String {format: "yyyy-MM-dd HH:mm:ss.SSS"}) if ((key) matches "EXPIRE_TIME"),
308     }
309   )
310 }]]</set-variable>
311 </ee:variables>
312 </ee:transform>
313 <logger level="INFO" doc:name="Info Log - Filtered OT Response" doc:id="06b0ef3c-5c20-44be-a374-e1c016c7b0b" message="<div>{{vars.otcSingleResponse}}</div> ++ vars.correlation_id ++ "SINGLE:" ++ "One Tick Response Filter
314 </sub-flow>
315 <sub-flow name="get-full-exchange-response-from-oneTick" doc:id="e13ca882-357c-4321-b0c1-d362a40767ed" >
316 <ee:transform doc:name="Build OTC QueryParam" doc:id="7e698c20-b03f-4b05-99c3-b55712247112">
317 <ee:message>
318 <ee:variables>
319 <<:variables>
320 <<:set-variable variableName="otcOryLoad"><![CDATA[<div>2.0
321 output application/json
322 ---
323 {
324   "query_type": "otq",
325   "otq": p("secure::otqFile"),
326   "username": p("secure::idh.account"),
327   "context": "VFLER",
328   "readable_time": "true",
329   "response": "json",
330 }
```

Files

develop

Q Go to file

log4j2.xml

test/resource

.gitignore

 mule-artifact.json

 pom.xml

 **exchange-rate-otc-api**

src

> main

< make

 config.xml

is-exchange-rat...

resources

test/resources



mule-artifact.json

pom.xml

financial-market-avi

geography-ani

industria-classificatio

inflation-judgment rate

10

10

```
dpe-int-service-fundamental / mule-rtf / src / exchange-rate-otc-api / src / main / mule / is-exchange-rate-otc-sys-api.xml
```

Code **Blame** 484 lines (477 loc) • 27.9 KB

```

324 "query_type":"req",
325 "req":{"securecookie":{
326   "username":"securecookie.account",
327   "context":"VIEW",
328   "readable_time":"true",
329   "response":"json",
330   "result_as_a_single_json":"true"
331 }}}</reset-variable>
332 </reset-variables>
333 </transform>
334 <logger level="INFO" docname="Logger Status message" docid="72604831-4ef1-4c93-b131-356c09d4efaf" message="%(00000" ++ vars.cgc_correlation_id ++ ".FULL:" ++ "build of exchangeRate request @" ++
335 <logger level="DEBUG" docname="Debug Log - OneTick Request" docid="c0808aa3-0f72-49ec-a4ab-9eb95c13ab71" message="%(00000" ++ vars.cgc_correlation_id ++ ".FULL:" ++ vars.otc_payload)"/>
336 <http:request method="POST" docname="Request ExchangeOTC" docid="197d7d24-e6cd-4f67-b406-7b3bdc4ec1" config-ref="HTTP_Request_configuration_OTC" path="%(p(quoted;secure:https.request.otc-path
337 <repeatable-file-store-stream bufferUnit="M" />
338 <http:body ><[[DATA[%(vars.otc_payload)]]]></http:body>
339 <http:headers><[[DATA[%(output application/java
340 ---
341 {
342   "Content-Type": "application/json"
343 }]]]></http:headers>
344 </http:request>
345 <logger level="INFO" docname="Info Log - Status message" docid="652f44dd-fa1e-4069-9a30-b7fa68f0e6a4" message="%(00000" ++ vars.cgc_correlation_id ++ ".FULL:" ++ "Received of exchange Rate respo
346 <logger level="DEBUG" docname="Debug Log - OneTick Response" docid="2f9c86b9-3f99-4dab-9dad-3970b37a3389" message="%(vars.otc_payload)"/>
347 <transform docname="Filter of response" docid="aaabca1e-fb8-4490-9818-b0227bf17db">
348 <reset-message>
349 </reset-message>
350 <reset-variables>
351 <reset-variable variableName="OtcResponse" ><[[DATA[Row 2.0
352 output application/json
353 ---
354 {
355   "OTChanges": vars.otc_payload.MESSAGES.Filter ($MSG_Type matches "PROCESS_EVENT") map ($item, index) ->
356     ((item) mapObject (value, key) ->
357       {
358         ("FROM_CURRENCY": (value[0][0 to 2])) if ((key) matches "DIRECTION"),
359         ("TO_CURRENCY": (value[0][3 to 5])) if ((key) matches "DIRECTION"),
360         ("TIMESTAMP": value[0] as Number as DateTime (unit: "milliseconds") as String {format: "yyyy-MM-dd HH:mm:ss.SSS"})
361         if (((key) matches "TS_MIN") and (value != null)).

```


Files

develop

Go to file

- log4j2.xml
- test/resources
- gitingnore
- mule-artifact.json
- pom.xml
- exchange-rate-otc-api
- src
- main
- mule
- config.xml
- is-exchange-ra...
- resources
- test/resources
- gitingnore
- mule-artifact.json
- pom.xml
- financial-market-api
- geography-api
- industry-classificatio...
- inflation-index-rate-...
- test
- consolidation

dpes-int-service-fundamental / mule-rtf / src / exchange-rate-otc-api / src / main / mule / is-exchange-rate-otc-gys-api.xml

Code Blame 484 lines (477 loc) · 27.9 KB

```
384 ---
385 {
386     client_secret : p("secure::api.clientSecret"),
387     client_id : p("secure::api.clientId"),
388     "G-CorrelationId" : vars.gcCorrelation_id ++ 'one'
389 }]]></http:headers>
390 <http:response-validator>
391     <http:failure-status-code-validator values="500" />
392 </http:response-validator>
393 </http:request>
394 <ee:transform doc:name="filter currency response" doc:id="8bf215eb-9c4b-4f2d-b8f4-4257d3dc359" >
395     <ee:message>
396     </ee:message>
397     <ee:variables>
398         <ee:set-variable variableName="filteredCurrencyResponse" xsl="DATA[xmlns 2.0]
399     output application/java
400     ---
401     {
402         "currencies" : vars.currencyResponse.response.currencies.currency map (item, index) ->
403             ((item) mapObject (value, key) ->
404                 {
405                     ("currencyId" : (value)) if ((key) matches "currencyUniqueIdIdentifier"),
406                     ("isoAlphaThreeCurrencyCode" : (value)) if ((key) matches "isoAlphaThreeCurrencyCode"),
407                     ("currencyName" : (value)) if ((key) matches "currencyName")
408                 }
409             )]]></ee:set-variable>
410     </ee:variables>
411     </ee:transform>
412     <logger level="INFO" doc:name="Info Log - Status message" doc:id="c9140582-4c96-45d4-ab86-c1713f7124e4" message="v["000000" ++ vars.gcCorrelation_id ++ "FULL:" ++ "Pulled full currency details @"
413     <ee:transform doc:name="combine OT and currency" doc:id="099d79b6-ac5b-429e-b458-35bd0d4d56d4" >
414         <ee:message>
415             <ee:set-payload xsl="DATA[xmlns 2.0]
416     output application/java
417     fun scaleExchange(rate, scalingFactor) = if (isEmpty(scalingFactor))==false and isEmpty(rate)==false and scalingFactor > 1) (rate / scalingFactor) else rate
418     ---
419     {
420     exchanges:
421     {
```

Files

develop

Go to file

- log4j2.xml
- test/resources
 - .gitignore
 - mule-artifact.json
 - pom.xml
- exchange-rate-otc-api
 - src
 - main
 - mule
 - config.xml
 - resources
 - test/resources
 - .gitignore
 - mule-artifact.json
 - pom.xml
 - financial-market-api
 - geography-api
 - industry-classification
 - inflation-index-rate
 - test
 - cgsec.json

dpe-int-service-fundamental / mule-rtf / src / exchange-rate-otc-api / src / main / mule / ls-exchange-rate-otc-sys-api.xml

Code Blame 484 lines (477 loc) · 27.9 KB

```
415 <ee:set-payload><[CDATA[<sw 2.0
416 output application/java
417 fun scaleExchangeRate, scalingFactor) = if (isEmpty(scalingFactor)==false and isEmpty(rate)==false and scalingFactor > 1) (rate / scalingFactor) else rate
418 ---
419 {
420   exchanges:
421     vars.OTCResponse.OTExchanges map (item, index) -> {
422       FROM_CURRENCY: item.FROM_CURRENCY,
423       TO_CURRENCY: item.TO_CURRENCY,
424       TIMESTAMP: item.TIMESTAMP,
425       BID_PRICE: scaleExchange(item.BID_PRICE, item.SCALING),
426       EXCH_TIME: item.EXCH_TIME,
427       (vars.filteredCurrencyResponse.currencies filter ($ isAlphaThreeCurrencyCode == item.FROM_CURRENCY) map ((fromCurr, indexOfFromCurr) -> {
428         (fromCurr.getIdentityFilter: fromCurr.currencyId as Number),
429         (fromCurr.getName: fromCurr.currencyName as String)
430       })),
431       (vars.filteredCurrencyResponse.currencies filter ($ isAlphaThreeCurrencyCode == item.TO_CURRENCY) map ((toCurr, indexOfToCurr) -> {
432         (toCurr.getIdentityFilter: toCurr.currencyId as Number),
433         (toCurr.getName: toCurr.currencyName as String)
434       })))
435     }
436   }</ee:set-payload>
437 </ee:message>
438 </ee:transform>
439 <logger level="DEBUG" doc:name="Debug Log - Combined OT and Currency Payload" doc:id="485d31ca-70ec-4ff5-b969-802385c431f5" message="<[<00000" ++ vars.cgCorrelation_id ++ "FULL" ++ payload]/>
440 <logger level="INFO" doc:name="Info Log - Status message" doc:id="7af73aee-1623-448d-8d0a-57c3926d9594" message="<[<00000" ++ vars.cgCorrelation_id ++ "FULL" ++ "Combined Onetick and Currency R
441 <ee:transform doc:name="Produce final Response" doc:id="7adca18-6109-4ba7-858f-b057397677e" >
442   <ee:message>
443     <ee:set-payload><[CDATA[<sw 2.0
444     output application/json
445     ---
446     {
447       "response": {
448         responseMetadata: {
449           timestamp: ((now() as Number {unit: "milliseconds"}) - vars.startTime) as String ++ " ms",
450           apiVersion: p("secure:api.version.number"),
451           serviceName: p("secure:api.name"),
452           "cg-CorrelationId": vars.cgCorrelation_id,
```

Files

develop

Q Go to file



log4j2.xml

> test/resources

 .gitignore

 mule-artifact.json

✎ pom.xml

➤ **exchange-rate-otc-api**

main

mule

config.xml

is-exchange-rat...

resources

test/resources

nitimora

mail-artifact icon

1

100



geography

■ **midsize-classical.com**

1

test

dpe-int-service-fundamental / mule-rtf / src / exchange-rate-otc-api / src / main / mule / ls-exchange-rate-otc-sys-apl.xml 

Code	Blame
484 lines (477 loc) • 27.9 KB	



↑ Top

```

450 apVersion: p("secure::api.version.number"),
451 serviceName: p("secure::api.name"),
452 "cg-correlationId": vars.cgcorrelation_id,
453 responseTime: now()
454 },
455 exchangeRates: {
456   exchangeRates: Flatten (payload.exchanges filter ($, BID_PRICE != null and $.fromCurrencyIdentifier != null and $.toCurrencyIdentifier != null) map ((value , indexOfOrder) -> {
457     "fromCurrencyIdentifier": value.fromCurrencyIdentifier,
458     "toCurrencyIdentifier": value.toCurrencyIdentifier,
459     "rateSourceCode": "OT",
460     "priceTypeCode": "RND",
461     "daysForwardCount": 0,
462     "exchangeRateSource": value, "EXCH_TIME",
463     "rate": value, "BID_PRICE",
464     "fromIsoAlphaThreeCurrencyCode": value, "FROM_CURRENCY",
465     "toIsoAlphaThreeCurrencyCode": value, "TO_CURRENCY",
466     "fromCurrencyName": value.fromCurrencyName,
467     "toCurrencyName": value.toCurrencyName,
468     "multiplyingDivideCode": "N",
469     "referenceDateProviderCode": "OT",
470     "auditStatusCode": "U",
471     "updatedAtName": "RSF",
472     "updatedAtTimestamp": value.TIMESTAMP
473   )))
474   }
475 }
476 ]]</ee:set-payload>
477
478 </ee:message>
479
480 <logger level="DEBUG" doc:name="Debug Log - Final Response" doc:id="45dc66d5-b063-4c70-8630-30c3cf07c166" message="!['{{{{{{}}}}}' ++ vars.cgcorrelation_id ++ "FULL:" ++ payload]"/>
481 </flow-ref doc:name="exit-handle-subflow" doc:id="838a2bec-78c4-497a-8bbe-21d58cd627cf" name="exit-handle-subflow"/>
482 </otherwise>
483 </choice>
484 </sub-flow>
485 </rule>

```

dpes-int-service-fundamental/mule-X

+

https://github.com/cg-edo/dpe-int-service-fundamental/blob/develop/mule-rt/src/exchange-rate-otc-api/src/main/resources/api/is-exchange-rate-otc-sys-api.raml

Code

Issues

1

Pull requests

1

Security and quality

Insights

Settings

This repository was archived by the owner on May 28, 2025. It is now read-only.

Files

develop

Go to file

T

src

main

mule

config.xml

is-exchange-rat...

resources

api

dataTypes

examples

exchange.mo...

is-exchange-f...

certs

stacking

application-ty...

exchange-rate-...

exchange-rate-...

exchange-rate-...

exchange-rate-...

exchange-rate-...

Nitin Gupta and Nitin Gupta Refreshed RAML to pull latest is-common-libraries version 1.0.7

Code

Blame

50 lines (46 loc) · 1.68 KB

9th Oct '15 · 5 years ago

file history

```
1 #RAML 1.0
2 title: is-exchange-rate-otc-sys-api
3 version: v1
4
5 uses:
6   Traits: exchange_modules/3d9f05f4-f871-4b62-ad0d-dae2b44361d9/1s-common-libraries/1.0.7/1s-common-libraries.raml
7
8 securitySchemes:
9   client-credentials:
10     type: x-client-credentials
11     description: Use application client_id and secret assigned by API administrator.
12
13 /exchangeRates:
14   get:
15     description: get exchange rates using fromCurrencyIdentifier, toCurrencyIdentifier, rateSourceCode, daysForwardCount, etc.
16     is:
17       - Traits::cg-CorrelationId
18       - Traits::standard-error-response
19       - Traits::client-credentials-required
20     queryParameters:
21       fromCurrencyIdentifier:
22         description: fromCurrencyIdentifier. Use one of fromCurrencyIdentifier or fromCurrencyCode.
23         type: Integer
24         example: 1
25         required: false
26       toCurrencyIdentifier:
27         description: toCurrencyIdentifier. Use one of toCurrencyIdentifier or toCurrencyCode.
28         type: Integer
29         example: 1
30         required: false
```

Q Go to file

is-exchange-rat...

api

dataTypes

example

exchange_mo...

is-exchange-r...

> certs

> **stacking**

 application-type...

 **exchange-rate...**

exchange-rate...

exchange-rate...

exchange-rate-

exchange-rate-

exchange-rate

exchange-

log4j2.xml

```

17 - Traits.cg-CorrelationId
18 - Traits.standard-error-response
19 - Traits.client-credentials-required
20 queryParameters:
21   fromCurrencyIdentifier:
22     description: fromCurrencyIdentifier. Use one of fromCurrencyIdentifier or fromCurrencyCode.
23     type: integer
24     example: 1
25     required: false
26   toCurrencyIdentifier:
27     description: toCurrencyIdentifier. Use one of toCurrencyIdentifier or toCurrencyCode.
28     type: integer
29     example: 1
30     required: false
31   fromIsoAlphaThreeCurrencyCode:
32     description: From Currency ISO Code. Use one of fromCurrencyIdentifier or fromIsoAlphaThreeCurrencyCode
33     type: string
34     example: "USD"
35     required: false
36   toIsoAlphaThreeCurrencyCode:
37     description: To Currency ISO Code. Use one of toCurrencyIdentifier or toIsoAlphaThreeCurrencyCode
38     type: string
39     example: "EUR"
40     required: false
41
42 responses:
43   200:
44     body:
45       application/json:
46         type: !include dataTypes/exchangeRatesOTCResponse.raml
47         application/xml:
48           type: !include dataTypes/exchangeRatesOTCResponse.raml
49
50 204:
51    description: No Content

```

This repository was archived by the owner on May 28, 2026. It is now read-only.

dpe-int-service-fundamental / mule-rtf / src / exchange-rate-otc-api / mule-artifact.json

ACNMO5_sapgroup updated mule-artifact

Code Blame 3 lines (3 loc) · 20 bytes

```
1 {  
2   "muleVersion": "4.0.0"  
3 }
```

edited 10 months ago History

- certs
- stacking
- application-type...
- exchange-rate-...
- exchange-rate-...
- exchange-rate-...
- exchange-rate-...
- exchange-rate-...
- exchange-rate-...
- exchange-rate-...
- log4j2.xml
- mup.csv
- test/resources
- gitignore
- mule-artifact.json
- pom.xml
- financial-market-api

806315 · 2 months ago History



```

1 <?xml version="1.0" encoding="UTF-8" standalone="no"?>
2 <project xmlns="http://maven.apache.org/POM/4.0.0" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 http://maven.apache.org/maven-v4_0_0.xsd">
3   <modelVersion>4.0.0</modelVersion>
4
5   <groupId>469f69f4-f071-4b62-a0d0-dae2b4361d0c</groupId>
6   <artifactId>exchange-rate-otc-api</artifactId>
7   <version>2.1.0</version>
8   <packaging>mule-application</packaging>
9
10  <name>exchange-rate-otc-api</name>
11  <parent>
12    <groupId>243c2b09-65ef-42de-8a22-b75d052659e</groupId>
13    <artifactId>opsmillParent</artifactId>
14    <version>4.0.0</version>
15    <relativePath>
16  </parent>
17  <properties>
18    <runtime.fabric.name>${RTF_GCP_FABRIC_NAME}</runtime.fabric.name>
19    <environment>${RTF_PRIVATE_ENVIRONMENT_ID}</environment>
20    <environment.name>${RTF_ENVIRONMENT_NAME}</environment.name>
21    <deploy.businessGroup>${RTF_PRIVATE_BUSINESS_GROUP_ID}</deploy.businessGroup>
22    <deploy.businessGroup>${RTF_PRIVATE_BUSINESS_GROUP}</deploy.businessGroup>
23    <mule.env.property>${RTF_ENVIRONMENT}</mule.env.property>
24    <mule.aes.key.property>${RTF_ENVIRONMENT_AES_KEY}</mule.aes.key.property>
25    <app.env.property>${RTF_APP_ENV}</app.env.property>
26    <application.name>${project.name}</application.name>
27    <public.url>${RTF_GCP_PROJECT_BASE}</public.url>
28    <deploy.replicationFactor>${RTF_REPLICATION_FACTOR}</deploy.replicationFactor>
29  </properties>
30
31  <build>
32    <plugins>
33      <plugin>
34        <groupId>org.mule.tools.maven</groupId>
35        <artifactId>mule-maven-plugin</artifactId>

```


Files

develop

Go to file

- > certs
- > stacking
 - application-ty...
 - exchange-rate-...
 - exchange-rate-...
 - exchange-rate-...
 - exchange-rate-...
 - exchange-rate-...
 - exchange-rate-...
 - exchange-rate-...
 - exchange-rate-...
 - log4j2.xml
 - map.csv
 - test/resources
 - .gitignore
 - mule-artifact.json
 - pom.xml
 - financial-market-api
 - geography-api
 - industry-classificatio...
 - inflation-index-rate-...
 - test
 - cgseccion

Code Blame 125 lines (120 loc) • 4.13 KB

```
70 <<dependency>
71   <groupId>com.mulesoft.modules</groupId>
72   <artifactId>mule-secure-configuration-property-module</artifactId>
73   <version>1.2.5</version>
74   <classifier>mule-plugin</classifier>
75   <<dependency>
76     <groupId>com.cagroup.sdn</groupId>
77     <artifactId>api-common-utils</artifactId>
78     <version>1.0.13</version>
79   </dependency>
80   <<dependency>
81     <groupId>org.mule.modules</groupId>
82     <artifactId>mule-orch-modules</artifactId>
83     <version>1.1.26</version>
84     <classifier>mule-plugin</classifier>
85   </dependency>
86   <<dependency>
87     <groupId>org.mule.connectors</groupId>
88     <artifactId>mule-objectstore-connector</artifactId>
89     <version>1.2.5</version>
90     <classifier>mule-plugin</classifier>
91   </dependency>
92   <<dependencies>
93     <repository>
94       <id>cgmaven</id>
95       <name>CG Maven</name>
96       <url>https://cgrepo.cagroup.com/repository/cgmvn</url>
97     </repository>
98     <id>anypoint-exchange-v2</id>
99     <name>Anypoint Exchange</name>
100     <url>https://maven.anypoint.mulesoft.com/api/v2/maven</url>
101     <layout>default</layout>
102   </repository>
103   <id>mulesoft-va-lenses</id>
```

Files

develop

Go to file

certs

- stacking
- application-tp...
- exchange-rate...
- exchange-rate...
- exchange-rate...
- exchange-rate...
- exchange-rate...
- exchange-rate...
- exchange-rate...
- log4j2.xml
- mapasv
- test/resources
- gitignore
- mule-artifactson
- pom.xml
- financial-market-api
- geography-api
- industry-classificatio...
- inflation-index-rate...
- test
- cgsecfson

dpe-int-service-fundamental / mule-rtf / src / exchange-rate-otc-api / pom.xml

Code Blame 125 lines (120 loc) · 4.13 KB

```
90 <version>1.2.5</version>
91 <classifier>mule-plugin</classifier>
92 </dependency>
93 </dependencies>
94 <repositories>
95 <repository>
96 <id>cgware</id>
97 <name>CG Maven</name>
98 <url>https://cgrepo.cargroup.com/repository/cgware</url>
99 </repository>
100 <repository>
101 <id>mypoint-exchange-v2</id>
102 <name>MyPoint Exchange</name>
103 <url>https://maven.mylpoint-mulesoft.com/api/v2/maven</url>
104 <layout>default</layout>
105 </repository>
106 <repository>
107 <id>mulesoft-releases</id>
108 <name>Mulesoft Releases Repository</name>
109 <url>https://repository.mulesoft.org/releases</url>
110 <layout>default</layout>
111 </repository>
112 </repositories>
113 <pluginInRepositories>
114 <pluginInRepository>
115 <id>mulesoft-releases</id>
116 <name>mulesoft release repository</name>
117 <layout>default</layout>
118 <url>https://repository.mulesoft.org/releases</url>
119 <snapshots>
120 <enabled>false</enabled>
121 </snapshots>
122 </pluginInRepository>
123 </pluginInRepositories>
124
125 </project>
```