Linux Logging for SOC

Most logs are stored in : /var/log
To filter use : grep

- -v : invert match
- -E : extended regex
- -i : ignore case
- -w : match whole word
- -x : match the whole line exactly
- -F : fixed string
- -o : print only the matched part
- -r : recursive search
- -l : only filenames that have match
- -L : filenames that do not match
- -q : quiet

Each successful logon and logoff is logged, we can filter them with "session opened" or "session closed"

/var/log/kern.log : Kernel messages and errors
/var/log/syslog : A consolidated stream of various Linux events
/var/log/dpkg.log : Package manager log on Debian-Based system
/var/log/dnf.log : Package manager log on RHEL-Based system

App specific logs are in : /var/log/nginx/...

We also can get bash-history from ~/.bash_history

ausearch : formats the output for better readability and support filtering option.

Linux Threat Detection 1

When Breach occured we think and act like a tree:
- for example: follow the ppid and figure out what happened after because of the process id
- and search until the root case of pid == 1

curl https://....com → Fetch a webpage
curl -O https://....com → Download a file
curl -o https://....com → Download and save with a name
curl -I https://....com → Show HTTP response headers only
curl -L https://....com → Follow Redirect
curl https://....com/users → Call an API
curl -X POST https://....com/login \ -H "Content-Type: application/
-d '{"username": "user", "password": "pass"}'
→ Send JSON in a POST request

curl https://....com/script.sh | bash
bash: executes it immediately