Linux Threat Detection 2

'Hack and Forget': attacks run at scale and focus on quick gains

- install Cryptominer
- Enroll to botnet
- Use as Proxe: use the victim to send phishing

wget : Download a file from the website
curl : Make a request to the webpage
ssh : Transfer a file via SCP or SFTP

secure copy — Secure file Transfer Protocol

```
scp user@server:/something/hi.txt /somewhere/hi.txt
```

This is the command, that I have tested myself:

```
scp ~/Desktop/hi.txt user@server:/home/user
```

- After this: `ausearch -i -x`, command should be written like `ausearch -i -x "wget"`

After copiying the malicious file into the system:

```
cd /tmp
rm -rf .X2*          → Delete the older forder
mkdir .X26-unix      → Similar to Linux system
cd .X26-unix
tar xf dota3.tar.gz  → Extracting a suspicious archive into hidden location
sleep 3s             → Envade detection
cd /tmp/.X26-unix/.rsync/c → archive unpacks into a deeper path that looks like tool
```

Internal network scanning / lateral movement discovery

```
nohup somewhere/tsm -p 22 [...] /tmp/up.txt 192.168
                                >> /dev/null 2>1&
sleep 8m

nohup somewhere/tsm -p 22 [...] /tmp/up.txt 172.16>>
                                /dev/null 2>1&
```

- tsm is a custom SSH scanner (~~like~~ worm-like scanner)
- It scans private ranges 192.168.x.x and 172.16.x.x for port 22 (SSH) to find more targets
- Output like "alive hosts" goes to tmp/up.txt

```
cd..; nohup /tmp/.X26-unix/.rsync/initall 2>1 &
```

- initall describes cryptominer (Monero)

/dev/null → black hole, anything I write to it is discarded

& → run the command in the background

>> → append

2>1 → 2 = stderr (error output stream)
1 = stdout (normal output stream)
Send error to wherever output is goin

Linux Threat Detection 3

So the persistence has many methods but there are the common

→ Cron Persistence
- → nohup
- → */10 → reinstalls every 10 minute

→ Systemd Persistense

We can detect by filtering by the path : -f

```
ausearch -i -f /etc/systemd
```

or look by the executions : -x

```
ausearch -i -x /crontab
```