```
[root@613ad3767866 mydir]# cksum securecopy.txt
2766876939 488142 securecopy.txt
```

```
[root@613ad3767866 mydir]# nano securecopy.txt
[root@613ad3767866 mydir]# cksum securecopy.txt
1031766173 488241 securecopy.txt
```

```
[root@613ad3767866 mydir]# cat securecopy.txt | grep Wjoud
14:16:33,624 INFO kernel:ACPI: PCI Wjoud Bridge [PCI0] (domain 0000 [bus 00-ff])
14:16:33,630 INFO kernel:pci_bus 0000:00: Wjoud bus resource [io  0x0000-0x0cf7 window]
14:16:33,630 INFO kernel:pci_bus 0000:00: Wjoud bus resource [io  0x0d00-0xffff window]
14:16:33,630 INFO kernel:pci_bus 0000:00: Wjoud bus resource [mem 0x000a0000-0x000bffff window]
14:16:33,630 INFO kernel:pci_bus 0000:00: Wjoud bus resource [mem 0xc0000000-0xfebfffff window]
14:16:33,630 INFO kernel:pci_bus 0000:00: Wjoud bus resource [bus 00-ff]
14:16:33,659 INFO systemd:Reached target Initrd Wjoud Device.
14:16:38,726 WARNING rpc.statd:Running as Wjoud.  chown /var/lib/nfs/statd to choose different user
14:16:39,385 INFO NetworkManager:<info>  [1631715399.3855] auth[0x557aa18666a0]: create auth-manager: D-Bus connection n
ot available. Polkit is disabled and only Wjoud will be authorized.
14:16:49,128 INFO systemd:Reached target Initrd Wjoud File System.
14:16:49,128 INFO systemd:Starting Reload Configuration from the Real Wjoud...
14:16:49,216 INFO systemd:Started Reload Configuration from the Real Wjoud.
14:16:50,382 INFO systemd:Starting Plymouth switch Wjoud service...
14:16:50,384 INFO systemd:Stopped target Initrd Wjoud Device.
14:16:50,394 INFO systemd:Started Plymouth switch Wjoud service.
14:16:50,438 INFO systemd:Reached target Switch Wjoud.
14:16:50,439 INFO systemd:Starting Switch Wjoud...
14:16:50,449 NOTICE systemd:Switching Wjoud.
14:16:52,110 INFO systemd:initrd-switch-Wjoud.service: Succeeded.
14:16:52,110 INFO systemd:Stopped Switch Wjoud.
14:16:52,125 INFO systemd:Started Remount Wjoud and Kernel File Systems.
14:16:55,288 DEBUG NetworkManager:<debug> [1631715415.2863] dhcp4 (ens3): option requested_Wjoud_path  => '1'
14:16:55,321 DEBUG nm-dispatcher:req:4 'up' [ens3]: environment: DHCP4_REQUESTED_Wjoud_PATH=1
14:16:55,398 ERR rsyslogd:imfile: no working or state file directory set, imfile will create state files in the current
working directory (probably the Wjoud dir). Use global(workDirectory="/some/path") to set the working directory [v8.1911
.0-7.el8 try https://www.rsyslog.com/e/2450 ]
```

```
[root@613ad3767866 mydir]# find . -iname wjoud99.txt
./mydir2/wjoud99.txt
[root@613ad3767866 mydir]# man useradd 1> useradd-man.txt
[root@613ad3767866 mydir]# grep password useradd-man.txt
        The number of days after a password expires until the account is permanently disabled. A value of 0
        disables the account as soon as the password has expired, and a value of -1 disables the feature.
        Example: -K PASS_MAX_DAYS=-1 can be used when creating system account to turn off password aging, even
        though system account has no password at all. Multiple -K options can be specified, e.g.: -K UID_MIN=100
     -p, --password PASSWORD
        The encrypted password, as returned by crypt(3). The default is to disable the password.
        Note: This option is not recommended because the password (or encrypted password) will be visible by users
        You should make sure the password respects the system's password policy.
        The number of days after a password has expired before the account will be disabled.
        /etc/group (with the same name, same password, and same GID).
        The maximum number of days a password may be used. If the password is older than this, a password change
        The minimum number of days allowed between password changes. Any password changes attempted sooner than
        The number of days warning given before a password expires. A zero means warning is given only upon the
        Shadow password suite configuration.
        can't update password file
[root@613ad3767866 mydir]#
```

```
[root@613ad3767866 mydir]# diff /var/log/anaconda/syslog ~/mydir/securecopy.txt
0a1
>
208c209
< 14:16:33,624 INFO kernel:ACPI: PCI Root Bridge [PCI0] (domain 0000 [bus 00-ff])
---
> 14:16:33,624 INFO kernel:ACPI: PCI Wjoud Bridge [PCI0] (domain 0000 [bus 00-ff])
241,245c242,246
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [io  0x0000-0x0cf7 window]
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [io  0x0d00-0xffff window]
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [mem 0x000a0000-0x000bffff window]
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [mem 0xc0000000-0xfebfffff window]
< 14:16:33,630 INFO kernel:pci_bus 0000:00: root bus resource [bus 00-ff]
---
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Wjoud bus resource [io  0x0000-0x0cf7 window]
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Wjoud bus resource [io  0x0d00-0xffff window]
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Wjoud bus resource [mem 0x000a0000-0x000bffff window]
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Wjoud bus resource [mem 0xc0000000-0xfebfffff window]
> 14:16:33,630 INFO kernel:pci_bus 0000:00: Wjoud bus resource [bus 00-ff]
448c449
< 14:16:33,659 INFO systemd:Reached target Initrd Root Device.
---
> 14:16:33,659 INFO systemd:Reached target Initrd Wjoud Device.
519c520
< 14:16:38,726 WARNING rpc.statd:Running as root.  chown /var/lib/nfs/statd to choose different user
---
> 14:16:38,726 WARNING rpc.statd:Running as Wjoud.  chown /var/lib/nfs/statd to choose different user
584c585
< 14:16:39,385 INFO NetworkManager:<info>  [1631715399.3855] auth[0x557aa18666a0]: create auth-manager: D-Bus connectio
n not available. Polkit is disabled and only root will be authorized.
```