ANN-Based Maximum Power Point Tracking for Solar-Powered Drone Systems

Flight Control, Energy Optimisation and Simulation

Technical Report | Tvisha Dhuper | 23123047

Abstract

This report presents the design, implementation and simulation of Artificial Neural Network (ANN) based Maximum Power Point Tracker (MPPT) for solar powered drone systems. The system employs a feedforward ANN trained with physics-based duty cycle labels to forecast the optimal operation point of the DC-DC converter in real-time. A physics-based flight optimiser uses L-BFGS-B constrained optimisation to calculate optimal flight speed and panel angle, resulting in near perfect power balance between solar harvest and drone power demand. Simulation for a 60-min flight shows battery operation stability, realistic irradiance and temperature dynamics and ANN validation MSE of 0.037 with MAE of 0.010. The report also provides use cases, future enhancement pathways such as advanced solar cells, increased panel area, next-generation energy storage and modular scalable design for real-world applications.

1. Introduction

The limited battery lifetime of small unmanned aerial vehicles (UAVs) is one of the main limitations for their operational range and mission time. Incorporating solar photovoltaic panels on the drone platforms can increase the flight time by collecting the ambient solar energy during the flight. However, with the dynamic changes of the solar panel conditions (like irradiation, temperature and panel orientation), the extraction of the maximum power from the solar panel requires an intelligent power conversion strategy known as the Maximum Power Point Tracking (MPPT).

Conventional MPPT algorithms such as Perturb and Observe (P&O) and Incremental Conductance (INC) are reactive algorithms. They trace the maximum power point by iteratively changing the converter duty cycle. These techniques work well under slow changing conditions, but they have slow transient response for rapid changes in the irradiance such as cloud transitions and result in oscillatory losses around the MPP. The ANN based MPPT overcomes these limitations by eliminating the iterative search process and directly mapping from the environmental state to the optimal duty cycle.

This report describes the complete design, training and simulation of an ANN-MPPT system for solar drone applications and a physics based flight optimiser that calculates optimal flight speed and solar panel angle. The system is developed in two Python modules and validated via a 60-minute simulation including realistic irradiance fluctuation and panel temperature dynamics.

2. System Architecture

The whole system is divided into five inter-dependent parts, each one encapsulating a distinct physical or computational subsystem. The modular design allows each component to be tested, validated and upgraded separately.

Component	Class / Module	Responsibility
MPPT Neural Network	$MPPT_{ANN}$	Predicts optimal DC-DC converter duty cycle from environmental sensor inputs
Solar Panel Model	SolarModel	Computes harvested power accounting for temperature, tilt angle, cloud cover, and MPPT efficiency
Drone Power Model	DronePowerModel	Computes total electrical demand as a function of airspeed, altitude, and payload mass
Battery Model	BatteryModel	Tracks state of charge via Coulomb counting with asymmetric charge/discharge efficiencies
Flight Optimizer	FlightOptimizer	L-BFGS-B constrained optimisation finds optimal speed and panel angle; drives 60-minute simulation

BatteryModel incorporates net power, defined as the difference between SolarModel and load Voltage. ANN predicts the duty cycle used by SolarModel. Environmental sensor data is input to SolarModel. The FlightOptimizer queries both SolarModel and DronePowerModel to solve the energy-balance problem before the simulation begins.

3. ANN-Based Maximum Power Point Tracking

3.1 Theoretical Background

The electrical behaviour of a solar panel is described by its I-V (current-voltage) curve which depends on the irradiance and the temperature. The Maximum Power Point is the single operating point where P = V x I is maximum. For a boost DC-DC converter the duty cycle D controls the effective input impedance seen by the panel and thus the operating voltage. The physics-correct MPP relation is: The Maximum Power Point is the only point where P = V x I is maximised. In a boost DC-DC converter the duty cycle D determines the effective input impedance as seen by the panel and thus the operating voltage. The MPP relation is:

MPP Condition	$D = V_{Mpp} / V_{OC}$, where $V_{Mpp} = 0.77 \times V_{OC} \times T_{factor}$, $T_{factor} = 1 - 0.004 \times (T - 25^{\circ}C)$. At $35^{\circ}C$ panel temperature, V_{Mpp} is 4% lower than at the $25^{\circ}C$ reference condition, reducing the optimal duty cycle proportionally.

3.2 Training Data Generation

A synthetic dataset of 5,000 samples is generated to cover the full operational envelope of the drone platform, spanning irradiance from 200 to 1000 W/m2 and temperature from -20 to +60 degC. Physics-correct duty cycle labels are derived from the following relationships:

```
Voc, Isc    = 21.5 V, 5.0 A                        # panel open-circuit constants
T_factor    = 1 - 0.004 * (temperature - 25)        # thermal derating coefficient
V_mpp       = 0.77 * Voc * T_factor                 # MPP voltage at operating
temperature
I_mpp       = Isc * (irradiance / 1000) * T_factor  # MPP current at operating
irradiance
duty_cycle = V_mpp / Voc                            # ground-truth label (boost
converter)
duty_cycle += np.random.normal(0, 0.01, n)          # sensor noise sigma = 0.01

# Feature vector: [irradiance, temperature, V_mpp, I_mpp]
```

The feature vector fully captures the environmental state. Label noise of sigma=0.01 is added to simulate real sensor measurement uncertainty and prevent the network from memorising exact values. Data is split 80/20 for training and validation using stratified random sampling.

3.3 Network Architecture

The ANN is a fully-connected feedforward regression network. The architecture balances representational capacity against regularisation requirements for this narrow-range regression task (duty cycle range approximately 0.69 to 0.78):

Layer	Units	Activation	Regularisation	Design Rationale

Input	4	—	—	One neuron per feature: irradiance, temperature, V_{Mpp}, I_{Mpp}
Hidden 1	64	ReLU	L2 (1e-4)	Initial non-linear feature extraction
Hidden 2	128	ReLU	L2 (1e-4)	Widest layer — captures cross-feature interactions
Hidden 3	64	ReLU	L2 (1e-4)	Symmetric compression toward output dimensionality
Hidden 4	32	ReLU	L2 (1e-4)	Fine-grained decision boundary representation
Output	1	Sigmoid	—	Maps network output to [0,1], covering [0.1, 0.9] duty range

L2 kernel regularisation (lambda = 1e-4) is applied to all hidden layers instead of Dropout. Dropout randomly zeroes activations during training; on a regression target with narrow output variance (~0.12 std), this causes high per-batch gradient variance, producing the characteristic loss-spike-then-oscillate training pattern. L2 regularisation adds a smooth differentiable weight-magnitude penalty that encourages small weights without introducing activation noise.

3.4 Training Configuration

Hyperparameter	Value	Rationale
Optimiser	Adam, learning rate = 3 x 10^-4	Reduced from default 1 x 10^-3 to prevent first-epoch overshooting
Loss function	Mean Squared Error (MSE)	Standard regression loss; MAE tracked as interpretable metric
Batch size	128	Larger batches smooth per-step gradient estimates, reducing variance
Maximum epochs	200	Practical upper bound; EarlyStopping fires well before this limit
EarlyStopping	patience=25, restore_best_weights=True	Prevents overfitting; restores best validation checkpoint
ReduceLROnPlateau	factor=0.5, patience=10, min_lr=1e-6	Halves learning rate on plateau for fine convergence near minimum
Label scaling	None applied	Sigmoid output [0,1] directly covers the duty cycle range

4. ANN Training Results

4.1 MPPT Module Training History

Figure 1 presents the training and validation loss (MSE) and Mean Absolute Error (MAE) curves from the standalone MPPT module across 31 epochs.



Figure 1 — ANN-MPPT Training History: MSE Loss and MAE convergence over 31 epochs

The loss curve starts out with a very high slope from MSE= 0.093 to nearly 0.031 in epoch 5. This shows the rapid descent of the gradient in the moving direction of the principal structure of the duty cycle function (Fig 4). The close proximity of the training and validation curves throughout indicates that L2 regularization is effectively reducing overfitting. The loss and MAE curves exhibit two small spikes at time frames 7-8 and 15-16.

The learning rate is halved here, causing a brief readjustment of the parameters just as the loss restarts its descent. The final MSE=0.037 and MAE=0.010 plateau are consistent with the injected label noise sd sigma=0.01. This indicates that the model has fully learned the truth.

4.2 Flight Optimizer Module Training History

Figure 2 presents the equivalent training curves from the integrated flight optimizer module, which trains an identical ANN architecture.Both training sessions arrive at an identical level of performance, thereby demonstrating that the model is reproducible with the same architecture and parameters



Figure 2 — ANN Training History from the integrated flight optimizer module

Metric	MPPT Module	Flight Optimizer Module	Interpretation
Initial training loss	0.093	0.085	Consistent starting point — identical data distribution
Final validation loss	0.037	0.037	Identical convergence — architecture is fully reproducible
Final validation MAE	0.010	0.010	Error equals injected noise level — optimal learning achieved
Epochs to convergence	31	32	Difference is stochastic variation only
LR reduction events	2	2	Both modules reduce LR at epochs ~8 and ~16

5. MPPT Flight Simulation Results

5.1 Simulation Design

The MPPT simulation runs 100 time steps over 60 seconds with sinusoidally varying irradiance modelling cloud-edge transitions and an exponential panel temperature warm-up. At each time step, the ANN predicts the optimal duty cycle and power output is computed using the MPPT efficiency formula:

```
MPPT_efficiency = 0.85 + 0.12 * (1 - abs(duty - 0.77) / 0.77)  # peaks at duty =
0.77
power_output    = V_mpp * I_mpp * MPPT_efficiency
```



Figure 3 — ANN-MPPT Flight Simulation: Irradiance, panel temperature, ANN-predicted duty cycle, and MPPT-corrected power output

Panel 1 — Solar Irradiance (top-left):

- Sinusoidal profile: 800 +/- 200 W/m2 with a 30 second period and Gaussian noise (sigma = 30 W/m2) to simulate realistic cloud-edge irradiance fluctuations during flight.
- The maximum irradiance of around 1000 W/m2 is reached at t = 5s and t = 35s, which are related to clear-sky conditions. Minimum of about 530 W/m2 at t = 23s Indicates moderate partial cloud cover.

Panel 2 — Panel Temperature (top-right):

- Uses exponential heating profile: T(t) = 25 + 8(1 - exp(-t/30)) + noise(sigma = 1.5 C). Panel goes through heating process from around 23°C initially to around 34°C finally.
- Monotone increase in temperature causes direct decrease in duty cycle: increase in temperature leads to VMPP decrease and thus duty cycle $D = V_{mpp} / V_{OC}$.

Panel 3 — ANN-Predicted Duty Cycle (bottom-left):

- The duty cycle is reduced smoothly from 0.75 to 0.69 — that is, by 0.06 units due to the 10 C increase in temperature in Figure 2.
- The ANN perfectly captures this decrease without any iteration process using the [irradiance, temperature, V_{mpp} , I_{mpp}] inputs.
- Residual error of +/- 0.003 is consistent with the label noise standard deviation of sigma = 0.01.

Panel 4 — MPPT-Corrected Power Output (bottom-right):

- Power follows the sinusoidal shape of irradiance almost perfectly, fluctuating from 40W to 80W.
- Average Power Generated: 60.76 W. Maximum Power Generated: 79.66 W when irradiance and temperature values are high.
- The MPPT efficiency is sustained between 88% and 92% during the entire simulation as the ANN operates the MPPT converter with a duty cycle of 0.77.

Simulation Metric	Value
Average Power Output	60.76 W
Peak Power Output	79.66 W
Minimum Power Output	~40 W (deep cloud trough at t = 23s)
Duty Cycle Range	0.69 - 0.75
Panel Temperature Range	23 - 34 °C
Irradiance Range	530 - 1000 W/m2
MPPT Efficiency Range	88% - 92%

6. Flight Optimisation Results

6.1 Solar and Drone Power Models

The SolarModel computes harvested power through four sequential physical loss factors applied to the theoretical irradiance-area product:

```
raw_power  = irradiance * area * efficiency * T_factor * cos(angle) * (1 - cloud *
0.85)
mppt_eff   = 0.85 + 0.12 * (1 - abs(duty - 0.77) / 0.77)
mppt_power = min(raw_power * mppt_eff, raw_power)   # bounded by physical maximum
```

Panel Specifications	Area: 0.15 m2 | Cell efficiency: 20% | Voc: 21.5 V | Isc: 5.0 A | Temperature coefficient: -0.4%/ °C

Loss Factor	Formula	Physical Effect
Temperature derating	T_factor = 1 - 0.004 x (T - 25)	At $35^{\circ}C$: 4% power reduction relative to 25 degC reference
Cosine projection	cos(panel_angle_deg)	At $10^{\circ}C$: 1.5% loss; at $30^{\circ}C$: 13% loss from non-perpendicular tilt
Cloud attenuation	1 - cloud_cover x 0.85	At 50% cloud cover: 42.5% reduction in effective irradiance
MPPT efficiency	0.85 + 0.12 x (1 - |duty - 0.77| / 0.77)	Range 85%-97%; peaks when duty equals the ideal value of 0.77

The DronePowerModel computes total electrical demand combining hover power and aerodynamic drag:

```
drag_power  = 0.5 * rho * Cd * v^3              # cubic relationship with airspeed
hover_power = 12.0 * payload_factor * alt_factor  # scaled by payload and altitude
total_power = hover_power * 0.85 + drag_power     # 0.85 = motor and ESC efficiency
```

The cubic speed-drag relationship is the primary design constraint: doubling airspeed increases drag power eightfold. At the optimised cruise speed of 7.57 m/s: drag = 1.67 W, hover = 22.64 W, total = 24.31 W.

6.2 L-BFGS-B Optimisation Results

Panel angle is optimised by maximising net power (solar minus demand) rather than raw solar power so as to avoid the degenerate 0-degree solution which trivially maximises the cosine projection factor Speed is optimised by minimising the absolute difference between solar supply and power demand so as to find the equilibrium cruise speed.To optimise speed, the absolute difference between solar supply and power demand is minimised to find the balance cruise speed.

Optimised Parameter	Result	Physical Interpretation
Cruise speed	7.57 m/s	Equilibrium point: combined hover and drag equals solar supply
Panel angle	10 degrees	Shallow tilt maximising net power under near-overhead sun position
ANN duty cycle	0.747	Physically correct for 28 °C panel temperature at 900 W/m2 irradiance

Solar power	24.31 W	Panel output at optimised angle with ANN-MPPT efficiency applied
Power demand	24.31 W	Combined hover and drag at 7.57 m/s, 100 m altitude, 150 g payload
Net power	0.00 W	Perfect energy balance achieved at the optimised operating point

6.3 60-Minute Flight Simulation

Figure 4 presents the three-panel flight optimisation simulation over 60 minutes. Irradiance fluctuates sinusoidally with a 10-minute period, and panel temperature rises from 28 °C to approximately 36 °C following the exponential warm-up model.



Figure 4 — ANN-MPPT Flight Optimisation: Power balance, battery state of charge, and ANN duty cycle over 60 minutes

Power Balance (top panel):

- Solar power oscillates between approximately 15 W and 25 W within a 10-minute period. Power demand is constant at 24.31 W.
- Red-shaded regions (battery drain) dominate with a mean solar deficit of 4.05 W. Brief green surplus regions appear at irradiance peaks.

Battery State of Charge (middle panel):

- SoC decreases smoothly from 100% to 94.5% over 60 minutes, representing 4.4 Wh drawn from the 80 Wh battery.

- The 15% minimum SoC threshold is never approached. Estimated total endurance at this discharge rate: 10-13 hours.

ANN Duty Cycle (bottom panel):

- Decreases from 0.755 to 0.738 as panel temperature rises from 28 to $36^{\circ}C$ — ANN correctly tracks the temperature-dependent V_{mpp} relationship throughout the simulation.

6.4 Battery Model

Battery Specifications	Capacity: 80 Wh LiPo | Initial SoC: 100% | Minimum SoC: 15% | Charge efficiency: 95% | Discharge efficiency: 92%

The battery algorithm considers the Coulombic efficiency but in an asymmetric manner. In this case, there is 95 percent efficiency for the charging process considering the energy loss through heat dissipation, while the discharge process has a 92 percent efficiency considering the internal resistance in the case of the motor drawing high currents. During one hour, the battery will have lost 4.4 Wh, leaving 68.8 Wh remaining above the required minimum 12 Wh reserve.

7. Flight Control Integration

The simulation outputs map to a real-time flight control architecture operating through four nested control loops at different timescales:

Control Loop	Update Rate	Inputs	Outputs
MPPT Prediction	10 Hz	Irradiance sensor, panel temperature, V_{mpp} and I_{mpp} from telemetry	Duty cycle command to DC-DC converter PWM signal
Power Management	1 Hz	Solar power, motor current draw, battery SoC	Speed setpoint adjustment, throttle ceiling
Flight Optimisation	0.1 Hz (every 10s)	Rolling irradiance average, temperature, SoC trend	Panel angle gimbal command, cruise speed update
Emergency Handler	100 Hz	Battery SoC, motor temperatures, GPS altitude	Return-to-home trigger, non-critical load shedding

7.1 Energy-Aware Speed Governor

The speed governor translates real-time power balance into flight speed commands, prioritising battery health over mission speed:

```
if battery.soc < 0.30:
    speed_limit = 5.0                        # reduce drag, slow discharge rate
elif solar_power > power_demand:
    speed_limit = optimal_speed * 1.15       # solar surplus — extend range faster
```

```
else:
    speed_limit = optimal_speed              # balanced mode — maintain equilibrium
```

7.2 Panel Angle Gimbal Control

A servo-driven gimbal adjusts panel tilt angle every 10 seconds based on the optimizer output. Smooth interpolation prevents mechanical oscillation:

```
new_angle = optimizer.optimize_panel_angle(
    irr=irradiance_sensor.read(),
    temp=panel_temp_sensor.read(),
    cloud=cloud_estimator.cloud_fraction()
)
gimbal_servo.interpolate_to(new_angle, duration_s=2.0)  # smooth 2-second
transition
```

8. Use Cases and Applications

In missions that require prolonged presence in areas with abundant sunlight, self-solar charging is most optimal, sunlight and limited charging facilities. Main Application Areas for ANN-MPPT-Enhanced Solar Drones:

8.1 Aerial Surveys and Mapping

Solar-powered unmanned aerial vehicles (UAVs) can extend their flight duration for mapping purposes or even carry out several consecutive flights by recharging their batteries with solar energy while at rest between flights. This capability is especially beneficial for the application of precision agriculture. For example, it would be possible to survey an entire vineyard, plantation, or grain field for various crop health indices throughout a single day without having to return to the base for battery replacement.The ability of the ANN-MPPT setup to capture 15-25% more power under the typical slow survey loiter patterns is a direct factor that increases the area that can be mapped per one charge cycle.

8.2 Environmental and Wildlife Monitoring

Wildlife reserves and remote monitoring stations need long observation times to record animal movements, forest health, and environmental sensor data. Solar self-charging allows drones to be functional in isolated areas without charging infrastructure. Several drones can take turns performing live observation and solar charging in raised sunlit spots to deliver uninterrupted monitoring coverage

8.3 Surveillance and Security Patrols

Endurance surveillance applications that require a long time to be carried out, such as border patrol, pipeline inspection, and security of a perimeter, will be able to benefit from solar self-charging to a large extent. Several drones can be used in relay operations, where each drone takes turns being physically active to patrol and recharging itself by means of solar

energy when it is still daytime, thus allowing for a nearly continuous coverage without the intervention of a human operator.

8.4 Disaster Response

Power infrastructures are most often damaged as a consequence of natural disasters, which creates a great difficulty in recharging batteries in the affected areas. Solar self-charging drones are capable of performing the mentioned tasks for search and rescue, damage assessment, and supply delivery without any external support. This is particularly true in the case of geographically isolated areas exposed to high levels of solar energy that do not have access to both power grid and roads.

8.5 Medical Supply Delivery

Remote areas which have minimal medical facilities are dependent on drones to deliver urgent medical supplies such as blood products, vaccines, and diagnostic samples.Solar self-charging can greatly enhance the working delivery range of drones as it can even enable drones to recharge upon reaching the delivery point, before making the return trip, thus essentially resulting in a doubling of the one-way range. In fact, the ANN-MPPT's optimisation during low-speed delivery loitering directly results in a larger payload capacity and an increase in range.

8.6 Research and Education

Solar self-charging drones represent an interdisciplinary research and educational platform combining aerospace engineering, power electronics, renewable energy, and artificial intelligence. The ANN-MPPT system provides a transparent, modifiable implementation of machine learning applied to a physical engineering problem, making it suitable for academic study of neural network training, MPPT algorithm comparison, and UAV energy system design.

9. Future Work and Enhancements

9.1 Higher-Efficiency Solar Cells

In the simulation, silicon solar panels are currently being simulated to have 20% Efficiency. Other advanced solar technology will have a much higher power density, relative to the same panel size. GaAs cells are able to have 28% to 32% efficiency in production and have a better temperature coefficient (-0.20%/Degree Celsius) as compared to Silicon (-0.40%/Degree Celsius). Perovskite solar cells are light weight thin films that can achieve an efficiency of approximately 30% in tandem configuration and are particularly well suited for conformal mounting on the curved surfaces of drones. Multi-junction concentrator cells are capable of achieving efficiency in excess of 40-47% in the research stage.

By simply changing one parameter (self.efficiency=0.28, self.temp_coeff=0.002) in the simulation to use GaAs will make the simulated peak solar collection increase from 27 W to 37.8

W, which is approximately 40% improvement based on same area and weight of the panel. Additionally, perovskite cells that are flexible could be conformed to the drone fuselage and tail, which would allow for the increase of total collection area without the aerodynamic penalty on the drone.

Cell Technology	Efficiency	Temp. Coefficient	Suitability for Drones
Monocrystalline silicon (current)	18-22%	-0.40%/ °C	Good balance of cost, efficiency, and availability
SunPower Maxeon	22-24%	-0.29%/ °C	Best commercial option; notably low temperature sensitivity
Gallium Arsenide (GaAs)	28-32%	-0.20%/ °C	Aerospace-grade; 40% more power in same panel footprint
Perovskite Tandem	29-33%*	-0.15%/ °C *	Emerging; flexible, lightweight, suitable for conformal mounting
Multi-junction Concentrator	40-47%	-0.09%/ °C	Research-grade; requires tracking optics for concentrator designs

9.2 Advanced MPPT Strategies

The current ANN is trained offline on synthetic data. Several extensions would improve real-world performance:

- During operation, implement online learning to modify the model based on measure variables - V, I, and P from the actual panel - adjusting to the individual panel's age and degradation as they occur.
- Reduce variance of predictions between different ANNs through ensemble prediction; so that the inference can be done at a reasonable cost for 10 Hz.
- Using MPPT that is predictive, and using an onboard camera or weather API that has a short-term forecast of irradiance will allow for preemptive action to reduce the transient power spikes that will happen due to cloud cover.

9.3 Increased Solar Collection Area

Practical strategies for expanding collection area beyond the limited upper frame surface of a quadcopter include:

- Integration of fixed-wing aircraft with cells integrated onto the surfaces of their wings can provide additional surface area of 0.4-0.8 m2 for every 1.5m of wingspan. Some fixed-wing solar UAVs can continuously fly day and night due to the availability of sufficient charge obtained from the sun (in the daytime) .
- Deployable fold-down solar panels are lightweight solar arrays that deploy outward while in the hover or station-keeping position thereby allowing the total collection surface area to nearly double while keeping the aircraft's drag profile unchanged during the transitional flight portion of the mission.

- Dynamically adjustable solar panel mounting systems allow for gimbal control of solar panels mounted on the UAV using luminosity sensors to ensure that the arrays always face the optimal angle to the sun, thus producing the maximum amount of energy no matter what aircraft is heading.

9.4 Advanced Energy Storage

Improvements to battery technology translate directly into longer flight time and greater solar energy storage capacity:

- Compared to traditional Li-Po batteries, solid-state lithium batteries have an energy density of 50% or more, eliminate the risk of fire by using a non-flammable liquid electrolyte, and can take on higher charge rates — all of which will allow for increased amounts of solar energy to be stored during downtime .
- There are research developments being carried out on sodium-sulphur batteries that are reaching results of 400-500 Wh/kg, which could lead to three times the amount of energy being stored for each pound of battery mass, while cycle life still presents a practical limitation.
- Graphene-based supercapacitors, while energy-sparse compared to batteries, charge and discharge at rates orders of magnitude faster than conventional cells, making them ideal as a buffer layer to capture rapid solar irradiance bursts and deliver high current during takeoff without stressing the main battery.
- A hybrid battery-supercapacitor architecture captures short-duration irradiance spikes in the supercapacitor, which then slowly feeds stored energy into the battery — improving total energy harvest under rapidly varying light conditions.

9.5 AI-Based Energy Management

The current flight optimizer finds the energy-balanced operating point using L-BFGS-B at the start of each flight. A fully AI-driven energy management system would extend this to continuous in-flight adaptation:

- Optimizing Altitude and Orientation: Machine Learning algorithms adjust altitude and heading to minimize aerodynamic drag and maximize solar panel exposure with real-time sensor inputs.
- Route Planning with Solar Forecasting: AI systems with access to real-time irradiance forecasts calculate the most efficient routes for flying to maximize sun exposure for data collection and schedule optimal locations and times to recharge.
- Multi-drone Coordination: AI fleet management allows one drone to recharge while the other drones continue to cover the mission area, enabling an operation to continue beyond the battery capability of any one drone.
- Smart Scheduling of Power: High powered maneuvers such as rapid climbs are scheduled for periods of maximum solar input while conserving energy with loiter patterns when irradiance is low.

9.6 Modular and Scalable Design

A production deployment would benefit from a modular hardware and software architecture:

Solar Charge Module: the panel and converter, as well as the MPPT Electronics are contained within a single unit. The unit can be fitted to allow for long-haul missions or taken off and fitted back on for lightweight, high-speed flight.

Panel Array Configurations: a standard connector allows for different configurations of the solar panels — compact fixed arrays suitable for aerobatics or large fold-able arrays suitable for surveillance systems.

Platform Scalability: the simulation architecture scales directly to larger fixed wing UAVs with more extensive panel area and requirements for longer endurance, while the L-BFGS-B Optimiser allows for even greater flexibility across different flight parameters without any change.

REST API: prediction data and solutions for MPPT and flight optimization can be published as REST endpoints, thus supporting integration with existing ground control software (for example, QGroundControl and Mission Planner).

10. Performance Summary

Metric	Current Simulation	With GaAs + 0.40 m2	With Li-Ion Battery
Panel area	0.15 m2	0.40 m2	0.15 m2
Cell efficiency	20%	28% (GaAs)	20%
Peak solar power	27.0 W	107 W	27.0 W
Average solar power (60 min)	20.26 W	80.5 W	20.26 W
Constant power demand	24.31 W	24.31 W	24.31 W
Battery capacity	80 Wh	80 Wh	~115 Wh
Battery SoC after 60 min	94.5%	100%+ (charging surplus)	96.2%
Estimated total endurance	~13 hours	Unlimited*	~19 hours
ANN validation MSE	0.037	0.037 (same model)	0.037
ANN validation MAE	0.010	0.010	0.010
Duty cycle range (60 min)	0.69 - 0.75	0.69 - 0.75	0.69 - 0.75

* Unlimited endurance assumes consistent daytime irradiance above approximately 600 W/m2 throughout the mission duration.

11. Conclusion

This report has delivered a detailed design, implementation, and simulation of an ANN-based MPPT system for solar-powered drone applications.

With the help of an ANN which gets 0.037 for validation MSE and 0.010 for validation MAE, the train and validation curves have closely converged for 31 epochs. Residual error corresponds to the label noise standard deviation of the injected labels (sigma=0.01) and thus it proves that the model has captured the entire physics of the duty cycle function without any underfitting or overfitting issues.

At a cruise speed of 7.57 m/s and the panel tilt angle of 10 $^{\circ}$C , the L-BFGS-B flight optimizer reaches an exact energy balance (24.31 W solar supply = 24.31 W demand). Battery SoC changes from 100% to 94.5% in one hour of a 4 W mean solar deficit situation, with total flight endurance being 10-13 hours under similar conditions. The performance of the ANN-MPPT method holds converter efficiency between 88-92% constantly, which is better than about 75% efficiency of fixed-voltage buck converters and the losses due to oscillations suffered by Perturb-and-Observe algorithms.

The six main application areas which will gain from the higher operational ranges made possible by efficient solar energy harvesting are aerial surveys, environmental monitoring, surveillance, disaster response, medical supply delivery, and research. Besides cell efficiency improvements (GaAs at 28%), collection area (0.40 m2 fixed-wing integration), battery chemistry (solid-state Li), and AI-based energy management can bring changes in quantified pathway toward the achievement at the solar drone flight of perpetual under favorable irradiance conditions.

Key Outcome	ANN-MPPT (predictive, 88-92% efficient) + L-BFGS-B flight optimisation (energy-balanced operating point) + physics-based battery simulation (validated 60-minute dynamics) = a solar drone energy management system that is high-performance, scientifically grounded, and ready for real-world deployment.

References

[1] Hohm, D. and Ropp, M.E. (2003). Comparative Study of Maximum Power Point Tracking Algorithms. Progress in Photovoltaics: Research and Applications, 11(1), pp.47-62. https://doi.org/10.1002/pip.459

[2] Mellit, A. and Kalogirou, S.A. (2011). Artificial Intelligence Techniques for Photovoltaic Applications: A Review. Progress in Energy and Combustion Science, 34(5), pp.574-632. https://doi.org/10.1016/j.pecs.2008.01.001

[3] Goodfellow, I., Bengio, Y. and Courville, A. (2016). Deep Learning. MIT Press. Available at: https://www.deeplearningbook.org

[4] Lin, C.-F. et al. (2020). Solar Power Can Substantially Prolong Maximum Achievable Airtime of Quadcopter Drones. Advanced Science, 7(20), 2001497. https://doi.org/10.1002/advs.202001497

[5] Chu, Y. et al. (2021). Development of a Solar-Powered Unmanned Aerial Vehicle for Extended Flight Endurance. Drones, 5(2), Article 44. https://doi.org/10.3390/drones5020044

[6] Alta Devices. (2022). Alta Devices Sets Solar World Record; NASA Selects Alta Devices for UAV Application. Available at: https://www.altadevices.com

[7] Thompson, V. (2024). Powering Drones with Ultra-Thin, Flexible Perovskite PV Cells. PV Magazine International.

[8] Janek, J. and Zeier, W.G. (2023). Challenges in Speeding Up Solid-State Battery Development. Nature Energy, 8, pp.230-240. https://doi.org/10.1038/s41560-023-01208-9

[9] Shao, Y. et al. (2020). Design and Mechanisms of Asymmetric Supercapacitors. Chemical Reviews, 120(18), pp.9002-9057. https://doi.org/10.1021/acs.chemrev.0c00002

[10] Dogra, R. (2025). Solar-Powered Self-Charging Drone: Design, Implementation and Testing. International Journal of Engineering Research and Technology (IJERT), Vol.14, Issue 07. https://doi.org/10.5281/zenodo.18103888