



CSE452 Computer Graphics

Lecture 10: Illumination

If there is no light...



What is light?

- Electromagnetic radiation that is visible to the human eye
 - Carried by “photons” but also exhibits wave behaviors
- Properties
 - Speed (constant)
 - Direction (straight)
 - Wavelength (“color”)




What is light?

- Electromagnetic radiation that is visible to the human eye
 - Carried by “photons” but also exhibits wave behaviors
- Properties
 - Speed (constant)
 - Direction (straight)
 - Wavelength (“color”)
 - Amplitude (“intensity”)



Where is purple or pink?



Where is purple or pink?




You may not have fully understood.

Important thing is “color is deep.”


How is a surface lit?

- By the (color and intensity of) light that is transmitted from the surface in the direction towards our eye
 - Active: the surface is emitting light (i.e., a light source)
 - Passive: the light originates from somewhere else





Passive Lighting

- When a photon hits a surface it may
 - Get absorbed (turned into heat or other energy)






Passive Lighting

- When a photon hits a surface it may
 - Get absorbed
 - Reflect






Passive Lighting

- When a photon hits a surface it may
 - Get absorbed
 - Reflect
 - Refract





Passive Lighting

- When a photon hits a surface it may
 - Get absorbed
 - Reflect
 - Refract







Passive Lighting

- When a photon hits a surface it may
 - Get absorbed
 - Reflect
 - Refract
 - Scatter



Passive Lighting

- When a photon hits a surface it may
 - Get absorbed
 - Reflect
 - Refract
 - Scatter
- What happens depends on:
 - The color and intensity of light
 - Color and material of surface
 - Reflective? Diffusive? Transparent? Opaque? Translucent?
 - Orientation of surface with respect to the light source and eye




Illumination (in Computer Graphics)

- Given
 - Light sources, object surfaces and the camera
- Compute
 - Color of each pixel on the screen
 - As intensity of photons that come towards the camera in that viewing direction


Computer Representation

- Light sources
 - Directional light (e.g., the sunlight)
 - Emitting photons in one direction
 - Point/Area light (e.g., light bulb)
 - Emitting photons in all directions from a single source
 - Spot light (e.g., a flashlight)
 - Emitting photons from a single source forming a cone
- Light attenuation
 - Intensity falls off with distance




Computer Representation

- Surface
 - A geometric surface can be
 - Discrete: consisting of polygons (e.g., triangles), or
 - Continuous: parametric surface (e.g., the sphere)
 - Each surface element is locally represented by
 - The point location
 - The normal vector of the tangent plane
 - Discrete: polygon normal
 - Continuous: first derivatives




Local Illumination





Local Illumination

- Light interaction with one surface
 - Only considers direct reflection of the light from the source
 - Assuming the path between the light source and the surface is unblocked
- Pros: Fast
- Cons: Missing many effects
 - Shadow
 - Refraction
 - Multi-hop reflection



Global Illumination


- Light interaction with all surfaces
 - Reflection/refraction involving multiple surfaces
 - Considers shadows (when the path between the light source and surface is blocked)
 - Complete (*Umbra*) or incomplete (*Penumbra*)
- Pros: Realistic
- Cons: Expensive



Umbra/Penumbra from Sun



Local vs. Global Illumination



If you want to know more...



Light and Color Song by ParrMr
[<http://www.youtube.com/watch?v=X1hIQvKbQDE>]

Overview


- Local illumination
 - Local lighting model (this lecture)
 - Drawing polygonal models (lecture 11)
- Global illumination
 - Ray tracing (lecture 12,13)
 - Radiosity (lecture 14)

Local Lighting Model


- Factors in computing reflected light:
 - Geometric configuration (between light source, surface and camera)
 - Light properties (source type, color, attenuation)
 - Surface material (color, shininess, etc.)
 - Others (polarization, fluorescence, phosphorescence, etc.)
- Lighting model: the math that computes reflected light
 - Physical model
 - Computes actual energy transmitted, very expensive
 - Non-physical model (OpenGL)
 - “Close enough”, “looks good”, but fast

Local Lighting Model

- Point light source
- Sum of three terms
 - Diffuse light
 - Diffusive reflection
 - Specular light
 - Highlights
 - Ambient light
 - Global, environment light



Local Lighting Model




Diffuse


Specular

Ambient

=



+




+



Parameters

- **Geometry**

- Surface normal (unit vec): $\mathbf{N} = \{N_x, N_y, N_z\}$
- Direction to light source (unit vec) $\mathbf{L} = \{L_x, L_y, L_z\}$
- Distance to light source: d_L
- Direction to camera: $\mathbf{V} = \{V_x, V_y, V_z\}$




Parameters

- **Geometry**

- Surface normal (unit vec): $\mathbf{N} = \{N_x, N_y, N_z\}$
- Direction to light source (unit vec) $\mathbf{L} = \{L_x, L_y, L_z\}$
- Distance to light source: d_L
- Direction to camera: $\mathbf{V} = \{V_x, V_y, V_z\}$

- **Light properties**

- Diffuse/Specular Light $\mathbf{I}_L = \{I_L^r, I_L^g, I_L^b\}$
- Ambient light: $\mathbf{I}_A = \{I_A^r, I_A^g, I_A^b\}$
- Attenuation coefficients: c_0, c_1, c_2



Parameters

- **Geometry**


- Surface normal (unit vec): $\mathbf{N} = \{N_x, N_y, N_z\}$
- Direction to light source (unit vec) $\mathbf{L} = \{L_x, L_y, L_z\}$
- Distance to light source: d_L
- Direction to camera: $\mathbf{V} = \{V_x, V_y, V_z\}$

- **Light properties**

- Diffuse/Specular Light $\mathbf{I}_L = \{I_L^r, I_L^g, I_L^b\}$
- Ambient light: $\mathbf{I}_A = \{I_A^r, I_A^g, I_A^b\}$
- Attenuation coefficients: c_0, c_1, c_2

- **Surface material**

- Diffuse coefficients: $\mathbf{k}_d = \{k_d^r, k_d^g, k_d^b\}$
- Specular coefficients: $\mathbf{k}_s = \{k_s^r, k_s^g, k_s^b\}$ and exponent: n
- Ambient coefficients: $\mathbf{k}_a = \{k_a^r, k_a^g, k_a^b\}$





Diffuse Reflection

- Simulates reflection on matte surfaces
 - Independent of view direction
- Lambert's Cosine Law

$$I_{\text{diff}} = I_L k_d \cos[\theta] = I_L k_d (\mathbf{N} \cdot \mathbf{L})$$

$(\theta < \pi / 2, \text{ or } \mathbf{N} \cdot \mathbf{L} \geq 0)$




Diffuse Reflection

- Simulates reflection on matte surfaces
 - Independent of view direction
- Lambert's Cosine Law

$$I_{\text{diff}} = I_L k_d \cos[\theta] = I_L k_d (\mathbf{N} \cdot \mathbf{L})$$

$(\theta < \pi / 2, \text{ or } \mathbf{N} \cdot \mathbf{L} \geq 0)$




- Compute for each color component :

$$I_{\text{diff}}^r = I_L^r k_d^r (\mathbf{N} \cdot \mathbf{L})$$

$$I_{\text{diff}}^g = I_L^g k_d^g (\mathbf{N} \cdot \mathbf{L})$$

$$I_{\text{diff}}^b = I_L^b k_d^b (\mathbf{N} \cdot \mathbf{L})$$





Specular Reflection

- Simulates highlight on shiny surfaces
 - Dependent on the viewing direction
- Phong's approximation

$$I_{\text{spec}} = I_L k_s \cos[\alpha]^n = I_L k_s (R \cdot V)^n$$

$(N \cdot L \geq 0)$

- R: reflected light direction
- n: specular exponent






Specular Reflection

- Simulates highlight on shiny surfaces
 - Dependent on the viewing direction
- Phong's approximation

$$I_{\text{spec}} = I_L k_s \cos[\alpha]^n = I_L k_s (R \cdot V)^n$$

$(N \cdot L \geq 0)$

- R: reflected light direction
- n: specular exponent





Specular Reflection

- Phong's approximation

$$I_{\text{spec}} = I_L k_s \cos[\alpha]^n = I_L k_s (R \cdot V)^n$$

$(N \cdot L \geq 0)$


- Often, k_s is independent of object



Ambient Reflection

- Simulates global illumination
 - Lights bounced off other objects
- Constant light (a simple hack)

$$I_{\text{amb}} = I_A k_a$$



Light Attenuation

- Simulates decrease of light energy over distance

- $I_L \leftarrow f_{att} I_L$

- Does not affect ambient light

- Inverse square law of energy fall-off

$$f_{att} = \frac{1}{d_L^2}$$

- In practice


$$f_{att} = \frac{1}{c_0 + c_1 d_L + c_2 d_L^2}$$

Putting Together


- Local (OpenGL) lighting model

$$\begin{aligned} I &= I_{\text{amb}} + I_{\text{diff}} + I_{\text{spec}} \\ &= I_A k_a + I_L f_{\text{att}} (k_d (N \cdot L) + k_s (R \cdot V)^n) \end{aligned}$$


- Compute for each color component




Example: Varying Parameter



Example: Varying Parameter




Example: Varying Parameter




Example: Attenuation

No attenuation:



Linear attenuation:



Quadratic attenuation:

