




Online Shopping






3 Tier

5 - 6



Java EE



<html>

<body>

html

==

} Java

html

==

} Java

html


</body>

</html>

JSP

Java Server
Pages

Servlet



Section 1 - Language Syntax

1. Directive `<%@ %>`
 - a. page (10 -12 attributes for eg. import, language, session)
 - b. include (statically including a page into the current page)
 - c. taglib (used to use other pre-defined or user define tag libraries)
2. Declaration `<%! %>` to define functions or variables that are available on the current page.
3. Scriptlet `<% %>` - a block of java code that is inserted in between the presentation, this can be of multiple lines and each statement should terminate with a semi-colon; You can have multiple Scriptlets within a JSP page as long as they are not nested.
4. Expression `<%= %>` - an expression is a single statement that always generates an output, non-void value return, the statement of an expression is passed as a parameter to the out.print method
5. Expression Language `${[objects]}`

Section 2 - Implicit Objects in JSP (by default available in Scriptlet or Expression)

1. request - HttpServletRequest
2. response - HttpServletResponse
3. session - HttpSession
4. config - ServletConfig
5. application - ServletContext
6. out - JspWriter (buffered version of the PrintWriter)
7. page - Object (this)
8. exception - Throwable
9. pageContext - PageContext

Section 3 - JSP Tag Library

1. `<jsp:useBean>` - Allows you to instantiate or obtaining an existing POJO Object
2. `<jsp:setProperty>` - sets the value of a property of a bean/POJO
3. `<jsp:getProperty>` - gets the value of a property of a bean/POJO
4. `<jsp:forward>` - Forwards the request to another url
5. `<jsp:include>` - Dynamically includes the contents of another url
6. `<jsp:plugin>` - flash, applet, excel, chart, pdf