MFC - CAP BOX

Rev J - GLUELESS, STEP 60 mm, LID HINGE AT THE END OF THE STEP

Material: E-flute litho-laminated board, caliper ~1.5 mm
Scale 1:1 - units mm - view from OUTSIDE (print side)
All creases fold away from viewer

Closed box (outside approx.): 218.2 W x 233.6 D x 199 H (same as Rev H)
Clear inside (between liners): 206 W x 226 D x 196 H (Rev C insert fits)
Sheet size: 731.6 x 947.6
Side seam gap: 4.9 mm square to the seam (as Rev H)

CHANGE vs Rev H (orange dashed outline):
10. The side split no longer starts in the back top corner.
Base side wall keeps full height 196 for 60 mm from the back,
then slopes 44.6 deg down to the front (front lip unchanged).
The base now hides the Rev C insert (top front corner ~53 mm
from the back at ~197 mm) when the lid is open.
11. Lid side ends 65.4 mm from the hinge; lid top is cut free
over the step. Lid front, lid ears unchanged.
12. Side liners, lid liners and lid ears re-mirrored about the
new 180 fold lines; liner tabs still land in the same 6 slots.
13. Base front height at the seam 32.6 (was 33.6).
14. Rev J: the top is split by a crease 65.4 mm from the back (where
the lid side starts). The back part is a FIXED TOP over the step;
the lid hinges on that crease, so the lid side turns about its
own tip and stays on the base step when the lid opens.
15. Fixed top has 2 side lock flaps (28 mm) that drop inside the
side walls over the step and hold it without glue.

NOTES - NO GLUE ANYWHERE (as Rev H)
1. Back and front lip fold up from BOTTOM.
2. Side-wall ears fold in; side walls go up, ears sit BEHIND the
front lip. Inner lip folds 180 down over them, tabs into slots.
3. Back ears fold in; side LINER folds 180 over the slope edge,
covers them, 2 tabs push into the bottom slots.
4. Fixed top folds over the step, its 2 lock flaps drop inside the side walls;
the lid hinges on the crease at the front edge of the fixed top.
5. Lid front down, lid sides down, lid liners 180 over the slope
edge; their ears go in BEHIND the lid front.
6. Lid inner front folds 180 up and traps those ears; the tuck
folds 180 down and goes in behind the inner lip.
7. Draft for white sample - printer to confirm crease and slot
allowances for their board before die.
8. E-flute: run flutes parallel to the long side folds.

Rev J - glueless - generated from Rev H geometry

LEGEND

- Cut (incl. 6 lock slots in bottom)
- Crease / fold
- Double crease 2 mm apart (180 folds)
- Bleed +3 mm for artwork
- Changed vs Rev H

SIDE VIEW, CLOSED (scale 1:2) - front at left



