

MASARYKOVA
UNIVERZITA
PŘÍRODOVĚDECKÁ FAKULTA
ÚSTAV BIOCHEMIE

Testování efektu AI Foundational models na analýzu NGS dat DNA sekvenování

Diplomová práce

TOMÁŠ VAMBERSKÝ

Vedoucí práce: Mgr. Vojtěch Bystrý, Ph.D. Brno 2026

Bibliografický záznam

Autorka:	Bc. Tomáš Vamberský Přírodovědecká fakulta, Masarykova univerzita Ústav biochemie
Název práce:	Testování efektu AI Foundational models na analýzu NGS dat DNA sekvenování
Studijní program:	Biochemie
Studijní obor:	Bioinformatika
Vedoucí práce:	Mgr. Vojtěch Bystrý, Ph.D.
Akademický rok:	2025/2026
Počet stran:	?? + ??
Klíčová slova:	AI; Foundation model; Transcription factor

Bibliographic Entry

Author: Bc. Tomáš Vamberský
Faculty of Science, Masaryk University
Department of Biochemistry

Title of Thesis: Testing AI Foundational Models for Impact on NGS DNA Sequencing Data Analysis

Degree Programme: Biochemistry

Field of Study: Bioinformatics

Supervisor: Mgr. Vojtěch Bystrý, Ph.D.

Academic Year: 2025/2026

Number of Pages: ?? + ??

Keywords: AI; Foundation model; Transkripční faktor

Abstrakt

V této bakalářské/diplomové/rigorózní práci se věnujeme ...

Abstract

In this thesis we study ...

Místo tohoto listu vložte kopii oficiálního zadání práce bez podpisů.

Poděkování

Na tomto místě bych chtěl(-a) poděkovat ...

Prohlášení

Prohlašuji, že jsem svouji diplomovou práci vypracoval samostatně pod vedením vedoucího práce s využitím informačních zdrojů, které jsou v práci citovány. Prohlašuji, že jsem pro stylistické úpravy textu využil nástroje AI a to plně v souladu s principy akademické integrity.

Brno 13. Května 2026

.....
Tomáš Vamberský

Table of Contents

List of Figures	x
List of Tables	xi
List of Abbreviations	xii
Introduction	1
Chapter 1. Theoretical background	2
1.1 Transcription factor binding	2
1.1.1 Transcription factors and DNA binding	2
1.1.2 Sequence determinants of binding	2
1.1.3 The specificity paradox	3
1.2 Next-generation sequencing and ChIP-seq	4
1.2.1 Short-read sequencing	4
1.2.2 Chromatin immunoprecipitation sequencing	5
1.2.3 Cut&Tag as a methodological contrast	5
1.2.4 Read alignment and peak calling	5
1.2.5 Reproducibility filtering and IDR	6
1.2.6 Data formats and reference genome	6
1.2.7 The ENCODE project	6
1.2.8 Long-range sequence context around binding sites	7
1.3 Next-generation sequencing and ChIP-seq	8
1.3.1 Short-read sequencing	8
1.3.2 Chromatin immunoprecipitation sequencing	8
1.3.3 Cut&Tag as a methodological contrast	9
1.3.4 Read alignment and peak calling	9
1.3.5 Reproducibility filtering and IDR	9
1.3.6 Data formats and reference genome	10
1.3.7 The ENCODE project	10
1.3.8 Long-range sequence context around binding sites	10
1.4 Computational approaches to TF binding site analysis	11
1.4.1 Position weight matrices	11
1.4.2 Motif discovery and enrichment analysis	12
1.4.3 Extensions beyond the independence model	12

1.4.4 The kilobase-scale context gap	13
1.5 Genomic foundation models	13
1.5.1 Self-supervised pretraining and the foundation model paradigm . . .	13
1.5.2 Genomic foundation models: a brief landscape	14
1.5.3 Evo and Evo 2	14
1.5.4 Embedding extraction and layer selection	15
1.5.5 Autoregressive context and its implications	16
Chapter 2. Aims of thesis	17
Chapter 3. Methods	18
3.1 Data	18
3.1.1 Transcription factors	18
3.1.2 ChIP-seq data sources	18
3.1.3 Cell-line coverage	19
3.1.4 Random-windows control	19
3.1.5 Reproducibility and seeding	20
3.2 Pipeline	20
3.2.1 Sequence extraction	20
3.2.2 Embedding extraction	21
3.2.3 Computational environment	21
3.3 Analyses	22
Chapter 4. Druhá kapitola s matematikou $\int f(x) dx$ v názvu	23
4.1 Podkapitola	26
Závěr	27
Bibliography	33
Appendix	34

List of Figures

List of Tables

3.1 Chosen ChIP-seq experiments	19
---	----

List of abbreviations

- $\mathbb{C}$ množina všech komplexních čísel
- $\mathbb{R}$ množina všech reálných čísel
- $\mathbb{Z}$ množina všech celých čísel
- $\mathbb{N}$ množina všech přirozených čísel

Introduction

Chapter 1

Theoretical background

1.1 Transcription factor binding

1.1.1 Transcription factors and DNA binding

Transcription factors (TFs) are proteins that modulate transcription by binding DNA in a sequence-specific manner. They act through regulatory elements such as promoters, enhancers, and silencers, recruiting the transcription machinery or modulating its activity. Most TFs share a modular architecture: a DNA-binding domain (DBD) that contacts the target sequence, paired with one or more effector domains responsible for transactivation, repression, or dimerisation. Because the DBD determines binding specificity, TFs are classified by DBD family rather than by effector function. The human genome encodes approximately 1600 sequence-specific TFs distributed across roughly 75 DBD families (Lambert et al., 2018). The families represented among the TFs studied in this thesis include the C2H2 zinc fingers (the largest human family, exemplified by CTCF), the basic helix-loop-helix proteins (MYC, which binds as an obligate heterodimer with MAX), and the ETS domain family (SPI1).

Target sequences are typically short motifs of 6–20 bp, recognized with tolerance for sequence variation. Despite the considerable structural variety across DBD families, all sequence-specific TFs face the same fundamental problem: they must locate their short target sequence among a large number of similar but non-functional sites distributed across a genome of several gigabases.

1.1.2 Sequence determinants of binding

The specificity of protein–DNA recognition rests on two complementary mechanisms: direct chemical recognition of bases (base readout) and recognition of sequence-dependent DNA geometry (shape readout).

Base readout operates through direct contacts — hydrogen bonds and van der Waals interactions — between amino acid side chains and the Watson–Crick edges of bases, predominantly in the major groove. *The major groove presents a distinctive pattern of hydrogen bond donors and acceptors* that permits discrimination between all four base pairs, including the orientation of A:T and T:A (Luscombe et al., 2001; Seeman et al.,

1976). The C2H2 zinc finger illustrates the mechanism: each $\beta\beta\alpha$ module contacts approximately three base pairs through specificity residues on the recognition helix, and the contributions of successive modules combine to determine the affinity and specificity of the full array. Position weight matrices (PWMs) are the natural statistical encoding of base readout, treating each position within the motif as an independent contribution to binding affinity (§1.4).

Shape readout depends on sequence context beyond the contact position. The geometry at any given base pair — minor groove width, propeller twist, helical twist, roll, and slide — is influenced by neighbouring bases over several positions in either direction, and is read by protein contacts that respond to local shape and electrostatics rather than to specific bases. The canonical example is recognition of narrow minor grooves by arginine residues: runs of A:T base pairs (A-tracts) produce locally narrowed minor grooves with concentrated negative electrostatic potential, which arginine side chains insert into and stabilise without forming base-specific hydrogen bonds (Rohs et al., 2009).

The two mechanisms are genuinely complementary rather than redundant. Crystal structures of TF–DNA complexes routinely show major-groove base-specific contacts and minor-groove shape-based contacts within the same interface, and augmenting PWM-based models with predicted shape features systematically improves binding prediction across TF families (Mathelier et al., 2016). Their combined reach is nonetheless bounded by the binding footprint: base readout depends on direct contacts within the 6–20 bp footprint, and shape readout, while sensitive to flanking sequence, is mediated through contacts within and immediately adjacent to it (Yang et al., 2017).

1.1.3 The specificity paradox

The degeneracy of TF motifs means that a typical 10 bp motif at moderate information content matches millions of sites in a mammalian genome, while in vivo occupancy — assayed by ChIP-seq, the standard method described in §1.3 — typically identifies between a few thousand and a few tens of thousands of bound sites per TF per cell line. CTCF in K562 cells, for example, has approximately 52 000 IDR-thresholded ENCODE peaks, against approximately 870 000 matches to the canonical CTCF motif in the hg19 genome at standard FIMO thresholds (Dozmorov et al., 2022). This discrepancy between motif presence and actual occupancy has been termed the transcription factor specificity paradox; it was formalised for prokaryotic TFs as the futility theorem by Wunderlich and Mirny (2009), who showed that in a sufficiently large genome even highly informative motifs predict more matches than there are TF molecules in the cell, making purely sequence-based recognition statistically insufficient. In practice, the paradox is reflected in the weak correlation between intrinsic in vitro affinity (measured by HT-SELEX or protein-binding microarrays) and in vivo occupancy: high-affinity sites can remain unbound, while low-affinity sites are often occupied (Slattery et al., 2014).

Several mechanisms partially resolve the discrepancy, each a substantial field in its own right. Chromatin accessibility is regarded as the dominant factor: only a small fraction of the genome is accessible to DNA-binding proteins at any given time, the remainder occluded by nucleosomes or compacted into heterochromatin, and most in

vivo TF binding occurs within accessible regions (Thurman et al., 2012). Cooperative binding with cofactors restricts binding further: many TFs bind productively only as part of a complex — homodimers, heterodimers, or larger assemblies — so the combinatorics of cofactor co-occupancy limit where productive binding can occur (Sönmezer et al., 2021). Cellular context adds a third layer: TF abundance, post-translational modification, and subcellular localisation are all condition-dependent and regulate the effective concentration of binding-competent protein. [TODO: yeah? where did i get this?]

A fourth contribution, less studied than the preceding three, is sequence context beyond the motif itself. Dror et al. (2015) demonstrated, in a systematic analysis of 239 TFs from HT-SELEX and 56 from ChIP-seq data, that the sequence and DNA shape environment surrounding bound motifs differs significantly from that surrounding unbound occurrences of the same motif, with differences extending well beyond the core binding site and exhibiting TF-family-specific patterns. [TODO: distinguish from shape readout somehow, read dror again] Crucially, the signal new was present in both the in vitro and in vivo datasets, ruling out the cellular environment as its sole source and establishing flanking sequence context as a genuine, sequence-encoded contributor to binding discrimination. Unlike chromatin accessibility and cooperative binding, this contribution is in principle directly accessible to any model that operates on raw sequence input.

The spatial scale at which sequence context influences binding spans several orders of magnitude: from the immediate flanks of the core motif (Dror et al., 2015), through the tens-to-hundreds of base pairs over which sequence composition modulates the nonspecific affinity experienced by a scanning TF (Afek a Lukatsky, 2013; Sela a Lukatsky, 2011), *out to the kilobase-scale compositional gradients recently characterised by Faltejsková et al. (2026)*. That last study, and its role as the biological motivation for the analyses in this thesis, is discussed in §1.3.8 following the description of the experimental data on which both studies are based. [TODO: soften claim - descriptive? implied?, is this first mention? mention it's a preprint?]

1.2 Next-generation sequencing and ChIP-seq

1.2.1 Short-read sequencing

Next-generation sequencing (NGS) refers to high-throughput DNA sequencing technologies that determine the nucleotide sequence of millions to billions of short DNA fragments in parallel. The dominant platform in current use is Illumina sequencing-by-synthesis: libraries of DNA fragments are clonally amplified on a flow cell surface, and each cycle of synthesis incorporates fluorescently labelled reversible-terminator nucleotides whose identity is read by imaging (Bentley et al., 2008). Typical read lengths are 50–150 bp per end; paired-end protocols sequence both ends of each fragment and are standard for ChIP-seq. The output is a set of FASTQ files containing read sequences and per-base quality scores. Key limitations are the short read length, which complicates mapping to repetitive regions, and a characteristic per-base error rate of approximately 10^{-3} , dominated by substitution errors.

NGS functions as a platform on which different upstream wet-lab protocols measure different genomic quantities: RNA-seq measures transcript abundance, ATAC-seq measures chromatin accessibility, and ChIP-seq measures protein–DNA contacts. The platform is otherwise identical across assays; what changes is the biological molecule subjected to fragmentation and *sequencing*.

1.2.2 Chromatin immunoprecipitation sequencing

Chromatin immunoprecipitation followed by sequencing (ChIP-seq) is the standard method for mapping genome-wide protein–DNA contacts at the population level (Park, 2009). [TODO: no access,] In the crosslinking variant used for most TF ChIP-seq experiments, cells are treated with formaldehyde to covalently crosslink protein–DNA complexes in situ, chromatin is then fragmented by sonication or enzymatic digestion to a target size of approximately 200 bp, and an antibody specific to the TF of interest is used to immunoprecipitate the crosslinked complexes. After reversal of crosslinks, the co-purified DNA is sequenced. The resulting reads are enriched at genomic positions occupied by the protein, producing a coverage signal that is higher at bound sites than at unbound genomic background.

The output of ChIP-seq is interpretable as a population-averaged estimate of contact frequency: sites occupied in a large fraction of cells contribute more fragments to the library and produce sharper, higher-amplitude peaks. This population averaging is a fundamental limitation: the assay does not report single-cell occupancy, cannot distinguish direct from indirect binding (a TF pulled down as part of a complex is not directly bound to the immunoprecipitated DNA), and is sensitive to antibody quality in ways that are difficult to control post-hoc.

1.2.3 Cut&Tag as a methodological contrast

An alternative to ChIP-seq that is increasingly used for TF mapping is CUT&Tag (Kaya-Okur et al., 2019). Rather than immunoprecipitating crosslinked complexes, CUT&Tag uses a Protein A–Tn5 transposase fusion, directed to the protein of interest by an antibody, to tagment (cut and insert sequencing adaptors into) the DNA in the immediate vicinity of the bound protein. The method requires lower cell inputs, produces lower background, and generates sharper peaks than ChIP-seq, making it particularly attractive for TFs with weak or transient binding. One CUT&Tag dataset (CTCF in K562 cells; (Kaya-Okur et al. 2019)) is included in the Faltejsková et al. dataset to which this thesis refers; all ChIP-seq data used in this thesis are from conventional ChIP-seq experiments.

1.2.4 Read alignment and peak calling

Sequencing reads are aligned to the reference genome using short-read aligners such as BWA (H. Li, 2013) or Bowtie 2 (langmeadFastGappedreadAlignment2012), [TODO: verify how to cite bowtie - i dont have access] producing coordinate-sorted BAM files with alignment information and mapping quality scores. Reads mapping to multiple

locations are typically filtered; duplicate reads arising from PCR amplification of the same fragment are also marked and excluded.

Enriched genomic regions (peaks) are identified by peak-calling algorithms that compare local fragment density in the immunoprecipitated sample against a control library, usually input chromatin from the same cells. MACS2 is the standard algorithm for TF ChIP-seq (Zhang et al., 2008); it models the expected fragment distribution, estimates local background from a sliding window, and assigns a p -value and q -value to each candidate peak under a Poisson model. The primary output is a narrowPeak BED-format file containing one row per peak, with columns for chromosomal coordinates, a peak score, $-\log_{10}(p)$, $-\log_{10}(q)$, and the offset of the peak summit from the start coordinate. For TF ChIP-seq, peak widths are typically 200–500 bp.

1.2.5 Reproducibility filtering and IDR

Because ChIP-seq is sensitive to antibody efficiency and library complexity, peaks called from a single experiment may include irreproducible signals. The Irreproducible Discovery Rate (IDR) framework provides a principled way to rank peaks by their reproducibility across biological or technical replicates (Q. Li et al., 2011). IDR fits a mixture model to the joint rank distribution of peaks across two replicates and assigns each peak a probability of arising from the reproducible component of the mixture. Peaks below an IDR threshold are retained; those above are discarded as likely irreproducible. The ENCODE project distributes IDR-thresholded peak calls as the recommended file type for downstream analysis (Dunham et al., 2012); conservative IDR-thresholded calls, which are thresholded at an IDR of 0.05 applied to the self-consistency ratio as well as the pooled-consistency ratio, are preferred where available. All peak files used in this thesis are IDR-thresholded narrowPeak files obtained from the ENCODE portal.

1.2.6 Data formats and reference genome

The narrowPeak format used throughout this thesis is a ten-column extension of the BED format, with the extension columns carrying the MACS2 signal, p -value, q -value, and summit offset. **[TODO: a few example lines of a narrowPeak file with the columns, for illustration?]** Reference genome sequences are stored in FASTA format and indexed with `samtools faidx` to allow efficient random-access retrieval of arbitrary intervals, which is required for the window-extraction step described in §??.

This thesis uses the hg19/GRCh37 human reference assembly throughout, consistent with the Faltejisková et al. analysis. The hg38/GRCh38 assembly is the current reference standard and differs from hg19 primarily in gap-filling and a small number of chromosome-level corrections; coordinates are not directly interchangeable, and liftover is required to transfer annotations between assemblies. Non-B DNA and CpG island annotations used by Faltejisková et al. are hg38-based and were not used in this thesis.

1.2.7 The ENCODE project

The Encyclopedia of DNA Elements (ENCODE) project is a large-scale, consortium-driven effort to functionally annotate the human genome through systematic appli-

cation of high-throughput assays including ChIP-seq, ATAC-seq, RNA-seq, and others (Dunham et al., 2012). ENCODE enforces standardised experimental protocols, antibody validation requirements, and bioinformatic pipelines, and applies automated quality-control audits to all deposited experiments. Experiments flagged by these audits as failing quality thresholds are marked accordingly on the portal; no red-flagged experiments are included in this thesis. All data are publicly available through the ENCODE portal (<https://www.encodeproject.org>) under permissive data use agreements. **[TODO: decide if the url is a footnote]**

The TFs and cell lines used in this thesis — MYC, CTCF, and SPI1 across cell lines GM12878, H1, K562, and MCF-7 — were selected from the Faltejsková et al. supplementary accession list, which is itself drawn from ENCODE. Full accession identifiers and selection criteria are given in §??. **[TODO: consider dropping]**

1.2.8 Long-range sequence context around binding sites

The ChIP-seq peak calls distributed by ENCODE identify the genomic coordinates of protein–DNA contacts, but the narrowPeak format records only a 200–500 bp window around the occupied site. Whether the broader sequence context surrounding a bound site encodes systematic, non-random features — and whether those features are consistent with a role in guiding TF recognition — is a question that cannot be answered from the peak coordinates alone.

Faltejsková et al. (2026) addressed this question in a recent descriptive study published in *Nucleic Acids Research*. They analysed a ± 5000 bp window around in vivo binding sites for ten TFs drawn from ENCODE ChIP-seq and one CUT&Tag dataset, dividing each 10 kb window into 50 bp non-overlapping segments and computing sequence composition features — GC content, dinucleotide frequencies, predicted DNA shape (via deepDNASHape), and HOCOMOCO-based TF affinity scores — across the profile from distal flanks to peak centre.

The principal finding is that GC content is significantly elevated in a patch spanning approximately 1–2 kb around the binding site for most of the ten TFs examined, with a typical magnitude of ~ 10 percentage points above the distal flank. Directional asymmetries in dinucleotide composition, pointing toward the binding site, were observed for several TFs including MYC, FOXK2, and p53, and are absent or weak for CTCF and SPI1. DNA shape features predicted from the local sequence context — in particular roll and helical twist — change in a manner consistent with increased bendability near the binding site. A small but significant enrichment of predicted Z-DNA and G-quadruplex motifs at the binding site was also observed for selected TFs, though the authors note these are insufficient to account for the full dinucleotide pattern.

These findings are interpreted through a “statistical funnel” model: broad compositional gradients around binding sites create a low-free-energy landscape that biases TFs undergoing one-dimensional facilitated diffusion toward the target site, complementing the short-range specific recognition described in §1.1.2. The study explicitly characterises this model as hypothesis-generating. Critically, it is a descriptive analysis: no model is tested for whether it can detect or exploit the sequence gradients described.

This descriptive gap is the primary motivation for the present thesis. The sequence

features characterised by Faltejsková et al. (2026) extend over 1–2 kb on either side of the binding site — a spatial scale that is inaccessible to conventional motif-based models by design, but that falls within the context window of recent genomic foundation models operating at single-nucleotide resolution. Whether the per-token embeddings of such a model encode the kilobase-scale compositional structure described above is the empirical question taken up in this thesis. The foundation model used, Evo 2, is introduced in §1.5.

1.3 Next-generation sequencing and ChIP-seq

1.3.1 Short-read sequencing

Next-generation sequencing (NGS) refers to high-throughput DNA sequencing technologies that determine the nucleotide sequence of millions to billions of short DNA fragments in parallel. The dominant platform in current use is Illumina sequencing-by-synthesis: libraries of DNA fragments are clonally amplified on a flow cell surface, and each cycle of synthesis incorporates fluorescently labelled reversible-terminator nucleotides whose identity is read by imaging (Bentley et al., 2008). Typical read lengths are 50–150 bp per end; paired-end protocols sequence both ends of each fragment and are standard for ChIP-seq. The output is a set of FASTQ files containing read sequences and per-base quality scores. Key limitations are the short read length, which complicates mapping to repetitive regions, and a characteristic per-base error rate of approximately 10^{-3} , dominated by substitution errors.

NGS functions as a platform on which different upstream wet-lab protocols measure different genomic quantities: RNA-seq measures transcript abundance, ATAC-seq measures chromatin accessibility, and ChIP-seq measures protein–DNA contacts. The platform is otherwise identical across assays; what changes is the biological molecule subjected to fragmentation and *sequencing*.

1.3.2 Chromatin immunoprecipitation sequencing

Chromatin immunoprecipitation followed by sequencing (ChIP-seq) is the standard method for mapping genome-wide protein–DNA contacts at the population level (Park, 2009). [TODO: no access,] In the crosslinking variant used for most TF ChIP-seq experiments, cells are treated with formaldehyde to covalently crosslink protein–DNA complexes in situ, chromatin is then fragmented by sonication or enzymatic digestion to a target size of approximately 200 bp, and an antibody specific to the TF of interest is used to immunoprecipitate the crosslinked complexes. After reversal of crosslinks, the co-purified DNA is sequenced. The resulting reads are enriched at genomic positions occupied by the protein, producing a coverage signal that is higher at bound sites than at unbound genomic background.

The output of ChIP-seq is interpretable as a population-averaged estimate of contact frequency: sites occupied in a large fraction of cells contribute more fragments to the library and produce sharper, higher-amplitude peaks. This population averaging is a fundamental limitation: the assay does not report single-cell occupancy, cannot

distinguish direct from indirect binding (a TF pulled down as part of a complex is not directly bound to the immunoprecipitated DNA), and is sensitive to antibody quality in ways that are difficult to control post-hoc.

1.3.3 Cut&Tag as a methodological contrast

An alternative to ChIP-seq that is increasingly used for TF mapping is CUT&Tag (Kaya-Okur et al., 2019). Rather than immunoprecipitating crosslinked complexes, CUT&Tag uses a Protein A–Tn5 transposase fusion, directed to the protein of interest by an antibody, to tagment (cut and insert sequencing adaptors into) the DNA in the immediate vicinity of the bound protein. The method requires lower cell inputs, produces lower background, and generates sharper peaks than ChIP-seq, making it particularly attractive for TFs with weak or transient binding. One CUT&Tag dataset (CTCF in K562 cells; (Kaya-Okur et al. 2019)) is included in the Faltejsková et al. dataset to which this thesis refers; all ChIP-seq data used in this thesis are from conventional ChIP-seq experiments.

1.3.4 Read alignment and peak calling

Sequencing reads are aligned to the reference genome using short-read aligners such as BWA (H. Li, 2013) or Bowtie 2 (`langmeadFastGappedreadAlignment2012`), **[TODO: verify how to cite bowtie - i dont have access]** producing coordinate-sorted BAM files with alignment information and mapping quality scores. Reads mapping to multiple locations are typically filtered; duplicate reads arising from PCR amplification of the same fragment are also marked and excluded.

Enriched genomic regions (peaks) are identified by peak-calling algorithms that compare local fragment density in the immunoprecipitated sample against a control library, usually input chromatin from the same cells. MACS2 is the standard algorithm for TF ChIP-seq (Zhang et al., 2008); it models the expected fragment distribution, estimates local background from a sliding window, and assigns a p -value and q -value to each candidate peak under a Poisson model. The primary output is a narrowPeak BED-format file containing one row per peak, with columns for chromosomal coordinates, a peak score, $-\log_{10}(p)$, $-\log_{10}(q)$, and the offset of the peak summit from the start coordinate. For TF ChIP-seq, peak widths are typically 200–500 bp.

1.3.5 Reproducibility filtering and IDR

Because ChIP-seq is sensitive to antibody efficiency and library complexity, peaks called from a single experiment may include irreproducible signals. The Irreproducible Discovery Rate (IDR) framework provides a principled way to rank peaks by their reproducibility across biological or technical replicates (Q. Li et al., 2011). IDR fits a mixture model to the joint rank distribution of peaks across two replicates and assigns each peak a probability of arising from the reproducible component of the mixture. Peaks below an IDR threshold are retained; those above are discarded as likely irreproducible. The ENCODE project distributes IDR-thresholded peak calls as the recommended

file type for downstream analysis (Dunham et al., 2012); conservative IDR-thresholded calls, which are thresholded at an IDR of 0.05 applied to the self-consistency ratio as well as the pooled-consistency ratio, are preferred where available. All peak files used in this thesis are IDR-thresholded narrowPeak files obtained from the ENCODE portal.

1.3.6 Data formats and reference genome

The narrowPeak format used throughout this thesis is a ten-column extension of the BED format, with the extension columns carrying the MACS2 signal, p -value, q -value, and summit offset. **[TODO: a few example lines of a narrowPeak file with the columns, for illustration?]** Reference genome sequences are stored in FASTA format and indexed with `samtools faidx` to allow efficient random-access retrieval of arbitrary intervals, which is required for the window-extraction step described in §??.

This thesis uses the hg19/GRCh37 human reference assembly throughout, consistent with the Faltejsová et al. analysis. The hg38/GRCh38 assembly is the current reference standard and differs from hg19 primarily in gap-filling and a small number of chromosome-level corrections; coordinates are not directly interchangeable, and liftover is required to transfer annotations between assemblies. Non-B DNA and CpG island annotations used by Faltejsová et al. are hg38-based and were not used in this thesis.

1.3.7 The ENCODE project

The Encyclopedia of DNA Elements (ENCODE) project is a large-scale, consortium-driven effort to functionally annotate the human genome through systematic application of high-throughput assays including ChIP-seq, ATAC-seq, RNA-seq, and others (Dunham et al., 2012). ENCODE enforces standardised experimental protocols, antibody validation requirements, and bioinformatic pipelines, and applies automated quality-control audits to all deposited experiments. Experiments flagged by these audits as failing quality thresholds are marked accordingly on the portal; no red-flagged experiments are included in this thesis. All data are publicly available through the ENCODE portal (<https://www.encodeproject.org>) under permissive data use agreements. **[TODO: decide if the url is a footnote]**

The TFs and cell lines used in this thesis — MYC, CTCF, and SPI1 across cell lines GM12878, H1, K562, and MCF-7 — were selected from the Faltejsová et al. supplementary accession list, which is itself drawn from ENCODE. Full accession identifiers and selection criteria are given in §??. **[TODO: consider dropping]**

1.3.8 Long-range sequence context around binding sites

The ChIP-seq peak calls distributed by ENCODE identify the genomic coordinates of protein–DNA contacts, but the narrowPeak format records only a 200–500 bp window around the occupied site. Whether the broader sequence context surrounding a bound site encodes systematic, non-random features — and whether those features are consistent with a role in guiding TF recognition — is a question that cannot be answered from the peak coordinates alone.

Faltejsková et al. (2026) addressed this question in a recent descriptive study published in *Nucleic Acids Research*. They analysed a ± 5000 bp window around in vivo binding sites for ten TFs drawn from ENCODE ChIP-seq and one CUT&Tag dataset, dividing each 10 kb window into 50 bp non-overlapping segments and computing sequence composition features — GC content, dinucleotide frequencies, predicted DNA shape (via deepDNASHape), and HOCOMOCO-based TF affinity scores — across the profile from distal flanks to peak centre.

The principal finding is that GC content is significantly elevated in a patch spanning approximately 1–2 kb around the binding site for most of the ten TFs examined, with a typical magnitude of ~ 10 percentage points above the distal flank. Directional asymmetries in dinucleotide composition, pointing toward the binding site, were observed for several TFs including MYC, FOXK2, and p53, and are absent or weak for CTCF and SPI1. DNA shape features predicted from the local sequence context — in particular roll and helical twist — change in a manner consistent with increased bendability near the binding site. A small but significant enrichment of predicted Z-DNA and G-quadruplex motifs at the binding site was also observed for selected TFs, though the authors note these are insufficient to account for the full dinucleotide pattern.

These findings are interpreted through a “statistical funnel” model: broad compositional gradients around binding sites create a low-free-energy landscape that biases TFs undergoing one-dimensional facilitated diffusion toward the target site, complementing the short-range specific recognition described in §1.1.2. The study explicitly characterises this model as hypothesis-generating. Critically, it is a descriptive analysis: no model is tested for whether it can detect or exploit the sequence gradients described.

This descriptive gap is the primary motivation for the present thesis. The sequence features characterised by Faltejsková et al. (2026) extend over 1–2 kb on either side of the binding site — a spatial scale that is inaccessible to conventional motif-based models by design, but that falls within the context window of recent genomic foundation models operating at single-nucleotide resolution. Whether the per-token embeddings of such a model encode the kilobase-scale compositional structure described above is the empirical question taken up in this thesis. The foundation model used, Evo 2, is introduced in §1.5.

1.4 Computational approaches to TF binding site analysis

1.4.1 Position weight matrices

The dominant computational representation of TF binding specificity is the position weight matrix (PWM), *also called a position-specific scoring matrix (PSSM)*. A PWM is derived from a set of aligned binding sequences of fixed width L : at each position $i \in \{1, \dots, L\}$ and nucleotide $b \in \{A, C, G, T\}$, the log-odds score $w_{i,b} = \log_2(f_{i,b}/p_b)$ is computed, where $f_{i,b}$ is the observed frequency of nucleotide b at position i among the training sequences and p_b is the background frequency of b (Stormo, 2000). The score of a candidate sequence is the sum of per-position log-odds terms; a threshold

on this score determines whether the sequence is called a binding site. The information content of the matrix, $IC = \sum_i \sum_b f_{i,b} \log_2(f_{i,b}/p_b)$, is a measure of the specificity of the motif and is used to produce the familiar sequence logo visualisation (Schneider and Stephens, 1990). **[TODO: sequence logo visual]**

The PWM model rests on an independence assumption: the contribution of each position to the total score is treated as additive, with no coupling between positions. This assumption is biologically inaccurate — adjacent nucleotides are correlated in both sequence and structural terms — but the model is computationally tractable, transferable across organisms, and sufficiently accurate for many applications. It remains the standard representation in curated databases such as JASPAR (Oveik Baydar et al., 2026) and HOCOMOCO (Vorontsov et al., 2024), which together provide PWM models for the large majority of human TFs.

1.4.2 Motif discovery and enrichment analysis

Given a set of ChIP-seq peak sequences, two related tasks arise: discovering the sequence motif enriched in the peaks (motif discovery), and testing whether a known motif is significantly enriched relative to a background set (motif enrichment).

MEME (Multiple Em for Motif Elicitation) addresses the discovery task using expectation maximisation to identify the PWM that best explains an overrepresented pattern across the input sequences (Bailey and Elkan, 1995); the broader MEME Suite extends this to enrichment testing, scanning, and comparative analysis (Bailey, Johnson et al., 2015). HOMER (Hypergeometric Optimization of Motif EnRichment) is widely used for ChIP-seq specifically: it optimises motif enrichment relative to a GC-matched background set, making it robust to the GC bias that is characteristic of many TF binding sites (Heinz et al., 2010). Scanning a genome with a known PWM to identify all sites above a score threshold is performed by tools such as FIMO (Grant et al., 2011); this is the operation used to count the motif matches discussed in §1.1.3.

1.4.3 Extensions beyond the independence model

Several approaches have been developed to relax the positional independence assumption. Dinucleotide weight matrices (DWMs) model pairwise dependencies between adjacent positions, capturing the nearest-neighbour sequence correlations that are mechanistically important for shape readout. Hidden Markov models and related probabilistic graphical models can represent variable-length motifs with internal positional dependencies, at the cost of increased model complexity and training data requirements. **[TODO: citation]** Convolutional neural networks trained on ChIP-seq data learn sequence representations that implicitly capture multi-position dependencies and outperform PWMs on held-out binding prediction benchmarks (Alipanahi et al., 2015); however, such models are typically trained in a supervised setting and require labelled positive and negative sequences.

A complementary line of work incorporates predicted DNA shape features alongside sequence features. Mathelier et al. (2016) showed that adding per-position shape predictions (minor groove width, propeller twist, roll, and helical twist computed by

DNASHape) as features alongside the PWM score systematically improves *in vivo* binding prediction across a broad range of TF families. The deepDNASHape model (J. Li et al., 2024), which predicts the same structural features from sequence using a neural network trained on molecular dynamics simulations, is used by Faltejsková et al. (2026) to characterise shape changes across the 10 kb window around binding sites.

1.4.4 The kilobase-scale context gap

All methods described above share a fundamental constraint: they operate on a fixed window whose width is determined by the binding footprint of the TF. PWMs typically span 6–20 bp; even extended models incorporating shape features or positional dependencies are anchored to the core motif and its immediate neighbourhood, typically within 50 bp. By construction, these methods cannot represent the kilobase-scale sequence composition gradients described in §1.3.8, because they have no mechanism for incorporating sequence at that distance from the binding site.

This constraint is not a limitation of any specific algorithm but is inherent to the class of models: the binding site itself is defined as a short sequence, and the model is designed to score that sequence. Capturing kilobase-scale context requires a qualitatively different modelling approach — one that processes the full sequence window and produces representations that integrate information across its entire length. Genomic foundation models, described in the following section, are a natural candidate for this role.

1.5 Genomic foundation models

1.5.1 Self-supervised pretraining and the foundation model paradigm

The dominant paradigm in modern sequence modelling [TODO: this is not specific to sequence modelling. bommasani is general about foundation model] is self-supervised pretraining on large unlabelled corpora, followed by task-specific adaptation. A model is trained to predict held-out portions of the input sequence from the remaining context: in masked language modelling, randomly selected tokens are replaced with a mask symbol and the model is trained to recover them; in autoregressive modelling, the model is trained to predict each token from all preceding tokens. Neither objective requires labelled data; the supervision signal is derived entirely from the sequence itself. The resulting model learns distributed representations that encode statistical regularities of the training corpus and that can be transferred to downstream tasks by fine-tuning on small labelled datasets or by extracting intermediate-layer embeddings for use as features (Bommasani et al., 2022).

The transformer architecture (Vaswani et al., 2017) is the backbone of most current foundation models. Its core mechanism, scaled dot-product attention, computes pairwise interactions between all positions in the input sequence, allowing each position's representation to integrate information from arbitrarily distant context. This property makes transformers well-suited for tasks that require long-range dependencies; however, the computational and memory cost of full attention scales quadratically with

sequence length, which places a practical ceiling on the context window at training time. For DNA, where biologically relevant interactions can span thousands to millions of base pairs, this is a fundamental constraint.

[TODO: Consider a schematic here contrasting the limited receptive field of a PWM scanner against the full-context attention of a transformer, to visually motivate why architecture matters for the kilobase-scale problem.]

1.5.2 Genomic foundation models: a brief landscape

The first genomic foundation model applied to regulatory sequence was DNABERT (Ji et al., 2021), which adapted the BERT masked language modelling objective to the human reference genome. DNABERT tokenises the genome into overlapping k -mers (default $k = 6$) and pretrains a bidirectional transformer on the resulting token sequences. The pretrained model was shown to transfer to promoter prediction, splice site detection, and TF binding site prediction by fine-tuning on small labelled datasets. A limitation of the k -mer tokenisation is that it conflates sequence position with token identity and produces a highly redundant vocabulary; the context window at inference time was also limited to 512 tokens, corresponding to roughly 512 bp of genomic sequence.

The Nucleotide Transformer (Dalla-Torre et al., 2025) scaled the masked language modelling approach to larger model sizes (up to 2.5 billion parameters) and a multi-species training corpus, demonstrating that scale improves transfer performance across a broad panel of regulatory prediction benchmarks. Its context window remains limited to a few kilobases at inference.

HyenaDNA (Nguyen, Poli, Faizi et al., 2023) addressed the context length problem by replacing the attention mechanism with the Hyena operator, a data-controlled convolutional recurrence that scales linearly in sequence length. Trained autoregressively on the human reference genome at single-nucleotide resolution, HyenaDNA extended the practical context window to up to 1 million base pairs, demonstrating for the first time that a genomic foundation model could be trained and evaluated at the scale of entire chromosomal regions. Performance on short-range benchmarks was competitive with transformer-based models; the primary advance was the demonstration that linear-scaling architectures could handle genomic context lengths that are infeasible for full attention.

1.5.3 Evo and Evo 2

Evo (Nguyen, Poli, Durrant et al., 2024) extended the long-context autoregressive paradigm to a multi-kingdom training corpus, pretraining a 7 billion parameter model on prokaryotic, viral, and eukaryotic genomes using the StripedHyena architecture. StripedHyena interleaves multi-head attention layers with Hyena convolutional layers, combining the strong local feature extraction of attention with the linear-scaling long-range context capture of the Hyena operator. Evo demonstrated capabilities in zero-shot variant effect prediction, coding sequence generation, and CRISPR guide RNA design.

Evo 2 (Brix et al., 2026) is the successor model, published in *Nature* in 2026. It is

trained autoregressively on OpenGenome2, a curated dataset of 8.8 trillion nucleotide tokens drawn from organisms across all domains of life, including prokaryotes, archaea, and eukaryotes. The architecture is StripedHyena 2, an updated version that further improves the integration of attention and gated convolutional layers. Models are available in three sizes: 1 billion, 7 billion, and 40 billion parameters. The 7 billion parameter checkpoint used in this thesis operates at single-nucleotide resolution with a context window of up to 1 million base pairs in its extended-context configuration (evo2_7b), or 8192 tokens in its base configuration (evo2_7b_base). Because the 10 kb windows used in this thesis exceed the 8192-token limit of the base checkpoint, the extended-context evo2_7b checkpoint is used throughout.

Evo 2 has been benchmarked on variant effect prediction across coding and non-coding variants, zero-shot fitness prediction for proteins and ncRNA, and generative sequence design; these evaluations are described in the original publication. Whether and how Evo 2 embeddings represent the sequence context around in vivo TF binding sites has not been examined.

1.5.4 Embedding extraction and layer selection

Foundation models trained autoregressively produce, at each token position, a hidden-state vector whose dimensionality equals the model's embedding dimension. These per-token hidden states are the primary substrate for embedding-based analyses: they can be mean-pooled across the sequence to produce a single fixed-length representation, or retained at full resolution to carry positional information.

For Evo 2 with a 7 billion parameter model, the embedding dimension is 4096. Each token (nucleotide) at each sequence position produces a 4096-dimensional vector; a 10 kb sequence therefore yields a $(10,000 \times 4096)$ matrix of hidden states before any pooling.

The choice of which layer's hidden states to extract is consequential. The final layer is specialised for the next-token prediction objective and carries information optimised for that task rather than for general-purpose representation. Intermediate layers have been shown empirically to produce more transferable representations for downstream tasks; *the exon classifier notebook distributed with Evo 2 uses layer blocks.28.mlp.13 as the embedding source for a classification task* [TODO: what else do they use it for?], and this layer is used in the present thesis for the same reason.

[TODO: consider cutting] In this thesis, each 10 kb sequence is processed in a single forward pass through evo2_7b, and the per-token hidden states from blocks.28.mlp.13 are extracted and mean-pooled within non-overlapping 50 bp bins to yield a (200×4096) positional embedding profile per peak. This binning resolution matches the 50 bp window size used by Faltejsková et al. (2026) for hand-engineered feature extraction, allowing a direct spatial correspondence between the two analyses. The technical details of the embedding pipeline are described in §??.

1.5.5 Autoregressive context and its implications

A property of autoregressive models that is directly relevant to the interpretation of positional embedding profiles is the asymmetry of context: at any token position t , the hidden state is computed from all preceding tokens $1, \dots, t-1$ but has no access to tokens at positions $t+1, \dots, L$. Tokens near the beginning of the sequence therefore have little or no left context, and their representations may differ systematically from tokens in the interior of the sequence where left context is rich. This warm-up effect is a model-level property, not a sequence-biological signal, and must be accounted for when interpreting positional embedding profiles derived from fixed-start 10 kb windows. The practical consequence for this thesis — and the trimming strategy adopted to address it — is described in §??.

[TODO: simplified StripedHyena 2 diagram, or the one from the paper]

Chapter 2

Aims of thesis

- 1.

Chapter 3

Methods

3.1 Data

3.1.1 Transcription factors

The descriptive analysis is performed on three human transcription factors selected to span distinct binding modes relevant to the questions posed in this thesis: CTCF, MYC, and SPI1. CTCF is an eleven-zinc-finger architectural factor with a long, well-characterised consensus motif and broad genomic occupancy, included as a strong-motif baseline against which embedding-based representations can be evaluated (Ong a Corces, 2014) MYC is a basic helix-loop-helix leucine-zipper factor that, in the analysis of Faltejsková et al. (2026), displays a pronounced directional dinucleotide asymmetry in the kilobase-scale flanks of its in vivo binding sites, making it a natural target for testing whether long-range sequence structure is reflected in Evo 2 representations (Lüscher a Vervoorts, 2012). SPI1 (PU.1) is an ETS-family lineage-specific factor that does not exhibit the directional flanking signature reported for MYC and is therefore included as a contrast factor for which the kilobase-scale signal is expected to be weaker or absent (Rothenberg et al., 2019).

3.1.2 ChIP-seq data sources

For each transcription factor, three ChIP-seq experiments are obtained from the ENCODE portal (Dunham et al., 2012), yielding nine BED files in total **[TODO: cite ENCODE portal / ENCODE3 if a more recent reference is preferred]**. Conservative IDR-thresholded narrowPeak files (Q. Li et al., 2011) are used where available; otherwise, the IDR-thresholded peak file is used. Cell-line selection follows the inclusion criterion adopted by Faltejsková et al. (2026), which retains only cell lines appearing in at least three experiments across their panel. The accessions, transcription factors, and biosamples comprising the embedded set are listed in Table ??, alongside the number of peaks supplied to the embedding pipeline. Sequence is extracted from the human reference assembly hg19 to maintain consistency with Faltejsková et al. (2026) and to permit direct comparison of per-bin readouts in the sanity check described in Section ??; this thesis does not consume any of the hg38-based annotation tracks

Tabulka 3.1: Chosen ChIP-seq experiments

TF	Cell line	ENCODE accession
MYC	GM12878	ENCFF765CKK
MYC	H1	ENCFF700CXD
MYC	MCF-7	ENCFF149BIS
CTCF	GM12878	ENCFF017XLW
CTCF	H1	ENCFF692RPA
CTCF	K562	ENCFF769AUF
SPI1	GM12878	ENCFF881ARS
SPI1	GM12878	ENCFF198SPL
SPI1	K562	ENCFF185DGL

(non-B DB, CpG islands, ENSEMBL regulatory features) used in the published study **[TODO: cite hg19 / GRCh37 (UCSC or Genome Reference Consortium)]**. BED files are downloaded programmatically from the ENCODE portal using the URL schema <https://www.encodeproject.org/files/{accession}/@@download/{accession}.bed.gz>. **[TODO: fix wrapping?]**

3.1.3 Cell-line coverage

The intended design covers the cell lines GM12878, H1, and K562 across all three transcription factors, providing a balanced grid for within-TF and across-TF comparisons. The realised design departs from this target in one respect: the MYC K562 file (ENCFF043WTJ) was not embedded within the available compute window, and the MYC MCF-7 file (ENCFF149BIS) was substituted as the third MYC experiment. The resulting cell-line coverage is therefore CTCF on GM12878, H1, K562; MYC on GM12878, H1, MCF-7; and SPI1 on GM12878 (two replicates) and K562. The interpretive consequences of this imbalance for any TF–cell-line interaction analysis are addressed in the Results and Discussion chapters.

3.1.4 Random-windows control

A random-windows control is constructed to provide a non-peak-centred reference that shares the window geometry, sequence preprocessing, and embedding pipeline of the ChIP-seq data and against which TF-centred positional structure can be contrasted. Two thousand 10 kb windows are sampled from hg19 autosomes and chromosome X, with chromosome selection weighted by usable sequence length and chromosomes Y and M excluded. Candidate windows are subjected to rejection sampling against the union of MYC and CTCF peak sets and against previously accepted control windows, ensuring the control is disjoint from those peak sets and internally non-overlapping. SPI1 peaks are not included in the rejection set: the control was generated before SPI1 was added to the design and was not subsequently regenerated; given the small genomic footprint of the SPI1 peak set the residual chance of overlap is bounded but non-zero. A fixed random seed of 42 is used throughout.

3.1.5 Reproducibility and seeding

Stochastic elements of the pipeline are seeded explicitly to support reproducibility of intermediate quantities. A fixed random seed of 42 is applied at every sampling and stochastic-fitting site, including peak subsampling, random-windows generation, and UMAP fitting; this differs from the procedure of Faltejsková et al. (2026), in which peak subsampling is performed without a fixed seed. The full source code, configuration files, and environment-setup scripts used to produce the embedded set and the analyses reported in subsequent chapters are available at the project repository <https://github.com/TypeTwo30312/tv-thesis>. **[TODO: probably footnote the repo]**

3.2 Pipeline

This part describes the deterministic chain from ENCODE BED files to per-peak embedding tensors stored on disk. The three stages—sequence extraction, embedding extraction, and the computational environment in which they run—are each implemented as a separate Jupyter notebook in the project repository, and are reported here in the order in which they execute.

3.2.1 Sequence extraction

Window extraction reads an ENCODE narrowPeak file and outputs a per-peak record containing the peak coordinates and a fixed-length DNA sequence centred on the binding site. The 10 kb window length is chosen to match the ± 5000 bp range over which Faltejsková et al. (2026) report statistically significant compositional structure around in vivo binding sites. The peak midpoint is used as the binding-site proxy: for the ENCODE narrowPeak files inspected in this thesis, the reported summit coincides with the midpoint of the peak interval (CTCF GM12878 peaks are uniformly ~ 356 bp wide, MYC GM12878 peaks ~ 390 bp, MYC H1 ~ 264 bp), and the midpoint convention matches that used by Faltejsková et al. (2026). Peaks whose 10 kb window would extend past a chromosome boundary are dropped rather than padded, since padding with non-biological characters would introduce a fixed-position bias into any subsequent positional analysis. Non-ACGT characters in the extracted sequence are masked to N at the extraction stage; the analysis-stage filtering of windows containing fully-N 50 bp bins is described in Part 3 (Section ??). **[TODO: adjust ?? when Part 3 is drafted]** For each BED file, peaks are uniformly subsampled to a maximum of 10 000 (all peaks are retained if fewer are available), matching the MAX_SIZE_SAMPLED parameter used by Faltejsková et al. (2026) but with a fixed random seed of 42 throughout. Each output row carries the columns peak_id, chr, start, end, center, and sequence, and is written as a gzip-compressed CSV. The ACCESSION__TF__BIOSAMPLE naming convention used throughout the pipeline is preserved from the published source code released alongside Faltejsková et al. (2026), so that the per-bin feature-extraction scripts from that work remain directly applicable to the sanity check reported in Part 3 (Section ??). **[TODO: adjust ?? when Part 3 is drafted]**

3.2.2 Embedding extraction

Embedding extraction is performed with the Evo 2 7B checkpoint released by Brix et al. (2026); the architecture and pretraining objective are described in the background chapter (Section ??). **[TODO: adjust ?? to the actual background-chapter label]** The 7B family is used because it runs natively in bfloat16 on Ampere-class hardware and does not require Transformer Engine or FP8 support, which are needed for the 20B and 40B variants and are unavailable on the GPUs accessible through the CERIT-SC cluster used in this work. **[TODO: not true!! fix, reasoning]** Within the 7B family, the 1 M-context variant (evo2_7b) is selected over the 8 kb-context base variant (evo2_7b_base) because the chosen 10 kb window exceeds the latter's context length. A single intermediate-layer embedding is extracted per token from the layer blocks.28.mlp.13; intermediate layers are recommended over the final layer for representation learning because the final layer is specialised to the next-token prediction objective, and blocks.28.mlp.13 is the layer used by the exon-classifier example in the official Evo 2 repository (Brix et al., 2026). **[TODO: either run a comparison or suggest it in discussion]** Each 10 kb sequence is tokenised under the Evo 2 byte-level scheme into a (1, 10000) integer tensor (one token per nucleotide), passed through the model in a single forward pass on one GPU, and the resulting (1, 10000, 4096) bfloat16 activation tensor is reshaped into 200 non-overlapping 50 bp bins and averaged within each bin to yield a (200, 4096) representation per peak, which is cast to fp16 before writing. The 50 bp bin width matches the k -mer resolution adopted by Faltejsková et al. (2026) so that per-bin readouts are directly comparable; non-overlapping bins are used in place of their 25 bp stride because each bin already integrates 50 input positions of the same forward pass and stride overlap would not contribute additional information. Unlike the strictly local hand-engineered features used by Faltejsková et al. (2026), each binned embedding has the full 10 kb window in its causal receptive field via the autoregressive forward pass, and so reflects model-internal aggregation of context up to that point rather than a fixed-window feature of the sequence itself. A streaming-write strategy based on `numpy.memmap` is used for the per-file accumulator together with a checkpoint every 500 peaks, because retaining all per-peak tensors in memory before writing exceeds the per-pod RAM allocation on the cluster for the larger BED files. The output of this stage is, per BED file, a single .npz archive containing the $(n_{\text{peaks}}, 200, 4096)$ fp16 array together with a .parquet sidecar carrying the peak_id column and BED-derived metadata in the same row order. Embedding extraction was performed on a single NVIDIA A40 GPU (46 GB VRAM) with peak allocation of 19.17 GB at batch size 1, at an observed throughput of approximately 0.5 peaks per second; the embedded set comprises the 9 ChIP-seq files of Part 1 plus the random-windows control of Section 3.1.4, totalling 96.9 GB of compressed embeddings on disk.

3.2.3 Computational environment

The embedding stage runs on the CERIT-SC JupyterHub platform under the NVIDIA PyTorch 2.5.0 container image, which provides a Python 3.10, CUDA 12.6, and Ubuntu 22.04 base; a project-specific Python 3.12 virtual environment is layered on top, installed via uv into the persistent home directory and pinning torch 2.7.1+cu128, flash-attn 2.8.0, pos

and `evo2`. A separate CPU-only environment is used for the analyses reported in Part 3, isolating the heavy GPU stack from sessions that do not require it and pinning `numpy`, `polars`, `scikit-learn`, and `umap-learn` alongside the standard scientific Python packages. Both environments are reproduced by setup scripts (`setup_evo2_env.sh`, `setup_exploration` **[TODO: nope! single evo2 environment, no setup scripts]** maintained alongside the source code, and the full code base, configuration files, and notebooks are available at the project repository¹.

3.3 Analyses

¹<https://github.com/TypeTwo30312/tv-thesis>

Druhá kapitola s matematikou $\int f(x) dx$ v názvu

$$\int f(x) \mathrm{d}x \quad (\text{rovnice})$$
$$\iint f(x) \mathrm{d}x \quad (4.1)$$

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consecetur a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consecetur. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu

nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus.

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetur odio sem sed wisi.

Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetur eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetur tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo.

Aliquam lectus. Vivamus leo. Quisque ornare tellus ullamcorper nulla. Mauris porttitor pharetra tortor. Sed fringilla justo sed mauris. Mauris tellus. Sed non leo. Nullam elementum, magna in cursus sodales, augue est scelerisque sapien, venenatis congue nulla arcu et pede. Ut suscipit enim vel sapien. Donec congue. Maecenas urna mi, suscipit in, placerat ut, vestibulum ut, massa. Fusce ultrices nulla et nisl.

Etiam ac leo a risus tristique nonummy. Donec dignissim tincidunt nulla. Vestibulum rhoncus molestie odio. Sed lobortis, justo et pretium lobortis, mauris turpis condimentum augue, nec ultricies nibh arcu pretium enim. Nunc purus neque, placerat id, imperdiet sed, pellentesque nec, nisl. Vestibulum imperdiet neque non sem accumsan laoreet. In hac habitasse platea dictumst. Etiam condimentum facilisis libero. Suspendisse in elit quis nisl aliquam dapibus. Pellentesque auctor sapien. Sed egestas sapien nec lectus. Pellentesque vel dui vel neque bibendum viverra. Aliquam porttitor nisl nec pede. Proin mattis libero vel turpis. Donec rutrum mauris et libero. Proin euismod porta felis. Nam lobortis, metus quis elementum commodo, nunc lectus elementum mauris, eget vulputate ligula tellus eu neque. Vivamus eu dolor. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Aenean nonummy turpis id odio. Integer euismod imperdiet turpis. Ut nec leo nec diam imperdiet lacinia. Etiam eget lacus eget mi ultricies posuere. In placerat tristique tortor. Sed porta vestibulum metus. Nulla iaculis sollicitudin pede. Fusce luctus tellus in dolor. Curabitur auctor velit a sem. Morbi sapien. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Donec adipiscing urna vehicula nunc. Sed ornare leo in leo. In rhoncus leo ut dui. Aenean dolor quam, volutpat nec, fringilla id, consectetur vel, pede.

Nulla malesuada risus ut urna. Aenean pretium velit sit amet metus. Duis iaculis. In

hac habitasse platea dictumst. Nullam molestie turpis eget nisl. Duis a massa id pede dapibus ultricies. Sed eu leo. In at mauris sit amet tortor bibendum varius. Phasellus justo risus, posuere in, sagittis ac, varius vel, tortor. Quisque id enim. Phasellus consequat, libero pretium nonummy fringilla, tortor lacus vestibulum nunc, ut rhoncus ligula neque id justo. Nullam accumsan euismod nunc. Proin vitae ipsum ac metus dictum tempus. Nam ut wisi. Quisque tortor felis, interdum ac, sodales a, semper a, sem. Curabitur in velit sit amet dui tristique sodales. Vivamus mauris pede, lacinia eget, pellentesque quis, scelerisque eu, est. Aliquam risus. Quisque bibendum pede eu dolor.

Donec tempus neque vitae est. Aenean egestas odio sed risus ullamcorper ullamcorper. Sed in nulla a tortor tincidunt egestas. Nam sapien tortor, elementum sit amet, aliquam in, porttitor faucibus, enim. Nullam congue suscipit nibh. Quisque convallis. Praesent arcu nibh, vehicula eget, accumsan eu, tincidunt a, nibh. Suspendisse vulputate, tortor quis adipiscing viverra, lacus nibh dignissim tellus, eu suscipit risus ante fringilla diam. Quisque a libero vel pede imperdiet aliquet. Pellentesque nunc nibh, eleifend a, consequat consequat, hendrerit nec, diam. Sed urna. Maecenas laoreet eleifend neque. Vivamus purus odio, eleifend non, iaculis a, ultrices sit amet, urna. Mauris faucibus odio vitae risus. In nisl. Praesent purus. Integer iaculis, sem eu egestas lacinia, lacus pede scelerisque augue, in ullamcorper dolor eros ac lacus. Nunc in libero.

Fusce suscipit cursus sem. Vivamus risus mi, egestas ac, imperdiet varius, faucibus quis, leo. Aenean tincidunt. Donec suscipit. Cras id justo quis nibh scelerisque dignissim. Aliquam sagittis elementum dolor. Aenean consectetur justo in pede. Curabitur ullamcorper ligula nec orci. Aliquam purus turpis, aliquam id, ornare vitae, porttitor non, wisi. Maecenas luctus porta lorem. Donec vitae ligula eu ante pretium varius. Proin tortor metus, convallis et, hendrerit non, scelerisque in, urna. Cras quis libero eu ligula bibendum tempor. Vivamus tellus quam, malesuada eu, tempus sed, tempor sed, velit. Donec lacinia auctor libero.

Praesent sed neque id pede mollis rutrum. Vestibulum iaculis risus. Pellentesque lacus. Ut quis nunc sed odio malesuada egestas. Duis a magna sit amet ligula tristique pretium. Ut pharetra. Vestibulum imperdiet magna nec wisi. Mauris convallis. Sed accumsan sollicitudin massa. Sed id enim. Nunc pede enim, lacinia ut, pulvinar quis, suscipit semper, elit. Cras accumsan erat vitae enim. Cras sollicitudin. Vestibulum rutrum blandit massa.

Sed gravida lectus ut purus. Morbi laoreet magna. Pellentesque eu wisi. Proin turpis. Integer sollicitudin augue nec dui. Fusce lectus. Vivamus faucibus nulla nec lacus. Integer diam. Pellentesque sodales, enim feugiat cursus volutpat, sem mauris dignissim mauris, quis consequat sem est fermentum ligula. Nullam justo lectus, condimentum sit amet, posuere a, fringilla mollis, felis. Morbi nulla nibh, pellentesque at, nonummy eu, sollicitudin nec, ipsum. Cras neque. Nunc augue. Nullam vitae quam id quam pulvinar blandit. Nunc sit amet orci. Aliquam erat elit, pharetra nec, aliquet a, gravida in, mi. Quisque urna enim, viverra quis, suscipit quis, tincidunt ut, sapien. Cras placerat consequat sem. Curabitur ac diam. Curabitur diam tortor, mollis et, viverra ac, tempus vel, metus.

Curabitur ac lorem. Vivamus non justo in dui mattis posuere. Etiam accumsan ligula id pede. Maecenas tincidunt diam nec velit. Praesent convallis sapien ac est. Aliquam ullamcorper euismod nulla. Integer mollis enim vel tortor. Nulla sodales placerat nunc.

Sed tempus rutrum wisi. Duis accumsan gravida purus. Nunc nunc. Etiam facilisis dui eu sem. Vestibulum semper. Praesent eu eros. Vestibulum tellus nisl, dapibus id, vestibulum sit amet, placerat ac, mauris. Maecenas et elit ut erat placerat dictum. Nam feugiat, turpis et sodales volutpat, wisi quam rhoncus neque, vitae aliquam ipsum sapien vel enim. Maecenas suscipit cursus mi.

4.1 Podkapitola

Quisque facilisis auctor sapien. Pellentesque gravida hendrerit lectus. Mauris rutrum sodales sapien. Fusce hendrerit sem vel lorem. Integer pellentesque massa vel augue. Integer elit tortor, feugiat quis, sagittis et, ornare non, lacus. Vestibulum posuere pellentesque eros. Quisque venenatis ipsum dictum nulla. Aliquam quis quam non metus eleifend interdum. Nam eget sapien ac mauris malesuada adipiscing. Etiam eleifend neque sed quam. Nulla facilisi. Proin a ligula. Sed id dui eu nibh egestas tincidunt. Suspendisse arcu.

Maecenas dui. Aliquam volutpat auctor lorem. Cras placerat est vitae lectus. Curabitur massa lectus, rutrum euismod, dignissim ut, dapibus a, odio. Ut eros erat, vulputate ut, interdum non, porta eu, erat. Cras fermentum, felis in porta congue, velit leo facilisis odio, vitae consectetur lorem quam vitae orci. Sed ultrices, pede eu placerat auctor, ante ligula rutrum tellus, vel posuere nibh lacus nec nibh. Maecenas laoreet dolor at enim. Donec molestie dolor nec metus. Vestibulum libero. Sed quis erat. Sed tristique. Duis pede leo, fermentum quis, consectetur eget, vulputate sit amet, erat.

Donec vitae velit. Suspendisse porta fermentum mauris. Ut vel nunc non mauris pharetra varius. Duis consequat libero quis urna. Maecenas at ante. Vivamus varius, wisi sed egestas tristique, odio wisi luctus nulla, lobortis dictum dolor ligula in lacus. Vivamus aliquam, urna sed interdum porttitor, metus orci interdum odio, sit amet euismod lectus felis et leo. Praesent ac wisi. Nam suscipit vestibulum sem. Praesent eu ipsum vitae pede cursus venenatis. Duis sed odio. Vestibulum eleifend. Nulla ut massa. Proin rutrum mattis sapien. Curabitur dictum gravida ante.

Phasellus placerat vulputate quam. Maecenas at tellus. Pellentesque neque diam, dignissim ac, venenatis vitae, consequat ut, lacus. Nam nibh. Vestibulum fringilla arcu mollis arcu. Sed et turpis. Donec sem tellus, volutpat et, varius eu, commodo sed, lectus. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Quisque enim arcu, suscipit nec, tempus at, imperdiet vel, metus. Morbi volutpat purus at erat. Donec dignissim, sem id semper tempus, nibh massa eleifend turpis, sed pellentesque wisi purus sed libero. Nullam lobortis tortor vel risus. Pellentesque consequat nulla eu tellus. Donec velit. Aliquam fermentum, wisi ac rhoncus iaculis, tellus nunc malesuada orci, quis volutpat dui magna id mi. Nunc vel ante. Duis vitae lacus. Cras nec ipsum.

Závěr

[illegible][illegible]

Quisque facilisis auctor sapien. Pellentesque gravida hendrerit lectus. Mauris rutrum sodales sapien. Fusce hendrerit sem vel lorem. Integer pellentesque massa vel augue. Integer elit tortor, feugiat quis, sagittis et, ornare non, lacus. Vestibulum posuere pellentesque eros. Quisque venenatis ipsum dictum nulla. Aliquam quis quam non metus eleifend interdum. Nam eget sapien ac mauris malesuada adipiscing. Etiam eleifend neque sed quam. Nulla facilisi. Proin a ligula. Sed id dui eu nibh egestas tincidunt. Suspendisse arcu.

Maecenas dui. Aliquam volutpat auctor lorem. Cras placerat est vitae lectus. Curabitur massa lectus, rutrum euismod, dignissim ut, dapibus a, odio. Ut eros erat, vulputate ut, interdum non, porta eu, erat. Cras fermentum, felis in porta congue, velit leo facilisis odio, vitae consectetur lorem quam vitae orci. Sed ultrices, pede eu placerat auctor, ante ligula rutrum tellus, vel posuere nibh lacus nec nibh. Maecenas laoreet dolor at enim. Donec molestie dolor nec metus. Vestibulum libero. Sed quis erat. Sed tristique. Duis pede leo, fermentum quis, consectetur eget, vulputate sit amet, erat.

Donec vitae velit. Suspendisse porta fermentum mauris. Ut vel nunc non mauris pharetra varius. Duis consequat libero quis urna. Maecenas at ante. Vivamus varius, wisi sed egestas tristique, odio wisi luctus nulla, lobortis dictum dolor ligula in lacus. Vivamus aliquam, urna sed interdum porttitor, metus orci interdum odio, sit amet euismod lectus felis et leo. Praesent ac wisi. Nam suscipit vestibulum sem. Praesent eu ipsum vitae pede cursus venenatis. Duis sed odio. Vestibulum eleifend. Nulla ut massa. Proin rutrum mattis sapien. Curabitur dictum gravida ante.

Phasellus placerat vulputate quam. Maecenas at tellus. Pellentesque neque diam, dignissim ac, venenatis vitae, consequat ut, lacus. Nam nibh. Vestibulum fringilla arcu mollis arcu. Sed et turpis. Donec sem tellus, volutpat et, varius eu, commodo sed, lectus. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Quisque enim arcu, suscipit

nec, tempus at, imperdiet vel, metus. Morbi volutpat purus at erat. Donec dignissim, sem id semper tempus, nibh massa eleifend turpis, sed pellentesque wisi purus sed libero. Nullam lobortis tortor vel risus. Pellentesque consequat nulla eu tellus. Donec velit. Aliquam fermentum, wisi ac rhoncus iaculis, tellus nunc malesuada orci, quis volutpat dui magna id mi. Nunc vel ante. Duis vitae lacus. Cras nec ipsum.

Morbi nunc. Aliquam consectetur varius nulla. Phasellus eros. Cras dapibus porttitor risus. Maecenas ultrices mi sed diam. Praesent gravida velit at elit vehicula porttitor. Phasellus nisl mi, sagittis ac, pulvinar id, gravida sit amet, erat. Vestibulum est. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Curabitur id sem elementum leo rutrum hendrerit. Ut at mi. Donec tincidunt faucibus massa. Sed turpis quam, sollicitudin a, hendrerit eget, pretium ut, nisl. Duis hendrerit ligula. Nunc pulvinar congue urna.

Nunc velit. Nullam elit sapien, eleifend eu, commodo nec, semper sit amet, elit. Nulla lectus risus, condimentum ut, laoreet eget, viverra nec, odio. Proin lobortis. Curabitur dictum arcu vel wisi. Cras id nulla venenatis tortor congue ultrices. Pellentesque eget pede. Sed eleifend sagittis elit. Nam sed tellus sit amet lectus ullamcorper tristique. Mauris enim sem, tristique eu, accumsan at, scelerisque vulputate, neque. Quisque lacus. Donec et ipsum sit amet elit nonummy aliquet. Sed viverra nisl at sem. Nam diam. Mauris ut dolor. Curabitur ornare tortor cursus velit.

Morbi tincidunt posuere arcu. Cras venenatis est vitae dolor. Vivamus scelerisque semper mi. Donec ipsum arcu, consequat scelerisque, viverra id, dictum at, metus. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut pede sem, tempus ut, porttitor bibendum, molestie eu, elit. Suspendisse potenti. Sed id lectus sit amet purus faucibus vehicula. Praesent sed sem non dui pharetra interdum. Nam viverra ultrices magna.

Aenean laoreet aliquam orci. Nunc interdum elementum urna. Quisque erat. Nullam tempor neque. Maecenas velit nibh, scelerisque a, consequat ut, viverra in, enim. Duis magna. Donec odio neque, tristique et, tincidunt eu, rhoncus ac, nunc. Mauris malesuada malesuada elit. Etiam lacus mauris, pretium vel, blandit in, ultricies id, libero. Phasellus bibendum erat ut diam. In congue imperdiet lectus.

Aenean scelerisque. Fusce pretium porttitor lorem. In hac habitasse platea dictumst. Nulla sit amet nisl at sapien egestas pretium. Nunc non tellus. Vivamus aliquet. Nam adipiscing euismod dolor. Aliquam erat volutpat. Nulla ut ipsum. Quisque tincidunt auctor augue. Nunc imperdiet ipsum eget elit. Aliquam quam leo, consectetur non, ornare sit amet, tristique quis, felis. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque interdum quam sit amet mi. Pellentesque mauris dui, dictum a, adipiscing ac, fermentum sit amet, lorem.

Ut quis wisi. Praesent quis massa. Vivamus egestas risus eget lacus. Nunc tincidunt, risus quis bibendum facilisis, lorem purus rutrum neque, nec porta tortor urna quis orci. Aenean aliquet, libero semper volutpat luctus, pede erat lacinia augue, quis rutrum sem ipsum sit amet pede. Vestibulum aliquet, nibh sed iaculis sagittis, odio dolor blandit augue, eget mollis urna tellus id tellus. Aenean aliquet aliquam nunc. Nulla ultricies justo eget orci. Phasellus tristique fermentum leo. Sed massa metus, sagittis ut, semper ut, pharetra vel, erat. Aliquam quam turpis, egestas vel, elementum in, egestas sit amet, lorem. Duis convallis, wisi sit amet mollis molestie, libero mauris porta dui, vitae aliquam arcu turpis ac sem. Aliquam aliquet dapibus metus.

Vivamus commodo eros eleifend dui. Vestibulum in leo eu erat tristique mattis. Cras

at elit. Cras pellentesque. Nullam id lacus sit amet libero aliquet hendrerit. Proin placerat, mi non elementum laoreet, eros elit tincidunt magna, a rhoncus sem arcu id odio. Nulla eget leo a leo egestas facilisis. Curabitur quis velit. Phasellus aliquam, tortor nec ornare rhoncus, purus urna posuere velit, et commodo risus tellus quis tellus. Vivamus leo turpis, tempus sit amet, tristique vitae, laoreet quis, odio. Proin scelerisque bibendum ipsum. Etiam nisl. Praesent vel dolor. Pellentesque vel magna. Curabitur urna. Vivamus congue urna in velit. Etiam ullamcorper elementum dui. Praesent non urna. Sed placerat quam non mi. Pellentesque diam magna, ultricies eget, ultrices placerat, adipiscing rutrum, sem.

Morbi sem. Nulla facilisi. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Nulla facilisi. Morbi sagittis ultrices libero. Praesent eu ligula sed sapien auctor sagittis. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Donec vel nunc. Nunc fermentum, lacus id aliquam porta, dui tortor euismod eros, vel molestie ipsum purus eu lacus. Vivamus pede arcu, euismod ac, tempus id, pretium et, lacus. Curabitur sodales dapibus urna. Nunc eu sapien. Donec eget nunc a pede dictum pretium. Proin mauris. Vivamus luctus libero vel nibh.

Fusce tristique risus id wisi. Integer molestie massa id sem. Vestibulum vel dolor. Pellentesque vel urna vel risus ultricies elementum. Quisque sapien urna, blandit nec, iaculis ac, viverra in, odio. In hac habitasse platea dictumst. Morbi neque lacus, convallis vitae, commodo ac, fermentum eu, velit. Sed in orci. In fringilla turpis non arcu. Donec in ante. Phasellus tempor feugiat velit. Aenean varius massa non turpis. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae;

Aliquam tortor. Morbi ipsum massa, imperdiet non, consectetur vel, feugiat vel, lorem. Quisque eget lorem nec elit malesuada vestibulum. Quisque sollicitudin ipsum vel sem. Nulla enim. Proin nonummy felis vitae felis. Nullam pellentesque. Duis rutrum feugiat felis. Mauris vel pede sed libero tincidunt mollis. Phasellus sed urna rhoncus diam euismod bibendum. Phasellus sed nisl. Integer condimentum justo id orci iaculis varius. Quisque et lacus. Phasellus elementum, justo at dignissim auctor, wisi odio lobortis arcu, sed sollicitudin felis felis eu neque. Praesent at lacus.

Vivamus sit amet pede. Duis interdum, nunc eget rutrum dignissim, nisl diam luctus leo, et tincidunt velit nisl id tellus. In lorem tellus, aliquet vitae, porta in, aliquet sed, lectus. Phasellus sodales. Ut varius scelerisque erat. In vel nibh eu eros imperdiet rutrum. Donec ac odio nec neque vulputate suscipit. Nam nec magna. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Nullam porta, odio et sagittis iaculis, wisi neque fringilla sapien, vel commodo lorem lorem id elit. Ut sem lectus, scelerisque eget, placerat et, tincidunt scelerisque, ligula. Pellentesque non orci.

Etiam vel ipsum. Morbi facilisis vestibulum nisl. Praesent cursus laoreet felis. Integer adipiscing pretium orci. Nulla facilisi. Quisque posuere bibendum purus. Nulla quam mauris, cursus eget, convallis ac, molestie non, enim. Aliquam congue. Quisque sagittis nonummy sapien. Proin molestie sem vitae urna. Maecenas lorem. Vivamus viverra consequat enim.

Bibliography

- [1] Ariel Afek and David B. Lukatsky. *Genome-Wide Organization of Eukaryotic Pre-Initiation Complex Is Influenced by Nonconsensus Protein-DNA Binding*. <https://arxiv.org/abs/1303.0103>. Mar. 2013. DOI: [10.1016/j.bpj.2013.01.038](https://doi.org/10.1016/j.bpj.2013.01.038). (Visited on 05/04/2026).
- [2] Babak Alipanahi et al. „Predicting the Sequence Specificities of DNA- and RNA-binding Proteins by Deep Learning“. In: *Nature Biotechnology* 33.8 (Aug. 2015), pp. 831–838. ISSN: 1546-1696. DOI: [10.1038/nbt.3300](https://doi.org/10.1038/nbt.3300). (Visited on 05/08/2026).
- [3] Timothy L. Bailey and Charles Elkan. „Unsupervised Learning of Multiple Motifs in Biopolymers Using Expectation Maximization“. In: *Machine Learning* 21.1 (Oct. 1995), pp. 51–80. ISSN: 1573-0565. DOI: [10.1007/BF00993379](https://doi.org/10.1007/BF00993379). (Visited on 05/04/2026).
- [4] Timothy L. Bailey, James Johnson, et al. „The MEME Suite“. In: *Nucleic Acids Research* 43.W1 (July 2015), W39–W49. ISSN: 0305-1048. DOI: [10.1093/nar/gkv416](https://doi.org/10.1093/nar/gkv416). (Visited on 05/04/2026).
- [5] David R. Bentley et al. „Accurate Whole Human Genome Sequencing Using Reversible Terminator Chemistry“. In: *Nature* 456.7218 (Nov. 2008), pp. 53–59. ISSN: 1476-4687. DOI: [10.1038/nature07517](https://doi.org/10.1038/nature07517). (Visited on 05/08/2026).
- [6] Rishi Bommasani et al. *On the Opportunities and Risks of Foundation Models*. July 2022. DOI: [10.48550/arXiv.2108.07258](https://doi.org/10.48550/arXiv.2108.07258). arXiv: [2108.07258 \[cs\]](https://arxiv.org/abs/2108.07258). (Visited on 05/04/2026).
- [7] Garyk Brixi et al. „Genome Modelling and Design across All Domains of Life with Evo 2“. In: *Nature* 652.8112 (Apr. 2026), pp. 1349–1361. ISSN: 1476-4687. DOI: [10.1038/s41586-026-10176-5](https://doi.org/10.1038/s41586-026-10176-5). (Visited on 05/05/2026).
- [8] Hugo Dalla-Torre et al. „Nucleotide Transformer: Building and Evaluating Robust Foundation Models for Human Genomics“. In: *Nature Methods* 22.2 (Feb. 2025), pp. 287–297. ISSN: 1548-7105. DOI: [10.1038/s41592-024-02523-z](https://doi.org/10.1038/s41592-024-02523-z). (Visited on 03/17/2025).
- [9] Mikhail G Dozmorov et al. „CTCF: An R/Bioconductor Data Package of Human and Mouse CTCF Binding Sites“. In: *Bioinformatics Advances* 2.1 (Dec. 2022), vbac097. ISSN: 2635-0041. DOI: [10.1093/bioadv/vbac097](https://doi.org/10.1093/bioadv/vbac097). (Visited on 04/30/2026). ■
- [10] Iris Dror et al. „A Widespread Role of the Motif Environment in Transcription Factor Binding across Diverse Protein Families“. In: *Genome Research* 25.9 (July 2015), pp. 1268–1280. ISSN: 1088-9051, 1549-5469. DOI: [10.1101/gr.184671.114](https://doi.org/10.1101/gr.184671.114). (Visited on 04/14/2026).

- [11] Ian Dunham et al. „An Integrated Encyclopedia of DNA Elements in the Human Genome“. In: *Nature* 489.7414 (Sept. 2012), pp. 57–74. ISSN: 1476-4687. DOI: [10.1038/nature11247](https://doi.org/10.1038/nature11247). (Visited on 05/04/2026).
- [12] Kateřina Faltejsová, Josef Šulc, and Jiří Vondrášek. *Non-Consensus Flanking Sequence of Hundreds of Base Pairs around in Vivo Binding Sites: Statistical Beacons for Transcription Factor Scanning*. Mar. 2026. DOI: [10.1101/2025.05.28.656598](https://doi.org/10.1101/2025.05.28.656598). (Visited on 03/14/2026).
- [13] Charles E. Grant, Timothy L. Bailey, and William Stafford Noble. „FIMO: Scanning for Occurrences of a given Motif“. In: *Bioinformatics* 27.7 (Apr. 2011), pp. 1017–1018. ISSN: 1367-4803. DOI: [10.1093/bioinformatics/btr064](https://doi.org/10.1093/bioinformatics/btr064). (Visited on 05/04/2026).
- [14] Sven Heinz et al. „Simple Combinations of Lineage-Determining Transcription Factors Prime *Cis*-Regulatory Elements Required for Macrophage and B Cell Identities“. In: *Molecular Cell* 38.4 (May 2010), pp. 576–589. ISSN: 1097-2765. DOI: [10.1016/j.molcel.2010.05.004](https://doi.org/10.1016/j.molcel.2010.05.004). (Visited on 05/04/2026).
- [15] Yanrong Ji et al. „DNABERT: Pre-Trained Bidirectional Encoder Representations from Transformers Model for DNA-language in Genome“. In: *Bioinformatics* 37.15 (Aug. 2021), pp. 2112–2120. ISSN: 1367-4803. DOI: [10.1093/bioinformatics/btab083](https://doi.org/10.1093/bioinformatics/btab083). (Visited on 05/04/2026).
- [16] Hatice S. Kaya-Okur et al. „CUT&Tag for Efficient Epigenomic Profiling of Small Samples and Single Cells“. In: *Nature Communications* 10.1 (Apr. 2019), p. 1930. ISSN: 2041-1723. DOI: [10.1038/s41467-019-09982-5](https://doi.org/10.1038/s41467-019-09982-5). (Visited on 05/08/2026).
- [17] Samuel A. Lambert et al. „The Human Transcription Factors“. In: *Cell* 172.4 (Feb. 2018), pp. 650–665. ISSN: 0092-8674. DOI: [10.1016/j.cell.2018.01.029](https://doi.org/10.1016/j.cell.2018.01.029). (Visited on 04/17/2026).
- [18] Heng Li. *Aligning Sequence Reads, Clone Sequences and Assembly Contigs with BWA-MEM*. May 2013. DOI: [10.48550/arXiv.1303.3997](https://doi.org/10.48550/arXiv.1303.3997). arXiv: [1303.3997 \[q-bio\]](https://arxiv.org/abs/1303.3997). (Visited on 05/08/2026).
- [19] Jinsen Li, Tsu-Pei Chiu, and Remo Rohs. „Predicting DNA Structure Using a Deep Learning Method“. In: *Nature Communications* 15.1 (Feb. 2024), p. 1243. ISSN: 2041-1723. DOI: [10.1038/s41467-024-45191-5](https://doi.org/10.1038/s41467-024-45191-5). (Visited on 05/08/2026).
- [20] Qunhua Li et al. „Measuring Reproducibility of High-Throughput Experiments“. In: *The Annals of Applied Statistics* 5.3 (Sept. 2011), pp. 1752–1779. ISSN: 1932-6157, 1941-7330. DOI: [10.1214/11-A0AS466](https://doi.org/10.1214/11-A0AS466). (Visited on 05/04/2026).
- [21] N. M. Luscombe, R. A. Laskowski, and J. M. Thornton. „Amino Acid-Base Interactions: A Three-Dimensional Analysis of Protein-DNA Interactions at an Atomic Level“. In: *Nucleic Acids Research* 29.13 (July 2001), pp. 2860–2874. ISSN: 1362-4962. DOI: [10.1093/nar/29.13.2860](https://doi.org/10.1093/nar/29.13.2860).
- [22] Bernhard Lüscher and Jörg Vervoorts. „Regulation of Gene Transcription by the Oncoprotein MYC“. In: *Gene* 494.2 (Feb. 2012), pp. 145–160. ISSN: 0378-1119. DOI: [10.1016/j.gene.2011.12.027](https://doi.org/10.1016/j.gene.2011.12.027). (Visited on 05/07/2026).

- [23] Anthony Mathelier et al. „DNA Shape Features Improve Transcription Factor Binding Site Predictions In Vivo“. In: *Cell Systems* 3.3 (Sept. 2016), 278–286.e4. ISSN: 2405-4712. DOI: [10.1016/j.cels.2016.07.001](https://doi.org/10.1016/j.cels.2016.07.001). (Visited on 04/30/2026).
- [24] Eric Nguyen, Michael Poli, Matthew G. Durrant, et al. „Sequence Modeling and Design from Molecular to Genome Scale with Evo“. In: *Science* 386.6723 (Nov. 2024), eado9336. DOI: [10.1126/science.ado9336](https://doi.org/10.1126/science.ado9336). (Visited on 03/17/2025).
- [25] Eric Nguyen, Michael Poli, Marjan Faizi, et al. *HyenaDNA: Long-Range Genomic Sequence Modeling at Single Nucleotide Resolution*. Nov. 2023. DOI: [10.48550/arXiv.2306.15794](https://doi.org/10.48550/arXiv.2306.15794). arXiv: [2306.15794 \[cs\]](https://arxiv.org/abs/2306.15794). (Visited on 05/04/2026).
- [26] Chin-Tong Ong and Victor G. Corces. „CTCF: An Architectural Protein Bridging Genome Topology and Function“. In: *Nature reviews. Genetics* 15.4 (Apr. 2014), pp. 234–246. ISSN: 1471-0056. DOI: [10.1038/nrg3663](https://doi.org/10.1038/nrg3663). (Visited on 05/07/2026).
- [27] Damla Ovek Baydar et al. „JASPAR 2026: Expansion of Transcription Factor Binding Profiles and Integration of Deep Learning Models“. In: *Nucleic Acids Research* 54.D1 (Jan. 2026), pp. D184–D193. ISSN: 1362-4962. DOI: [10.1093/nar/gkaf1209](https://doi.org/10.1093/nar/gkaf1209).
- [28] Peter J. Park. „ChIP–Seq: Advantages and Challenges of a Maturing Technology“. In: *Nature Reviews Genetics* 10.10 (Oct. 2009), pp. 669–680. ISSN: 1471-0064. DOI: [10.1038/nrg2641](https://doi.org/10.1038/nrg2641). (Visited on 05/08/2026).
- [29] Remo Rohs et al. „The Role of DNA Shape in Protein-DNA Recognition“. In: *Nature* 461.7268 (Oct. 2009), pp. 1248–1253. ISSN: 0028-0836. DOI: [10.1038/nature08473](https://doi.org/10.1038/nature08473). (Visited on 04/30/2026).
- [30] Ellen V. Rothenberg, Hiroyuki Hosokawa, and Jonas Ungerback. „Mechanisms of Action of Hematopoietic Transcription Factor PU.1 in Initiation of T-Cell Development“. In: *Frontiers in Immunology* 10 (Feb. 2019). ISSN: 1664-3224. DOI: [10.3389/fimmu.2019.00228](https://doi.org/10.3389/fimmu.2019.00228). (Visited on 05/07/2026).
- [31] N C Seeman, J M Rosenberg, and A Rich. „Sequence-Specific Recognition of Double Helical Nucleic Acids by Proteins.“ In: *Proceedings of the National Academy of Sciences* 73.3 (Mar. 1976), pp. 804–808. DOI: [10.1073/pnas.73.3.804](https://doi.org/10.1073/pnas.73.3.804). (Visited on 04/30/2026).
- [32] Itamar Sela and David B. Lukatsky. „DNA Sequence Correlations Shape Nonspecific Transcription Factor-DNA Binding Affinity“. In: *Biophysical Journal* 101.1 (July 2011), pp. 160–166. ISSN: 0006-3495, 1542-0086. DOI: [10.1016/j.bpj.2011.04.037](https://doi.org/10.1016/j.bpj.2011.04.037). (Visited on 05/04/2026).
- [33] Thomas D. Schneider and R. Michael Stephens. „Sequence Logos: A New Way to Display Consensus Sequences“. In: *Nucleic Acids Research* 18.20 (Oct. 1990), pp. 6097–6100. ISSN: 0305-1048. DOI: [10.1093/nar/18.20.6097](https://doi.org/10.1093/nar/18.20.6097). (Visited on 05/08/2026).
- [34] Matthew Slattery et al. „Absence of a Simple Code: How Transcription Factors Read the Genome“. In: *Trends in biochemical sciences* 39.9 (Sept. 2014), pp. 381–399. ISSN: 0968-0004. DOI: [10.1016/j.tibs.2014.07.002](https://doi.org/10.1016/j.tibs.2014.07.002). (Visited on 04/30/2026).

- [35] Can Sönmezer et al. „Molecular Co-Occupancy Identifies Transcription Factor Binding Cooperativity in Vivo“. In: *Molecular cell* 81.2 (Jan. 2021), 255–267.e6. ISSN: 1097-2765. DOI: [10.1016/j.molcel.2020.11.015](https://doi.org/10.1016/j.molcel.2020.11.015). (Visited on 05/08/2026).
- [36] Gary D. Stormo. „DNA Binding Sites: Representation and Discovery“. In: *Bioinformatics* 16.1 (Jan. 2000), pp. 16–23. ISSN: 1367-4811, 1367-4803. DOI: [10.1093/bioinformatics/16.1.16](https://doi.org/10.1093/bioinformatics/16.1.16). (Visited on 04/24/2026).
- [37] Robert E. Thurman et al. „The Accessible Chromatin Landscape of the Human Genome“. In: *Nature* 489.7414 (Sept. 2012), pp. 75–82. ISSN: 1476-4687. DOI: [10.1038/nature11232](https://doi.org/10.1038/nature11232). (Visited on 05/04/2026).
- [38] Ashish Vaswani et al. „Attention Is All You Need“. In: *Proceedings of the 31st International Conference on Neural Information Processing Systems*. NIPS’17. Red Hook, NY, USA: Curran Associates Inc., Dec. 2017, pp. 6000–6010. ISBN: 978-1-5108-6096-4. (Visited on 03/18/2025).
- [39] Ilya E Vorontsov et al. „HOCOMOCO in 2024: A Rebuild of the Curated Collection of Binding Models for Human and Mouse Transcription Factors“. In: *Nucleic Acids Research* 52.D1 (Jan. 2024), pp. D154–D163. ISSN: 0305-1048. DOI: [10.1093/nar/gkad1077](https://doi.org/10.1093/nar/gkad1077). (Visited on 05/04/2026).
- [40] Zeba Wunderlich and Leonid A. Mirny. „Different Gene Regulation Strategies Revealed by Analysis of Binding Motifs“. In: *Trends in Genetics* 25.10 (Oct. 2009), pp. 434–440. ISSN: 0168-9525. DOI: [10.1016/j.tig.2009.08.003](https://doi.org/10.1016/j.tig.2009.08.003). (Visited on 05/04/2026).
- [41] Lin Yang et al. „Transcription Factor Family-Specific DNA Shape Readout Revealed by Quantitative Specificity Models“. In: *Molecular Systems Biology* 13.2 (Feb. 2017), p. 910. ISSN: 1744-4292. DOI: [10.15252/msb.20167238](https://doi.org/10.15252/msb.20167238). (Visited on 04/30/2026).
- [42] Yong Zhang et al. „Model-Based Analysis of ChIP-Seq (MACS)“. In: *Genome Biology* 9.9 (Sept. 2008), R137. ISSN: 1474-760X. DOI: [10.1186/gb-2008-9-9-r137](https://doi.org/10.1186/gb-2008-9-9-r137). (Visited on 05/04/2026).

Appendix

Sem můžete přidat přílohu. Pokud chcete “Přílohy”, tak upravte definici záhlaví v souboru sci.muni.thesis.sty, viz příkaz \HlavickaPriloha.

Quisque facilisis auctor sapien. Pellentesque gravida hendrerit lectus. Mauris rutrum sodales sapien. Fusce hendrerit sem vel lorem. Integer pellentesque massa vel augue. Integer elit tortor, feugiat quis, sagittis et, ornare non, lacus. Vestibulum posuere pellentesque eros. Quisque venenatis ipsum dictum nulla. Aliquam quis quam non metus eleifend interdum. Nam eget sapien ac mauris malesuada adipiscing. Etiam eleifend neque sed quam. Nulla facilisi. Proin a ligula. Sed id dui eu nibh egestas tincidunt. Suspendisse arcu.

Maecenas dui. Aliquam volutpat auctor lorem. Cras placerat est vitae lectus. Curabitur massa lectus, rutrum euismod, dignissim ut, dapibus a, odio. Ut eros erat, vulputate ut, interdum non, porta eu, erat. Cras fermentum, felis in porta congue, velit leo facilisis odio, vitae consectetur lorem quam vitae orci. Sed ultrices, pede eu placerat auctor, ante ligula rutrum tellus, vel posuere nibh lacus nec nibh. Maecenas laoreet dolor at enim. Donec molestie dolor nec metus. Vestibulum libero. Sed quis erat. Sed tristique. Duis pede leo, fermentum quis, consectetur eget, vulputate sit amet, erat.

Donec vitae velit. Suspendisse porta fermentum mauris. Ut vel nunc non mauris pharetra varius. Duis consequat libero quis urna. Maecenas at ante. Vivamus varius, wisi sed egestas tristique, odio wisi luctus nulla, lobortis dictum dolor ligula in lacus. Vivamus aliquam, urna sed interdum porttitor, metus orci interdum odio, sit amet euismod lectus felis et leo. Praesent ac wisi. Nam suscipit vestibulum sem. Praesent eu ipsum vitae pede cursus venenatis. Duis sed odio. Vestibulum eleifend. Nulla ut massa. Proin rutrum mattis sapien. Curabitur dictum gravida ante.

Phasellus placerat vulputate quam. Maecenas at tellus. Pellentesque neque diam, dignissim ac, venenatis vitae, consequat ut, lacus. Nam nibh. Vestibulum fringilla arcu mollis arcu. Sed et turpis. Donec sem tellus, volutpat et, varius eu, commodo sed, lectus. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Quisque enim arcu, suscipit nec, tempus at, imperdiet vel, metus. Morbi volutpat purus at erat. Donec dignissim, sem id semper tempus, nibh massa eleifend turpis, sed pellentesque wisi purus sed libero. Nullam lobortis tortor vel risus. Pellentesque consequat nulla eu tellus. Donec velit. Aliquam fermentum, wisi ac rhoncus iaculis, tellus nunc malesuada orci, quis volutpat dui magna id mi. Nunc vel ante. Duis vitae lacus. Cras nec ipsum.

Morbi nunc. Aliquam consectetur varius nulla. Phasellus eros. Cras dapibus porttitor risus. Maecenas ultrices mi sed diam. Praesent gravida velit at elit vehicula porttitor. Phasellus nisl mi, sagittis ac, pulvinar id, gravida sit amet, erat. Vestibulum est. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Curabitur id sem elementum leo ru-

trum hendrerit. Ut at mi. Donec tincidunt faucibus massa. Sed turpis quam, sollicitudin a, hendrerit eget, pretium ut, nisl. Duis hendrerit ligula. Nunc pulvinar congue urna.

Nunc velit. Nullam elit sapien, eleifend eu, commodo nec, semper sit amet, elit. Nulla lectus risus, condimentum ut, laoreet eget, viverra nec, odio. Proin lobortis. Curabitur dictum arcu vel wisi. Cras id nulla venenatis tortor congue ultrices. Pellentesque eget pede. Sed eleifend sagittis elit. Nam sed tellus sit amet lectus ullamcorper tristique. Mauris enim sem, tristique eu, accumsan at, scelerisque vulputate, neque. Quisque lacus. Donec et ipsum sit amet elit nonummy aliquet. Sed viverra nisl at sem. Nam diam. Mauris ut dolor. Curabitur ornare tortor cursus velit.

Morbi tincidunt posuere arcu. Cras venenatis est vitae dolor. Vivamus scelerisque semper mi. Donec ipsum arcu, consequat scelerisque, viverra id, dictum at, metus. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut pede sem, tempus ut, porttitor bibendum, molestie eu, elit. Suspendisse potenti. Sed id lectus sit amet purus faucibus vehicula. Praesent sed sem non dui pharetra interdum. Nam viverra ultrices magna.

Aenean laoreet aliquam orci. Nunc interdum elementum urna. Quisque erat. Nullam tempor neque. Maecenas velit nibh, scelerisque a, consequat ut, viverra in, enim. Duis magna. Donec odio neque, tristique et, tincidunt eu, rhoncus ac, nunc. Mauris malesuada malesuada elit. Etiam lacus mauris, pretium vel, blandit in, ultricies id, libero. Phasellus bibendum erat ut diam. In congue imperdiet lectus.

Aenean scelerisque. Fusce pretium porttitor lorem. In hac habitasse platea dictumst. Nulla sit amet nisl at sapien egestas pretium. Nunc non tellus. Vivamus aliquet. Nam adipiscing euismod dolor. Aliquam erat volutpat. Nulla ut ipsum. Quisque tincidunt auctor augue. Nunc imperdiet ipsum eget elit. Aliquam quam leo, consectetur non, ornare sit amet, tristique quis, felis. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque interdum quam sit amet mi. Pellentesque mauris dui, dictum a, adipiscing ac, fermentum sit amet, lorem.

Ut quis wisi. Praesent quis massa. Vivamus egestas risus eget lacus. Nunc tincidunt, risus quis bibendum facilisis, lorem purus rutrum neque, nec porta tortor urna quis orci. Aenean aliquet, libero semper volutpat luctus, pede erat lacinia augue, quis rutrum sem ipsum sit amet pede. Vestibulum aliquet, nibh sed iaculis sagittis, odio dolor blandit augue, eget mollis urna tellus id tellus. Aenean aliquet aliquam nunc. Nulla ultricies justo eget orci. Phasellus tristique fermentum leo. Sed massa metus, sagittis ut, semper ut, pharetra vel, erat. Aliquam quam turpis, egestas vel, elementum in, egestas sit amet, lorem. Duis convallis, wisi sit amet mollis molestie, libero mauris porta dui, vitae aliquam arcu turpis ac sem. Aliquam aliquet dapibus metus.

Vivamus commodo eros eleifend dui. Vestibulum in leo eu erat tristique mattis. Cras at elit. Cras pellentesque. Nullam id lacus sit amet libero aliquet hendrerit. Proin placerat, mi non elementum laoreet, eros elit tincidunt magna, a rhoncus sem arcu id odio. Nulla eget leo a leo egestas facilisis. Curabitur quis velit. Phasellus aliquam, tortor nec ornare rhoncus, purus urna posuere velit, et commodo risus tellus quis tellus. Vivamus leo turpis, tempus sit amet, tristique vitae, laoreet quis, odio. Proin scelerisque bibendum ipsum. Etiam nisl. Praesent vel dolor. Pellentesque vel magna. Curabitur urna. Vivamus congue urna in velit. Etiam ullamcorper elementum dui. Praesent non urna. Sed placerat quam non mi. Pellentesque diam magna, ultricies eget, ultrices placerat, adipiscing rutrum, sem.

Morbi sem. Nulla facilisi. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Nulla facilisi. Morbi sagittis ultrices libero. Praesent eu ligula sed sapien auctor sagittis. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Donec vel nunc. Nunc fermentum, lacus id aliquam porta, dui tortor euismod eros, vel molestie ipsum purus eu lacus. Vivamus pede arcu, euismod ac, tempus id, pretium et, lacus. Curabitur sodales dapibus urna. Nunc eu sapien. Donec eget nunc a pede dictum pretium. Proin mauris. Vivamus luctus libero vel nibh.

Fusce tristique risus id wisi. Integer molestie massa id sem. Vestibulum vel dolor. Pellentesque vel urna vel risus ultricies elementum. Quisque sapien urna, blandit nec, iaculis ac, viverra in, odio. In hac habitasse platea dictumst. Morbi neque lacus, convallis vitae, commodo ac, fermentum eu, velit. Sed in orci. In fringilla turpis non arcu. Donec in ante. Phasellus tempor feugiat velit. Aenean varius massa non turpis. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae;

Aliquam tortor. Morbi ipsum massa, imperdiet non, consectetur vel, feugiat vel, lorem. Quisque eget lorem nec elit malesuada vestibulum. Quisque sollicitudin ipsum vel sem. Nulla enim. Proin nonummy felis vitae felis. Nullam pellentesque. Duis rutrum feugiat felis. Mauris vel pede sed libero tincidunt mollis. Phasellus sed urna rhoncus diam euismod bibendum. Phasellus sed nisl. Integer condimentum justo id orci iaculis varius. Quisque et lacus. Phasellus elementum, justo at dignissim auctor, wisi odio lobortis arcu, sed sollicitudin felis felis eu neque. Praesent at lacus.

Vivamus sit amet pede. Duis interdum, nunc eget rutrum dignissim, nisl diam luctus leo, et tincidunt velit nisl id tellus. In lorem tellus, aliquet vitae, porta in, aliquet sed, lectus. Phasellus sodales. Ut varius scelerisque erat. In vel nibh eu eros imperdiet rutrum. Donec ac odio nec neque vulputate suscipit. Nam nec magna. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Nullam porta, odio et sagittis iaculis, wisi neque fringilla sapien, vel commodo lorem lorem id elit. Ut sem lectus, scelerisque eget, placerat et, tincidunt scelerisque, ligula. Pellentesque non orci.

Etiam vel ipsum. Morbi facilisis vestibulum nisl. Praesent cursus laoreet felis. Integer adipiscing pretium orci. Nulla facilisi. Quisque posuere bibendum purus. Nulla quam mauris, cursus eget, convallis ac, molestie non, enim. Aliquam congue. Quisque sagittis nonummy sapien. Proin molestie sem vitae urna. Maecenas lorem. Vivamus viverra consequat enim.

