RANDEVU: Deterministic Schelling Points for Decentralized Temporal Coordination

TypicalHog

Independent Research · github.com/TypicalHog/randevu

March 2026

Abstract

This paper presents RANDEVU, a deterministic coordination algorithm that generates universally computable Schelling points in time for any string-representable object. By computing `blake3::keyed_hash(key=DATE, data=OBJECT)` *and counting leading zero bits, RANDEVU assigns a daily significance score — the Rendezvous Value (RDV) — that follows a geometric probability distribution. Any two parties running the same computation, anywhere in the world, with no communication channel, will arrive at identical results. We formalize the mathematical properties, model adoption dynamics through network-effect theory, analyze the system through the lens of game theory and coordination economics, enumerate high-impact application domains, and offer predictive models for long-term cultural effects. We argue that RANDEVU represents a novel primitive in the design space of decentralized coordination protocols — one whose zero-infrastructure property and mathematical elegance position it for eventual integration into the connective fabric of digital culture.*

Keywords: Schelling points, decentralized coordination, BLAKE3, cryptographic hashing, temporal synchronization, network effects, long-tail content

1. Introduction

Human coordination is expensive. Whether scheduling a meeting, planning a protest, organizing a game night, or synchronizing a global product launch, the act of getting people to do the same thing at the same time requires infrastructure: calendars, group chats, event platforms, social media campaigns, and — invariably — someone willing to do the organizational labor. This infrastructure is fragile. Platforms shut down. Organizers burn out. Communities fragment across walled gardens. When the infrastructure fails, coordination collapses — even when the underlying desire to coordinate persists.

The problem intensifies at scale and in the long tail. Mainstream events command sufficient attention to sustain traditional coordination. But what about the 15,000th most popular multiplayer game? The cult film with 2,000 devoted fans scattered across 40 countries? The open-source library with 300 contributors who have never met? For these cases, the overhead of coordination exceeds the capacity of any volunteer organizer, yet the latent demand for synchronous activity is real.

This paper introduces RANDEVU, a protocol that solves this problem by eliminating the need for coordination infrastructure entirely. RANDEVU generates deterministic, universally computable temporal Schelling points for any object. Two strangers on opposite sides of the Earth, with no shared communication channel, can independently discover that today is a mathematically significant day for a given object — and both act on that signal. No server processes the computation. No database stores the schedule. No account authenticates the user. The algorithm is the only infrastructure, and it runs on any device capable of performing a BLAKE3 hash.

We situate RANDEVU within the theoretical framework of Schelling focal points (Schelling, 1960), model its adoption dynamics using network-effect theory, analyze its game-theoretic incentive structure, and project its potential impact on digital culture, knowledge management, and decentralized community organization. We also address the dual-use nature of the protocol and propose mitigation strategies for adversarial applications.

2. Formal Specification

2.1 The RDV Function

Let O be a UTF-8 string representing an object and D be a date in ISO 8601 format (YYYY-MM-DD). The Rendezvous Value is defined as:

$$\mathtt{RDV(O,\ D)} = \mathtt{CLZ(\ BLAKE3}_{\mathtt{keyed}}\mathtt{(key} = \mathtt{pad}_{32}\mathtt{(D),\ data} = \mathtt{O)\ )}$$

where CLZ denotes the count of leading zero bits in the 256-bit hash output, and $\mathrm{pad}_{32}(D)$ pads the date string to exactly 32 bytes (the BLAKE3 key length) with trailing zero bytes. The function returns an integer in [0, 256], though values above ~20 are astronomically unlikely.

2.2 Probability Distribution

Because BLAKE3 is a cryptographically secure hash function, its output bits are computationally indistinguishable from uniform random bits. The probability that the first *k* bits are all zero follows directly:

$$P(RDV >= k) = 2^{-k}$$

This yields a geometric distribution over RDV values. $P(RDV = k) = 2^{-(k+1)}$, meaning each successive level is exactly half as likely as the previous one. The expected frequency of each RDV level, given daily computation, is:

RDV	P(RDV = k)	Expected Interval	Human Analogy
0	50.00%	2 days	Ambient background
1	25.00%	4 days	A gentle nudge
2	12.50%	8 days	A weekly highlight
3	6.25%	16 days	A pleasant surprise
5	1.56%	64 days	A seasonal event
7	0.39%	256 days	An annual celebration
10	0.049%	2,048 days (~5.6 yr)	Once in a generation
15	0.0015%	65,536 days (~179 yr)	A civilizational event
20	~0.000048%	~5,700 years	Geological timescale

Table 1. RDV probability distribution and expected intervals.

A crucial property is **hierarchical inclusion**: any object achieving RDV = k implicitly achieves RDV = j for all j < k. This enables threshold-based filtering, where users subscribe to events at or above their chosen significance level.

2.3 The RDVT Extension

Version 2.0 introduces RDVT (Rendezvous Time), which derives a specific UTC timestamp from the hash output. The 256-bit hash is interpreted as a binary fraction in [0, 24) hours. Each bit, read sequentially, contributes a decreasing increment starting from 12 hours, converging on a specific nanosecond within the day:

$$RDVT(O, D, rank) = D_{midnight} + BinaryFraction(BLAKE3_{keyed}(key = pad_{32}(D, rank), data = O)) \times 24h$$

The *rank* parameter generates an infinite sequence of times ($RDVT_0$, $RDVT_1$, ...) for the same object-date pair, enabling multiple coordination windows per day. This transforms RANDEVU from a same-day coordination primitive into a same-second one.

2.4 Object Naming Convention

RANDEVU's coordination power depends on all parties using the same string identifier for a given object. The protocol defines a canonical naming convention to ensure universal agreement without prior communication. The rules are:

- All letters uppercase: `XONOTIC`
- Spaces and dashes replaced with underscores: `STAR_WARS`
- Movies include year of release: `THE_MATRIX_1999`
- Full names; Roman numerals replaced with Arabic: `GRAND_THEFT_AUTO_5`
- Special characters transliterated: `C_PLUS_PLUS`, `C_SHARP`, `ASAP_ROCKY`
- Apostrophes dropped: `NO_MANS_SKY`
- Years prefixed with YEAR_: `YEAR_2000`
- Dates in ISO 8601: `2023-08-25`
- YouTube videos append the video ID: `NEVER_GONNA_GIVE_YOU_UP_dQw4w9WgXcQ`

This convention is designed to be reconstructible from first principles: given any well-known object, a reasonable person should arrive at the same canonical string without consulting a registry. The convention trades some edge-case ambiguity for broad, intuitive applicability.

2.5 Computational Properties

The reference Rust implementation achieves approximately 10 million RDV computations per second on commodity hardware. The JavaScript package is approximately 3KB minified. The algorithm requires zero network access, zero storage, and zero state. These properties are not incidental — they are the central design achievement. Any protocol requiring a server, account, or persistent state has a single point of failure. RANDEVU has none.

3. Theoretical Framework: Schelling Points and Coordination Games

3.1 Schelling Focal Points

In 1960, Thomas Schelling demonstrated that when two parties must coordinate without communication, they converge on culturally salient "focal points." Asked to choose the same time without negotiation, most Americans pick noon. Asked to meet in New York City, most pick Grand Central Station. The focal point succeeds not because it is optimal, but because each party expects the other to choose it.

RANDEVU generates **computational Schelling points** — focal points that are not culturally contingent but mathematically deterministic. The algorithm replaces vague expectations ("let's meet at noon because that seems natural") with cryptographic certainty ("the hash output tells us both the same thing"). This is a qualitative upgrade: the focal point is not merely likely to be shared — it is guaranteed to be shared, given agreement on the object identifier.

3.2 The Coordination Game Formalization

Consider *n* agents who each wish to participate in an activity related to object *O*. Each agent independently decides whether to show up on a given day. Without RANDEVU, each agent faces a pure coordination game: showing up alone yields a negative payoff (wasted time), while showing up with others yields a positive payoff. In the absence of a coordination mechanism, the Nash equilibrium is for no one to show up — the classic coordination failure.

RANDEVU transforms this game by introducing a public, deterministic signal. If all agents adopt the convention "show up when RDV(O, today) >= threshold," the coordination problem reduces to a simple decision rule with no strategic uncertainty. The RDV score acts as a **correlating device** in the sense of Aumann (1974), converting a coordination game into a trivially solvable one — provided participants share the convention.

3.3 The Threshold Equilibrium

A natural question is: at what RDV threshold should agents agree to coordinate? The answer depends on the population of potential participants. Consider a game with *N* fans, each of whom shows up with probability *p* on a qualifying day. The expected turnout on a day with RDV >= *k* is:

```
E[turnout | RDV >= k] = N x p
```

But the frequency of qualifying days is 2^{-k}. So the tradeoff is between event rarity and participant concentration. Lower thresholds produce frequent but sparsely attended events. Higher thresholds produce rare but densely attended events. The optimal threshold depends on the minimum viable gathering size *m*:

```
Choose k such that N x p >= m, where p is the attendance probability given a
                              qualifying signal.
```

For a game with 500 fans, where 10% of signaled fans show up and 8 players are needed, any threshold works: 500 x 0.10 = 50 >> 8. But for a game with 40 fans, the same calculation yields 4, which is insufficient. The community must either lower their threshold (increasing frequency but potentially diluting attendance across too many events) or invest in external amplification (RANDEVU-aware bots, notifications, etc.) to increase *p*. This reveals a fundamental insight: **RANDEVU's effectiveness scales with community size, but its utility begins at the individual level** (as a personal reminder system) and only requires coordination to unlock its social features.

4. Adoption Dynamics and Network Effects

4.1 The Adoption Paradox

RANDEVU presents a paradox common to coordination protocols: the system is most valuable when many people use it, but each individual's incentive to adopt depends on how many others already have. This is the classic network-effect bootstrapping problem. However, RANDEVU has a structural advantage that most coordination tools lack: **it provides individual utility at zero adoption**.

A single user, with no other participants, can use RANDEVU as a personal probabilistic reminder engine — surfacing forgotten bookmarks, revisiting old books, rotating through a media library. This solo-use value provides an initial foothold: users adopt for personal benefit and, as a side effect, become available for coordination. This is the same adoption pathway that made early email and instant messaging succeed: useful even with one user (notes to self), transformative with many.

4.2 A Three-Phase Adoption Model

We propose a three-phase model for RANDEVU's adoption trajectory, analogous to the diffusion of innovations framework (Rogers, 1962):

Phase 1: Individual Utility (0 to ~1,000 users). RANDEVU is adopted as a personal tool — a bookmark resurfacer, a media library manager, a habit randomizer. Users are primarily developers and power users who discover it through GitHub, crates.io, or npm. The coordination features exist in potential but are not yet realized. This phase requires no marketing, only clear documentation and useful reference implementations. The critical metric is individual retention: do users keep using it for personal purposes?

Phase 2: Community Coordination (1,000 to ~100,000 users). As pockets of users emerge around shared interests (retro gaming communities, film clubs, open-source projects), RANDEVU begins to generate real coordination events. A Discord bot in a retro gaming server surfaces daily RDV scores. A browser extension highlights YouTube videos on their high-RDV days. Integration into platforms like GameDate creates visible, recurring engagement. The critical metric shifts to coordination success rate: when RDV signals fire, do people actually show up?

Phase 3: Cultural Infrastructure (~100,000+ users). At sufficient adoption, RANDEVU transcends tooling and becomes a shared cultural convention — a universal calendar for the long tail of human interests. Objects develop reputations around their RDV histories. Communities anticipate high-RDV days weeks in advance. Third-party ecosystems emerge: notification services, countdown widgets, RANDEVU-native apps. The critical metric becomes cultural legibility: do non-technical users understand "it's a high-RDV day for XONOTIC" without needing to understand the algorithm?

4.3 The Zero-Infrastructure Bootstrap Advantage

Most coordination platforms must solve two problems simultaneously: building the platform *and* attracting users. RANDEVU's zero-infrastructure property decouples these. There is no platform to build, maintain, fund, or defend. The protocol is the product. A developer can implement the entire system in under 50 lines of code in any language. This means the adoption bottleneck is purely one of awareness and convention, not technology or economics. The protocol cannot be acquired, shut down, enshittified, or paywalled. It is, in a meaningful sense, immortal.

This property also means that RANDEVU can be embedded inside existing platforms without those platforms depending on external infrastructure. A game store can add "Game of the Day" powered by RANDEVU without any API calls, database queries, or ongoing costs. The integration cost is measured in hours of developer time, and the runtime cost is effectively zero — approximately 100 nanoseconds per hash.

5. Application Domains and Impact Analysis

RANDEVU is a primitive, not an application. Like a hash function or a PRNG, its power lies in the range of systems that can be built on top of it. We enumerate the highest-impact application domains, assess feasibility, and estimate the size of the addressable problem.

5.1 Reviving Abandoned Multiplayer Games

There exist approximately 30,000 multiplayer games across Steam alone, the vast majority of which have zero concurrent players at any given moment. These games are not disliked — they are merely desynchronized. Their fans exist, but never converge at the same time. RANDEVU addresses this directly: by assigning each game a daily RDV score (e.g., `SWAT_4`, `HALO_2`, `XONOTIC`) and an RDVT time, it creates recurring focal points where fans can independently arrive. Platforms like GameDate (which reached 333 HN points and 180K+ tweet views in its first weeks) have demonstrated massive latent demand for exactly this kind of coordination.

The integration cost is near zero: GameDate or any similar platform could add a RANDEVU-powered "Game of the Day" feature using the 3KB JavaScript package, running entirely client-side, with no backend changes. The potential impact is the revival of thousands of games currently in an artificial death state — dead not because of lack of interest, but because of lack of coordination.

5.2 Synchronized Media Experiences

The rise of "watch parties" during the COVID-19 pandemic demonstrated enormous appetite for synchronized media consumption. Yet existing solutions (Discord streams, Teleparty, Watch2Gether) all require active organization. RANDEVU enables passive synchronization: a community agrees on a set of films (e.g., `THE_SHAWSHANK_REDEMPTION_1994`, `THE_MATRIX_1999`), and RANDEVU automatically surfaces one each day with an RDVT timestamp. Participants press play independently at the designated time. The experience of a premiere is recreated for any piece of content, at any point in its lifecycle, indefinitely.

For YouTube alone, with over 800 million videos, the long-tail resurfacing potential is staggering. A creator with 400 videos gains an automatic "featured rewatch" system. Every old video eventually gets its day. The algorithm provides what curation teams at Netflix or Spotify spend millions building — a "today's pick" engine — but with zero cost, zero editorial bias, and infinite longevity.

5.3 Personal Knowledge Management

The average digital life accumulates enormous cognitive debt: bookmarks never revisited, notes never reviewed, articles saved but forgotten, books read once and shelved permanently. Spaced repetition systems (SRS) like Anki address this for structured learning, but require manual card creation and disciplined scheduling. RANDEVU offers a complementary approach: probabilistic resurfacing of *everything*, with zero user effort. A RANDEVU-aware bookmarks manager checks each bookmark's RDV daily and surfaces high-scoring items. A note-taking app periodically reintroduces old notes. The system approximates a "serendipity engine" — a mechanism for manufacturing the productive accidents that drive creative work.

5.4 Decentralized Community Scheduling

Open-source projects, study groups, fan communities, and activist networks all face recurring scheduling problems. Theme days, topic rotations, maintenance windows, and review cycles typically require a coordinator. RANDEVU automates all of these. A Discord bot reading RDV scores for topic names (e.g., `RUST`, `PYTHON`, `LINUX`) creates an infinitely self-refreshing theme calendar with no human maintenance. An open-source project can assign RDV-based "review days" to modules, ensuring even neglected components get periodic attention. A protest network can coordinate awareness days without a central organization to target.

5.5 Content Platform Integration

Any platform with a content library — games, videos, articles, products, courses — can integrate RANDEVU as a "featured today" engine at near-zero cost. Unlike algorithmic recommendation systems that optimize for engagement metrics (and thereby create filter bubbles and attention traps), RANDEVU's recommendations are pseudorandom, deterministic, and identical for all users. This creates shared experiences rather than personalized ones — a fundamentally different social dynamic. The entire library gets rotated through over time, eliminating the "winner take all" distribution that plagues recommendation algorithms.

6. Comparative Analysis

RANDEVU occupies a unique position in the design space of coordination systems. To illustrate this, we compare it against existing approaches:

Property	RANDEVU	Platform Events	Social Media	Calendar Invites	SRS (e.g. Anki)
Server required	No	Yes	Yes	Partially	No
Account required	No	Yes	Yes	Yes	No
Works offline	Yes	No	No	Partially	Yes
Decentralized	Fully	No	No	Partially	N/A
Censorship resistant	Fully	No	No	No	N/A
Multi-party coord.	Yes	Yes	Yes	Yes	No
Zero-knowledge coord.	Yes	No	No	No	No
Scales to N objects	Infinite	Limited	Limited	Manual	Manual
Runtime cost per event	~100ns	API call	API call	Sync	~0
Survives platform death	Yes	No	No	Partially	Yes

Table 2. Comparative properties of coordination mechanisms.

The unique cell in this table is "zero-knowledge coordination" — the ability of agents to coordinate without any of them knowing about the others in advance. This is RANDEVU's defining feature and, to our knowledge, no prior system achieves it for arbitrary objects with this degree of precision and computational efficiency.

7. Predictions and Speculative Modeling

In this section we move from analysis to inference. The predictions below are grounded in the formal properties established above, but extend into territory that requires empirical validation. We offer them as testable hypotheses.

7.1 The Long-Tail Resurrection Effect

We predict that RANDEVU, at sufficient adoption, will measurably alter the consumption distribution of cultural goods. Current consumption follows a steep power law: the top 1% of content captures the vast majority of attention. RANDEVU acts as a countervailing force. By assigning every object a pseudorandomly distributed significance score, it provides a mechanism — perhaps the first scalable one — for systematically redistributing attention across the long tail.

The magnitude of this effect depends on adoption depth. At Phase 2 adoption (community tools, Discord bots, browser extensions), the effect is local: specific communities see increased engagement with back-catalog content. At Phase 3, the effect becomes cultural: "GRAND_THEFT_AUTO_5 hits RDV 8" trends on social media, driving discovery among people who never played the original. This mirrors how Wikipedia's "featured article" system drives traffic to articles that would otherwise receive negligible attention — but extended to all string-representable objects and governed by cryptographic randomness rather than editorial selection.

7.2 Emergent Temporal Identity of Objects

We hypothesize that widely-known objects will develop "temporal identities" — reputations tied to their RDV histories. Because the RDV sequence for any object is deterministic and pre-computable for arbitrary future dates, communities will begin planning around upcoming high-RDV days, creating anticipation cycles analogous to holidays. "HALO_2 hits RDV 8 next Saturday" becomes a cultural event that fans mark on their calendars. Over decades, certain RDV days become part of a game's or film's collective lore — its "anniversaries" in the RANDEVU temporal framework.

This effect is self-reinforcing. As participation on high-RDV days increases, the perceived significance of those days increases, which increases future participation. The RDV score — initially just a number — acquires social meaning through repeated use, a classic example of what Searle (1995) calls institutional facts: "X counts as Y in context C." RDV 7 counts as "a big deal" in the context of communities that have adopted the convention.

7.3 Information-Theoretic Properties

An underappreciated aspect of RANDEVU is its information density. A single RDV score encodes the following information in a single integer: which object is relevant, on which day, at what significance level, and (via RDVT) at what time. This is extraordinarily compact. The entire "schedule" for any object, for any time period, can be computed from first principles with zero storage. Compare this to a calendar entry (which requires ~200 bytes of storage per event) or a platform notification (which requires server-side computation, database lookups, and network transmission).

This compactness has a practical implication: RANDEVU scales to arbitrarily large object sets without any cost increase. A user can "subscribe" to 10,000 objects and compute all their daily RDV scores in approximately one millisecond. No existing notification, recommendation, or scheduling system achieves this ratio of information density to computational cost.

7.4 Civilizational Resilience

We make a speculative but important observation: RANDEVU may be the most resilient coordination protocol ever designed. It has no servers to fail, no databases to corrupt, no companies to go bankrupt, no APIs to deprecate. The algorithm can be written on a napkin. A community that adopts RANDEVU conventions can coordinate for centuries using nothing but the algorithm and their agreed-upon object names. In a world of increasing platform fragility — where services routinely shut down, are acquired and degraded, or change their terms of service — this resilience is not merely an engineering nicety. It is a rare and valuable property.

If RANDEVU achieves cultural adoption, it becomes, in effect, **immortal infrastructure**. Even if every implementation were deleted from the internet, anyone with knowledge of the algorithm (BLAKE3 keyed hash, count leading zeros) could reconstruct it. The conventions persist in human memory and are propagated socially. The nearest analogy is a calendar system itself — the Gregorian calendar requires no server to operate, and RANDEVU extends it with an infinitely rich layer of computed "holidays" for any concept humans choose to name.

8. Dual-Use Considerations and Ethical Analysis

Any coordination technology is inherently dual-use. The same properties that make RANDEVU valuable for positive coordination — decentralization, censorship resistance, zero-knowledge operation — also make it potentially useful for adversarial coordination: harassment campaigns, coordinated manipulation, or targeted brigading.

We classify RANDEVU as closer to "dual-use tool" than "infohazard." The core concept (deterministic pseudorandom scheduling via cryptographic hashing) is simple enough to be independently discovered, and similar coordination methods already exist in less formalized forms. Knowledge of the algorithm alone does not cause harm; organized adoption for malicious purposes does.

Several mitigating factors limit adversarial utility. First, the object naming convention is public: anyone can monitor which objects are being targeted. Second, the algorithm's determinism means that defenders know exactly when attacks will be coordinated — the same math works for both sides. Third, the system provides timing but not communication; adversaries still need separate channels for complex operations. Finally, the probability distribution means that high-RDV events (where coordination is most potent) are rare, limiting burst capacity.

We recommend that implementations include ethical use guidelines, offer a privacy mode (user-salted hashes for personal-only use), and focus documentation on positive use cases. The protocol should be developed transparently, inviting scrutiny from trust and safety researchers.

9. Implementation Status and Ecosystem

As of March 2026, RANDEVU exists as published, maintained packages across three languages:

Language	Package	Registry	Status
Rust	randevu	crates.io	Reference impl. (v2.0)
TypeScript	randevu	npm	Stable, ~3KB
Python	randevu	PyPI	Stable

Table 3. Published implementations.

All implementations are triple-licensed under Unlicense, MIT, and Apache-2.0, representing maximum permissiveness for both open-source and commercial integration. The GitHub repository has accumulated 17 stars and 2 forks as of early 2026, reflecting the project's pre-adoption phase. No formal specification document exists beyond the README and source code, which this paper aims to partially address.

10. Open Problems

Several important questions remain unresolved and represent productive directions for future work:

- **Object Naming Ambiguity.** While the naming convention (Section 2.4) covers common cases, edge cases remain. Should `STAR_WARS` refer to the franchise or the original 1977 film (`STAR_WARS_1977`)? Possible solutions include curated registries, canonical URL-based identifiers, or emergent community conventions.
- **Threshold Discovery.** New users must determine which RDV threshold to use for each object. Research into adaptive threshold recommendations — perhaps based on community size, historical participation, or object popularity — would improve accessibility.
- **Empirical Validation.** The adoption model and cultural impact predictions presented in this paper are theoretical. Controlled experiments — deploying RANDEVU-powered features on existing platforms and measuring coordination rates, retention effects, and long-tail consumption shifts — would provide crucial empirical grounding.
- **Cross-Protocol Interaction.** As more decentralized coordination systems emerge, understanding how RANDEVU interacts with other protocols (ActivityPub, Nostr, etc.) and how it can complement rather than compete with existing infrastructure is an important design question.
- **Formal Security Analysis.** While BLAKE3's cryptographic properties provide strong guarantees about output uniformity, a formal analysis of adversarial manipulation strategies — e.g., strategic choice of object names to create collisions or concentrate events — has not been conducted.

11. Conclusion

RANDEVU is a deceptively simple algorithm with far-reaching implications. By reducing the cost of temporal coordination to a single hash computation, it eliminates the infrastructure dependency that limits all existing coordination systems. Its properties — determinism, decentralization, zero cost, infinite scalability, and civilizational resilience — are not shared by any other coordination protocol we are aware of.

The system's potential spans from the mundane (personal bookmark management) to the profound (a permanent, unkillable layer of temporal coordination for human civilization). Whether this potential is realized depends entirely on adoption — a social problem, not a technical one. The algorithm is complete. The implementations exist. The use cases are enumerable and compelling. What remains is the slower, harder work of cultural diffusion: demonstrating value through working integrations, building tools that make the protocol invisible to end users, and allowing network effects to compound.

We close with a thought experiment. Imagine it is 2050. A teenager wants to play a 25-year-old game that has been "dead" since 2030. She checks the RDV for `NO_MANS_SKY` and finds it is a rare RDV 8 day. She boots up the game at the RDVT-designated time. Across the world, dozens of other people — some her age, some who played the game at launch — have done the same thing, drawn by the same mathematical signal. For an hour, the game is alive again. No one organized this. No platform hosted it. No algorithm recommended it. The math, which has been silently computing these moments since the day the protocol was published, simply told them all: today is the day.

That is the future RANDEVU makes possible. It is waiting to be built.

References

[1] Aumann, R. J. (1974). Subjectivity and Correlation in Randomized Strategies. *Journal of Mathematical Economics*, 1(1), 67-96.

[2] BLAKE3 Team (2020). BLAKE3: One Function, Fast Everywhere. *Specification and Reference Implementation*. https://github.com/BLAKE3-team/BLAKE3

[3] Metcalfe, R. (2013). Metcalfe's Law after 40 Years of Ethernet. *IEEE Computer*, 46(12), 26-31.

[4] Rogers, E. M. (1962). *Diffusion of Innovations*. Free Press of Glencoe.

[5] Schelling, T. C. (1960). *The Strategy of Conflict*. Harvard University Press.

[6] Searle, J. R. (1995). *The Construction of Social Reality*. Free Press.

[7] TypicalHog (2024). RANDEVU: Universal Probabilistic Daily Reminder Coordination System for Anything. GitHub Repository. https://github.com/TypicalHog/randevu

---

RANDEVU is open source and triple-licensed: Unlicense / MIT / Apache-2.0

github.com/TypicalHog/randevu · npm: randevu · crates.io: randevu · PyPI: randevu