Shopbop UW Capstone Common API Calls - 2025

Images

Base URL: https://api.shopbop.com
Base URL for images: https://`m.media-amazon.com/images/G/01/Shopbop/p`
URL suffix for images: found in response of Search API call, with schema `response.products[product_index].colors.images[image_index]`

HTTP Information

HTTP Methods: All API calls listed here are GET's.

Headers:

- **Accept**: Basic HTTP header to specify what MIME types the client is able to understand. Use 'application/json' for the purposes of this project: `'accept: application/json'`
- **Client-Id:** String identifying the client that's calling the API. We will be using 'Shopbop-UW-<Team Num>-2024' for this project: `'Client-Id: Shopbop-UW-Team1-2024' & 'Client-Id: Shopbop-UW-Team2-2024'`
- **Client-Version:** String identifying the version of the client that's calling the API. Use '1.0.0' for this project: `'Client-Version: 1.0.0'`

API Calls

SEARCH

Description: Browse products by search keyword
Endpoint: /public/search
Parameters:

Query Parameter	Type	Definition	List of possible values (If applicable)
allowOutOfStockItems	String	Defines whether or not out of stock products are returned	"false" or "true"
q	String	A search term (required)	
sort	String	Sort type	'editors-pick', 'exclusives', 'hearts', 'price-high-low', 'price-low-high', 'ratings'
minPrice	String	Minimum price	
maxPrice	String	Maximum price	
limit	Int32	Limit results	
dept	String	Department ID	"WOMENS", "MENS"
lang	String	Language ("en") or locale ("en-US")	English ("en-US"), Chinese ("zh-CN"), or Russian ("ru-RU")
offset	Int32	Defines the product the responses should start with	

Example:

```
curl -X 'GET' \
    'https://api.shopbop.com/public/search?lang=en-US¤cy=USD&q=jeans&limit=40&minPrice=25&maxPrice=500&siteId=1006&allowOutOfStockItems=false&dept=WOMENS' \
    -H 'accept: application/json' \
```

```
-H 'Client-Id: Shopbop-UW-Team1-2024' \
-H 'Client-Version: 1.0.0'
```

CATEGORIES

Description: Get public folders. This API call will return a navigation tree, the leaves of which are called categories. Each category has products associated with it. If you would like to build some sort of navigation within your project to get to a screen with a list of products, this is the call you want to use.
Endpoint: /public/folders
Query Parameters:

Query Parameter	Type	Definition	List of possible values (If applicable)
dept	String	Department ID	"WOMENS", "MENS"
lang	String	Language ("en") or locale ("en-US")	English ("en-US"), Chinese ("zh-CN"), or Russian ("ru-RU")

Example:

```
curl -X 'GET' \
  'https://api.shopbop.com/public/folders?lang=en-US&dept=WOMENS' \
  -H 'accept: application/json' \
  -H 'Client-Id: Shopbop-UW-Team1-2024' \
  -H 'Client-Version: 1.0.0'
```

BROWSE BY CATEGORY

Description: Retrieve Browse products for a given category (obtained from the above call)
Endpoint: /public/categories/{categoryId}/products
Parameters:

Parameter	Type	Definition	List of possible values (If applicable)	Parameter Type
allowOutOfStockItems	String	Defines whether or not out of stock products are returned	"false" or "true"	Query
lang	String	Language ("en") or locale ("en-US")	English ("en-US"), Chinese ("zh-CN"), or Russian ("ru-RU")	Query
categoryId	String	Category Id (required)		Path
colors	String	Provide this parameter to refine your results to include only products in these colors	Example: Black, Blue, White, etc.	Query
sort	String	Sort type	‘editors-pick', ‘exclusives', ‘hearts', ‘price-high-low', ‘price-low-high', ‘ratings’	Query
minPrice	String	Minimum price		Query
maxPrice	String	Maximum price		Query
limit	Int32	Limit results		Query
dept	String	Department ID	"WOMENS", "MENS"	Query
q	String	Search string to apply within category		Query
offset	Int32	Defines the product the responses should start with		Query

Example:

```
curl -X 'GET' \
'https://api.shopbop.com/public/categories/13198/products?lang=en-US¤cy=USD&limit=40&q=shoes&minPrice=25&maxPrice=500&dept=WOMENS' \
```

```
-H 'accept: application/json' \
-H 'Client-Id: Shopbop-UW-Team1-2024' \
-H 'Client-Version: 1.0.0'
```

GET PRODUCT DETAILS

Description: Get details for a particular product given a product ID
Endpoint: /public/products/{productSins}
Parameters:

Parameter	Type	Definition	List of possible values (If applicable)	Parameter Type
lang	String	Language ("en") or locale ("en-US")	English ("en-US"), Chinese ("zh-CN"), or Russian ("ru-RU")	Query
productSins	String	Comma separated list of sins - works at style/color/size levels		Path

Example:

```
curl -X 'GET' \
'https://api.shopbop.com/public/products/1547795609,1564465741,1502880995?lang=en-US' \
-H 'accept: application/json' \
-H 'Client-Id: Shopbop-UW-Team1-2024' \
-H 'Client-Version: 1.0.0'
```

OUTFITS

Description: Retrieve outfits that include the specified product. The response will include all active colors for the product. Any colors without outfits will have an empty outfits list.
Endpoint: /public/products/{productSin}/outfits
Parameters:

Parameter	Type	Definition	List of possible values (If applicable)	Parameter Type
productSin	String	SIN of the product		Path
lang	String	Language ("en") or locale ("en-US")	English ("en-US"), Chinese ("zh-CN"), or Russian ("ru-RU")	Query

Example:

```
curl -X 'GET' \
    'https://api.shopbop.com/public/products/1569471937/outfits?lang=en-US' \
    -H 'accept: application/json' \
    -H 'Client-Id: Shopbop-UW-Team1-2024' \
    -H 'Client-Version: 1.0.0'
```

CORS Errors

While calling our API from your application code in a browser, you may run into a Cross Origin Resource Sharing (CORS) error. Browsers enforce CORS to prevent websites from making calls to a different domain for security purposes. You can read more on the subject at the below links:

- https://aws.amazon.com/what-is/cross-origin-resource-sharing
- https://developer.mozilla.org/en-US/docs/Web/HTTP/CORS

We recommend using one of two strategies to mitigate this:

1. Make your Shopbop API calls on the server-side of your application (i.e. when running a Lambda), and provide the API response to the browser
2. Proxy API calls on the client-side through your domain
    a. This can be accomplished with an AWS API Gateway that runs on the same domain as your website (for example: api.myproject.com). You can configure this gateway to forward the browser's request to the Shopbop API.