

Topics in Unsupervised Learning

Amit Ezer, Tzvi Greenfeld

April 2023

Contents

| | | |
|----------|--|----------|
| 1 | Synthetic data tests | 2 |
| 1.1 | K-means results (For the first initialization) | 3 |
| 1.2 | PDC-DP results (For the first initialization) | 4 |
| 2 | Mandrill | 5 |
| 2.1 | K-means | 6 |
| 2.2 | PDC-DP | 7 |
| 3 | Final project statement | 8 |

1 Synthetic data tests




Figure 1: Different initialization results

1.1 K-means results (For the first initialization)




Figure 2: K-means clustering for synthetic data with different k values

As shown by the plots above, we can clearly see that as k gets closer to the number of isotropic Gaussians used to generate the data, the results are clustered better. As expected, for $k = 1$ we only got 1 cluster and for $k = n$ there are n clusters with single point in each cluster.

1.2 PDC-DP results (For the first initialization)




Figure 3: PDC-DP clustering for synthetic data with different λ values

When clustering with PDC-DP-means, we can see the relation between λ and the space populated by our data. Here we have limited the data to be in $\{[-10, 10], [-10, 10]\}$ and the best results were obtained by setting $\lambda = 10$.

2 Mandrill



Figure 4: Original image of a mandrill

The image is 500×800 pixels, therefore the data is $n = 40,000$, $data \in \mathbb{R}^3$

2.1 K-means



$k = 5$



$k = 10$



$k = 20$



$k = 30$

Figure 5: K-means RGB clustering results

2.2 PDC-DP



$\lambda = 500$



$\lambda = 250$



$\lambda = 180$



$\lambda = 100$

Figure 6: PDC-DP RGB clustering results

As λ gets smaller, the number of clusters grows. For $\lambda = 500$ we got 3 clusters, and for $\lambda = 100$ we got 64 clusters, leading to the output image being closer to the input data.

3 Final project statement

We chose to Extend the (P)DC-DP-means Algorithm to Streaming data. (Project #1)