Table of Contents

1. Speech recognition.	 2
2. Flow	 3

Welcome

Project Willy

- History of Willy
- Project Willy
- Publicity
- Sponsors

Getting started

- Development Guide
- Driving Willy
- Documentation

Build of Willy

- Design history
- Requirements
- Design reference
- Physical build
- Hardware

Robotic Operating System

- Introduction to ROS
- ROS Tutorials
- Multi master

Architecture

- Software Architecture
- Hardware Architecture
- Skylab Architecture
- ROS topic design

Hardware nodes

- sensor node
- si node
- power node
- WillyWRT

Components

- ROS master
- New ROS master on Lubuntu
- Brain

- Sonar
- Lidar
- Localization and navigation
- Motor controller
- Joystick
- Social interaction
- Speech
- Speech recognition

Skylab

- Setup Skylab
- Python scripts
- Webserver
- Functions of the webserver
- Skylab servers
- ROS installation on Ubuntu VMs in Skylab
- DNS,DHCP, pfSense & Ubuntu

Radeffect App

• Radeffect App

Lessons learned

- Todo & Advice
- Lessons Learned

Archive

- Previous Groups
- Research Archive

1. Speech recognition

Listening to speech is located on the SI node and is done with a Python script. The script is published at the Github location: https://github.com/Windesheim-Willy/speech_recognition/blob/master/start_recognition.py . Two essential services are used:

- Speech recognition (speech to text conversion) of Google through the use the module speech_recognition
- Fuzzy logic search option throug the use of the module fuzzywuzzy

2. Flow

The general flow in the script is as follows:

- The neccesary modules are imported
- The hit ratio used for fuzzy logic resemblance is set
- Two topics are set for publishing
- Speech is captured through the micropohone
- Speech is transferred to Google for translation in clear text in Dutch
- Text is published on topic /interaction/clear_text
- Text is compared with fuzzy logic to keywords, when hit the number 1 is published on topic /interaction/is_active