Table of Contents

1	Development Guide	2
	1.1. Prerequisite	2
	1.2. Github	3
	1.3. Compilation	4
	1.4. Testing/Debugging	4
	1.5. Running Scripts	5

Welcome

Project Willy

- History of Willy
- Project Willy
- Publicity
- Sponsors

Getting started

- Development Guide
- Driving Willy
- Documentation

Build of Willy

- Design history
- Requirements
- Design reference
- Physical build
- Hardware

Robotic Operating System

- Introduction to ROS
- ROS Tutorials
- Multi master

Architecture

- Software Architecture
- Hardware Architecture
- Skylab Architecture
- ROS topic design

Hardware nodes

- sensor node
- si node
- power node
- WillyWRT

Components

- ROS master
- New ROS master on Lubuntu
- Brain

- Sonar
- Lidar
- Localization and navigation
- Motor controller
- Joystick
- Social interaction
- Speech
- Speech recognition

Skylab

- Setup Skylab
- Python scripts
- Webserver
- Functions of the webserver
- Skylab servers
- ROS installation on Ubuntu VMs in Skylab
- DNS,DHCP, pfSense & Ubuntu

Radeffect App

• Radeffect App

Lessons learned

- Todo & Advice
- · Lessons Learned

Archive

- Previous Groups
- Research Archive

1. Development Guide

1.1. Prerequisite

- Basic knowlegde of NodeJs, Git and ROS
- Install Git & Editor https://code.visualstudio.com/
- Install NodeJS https://nodejs.org/en/download/
- Install Sails

npm install sails -g

- If on Windows:
 - 1. Install Ubuntu
 - Got to Microsoft store
 - Search for 'Ubuntu'
 - Click get/install
 - 2. Install ROS
 - Follow ROS Kinetic installation + (this might take some time) http://wiki.ros.org/kinetic/ Installation/Ubuntu

```
sudo apt-get install ros-kinetic-desktop-full
```

• And enviroment setup

```
echo "source /opt/ros/kinetic/setup.bash" >> ~/.bashrc
source ~/.bashrc
```

Test the installation running ROS

```
roscore
```

Done for now

(ctrl+c)

1.2. Github

- Invite your personal Github account to acces Windesheim-Willy repos https://github.com/orgs/Windesheim-Willy/people
- Clone Git Repo

```
git clone https://github.com/Windesheim-Willy/repo-name
```

• Switch to test branch

```
git checkout -b origin/test
```

1.3. Compilation

Compilation is done via catkin, this is done to create a rospackage so that nodejs can run in a ROS environment.

```
cd WWEB/src
npm install
cd ..
source /opt/ros/kinetic/setup.bash
catkin_make
```

1.4. Testing/Debugging

Run without ros:

```
cd WWEB/src
sails lift (or node app.js)
```

Run with Ros:

1. Start Roscore

• Open a terminal (Ubuntu app on windows) -

```
cd WWEB
source devel/setup.bash
roscore
```

2. Run webplatform

• Open a terminal (Ubuntu app on windows) -

```
cd WWEB
source devel/setup.bash
rosrun willyweb start.sh
```

The rosrun command might not have acces to port 80 for this to work use sudo -s



```
sudo -s
rosrun willyweb start.sh
```

1.5. Running Scripts

In the same manner as you would do Testing/Debugging you can also run scripts. Scripts are located in the folder 'WWEB/src/scripts'.

1. Start Roscore

• Open a terminal (Ubuntu app on windows) -

```
cd WWEB
source devel/setup.bash
roscore
```

2. Run sending script

• Open a terminal (Ubuntu app on windows) -

```
cd WWEB
source devel/setup.bash
rosrun willyweb scripts/send.js
```

3. Run receive script

• Open a terminal (Ubuntu app on windows) -

```
cd WWEB
source devel/setup.bash
rosrun willyweb scripts/receive.js
```

0

Rosrun makes it possible to communicate with ROS because it is now run as a ROS package

The 'start.sh' script consist out of a simple run script which launches the webplatform



#!/usr/bin/env bash
node src/app.js