

GTFShift: A Data-Driven Tool for Prioritizing Bus Lane Implementation

Rosa Félix, Gonçalo Matos

May 12, 2025

Abstract

Identifying the streets with the highest density of bus transit can help in planning and prioritizing the implementation of bus lanes. GTFShift R package uses the General Transit Feed Specification (GTFS) to perform this analysis, allowing for an aggregated overview of the transit density over a given territory.

Keywords: Keywords here, but also in the webform.

1 Questions

Bus lanes (or Transit priority lanes) improve bus operation reliability by reducing the variability of its running time ([Surprenant-Legault & El-Geneidy, 2011](#)), increasing the average commercial speed that can ultimately be used to increase the frequency of service without additional material or human resources ([Basso et al., 2011](#)). Benefits multiplied by a contiguous network, with the highest savings in travel time verified at intersections ([Truong et al., 2015](#)).

However, introducing them on heterogeneous traffic infrastructure has an impact on other modes, such as private vehicles, that with less space allocated, witness a decrease in the level of service ([Arasan & Vedagiri, 2010](#)), jeopardizing public acceptance ([Batty et al., 2014](#)). Identifying the most critical corridors in the network is then critical to quantify impacts, justify, and prioritize interventions.

GTFShift package provides tools for this process, focused on geospatial analysis of the density of the network per street segment. Based on the analysis of the General Transit Feed Specification (GTFS), it extends the capabilities of other R libraries that work with this transit standard, such as tidytransit ([Poletti et al., 2025](#)) and GTFSWizard [de O. Quesado Filho et al. \(2025\)](#).

- How to get an overview of where bus lanes should be prioritized for a given territory?
- Efficient public transport

Bus lanes have the potential to significantly improve bus speed and reliability by limiting the negative impacts of traffic congestion ([6](#)).

When planning bus lanes, we should consider:

- Roadway Capacity: Bus lanes should be implemented on roads with adequate width to accommodate both bus traffic and other vehicles.
- Route Length: Bus lanes should be created for a good length of the road, rather than short stretches, to be effective.
- Traffic Conditions: Careful consideration should be given to traffic flows and potential impacts on other road users, especially on already congested roadways.
- Public Support: Ensuring sufficient public support for bus lane regulations and enforcement is crucial for success.
- Hourly frequency of buses and trams at a peak hour

- Number of lanes (2 or more) in the same direction
- Existing bus lanes in the area

These are only rule of thumb, and the decision should be based on a more detailed analysis of the network, including the existing traffic conditions, the number of bus stops, and the overall demand for public transport in the area. Public policies may opt to implement bus lanes in streets with only one lane, or implement dynamic bus lanes (for peak hours only), for instance.

See also [Szarata \(2022\)](#); [Cesme et al. \(2018\)](#). the last ones also suggest estimated Travel Time Savings Under Various Enforcement Scenarios.

Dedicated bus lanes are typically applied on major routes with frequent headways (10 minutes at peak) or where traffic congestion may significantly affect reliability.

<https://nacto.org/publication/transit-street-design-guide/>

2 Methods

GTFSShift is an R package that provides methods for the entire workflow of bus network density analysis.

Starting with the load of the GTFS feed, with `load_feed()` fixing any integrity errors that might hinder the analysis process.

If the GTFS feed location is unknown, it can be queried using `query_mobilitydatabase()`, a method that asks the Mobility Database API for the feeds that match the parameters provided, such as the municipality, country, or even a boundary box.

Then, to expand the scope analysis, it includes a method for aggregating multiple feeds, `unify().create_calendar()` complements it, solving compatibility issues between feeds with `calendar_dates.txt` only and others with `calendar.txt`.

Narrowing the scope is also possible, using filtering methods according to multiple parameters, such as `filter_by_agency()`, `filter_by_modes()`, and `filter_by_route_name()`. They extend the filtering already provided by the tidytransit package.

Finally, network density can be analyzed at the stop level, with `get_stop_frequency_hourly()`, or at the route level, with `get_route_frequency_hourly()`. This analysis is aggregated by stop, route, and hour.

For an aggregated geospatial analysis, the last accepts an `overline` flag, which overlaps routes in street segments, creating a single route network with combined frequencies. This aggregation is performed using `stplanr::overline2()` ([Lovelace & Ellison, 2018](#)).

To compare the streets with higher transit density and the existing bus lanes, `osm_bus_lanes()` allows to export the roads classified as bus lanes in OpenStreetMap, given a bounding box.

3 Findings

By applying the methods presented in the previous chapter, it was possible to analyse the bus network density for Lisbon city, in Portugal.

The analysis was performed using the aggregated feeds of both Carris and Carris Metropolitana, respectively, the urban and sub-urban bus operators in the area.

The results, presented in Figure 1, allow for the identification of the street segments with higher bus transit density.

The previous approach, nevertheless, can be problematic if the GTFS shapes do not share the same geometry. For instance, if the edges of the lines do not overlap, lines might not be aggregated correctly, causing inconsistent results. As an alternative, *GTFSShift* provides the method `network_overline()`, that allows for an alternative route aggregation. Given a simplified network (generated externally), it identifies the segments corresponding to each route and uses them to aggregate the attribute defined in the parameters. It can be used to aggregate the routes frequencies.

Additionally, filtering the road network segments by existing number of lanes in the same direction (2 or more) may better support the decision of implementing bus corridors.




Fig. 1. Road segments with higher bus frequency, in Lisbon, at 8 am. The larger and lighter lines represent the streets with higher hourly bus frequency. Carto basemap.

Further enhancements of the method may include the passenger capacity per hour, instead of the frequency of the number of vehicles. For instance, bus routes with articulated buses (more than 80 passengers) would weight more than an historical tram route (max 25 passengers).

Acknowledgements

The authors acknowledge Francisco Costa and Manuel Banza for valuable discussion on the refined methods and further developments. R Felix is grateful for the Foundation for Science and Technology's support through funding UIDB/04625/2025 from the research unit CERIS.

References

- Arasan, V. T., & Vedagiri, P. (2010, 5). Study of the impact of exclusive bus lane under highly heterogeneous traffic condition. *Public Transport*, 2(1-2), 135–155. doi: 10.1007/s12469-010-0021-x
- Basso, L. J., Guevara, C. A., Gschwender, A., & Fuster, M. (2011, 2). Congestion pricing, transit subsidies and dedicated bus lanes: Efficient and practical solutions to congestion. *Transport Policy*, 18(5), 676–684. doi: 10.1016/j.tranpol.2011.01.002
- Batty, P., Palacin, R., & González-Gil, A. (2014, 12). Challenges and opportunities in developing urban modal shift. *Travel Behaviour and Society*, 2(2), 109–123. doi: 10.1016/j.tbs.2014.12.001
- Cesme, B., Roisman, R., Burns, R., List, K., Koudounas, A., Cuellar, J., ... Miller, D. (2018, 12). Strategies and barriers in effective bus lane implementation and management: Best practices for use in the greater washington, d.c. region. *Transportation Research Record: Journal of the Transportation Research Board*, 2672(8), 29–40. Retrieved from <https://journals.sagepub.com/doi/10.1177/0361198118791914> doi: 10.1177/0361198118791914
- de O. Quesado Filho, N., Guimarães, C. G. C., & de Oliveira Neto, F. M. (2025). Gtfswizard: Exploring and manipulating gtfs files [Computer software manual]. Retrieved from <https://cran.r-project.org/package=GTFswizard> (R package version 1.1.0) doi: 10.32614/CRAN.package.GTFswizard
- Lovelace, R., & Ellison, R. (2018). stplanr: A package for transport planning. *The R Journal*, 10(2), 10. doi: 10.32614/RJ-2018-053
- Poletti, F., Herszenhut, D., Padgham, M., Buckley, T., & Noriega-Goodwin, D. (2025). tidytransit: Read, validate, analyze, and map gtfs feeds [Computer software manual]. Retrieved from <https://github.com/r-transit/tidytransit> (R package version 1.7.0)
- Surprenant-Legault, J., & El-Geneidy, A. M. (2011, 1). Introduction of reserved bus lane. *Transportation Research Record Journal of the Transportation Research Board*, 2218(1), 10–18. doi: 10.3141/2218-02
- Szarata, M. (2022, 09). Bus lane implementation strategy. *Transport Problems*, 17(3), 97–108. Retrieved from http://transportproblems.polsl.pl/pl/Archiwum/2022/zeszyt3/2022t17z3_08.pdf doi: 10.20858/tp.2022.17.3.08
- Truong, L. T., Sarvi, M., & Currie, G. (2015, 1). Exploring multiplier effects generated by bus lane combinations. *Transportation Research Record Journal of the Transportation Research Board*, 2533(1), 68–77. doi: 10.3141/2533-08