


Ссылка: 2


```
public class Role
{
    [Key]
    Ссылка: 1
    public int RoleID { get; set; }
    Ссылка: 0
    public string RoleName { get; set; }

    Ссылка: 0
    public virtual ICollection<User> Users { get; private set; } = new ObservableCollection<User>();
}
```




Ссылка: 5


```
public class ModelContext : DbContext
{
    Ссылка: 2
    public DbSet<User> Users { get; set; }
    Ссылка: 0
    public DbSet<Role> Roles { get; set; }
    Ссылка: 0
    protected override void OnConfiguring(DbContextOptionsBuilder optionsBuilder)
    {
        optionsBuilder.UseSqlite("Data Source = Test.db");
        optionsBuilder.UseLazyLoadingProxies();
    }
}
```




```
<Application.Resources>
  <ResourceDictionary>
    <ResourceDictionary.MergedDictionaries>
      <materialDesign:BundledTheme BaseTheme="Light" PrimaryColor="DeepPurple" SecondaryColor="Lime" />
      <ResourceDictionary Source="pack://application:,,,/MaterialDesignThemes.Wpf;component/Themes/MaterialDesignTheme.Defaults.xaml" />
    </ResourceDictionary.MergedDictionaries>
  </ResourceDictionary>
</Application.Resources>
```



```
Ссылка: 3
public partial class App : Application
{
    Ссылка: 0
    protected override void OnStartup(StartupEventArgs e)
    {
        DatabaseFacade facade = new DatabaseFacade(new ModelContext());
        facade.EnsureCreated();
    }
}
```



```
Ссылка: 4
public static class Util
{
    Ссылка: 4
    public static Frame? UtilFrame { get; set; }
}
```



```
<Window x:Class="WpfApp1.MainWindow"
xmlns="http://schemas.microsoft.com/winfx/2006/xaml/presentation"
xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml"
xmlns:d="http://schemas.microsoft.com/expression/blend/2008"
xmlns:mc="http://schemas.openxmlformats.org/markup-compatibility/2006"
xmlns:local="clr-namespace:WpfApp1"
mc:Ignorable="d"
WindowStyle="None"
WindowStartupLocation="CenterScreen"
ResizeMode="NoResize"
Background="■"Transparent"
AllowsTransparency="True"
Height="700"
Width="1024">
  <Grid MouseDown="Grid_MouseDown">
    <Image Source="/Images/main_bg.jpg"
    Stretch="UniformToFill"/>
    <Frame x:Name="MainFrame"
    NavigationUIVisibility="Hidden"/>
  </Grid>
</Window>
```






Ссылка: 2

```
public partial class MainWindow : Window
{
    Ссылка: 0
    public MainWindow()
    {
        InitializeComponent();
        Util.UtilFrame = MainFrame;
        MainFrame.Navigate(new LoginPage());
    }

    Ссылка: 1
    private void Grid_MouseDown(object sender, System.Windows.Input.MouseButtonEventArgs e)
    {
        if (e.ClickCount == 2)
        {
            Application.Current.Shutdown();
        }
    }
}
```



```
Зависимости
├── Core
├── Images
├── Model
├── View
├── Pages
│   ├── LoginPage.xaml
│   └── RegistrationPage.xaml
├── MainWindow.xaml
├── App.xaml
└── AssemblyInfo.cs
```

```
<Page x:Class="WpfAppl.View.Pages.LoginPage"
      xmlns="http://schemas.microsoft.com/winfx/2006/xaml/presentation"
      xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml"
      xmlns:mc="http://schemas.openxmlformats.org/markup-compatibility/2006"
      xmlns:d="http://schemas.microsoft.com/expression/blend/2008"
      xmlns:local="clr-namespace:WpfAppl.View.Pages"
      xmlns:materialDesign="http://materialdesigninxaml.net/winfx/xaml/themes"
      mc:Ignorable="d"
      d:DesignHeight="700"
      d:DesignWidth="1024"
      FontFamily="Comic Sans MS">

    <Grid>
        <Grid.ColumnDefinitions>
            <ColumnDefinition Width="1*" />
            <ColumnDefinition Width="1*" />
        </Grid.ColumnDefinitions>
        <Border Grid.Column="1"
                HorizontalAlignment="Left"
                VerticalAlignment="Center"
                Width="445"
                Height="485"
                CornerRadius="55"
                BorderBrush="#3F3FD0"
                BorderThickness="2"
                Background="#FFFFFF">
```

```

<Grid>
  <StackPanel HorizontalAlignment="Center"
    VerticalAlignment="Top">
    <StackPanel Margin="0 30 0 0">
      <TextBlock FontSize="26"
        FontWeight="SemiBold">
        <Run Text="Практическая работа "
          Foreground="#4D47ED"/>
        <Run Text="№6"
          Foreground="#000000"/>
      </TextBlock>

      <TextBlock Text="Работа с SQLite"
        TextAlignment="Center"
        FontWeight="Regular"
        FontSize="15"
        Foreground="#67686F"/>

      <materialDesign:PackIcon Kind="Database"
        Margin="0 20 0 0"
        HorizontalAlignment="Center"
        VerticalAlignment="Center"
        Foreground="#67686F"
        Height="110"
        Width="100"/>
    </StackPanel>
  </Grid>

```

```

<StackPanel Orientation="Horizontal"
  Margin="0 20 0 0">
  <materialDesign:PackIcon Kind="Email"
    Width="25"
    Height="25"
    Margin="0 3 10 0"/>
  <TextBox Width="305"
    x:Name="TbLogin"
    FontWeight="Regular"
    Foreground="#67686F"
    FontSize="15"
    materialDesign:HintAssist.Hint="Введите адрес электронной почты..."
    materialDesign:TextFieldAssist.HasClearButton="True"
    materialDesign:TextFieldAssist.UnderlineBrush="#FFFFFF"/>
</StackPanel>

<StackPanel Orientation="Horizontal"
  Margin="0 20 0 0">
  <materialDesign:PackIcon Kind="Password"
    Width="25"
    Height="25"
    Margin="0 3 10 0"/>
  <PasswordBox Width="305"
    FontWeight="Regular"
    x:Name="PbPassword"
    Foreground="#67686F"
    FontSize="15"
    materialDesign:HintAssist.Hint="Введите пароль..."
    materialDesign:TextFieldAssist.HasClearButton="True"
    materialDesign:TextFieldAssist.UnderlineBrush="#FFFFFF"/>
</StackPanel>

```

```

<StackPanel Margin="0 20 0 0">
    <CheckBox Content="Запомнить пароль"
        Foreground="■" #5B5B5B"
        Background="■" #3F3FD0"
        Cursor="Hand"
        FontSize="15"/>
</StackPanel>

<StackPanel Margin="0 20 0 0"
    Orientation="Horizontal">
    <Button Width="120"
        Margin="0 0 20 0"
        x:Name="BtnLogin"
        Click="BtnLogin_Click"
        Height="50"
        Background="■" #3F3FD0"
        BorderBrush="■" #3F3FD0"
        Foreground="■" #FFFFFF"
        Style="{StaticResource MaterialDesignRaisedButton}"
        materialDesign:ButtonProgressAssist.Value="-1"
        materialDesign:ButtonProgressAssist.IndicatorForeground="■" #FFFFFF"
        materialDesign:ButtonProgressAssist.IndicatorBackground="■" Transparent"
        materialDesign:ButtonProgressAssist.IsIndicatorVisible="True"
        materialDesign:ButtonProgressAssist.IsIndeterminate="True"
        IsEnabled="{Binding DataContext.ControlsEnabled,
            RelativeSource={RelativeSource FindAncestor, AncestorType=Window}}">
        <StackPanel Orientation="Horizontal">
            <materialDesign:PackIcon Kind="LoginVariant"
                Margin="0 2 3 0"/>
            <TextBlock Text="Войти"/>
        </StackPanel>
    </Button>



```

```

    <Button Width="220"
        x:Name="BtnRegistration"
        Click="BtnRegistration_Click"
        Height="50"
        Background="■" Transparent"
        BorderBrush="■" #3F3FD0"
        Foreground="■" #3F3FD0"
        Style="{StaticResource MaterialDesignOutlinedButton}"
        materialDesign:ButtonProgressAssist.Value="-1"
        materialDesign:ButtonProgressAssist.IndicatorForeground="■" #3F3FD0"
        materialDesign:ButtonProgressAssist.IsIndicatorVisible="True"
        materialDesign:ButtonProgressAssist.IsIndeterminate="True"
        IsEnabled="{Binding DataContext.ControlsEnabled,
            RelativeSource={RelativeSource FindAncestor, AncestorType=Window}}">
        <StackPanel Orientation="Horizontal">
            <materialDesign:PackIcon Kind="Terrain"
                Margin="0 2 3 0"/>
            <TextBlock Text="Создать аккаунт "/>
        </StackPanel>
    </Button>
</StackPanel>

</StackPanel>
</Grid>
</Border>

```



```

Ссылка: 3
public partial class LoginPage : Page
{
    private ModelContext? _db = null;
    Ссылка: 3
    public LoginPage()
    {
        InitializeComponent();
        _db = new ModelContext();
    }

    Ссылка: 1
    private void BtnLogin_Click(object sender, RoutedEventArgs e)
    {
        User? userModel = _db?.Users.FirstOrDefault(predicate: x => x.Login == TbLogin.Text &&
                                                                    x.Password == PbPassword.Password);
    }
}

```



```

if (userModel != null)
{
    switch (userModel.Role.RoleID)
    {
        case 1:
            MessageBox.Show("Администратор",
                            "Системное сообщение",
                            MessageBoxButton.OK,
                            MessageBoxImage.Information);

            break;
        case 2:
            MessageBox.Show("Пользователь",
                            "Системное сообщение",
                            MessageBoxButton.OK,
                            MessageBoxImage.Information);

            break;
        case 3:
            MessageBox.Show("Гость",
                            "Системное сообщение",
                            MessageBoxButton.OK,
                            MessageBoxImage.Information);

            break;
    }
}
else
{
    MessageBox.Show("Ошибка ввода данных", "Системное сообщение", MessageBoxButton.OK, MessageBoxImage.Error);
}


```

Ссылка: 1

```

private void BtnRegistration_Click(object sender, RoutedEventArgs e)
{
    Util.UtilFrame?.Navigate(new RegistrationPage());
}

```



```

Зависимости
├── Core
├── Images
├── Model
├── View
│   ├── Pages
│   │   ├── LoginPage.xaml
│   │   └── RegistrationPage.xaml
│   ├── MainWindow.xaml
│   └── App.xaml
└── C# AssemblyInfo.cs

```

```

<Page x:Class="WpfApp1.View.Pages.RegistrationPage"
      xmlns="http://schemas.microsoft.com/winfx/2006/xaml/presentation"
      xmlns:x="http://schemas.microsoft.com/winfx/2006/xaml"
      xmlns:mc="http://schemas.openxmlformats.org/markup-compatibility/2006"
      xmlns:d="http://schemas.microsoft.com/expression/blend/2008"
      xmlns:materialDesign="http://materialdesigninxaml.net/winfx/xaml/themes"
      xmlns:local="clr-namespace:WpfApp1.View.Pages"
      mc:Ignorable="d"
      d:DesignHeight="700"
      d:DesignWidth="1024"
      FontFamily="Comic Sans MS">

```

```

<Grid>
  <Grid.ColumnDefinitions>
    <ColumnDefinition Width="1*" />
    <ColumnDefinition Width="1*" />
  </Grid.ColumnDefinitions>
  <Border Grid.Column="0"
    HorizontalAlignment="Right"
    VerticalAlignment="Center"
    Width="445"
    Height="485"
    CornerRadius="55"
    BorderBrush="■" "#3F3FD0"
    BorderThickness="2"
    Background=■ "FFFFFF">
    <Grid>
      <StackPanel HorizontalAlignment="Center"
        VerticalAlignment="Top">
        <StackPanel Margin="0 30 0 0">
          <TextBlock FontSize="26"
            FontWeight="SemiBold">
            <Run Text="Практическая работа "
              Foreground=■ "#4D47ED" />
            <Run Text="№6"
              Foreground=■ "#000000" />
          </TextBlock>

          <TextBlock Text="Работа с SQLite"
            TextAlignment="Center"
            FontWeight="Regular"
            FontSize="15"
            Foreground=■ "#67686F" />
        </StackPanel>
      </StackPanel>
    </Grid>
  </Border>

```

```

    <materialDesign:PackIcon Kind="Database"
      Margin="0 20 0 0"
      HorizontalAlignment="Center"
      VerticalAlignment="Center"
      Foreground=■ "#67686F"
      Height="110"
      Width="100" />
  </StackPanel>

  <StackPanel Orientation="Horizontal"
    Margin="0 20 0 0">
    <materialDesign:PackIcon Kind="Email"
      Width="25"
      Height="25"
      Margin="0 3 10 0" />

    <TextBox Width="305"
      x:Name="TbLogin"
      FontWeight="Regular"
      Foreground=■ "#67686F"
      FontSize="15"
      materialDesign:HintAssist.Hint="Введите адрес электронной почты..."
      materialDesign:TextFieldAssist.HasClearButton="True"
      materialDesign:TextFieldAssist.UnderlineBrush=■ "FFFFFF" />
  </StackPanel>

```

```

<StackPanel Orientation="Horizontal"
    Margin="0 20 0 0">
    <materialDesign:PackIcon Kind="Password"
        Width="25"
        Height="25"
        Margin="0 3 10 0"/>
    <PasswordBox Width="305"
        FontWeight="Regular"
        x:Name="PbPassword"
        Foreground="■" "#67686F"
        FontSize="15"
        materialDesign:HintAssist.Hint="Введите пароль..."
        materialDesign:TextFieldAssist.HasClearButton="True"
        materialDesign:TextFieldAssist.UnderlineBrush="■" "#FFFFFF"/>
</StackPanel>

<StackPanel Margin="0 20 0 0">
    <CheckBox Content="Отобразить пароль"
        Foreground="■" "#5B5B5B"
        Background="■" "#3F3FD0"
        Cursor="Hand"
        FontSize="15"/>
</StackPanel>

```

```


<StackPanel Margin="0 20 0 0"
    Orientation="Horizontal">
    <Button Width="220"
        x:Name="BntCreat"
        Click="BntCreat_Click"
        Height="50"
        Background="■" "Transparent"
        BorderBrush="■" "#3F3FD0"
        Foreground="■" "#3F3FD0"
        Style="{StaticResource MaterialDesignOutlinedButton}"
        materialDesign:ButtonProgressAssist.Value="-1"
        materialDesign:ButtonProgressAssist.IndicatorForeground="■" "#3F3FD0"
        materialDesign:ButtonProgressAssist.IsIndicatorVisible="True"
        materialDesign:ButtonProgressAssist.IsIndeterminate="True"
        IsEnabled="{Binding DataContext.ControlsEnabled,
            RelativeSource={RelativeSource FindAncestor, AncestorType=Window}}">
        <StackPanel Orientation="Horizontal">
            <materialDesign:PackIcon Kind="Create"
                Margin="0 2 3 0"/>
            <TextBlock Text="Создать аккаунт" />
        </StackPanel>
    </Button>

```


```

<Button Width="170"
        Margin="20 0 0 0"
        x:Name="BtnBack"
        Click="BtnBack_Click"
        Height="50"
        Background="#3F3FD0"
        BorderBrush="#3F3FD0"
        Foreground="FFFFFF"
        Style="{StaticResource MaterialDesignRaisedButton}"
        materialDesign:ButtonProgressAssist.Value="-1"
        materialDesign:ButtonProgressAssist.IndicatorForeground="FFFFFF"
        materialDesign:ButtonProgressAssist.IndicatorBackground="Transparent"
        materialDesign:ButtonProgressAssist.IsIndicatorVisible="True"
        materialDesign:ButtonProgressAssist.IsIndeterminate="True"
        IsEnabled="{Binding DataContext.ControlsEnabled,
                    RelativeSource={RelativeSource FindAncestor, AncestorType=Window}}">
    <StackPanel Orientation="Horizontal">
        <materialDesign:PackIcon Kind="SpyOff"
                                Margin="0 2 3 0"/>
        <TextBlock Text="Или Войти"/>
    </StackPanel>
</Button>
</StackPanel>

```







```
public partial class RegistrationPage : Page
{
    private ModelContext? _db = null;
    private User _user = new User();
    Ссылка: 1
    public RegistrationPage()
    {
        InitializeComponent();

        _db = new ModelContext();
    }

    Ссылка: 1
    private void BtnBack_Click(object sender, RoutedEventArgs e)
    {
        Util.UtilFrame?.Navigate(new LoginPage());
    }

    Ссылка: 1
    private void BtnCreat_Click(object sender, RoutedEventArgs e)
    {
        if (string.IsNullOrEmpty(TbLogin.Text) ||
            string.IsNullOrEmpty(PbPassword.Password))
        {
            MessageBox.Show("Ошибка ввода данных",
                            "Системное сообщение",
                            MessageBoxButton.OK,
                            MessageBoxImage.Error);
        }
    }
}
```

```
else
{
    try
    {
        _user.Login = TbLogin.Text;
        _user.Password = PbPassword.Password;
        _user.RoleID = 2;

        MessageBox.Show("Аккаунт пользователя успешно создан",
                        "Системное сообщение",
                        MessageBoxButton.OK,
                        MessageBoxImage.Error);

        _db?.Users.Add(_user);
        _db?.SaveChanges();

        Util.UtilFrame?.Navigate(new LoginPage());
    }
    catch (Exception ex)
    {
        MessageBox.Show(ex.Message.ToString(),
                        "Системное сообщение",
                        MessageBoxButton.OK,
                        MessageBoxImage.Error);
    }
}
```