October 27, 2026

Vulnerability Scan Report



HostedScan Security

hostedscan.com

Table of Contents

1.0 Executive Summary 3

2.0 Trends 4

3.0 Vulnerabilities By Target 6

4.0 Passive Web Application Vulnerabilities 8

5.0 Network Vulnerabilities 18

6.0 Open TCP Ports 22

7.0 Glossary 25

1.0 Executive Summary

Vulnerability scans were conducted on select servers, networks, websites, and applications. This report contains the discovered potential vulnerabilities from these scans. Vulnerabilities have been classified by severity. Higher severity indicates a greater risk of a data breach, loss of integrity, or availability of the targets.

1.1 Total Vulnerabilities

Below are the total number of vulnerabilities found by severity. Critical vulnerabilities are the most severe and should be evaluated first. An accepted vulnerability is one which has been manually reviewed and classified as acceptable to not fix at this time, such as a false positive detection or an intentional part of the system's architecture.

Critical	High	Medium	Low	Accepted
0	0	5	6	0



1.2 Report Coverage


This report includes findings for **1 target** scanned. Each target is a single URL, IP address, or fully qualified domain name (FQDN).

1	7	2	2
Total Targets	Passive Web Application Vulnerabilities	Network Vulnerabilities	Open TCP Ports

2.0 Trends


2.1 Open Risks

Total number of vulnerabilities grouped by severity level.




2.2 Exposure Window

Total number of unresolved vulnerabilities grouped by age (time since first detection).



2.3 Health Score

Total score based on the cumulated risks for all targets.



3.0 Vulnerabilities By Target

This section contains the vulnerability findings for each scanned target. Prioritization should be given to the targets with the highest severity vulnerabilities. However, it is important to take into account the purpose of each system and consider the potential impact a breach or an outage would have for the particular target.

3.1 Targets Summary (1)

The number of potential vulnerabilities found for each target by severity.

Target	Critical	High	Medium	Low	Accepted
https://u77w41.github.io/anurup/	0	0	5	6	0

3.2 Target Breakdowns

Details for the potential vulnerabilities found for each target by scan type.

A https://u77w41.github.io/anurup/

Scans run: OpenVAS | Nmap | ZAP Passive

Total Risks

0	0	5	6	0

45% 55%

Passive Web Application Vulnerabilities Last scanned: 10/27/2026	Severity	First Detected
Cross-Domain Misconfiguration	Medium	10/27/2026
Absence of Anti-CSRF Tokens	Medium	10/27/2026
Sub Resource Integrity Attribute Missing	Medium	10/27/2026
Content Security Policy (CSP) Header Not Set	Medium	10/27/2026
Missing Anti-clickjacking Header	Medium	10/27/2026
X-Content-Type-Options Header Missing	Low	10/27/2026
Strict-Transport-Security Header Not Set	Low	10/27/2026
Network Vulnerabilities Last scanned: 10/27/2026	Severity	First Detected
ICMP Timestamp Reply Information Disclosure CVSS Score: 2.1	Low	10/27/2026
TCP Timestamps Information Disclosure CVSS Score: 2.6	Low	10/27/2026
Open TCP Ports Last scanned: 10/27/2026	Severity	First Detected
Open TCP Port: 80	Low	10/27/2026
Open TCP Port: 443	Low	10/27/2026

4.0 Passive Web Application Vulnerabilities

The OWASP ZAP Passive Web Application scan crawls the pages of a website or web application. The passive scan inspects each page as well as the requests and responses sent between the server. The passive scan checks for vulnerabilities such as cross-domain misconfigurations, insecure cookies, vulnerable Javascript dependencies, and more.

4.1 Scan Coverage

Shows how recently the included targets were last scanned.

Never scanned	More than 90 days ago	Last 90 days	Last 30 days
0	0	0	1

4.2 Total Vulnerabilities

Total number of vulnerabilities found by severity.

Critical	High	Medium	Low	Accepted
0	0	5	2	0



4.3 Vulnerabilities Breakdown

Summary list of all detected vulnerabilities.

Title	Severity	Open	Accepted
Cross-Domain Misconfiguration	Medium	1	0
Absence of Anti-CSRF Tokens	Medium	1	0
Sub Resource Integrity Attribute Missing	Medium	1	0
Content Security Policy (CSP) Header Not Set	Medium	1	0
Missing Anti-clickjacking Header	Medium	1	0
X-Content-Type-Options Header Missing	Low	1	0
Strict-Transport-Security Header Not Set	Low	1	0

4.4 Vulnerability Details

Detailed information about each potential vulnerability found by the scan.

Cross-Domain Misconfiguration

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Medium	1 target	2 hours ago

Description

Web browser data loading may be possible, due to a Cross Origin Resource Sharing (CORS) misconfiguration on the web server.

Solution

Ensure that sensitive data is not available in an unauthenticated manner (using IP address white-listing, for instance).

Configure the "Access-Control-Allow-Origin" HTTP header to a more restrictive set of domains, or remove all CORS headers entirely, to allow the web browser to enforce the Same Origin Policy (SOP) in a more restrictive manner.

Instances (1 of 5)

uri: https://u77w41.github.io/anurup/
method: GET
evidence: Access-Control-Allow-Origin: *
otherinfo: The CORS misconfiguration on the web server permits cross-domain read requests from arbitrary third party domains, using unauthenticated APIs on this domain. Web browser implementations do not permit arbitrary third parties to read the response from authenticated APIs, however. This reduces the risk somewhat. This misconfiguration could be used by an attacker to access data that is available in an unauthenticated manner, but which uses some other form of security, such as IP address white-listing.

References

https://vulncat.fortify.com/en/detail?category=HTML5&subcategory=Overly%20Permissive%20CORS%20Policy

Vulnerable Target	First Detected	Last Detected
https://u77w41.github.io/anurup/	10/27/2026	10/27/2026

Absence of Anti-CSRF Tokens

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Medium	1 target	2 hours ago

Description

No Anti-CSRF tokens were found in a HTML submission form.

A cross-site request forgery is an attack that involves forcing a victim to send an HTTP request to a target destination without their knowledge or intent in order to perform an action as the victim. The underlying cause is application functionality using predictable URL/form actions in a repeatable way. The nature of the attack is that CSRF exploits the trust that a web site has for a user. By contrast, cross-site scripting (XSS) exploits the trust that a user has for a web site. Like XSS, CSRF attacks are not necessarily cross-site, but they can be. Cross-site request forgery is also known as CSRF, XSRF, one-click attack, session riding, confused deputy, and sea surf.

CSRF attacks are effective in a number of situations, including:

* The victim has an active session on the target site.

* The victim is authenticated via HTTP auth on the target site.

* The victim is on the same local network as the target site.

CSRF has primarily been used to perform an action against a target site using the victim's privileges, but recent techniques have been discovered to disclose information by gaining access to the response. The risk of information disclosure is dramatically increased when the target site is vulnerable to XSS, because XSS can be used as a platform for CSRF, allowing the attack to operate within the bounds of the same-origin policy.

Solution

Phase: Architecture and Design

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid.

For example, use anti-CSRF packages such as the OWASP CSRFGuard.

Phase: Implementation

Ensure that your application is free of cross-site scripting issues, because most CSRF defenses can be bypassed using attacker-controlled script.

Phase: Architecture and Design

Generate a unique nonce for each form, place the nonce into the form, and verify the nonce upon receipt of the form. Be sure that the nonce is not predictable (CWE-330).

Note that this can be bypassed using XSS.

Identify especially dangerous operations. When the user performs a dangerous operation, send a separate confirmation request to ensure that the user intended to perform that operation.

Note that this can be bypassed using XSS.

Use the ESAPI Session Management control.

This control includes a component for CSRF.

Do not use the GET method for any request that triggers a state change.

Phase: Implementation

Check the HTTP Referer header to see if the request originated from an expected page. This could break legitimate functionality, because users or proxies may have disabled sending the Referer for privacy reasons.

Instances (1 of 3)

uri: https://u77w41.github.io/tags/
method: GET
evidence: <form method=dialog class=pagination-jump-form>
otherinfo: No known Anti-CSRF token [anticsrf, CSRFToken, __RequestVerificationToken, csrfmiddlewaretoken, authenticity_token, OWASP_CSRFTOKEN, anoncsrf, csrf_token, _csrf, _csrfSecret, __csrf_magic, CSRF, _token, _csrf_token, _csrfToken, data[_Token][key], _wpnonce] was found in the following HTML form: [Form 1: "pagination-jump-input"].

References

https://cheatsheetseries.owasp.org/cheatsheets/Cross-Site_Request_Forgery_Prevention_Cheat_Sheet.html
https://cwe.mitre.org/data/definitions/352.html

Vulnerable Target	First Detected	Last Detected
https://u77w41.github.io/anurup/	10/27/2026	10/27/2026

Sub Resource Integrity Attribute Missing

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Medium	1 target	2 hours ago

Description

The integrity attribute is missing on a script or link tag served by an external server. The integrity tag prevents an attacker who have gained access to this server from injecting a malicious content.

Solution

Provide a valid integrity attribute to the tag.

Instances (1 of 5)

uri: https://u77w41.github.io/p/anurup/
method: GET
evidence: <link rel=preload as=style href="https://fonts.googleapis.com/css2?family=Lato:wght@300;400;700&display=swap">

References

https://developer.mozilla.org/en-US/docs/Web/Security/Defenses/Subresource_Integrity

Vulnerable Target	First Detected	Last Detected
https://u77w41.github.io/anurup/	10/27/2026	10/27/2026

Content Security Policy (CSP) Header Not Set

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Medium	1 target	2 hours ago

Description

Content Security Policy (CSP) is an added layer of security that helps to detect and mitigate certain types of attacks, including Cross Site Scripting (XSS) and data injection attacks. These attacks are used for everything from data theft to site defacement or distribution of malware. CSP provides a set of standard HTTP headers that allow website owners to declare approved sources of content that browsers should be allowed to load on that page — covered types are JavaScript, CSS, HTML frames, fonts, images and embeddable objects such as Java applets, ActiveX, audio and video files.

Solution

Ensure that your web server, application server, load balancer, etc. is configured to set the Content-Security-Policy header.

Instances (1 of 5)

uri: https://u77w41.github.io/anurup/
method: GET

References

https://developer.mozilla.org/en-US/docs/Web/HTTP/Guides/CSP
https://cheatsheetseries.owasp.org/cheatsheets/Content_Security_Policy_Cheat_Sheet.html
https://www.w3.org/TR/CSP/
https://w3c.github.io/webappsec-csp/
https://web.dev/articles/csp
https://caniuse.com/#feat=contentsecuritypolicy
https://content-security-policy.com/

Vulnerable Target	First Detected	Last Detected
https://u77w41.github.io/anurup/	10/27/2026	10/27/2026

Missing Anti-clickjacking Header

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Medium	1 target	2 hours ago

Description

The response does not protect against 'ClickJacking' attacks. It should include either Content-Security-Policy with 'frame-ancestors' directive or X-Frame-Options.

Solution

Modern Web browsers support the Content-Security-Policy and X-Frame-Options HTTP headers. Ensure one of them is set on all web pages returned by your site/app.

If you expect the page to be framed only by pages on your server (e.g. it's part of a FRAMESET) then you'll want to use SAMEORIGIN, otherwise if you never expect the page to be framed, you should use DENY. Alternatively consider implementing Content Security Policy's "frame-ancestors" directive.

Instances (1 of 5)

uri: https://u77w41.github.io/anurup/
method: GET
param: x-frame-options

References

https://developer.mozilla.org/en-US/docs/Web/HTTP/Reference/Headers/X-Frame-Options

Vulnerable Target	First Detected	Last Detected
https://u77w41.github.io/anurup/	10/27/2026	10/27/2026

X-Content-Type-Options Header Missing

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Low	1 target	2 hours ago

Description

The Anti-MIME-Sniffing header X-Content-Type-Options was not set to 'nosniff'. This allows older versions of Internet Explorer and Chrome to perform MIME-sniffing on the response body, potentially causing the response body to be interpreted and displayed as a content type other than the declared content type. Current (early 2014) and legacy versions of Firefox will use the declared content type (if one is set), rather than performing MIME-sniffing.

Solution

Ensure that the application/web server sets the Content-Type header appropriately, and that it sets the X-Content-Type-Options header to 'nosniff' for all web pages.

If possible, ensure that the end user uses a standards-compliant and modern web browser that does not perform MIME-sniffing at all, or that can be directed by the web application/web server to not perform MIME-sniffing.

Instances (1 of 5)

uri: https://u77w41.github.io/anurup/
method: GET
param: x-content-type-options
otherinfo: This issue still applies to error type pages (401, 403, 500, etc.) as those pages are often still affected by injection issues, in which case there is still concern for browsers sniffing pages away from their actual content type. At "High" threshold this scan rule will not alert on client or server error responses.

References

https://learn.microsoft.com/en-us/previous-versions/windows/internet-explorer/ie-developer/compatibility/gg622941(v=vs.85)
https://owasp.org/www-community/Security_Headers

Vulnerable Target	First Detected	Last Detected
https://u77w41.github.io/anurup/	10/27/2026	10/27/2026

Strict-Transport-Security Header Not Set

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Low	1 target	2 hours ago

Description

HTTP Strict Transport Security (HSTS) is a web security policy mechanism whereby a web server declares that complying user agents (such as a web browser) are to interact with it using only secure HTTPS connections (i.e. HTTP layered over TLS/SSL). HSTS is an IETF standards track protocol and is specified in RFC 6797.

Solution

Ensure that your web server, application server, load balancer, etc. is configured to enforce Strict-Transport-Security.

Instances (1 of 1)

uri: https://u77w41.github.io/anurup/sw.js
method: GET

References

https://cheatsheetseries.owasp.org/cheatsheets/HTTP_Strict_Transport_Security_Cheat_Sheet.html
https://owasp.org/www-community/Security_Headers
https://en.wikipedia.org/wiki/HTTP_Strict_Transport_Security
https://caniuse.com/stricttransportsecurity
https://datatracker.ietf.org/doc/html/rfc6797

Vulnerable Target	First Detected	Last Detected
https://u77w41.github.io/anurup/	10/27/2026	10/27/2026

5.0 Network Vulnerabilities

The OpenVAS network vulnerability scan tests servers and internet connected devices for over 150,000 vulnerabilities. OpenVAS uses the Common Vulnerability Scoring System (CVSS) to quantify the severity of findings. 0.0 is the lowest severity and 10.0 is the highest.

5.1 Scan Coverage

Shows how recently the included targets were last scanned.

Never scanned	More than 90 days ago	Last 90 days	Last 30 days
0	0	0	1

5.2 Total Vulnerabilities

Total number of vulnerabilities found by severity.

Critical	High	Medium	Low	Accepted
0	0	0	2	0

100%

5.3 Vulnerabilities Breakdown

Summary list of all detected vulnerabilities.

Title	Severity	CVSS Score	EPSS Score	Open	Accepted
ICMP Timestamp Reply Information Disclosure	Low	2.1	32%	1	0
TCP Timestamps Information Disclosure	Low	2.6		1	0

HostedScan Free Trial Report

5.4 Vulnerability Details

Detailed information about each potential vulnerability found by the scan.

ICMP Timestamp Reply Information Disclosure

SEVERITY	AFFECTED TARGETS	LAST DETECTED	CVSS SCORE	EPSS SCORE
Low	1 target	48 minutes ago	2.1	32%

Description

The remote host responded to an ICMP timestamp request.

The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

This information could theoretically be used to exploit weak time-based random number generators in other services.

The following response / ICMP packet has been received:
- ICMP Type: 14
- ICMP Code: 0

Solution

Various mitigations are possible:

- Disable the support for ICMP timestamp on the remote host completely

- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

References

CVE-1999-0524
https://datatracker.ietf.org/doc/html/rfc792
https://datatracker.ietf.org/doc/html/rfc2780

Vulnerable Target	First Detected	Last Detected
https://u77w41.github.io/anurup/	10/27/2026	10/27/2026

TCP Timestamps Information Disclosure

SEVERITY	AFFECTED TARGETS	LAST DETECTED	CVSS SCORE
Low	1 target	48 minutes ago	2.6

Description

The remote host implements TCP timestamps and therefore allows to compute the uptime.

The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.

A side effect of this feature is that the uptime of the remote host can sometimes be computed.

It was detected that the host implements RFC1323/RFC7323.

The following timestamps were retrieved with a delay of 1 seconds in-between:
Packet 1: 2218331830
Packet 2: 1052559042

Solution

To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.

To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled'

Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.

The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.

See the references for more information.

References

https://datatracker.ietf.org/doc/html/rfc1323
https://datatracker.ietf.org/doc/html/rfc7323
https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152
https://www.fortiguard.com/psirt/FG-IR-16-090

Vulnerable Target	First Detected	Last Detected
https://u77w41.github.io/anurup/	10/27/2026	10/27/2026

6.0 Open TCP Ports

The NMAP TCP port scan discovers open TCP ports with a complete scan of ports 0 to 65535.

6.1 Scan Coverage

Shows how recently the included targets were last scanned.

0	0	0	1
Never scanned	More than 90 days ago	Last 90 days	Last 30 days

6.2 Total Vulnerabilities

Total number of vulnerabilities found by severity.

Critical	High	Medium	Low	Accepted
0	0	0	2	0

100%

6.3 Vulnerabilities Breakdown

Summary list of all detected vulnerabilities.

Title	Severity	Open	Accepted
Open TCP Port: 80	Low	1	0
Open TCP Port: 443	Low	1	0

6.4 Vulnerability Details

Detailed information about each potential vulnerability found by the scan.

Open TCP Port: 80

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Low	1 target	2 hours ago

Description

An open port may be an expected configuration. For example, web servers use port 80 to serve websites over http and port 443 to serve websites over https. For a list of commonly used ports see https://en.wikipedia.org/wiki/List_of_TCP_and_UDP_port_numbers.

An unexpected open port could give unintended access to applications, data, and private networks. Open ports can also be dangerous when expected services are out of date and exploited through security vulnerabilities.

Vulnerable Target	First Detected	Last Detected
https://u77w41.github.io/anurup/	10/27/2026	10/27/2026

Open TCP Port: 443

SEVERITY	AFFECTED TARGETS	LAST DETECTED
Low	1 target	2 hours ago

Description

An open port may be an expected configuration. For example, web servers use port 80 to serve websites over http and port 443 to serve websites over https. For a list of commonly used ports see https://en.wikipedia.org/wiki/List_of_TCP_and_UDP_port_numbers.

An unexpected open port could give unintended access to applications, data, and private networks. Open ports can also be dangerous when expected services are out of date and exploited through security vulnerabilities.

Vulnerable Target	First Detected	Last Detected
https://u77w41.github.io/anurup/	10/27/2026	10/27/2026

HostedScan Free Trial Report

7.0 Glossary

Accepted Vulnerability

An accepted vulnerability is one which has been manually reviewed and classified as acceptable to not fix at this time, such as a false positive scan result or an intentional part of the system's architecture.

Active Web Application Vulnerabilities

The OWASP ZAP Active Web Application scan crawls the pages of a website or web application testing for vulnerabilities and configuration weaknesses. The active scan includes all of the passive scan tests and additionally makes requests and submits forms to actively test an application for more vulnerabilities. The active scan tests for vulnerabilities such as SQL injection, remote command execution, XSS, and more.

Fully Qualified Domain Name (FQDN)

A fully qualified domain name is a complete domain name for a specific website or service on the internet. This includes not only the website or service name, but also the top-level domain name, such as .com, .org, .net, etc. For example, 'www.example.com' is an FQDN.

Passive Web Application Vulnerabilities

The OWASP ZAP Passive Web Application scan crawls the pages of a website or web application. The passive scan inspects each page as well as the requests and responses sent between the server. The passive scan checks for vulnerabilities such as cross-domain misconfigurations, insecure cookies, vulnerable Javascript dependencies, and more.

Network Vulnerabilities

The OpenVAS network vulnerability scan tests servers and internet connected devices for over 150,000 vulnerabilities. OpenVAS uses the Common Vulnerability Scoring System (CVSS) to quantify the severity of findings. 0.0 is the lowest severity and 10.0 is the highest.

Open TCP Ports

The NMAP TCP port scan discovers open TCP ports with a complete scan of ports 0 to 65535.

Open UDP Ports

The NMAP UDP port scan discovers open ports of common UDP services

Vulnerability

A weakness in the computational logic (e.g., code) found in software and hardware components that, when exploited, results in a negative impact to confidentiality, integrity, or availability. Mitigation of the vulnerabilities in this context typically involves coding changes, but could also include specification changes or even specification deprecations (e.g., removal of affected protocols or functionality in their entirety).

SSL/TLS Security

The SSLyze security scan tests for misconfigured SSL/TLS certificates, expired certificates, weak ciphers, and SSL/TLS vulnerabilities such as Heartbleed.

Target

A target represents target is a single URL, IP address, or fully qualified domain name (FQDN) that was scanned.

Severity

Severity represents the estimated impact potential of a particular vulnerability. Severity is divided into 5 categories: Critical, High, Medium, Low and Accepted.

CVSS Score

The CVSS 3.0 score is a global standard for evaluating vulnerabilities with a 0 to 10 scale. CVSS maps to threat levels:
0.1 - 3.9 = Low
4.0 - 6.9 = Medium
7.0 - 8.9 = High
9.0 - 10.0 = Critical

EPSS Score

The EPSS score is the estimated probability that a given vulnerability will be exploited in the wild within the next 30 days, on a 0% to 100% scale.



This report was prepared using

HostedScan Security®

For more information, visit hostedscan.com

Founded in Seattle, Washington in 2019, HostedScan, LLC. is dedicated to making continuous vulnerability scanning and risk management much more easily accessible to more businesses.

HostedScan, LLC.

2212 Queen Anne Ave N
Suite #521
Seattle, WA 98109

Terms & Policies
hello@hostedscan.com