IBM Z DATATHON 2026 · THEME 2: AI SECURED

Los Antimarrulla

Privacy-preserving screening

AI estimates diabetes risk from encrypted inputs. Designed for IBM LinuxONE; local results available today.

Javier Augusto Rebull Saucedo · Álvaro Hernández Jarquín
Carlos Enrique Gonzalez Moran · Yazmin Ivonne Flores Martinez
UACJ · Master’s in AI and Data Analytics (MIAAD)


01 · THE PROBLEM

Diabetes is widespread; health records are sensitive

18.3% of adults in Mexico live with diabetes

1 in 3 people with diabetes are unaware of it

112,577 deaths in 2024: Mexico's second leading cause of death



Can AI calculate risk without reading the patient's inputs?

Sources: ENSANUT 2022 (Basto-Abreu et al., Salud Pública de México, 2023); 2024 registered deaths and SSA hospital discharge microdata, DGIS/INEGI.

02 · THE SOLUTION

Calculate risk from encrypted inputs

1 · Hospital encrypts

Encrypt all 19 indicators; retain the private key at the hospital

2 · Service evaluates

The model operates on ciphertexts without the private key

3 · Return ciphertext

Only the hospital can decrypt the returned score

4 · Decrypt and explain

The hospital displays risk and the largest model contributions

Ciphertexts only

The risk service receives no readable age, BMI, blood pressure or other feature

Same ranking

Local sample: encrypted AUC equals plaintext AUC

Screening support

Prioritize confirmatory glucose testing; this is not a diagnosis

AI sees the risk. Nobody sees the patient.

Scope: the risk service receives ciphertexts only. The planned LinuxONE demo uses two containers on one VM with a trusted administrator and synthetic patients. VM execution is still pending.

03 · HOMOMORPHIC ENCRYPTION

Calculate a score without decrypting inputs

THE PAILLIER PROPERTY

$$\mathrm{Enc}(a) \cdot \mathrm{Enc}(b) = \mathrm{Enc}(a + b)$$

$$\mathrm{Enc}(a)^{k} = \mathrm{Enc}(k \cdot a)$$

$$\prod \mathrm{Enc}(x_i)^{w_i} = \mathrm{Enc}(w \cdot x)$$

The service combines ciphertexts with model weights to obtain an encrypted score. The hospital decrypts and applies the sigmoid.

In transit — Mutual TLS 1.3 between hospital and service


At rest — AES-256-GCM in the hospital vault

During use — 2048-bit Paillier: calculation without decryption

Who can see what?

Component	Patient inputs	Risk result
Hospital (private-key holder)	Plaintext: its own patients	Plaintext
Risk service (no private key)	**Ciphertexts only**	**Ciphertext only**
Hospital vault records	**AES-256-GCM ciphertext**	**AES-256-GCM ciphertext**
Service logs	**No: IDs, ms and byte counts only**	**No**

Two containers; the private key stays at the hospital



Planned demo
Both containers share one VM with a trusted administrator. A production hospital would run its container on its own infrastructure.

Large-integer workload

Modular exponentiation over integers thousands of bits long for every patient

Isolation and encryption


Separate containers and mutual TLS; effective CPACF use has not been measured

Measure the actual platform

Local results available; repeat the same benchmark on LinuxONE

Stack: Python · scikit-learn · python-paillier + gmpy2 · cryptography (TLS 1.3, AES-256-GCM) · Docker (Ubuntu 24.04, s390x)

The service sees ciphertexts; the hospital sees risk



Actual English UI with a synthetic patient · local containers · LinuxONE run pending

2,000 of 2,000
decrypted integers exactly match the fixed-point reference

ROC-AUC 0.807
equal across float, fixed point and encryption on the same 2,000 records

115 ms (p50)
Hospital API: encrypt, mTLS, evaluate, decrypt and vault write (200 synthetic requests)

24.3 KB → 1.4 KB
19 input ciphertexts → one encrypted score

LOCAL benchmark · model logistic-cdc19-v1 · commit be9b27e · macOS arm64 / Docker · 2048-bit key. API p95: 118 ms. LinuxONE run pending; repeat with make measure-api-docker.

Train on public data; evaluate encrypted patient inputs

253,680 public CDC BRFSS 2015 health survey records (UCI ID 891)

19 indicators: BMI, blood pressure, cholesterol, activity, age… (Education and Income removed)

13.9% self-reported prediabetes or diabetes: account for class imbalance

1. **Train on public records**
   Logistic regression; standardization folded into model weights
2. **Quantize the weights**
   Round weights × 10^9; all 19 inputs are already integers
3. **Encrypt patient inputs**
   Encrypt 19 indicators using the hospital's key
4. **Encrypted score → risk**
   The service evaluates w · x on ciphertexts; the hospital decrypts and applies sigmoid

TEST RESULTS (38,052 RECORDS)

Metrics

ROC-AUC 0.825 · AP 0.414 · sensitivity 0.807 · specificity 0.689 · PPV 0.296 · Brier 0.098. Threshold selected on validation.

Limitations

Label: self-reported U.S. diagnosis, not future diabetes. A separate reduced ten-feature ENSANUT model reaches AUC ≈0.77 and underestimates risk.

Source: UCI Machine Learning Repository, CDC Diabetes Health Indicators (ID 891).

Screening support without sharing readable records

Earlier screening

Support earlier confirmatory testing for people who may be unaware of diabetes

Patient trust

The external risk service receives encrypted inputs

Privacy safeguards

A privacy-preserving design; clinical and legal review remain necessary

Further applications

Explore other linear screening models after separate validation

AI sees the risk. Nobody sees the patient.



Los Antimarrulla · UACJ · MIAAD
We challenge idleness and procrastination
github.com/UACJ-MIAAD/antimarrulla-ibmz-datathon-2026

Thank you

Screening support does not replace medical diagnosis.