

Principles of Programming Languages Compilation

Andrei Arusoaie¹

¹Department of Computer Science

December 14, 2020

Outline

Motivation

Outline

Motivation

Demo(s)

Expressions

Defining a stack machine

Compilation & Soundness

Motivation

- ▶ Interactive theorem provers: Coq, Isabelle

Motivation

- ▶ Interactive theorem provers: Coq, Isabelle
- ▶ Why?

Motivation

- ▶ Interactive theorem provers: Coq, Isabelle
- ▶ Why?
 - ▶ Mathematical proofs are often big and lacking details

Motivation

- ▶ Interactive theorem provers: Coq, Isabelle
- ▶ Why?
 - ▶ Mathematical proofs are often big and lacking details
 - ▶ Proofs can be developed using computers

Motivation

- ▶ Interactive theorem provers: Coq, Isabelle
- ▶ Why?
 - ▶ Mathematical proofs are often big and lacking details
 - ▶ Proofs can be developed using computers
 - ▶ Use a tool for handling all proof details

Motivation

- ▶ Interactive theorem provers: Coq, Isabelle
- ▶ Why?
 - ▶ Mathematical proofs are often big and lacking details
 - ▶ Proofs can be developed using computers
 - ▶ Use a tool for handling all proof details
 - ▶ Make sure proofs are **exact** - computer checked

Motivation

- ▶ Interactive theorem provers: Coq, Isabelle
- ▶ Why?
 - ▶ Mathematical proofs are often big and lacking details
 - ▶ Proofs can be developed using computers
 - ▶ Use a tool for handling all proof details
 - ▶ Make sure proofs are **exact** - computer checked
- ▶ These can be used to define PLs and to prove properties about them

Outline

Motivation

Demo(s)

Expressions

Defining a stack machine

Compilation & Soundness

Simple expressions in Coq

- ▶ Simple language of expressions - BNF:

$$\text{Exp} ::= \text{Nat} \mid \text{Id} \mid \text{Exp} \text{ "+" } \text{Exp} \mid \text{Exp} \text{ "*" } \text{Exp}$$

Simple expressions in Coq

- ▶ Simple language of expressions - BNF:

$\text{Exp} ::= \text{Nat} \mid \text{Id} \mid \text{Exp} \text{ "+" } \text{Exp} \mid \text{Exp} \text{ "*" } \text{Exp}$

- ▶ (Abstract) syntax can be defined using `Inductive`:

```
Inductive Exp :=  
  | const : nat -> Exp  
  | id : string -> Exp  
  | plus : Exp -> Exp -> Exp  
  | times : Exp -> Exp -> Exp.
```

Interpreter

- ▶ Expressions are interpreted in an environment, their interpretation being a value

Interpreter

- ▶ Expressions are interpreted in an environment, their interpretation being a value
- ▶ The interpretation function:

```
Fixpoint interpret (e : Exp)
    (sigma : Var -> nat) : nat :=
match e with
| const x => x
| id s => sigma s
| plus e1 e2=>(interpret e1 sigma)+(interpret e2 sigma)
| times e1 e2=>(interpret e1 sigma)*(interpret e2 sigma)
end.
```

Outline

Motivation

Demo(s)

Expressions

Defining a stack machine

Compilation & Soundness

Exercise: a stack machine

► Syntax:

```
Inductive Instruction :=  
| push_const : nat -> Instruction  
| push_var   : Var -> Instruction  
| add        : Instruction  
| mul        : Instruction.
```

Exercise: a stack machine

► Semantics:

```
Fixpoint run_instruction (i : Instruction)
  (env : Var -> nat) (stack : list nat) :=
match i with
| push_const n => n :: stack
| push_var v  => (env v) :: stack
| add         => match stack with
  | n1 :: n2 :: s' => (n1 + n2) :: s'
  | _              => stack
  end
| mul         => match stack with
  | n1 :: n2 :: s' => (n1 * n2) :: s'
  | _              => stack
  end
end.
```

Exercise: a stack machine

► Run instructions:

```
Fixpoint run (instr : list Instruction)
  (env : Var -> nat)
  (stack : list nat) : list nat :=
match instr with
| nil => stack
| i :: is' => run is' env
               (run_instruction i env stack)
end.
```

Outline

Motivation

Demo(s)

Expressions

Defining a stack machine

Compilation & Soundness

Compile

► Compilation of `Exp` to the stack machine:

```
Fixpoint compile (e:Exp) : list Instruction :=  
  match e with  
  | const n => push_const n :: nil  
  | id v => push_var v :: nil  
  | plus e1 e2 => (compile e1) ++ (compile e2)  
                  ++ (add :: nil)  
  | times e1 e2 => (compile e1) ++ (compile e2)  
                  ++ (mul :: nil)  
end.
```

Compilation results

► Compilation correct:

Theorem `compilation_correct`:
 forall e env,
 run (compile e) env nil =
 (interpret e env) :: nil.

Compilation results

► Compilation correct:

Theorem `compilation_correct`:

```
forall e env,  
  run (compile e) env nil =  
    (interpret e env) :: nil.
```

► Invariant:

Lemma `compilation_correct'`:

```
forall e env is' stack,  
  run (compile e ++ is') env stack =  
    run is' env (interpret e env :: stack).
```

Bottom line

- ▶ We have defined two languages in Coq: a language of expressions Exp and a stack machine
- ▶ We show how Exp can be compiled to the stack machine
- ▶ We **prove** compilation correct!

CompCert - I

- ▶ X. Leroy, S. Blazy, Z. Dargaye, J.B. Tristan; et al.
- ▶ Link: <http://compcert.inria.fr/>
- ▶ Project: develop and prove a realistic compiler, usable for critical embedded software
- ▶ Source language: a very large subset of C
- ▶ Target language: PowerPC/ARM/x86 assembly
- ▶ Generates compact and fast code; careful code generation + some optimizations
- ▶ Compiler written from scratch + proof

CompCert - II

- ▶ 50000 lines of Coq
- ▶ 4 person-years
- ▶ Trusted execution, certified compilation, static analysis (Verasco)
- ▶ Direct and indirect project partners: Airbus, AbsInt, etc.
- ▶ Airbus: flight control software of the A380
- ▶ MTU: critical control system in diesel engines that are deployed in nuclear power plants
- ▶ Institute of Flight System Dynamics at TUM: development of flight control and navigation algorithms

Resources

1. Chapter Small-Step Operational Semantics in **Software Foundations - Volume 2**, Benjamin C. Pierce, Arthur Azevedo de Amorim, Chris Casinghino, Marco Gaboardi, Michael Greenberg, Cătălin Hrițcu, Vilhelm Sjöberg, Andrew Tolmach, Brent Yorgey

Section “*A Small-Step Stack Machine*”:

[https://softwarefoundations.cis.upenn.edu/
plf-current/Smallstep.html#lab169](https://softwarefoundations.cis.upenn.edu/plf-current/Smallstep.html#lab169)