
# TMC4671 BOB Description

Document Revision V1.00 • 2018-May -16

# Module Top View



### Pin List

Left	Signal	Right	ht Signal	
1	+5V	17	VM (080V)	
2	VCCIO (3.3V)	18	GND	
3	GND	19	PWM_Y2_L	
4	STP	20	PWM_Y2_H	
5	DIR	21	PWM_WY1_L	
6	CSN	22	PWM_WY1_H	
7	SCK	23	PWM_VX2_L	
8	MOSI	24	PWM_VX2_H	
9	MISO	25	PWM_UX1_L	
10	RXD	26	PWM_UX1_H	
11	TXD	27	HALL_UX	
12	GND	28	HALL_V	
13	ADC_I0	29	HALL_WY	
14	ADC_I1	30	ENC1_A	
15	GND	31	ENC1_B	
16	GND	32	ENC1_N	

### Features and additional Resources

- TMC4671-LA Hardware Servo Controller
- Supply and I/O voltage 3.3V and 5V (with blue LED indicator)
- Motor supply voltage input to measure motor supply (0...80V)
- Communication and configuration via SPI and UART interface
- Real-time Monitoring Interface for live debugging and tuning using Trinamic's RTMI adapter
- Additional Step/Direction Interface from a motion controller
- · Encoder- and Hall-Feedback
- Supply and status indicator LEDs
- Board width 1.5", board height 1.6"
- 2x16 pin 0.1" header rows for pins/connectors, distance of rows 1.4"
- Link to additional information and IC data sheet
- · Link to evaluation kit

## **RTMI Connector**

The real-time monitoring interface connector is used to connect to Trinamic's RTMI adapter for live monitoring and tuning of the TMC4671 control loops at control loop sampling frequency. The onboard connector itself is of type Hirose DF20F-10DP-1V(56).

The mating female counter part is of type Hirose DF20A-10DS-1C. A connecting cable comes with the USB-2-RTMI adapter.

Left	Signal	Right	Signal	
1	+3.3V	2	n.c.	
3	DBG_SPI_nSCS	4	DBG_SPI_TRG	
5	DBG_SPI_SCK	6	GND	
7	DBG_SPI_MOSI	8	GND	
9	DBG_SPI_MISO	10	GND	










## Bill of Materials

Pcs.	MPN	Value	Footprint	Description
13	MC0603B104K100CT	100nF, 10V	0603	Cap, Multicomp
8	MC0603N101J500CT	100pF, 50V, 5%	0603	Cap, Multicomp
1	MCSH18B103K100CT	10nF, 10V	0603	Cap, Multicomp
1	GRM31CR61A476ME15L	47uF, 10V	1206	Cap, Murata
1	MC0603B104K100CT	100nF, 10V	0603	Cap, Multicomp
1	MC0603X474K160CT	470nF, 16V	0603	Cap, Multicomp
1	MC0603X475K100CT	4.7uF, 10V	0603	Cap, Multicomp
1	LTST-C191KRKT	$V_f = 2V @ I_f = 20mA$	0603	LED, Lite-On
3	BAT54S	30V, 200mA	SOT95P237X130-3N	SS Schottky, Taiwan Semiconductor
2	LTST-C191TBKT	$V_f = 2.8 \text{V } @I_f = 20 \text{mA}$	0603	LED, Lite-On
1	TMC4671-LA	Integrated Servo Controller IC	QFN40P1050X650X90_HS-77N	TRINAMIC Motion Control
2	SN74LVC3G17DCUR	triple schmitt trigger, 1.65V-5.5V	TSSOP50P310X90-8L	Texas Instruments
1	MFB-160808-0030PQ	30R	0603	MECMARCOM
1	DF20F-10DP-1V(56)	Wire-2-board header, 1mm pitch, 10pins,	DF20 series, SMD	Hirose Electric Co Ltd
6	MC0063W0603110K	10k	0603	Res, Multicomp
1	MCWR06X1201FTL	1k2	0603	Res, Multicomp
6	MCWR06X22R0FTL	22R, 1/10W, 1%	0603	Res, Multicomp
6	WR06X4701FTL	4k7, 1/10W, 1%	0603	Res, Walsin
2	MCWR06X1000FTL	100R	0603	Res, Multicomp
1	MCWR06X1501FTL	1k5	0603	Res, Multicomp
1	MCWR06X1003FTL	100k	0603	Res, Multicomp
2	MC0063W060311K	1k, 1/10W, 1%	0603	Res, Multicomp
2	SRV05-4.TCT	TVS, 17.5V	SOT95P280X145-6N	ESD Prot. diode, SEMTECH
1	FOX924B-25.000	25MHz, 2.5ppm, 3.3V	4-SMD, no lead	Oscillator, FOX Electronics












TMC4671 Sensing & Output













# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Trinamic:
TMC4671-BOB