Movie Events Application Requirements

1. Overview

The application allows a single dummy authenticated test user to browse, search, sort, filter, view, join, create, update, and delete movie events. It also includes supporting features for favorites, favorite-event notifications, price watching, best seat guidance, referral codes, movie marathons, a movie slot machine, and a movie trivia wheel.

There are no login, registration, or profile screens/views. Authentication is represented by a dummy test user that already exists in the application context.

2. User and Actor Model

Actor	Description
Dummy Authenticated User	The application shall operate for a single authenticated dummy test user.

The application shall operate for a single authenticated dummy test user.

3. Architectural and Consistency Constraints

3.1. Separation of concerns

ID	Requirement
ARCH-1	Domain models shall define application data and relationships.
ARCH-2	Repositories shall handle data access and persistence operations.
ARCH-3	Services shall implement business rules and feature workflows.
ARCH-4	Views/ViewModels or equivalent presentation components shall handle UI behavior and user interaction.

3.2. Consistency

ID	Requirement
CONS-1	The same event data definitions shall be reused across browsing, details, management, favorites, marathons, and game features where applicable.
CONS-2	Search, sort, and filter behavior shall be consistent across all relevant event lists.

4. Domain and Data Requirements

The following domain entities are required to support the application.

4.1. User

ID	Requirement	Owner
DR-1-1	A dummy authenticated test user shall exist in persistent storage.	Rares
DR-1-2	The user shall be identifiable by a unique user identifier.	Rares
DR-1-3	The user shall own personal data such as joined events, created events, favorites, notifications, rewards, referral code, spin state, and marathon progress.	Tudor

4.2. Event

ID	Requirement	Owner
DR-2-1	An Event entity shall exist for every movie event shown in the application.	Rares
DR-2-2	An event shall support at least title, description, poster, date/time, location reference, ticket price, historical event rating, event type, seat capacity information, and creator reference.	Rares
DR-2-3	An event shall support participation records for joined users.	Emanuel
DR-2-4	An event shall support one or more movie screenings.	Emanuel

4.3. Location

ID	Requirement	Owner
DR-3-1	A Location entity shall exist for venues where events are held.	Emanuel
DR-3-2	A location shall support enough information to identify and display the venue in event lists and event details.	Emanuel
DR-3-3	A location may have one or more hall layouts.	Emanuel

4.4. Hall Layout

ID	Requirement	Owner
DR-4-1	A HallLayout entity shall exist to support the Best Seat Map feature as a proper seat-based feature.	Emanuel
DR-4-2	A hall layout shall support rows, columns, seat identifiers, and seat availability state.	Emanuel
DR-4-3	A hall layout shall be associated with a location or specific hall within a location.	Emanuel

4.5. Participation

ID	Requirement	Owner
DR-5-1	A Participation entity or equivalent relation shall link a user to an event they joined or purchased.	Tudor
DR-5-2	Participation shall prevent the same user from joining the same event more than once.	Tudor

4.6. Favorite Event

ID	Requirement	Owner
DR-6-1	A FavoriteEvent entity or equivalent relation shall link a user to an event saved as favorite.	Filip
DR-6-2	Favorite events shall be stored independently for each user.	Filip

4.7. Notification

ID	Requirement	Owner
DR-7-1	A Notification entity shall support favorite-event notifications.	Filip
DR-7-2	A notification shall store at least user reference, event reference, notification type, short message, creation date, and read/view state if implemented.	Filip
DR-7-3	Notification data for favorites shall be persisted.	Filip

4.8. Price Watch Entry

ID	Requirement	Owner
DR-8-1	A PriceWatchEntry structure shall exist in local persistent client storage.	Emanuel
DR-8-2	A price watch entry shall store at least user context, event reference, target price, and current watch state.	Emanuel

4.9. Referral Code

ID	Requirement	Owner
DR-9-1	A ReferralCode entity or equivalent user-linked structure shall store a unique permanent code for each user.	Tudor
DR-9-2	The code shall support tracking of successful uses per event.	Tudor

4.10. Referral Interaction

ID	Requirement	Owner
DR-10-1	A ReferralInteraction entity shall log each successful referral code use.	Tudor
DR-10-2	It shall store at least ambassador user reference, referred user reference, event reference, and timestamp.	Tudor

4.11. Reward

ID	Requirement	Owner
DR-11-1	A Reward entity shall represent earned benefits such as free enrollment, free movie ticket, and slot-machine discount.	Tudor
DR-11-2	A reward shall store at least reward type, owner user reference, redemption status, applicability scope, and any relevant event or movie linkage.	Tudor
DR-11-3	Rewards may stack, but the final ticket price shall never become negative.	Tudor

4.12. Movie

ID	Requirement	Owner
DR-12-1	A Movie entity shall exist for movie-related features.	Andrei
DR-12-2	A movie shall support enough metadata to power event displays and movie-related features, including at least title, genre, actor relationships, director relationship, and movie rating where applicable.	Andrei

4.13. Genre

ID	Requirement	Owner
DR-13-1	A Genre entity shall exist for movie categorization and slot machine selection.	Andrei

4.14. Actor

ID	Requirement	Owner
DR-14-1	An Actor entity shall exist for slot machine selection.	Andrei

4.15. Director

ID	Requirement	Owner
DR-15-1	A Director entity shall exist for slot machine selection.	Andrei

4.16. Trivia Question

ID	Requirement	Owner
DR-16-1	A TriviaQuestion entity shall exist for trivia wheel and marathon verification.	Andreea
DR-16-2	A trivia question shall store question text, category, answer options, correct answer identifier, and movie linkage where required.	Andreea

4.17. Marathon

ID	Requirement	Owner
DR-17-1	A Marathon entity shall exist for the Movie Marathons feature area.	Maria
DR-17-2	A marathon shall support week scoping, theme, challenge tier, prerequisite relation if applicable, and leaderboard context.	Maria

4.18. Marathon Progress

ID	Requirement	Owner
DR-18-1	A MarathonProgress entity shall track a user's verified movie progress inside a marathon.	Maria
DR-18-2	It shall support completion count, trivia accuracy, and completion timestamping needed for ranking.	Maria

4.19. Spin Tracking

ID	Requirement	Owner
DR-19-1	A user-linked spin tracking structure shall exist for Movie Slot Machine and Movie Trivia Wheel.	Andreea
DR-19-2	It shall store remaining spins or last spin timestamps and any streak-related state required by each feature.	Andreea

5. Functional Requirements

5.1. Home list and sections

ID	Requirement	Owner
FR-EB-1	The system shall display a list of movie events when the user opens the home screen.	Filip
FR-EB-2	The system shall group events into sections displayed in horizontally scrollable rows.	Filip
FR-EB-3	The system shall allow the user to select a section by clicking its title.	Filip
FR-EB-4	When a section is selected, the system shall display all events belonging to that section.	Filip
FR-EB-5	The system shall display each event card with at least poster, date, location, and price.	Filip
FR-EB-6	The system shall allow the user to navigate to the My Events section.	Filip
FR-EB-7	The system shall allow the user to navigate to the Event Management table view.	Filip

5.2. Search

ID	Requirement	Owner
FR-SEARCH-1	The system shall allow the user to search for events by title.	Rares
FR-SEARCH-2	The system shall display events whose title or type matches the search query.	Rares
FR-SEARCH-3	The system shall combine the search query with the currently active sort and filters.	Rares
FR-SEARCH-4	The system shall provide search on every event list where it is relevant, including the home event list, section event list, My Events lists, My Favorites, and the Event Management table view.	Rares
FR-SEARCH-5	Search results shall update the currently displayed list without affecting unrelated event lists elsewhere in the application.	Rares

5.3. Sorting

ID	Requirement	Owner
FR-SORT-1	The system shall allow the user to sort events by price.	Rares
FR-SORT-2	The system shall allow the user to sort events by historical event rating.	Rares
FR-SORT-3	The system shall apply the selected sorting option to the currently displayed list.	Rares
FR-SORT-4	The system shall allow only one sorting option to be active at a time per displayed event list.	Rares
FR-SORT-5	The system shall provide sorting on every event list where it is relevant, including the home event list, section event list, My Events lists, My Favorites, and the Event Management table view.	Rares

5.4. Filtering

ID	Requirement	Owner
FR-FILTER-1	The system shall allow the user to filter events by price range.	Rares
FR-FILTER-2	The system shall allow the user to filter events by type.	Rares
FR-FILTER-3	The system shall allow the user to filter events by location.	Rares
FR-FILTER-4	The system shall allow the user to filter events by minimum historical event rating.	Rares
FR-FILTER-5	The system shall combine all active filters when displaying results.	Rares
FR-FILTER-6	The system shall allow the user to clear all active filters.	Rares
FR-FILTER-7	The system shall provide filtering on every event list where it is relevant, including the home event list, section event list, My Events lists, My Favorites, and the Event Management table view.	Rares

ID	Requirement	Owner
FR-DETAIL-1	The system shall allow the user to select an event from an event list by clicking its card.	Tudor
FR-DETAIL-2	When an event is selected, the system shall display the event details page.	Tudor
FR-DETAIL-3	The event details page shall display title, description, historical event rating, location, date, price, and poster.	Tudor
FR-DETAIL-4	The event details page shall display seat availability information if the event uses seat-based capacity tracking.	Emanuel
FR-DETAIL-5	The system shall allow the user to mark an event as “Will attend” if the event is free.	Tudor
FR-DETAIL-6	The system shall allow the user to purchase a ticket if the event is paid.	Tudor
FR-DETAIL-7	The purchasing action shall redirect the user to the Buy/Sell view.	Tudor
FR-DETAIL-8	The system shall record the user’s participation after a successful join or purchase.	Tudor
FR-DETAIL-9	The system shall prevent the same user from joining the same event more than once.	Tudor
FR-DETAIL-10	The system shall allow reward-based discounts and free enrollments to be applied during paid-event checkout where applicable.	Tudor
FR-DETAIL-11	When multiple rewards or discounts stack, the final calculated ticket price shall not be less than zero.	Tudor

ID	Requirement	Owner
FR-ME-1	The system shall display a list of events created by the authenticated user.	Filip
FR-ME-2	The system shall display a list of events joined by the authenticated user.	Filip
FR-ME-3	The system shall allow the user to create an event.	Maria
FR-ME-4	The system shall allow the creator of an event to edit that event.	Maria
FR-ME-5	The system shall allow the creator of an event to delete that event.	Maria
FR-ME-6	The system shall update the displayed lists after create, edit, delete, join, or cancel participation actions.	Filip
FR-ME-7	The system shall allow the user to cancel participation in an event they have joined.	Maria

ID	Requirement	Owner
FR-CRUD-1	The system shall provide a paginated table containing minimal information about events.	Maria
FR-CRUD-2	The system shall allow the user to select an event row from the table.	Maria
FR-CRUD-3	The system shall display detailed information for the selected event in a separate view or page.	Maria
FR-CRUD-4	The system shall support create, update, and delete operations for events from this management area.	Maria

ID	Requirement	Owner
FR-VP-1	The system shall validate required fields when creating or editing an event.	Maria
FR-VP-2	The system shall reject invalid event data such as empty title, empty location, invalid date, or negative price.	Maria
FR-VP-3	The system shall store users, events, and participation data in long-term storage.	Rares
FR-VP-4	The system shall load persisted data when the application starts.	Rares
FR-VP-5	The system shall persist favorites, favorite-event notifications, referral data, rewards, seat layouts, seat availability, movie data, trivia questions, marathon definitions, and marathon progress in long-term storage.	Emanuel
FR-VP-6	The system shall use local persistent client storage for price watcher data.	Emanuel

5.5. Favorite navigation and interface

ID	Requirement	Owner
FR-FAV-1	The system shall provide a Favorite button on the page of every event.	Filip
FR-FAV-2	When the user selects the Favorite button, the system shall store the selected event in the user’s favorites list in persistent storage.	Filip
FR-FAV-3	The system shall provide a dedicated My Favorites page where the user can view all events they have marked as favorites.	Filip
FR-FAV-4	The My Favorites page shall display at least the event title, date, location, and current price for each saved event.	Filip
FR-FAV-5	The system shall allow the user to remove an event from the favorites list.	Filip

5.6. Favorite management logic

ID	Requirement	Owner
FR-FAV-6	The system shall ensure that the same event cannot be added twice to the favorites list for the same user.	Filip
FR-FAV-7	The system shall store favorite events separately for each user.	Filip
FR-FAV-8	The system shall only allow events that already exist in persistent storage to be added to the favorites list.	Filip
FR-FAV-9	The system shall allow the user to view all favorite events at any time through the My Favorites page.	Filip

5.7. Favorite notification logic

ID	Requirement	Owner
FR-FAV-10	The system shall monitor changes related to the events saved in the user's favorites list.	Filip
FR-FAV-11	The system shall notify the user when the price of a favorite event decreases.	Filip
FR-FAV-12	The system shall notify the user when new seats become available for a favorite event that was previously full.	Filip
FR-FAV-13	A relevant seat-availability change shall be defined as available seats changing from 0 to a value greater than 0.	Filip
FR-FAV-14	The system shall create at most one notification for each relevant change, per user and per event state.	Filip
FR-FAV-15	Each favorite-event notification shall include at least the event title, change type, a short message, and creation date.	Filip
FR-FAV-16	Favorite-event notifications shall be displayed inside the application interface and shall be stored in persistent storage for later viewing.	Filip
FR-FAV-17	Favorite-event notifications shall remain separate from Price Watcher alerts.	Filip

5.8. Navigation and interface

ID	Requirement	Owner
FR-PW-1	Each event card displayed in the main list shall include a bell icon to allow users to toggle price monitoring.	Emanuel
FR-PW-2	The My Events section shall include a Price Watchlist tab or category.	Emanuel
FR-PW-3	Upon activating the watcher, the system shall prompt the user to define a target price.	Emanuel

5.9. Price comparison logic

ID	Requirement	Owner
FR-PW-4	The system shall compare the current event price with the user-defined target price.	Emanuel
FR-PW-5	A synchronization check shall occur automatically whenever the application initializes, performing a full refresh of the Price Watchlist by querying persisted event data.	Emanuel
FR-PW-6	If the current event price is less than or equal to the target price, the system shall apply a PRICE DROP DETECTED banner to the event card.	Emanuel
FR-PW-7	Price Watcher alerts shall refer only to price changes and shall not replace favorite-event notifications.	Emanuel

5.10. Constraints

ID	Requirement	Owner
FR-PW-8	The system shall store Price Watcher preferences in local persistent client storage.	Emanuel
FR-PW-9	The system shall limit the user to a maximum of 3 active price watchers at any given time.	Emanuel

5.11. Navigation and interface

ID	Requirement	Owner
FR-BS-1	The event detail page shall include a Visual Seat Guide button positioned near the event's location and price information.	Emanuel
FR-BS-2	Clicking the Visual Seat Guide button shall open a modal interface displaying an interactive seat map for the selected event location or hall.	Emanuel
FR-BS-3	The seat guide interface shall include a graphical representation of the screen at the top of the grid.	Emanuel
FR-BS-4	The seat guide interface shall include a seat grid color-coded by seat quality.	Emanuel
FR-BS-5	The seat guide interface shall include a distinct Sweet Spot marker highlighting the most recommended seats.	Emanuel

5.12. Seat and layout data

ID	Requirement	Owner
FR-BS-6	The system shall store hall layouts so the Best Seat Map operates as a proper seat-based feature rather than only a generic visualization.	Emanuel
FR-BS-7	Each hall layout shall define rows, columns, and uniquely identifiable seats.	Emanuel
FR-BS-8	The system shall associate seat availability with the corresponding event or event screening.	Emanuel

5.13. Recommendation logic

ID	Requirement	Owner
FR-BS-9	The system shall evaluate seat quality using hall geometry and screen-relative position.	Emanuel
FR-BS-10	The system shall identify a Sweet Spot region centered around the optimal viewing and audio area of the hall.	Emanuel
FR-BS-11	The system shall visually distinguish poor seats, standard seats, and optimal seats.	Emanuel
FR-BS-12	The system shall visually indicate unavailable seats separately from available seats.	Emanuel

5.14. General adaptation for this project

Because the application has no profile screen, referral-code information shall be exposed through a dedicated in-application area that is accessible to the dummy authenticated user.

5.15. Navigation and interface

ID	Requirement	Owner
FR-REF-1	The system shall display the user's unique Ambassador Code in a dedicated in-application referral area.	Tudor
FR-REF-2	The system shall provide a Referral History dashboard showing who used the code and for which events.	Tudor
FR-REF-3	The enrollment form shall include an optional text field for entering a Referral Code.	Tudor

5.16. Referral generation and validation

ID	Requirement	Owner
FR-REF-4	The system shall generate a unique permanent alphanumeric referral code for the user.	Tudor
FR-REF-5	When a Referral Code is entered during enrollment, the system shall validate that the code exists and belongs to a valid user.	Tudor
FR-REF-6	The system shall reject referral-code usage if the user entering the code is also the code owner.	Tudor

5.17. Referral logging and rewards

ID	Requirement	Owner
FR-REF-7	Each successful use of a referral code shall be logged as a ReferralInteraction linked to a specific EventID.	Tudor
FR-REF-8	Once the system detects 3 successful usages of a code for the same event, the ambassador shall be granted a free enrollment reward for that same event only.	Tudor
FR-REF-9	The referral reward shall be stored as a redeemable reward and shall be redeemable once.	Tudor

5.18. Navigation and interface

ID	Requirement	Owner
FR-SM-1	The system shall provide a Movie Slot Machine button on the home screen.	Andrei
FR-SM-2	When the user selects the Movie Slot Machine button, the system shall navigate the user to the Movie Slot Machine page.	Andrei
FR-SM-3	The Movie Slot Machine page shall contain a slot-machine style interface with three vertical reels.	Andrei
FR-SM-4	The reels shall represent the categories Genre, Actor, and Director.	Andrei
FR-SM-5	Each reel shall display one value at a time.	Andrei
FR-SM-6	Reel values shall be selected from the corresponding persisted movie-related data.	Andrei
FR-SM-7	The Movie Slot Machine page shall contain a Spin button.	Andrei
FR-SM-8	Pressing Spin shall initiate a slot-machine spin animation.	Andrei
FR-SM-9	During the spin animation, each reel shall display multiple values from its category sequentially.	Andrei
FR-SM-10	Each reel shall stop spinning independently.	Andrei
FR-SM-11	The reels shall stop in the order Genre, Actor, Director.	Andrei
FR-SM-12	The final reel values shall represent the generated roulette combination.	Andrei
FR-SM-13	The system shall allow users to trigger the spin using keyboard input.	Andrei

5.19. Event matching logic

ID	Requirement	Owner
FR-SM-14	The system shall select reel values using random selection from the corresponding categories.	Andrei
FR-SM-15	The system shall only select values that are associated with at least one currently available event screening.	Andrei
FR-SM-16	The system shall ensure that the generated combination produces at least one matching movie event.	Andrei
FR-SM-17	The system shall retrieve events containing screenings of matching movies.	Andrei
FR-SM-18	The system shall retrieve only future or active screenings.	Andrei
FR-SM-19	For each matching event, the system shall retrieve at least movie title, event name, event location, ticket price, and movie rating.	Andrei
FR-SM-20	After the reels stop, the system shall display a results section below the slot machine.	Andrei
FR-SM-21	The results section shall display all events that match the generated combination.	Andrei
FR-SM-22	Each result card shall contain a View Event button.	Andrei
FR-SM-23	When the user selects View Event, the system shall navigate to the event details page.	Andrei

5.20. Spin economy

ID	Requirement	Owner
FR-SM-24	The system shall provide each user with one free Movie Slot Machine spin per day.	Andrei
FR-SM-25	The system shall reset the user's daily free spin at 00:00 server time each day.	Andrei
FR-SM-26	The system shall prevent the user from initiating a spin when the user has zero available spins.	Andrei
FR-SM-27	The system shall display the number of available spins on the Movie Slot Machine page.	Andrei
FR-SM-28	The system shall grant the user one additional spin when the user joins an event.	Andrei
FR-SM-29	The system shall limit bonus spins earned from event participation to a maximum of two spins per user per day.	Andrei
FR-SM-30	The system shall immediately update the user's available spin count after a bonus spin is awarded.	Andrei
FR-SM-31	The system shall track the number of consecutive days the user opens the application.	Andrei
FR-SM-32	The system shall grant the user one additional spin when the user reaches a three-day consecutive login/open streak.	Andrei
FR-SM-33	After awarding the streak spin, the system shall reset the streak counter.	Andrei

5.21. Jackpot and reward logic

ID	Requirement	Owner
FR-SM-34	The system shall determine whether the generated Genre, Actor, and Director combination corresponds to an existing movie in persistent storage.	Andrei
FR-SM-35	If a movie exists that matches the generated combination, the system shall trigger a Movie Slot Machine Jackpot.	Andrei
FR-SM-36	When a jackpot occurs, the system shall grant the user a discount reward applicable to all events containing a screening of the matching movie.	Andrei
FR-SM-37	The chance of winning a jackpot shall be intentionally small because the jackpot reward is high-value.	Andrei
FR-SM-38	The jackpot discount percentage shall be configurable.	Andrei
FR-SM-39	The results section shall highlight events containing the matching movie when a jackpot occurs.	Andrei
FR-SM-40	Highlighted events shall visually indicate that a discount has been awarded.	Andrei
FR-SM-41	The discount shall be applied when the user joins or purchases a qualifying matching-movie event.	Andrei

5.22. Navigation and interface

ID	Requirement	Owner
FR-MW-1	The home page shall contain a Movie Trivia Wheel section with a short description and a Spin the Wheel button.	Andreea
FR-MW-2	Pressing the Spin button shall open the Trivia Wheel interface.	Andreea
FR-MW-3	The wheel shall contain at least the categories Actors, Directors, Movie Quotes, Oscars and Awards, and General Movie Trivia.	Andreea
FR-MW-4	The interface shall include the wheel visualization, a Spin button, the number of remaining spins available, and a short explanation of the reward rules.	Andreea
FR-MW-5	Pressing the Spin button shall trigger a wheel-spinning animation, after which one category shall be randomly selected and displayed.	Andreea
FR-MW-6	After a category is selected, the interface shall transition to the Trivia Question screen.	Andreea

5.23. Trivia flow

ID	Requirement	Owner
FR-MW-7	Each trivia session shall consist of 20 multiple-choice questions belonging to the selected category.	Andreea
FR-MW-8	Questions shall be displayed one at a time and shall include the question text, four possible answers, and exactly one correct answer.	Andreea
FR-MW-9	The user shall select one answer before moving to the next question.	Andreea
FR-MW-10	Immediately after answer submission, the system shall evaluate the answer and update the displayed score counter.	Andreea
FR-MW-11	Questions shall not be skippable and shall not be revisitable after submission.	Andreea
FR-MW-12	The trivia session shall end when all questions have been answered or when the user exits the session.	Andreea
FR-MW-13	At the end of the session, a results screen shall display the total number of correct answers and whether a reward was earned.	Andreea

5.24. Trivia selection logic

ID	Requirement	Owner
FR-MW-14	Trivia questions shall be stored in persistent storage together with question text, category, four answer options, and correct answer identifier.	Andreea
FR-MW-15	When a trivia session starts, the application shall randomly select 20 questions belonging to the chosen category.	Andreea
FR-MW-16	The same question shall not appear more than once within the same trivia session.	Andreea
FR-MW-17	The selected questions shall also be randomized in presentation order.	Andreea

5.25. Hint system

ID	Requirement	Owner
FR-MW-18	Each trivia session shall provide the user with one hint token.	Andreea
FR-MW-19	The hint shall be activatable during any question using a Hint button near the answer options.	Andreea
FR-MW-20	When the hint is activated, the application shall remove two incorrect answers from the available options.	Andreea
FR-MW-21	After the hint is used, the Hint button shall become disabled for the remainder of the session.	Andreea
FR-MW-22	The interface shall clearly indicate whether the hint has already been used.	Andreea

5.26. Reward logic

ID	Requirement	Owner
FR-MW-23	A user shall receive a free movie event ticket reward only if all 20 trivia questions are answered correctly.	Andreea
FR-MW-24	When a reward is generated, it shall be stored together with reward type and redemption status.	Andreea
FR-MW-25	The reward shall be applicable to any movie event.	Andreea
FR-MW-26	The reward shall never expire until redeemed.	Andreea
FR-MW-27	The reward shall be applicable during checkout when the user selects a movie event.	Andreea
FR-MW-28	After the reward is used, the system shall mark it as redeemed to prevent reuse.	Andreea
FR-MW-29	A trivia-wheel reward shall be redeemable once only.	Andreea

5.27. Spin limitations

ID	Requirement	Owner
FR-MW-30	Each user shall be allowed one trivia wheel spin per day.	Andreea
FR-MW-31	The application shall store the timestamp of the user's most recent trivia wheel spin.	Andreea
FR-MW-32	If the user attempts to spin the wheel again before the next daily reset, the spin action shall be blocked.	Andreea
FR-MW-33	In this case, the interface shall display a message informing the user when the next spin will become available.	Andreea
FR-MW-34	The daily spin counter shall reset automatically at 00:00 server time.	Andreea

5.28. Feature area

ID	Requirement	Owner
FR-MM-1	The system shall provide Movie Marathons as a separate feature area from normal event browsing.	Maria
FR-MM-2	The Movie Marathons feature area shall display the currently active weekly marathons.	Maria

5.29. Weekly sprint model

ID	Requirement	Owner
FR-MM-3	The feature shall use a weekly sprint model that resets completely every week.	Maria
FR-MM-4	Every Monday at 00:00, the previous week's marathons shall end and a new set of themed marathons shall be released.	Maria
FR-MM-5	Each week shall contain themed marathon definitions.	Maria
FR-MM-6	Users shall have until Sunday night to log progress and verify movie views for the active week.	Maria

5.30. Verification logic

ID	Requirement	Owner
FR-MM-7	Clicking Log for a movie shall trigger a Rapid-Fire Trivia Check.	Maria
FR-MM-8	The system shall pull three multiple-choice questions at random from a movie-specific trivia pool.	Maria
FR-MM-9	A user shall answer all 3 out of 3 questions correctly for that movie to count toward marathon progress.	Maria
FR-MM-10	The verification process shall prevent unverified progress from counting toward rankings.	Maria

5.31. Tiered progression

ID	Requirement	Owner
FR-MM-11	Some marathons shall be designated as Elite.	Maria
FR-MM-12	Elite marathons shall remain locked until the prerequisite Standard marathon is completed within the same week.	Maria
FR-MM-13	Prerequisite logic shall be configurable per marathon definition.	Maria

5.32. Marathon leaderboards

ID	Requirement	Owner
FR-MM-14	Every marathon shall have its own live leaderboard.	Maria
FR-MM-15	Rankings shall be isolated to the specific marathon and shall not carry over to other marathons or future weeks.	Maria
FR-MM-16	Participants shall be ranked first by total number of successfully verified movies within that marathon.	Maria
FR-MM-17	If completion counts are tied, rank shall be determined by trivia accuracy.	Maria
FR-MM-18	If completion and accuracy are tied, rank shall be determined by who finished the marathon fastest.	Maria

6. Business Rules

ID	Requirement	Owner
BR-1	The application shall operate with a dummy authenticated test user and no login/registration/profile screens.	Tudor
BR-2	All features shall be available to the same user role.	Tudor
BR-3	The same user shall not join the same event more than once.	Tudor
BR-4	Favorite events shall not contain duplicates for the same user.	Filip
BR-5	Favorite-event notifications shall be created only for relevant changes and not duplicated for the same user and event state.	Filip
BR-6	Price Watcher alerts shall track only price thresholds and shall remain separate from favorite-event notifications.	Emanuel
BR-7	Price Watcher entries shall be limited to 3 active watches at a time.	Emanuel
BR-8	Referral rewards shall be granted only after 3 successful code uses for the same event.	Tudor
BR-9	Referral rewards shall apply only to that same event.	Tudor
BR-10	Slot machine jackpot rewards shall apply to all events containing a screening of the matching movie.	Andrei
BR-11	Slot machine jackpot win probability shall remain small relative to the reward value.	Andrei
BR-12	Trivia wheel rewards shall apply to any movie event, never expire before use, and be redeemable only once.	Andreea
BR-13	Rewards may stack, including combinations that reduce an event price to zero.	Tudor
BR-14	Stacked rewards shall never reduce a ticket price below zero.	Tudor
BR-15	Marathon rankings shall reset with each weekly cycle.	Maria

7. Non-Functional Requirements

7.1. Persistence and startup

ID	Requirement	Owner
NFR-1	Persisted data shall be loaded at application startup before dependent features are used.	Andreea
NFR-2	Persistent data and local client data shall remain consistent enough that the user sees current event state after startup refresh.	Emanuel

7.2. Performance and responsiveness

ID	Requirement	Owner
NFR-3	Event search, sort, and filter operations shall respond fast enough to support normal interactive use on the supported application environment.	Filip
NFR-4	Application startup refresh shall update dependent features such as favorites and price watcher without causing duplicate state creation.	Emanuel
NFR-5	Modal and game interfaces shall remain responsive during animations and state updates.	Maria

7.3. Data integrity

ID	Requirement	Owner
NFR-6	The system shall preserve referential integrity between users, events, participations, favorites, notifications, rewards, and referrals.	Tudor
NFR-7	Reward redemption state shall be persisted correctly to prevent duplicate use.	Tudor
NFR-8	Event and seat availability changes shall not produce contradictory UI state across event details, favorites, and best seat map views.	Emanuel

7.4. Maintainability

ID	Requirement	Owner
NFR-9	Domain models, repositories, services, and UI logic shall be implemented with clear separation of concerns.	Rares
NFR-10	Feature-specific logic shall be encapsulated so new features can be added without tightly coupling unrelated modules.	Maria
NFR-11	Shared event-list behavior such as search, sort, and filter shall be reusable across relevant views.	Rares

8. Implementation Notes

ID	Constraint
NOTE-1	References in imported requirements to account creation or profile visibility are adapted to this project by exposing the same data through dedicated in-application areas for the dummy authenticated user.
NOTE-2	Best Seat Map shall be implemented as a proper hall-layout and seat-based feature, not only as a virtual approximation.
NOTE-3	Price Watcher shall use implementation-safe local persistent client storage rather than requiring database schema changes.
NOTE-4	Historical event rating is the normalized wording replacing prior “past rating” terminology.
NOTE-5	Search, sort, and filter requirements apply everywhere they are relevant, not only on the home list.
NOTE-6	Movie Marathons are a separate feature area and not just a property of normal events.
NOTE-7	Reward stacking is allowed, but negative final prices are forbidden.

9. Requirement Coverage Summary by Owner

Owner	Coverage
Rares	Project base setup and core architectural foundation Core user and event model foundation Search requirements Sorting requirements Filtering requirements Persistence startup foundation Shared event-list reuse requirement
Emanuel	Best Seat Map Price Watcher Location and hall-related event support Event persistence consistency related to venue/seat data
Filip	Favorite Events Favorite-event notifications Home browsing flow and event-list presentation My Events list presentation updates
Maria	Movie Marathons Event management table and CRUD area Validation flow for create/update operations
Andrei	Movie Slot Machine Movie domain model
Andreea	Movie Trivia Wheel Shared spin tracking structures Startup loading dependency for spin-based features
Tudor	Referral Code System Reward model and reward business rules Event details/join/purchase flow Participation domain and related integrity rules